```
1 //
2 // Shaun Chemplavil U08713628
3 // shaun.chemplavil@gmail.com
4 // C/C++ Programming III : Intermediate Programming with Objects
 5 // 151116 Raymond L. Mitchell III
 6 // StringUtility.h
 7 // Win10
8 // Visual C++ 19.0
9 //
10 // File contains the StringUtility class definition
11 //
12 #ifndef SHAUNCHEMPLAVIL_STRINGUTILITY_H
13 #define SHAUNCHEMPLAVIL_STRINGUTILITY_H
14
15 #include <string>
16 #include <vector>
17
18 using std::string;
19 using std::vector;
20
21 namespace ShaunChemplavil
22 {
23
      class StringUtility
24
      {
25
26
      public:
         string join(const vector<string> &strings, char delimiter);
27
28
         vector<string> reverse(const vector<string> &strings);
29
         vector<string> combine(const vector<string> &left, const vector<string>
          &right);
30
         vector<string> leftPad(const vector<string> &strings, char pad);
31
      };
32 }
33 #endif
```

```
1 //
 2 // Shaun Chemplavil U08713628
 3 // shaun.chemplavil@gmail.com
 4 // C/C++ Programming III : Intermediate Programming with Objects
 5 // 151116 Raymond L. Mitchell III
 6 // StringUtility.cpp
 7 // Win10
 8 // Visual C++ 19.0
10 // File contains the display member function for the StringUtility class
11 //
12
13 #include "StringUtility.h"
14
15 namespace ShaunChemplavil
16 {
17
       string StringUtility::join(const vector<string> &strings, char delimiter)
18
       {
19
          string out;
          for (size_t i = 0; i < strings.size(); i++)</pre>
20
21
22
             //append string to output string
23
             out += strings[i];
24
             // Do not add the delimiter after the last string!
25
             if (i < (strings.size() - 1))</pre>
26
                out += delimiter;
27
          }
28
          return out;
29
       }
30
       vector<string> StringUtility::reverse(const vector<string> &strings)
31
32
         vector<string> out;
33
          // Use an int to index each element of vector of strings
34
          // start with last element, and decrement until the index is
35
          // negative
36
          for (int i = (strings.size() - 1); i >= 0; i--)
37
38
             // declare temporary string to append elements of string
39
             // indexing logic is the same as for the vector of strings
             string temp;
             for (int j = (strings[i].size() - 1); j >= 0; j--)
41
42
                temp += strings[i].at(j);
43
44
             // Add the reversed string onto the output vector of strings
45
             out.push_back(temp);
46
          }
47
          return out;
48
49
       vector<string> StringUtility::combine(const vector<string> &left, const
        vector<string> &right)
50
       {
51
          vector<string> out;
```

```
...8\Cpp_Certification_Course\Exercise\CA3\StringUtility.cpp
```

```
2
```

```
52
53
          //Append every permutation of the left and right input vectors of string
54
          for (size_t i = 0; i < left.size(); i++)
             for (size_t j = 0; j < right.size(); j++)</pre>
55
56
                // append the elements of each vector of strings
57
                out.push_back(left[i] + right[j]);
58
59
          return out;
60
61
       vector<string> StringUtility::leftPad(const vector<string> &strings, char pad)
62
63
          vector<string> out;
64
          size_t max_size = 0;
65
          // Find the longest string in the vector
66
          for (size_t i = 0; i < strings.size(); i++)</pre>
             max_size = max_size > strings[i].size() ? max_size : strings[i].size();
67
68
69
          // Now do appropriate left padding
70
          for (size_t i = 0; i < strings.size(); i++)</pre>
71
          {
72
             string padStr;
73
74
             out.push_back(padStr.assign(max_size - strings[i].size(), pad).append
              (strings[i]));
75
          }
76
77
          return out;
78
       }
79 }
80
```

```
1 //
 2 // Shaun Chemplavil U08713628
 3 // shaun.chemplavil@gmail.com
 4 // C/C++ Programming III : Intermediate Programming with Objects
 5 // 151116 Raymond L. Mitchell III
 6 // hw7.cpp
 7 // Win10
 8 // Visual C++ 19.0
10 // Test Program for the StringUtility class
11 //
12
13 #include "StringUtility.h"
14 #include <iostream>
15
16 using std::cout;
17 using ShaunChemplavil::StringUtility;
18 using std::string;
19 using std::vector;
20
21 int main()
22 {
23
       vector<string> strings, right, left;
       strings = {"The", "quick", "brown", "fox", "jumps", "over", "the", "lazy",
24
        "dog"};
25
       left = {"Mr.", "Mrs."};
       right = {"Jones", "Smith", "Williams"};
27
28
       char delimiter = ',';
29
       StringUtility testUtility;
30
       string output;
31
32
       // Test join member function of StringUtility class
       cout << "6) Testing join member function \n";</pre>
33
34
       output = testUtility.join(strings, delimiter);
35
       cout << output << "\n";</pre>
36
37
       // Test reverse member function of StringUtility class
38
       vector<string> outVec;
39
       cout << "\n7) Testing reverse member function\n";</pre>
40
       outVec = testUtility.reverse(strings);
41
42
       for (size_t i = 0; i < outVec.size(); i++)</pre>
43
          cout << outVec[i] << "\n";</pre>
44
45
       // Test combine member function of StringUtility class
46
       cout << "\n8) Testing combine member function\n";</pre>
47
       outVec = testUtility.combine(left, right);
48
       for (size_t i = 0; i < outVec.size(); i++)</pre>
49
          cout << outVec[i] << "\n";</pre>
50
51
       // Test leftPad member function of StringUtility class
```

```
delimiter = '*';
cout << "\n9) Testing leftPad member function\n";
outVec = testUtility.leftPad(strings, delimiter);
for (size_t i = 0; i < outVec.size(); i++)
cout << outVec[i] << "\n";
}</pre>
```

