
P Channel Lateral MOSFET

- Designed specifically for linear audio amplifier applications
- High-speed for high bandwidth amplifiers
- High voltage rating - 200V
- TO-264 plastic package
- Enhanced oscillation suppression in multi-device applications
- Complementary N-channel available – ECW20N20



ABSOLUTE MAXIMUM RATINGS		(T_C = 25°C unless otherwise stated)
V_{DSS}	Drain – Source Voltage	-200V
V_{GSS}	Gate – Source Voltage	+/-14V
I_D	Continuous Drain Current	-16A
I_{DR}	Body Drain Diode Current	-16A
P_D	Allowable Power Dissipation* T_{case} = 25°C	250W
T_{ch}	Channel Temperature	150°C
T_{stg}	Storage Temperature Range	-55 to +150°C

**Thermal Resistance, Junction To Case* *0.5 deg/watt*

ELECTRICAL CHARACTERISTICS (TC = 25°C unless otherwise stated)

Symbols	Parameters	Test Conditions		Min.	Typ	Max.	Units
BV_{DSX}	Drain-Source Breakdown Voltage	V_{GS} = -10V	I_D = -10mA	-200			V
I_{GSS}	Gate-Source Leakage Current	V_{DS} = 0	V_{GS} = ±20V			100	µA
$V_{GS(off)}$	Gate-Source Cut-off Voltage	V_{DS} = -10V	I_D = -100mA	-0.1		-1.5	V
$V_{DS(sat)}$*	Drain-Source Saturation Voltage	V_{GD} = 0	I_D = -16A			-12	V
|yfs|*	Forward Transfer Admittance	V_{DS} = 10V	I_{DS} = -3A	1.4		4	S(℧)
I_{DSX}	Drain-Source Cut-Off Current	V_{GS} = -10V	V_{DS} = -200V			-10	mA


* Pulse Test: Pulse Width = 300µs, Duty Cycle ≤ 2%

DYNAMIC CHARACTERISTICS


Symbols	Parameters	Test Conditions	Min.	Typ	Max.	Units
C_{iss}	Input Capacitance	V_{GS} = 0 V_{DS} = -10V f = 1.0MHz		2060		pF
C_{oss}	Output Capacitance			860		pF
C_{rss}	Reverse Transfer Capacitance			55		pF
t_{on}	Turn-On Time	V_{DS} = -20V I_D = -14A		160		ns
t_{off}	Turn-Off Time			70		ns

GENERAL CHARACTERISTICS (T = 25°C unless otherwise stated)


Typical Output Characteristics




Typical Output Characteristics




Transfer Characteristics




Transfer Characteristic




Drain -Source Voltage
vs Gate-Source Voltage




Transconductance




Typical Capacitance
vs Gate -Source Voltage (V)



Forward Bias Safe Operating Area





MECHANICAL DATA dimensions in mm(inches)

Exicon products are available at www.profusion.uk