The Experimental Oberon System

Andreas Pirklbauer

11.11.2019

Experimental Oberon¹ is a revision of the FPGA Oberon² operating system and its compiler. It contains a number of enhancements, including the Revised Oberon-2 programming language implementing as a strict superset of Revised Oberon (Oberon-07), safe module unloading, system building and maintenance tools, smooth fractional line scrolling of displayed texts with variable line spaces, multiple logical displays and other improvements. Some of these enhancements are of a purely experimental nature, while others serve the explicit purpose of exploring potential future extensions.

1. Revised Oberon-2 programming language

Revised Oberon-2 is a revision of the programming language Oberon-2³. The main difference to the original is that it implements a strict superset of Revised Oberon (Oberon-07) as defined in 2007/2016⁴ rather than being based on the original language *Oberon* as defined in 1988/1990⁵.

Original Oberon (1988/1990) Original Oberon-2 (1991/1993)



Revised Oberon (2007/2016) **→** Revised Oberon-2 (2019/2020)

Its principal features include type-bound procedures, a dynamic heap allocation procedure for fixed-length and open arrays, a numeric case statement, exporting and importing of string constants, and no access to intermediate objects within nested scopes.

The Revised Oberon-2 language is described in more detail in a separate document⁶.

2. Safe module unloading

In the Oberon system, there exist several possible types of references to a loaded module M:

- 1. Client references exist when other loaded modules import module M. Client modules may refer by name to exported constants, types, variables or procedures declared in module M.
- 2. Type references exist when type tags (addresses of type descriptors) in dynamic objects reachable by other loaded modules refer to descriptors of types declared in module M.
- 3. Procedure variable references exist when procedure variables in static or dynamic objects reachable by other loaded modules refer to procedures declared in module M.

¹ http://www.github.com/andreaspirklbauer/Oberon-experimental

http://www.inf.ethz.ch/personal/wirth/ProjectOberon/index.html (FPGA Oberon, 2013 Edition); see also http://www.projectoberon.com Mössenböck H., Wirth N.: The Programming Language Oberon-2. Structured Programming, 12(4):179-195, 1991

wiosseribous in, wild in. The Frogramming Language Oberiol-2. Structured Frogram http://www.inf.ethz.ch/personal/wirth/Oberon/Oberon07.Report.pdf (Revision 3.5.2016) https://inf.ethz.ch/personal/wirth/Oberon/Oberon.Report.pdf (Revision 1.10.1990)

https://github.com/andreaspirklbauer/Oberon-experimental/blob/master/Documentation/The-Revised-Oberon2-Programming-Language.pdf

4. Pointer variable references to static module data exist when pointer variables in static or dynamic objects reachable by other loaded modules refer to static objects declared in module M. Such references can only be created by resorting to low-level facilities and should be avoided and, in fact, be disallowed (pointer variables should point exclusively to anonymous variables allocated in the heap when needed during program execution).

In most Oberon implementations, only *client* references are checked prior to module unloading. *Type*, *procedure* and *pointer variable* references to static module data are usually not checked, although various approaches are typically employed to address the case where such references do exist. As a result, module unloading has traditionally left an Oberon system in an *unsafe* state, which will become *unstable* the moment another module loaded later *overwrites* a previously released module block and other modules or data elements still contain "dangling" references to its (now overwritten) *type descriptors*, *procedures* or *static objects*. In addition, unloading of module *groups* with references only among themselves is usually not supported.

Experimental Oberon checks *all* possible types of references and fully implements *safe* module unloading for individual modules or module groups. The mechanism of safe module unloading is described in more detail in a separate document⁷.

3. System building and maintenance tools

A minimal version of the Oberon system *building tools*, as outlined in chapter 14 of the book *Project Oberon 2013 Edition*, has been added. They provide the necessary tools to establish the prerequisites for the *regular* Oberon startup process either on an existing *local* system or on a bare metal *target* system connected to a *host* via a data link (e.g., an RS-232 serial line).

The boot linker (procedure *ORL.Link*) links a set of object files together and generates a valid boot file from them. It can be used to either generate the *regular* boot file to be loaded onto the *boot area* of a disk or the *build-up* boot file sent over a data link to a target system. The name of the top module is supplied as a parameter. For the *regular* boot file, this is typically module *Modules*, the top module of the *inner core* of the Oberon system. For the *build-up* boot file, it is usually module *Oberon0*, a simple command interpreter mainly used for system building and maintenance purposes.

The command *ORL.Load* loads a valid *boot file*, as generated by the command *ORL.Link*, onto the boot area of the local disk, one of the two valid *boot sources* (the other being the data link). This command can be used if the user already has a running Oberon system. It is executed *on* the system to be modified and overwrites the boot area of the *running* system.

The tools to build an entirely new Oberon system on a bare metal *target* system connected to a *host* system via a communication link are provided by the module pair *ORC* (for Oberon to RISC Connection) running on the host system and *Oberon0* running on the target system.

The command *ORC.Load Oberon0.bin* loads the Oberon-0 command interpreter over the data link to the target system and starts it there. The commands *ORC.Send* and *ORC.Receive* transfer files between the host and the target system. The command *ORC.SR* ("send, then receive sequence of items") initiates a command on the target system and receives the command's response (if any).

 $^{^{7} \} http://github.com/andreaspirklbauer/Oberon-experimental/blob/master/Documentation/Safe-module-unloading-in-Oberon.pdf$

One can also include an *entire* Oberon system in a single *boot file*. Sending a pre-linked binary file containing the entire Oberon system over a serial link to a target system is similar to booting a commercial operating system in a *Plug & Play* fashion over the network or from a USB stick.

There is a variety of other Oberon-0 commands that can be initiated from the host system once the Oberon-0 command interpreter is running on the target system, for example commands for system inspection, loading and unloading of modules or the (remote) execution of commands.

Finally, there are tools to modify the boot loader itself (module *BootLoad*), a small *standalone* program permanently resident in the computer's read-only store (ROM or PROM) – although there generally is no need to do so. Such standalone programs can be created with the regular Oberon compiler. Once compiled, the tool command *ORX.WriteFile* can be used to extract the code section from the boot loader's object file and to convert it to a PROM file compatible with the specific hardware used. Transferring the boot loader to the permanent read-only store of the target hardware typically requires the use of proprietary (or third-party) tools.

The system building tools for FPGA Oberon and Experimental Oberon, as outlined above, are described in more detail in a separate document⁸.

4. Smooth scrolling of displayed texts with variable line spaces

Experimental Oberon enables completely smooth, fractional line scrolling of displayed texts with variable lines spaces and dragging of entire viewers with continuous content refresh. Both *far* (positional) scrolling and *near* (pixel-based) scrolling are realized. The system automatically switches back and forth between the two scrolling modes based on the horizontal position of the mouse pointer. For the purist, such a feature may represent an "unnecessary embellishment" of Oberon, but it is simply indispensable if the system is to support touch display devices where a mouse is absent and viewers may not have scrollbars. In such an environment, continuous scrolling is the only acceptable way to scroll and presents a more natural user interface. As a welcome side effect, the initial learning curve for users new to the Oberon system and its user interface is *considerably* reduced.

5. Multiple logical display areas ("virtual displays")

The Oberon system was designed to operate on a *single* abstract logical display area which is decomposed into a number of vertical *tracks*, each of which is further decomposed into a number of horizontal *viewers*. Experimental Oberon adds the ability to create *several* such display areas (or *displays* for short) on the fly and to seamlessly switch between them. Thus, the extended conceptual hierarchy of the display system consists of the triplet (*display, track, viewer*) and consequently the underlying base module *Viewers* exports procedures to add and remove *displays*, open and close *tracks* within existing displays and open and close individual *viewers* within tracks. There are no restrictions on the number of displays, tracks or viewers that can be created. Focus viewers and text selections are separately defined for each display, but there is only one system-wide log.

This scheme naturally maps to systems with multiple *physical* monitors attached to the same computer. It can also be used to realize super-fast context switching, for example in response to a swipe gesture on a touch display device.

 $^{^8 \} https://github.com/andreaspirklbauer/Oberon-experimental/blob/master/Documentation/The-Oberon-system-building-tools.pdf$

The command System. OpenDisplay name opens a new logical display with the specified name, System. CloseDisplay id closes an existing one. System. ShowDisplays lists all open displays, System. ThisDisplay shows the display id and name of the current display, System. SetDisplay id switches to a new display, System. SetDisplayName id name assigns a new name to an existing display, and System. PrevDisplay and System. NextDisplay "rotate" through the open displays.

The additional commands System. Expand, System. Spread and System. Clone are displayed in the title bar of every menu viewer. System. Expand expands the viewer as much as possible by reducing all other viewers in its track to their minimum heights, leaving just their title bars visible. The user can switch back to any of the minimized viewers by clicking on System. Expand again in any of these title bars. System. Spread evenly redistributes all viewers vertically. This may be useful after having invoked System. Expand. System. Clone opens a new logical display on the fly and displays a copy of the initiating viewer there. The user can then toggle between the two copies of the viewer (i.e. switch logical displays) with a single mouse click.

* * *