```
Alice (Caller)
                                                                                      Server (WhatsApp)
                                                                                                                                                                                             Bob (Callee)
\text{HKDF}: (\textit{Key}, \textit{Info}, \textit{Salt}, i) \rightarrow \{0, 1\}^{i \times 8}
\operatorname{Enc}_k:(m)\to\operatorname{AES-128-ICM}_k(m)
\operatorname{Auth}_{ak}:(m,j)\rightarrow\operatorname{HMAC-SHA1}_{ak}(m)\in\left\{0,1\right\}^{j\times8}
StreamInit : (Key, IV, Nonce) \rightarrow StreamContext
ms \leftarrow_{\$} \{0,1\}^{256}
id_{call} \leftarrow_{\$} \{0,1\}^{256}
                                    Noise(id_{call}, id_A, id_B, Signal(ms))
                                                                                                                                   Noise(id_{call}, id_A, id_B, Signal(ms))
k_{A0}, s_{A0} \leftarrow \text{HKDF}(ms, id_A, 0, 46)
                                                                                                                                                             k_{A0}, s_{A0} \leftarrow \text{HKDF}(ms, id_A, 0, 46)
k_{A1}, s_{A1} \leftarrow ?
                                                                                                                                                                                                k_{A1}, s_{A1} \leftarrow ?
k_{A2}, s_{A2} \leftarrow ?
                                                                                                                                                                                                k_{A2}, s_{A2} \leftarrow ?
n_{A0} \leftarrow \text{HKDF}(id_{call}, id_{A}, 0, 4)
                                                                                                                                                                  n_{A0} \leftarrow \text{HKDF}(id_{call}, id_A, 0, 4)
n_{A1} \leftarrow \text{HKDF}(id_{call}, id_A, 1, 4)
                                                                                                                                                                  n_{A1} \leftarrow \text{HKDF}(id_{call}, id_A, 1, 4)
n_{A2} \leftarrow \text{HKDF}(id_{call}, id_A, 4, 4)
                                                                                                                                                                  n_{A2} \leftarrow \text{HKDF}(id_{call}, id_A, 4, 4)
                                                                                                                                                                                                     ak_{A0} \leftarrow ?
ak_{A0} \leftarrow ?
ak_{A1} \leftarrow ?
                                                                                                                                                                                                     ak_{A1} \leftarrow ?
ak_{A2} \leftarrow ?
                                                                                                                                                                                                     ak_{A2} \leftarrow ?
c_{Ai} \leftarrow \operatorname{Enc}_{k_{Ai}}(m_{Ai})
srtpHeader_{Ai} \leftarrow ssrc_{Ai}, seq_{Ai}, t
auth_{A0} \leftarrow \text{Auth}_{ak_{A0}}(0,4)
auth_{A1} \leftarrow \text{Auth}_{ak_{A1}}(0,4)
auth_{A2} \leftarrow \text{Auth}_{ak_{A2}}(srtpHeader_{A2}|c_{A2},10)
stream_{Ai} \leftarrow StreamInit(k_{Ai}, s_{Ai}, n_{Ai})
                                                                                                                                                    stream_{Ai} \leftarrow StreamInit(k_{Ai}, s_{Ai}, n_{Ai})
                                                                                    srtpHeader_{Ai}, c_{Ai}, auth_{Ai}
k_{B0}, s_{B0} \leftarrow \text{HKDF}(ms, id_B, 0, 46)
                                                                                                                                                            k_{B0}, s_{B0} \leftarrow \text{HKDF}(ms, id_B, 0, 46)
k_{B1}, s_{B1} \leftarrow ?
                                                                                                                                                                                               k_{B1}, s_{B1} \leftarrow ?
k_{B2}, s_{B2} \leftarrow ?
                                                                                                                                                                                                k_{B2}, s_{B2} \leftarrow ?
n_{B0} \leftarrow \text{HKDF}(id_{call}, id_B, 0, 4)
                                                                                                                                                                  n_{B0} \leftarrow \text{HKDF}(id_{call}, id_B, 0, 4)
                                                                                                                                                                  n_{B1} \leftarrow \text{HKDF}(id_{call}, id_B, 1, 4)
n_{B1} \leftarrow \text{HKDF}(id_{call}, id_B, 1, 4)
n_{B2} \leftarrow \text{HKDF}(id_{call}, id_B, 4, 4)
                                                                                                                                                                  n_{B2} \leftarrow \text{HKDF}(id_{call}, id_B, 4, 4)
ak_{B0} \leftarrow ?
                                                                                                                                                                                                     ak_{B0} \leftarrow ?
ak_{B1} \leftarrow ?
                                                                                                                                                                                                     ak_{B1} \leftarrow ?
ak_{B2} \leftarrow ?
                                                                                                                                                                                                     ak_{B2} \leftarrow ?
                                                                                                                                                                                   c_{Bi} \leftarrow \operatorname{Enc}_{k_{Bi}}(m_{Bi})
                                                                                                                                                                srtpHeader_{Bi} \leftarrow ssrc_{Bi}, seq_{Bi}, t
                                                                                                                                                                          auth_{B0} \leftarrow \text{Auth}_{ak_{B0}}(0,4)
                                                                                                                                                                          auth_{B1} \leftarrow \text{Auth}_{ak_{B1}}(0,4)
                                                                                                                                           auth_{B2} \leftarrow \text{Auth}_{ak_{B2}}(srtpHeader_{B2}|c_{B2}, 10)
stream_{Bi} \leftarrow StreamInit(k_{Bi}, s_{Bi}, n_{Bi})
                                                                                                                                                    stream_{Bi} \leftarrow StreamInit(k_{Bi}, s_{Bi}, n_{Bi})
                                                                                    srtpHeader_{Bi}, c_{Bi}, auth_{Bi}
```

Figure 6.1: WhatsApp VoIP Protocol