
Oritone LaTeX Manual

Oritone Maintainers

2026-05-04

Abstract

Oritone is a LaTeX package and class collection for CVs, manuscripts, theses, and Beamer presentations. It centralizes color roles, font roles, listings, plots, localized labels, callouts, title rules, and page furniture so the individual document frontends share one visual language.

Keywords: LaTeX • document classes • Beamer theme • Recursive fonts • technical documents

Contents

1	Package Layout	2
2	Installation	3
3	Core Package	3
3.1	Options	4
4	Fonts	4
5	Shared Design Roles	5
6	CV Class	6
6.1	CV Options	6
6.2	CV Commands	7
7	Manuscript Class	7

7.1	Manuscript Options	8
7.2	Manuscript Features	8
8	Thesis Class	8
8.1	Thesis Options	9
8.2	Thesis Commands	10
9	Beamer Theme	10
9.1	Beamer Options	11
9.2	Beamer Commands	11
10	Listings and Plots	11
11	Examples and Tests	12
12	Release Maintenance	12

1 • Package Layout

The public source tree is intentionally small:

Path	Purpose
<code>tex/latex/oritone/oritone.sty</code>	Shared palette, color modes, semantic color roles, listings, and PGFPlots integration.
<code>tex/latex/oritone/oritone-fonts.sty</code>	Engine-aware font role loading for serif, sans, mono, and math fonts.
<code>tex/latex/oritone/oritone-design.sty</code>	Shared document-design helpers: labels, links, page colors, callouts, and ruled title blocks.
<code>tex/latex/oritone/oritone-cv.cls</code>	Compact CV class based on article.
<code>tex/latex/oritone/oritone-manuscript.cls</code>	Review-friendly manuscript class based on extarticle.
<code>tex/latex/oritone/oritone-thesis.cls</code>	Long-form thesis class based on book.
<code>tex/latex/oritone/beamerthemeOritone.sty</code> and subthemes	Beamer theme, color theme, font theme, inner theme, outer theme, and shared theme options.
<code>examples/</code>	Filled example documents and mode wrappers used by the documentation build.
<code>testfiles/</code>	l3build regression and smoke tests.

2 • Installation

From a checkout, install the files into the local TeX tree with:

```
1 l3build install
```

For one-off local testing without installing, put the source directory on `TEXINPUTS`:

```
1 TEXINPUTS="$(pwd)/tex/latex/oritone//:" pdflatex examples/manuscript-white.tex
```

The package targets LaTeX2e from 2020-10-01 or newer. The examples and tests are expected to compile with pdfLaTeX, LuaLaTeX, and XeLaTeX, subject to the font notes in [Section 4](#).

3 • Core Package

The base package is loaded directly when a document only needs the palette, listing style, or plot style:

```
1 \usepackage[mode=white,accent=blue,listings,plots]{oritone}
```

3.1 • Options

Option	Values	Effect
mode	light, dark, white, black	Selects the active foreground, background, surface, and semantic color roles.
accent	auto, orange, sky, green, yellow, blue, vermillion, rose, purple, red, amber, cyan	Selects the accent hue used for links, rules, headings, and progress bars.
accentshade	normal, dark, darker, light, lighter	Shades the main accent toward the foreground text (dark/darker) or the page background (light/lighter), leaving the derived accent ramp unchanged. Useful when the default accent looks too bright on the light and white modes.
listings or julia	Boolean	Loads listings and enables the shared Oritone listing styles.
plots or pgfplots	Boolean	Loads pgfplots and enables the shared Oritone plot cycle and axis defaults.

The active mode and accent can also be changed after package load:

```
1 \oritonesetup{mode=dark,accent=amber}
2 \oritonesetup{mode=white,accent=blue,accentshade=dark}
```

4 • Fonts

Font loading is centralized in oritone-fonts. The default role profile is:

Role	Default	Used for
Serif	STIX Two Text	Body text in manuscript and thesis documents.
Math	STIX Two Math	Math in unicode engines; pdfLaTeX uses the STIX2 package.
Sans	Roboto Condensed	CV body text, headings, title pages, headers, footers, Beamer text, labels, and other display roles.
Mono	Recursive Mono	Listings, verbatim-like text, and code-oriented helper macros.

LuaLaTeX and XeLaTeX use fontspec and unicode-math. They first try installed Roboto, Recursive, and STIX names, then known static font file names, then fallback families.

pdfLaTeX cannot load OpenType system fonts directly. For Roboto Condensed it uses the roboto package, and for Recursive Mono the optional external recursive package when `recursive.sty` is installed. If a support package is missing, Oritone warns and falls back to PT Sans and Inconsolata so the document remains compileable.

```
1 git clone git@github.com:schmaeke/latex-recursive.git
2 cd latex-recursive
3 l3build install
```

Advanced users can load oritone-fonts directly with role overrides:

```
1 \usepackage[
2   serif=TeX Gyre Termes,
3   sans=Recursive Sans,
4   mono=Recursive Mono,
5   math=STIX Two Math,
6   sansscale=0.95,
7   monoscale=1.0
8 ]{oritone-fonts}
```

5 • Shared Design Roles

oritone-design is loaded by the classes and theme. It provides:

- `\oritoneApplyPageColors` for applying the active foreground and background to the page.
- `\oritoneSetSemanticLinks` for semantic hyperref colors.
- `\oritoneRuledTitle` for title text framed by horizontal rules.
- `\oritonedefinecallouts` for `oritonenote`, `oritoneexample`, and `oritonewarning`.
- `\oritonelabel` and `\oritonecurrentlabel` for localized labels such as page, abstract, keywords, declaration, and footer text.

Most documents should not load `oritone-design` directly. Use the classes or the Beamer theme unless you are building another Oritone-compatible frontend.

6 • CV Class

The CV class is a compact, sans-serif article derivative:

```

1 \documentclass[white,10pt,a4paper,language=english]{oritone-cv}
2
3 \name{Ada}
4 \surname{Sterling}
5 \shortinfo{\maillink{ada@example.com}\sep\weblink{\faGlobe}{ada.dev}{ada.dev}}
6 \phrase{I build reliable research software.}
7
8 \begin{document}
9 \cvhead
10 \cvsection{Experience}
11 \cvdatedentry{Example Laboratory}{2022--Present}{Built reusable workflows.}
12 \end{document}

```

6.1 • CV Options

The class accepts `light`, `dark`, `white`, `black`, or `mode=...`; `accent=...`; `language=...`; ordinary article paper options; and `10pt`, `11pt`, or `12pt`. If no paper or size is selected, it defaults to A4 and 10 pt.

6.2 • CV Commands

Command	Purpose
<code>\name, \surname, \shortinfo, \phrase</code>	Store header metadata for <code>\cvhead</code> .
<code>\cvhead</code>	Render the name, contact line, accent rule, and phrase.
<code>\cvsection</code>	Schedule a section heading.
<code>\cventry</code>	Entry with title and body.
<code>\cvdatedentry</code>	Entry with title, date/meta column, and body.
<code>\cvdatedentryshort</code>	Compact dated entry for projects, talks, skills, or short lists.
<code>\cvcustomentry</code>	Explicit title, right-side meta, and body.
<code>\maillink, \phonelink, \weblink, \inlinelink</code>	Contact and inline link helpers.
<code>\sep, \lastupdated, \highlighted</code>	Inline separators and small text helpers.

7 • Manuscript Class

The manuscript class is intended for review drafts, internal reports, preprints, and short technical papers:

```

1 \documentclass[white,11pt,oneside,accent=blue]{oritone-manuscript}
2
3 \title{A Reusable Scientific Report}
4 \author[1]{Ada Example}
5 \affil[1]{Example University}
6 \date{\today}
7
8 \begin{document}
9 \maketitle
10
11 \begin{abstract}
12 The abstract spans the full text width and has no first-line indent.
13 \end{abstract}
14
15 \keywords{reports\keywordsep LaTeX\keywordsep reusable classes}
16
17 \section{Introduction}

```

```

18 Body text starts here.
19 \end{document}

```

7.1 • Manuscript Options

The class accepts `light`, `dark`, `white`, `black`, or `mode=...`; `accent=...`; `language=...`; `oneside` or `twoside`; common paper options; and extarticle sizes from `8pt` through `20pt`. The default is A4, 10 pt, two-sided.

7.2 • Manuscript Features

- Full-width abstract with localized sans-serif heading.
- `\keywords` helper with localized label and `\keywordsep` separator.
- Optional `\printcompileinfo` footer timestamp.
- Dense sans-serif headings through `titlesec`.
- `authblk` author and affiliation support.
- `lineno`, `cleveref`, `hyperref`, `listings`, `TikZ`, and semantic callouts.

8 • Thesis Class

The thesis class is a longer-form book derivative with front matter, metadata helpers, bibliography helpers, declaration page, plots, listings, and two-sided running heads.

```

1 \documentclass[english,white,bibtex]{oritone-thesis}
2
3 \title{A Thesis Built with Oritone}
4 \author{Ada Example}
5 \date{\today}
6
7 \universityName{Example University}
8 \studyProgram{Computational Engineering}
9 \desiredDegree{Master of Science}
10 \firstExaminer{Prof. A. Example}{Computational Methods}
11 \secondExaminer{Prof. B. Sample}{Software Systems}
12 \thesisSubject{Thesis class demonstration}

```



```

13 \thesisKeywords{LaTeX, thesis, Oritone}
14 \thesisBibliographyResource{references}
15
16 \begin{document}
17 \frontmatter
18 \maketitle
19 \abstractChapter
20 Abstract text.
21 \tableofcontents
22 \mainmatter
23 \chapter{Introduction}
24 \printThesisBibliography
25 \declarationOfAcademicIntegrity
26 \end{document}

```

8.1 • Thesis Options

The class accepts `light`, `dark`, `white`, `black`, or `mode=...`; `accent=...`; `language=...`; `oneside` or `twoside`; common paper options; `10pt`, `11pt`, or `12pt`; `draft` or `final`; `bibtex` or `biblatex`; and `colorlinks` or `hidelinks`. The default is A4, 12 pt, two-sided, final, BibTeX, and color links.

8.2 • Thesis Commands

Command	Purpose
<code>\universityName,</code> <code>\universityLogo,</code> <code>\universityLogoWidth</code>	Institution title-page metadata.
<code>\studyProgram, \desiredDegree</code>	Degree metadata.
<code>\firstExaminer,</code> <code>\secondExaminer</code>	Examiner metadata.
<code>\thesisSubject,</code> <code>\thesisKeywords</code>	PDF metadata.
<code>\abstractChapter</code>	Localized unnumbered abstract chapter.
<code>\thesisBibliographyStyle,</code> <code>\thesisBibliographyResource,</code> <code>\printThesisBibliography</code>	BibTeX/BibLaTeX abstraction helpers.
<code>\declarationOfAcademicIntegrity</code>	Localized declaration page.
<code>\todo, \linktt, \intd, \Assembly,</code> <code>\bs</code>	Small thesis prose and math helpers.

9 • Beamer Theme

Use the theme with a regular Beamer document:

```

1 \documentclass[aspectratio=1610]{beamer}
2 \usetheme[mode=light,accent=blue]{Oritone}
3
4 \title{A Complete Oritone Deck}
5 \author{Ada Example}
6 \institute{Example Laboratory}
7 \date{\today}
8 \biglogo{example-image-a}
9 \smalllogo{example-image-b}
10
11 \begin{document}
12 \maketitle
13 \sectionframe{Overview}
14 \begin{frame}{Motivation}
15   \begin{block}{Claim}

```

```

16     Shared package roles keep slides and documents consistent.
17   \end{block}
18 \end{frame}
19 \closingframe{Thank you}{example.com/oritone}{Questions}
20 \end{document}

```

9.1 • Beamer Options

The theme accepts `light`, `dark`, `white`, `black`, or `mode=...`; `accent=...`; `accentshade=...`; the accent shortcut options; and `draftlogos` or `showlogoplaceholders`. Missing logo placeholders are silent unless a placeholder option is enabled.

9.2 • Beamer Commands

Command	Purpose
<code>\titleframe</code> or <code>\maketitle</code>	Render the Oritone title slide.
<code>\sectionframe</code>	Create a section divider slide.
<code>\standoutframe</code>	Create a slide without normal header/footer chrome and with a left accent rule.
<code>\closingframe</code>	Render a closing slide with title and optional logo.
<code>\slidebackground</code> , <code>\noslidebackground</code>	Set or clear the optional curved slide background image.
<code>\coauthors</code> , <code>\smalllogo</code>	<code>\biglogo</code> , Presentation metadata helpers.
<code>\weblink</code>	Link helper for bare host names.

10 • Listings and Plots

Classes call `\oritonelistingsetup` and select the shared `oritone-listing` style automatically. The base style uses Recursive Mono or the configured mono fallback, a smaller code size, and the document's line spacing stretch.

```

1 function residual(values)
2   return sum(abs, values)
3 end

```

Listing 1: A compact listing.

The thesis class and Beamer examples call `\oritonepgfplotssetup` to install the shared axis and color-cycle defaults. Users of the base package can enable the same behavior with:

```
1 \usepackage[plots]{oritone}
2 \oritonepgfplotssetup
```

The plot cycle follows the Okabe-Ito colorblind-safe palette, mapped to the closest Oritone hues and ordered blue, vermillion, green, purple, sky, orange, yellow, and gray. The colors are available individually as `plotblue`, `plotvermillion`, `plotgreen`, `plotpurple`, `plotsky`, `plotorange`, `plotyellow`, and `plotgray`.

11 • Examples and Tests

Build the documentation and example PDFs with:

```
1 l3build doc
```

This creates the manual and the mode-specific example PDFs under `build/doc`. The source examples are intentionally filled documents so title pages, headings, captions, listings, plots, tables, line numbers, links, headers, footers, and slide furniture are visible during review.

Run the regression suite with:

```
1 l3build check
```

The suite covers color mode switching, listings, plots, and smoke tests for the CV, manuscript, thesis, and Beamer public entry points.

12 • Release Maintenance

Before tagging a release, run the checklist in `RELEASE.md`. The short version is:

```
1 l3build check
2 l3build doc
3 rsync -a build/doc/oritone.pdf doc/oritone.pdf
```

Screenshots in `assets/screenshots` should be refreshed from the current generated example PDFs whenever the visual design changes.