Early Identification of Human Cognitive Biases in the Design of Joint Cognitive Systems: A Feasibility Study

Martin Schmettow

Joel Surall

Valeria Resendez Gomez

ABSTRACT

Cognitive biases systematically impair professional decision-making, and AI systems trained on human-generated data risk inheriting or amplifying these distortions. This paper presents a proof-of-concept for a literature-grounded retrieval-augmented generation (RAG) system aimed at detecting cognitive biases in narratives collected during requirements elicitation, with dual application goals: preventing biased patterns from entering AI training data and enabling targeted bias mitigation in joint human–AI operation. Across five professional domains—emergency medicine, aviation, finance, cybersecurity, and engineering—the system identified 20 of 21 intentionally embedded biases in structured scenarios. Testing with simulated Cognitive Task Analysis (CTA) interview narratives revealed key technical requirements for a RAG-based expert system, including prompt-length limits and model capacity. Findings indicate that retrieval-grounded approaches are a promising starting point for AI-supported bias awareness in complex professional contexts, contingent on curated knowledge bases and capable language models.

ACM Reference Format:

Martin Schmettow, Joel Surall, and Valeria Resendez Gomez. 2026. Early Identification of Human Cognitive Biases in the Design of Joint Cognitive Systems: A Feasibility Study. In . ACM, New York, NY, USA, 5 pages. https://doi.org/10.1145/nnnnnnn.nnnnnnn

1 INTRODUCTION

1.1 Cognitive Bias in Professional Decision-Making

Professionals in domains such as healthcare, aviation, and management frequently make critical decisions under conditions of time pressure, uncertainty, and high workload (Berthet 2022; Egoda Kapuralalage et al. 2025; Korentsides et al. 2026). In such environments, decision-making is often supported by heuristics—intuitive mental shortcuts—that allow individuals to process information rapidly and efficiently (Agarwal et al. 2023; Korteling and Toet 2022). Although heuristics help manage limited cognitive resources, they can also lead to systematic deviations from rational standards of reasoning and probability. These deviations are commonly described as cognitive biases (Knipper et al. 2025; Korteling and Toet 2022).

Cognitive biases have been linked to errors in a wide range of professional contexts. In surgical environments they have been implicated in a substantial proportion of adverse clinical events (Agarwal et al. 2023). In emergency departments, biases such as anchoring and availability can influence triage decisions and contribute to diagnostic errors (Bhuvaneswari et al. 2025; Egoda Kapuralalage et al. 2025). Similarly, in strategic and managerial decision-making, confirmation bias and overconfidence can distort risk assessment and contribute to flawed strategic choices (Rau and Bromiley 2025; Theodorakopoulos, Theodoropoulou, and Halkiopoulos 2025). These findings suggest that cognitive biases represent a persistent challenge for reliable decision-making in complex professional environments.

1.2 AI-Supported Decision-Making and Bias Amplification

At the same time, artificial intelligence (AI) and automated decision-support systems are increasingly integrated into professional workflows. While such systems are often expected to improve decision quality, they do not automatically eliminate cognitive biases. AI systems frequently inherit patterns present in human-generated data and can reproduce or amplify biased reasoning structures (Aich 2025; Vicente and Matute 2023). In addition, the presence of automated recommendations can influence human judgment through *automation bias*—the tendency to over-rely on algorithmic outputs even when contradictory information is available (Romeo and Conti 2026). Under conditions of time pressure and cognitive load, professionals may therefore defer uncritically to algorithmic suggestions, creating situations in which human and machine biases interact rather than cancel each other out (Lim 2025; Mahajan et al. 2025).

In response to these challenges, recent research has explored debiasing strategies aimed at promoting more reflective and

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.
Conference'17, July 2017, Washington, DC, USA
© 2026 Copyright held by the owner/author(s). Publication rights licensed to ACM.
ACM ISBN 978-x-xxxx-xxxx-x/YY/MM
https://doi.org/10.1145/nnnnnnn.nnnnnnn

analytically engaged decision-making. These approaches include metacognitive training, cognitive forcing functions, and system designs that introduce deliberate friction to encourage users to reconsider initial judgments (Baruh, Cemalcilar, and Stoycheff 2026; Cabitza et al. 2024). Other proposals involve collaborative AI architectures, such as multi-agent systems or adversarial prompting approaches, which challenge preliminary conclusions and encourage the consideration of alternative explanations (Cabitza et al. 2024; Ke et al. 2024). Across these approaches, a common principle is that decision quality can improve when individuals are supported in questioning initial interpretations and considering alternative explanations.

1.3 Retrieval-Augmented Generation for Bias Detection

Research on cognitive biases is rooted in the concept of bounded rationality, first introduced by Herbert Simon. The heuristics-and-biases research program developed by Kahneman and Tversky later expanded this work by showing how human judgment systematically departs from ideal rational models. The theme of Bounded Rationality has been very productive in the past and present, which makes it challenging to absorb into a user requirements analysis method. At the same time the immense body of literature could serve very well to create an LLM-based conversational agent using retrieval-augmented generation (RAG). In contrast to unguided language model generation, RAG systems combine generative models with external knowledge retrieval, allowing responses to be grounded in a curated body of literature or domain-specific knowledge (Albashrawi 2025; Soroush et al. 2025). This grounding improves transparency and traceability by linking generated explanations to identifiable sources. For topics such as cognitive bias detection, this architecture is particularly relevant because meaningful support requires connecting narrative descriptions of decision processes with established theoretical concepts and evidence-based debiasing strategies.

Detecting biases in realistic professional narratives, however, remains difficult. Cognitive biases are rarely expressed explicitly; instead, they are often reflected indirectly in interpretation patterns, selective framing of information, or reliance on memorable narratives rather than statistical evidence (Echterhoff et al. 2024; Korteling, Paradies, and Sassen-van Meer 2023). These characteristics make subtle biases difficult to identify through introspection or self-report. Narrative materials such as Cognitive Task Analysis (CTA) interviews therefore provide a challenging but ecologically relevant test case for exploring AI-supported bias detection.

1.4 Aim of the Study

For the design og cognitive joint systems, two goals can be derived from Bounded Rationality, (a) a *preventive strategy* in which identified biases are prevented from entering AI training data, and (b) an *progressive strategy* in which the system is specifically trained to counteract biases in joint human–AI operation. The present project developed and explored a proof-of-concept for a literature-grounded RAG system aimed at detecting cognitive biases in user requirement artifacts. The project investigated whether an AI system anchored in a curated body of cognitive bias literature could identify bias patterns in fictional professional scenarios and narrative interview material across multiple professional domains.

2 METHOD

This project followed an exploratory, design-oriented proof-of-concept approach structured into five successive phases: (1) literature exploration and corpus scoping, (2) automated corpus construction, (3) RAG-based testing with structured professional scenarios, (4) evaluation framework development using simulated CTA interviews, and (5) implementation of a local RAG system to address technical constraints. In the following sections the approach is summarized, whereas a detailed report can be found in Surall and Schmettow (2026).

2.1 Literature Corpus (Phases 1–2)

The first phase systematically identified literature on cognitive biases, debiasing strategies and human–AI interaction. Searches covered PsycINFO, PubMed/MEDLINE, Web of Science, Scopus, ACM Digital Library, IEEE Xplore, and Google Scholar. Search string development was supported iteratively using ChatGPT. In the second phase, a Python-based Scopus web scraper was used to extract article metadata, producing an initial corpus of more than 250 research papers after combined manual and automated retrieval.

2.2 Scenario Testing with NotebookLM (Phase 3)

To conduct an initial feasibility test, fictional professional scenarios were constructed using ChatGPT across five domains: emergency medicine (chest-pain triage), aviation (flight decision-making), finance (loan approval), cybersecurity (incident response), and engineering/project management. Each scenario embedded a predefined set of cognitive biases reflecting decision conditions such as time pressure, incomplete information, workload, and social influence. In total, 21 biases were intentionally embedded across the five scenarios. The literature corpus was loaded into Google NotebookLM—which supports up to 50 simultaneously embedded PDF sources—and the system was prompted to identify cognitive biases, explain their contextual relevance, and suggest debiasing actions. Detected biases were compared with the embedded reference set; ChatGPT assisted in summarizing the overlap, and results were manually reviewed for accuracy.

2.3 CTA Interview Materials (Phase 4)

To increase task realism, two simulated CTA interview narratives were generated using ChatGPT, with instructions to embed up to three biases per narrative without making them explicitly identifiable. The first interview was shorter and focused on operational decision-making; the second was

longer and included unrelated contextual content (stress management, hobbies) to simulate realistic interview noise. An annotated reference solution—mapping each bias to specific transcript passages and explanations—was created to serve as a benchmark for future human–RAG comparison.

Biases were embedded in statements describing operational reasoning, for example: "I considered rerouting it slightly, but last time I tried a new path it didn't help, so I stuck with the standard route." This passage illustrates a preference for established procedures and reluctance to deviate from prior decisions, which corresponds to status quo bias and conservatism. Other passages reflected patterns such as reliance on past outcomes, assumptions about predictability of others' behaviour, and optimistic expectations about system stability.

2.4 Local RAG Implementation (Phase 5)

Because NotebookLM imposes a prompt input limit of approximately 250 words—preventing analysis of full interview transcripts—a local RAG system was implemented using OpenNotebookLM (an open-source alternative) running via the Ollama inference framework. Setup required manual troubleshooting beyond the available documentation. Due to hardware constraints (limited VRAM and RAM), only a lower-capacity language model could be run locally. The system was evaluated for its ability to detect biases in the embedded literature-grounded setting.

3 RESULTS

3.1 Structured Scenario Testing

Across the five professional scenarios, NotebookLM identified 20 of the 21 intentionally embedded biases (95.2%). The single missed bias was *base-rate neglect* in the emergency department scenario—a probabilistic reasoning bias not explicitly cued in the narrative. In the remaining four scenarios, all embedded biases were detected. In several cases the system applied slightly different labels than the predefined categories, but the underlying concepts corresponded closely to the intended biases.

Beyond identification, the system consistently linked detected biases to contextual triggers within the scenarios, including time pressure, reliance on automated systems, authority influence, prior experiences, and organizational incentives. Suggested debiasing strategies focused on slowing decision processes, introducing structured review moments, applying checklists or cognitive forcing techniques, and encouraging consideration of alternative interpretations. Detection was strongest for explicitly cued biases such as anchoring, confirmation bias, automation bias, authority bias, and escalation of commitment.

3.2 CTA Interview Framework

Phase 4 produced two simulated CTA interview narratives embedding a range of subtle biases—including confirmation bias, status quo/conservatism bias, optimism bias, availability bias, overconfidence, and anchoring—alongside a structured evaluation framework. This framework comprised a participant reporting form, a multi-evaluator comparison checklist, and an annotated reference solution.

However, the planned comparison between RAG-based and human expert detection could not be executed. The prompt-length limit of NotebookLM (approximately 250 words) prevented the full interview transcripts from being submitted as input. Fragmenting the interviews would have removed contextual cues necessary for interpreting the embedded biases, so this strategy was not pursued.

3.3 Local RAG System

The local OpenNotebookLM system was successfully installed and could process document sources and generate retrieval-grounded responses. Initial tests confirmed that the system could identify cognitive biases in provided material. However, detection quality was lower than in the NotebookLM experiments: some biases were described using broader conceptual language rather than precise bias labels, and some embedded biases were missed entirely. These limitations are attributed primarily to the lower reasoning capacity of the model required by the available hardware.

The experiments also highlighted an important corpus-design consideration: retrieval quality did not improve with larger document collections. A large heterogeneous embedding space can reduce retrieval precision, suggesting that a smaller, carefully curated set of sources is preferable to a broad but loosely structured corpus.

4 DISCUSSION

4.1 Feasibility and Scope

The results demonstrate that a literature-grounded RAG system can operationalize cognitive bias detection when narrative cues are sufficiently salient. The near-complete detection rate in structured scenarios (20/21 biases) supports the feasibility of the approach for professional decision contexts. The single missed bias—base-rate neglect—was consistent with the broader literature on probabilistic reasoning biases, which are harder to detect because they depend on implicit statistical reasoning rather than explicit narrative cues (Knipper et al. 2025).

The ability to link detected biases to contextual decision factors and to generate plausible debiasing suggestions illustrates the potential of RAG systems to translate theoretical constructs from cognitive psychology into interpretive tools for professional decision situations. These properties are relevant to both application strategies motivating the project: preventing biased patterns from contaminating AI training corpora and supporting active debiasing in joint human–AI operation.

4.2 Technical Constraints

Several practical constraints limit the current scope of the system. The prompt-length limitation of cloud-based RAG interfaces prevented the analysis of full CTA interview transcripts, highlighting a critical gap between the complexity of realistic qualitative data and the technical affordances of current tools. The local RAG implementation partially addressed this gap but introduced trade-offs related to hardware capacity and model performance. Taken together, these findings suggest that the effectiveness of literature-grounded RAG systems depends on three interacting factors: the reasoning capabilities of the underlying language model, system-level constraints such as context-length limits, and the quality and structure of the embedded knowledge corpus.

4.3 Limitations

The professional scenarios used in testing were fictional and relatively structured, limiting ecological validity. Because cognitive biases were intentionally embedded within the scenarios, their presence may have been more detectable than in naturally occurring professional narratives. As a result, the detection rates observed in structured testing conditions may overestimate performance in real-world settings where biases are more subtle and context-dependent. On teh opposite, the simulated CTA interviews were not fully evaluated due to the prompt-length constraint. The local RAG setup underestimates achievable performance because hardware limitations required a low-capacity model. Finally, the literature corpus was only partially curated, and the subset available for embedding may not have been optimally composed for targeted retrieval.

4.4 Future Directions

Future work should (1) develop a focused, curated corpus of key publications on cognitive biases and decision-making to improve retrieval precision; (2) test the system using more capable local RAG configurations on higher-performance hardware, enabling analysis of complete CTA interview transcripts without fragmentation; (3) conduct a systematic comparison between human expert bias detection and RAG-based detection using the evaluation framework developed in Phase 4; and (4) explore integration of RAG-based bias detection into professional training environments as a reflective decision-support tool.

In addition, future studies should evaluate system performance using more ecologically valid materials, including real-world professional narratives and naturally occurring CTA interview data. Such studies should incorporate systematic reporting of false positives, false negatives, and cases of label disagreement to provide a more comprehensive understanding of detection behavior. Establishing inter-rater reliability among human annotators will further strengthen the validity of reference annotations.

Future evaluations should also include human comparison baselines, allowing calculation of standard performance metrics such as precision and recall. These measures will support more rigorous benchmarking and enable clearer assessment of how well detection accuracy observed in synthetic materials generalizes to real-world contexts. Finally, future research may explore adaptive retrieval strategies and corpus structuring methods to optimize retrieval performance in large-scale knowledge bases.

5 CONCLUSION

In an ideal joint cognitive system the partners complement each other rather than mirror or in the worst case amplify each others biases. Being able to identify potential biases early in the process is a critical step towards this goal. The present project demonstrates that detecting cognitive biases in requirements narratives is possible, making use of the extensive scientific literature. Bridging the gap between scientific research and engineering has always been a challenge. It seems feasible to build RAG-based tools that deliver on-demand scientific knowledge to system analysts in the field.

REFERENCES

Agarwal, S., H. Aylmore, H. Marcus, and A. Pandit. 2023. "374 Cognitive Biases and Heuristics in Surgical Settings: A Systematic Review." *British Journal of Surgery* 110 (Supplement_7): znad258.011. https://doi.org/10.1093/bjs/znad258.011.

Aich, P. 2025. "Cognitive Bias in AI Recommendations: Understanding and Mitigating Human-AI Decision-Making Errors." In *Proceedings of the 13th International Conference on Human-Agent Interaction*, 583–84. https://doi.org/10.1145/3765766.3765887.

Albashrawi, M. 2025. "Generative AI for Decision-Making: A Multidisciplinary Perspective." *Journal of Innovation & Knowledge* 10 (4): 100751. https://doi.org/10.1016/j.jik.2025.100751.

Baruh, L., Z. Cemalcilar, and A. Stoycheff. 2026. "Mitigating Cognitive Biases in Higher Education Contexts Through a Brief Video-Based Intervention: A Randomized Controlled Trial." *Computers & Education* 245: 105535. https://doi.org/10.1016/j.compedu.2025.105535.

Berthet, V. 2022. "The Impact of Cognitive Biases on Professionals' Decision-Making: A Review of Four Occupational Areas." *Frontiers in Psychology* 12: 802439. https://doi.org/10.3389/fpsyg.2021.802439.

Bhuvaneswari, E., K. D. V. Prasad, M. Ashraf, S. Jadhav, T. R. K. Rao, and T. Sudha Rani. 2025. "A Human-Centered Hybrid AI Framework for Optimizing Emergency Triage in Resource-Constrained Settings." *Intelligence-Based Medicine* 12: 100311. https://doi.org/10.1016/j.ibmed.2025.100311.

Cabitza, F., C. Natali, L. Famiglini, A. Campagner, V. Caccavella, and E. Gallazzi. 2024. "Never Tell Me the Odds: Investigating Pro-Hoc Explanations in Medical Decision

Making." *Artificial Intelligence in Medicine* 150: 102819. https://doi.org/10.1016/j.artmed.2024.102819.

Echterhoff, J. M., Y. Liu, A. Alessa, J. McAuley, and Z. He. 2024. "Cognitive Bias in Decision-Making with LLMs." In *Findings of the Association for Computational Linguistics: EMNLP 2024*, 12640–53. https://doi.org/10.18653/v1/2024.findings-emnlp.739.

Egoda Kapuralalage, T. N., H. F. Chan, U. Dulleck, J. A. Hughes, B. Torgler, and S. Whyte. 2025. "Clinical Decision-Making: Cognitive Biases and Heuristics in Triage Decisions in the Emergency Department." *The American Journal of Emergency Medicine* 92: 60–67. https://doi.org/10.1016/j.ajem.2025.02.043.

Ke, Y., R. Yang, S. A. Lie, T. X. Y. Lim, Y. Ning, I. Li, H. R. Abdullah, D. S. W. Ting, and N. Liu. 2024. "Mitigating Cognitive Biases in Clinical Decision-Making Through Multi-Agent Conversations Using Large Language Models: Simulation Study." *Journal of Medical Internet Research* 26: e59439. https://doi.org/10.2196/59439.

Knipper, R. A., C. S. Knipper, K. Zhang, V. Sims, C. Bowers, and S. Karmaker. 2025. "The Bias Is in the Details: An Assessment of Cognitive Bias in LLMs." https://doi.org/10.48550/arxiv.2509.22856.

Korentsides, J., E. R. Merwin, L. Berger, L. Laskey, S. R. Winter, B. Sobel, and J. R. Keebler. 2026. "The Use of Artificial Intelligence (AI) in the Flight Deck: Enhancing Human-AI Teamwork in Aviation." *Journal of the Air Transport Research Society* 6: 100099. https://doi.org/10.1016/j.jatrs.2025.100099.

Korteling, J. E., G. L. Paradies, and J. P. Sassen-van Meer. 2023. "Cognitive Bias and How to Improve Sustainable Decision Making." *Frontiers in Psychology* 14: 1129835. https://doi.org/10.3389/fpsyg.2023.1129835.

Korteling, J. E., and A. Toet. 2022. "Cognitive Biases." In *Encyclopedia of Behavioral Neuroscience*, 2nd ed., 610–19. Elsevier. https://doi.org/10.1016/B978-0-12-809324-5.24105-9.

Lim, C. 2025. "DeBiasMe: De-biasing Human-AI Interactions with Metacognitive AIED Interventions." https://doi.org/10.48550/arXiv.2504.16770.

Mahajan, A., Z. Obermeyer, R. Daneshjou, J. Lester, and D. Powell. 2025. "Cognitive Bias in Clinical Large Language Models." *Npj Digital Medicine* 8 (1): 428. https://doi.org/10.1038/s41746-025-01790-0.

Rau, D., and P. Bromiley. 2025. "A Review of Cognitive Biases in Strategic Decision Making." *Long Range Planning* 58 (3): 102529. https://doi.org/10.1016/j.lrp.2025.102529.

Romeo, G., and D. Conti. 2026. "Exploring Automation Bias in Human–AI Collaboration: A Review and Implications for Explainable AI." *AI & Society* 41 (1): 259–78. https://doi.org/10.1007/s00146-025-02422-7.

Soroush, A., M. Giuffrè, S. Chung, and D. L. Shung. 2025. "Generative Artificial Intelligence in Clinical Medicine and Impact on Gastroenterology." *Gastroenterology* 169 (3): 502–517.e1. https://doi.org/10.1053/j.gastro.2025.03.038.

Surall, J., and M. Schmettow. 2026. "Cognitive Biases in Human-AI Interaction: A Systematic Review of Bias Types, Mitigation Strategies, and Future Research Directions." https://github.com/schmettow/pub-cog-debias/blob/main/Surall_Schmettow_cognitive_debiasing.pdf.

Theodorakopoulos, L., A. Theodoropoulou, and C. Halkiopoulos. 2025. "Cognitive Bias Mitigation in Executive Decision-Making: A Data-Driven Approach Integrating Big Data Analytics, AI, and Explainable Systems." *Electronics* 14 (19): 3930. https://doi.org/10.3390/electronics14193930.

Vicente, L., and H. Matute. 2023. "Humans Inherit Artificial Intelligence Biases." *Scientific Reports* 13 (1): 15737. https://doi.org/10.1038/s41598-023-42384-8.