

WHEN TO WRITE A KUBERNETES OPERATOR AND HOW TO DO IT RIGHT (FEATURING: TEA)

ABOUT ME

Michael Schmitt

Sitereliability Engineer at Interhyp

<https://www.interhyp.de>

SO WHEN *DOES* AN OPERATOR MAKE SENSE?

When you need:

- relationships between resources
- invariants (“if X exists, Y must exist”)
- lifecycle & cleanup
- continuous enforcement


WHEN YOU *DON'T* NEED ONE

If it's:

- static resources
- one-off generation
- simple templating

 **Just use YAML.**

NO MAGIC. JUST A LOOP.



WHAT MAKES A GOOD OPERATOR?

- simple reconciliation logic
- idempotent behavior
- clear, meaningful status
- boring, predictable outcomes

THE LINE TO DRAW

You declare

- What you want with YAML

The Operator handles

- All relationships
- Complete Lifecycle
- Keeps everything in desired state
- Tells you when it fails

LET'S SCAFFOLD AN OPERATOR...

Install Go, a Kubernetes Distribution, Get the Operator SDK

```
operator-sdk init --domain "$DOMAIN" --repo "$REPO"
```

```
1 operator-sdk create api \  
2   --group kitchen \  
3   --version v1alpha1 \  
4   --kind Teapot \  
5   --resource \  
6   --controller
```


DEMO

TAKEAWAYS

- Operators are powerful - and expensive
- Write them rarely
- Keep them small
- Status is your UX

THANK YOU :-)



- [Presentation](#)
- [Golang](#)
- [Operator SDK](#)
- [Tea Pot Operator](#)
- [My LinkedIn Profile](#)