


X-Transfer: Enabling and Optimising Cross-PCN Transactions

Lukas Aumayr, Zeta Avarikioti, Iosif Salem, Stefan Schmid, **Michelle Yeo**




Payment channel networks

- Payment Channel Networks (PCNs) improve scalability and privacy of blockchains




Payment channel networks

- Payment Channel Networks (PCNs) improve scalability and privacy of blockchains




Payment channel networks

- Payment Channel Networks (PCNs) improve scalability and privacy of blockchains




Payment channel networks

- Payment Channel Networks (PCNs) improve scalability of blockchains
- Intermediary nodes charge fees to forward payments




Secure and interoperable PCNs



Secure and interoperable PCNs

- Issues:


1. Interoperability: how to convert payments across two systems?



Secure and interoperable PCNs

- Issues:


1. Interoperability: how to convert payments across two systems?
2. Security: what if intermediary runs away with payments?



Secure and interoperable PCNs

- Issues:

1. Interoperability: how to convert payments across two systems?
2. Security: what if intermediary runs away with payments?
3. Scalability: what if there are lots of payments?



Atomic cross-PCN transactions

Bridge solutions	[Herlihy18], [BKLZ20], [MTVFM23], [SAAMG23], [SABAM24]
TTP	[JYSLWL23]
Deposits	[ZQ23]

Atomic cross-PCN transactions

Bridge solutions	[Herlihy18], [BKLZ20], [MTVFM23], [SAAMG23], [SABAM24]
TTP	[JYSLWL23]
Deposits	[ZQ23]


Our work: first lightweight, scalable, fully off-chain, non-TTP solution

X-transfer desiderata

- Balance security
- Fee minimisation
- Computational feasibility
- Privacy


X-transfer

- Transaction aggregation + atomic cross-PCN execution



X-transfer


- Transaction aggregation + atomic cross-PCN execution
- Hub nodes: execute cross-PCN transfers
 - Hubs only execute transactions, do not send or receive
 - Star topology for efficient transaction aggregation¹



¹Increasing Throughput in Payment Channel Networks with Transaction Aggregation. TYASPS. **AFT 2022**


X-transfer: aggregation phase

- Goal:
 - Maximise client-to-hub transaction volume
 - Output optimal flow topology among hubs
 - Compute setup parameters for execution



X-transfer: aggregation phase

- Goal:
 - Maximise client-to-hub transaction volume
 - Output optimal flow topology among hubs
 - Compute setup parameters for execution



solve ILP and connect hubs


MPC to preserve privacy

X-transfer: aggregation phase

- Goal:
 - Maximise client-to-hub transaction volume
 - Output optimal flow topology among hubs
 - Compute setup parameters for execution




Safe PCNs: PCNs that have positive or 0 inflow from clients



X-transfer: aggregation phase

- Goal:
 - Maximise client-to-hub transaction volume
 - Output optimal flow topology among hubs
 - Compute setup parameters for execution


Safe PCNs: PCNs that have positive or 0 inflow from clients




Invariants:

1. Safe PCNs execute first
2. There is a receiver in unsafe PCN that has a corresponding sender in a safe PCN

X-transfer: execution phase



- Thora² for atomic execution in each PCN
- h_k samples secret s , $H(s)$ additional hashlock



²Thora: Atomic and Privacy-Preserving Multi-Channel Updates. AAM. **CCS 2022**

X-transfer analysis

Theorem (informal)

X-transfer satisfies balance security, computational feasibility, near optimality and privacy

Conclusion

- X-transfer: first lightweight, scalable, fully off-chain cross-PCN transaction aggregation and payment protocol
- Future directions:
 - Fee structure for hubs
 - Exchange rates

michellexyeo@gmail.com

