

Reinforcement Learning in Vision: A Survey

Weijia Wu¹ Chen Gao¹ Joya Chen¹ Kevin Qinghong Lin¹ Qingwei Meng²
 Yiming Zhang³ Yuke Qiu² Hong Zhou² Mike Zheng Shou¹ *

¹Show Lab, National University of Singapore

²Zhejiang University

³The Chinese University of Hong Kong

Abstract

Recent advances at the intersection of reinforcement learning (RL) and visual intelligence have enabled agents that not only perceive complex visual scenes but also reason, generate, and act within them. This survey offers a critical and up-to-date synthesis of the field. We first formalize visual RL problems and trace the evolution of policy-optimization strategies from RLHF to verifiable reward paradigms, and from Proximal Policy Optimization to Group Relative Policy Optimization. We then organize more than 200 representative works into four thematic pillars: multi-modal large language models, visual generation, unified model frameworks, and vision-language-action models. For each pillar we examine algorithmic design, reward engineering, benchmark progress, and we distill trends such as curriculum-driven training, preference-aligned diffusion, and unified reward modeling. Finally, we review evaluation protocols spanning set-level fidelity, sample-level preference, and state-level stability, and we identify open challenges that include sample efficiency, generalization, and safe deployment. Our goal is to provide researchers and practitioners with a coherent map of the rapidly expanding landscape of visual RL and to highlight promising directions for future inquiry. Resources are available at: <https://github.com/weijiawu/Awesome-Visual-Reinforcement-Learning>.

1 Introduction

Reinforcement Learning (RL) has achieved remarkable successes in the field of Large Language Models (LLMs) (Jaech et al., 2024; Rafailov et al., 2023), most notably through paradigms like Reinforcement Learning from Human Feedback (RLHF) (Ouyang et al., 2022) and innovative frameworks such as DeepSeek-R1 (Guo et al., 2025a). These methodologies have significantly enhanced the capabilities of LLMs, aligning generated outputs closely with human preferences and enabling nuanced, complex reasoning and interaction capabilities previously unattainable through supervised learning alone.

In recent years, inspired by these remarkable achievements from LLM, there has been an explosive interest in extending the RL methodologies that proved successful for LLMs to multimodal large models, including Vision-Language Models (VLM) (Zhou et al., 2025a; Zheng et al., 2025; Zhang et al., 2025g), Vision-Language-Action models (VLA) (Lu et al., 2025b; Tan et al., 2025b; Luo et al., 2025; Yuan et al., 2025b), diffusion-based visual generation models (Fan et al., 2023b; Black et al., 2023; Zhou et al., 2025c), and unified multimodal frameworks (Mao et al., 2025; Wang et al., 2024b; 2025a), as shown in Figure 1. Multimodal models such as Gemini 2.5 (DeepMind, 2025) have leveraged RL to align visual-textual reasoning processes and produce outputs with higher semantic coherence and alignment with human judgments. Concurrently, VLA models integrating vision and language with action-oriented outputs have adopted RL to optimize complex sequential decision-making processes in interactive environments, significantly improving task-specific performance in GUI automation (Yuan et al., 2025b; Shi et al., 2025), robotic manipulation (Lu et al., 2025b), and embodied navigation (Kim et al., 2025). The rapid advancement of diffusion-based generative models has further spurred

*Corresponding author : Mike Zheng Shou (mikeshou@nus.edu.sg).




Figure 1: **Timeline of Representative Visual Reinforcement Learning Models.** The figure presents a chronological overview of key Visual RL models from 2023 to 2025, organized into four tracks: Multimodal LLM, Visual Generation, Unified Models, and VLA Models.

this RL-driven innovation wave. Works like ImageReward (Xu et al., 2023) have introduced reinforcement learning to enhance the semantic alignment and visual quality of generative outputs, refining diffusion-based generation through iterative feedback mechanisms derived from human preferences or automated reward critics. Moreover, unified models that blend multiple tasks, *i.e.*, understanding, and generation, into single architectures (Mao et al., 2025; Jiang et al., 2025b) have increasingly relied on RL-driven fine-tuning, achieving generalization and task transfer previously considered challenging. Despite the substantial progress in integrating reinforcement learning with multimodal large language models, several core challenges remain. These include stabilizing policy optimization under complex reward signals, managing high-dimensional and diverse visual inputs, and designing scalable reward functions that support long-horizon decision-making. Addressing these challenges necessitates methodological innovations in both algorithmic design and evaluation protocols.

In this survey, we present a comprehensive synthesis of recent advances in visual reinforcement learning within the context of multimodal large models, with a focus on the surge of research activity since 2024. We begin by revisiting foundational RL successes in language models, such as RLHF (Ouyang et al., 2022) and DeepSeek-R1 (Guo et al., 2025a), which have laid the groundwork for multimodal adaptation. Subsequently, we discuss how these strategies have evolved in the visual domain, categorizing over 200 representative works into four key domains: (i) multimodal large language models, (ii) visual generation, (iii) unified RL frameworks, and (iv) vision-language-action agents, as shown in Figure 1. Within each category, we analyze key developments in algorithmic formulations, reward modeling, and benchmarking methodologies. Finally, we identify open challenges and future directions, highlighting the need for more efficient multimodal reasoning, robust long-horizon learning strategies for VLA tasks, and scalable, high-fidelity reward signals tailored to visual generation. Through this comprehensive overview, we offer a structured overview of visual reinforcement learning to support future research and practical deployment in this rapidly evolving field.

Our key contributions are as follows:

Table 1: **Glossary of Symbols for Visual Reinforcement Learning.** It consolidates the notation that recurs across Sections §2.1–§2.3, with the rightmost column pointing to each appearance of the symbol.

Symbol	Alias	Meaning	Appears in
p	prompt	User prompt (initial state)	§2.1, §2.2.1, §2.3.1, §2.3.2
a_t	action	Token / pixel patch / diffusion noise at step t	§2.1, Eq. (8), §2.3.2
y	traj	Full continuation (a_1, \dots, a_T)	§2.1, §2.2.1, §2.2.3
y_i	continuation	i -th continuation in a GRPO group	§2.1, §2.3.2
s_t	state	Prompt plus previously generated actions	§2.1, §2.3.1, §2.3.2
π_θ	policy	Trainable model (current parameters)	§2.1, §2.2.1, §2.2.2, §2.3.1, §2.3.2
$\pi_{\theta_{\text{old}}}$	behaviour policy	Frozen policy that produced current batch	Eq. (10), §2.3.2
π_{SFT}	SFT baseline	Supervised-fine-tuned checkpoint	§2.2.1, §2.3.1
π_{ref}	reference	Policy used in KL regulariser	§2.1, §2.3.1, §2.3.2
ρ_t	ratio	Importance weight $\pi_\theta / \pi_{\theta_{\text{old}}}$	Eq. (10), §2.3.2
V_ψ	critic	Value network predicting future return	§2.3.1
\hat{A}_t	advantage	GAE advantage (token-level)	Eq. (9), §2.3.1
$\hat{A}_{i,t}$	group adv.	Group-normalised advantage (GRPO)	Eq. (12), §2.3.2
$O = \{a_t\}_1^G$	group	Set of G continuations for one prompt at t timestep	§2.1, §2.3.2
G	group size	Number of continuations per prompt	§2.1, §2.3.2
$r_\phi(s_t, a_t)$	token reward	Immediate reward from frozen preference model	§2.3.1
r_i	token reward	Reward of the i -th continuation in group	§2.3.2
$\text{mean}(\cdot)$	mean	Group reward mean in GRPO	§2.3.2
$\text{std}(\cdot)$	std	Group reward standard deviation in GRPO	§2.3.2
$R_\phi(p, y)$	RM	Sequence-level reward model (RLHF)	§2.2.1
ϵ	clip	PPO clipping threshold	Eq. (10), §2.3.2
β	KL weight	Weight balancing KL vs. reward	Eq. (8), §2.2.1, §2.3.2
$\text{KL}(\ \cdot\)$	KL	Divergence between policy and reference	§2.2.1, §2.3.1, §2.3.2
$D_{\text{KL}}(p)$	est. KL	Token-average KL estimator in GRPO	Eq. (13)

- We provide a systematic and up-to-date survey of over 200 visual reinforcement learning studies, encompassing MLLMs, visual generation, unified models, and vision-language-action agents.
- We analyze advances in policy optimization, reward modeling, and benchmarking across subfields, revealing key challenges and future directions: such as reward design in visual generation and the lack of intermediate supervision in reasoning and VLA tasks.
- We introduce a principled taxonomy of Visual RL methods based on metric granularity and reward supervision, including three reward paradigms for image generation. This framework clarifies the design trade-offs across domains and offers actionable insights for selecting and developing RL strategies.

2 Preliminary: Reinforcement Learning in LLM

This section lays the foundation for the RL of multi-modal models. We first formalize the notation (§2.1), casting text and image generation as a Markov Decision Process. Next, we examine three alignment paradigms (§2.2): *RL from Human Feedback* (RLHF), *Group-Relative Policy Optimization* (GRPO), and *Reinforcement Learning with Verifiable Rewards* (RLVR), each aligning policies via human preferences or deterministic checks. Finally, §2.3 reviews the core policy gradient methods (PPO, GRPO) and their adaptations to visual reasoning and generation.

2.1 Notation and Problem Formulation

We cast text- or image-generation as an episodic Markov decision process. We treat the user *prompt* p as the **initial state** $s_0 = p$. At timestep t , the state is the prompt plus all previously generated actions:

$$s_t = (p, a_1, \dots, a_{t-1}). \quad (1)$$

A *continuation* is the full action sequence $\{a_1, \dots, a_T\}$, where each token $a_t \in \mathcal{A}$ is sampled autoregressively from the policy:

$$\pi_\theta(a_t | s_t) = \pi_\theta(a_t | p, a_1, \dots, a_{t-1}). \quad (2)$$




Figure 2: **Three Alignment Paradigms for Reinforcement Learning.** (a) RLHF learns a reward model from human preference data and optimizes the policy via PPO. (b) DPO removes the reward model and directly optimizes a contrastive objective against a frozen reference. (c) RLVR replaces subjective preferences with deterministic verifiable signals and trains the policy using GRPO.

In words, the prompt anchors the state sequence, and each new action is chosen in the context of that prompt and the tokens already produced.

A fixed reference model (*e.g.*, the supervised fine-tuned checkpoint) is denoted π_{ref} . Human preferences are distilled into a scalar reward model $R_\phi(p, y)$, replacing the reward from the unknown environment. We write $\rho_t(\theta) = \pi_\theta(a_t | s_t) / \pi_{\theta_{\text{old}}}(a_t | s_t)$ for the importance ratio between new and behavior policies. \hat{A}_t is used to denote the advantage estimate. PPO reduces the variance of \hat{A}_t with a learned critic \hat{V}_ψ , whereas GRPO replaces the critic by a *group-relative* baseline computed from a set $O = \{a_i\}_{i=1}^G$ of continuations that share the same prompt. All two algorithms add a KL regulariser $\text{KL}(\pi_\theta(\cdot | p) \| \pi_{\text{ref}}(\cdot | p))$ weighted by β to keep the updated policy close to the reference. Unless stated otherwise, expectations $\mathbb{E}[\cdot]$ are over prompts $p \sim \mathcal{D}$ and continuations drawn from the specified policy.

2.2 Alignment Paradigms

2.2.1 RL from Human Feedback

RLHF (Ouyang et al., 2022) extends the underlying MDP with *pairwise preference data* curated from human annotators. Each preference example is a triple (p, y_A, y_B) , where p is the prompt (or state sequence) and (y_A, y_B) are two candidate continuations (trajectories, images, *etc.*); the label $y \in \{0, 1\}$ records which continuation is preferred, as shown in Figure 2.

Reward-model learning. A scalar reward model R_ϕ is trained to reproduce the pairwise ordering via a Bradley–Terry likelihood:

$$\mathcal{L}_{\text{RM}} = - \sum_{(p, y_A, y_B)} \left[y \log \sigma(R_\phi(p, y_A) - R_\phi(p, y_B)) + (1 - y) \log \sigma(R_\phi(p, y_B) - R_\phi(p, y_A)) \right], \quad (3)$$

where $\sigma(\cdot)$ is the logistic function. After convergence, R_ϕ provides a *dense, differentiable* proxy for human preference.

Policy optimization. The policy π_θ is finally fine-tuned by maximizing (i) the learned reward, (ii) a KL penalty that keeps the policy close to the supervised-fine-tuned baseline π_{SFT} , and (iii) an *optional* log-likelihood regulariser on the original pre-training distribution, as introduced in InstructGPT (Ouyang et al., 2022)¹:

$$\max_{\theta} \underbrace{\mathbb{E}_{(p,y) \sim \pi_\theta} [R_\phi(p,y)]}_{\text{reward}} - \beta \underbrace{\mathbb{E}_p [\text{KL}(\pi_\theta(\cdot|p) \parallel \pi_{\text{SFT}}(\cdot|p))]}_{\text{SFT anchoring}} + \gamma \underbrace{\mathbb{E}_{x \sim D_{\text{pretrain}}} [\log \pi_\theta(x)]}_{\text{pre-training log-likelihood}}. \quad (4)$$

In practice, the first two terms are optimised with KL-regularised PPO over minibatches of sampled continuations, while the third term adds the pre-training gradients (“PPO-ptx” in (Ouyang et al., 2022)) to mitigate performance regressions on the original corpus.

Three-stage recipe. Most modern RLHF pipelines follow the three-stage recipe, as shown in Figure 2 (a). Step 1: Collect demonstration data, and train a supervised policy; Step 2: Collect comparison data, and train a reward model; Step 3: Optimize a policy π_θ against the reward model using PPO. The paradigm was *pioneered* by Christiano et al., (Christiano et al., 2017), who trained Atari and robotic agents from pairwise human preferences. Ouyang et al., (Ouyang et al., 2022) later *scaled* the recipe to large language models (InstructGPT) by coupling preference modeling with PPO. For vision, reward models such as ImageReward (Xu et al., 2023) and Human Preference Score (HPS) (Wu et al., 2023b) supply dense aesthetic signals that guide text-to-image diffusion and related tasks.

2.2.2 Direct Preference Optimization

Direct Preference Optimisation (DPO) (Rafailov et al., 2023) takes exactly the *same* pairwise-preference data as RLHF but removes the intermediate reward-model and RL loop. Instead, it derives a *closed-form*, *supervised* objective that implicitly enforces a KL constraint to a frozen reference policy π_{ref} , as shown in Figure 2 (b).

Closed-form objective. For every prompt p annotators rank two continuations (y_A, y_B) and order them so that y_A is the preferred continuation (“winner”) and y_B the non-preferred one (“loser”). Thus the dataset consists of triples $(p, y_A, y_B) \sim \mathcal{D}$. Let π_{ref} be a frozen reference policy (e.g., the SFT checkpoint) and let $\beta > 0$ be a temperature hyper-parameter. DPO minimizes:

$$\mathcal{L}_{\text{DPO}} = -\mathbb{E}_{(p,y_A,y_B) \sim \mathcal{D}} \left[\log \sigma(\beta \Delta_\theta(p, y_A, y_B)) \right], \quad (5)$$

where the log-odds gap is:

$$\begin{aligned} \Delta_\theta(p, y_A, y_B) &= \log \frac{\pi_\theta(y_A | p)}{\pi_{\text{ref}}(y_A | p)} - \log \frac{\pi_\theta(y_B | p)}{\pi_{\text{ref}}(y_B | p)} \\ &= [\log \pi_\theta(y_A | p) - \log \pi_\theta(y_B | p)] - [\log \pi_{\text{ref}}(y_A | p) - \log \pi_{\text{ref}}(y_B | p)]. \end{aligned} \quad (6)$$

The logistic function $\sigma(z) = 1/(1 + e^{-z})$ turns the gap into a binary-classification loss; training proceeds with standard maximum-likelihood gradients, no reward model, value network, or importance sampling is required.

2.2.3 Reinforcement Learning with Verifiable Rewards

Reinforcement Learning with Verifiable Rewards (RLVR) eliminates the subjectivity and data-collection cost of RLHF by replacing pairwise human preferences with *deterministic*, *programmatically checkable* reward signals $v : (p, y) \mapsto \{0, 1, \dots, K\}$. Typical examples include **pass/fail** unit tests for code synthesis, exact-match answers in mathematics, IoU/DICE thresholds for segmentation, or formal output-format validators (e.g., LeetCode compiler). Because the reward is generated *online* by execution or metric evaluation, RLVR removes both (i) the reward-model training stage of RLHF and (ii) the contrastive surrogate loss of DPO,

¹The coefficients β and γ respectively control the strength of the KL penalty and the pre-training log-likelihood term. Setting $\gamma=0$ recovers the standard PPO objective.




Figure 3: **Two Representative Policy Optimization Algorithms for LLM.** PPO (a) uses a learned value model V_ψ for advantage estimation and injects the KL penalty at each token. GRPO (b) removes the value model, computes group-normalized advantages $\hat{A}_{i,t}$ across G continuations, and applies an explicit prompt-level KL penalty.

while still enabling substantial policy improvements beyond supervised learning (Guo et al., 2025a; Shao et al., 2024b; Lambert et al., 2024), as shown in Figure 2 (c).

Verifiable reward. For a prompt (state) p and a sampled continuation y , a verifier returns:

$$r(p, y) = v(p, y) \in \{0, 1\}, \quad (7)$$

e.g., “pass” if the generated program solves all hidden tests. The same idea applies to vision: a generated mask that attains $\text{IoU} \geq 0.9$ with ground truth, or an image whose CLIP similarity exceeds a hard threshold can be awarded $r=1$. Current most RLVR systems (*e.g.*, DeepSeekMath, Deepseek-R1) adopt GRPO (Shao et al., 2024b) (see Equ. 12) and standard KL regularization to train the policy model.

RLVR therefore follows a concise two-stage pipeline. Step 1: Supervised policy pre-training on demonstrations $\{(p, y)\}$, producing the initial π_{SFT} . Step 2: RL fine-tuning with GRPO/PPO against the on-the-fly verifiable reward $v(p, y)$, optionally mixing in a small percentage of teacher-forced SFT updates to stabilise training.

2.3 Policy-Optimization Algorithms

2.3.1 Proximal Policy Optimization

Proximal Policy Optimization (PPO) (Schulman et al., 2017) is a first order trust region method that updates the policy π_θ while *staying close to the previous policy* $\pi_{\theta_{\text{old}}}$ at every step, as shown in Figure 3 (a). In text- or image-generation problems we treat a prompt p as the initial state s_0 and the continuation $\{a_1, \dots, a_T\}$ as the trajectory. Define the importance-sampling ratio $\rho_t(\theta)$ and immediate reward r_ϕ :

- **Importance-sampling ratio**

$$\rho_t(\theta) = \frac{\pi_\theta(a_t | s_t)}{\pi_{\theta_{\text{old}}}(a_t | s_t)},$$

which re-weights the gradient estimate from the behavior policy to the updated policy.

- **Immediate reward** $r_\phi(s_t, a_t)$, provided by a *frozen* reward model r_ϕ that has been pre-trained to approximate human preference.

- **Value baseline** $V_\psi(s_t)$, produced by a *learned* value network V_ψ that regresses the expected discounted return from state s_t .

With the KL-regularised reward between the policy model and reference model, r_t^{PPO} can be defined:

$$r_t^{\text{PPO}} = r_\phi(s_t, a_t) - \beta \log \frac{\pi_\theta(a_t | s_t)}{\pi_{\text{ref}}(a_t | s_t)}, \quad (8)$$

where the KL term (latter item) keeps the updated policy π_θ from drifting too far from the frozen reference π_{ref} . β balances exploration (via KL proximity to the frozen reference model π_{ref}) against exploitation of the reward model. A larger β implies stricter proximity and thus safer but potentially slower learning. Then the generalized advantage estimator (GAE) (Schulman et al., 2015) produces \hat{A}_t :

$$\hat{A}_t = \text{GAE}(r_t^{\text{PPO}}, V_\psi), \quad (9)$$

where GAE computes advantage values by exponentially weighting multi-step reward estimates, providing a smooth trade-off between low-variance learning and high-variance Monte Carlo returns.

The surrogate objective maximized by PPO is then:

$$\mathcal{L}_{\text{PPO}} = \mathbb{E}_t \left[\min \left(\rho_t(\theta) \hat{A}_t, \text{clip}(\rho_t(\theta), 1 - \epsilon, 1 + \epsilon) \hat{A}_t \right) \right], \quad (10)$$

where the hyper-parameter $\epsilon \in (0, 1)$ controls the width of the trust region. Accurate and low-variance \hat{A}_t estimates are therefore critical, they direct each policy update and ultimately determine the stability and sample efficiency of PPO.

2.3.2 Group Relative Policy Optimization

Group Relative Policy Optimisation (GRPO) (Shao et al., 2024b) extends PPO by discarding the learned value (critic) network and replacing it with a *group-relative* baseline computed from multiple outputs sampled for the same prompt. This design markedly reduces memory consumption while aligning the advantage estimator with the comparison-based reward model, as shown in Figure 3 (b).

Group Relative Baseline. For each prompt p , we sample a group of G full continuations $a_1, \dots, a_G \sim \pi_\theta(\cdot | p)$, where each continuation $a_{:,t} = (a_{1,t}, \dots, a_{G,t})$ is a sequence of tokens indexed by timestep t . The frozen reward model $r_\phi(p, a_{i,t})$ then assigns a scalar score to each token $a_{i,t}$ conditioned on the prompt. These sequence level rewards are then normalized across the group to compute a group-relative advantage signal:

$$\hat{A}_{i,t} = \tilde{r}_{i,t} = \frac{r_{i,t} - \text{mean}(\mathbf{r}_{:,t})}{\text{std}(\mathbf{r}_{:,t})}, \quad (11)$$

where $\text{mean}(\cdot)$ and $\text{std}(\cdot)$ denote the mean and standard deviation functions used to compute the group relative advantage. The same \hat{A}_i is reused for every token $a_{i,t}$ in the continuation, producing the clipped surrogate:

$$\begin{aligned} \mathcal{L}_{\text{GRPO}} = \mathbb{E}_{p \sim \mathcal{D}} \left[\frac{1}{G} \sum_{i=1}^G \frac{1}{|a_i|} \sum_{t=1}^{|a_i|} \min(\rho_{i,t} \hat{A}_{i,t}, \text{clip}(\rho_{i,t}, 1 - \epsilon, 1 + \epsilon) \hat{A}_{i,t}) \right] \\ - \beta \mathbb{E}_p \left[D_{\text{KL}}(\pi_\theta(\cdot | p) \parallel \pi_{\text{ref}}(\cdot | p)) \right], \end{aligned} \quad (12)$$

where $\rho_{i,t} = \pi_\theta(a_{i,t} | s_{i,t}) / \pi_{\text{old}}(a_{i,t} | s_{i,t})$. The explicit KL penalty $D_{\text{KL}}(\cdot)$ keeps π_θ near the reference π_{ref} , while the group-relative advantage \hat{A}_i replaces the value baseline V_ψ , roughly halving memory and compute yet retaining a low-variance learning signal.

Prompt-level KL estimator. Instead of injecting a token-wise penalty into the reward (as PPO does with $\beta \log \frac{\pi_\theta}{\pi_{\text{ref}}}$), GRPO adds a *separate* prompt-level regulariser. With the G sampled continuations we form an unbiased token-average estimate:

$$D_{\text{KL}}(p) = \frac{1}{G} \sum_{i=1}^G \frac{1}{|a_i|} \sum_{t=1}^{|a_i|} \log \left(\frac{\pi_\theta(a_{i,t} | s_{i,t})}{\pi_{\text{ref}}(a_{i,t} | s_{i,t})} \right), \quad (13)$$




Figure 4: **Overall taxonomy of reinforcement-learning research in vision.** The chart groups existing work by high-level domain (MLLMs, visual generation, unified models, and vision-language action agents) and then by finer-grained tasks, illustrating representative papers for each branch.

which measures how far the current policy drifts from the frozen reference π_{ref} over the *whole* continuation.

Relative to PPO in Equ. (10), GRPO introduces two key improvements: 1) *Eliminates the value (critic) network.* Variance reduction is achieved by a *group-relative* baseline, leading to lower memory footprint and fewer hyper-parameters. 2) *Separates the KL loss channel.* The KL divergence is optimized as an explicit regulariser rather than folded into the advantage, yielding a transparent trade-off between reward maximization and reference anchoring.

3 Reinforcement Learning in Vision

3.1 Multi-Modal Large Language Models

We categorize the works into four coherent groups, each defined by shared RL-driven objectives and internal reasoning mechanisms.

3.1.1 Conventional RL-based MLLMs

We refer to *conventional RL-based MLLMs* as approaches that apply reinforcement learning primarily to *align* a vision–language backbone with *verifiable, task-level rewards*, without explicitly modeling multi-step chain-of-thought reasoning. Typical works RePIC (Oh et al., 2025), GoalLadder (Zakharov & Whiteson, 2025), Drive-R1 (Li et al., 2025e) and VLM-R1 (Shen et al., 2025b) replace preference models with *deterministic validators* (e.g., exact-match, IoU, BLEU) and optimize the policy by GRPO/PPO variants under a KL regulariser. This design yields stable value-free training, improves zero-shot robustness on captioning, grounding and autonomous-driving benchmarks, and substantially reduces the annotation cost typically incurred by supervised fine-tuning.

Recent extensions demonstrate the flexibility of this paradigm. GRPO-CARE (Chen et al., 2025b) introduces consistency-aware group normalization to mitigate reward variance, while Q-Ponder (Cai et al., 2025c) adds a pondering controller. From a data perspective, MoDoMoDo formulates a multi-domain mixture optimization that predicts reward distributions and selects optimal curricula (Liang et al., 2025); V-Triune further unifies perception and reasoning tasks within a single triple-objective pipeline, empirically validating that rule-based RL scales to diverse visual signals (Ma et al., 2025). Collectively, these studies indicate that (i) verifiable rewards can serve as a low-cost alternative to human feedback, (ii) group-relative objectives offer higher training stability than token-level PPO on heterogeneous visual tasks, and (iii) curriculum or data-mixture scheduling is emerging as a key ingredient for broad generalization.

3.1.2 Spatial and 3D Perception

2D perception. Perception centric works applies RL to sharpen object detection, segmentation and grounding without engaging in lengthy chain-of-thought reasoning. Omni-R1 (Zhong et al., 2025) introduces a two-system (global–local) GRPO pipeline that verifies predictions via rule-based metrics, yielding notable improvements on region-level benchmarks and emotion-recognition tasks. DIP-R1 (Park et al., 2025b) further decomposes perception into step-wise “inspect → observe → act” cycles, where each stage receives deterministic IoU or counting-based rewards to boost fine-grained detection. Perception-R1 (Yu et al., 2025) revisits the effect of GRPO on a spectrum of detection and OCR datasets. Complementing these, VisRL (Chen et al., 2025h) frames intention-guided focus selection as an RL sub-policy, eliminating expensive region labels and consistently outperforming supervised strong baselines on visual grounding tasks.

3D perception. Beyond 2-D, several studies leverage RL to align multimodal models with physically consistent 3-D layouts. MetaSpatial (Pan & Liu, 2025) employs rendered depth/IoU rewards to refine spatial reasoning for AR/VR scene generation, whereas Scene-R1 (Yuan et al., 2025c) couples video-grounded snippet selection with a two-stage grounding policy to learn 3-D scene structure without point-level supervision. At molecular scale, BindGPT (Zholus et al., 2025) treats atom placement as sequential actions and uses binding-affinity estimators as verifiable rewards, demonstrating the scalability of perception-focused RL to 3-D biochemical design. Collectively, these approaches underscore a common recipe: (i) formulate detection/segmentation/3-D alignment as Markov decision problems, (ii) craft deterministic spatial rewards (e.g., IoU, depth consistency, binding energy), and (iii) fine-tune pretrained VLM backbones via GRPO/PPO for stable perception enhancement—thereby differentiating themselves from reasoning-oriented RL variants.

3.1.3 Image Reasoning

Thinking about Images methods enhance multimodal reasoning by *verbalising* observations of a static picture before producing an answer, but the visual content itself is not modified during inference. By contrast, Thinking with Images elevates the picture to an *active, external workspace*: models iteratively *generate, crop, highlight, sketch or insert explicit visual annotations* as tokens in their chain-of-thought, thereby aligning linguistic logic with grounded visual evidence.

Think about Image. Early think about image works for spatial VQA employs view-consistent or transformation-invariant objectives, such as SVQA-R1 (Wang & Ling, 2025) and STAR-R1 (Li et al., 2025g). VL-GenRM (Zhang et al., 2025d) and RACRO (Gou et al., 2025) refine preference data or caption rewards to curb hallucinations. Benchmark-oriented efforts such as EasyARC (Unsal & Akkus, 2025) offer

procedurally generated, fully verifiable tasks that suit outcome-based reinforcement learning. To mitigate shortcut reliance and improve generality, Visionary-R1 (Xia et al., 2025) enforces image interpretation before reasoning, whereas UniVG-R1 (Bai et al., 2025) unifies referring, captioning, and detection by coupling a grounding corpus with GRPO fine-tuning. Extensions such as EchoInk-R1 (Xing et al., 2025) further enrich visual reasoning by integrating audio–visual synchrony under GRPO optimization. Meanwhile, curriculum-driven frameworks—WeThink, G1, GThinker, and Observe-R1 progressively increase task complexity or introduce re-thinking cues (*e.g.*, difficulty ladders, multimodal format constraints) to cultivate deeper and more structured reasoning capabilities in MLLMs. These methods show that language only RL with well-designed visual correctness rewards significantly improves model accuracy, robustness, and out-of-distribution performance.

Think with Image. Early think with image works grounds reasoning via discrete *region-level* operations: GRIT (Fan et al., 2025) interleaves bounding-box tokens with language and trains under GRPO to maximize both answer correctness and box fidelity, while VILASR (Wu et al., 2025a) generalizes this idea to multi-view and video settings, enforcing cross-view spatial consistency. Ground-R1 (Cao et al., 2025) and BRPO (Chu et al., 2025) adopt two-stage pipelines that first highlight evidence regions (via IoU-based or reflection rewards) before verbal reasoning. A complementary thread explores pixel-space or sequence-level manipulation. Visual Planning (Xu et al., 2025b) replaces text chains with imagined image roll-outs rewarded by downstream task success; Pixel Reasoner (Su et al., 2025a) augments the action space with crop, erase and paint primitives and balances exploration through curiosity-driven rewards, whereas DeepEyes (Zheng et al., 2025) shows that end-to-end RL can spontaneously induce such visual thinking behaviours. Finally, TACO (Kan et al., 2025) introduces a think–answer consistency objective that resamples long visual–verbal chains until their intermediate edits align with the final answer. Together, these systems demonstrate that explicitly generating or editing visual artefacts during reasoning optimized via GRPO or R1-style outcome RL—yields more faithful, interpretable and robust image understanding than language only approaches.

3.1.4 Video Reasoning

Video reasoning extends the capabilities of MLLMs to process temporal dynamics, requiring not only spatial perception but also sequential understanding and causal inference. Recent works in this domain have proposed diverse approaches to tackle complex reasoning over video inputs. For instance, VQ-Inspire (Zhang et al., 2025h) introduces a hierarchical reward design and self-consistency voting mechanism tailored to the question–answering process over long videos. TW-GRPO (Dang et al., 2025) combines token wise credit assignment with GRPO-style optimization to improve fine-grained temporal alignment between textual reasoning and video evidence. Meanwhile, several R1-style frameworks have been developed to unlock video understanding in complex real-world or egocentric settings. EgoVLM (Vinod et al., 2025) and VAU-R1 (Zhu et al., 2025b) focus on egocentric video reasoning with visual memory and utility-based rewards. DeepVideo-R (Park et al., 2025a) integrates dense video encodings and external reward functions to supervise long-horizon reasoning. TimeMaster (Zhang et al., 2025e) explicitly structures temporal abstraction and reasoning via curriculum learning, while VideoR1 (Feng et al., 2025) proposes a scalable RL framework for video-based QA tasks across multiple domains. Collectively, these works highlight the importance of aligning temporal representations with language trajectories through reinforcement learning, paving the way for robust and generalizable video reasoning agents.

3.2 Visual Generation

3.2.1 Image Generation

RL for image generation models departs from the language counterpart in both *action space* continuous diffusion steps or prompt refinements and *reward design*, which must capture perceptual quality, text–image alignment, and subject fidelity. A first family learns an explicit *visual reward model*: ImageReward (Xu et al., 2023) supplies human-preference scores that drive policy-gradient fine-tuning of diffusion backbones in DiffPPO (Xiao et al., 2024), Dpok (Fan et al., 2023a), and FocusDiff (Pan et al., 2025). A second line bypasses reward modelling by optimising *pairwise or unary preferences*: DDPO (Black et al., 2023), DiffusionDPO (Wallace et al., 2024), Diffusion-KTO (Li et al., 2024b), and DiffusionRPO (Gu et al., 2024)




Figure 5: **Three reward paradigms for RL-based image generation.** (a) Human-Centric Preference Optimization: aligns outputs with human aesthetic scores (HPS (Wu et al., 2023b), ImageReward (Xu et al., 2023)); (b) Multimodal Reasoning-Based Evaluation: scores images via multimodal reasoning consistency (UnifiedReward (Wang et al., 2025j), PARM (Guo et al., 2025d)); (c) Metric-Driven Objective Optimization: minimizes task-specific quantitative metrics such as FID and IoU.

treat denoising trajectories as MDPs and apply R1/GRPO updates to maximise comparative human feedback. Beyond alignment, works such as PrefPaint (Liu et al., 2024a), Parrot (Lee et al., 2024), and RLRf (Rodriguez et al., 2025b) craft multi-objective or render-and-compare rewards to refine aesthetics, diversity, or vector graphics. RL has also been used to inject *reasoning and prompt adaptation*: ReasonGen-R1 (Zhang et al., 2025i), GoT-R1 (Duan et al., 2025) and RePrompt (Wu et al., 2025b) first generate textual plans or improved prompts, then reinforce the generator for coherent scene synthesis. Finally, personalisation methods—DPG-T2I (Wei et al., 2024), RPO (Miao et al., 2024a), and B²-DiffuRL (Hu et al., 2025a) optimize rewards that measure subject fidelity under scarce reference images. Collectively, these studies show that RL, armed with perceptual or preference-based rewards, can steer diffusion models toward higher realism, stronger prompt faithfulness, controllable layout, and user-specific appearance capabilities difficult to achieve with likelihood training alone.

3.2.2 Video Generation

Applying RL to video generation introduces challenges absent in images: rewards must capture *temporal coherence*, *motion naturalness*, and *text-video alignment* across hundreds of frames. Early work such as InstructVideo (Yuan et al., 2024) repurposed image scorers and applied PPO to refine short clips, whereas VideoRM (Wu et al., 2024) and VideoReward (Liu et al., 2025b) learn dedicated preference models that grade entire sequences for smoothness, consistency and prompt faithfulness. Building on GRPO/R1, DanceGRPO (Xue et al., 2025) shows that group-normalized returns stabilize long-horizon optimization and boost aesthetic and alignment scores across diffusion and flow backbones.

Beyond preference alignment, specialized rewards tackle domain-specific goals. GAPO (Zhu et al., 2025a) exploits gap-aware ranking to fine-tune anime videos; Phys-AR (Lin et al., 2025) penalizes violations of physics to yield plausible trajectories; and InfLVG (Fang et al., 2025) trains an inference-time policy that retains only context tokens beneficial for multi-scene coherence. Auxiliary critics further facilitate training: VideoScore (He et al., 2024b) and Gradeo (Mou et al., 2025) offer explainable, multi-factor scores, while TeViR (Chen et al., 2025d) feeds imagined video roll-outs as dense rewards to downstream control agents. Collectively, these studies demonstrate that carefully crafted sequence level rewards and group-relative policy updates are key to producing temporally consistent, semantically aligned, and physically plausible videos capabilities difficult to obtain with likelihood training alone.

3.2.3 3D Generation

RL for 3D generation differs from 2D and video tasks as rewards operate on *volumetric structures* or *rendered views*, often requiring expensive render-and-compare loops. DreamCS (Zou et al., 2025) pioneers this paradigm by framing text-to-mesh synthesis as a Markov decision process: a diffusion backbone proposes coarse shapes, then a policy refines vertex positions under a reward that jointly measures silhouette IoU, CLIP text-mesh alignment, and mesh smoothness. On the reward side, DreamReward (Ye et al., 2024) introduces a large-scale human preference dataset of rendered 3-D assets and trains a geometry-aware critic that scores prompts, renders, and latent SDFs; the learned signal enables stable PPO fine-tuning of existing text-to-shape models.

A complementary line adopts direct preference optimization. DreamDPO (Zhou et al., 2025c) extends DPO to NeRF and mesh diffusion models by sampling paired 3D outputs and maximizing the margin dictated by human comparisons, achieving superior prompt fidelity without an explicit value network. Finally, Nabla-R2D3 (Liu et al., 2025d) tackles *interactive scene editing*: the agent sequentially adds, deletes, or transforms objects in a 3D scene; reward is computed via real-time rasterized views and task-specific validators (*e.g.*, occupancy, spatial relations). Group-relative policy optimization (R2D3) stabilizes training despite sparse feedback. Together, these studies demonstrate that RL, equipped with geometry-aware or render-based rewards, provides an effective mechanism for controlling structural integrity, text alignment, and interactive editability capabilities that standard likelihood or score-distillation objectives struggle to capture in the 3D domain.

3.3 Unified Model

Task specific RL maximizes a reward tied to a *single* objective, whereas *Unified RL* optimizes a *shared* policy and reward across multiple vision-language tasks (*e.g.*, understanding and generation).

3.3.1 Unified RL

Unlike task specific pipelines that attach RL to a single downstream objective, *Unified RL* methods optimize a **shared policy** across heterogeneous multimodal tasks under a *single* reinforcement signal. The central idea is to merge understanding and generation trajectories into one training loop typically using Group-Relative or R1-style methods.

UniRL (Mao et al., 2025) exemplifies this paradigm: a visual autoregressive backbone is first instruction-tuned, then jointly fine-tuned on VQA, captioning and image generation with a blended reward measuring textual correctness, CLIP-based alignment, and aesthetic quality. CoRL (Jiang et al., 2025b) pushes the idea further by alternating “co-understanding” and “co-generation” batches within the same GRPO step. To address inefficiency in dense token spaces, SelfTok (Wang et al., 2025a) discretises multi-modal actions into a self-evolving token set and demonstrates that a single RL head can govern retrieval, grounding, and synthesis with minimal extra parameters. Finally, HermesFlow (Yang et al., 2025c) couples an autoregressive text module with a rectified flow image decoder under one cross-task reward, illustrating that diffusion-style and language-style policies can be harmonized through unified reinforcement updates. Together, these works suggest that sharing a common RL objective across tasks not only reduces training cost but also encourages emergent cross modal generalization unavailable to isolated, task specific fine-tuning.

3.3.2 Task specific RL

In contrast to the unified approaches of §3.3.1, task-specific RL confines the reward signal to a single downstream objective, optimizing one functional head while leaving other capabilities untouched. VARGPT-v1.1 (Zhuang et al., 2025) exemplifies this strategy: although the underlying visual autoregressive model can handle both understanding and generation, its RL stage targets *only* visual generation with DPO. Similarly, Emu3 (Wang et al., 2024b) introduces RL exclusively to polish its image generation branch, which leveraging pair wise human preferences. For the multimodal understanding abilities of model (*e.g.*, captioning, VQA), the work just train this part by task specific fine-tuning alone.

3.4 Vision Language Action Models

3.4.1 GUI Automation

Modern GUI RL research frames screen understanding and action prediction as a vision–language decision process, then employs rule-based or preference rewards to close the perception–action loop. On desktop and web interfaces, GUI-R1 (Luo et al., 2025) introduces an R1-style rule set that maps click success, text entry, and scroll validity to dense rewards. UI-R1 (Lu et al., 2025) adds GRPO with a novel action-specific KL term to stabilize long-horizon plans, while SE-GUI (Yuan et al., 2025b) applies self-evolutionary filtering to distil high-fidelity trajectories. Focusing on trajectory reuse, UIShift (Gao et al., 2025b) formulates an inverse dynamics objective that lets MLLM learn actions from unlabeled GUI pairs and then refines them via RL. Complementary preference-based frameworks include LPO (Tang et al., 2025) that rewards spatial proximity for precise clicks. ProgRM (Zhang et al., 2025b) injects program-level logical checks, and RUIG (Zhang et al., 2023) leverages instruction grounding with reinforcement signals. Tool-specific baselines such as Ui-tars (Qin et al., 2025) offer larger action vocabularies yet still rely on rule-driven RL for robust execution.

Mobile scenarios introduce latency and on-device constraints. AgentCPM-GUI (Zhang et al., 2025j) compresses the action space and conducts GRPO fine-tuning. MobileGUI-RL (Shi et al., 2025) advances this line via online RL with task-level rewards to improve exploration under limited memory, and Mobile-R1 (Gu et al., 2025) extends interactive multi-turn RL to correct error cascades during long tasks. At inference, GTA1 (Yang et al., 2025e) samples multiple action candidates and employs a judge model to pick the best, effectively trading compute for higher success rates. Additional, light-weight models such as Appvlm (Papoudakis et al., 2025) demonstrate that modest-sized MLLM, after GRPO fine-tuning, can control smartphone apps with competitive precision. To adaptively reduce the thinking length, the TON (Wang et al., 2025b) proposes a thought-dropout solution during supervised fine-tuning stage, then GRPO skill adaptively skip unnecessary reasoning process for efficiently thinking.

Collectively, these studies show that GUI agents benefit from rule-verifiable rewards, group-normalized policy updates, and preference-guided localization, achieving rapid progress toward reliable, cross-platform automation.

3.4.2 Visual Navigation

RL-driven visual navigation research now couples large vision–language models with embodied control, employing group-normalized or time-decayed returns to maintain long-horizon stability. OctoNav-R1 (Gao et al., 2025a) exploits a hybrid RL pipeline with a “think-before-action” ability for VLA model, then translate egocentric frames into low-level actions. Focusing on dataset efficiency, VLN-R1 (Qi et al., 2025) builds an end-to-end navigator and introduces a time-decayed reward to handle continuous trajectories. At the system level, Flare (Hu et al., 2024a) demonstrates that fine-tuning a multi-task robotics policy with large-scale RL in simulation can generalize to real-world household tasks. Complementary advances include More (Zhao et al., 2025), which augments omni-directional inputs with memory-guided policy distillation, and RAPID (Kim et al., 2025), which integrates pose priors for faster convergence in unseen layouts. These works show that using temporal rewards, memory sampling, and environment priors with GRPO/PPO helps VLA agents navigate more reliably and efficiently.

3.4.3 Visual Manipulation

Visual manipulation tasks (*e.g.*, object relocation, tool use, and multi-step rearrangement) require fine-grained perception and long-horizon planning. Recent works (Chen et al., 2025g; Shu et al., 2025) integrate reinforcement learning with vision–language models to enhance generalization, interactivity, and policy consistency. TGRPO (Chen et al., 2025g) introduces a task-grounded reward formulation and group normalized updates to stabilize training for open-ended object manipulation. RFTF (Shu et al., 2025) applies rule-based rewards to support interactive table top tasks and emphasizes training with minimal human supervision. Meanwhile, RLVLA (Liu et al., 2025c) and VLA-RL (Lu et al., 2025b) explore curriculum-based or progressive reinforcement learning for VLM-based robot agents, achieving high success rates across diverse rearrangement environments.




Figure 6: **Metric Granularity in Visual RL.** (a) Set-level metric \mathcal{M}_{set} : one score over the whole prompt set, used for final evaluation (*e.g.*, FID). (b) Sample-level metric $\mathcal{M}_{\text{samp}}$: per-output rewards that train the policy (RLHF, DPO). (c) State-level metric $\mathcal{M}_{\text{state}}^t$: training-time signals like KL or length drift, used to monitor stability. Notation: p_i , y_{gen}^i , y_{gt}^i denote the prompt, the generated output, and ground truth, respectively. π_{θ_0} and π_{θ_t} refer to the 0-th and t -th policy model. $R_{\phi}(\cdot)$ denotes the reward model.

Building on this, ConRFT (Chen et al., 2025e) and iRe-VLA (Guo et al., 2025b) introduce consistency-aware and instruction-refinement strategies respectively, using RL to align visual predictions with physical interaction outcomes. RIPT-VLA focuses on interactive prompting during manipulation, bridging LLM planning and low-level control through reinforced feedback (Tan et al., 2025b). Finally, ReinBot (Zhang et al., 2025c) leverages multimodal rollouts and preference-based updates to improve real-world manipulation robustness (Zhang et al., 2025c). Collectively, these studies highlight the role of vision-language reasoning, structured reward design, and RL-based refinement in advancing embodied manipulation under complex, language-conditioned settings.

4 Metrics and Benchmarks

Evaluating visual reinforcement learning (RL) with large models requires both traditional RL metrics (Jordan et al., 2020; Agarwal et al., 2021) and new ones designed for complex, open-ended outputs. Metrics like cumulative return and task success rate are still useful especially in tasks involving agents and environments but they are increasingly combined with preference-based evaluations. In this section, we discuss metrics and benchmarks across four major application areas of large-model RL.

4.1 Formalizing Metric Granularity

Let $\mathcal{P}_{\text{test}} = \{p_1, \dots, p_D\}$ denote a fixed set of *prompts* (inputs) and let a generative policy $\pi_{\theta}(y | p)$ produce an *output* y (text, image, video, *etc.*) conditioned on each prompt $p \in \mathcal{P}_{\text{test}}$. As shown in Figure 6, we distinguish three granularities of evaluation:

Task Metric \mathcal{M}_{set} (Set-level). As illustrated in Fig. 6 (a), set-level metrics evaluate the generative policy π_{θ} over the full prompt set $\mathcal{P}_{\text{test}}$, by comparing the distribution of generated outputs $\mathcal{Y}_{\text{gen}} = \{\pi_{\theta}(\cdot | p_i)\}_{i=1}^D$ to a reference set of ground-truth outputs $\mathcal{Y}_{\text{gt}} = \{y_{\text{gt}}^i\}_{i=1}^D$. When the evaluation function operates *without*

Table 2: **Overview of evaluation metrics in large-model visual RL.** Each task family is broken down into Task Metrics (RL-free external benchmarks), Reward Metrics (how the learning signal is computed), and Model-state Metrics (diagnostics tracked during optimization).

Task Family	Task Metric \mathcal{M}_{set} (RL-free benchmarks / scores)	Reward / Advantage Estimation $\mathcal{M}_{\text{samp}}$ (scoring & preference signals)	Model-state Metric $\mathcal{M}_{\text{state}}^t$ (training diagnostics)
Multimodal LLMs/ VLMs	<ul style="list-style-type: none"> • Comprehensive Evaluation: <i>e.g.</i>, MME (Fu et al., 2023), SEED-Bench (Li et al., 2024a), VQA v2 (Goyal et al., 2017), MMBench (Liu et al., 2024b). • OCR: <i>e.g.</i>, TextVQA (Singh et al., 2019), OCR-VQA (Mishra et al., 2019), OCRBench (Liu et al., 2023b). • Mathematical: <i>e.g.</i>, MathVista (Lu et al., 2023). • Documentation: <i>e.g.</i>, ChartQA (Lu et al., 2023), DocVQA (Mathew et al., 2021), InfoVQA (Mathew et al., 2022). • Multilingual: <i>e.g.</i>, CMMU (Zhang et al., 2024a), CMMU (He et al., 2024c). 	<ul style="list-style-type: none"> • Reward from Human Preference: <i>e.g.</i>, InstructGPT (Ouyang et al., 2022), LLaVA-RLHF (Sun et al., 2023). • Verifiable Rewards: <i>e.g.</i>, Deepseekmath (Shao et al., 2024b), IoU (Rezatofighi et al., 2019), CodeRL (Le et al., 2022). • Reward from Model Preference: <i>e.g.</i>, CriticGPT (McAleese et al., 2024). 	<ul style="list-style-type: none"> • Output length monitoring: <i>e.g.</i>, DPO (Rafailov et al., 2023). • KL-divergence: <i>e.g.</i>, InstructGPT (Ouyang et al., 2022).
Visual Generation (Image / Video / 3D)	<ul style="list-style-type: none"> • Image Fidelity & Diversity: <i>e.g.</i>, FID (Heusel et al., 2017), Inception Score (IS) (Salimans et al., 2016). • Pixel-level Reconstruction: <i>e.g.</i>, PSNR (Wang et al., 2004), SSIM (Wang et al., 2004). • Semantic Alignment: <i>e.g.</i>, Geneval (Ghosh et al., 2023), T2I-CompBench (Huang et al., 2023), CLIP Score (Radford et al., 2021), Frechet CLIP Distance (Betzalel et al., 2022). • Video Fidelity & Diversity: <i>e.g.</i>, FVD (Unterthiner et al., 2019), Video IS (Saito et al., 2020). 	<ul style="list-style-type: none"> • Reward from Human Preference: <i>e.g.</i>, ImageReward (Xu et al., 2023), HPS (Wu et al., 2023b), HPS V2 (Wu et al., 2023b), Pick-a-pic (Kirstain et al., 2023), VideoReward (Liu et al., 2025b), RichHF-18K (Liang et al., 2024). • Verifiable Rewards: <i>e.g.</i>, MotionPrompt (Nam et al., 2025), DSPO (Cai et al., 2025b), Instructrl4pix (Li et al., 2024c). • Reward from Model Preference: <i>e.g.</i>, VideoPrefer (Wu et al., 2024), PARM (Zhang et al., 2025f). 	<ul style="list-style-type: none"> • Denoising Trajectory Diagnostics: <i>e.g.</i>, VARD (Dai et al., 2025), Inversion-DPO (Li et al., 2025f). • KL-divergence: <i>e.g.</i>, DDPO (Black et al., 2023), VARD (Dai et al., 2025).
Unified Models	<ul style="list-style-type: none"> • Generation-oriented Task Metrics: <i>e.g.</i>, GenEval (Ghosh et al., 2023), DPG-Bench (Hu et al., 2024b), ParaPrompts (Wu et al., 2025d). • Understanding-oriented Task Metrics: <i>e.g.</i>, MME (Fu et al., 2023), POPE (Li et al., 2023). 	<ul style="list-style-type: none"> • Unified Rewards: <i>e.g.</i>, UniRL (Mao et al., 2025), CoRL (Jiang et al., 2025b). • Task-specific Rewards: <i>e.g.</i>, Vargpt-v1.1 (Zhuang et al., 2025), Emu3 (Wang et al., 2024b). 	<ul style="list-style-type: none"> • Generation-Understanding Imbalance: <i>e.g.</i>, UniRL (Mao et al., 2025). • KL-divergence: <i>e.g.</i>, HermesFlow (Yang et al., 2025c).
Vision-Language Action Agents (GUI / Navigation / Manip.)	<ul style="list-style-type: none"> • GUI Action Accuracy (offline): <i>e.g.</i>, ScreenSpot (Cheng et al., 2024), ScreenSpot-Pro (Li et al., 2025c), Ui-vision (Nayak et al., 2025). • Task Success rate (online): <i>e.g.</i>, Webarena (Zhou et al., 2023), Osworld (Xie et al., 2024), Windows agent arena (Bonatti et al., 2024). • Model-based Evaluation: <i>e.g.</i>, Agentrewardbench (Lü et al., 2025), Webworld (Chae et al., 2024), Digirl (Bai et al., 2024). • Reward from Human Preference: <i>e.g.</i>, RFTF (Shu et al., 2025). 	<ul style="list-style-type: none"> • Rule-based Success (binary) (IoU, Action Accuracy): <i>e.g.</i>, UI-R1 (Lu et al., 2025), ARPO (Lu et al., 2025a), VLA-RL (Lu et al., 2025b), iRe-VLA (Guo et al., 2025b). • Model Preference Critic: <i>e.g.</i>, ProgRM (Zhang et al., 2025b). • Dense Shaping (distance or coverage): <i>e.g.</i>, LPO (Tang et al., 2025), Gui-r1 (Luo et al., 2025). 	<ul style="list-style-type: none"> • Action trajectory length: <i>e.g.</i>, Osworld (Xie et al., 2024). • KL penalty for policy stability: <i>e.g.</i>, GUI-R1 (Luo et al., 2025), UI-R1 (Lu et al., 2025). • Output length monitoring: <i>e.g.</i>, UI-R1 (Lu et al., 2025).

access to ground-truth outputs such as CLIPScore (Hessel et al., 2021), we define:

$$\mathcal{M}_{\text{set}} = \frac{1}{D} \sum_{i=1}^D \mathbb{E}_{y \sim \pi_{\theta}(\cdot | p_i)} [\mathcal{M}_{\text{samp}}(y_{\text{gen}}^i, p_i)], \quad (14)$$

where $\mathcal{M}_{\text{samp}}(y, p)$ denotes a sample-level reward function applied to each generated output. By contrast, many classical vision metrics do rely on reference outputs such as IoU (Rezatofighi et al., 2019). For these cases, set-level evaluation is defined as:

$$\mathcal{M}_{\text{set}} = \frac{1}{D} \sum_{i=1}^D \mathbb{E}_{y \sim \pi_{\theta}(\cdot | p_i)} [\mathcal{M}_{\text{samp}}(y_{\text{gen}}^i, y_{\text{gt}}^i, p_i)], \quad (15)$$

where each ground-truth output y_{gt}^i denotes i -th ground truth from the reference set.

Reward/Advantage metric $\mathcal{M}_{\text{samp}}$ (Sample-level). As illustrated in Fig. 6 (b), reward and advantage metrics $\mathcal{M}_{\text{samp}}$ operate at the granularity of individual input-output pairs, forming the backbone of reinforcement learning in generative settings. Given a prompt p_i , the policy π_{θ} generates a sample y_{gen}^i , which is then scored by $\mathcal{M}_{\text{samp}}(y_{\text{gen}}^i, p_i)$ to compute a scalar reward or advantage signal. This feedback is used to optimize the policy via reinforcement learning (e.g., PPO (Schulman et al., 2017), DPO (Rafailov et al., 2023)). In preference-based learning, the sample-level metric is often learned from human or GPT-4 comparisons (Ouyang et al., 2022; Sun et al., 2023), or automatically derived via scoring models like CLIPScore (Hessel et al., 2021), or ImageReward (Xu et al., 2023). When rewards are reference-dependent (e.g., using PSNR (Wang et al., 2004) or IoU (Rezatofighi et al., 2019)), $\mathcal{M}_{\text{samp}}$ compares the generated output y_{gen}^i to a ground-truth output y_{gt}^i . Formally, the reward signal can be expressed as:

$$\mathcal{M}_{\text{samp}}(y_{\text{gen}}^i, p_i) = R_{\phi}(y_{\text{gen}}^i, p_i) \quad \text{or} \quad R_{\phi}(y_{\text{gen}}^i, y_{\text{gt}}^i, p_i), \quad (16)$$

depending on whether the reward model R_{ϕ} operates with or without access to ground-truth outputs. In practice, the per-sample scores are transformed into step-wise advantages $\hat{A}_{i,t}$ (where t indexes generation steps). These advantages directly drive policy updates, enabling reward shaping and exploration control at the level of individual outputs.

State-level Metric $\mathcal{M}_{\text{state}}^t$. As depicted in Fig. 6 (c), state-level metrics monitor the *training dynamics* of the current policy π_{θ_t} at iteration t . A common choice is the KL divergence to a frozen reference policy π_{θ_0} :

$$\mathcal{M}_{\text{state}}^t = \mathbb{E}_{p \sim \mathcal{P}_{\text{val}}} D(\pi_{\theta_t}(\cdot | p) \| \pi_{\theta_0}(\cdot | p)). \quad (17)$$

Other diagnostics include *output-length drift* for autoregressive models and *DDIM step-trace variance* for diffusion models. By tracking $\mathcal{M}_{\text{state}}^t$ during optimisation, practitioners detect reward hacking, mode collapse, or excessive policy shift before these issues degrade final performance.

4.2 Evaluation of Multi-Modal Large Language Models

Task Metric. As summarized in Table 2, MLLM are first judged on *external, RL-free benchmarks*. General reasoning suites such as MME (Fu et al., 2023), SEED-BENCH (Li et al., 2024a) and MMBENCH (Liu et al., 2024b) measure factual QA, commonsense and multi-step chain-of-thought across images. Domain-specific subsets probe OCR (TextVQA (Singh et al., 2019)), mathematics (MathVista (Lu et al., 2023)), documents (ChartQA (Lu et al., 2023)) and multilingual grounding (CMMU (Zhang et al., 2024a)).

Reward Metric. During training, each generated answer is scored with a sample-level reward $\mathcal{M}_{\text{samp}}$. Three sources dominate current practice. (i) *Human-preference rewards* are learned from large RLHF corpora e.g., InstructGPT (Ouyang et al., 2022) and LLaVA-RLHF (Sun et al., 2023), and give dense feedback that closely matches user judgements. (ii) *Verifiable rewards* arise when a sub-task admits deterministic checks, such as unit-test pass rate in CodeRL (Le et al., 2022) or symbolic exactness in DeepSeekMath (Shao et al., 2024b); they are noise-free but limited in scope. (iii) *Model-preference rewards* replace humans with a stronger frozen critic, e.g., CriticGPT (McAleese et al., 2024), delivering scalable but potentially biased supervision. The chosen reward is converted to advantages $\hat{A}_{i,t}$ and optimized via PPO, GRPO or DPO.

Model-State Metric. Beyond external scores, practitioners track light-weight diagnostics $\mathcal{M}_{\text{state}}^t$ throughout RL updates. Two lightweight diagnostics are widely adopted: (i) *Output length drift*, the deviation of answer length from the SFT baseline large drift foreshadows verbosity or repetition (Rafailov et al., 2023); (ii) *KL divergence* between the current policy π_{θ_t} and frozen SFT reference π_{θ_0} , as used in InstructGPT (Ouyang et al., 2022).

4.3 Evaluation of Visual Generation Models

Task Metric. As listed in Table 2, final quality is judged on standard, RL-free benchmarks that target complementary axes. Image fidelity & diversity is measured by FID and Inception Score, while pixel-level reconstruction tasks (super-resolution, inpainting) use PSNR or SSIM. For prompt alignment, CLIP Score and Fréchet CLIP Distance quantify semantic correctness; video models additionally report FVD or Video IS to capture temporal coherence.

Reward Metric. During RL fine-tuning, each generated image or video receives a sample-level reward $\mathcal{M}_{\text{samp}}$. Human-preference rewards, *e.g.*, ImageReward (Xu et al., 2023) and HPS (Wu et al., 2023b) supply dense signals that correlate well with aesthetic appeal. When a deterministic checker exists, authors turn to *verifiable rewards*: MotionPrompt (Nam et al., 2025) and DSPO (Cai et al., 2025b) use optical-flow, object masks that can be evaluated without humans. A third route relies on model preference rewards, where a stronger frozen critic (*e.g.*, VideoPrefer (Wu et al., 2024) or PARM (Zhang et al., 2025f)) scores samples, enabling scalable DPO/PPO training.

Model-State Metric. Two light diagnostics track training stability. (i) Denoising trajectory statistics: VARD (Dai et al., 2025) and Inversion DPO (Li et al., 2025f) record per-step noise predictions or DDIM traces; pathological spikes reveal early collapse. (ii) KL divergence between the current diffusion policy and its frozen base ($\pi_{\theta_t} \parallel \pi_{\theta_0}$), popularized by DDPO (Black et al., 2023) and reused in VARD.

4.4 Evaluation of Unified Models

Task Metric. Two benchmark families are widely adopted. *Generation-oriented suites* such as GenEval (Ghosh et al., 2023), DPG-Bench (Hu et al., 2024b), and ParaPrompts (Wu et al., 2025d) focus on prompt-faithful generation, testing multi-object composition, style control, and long-caption adherence. Conversely, understanding-oriented benchmarks (MME (Fu et al., 2023), POPE (Li et al., 2023)) measure grounding, reasoning and hallucination detection from the same backbone.

Reward Metric. Recent work explores two design philosophies for training signals. *Unified rewards* (*e.g.*, UniRL (Mao et al., 2025), CoRL (Jiang et al., 2025b)) blend multiple objectives textual correctness, CLIP alignment, aesthetic quality—into a single scalar that drives one shared policy across tasks. In contrast, task-specific rewards keep the generator and understanding heads separate, applying RL only to the generation branch as in VARGPT-v1.1 (Zhuang et al., 2025) or Emu3 (Wang et al., 2024b). The former promotes cross-modal transfer, while the latter preserves the stability of perception modules.

Model-State Metric. Unified models additionally track fine-grained diagnostics during RL. UniRL (Mao et al., 2025) proposes a generation-understanding imbalance score the absolute gap between batch-level rewards on the two task families to prevent one modality from dominating the update. HermesFlow (Yang et al., 2025c) monitors the KL divergence between the current shared policy π_{θ_t} and its supervised baseline π_{θ_0} on *both* generation and understanding prompts, serving as an early-warning signal for policy collapse. These state-level curves $\mathcal{M}_{\text{state}}^t$ allow practitioners to stop or re-weight training before external task scores degrade.

4.5 Evaluation of Vision Language Action Models

Task Metric. In GUI Automation task, there are multiple benchmarks could be classified into online or offline scenarios. For *offline* setting, it mainly have grounding and navigation parts. For grounding, mainly check whether the click action fail into the target button; For navigation, it requires model to predict current action conditioned on oracle past history, this mainly dependent on whether the action class (click or type) are correctly predicted per step. For *online* setting, it is more challenging, because it requires the model to fully perform multi-step execution which is long procedural then check whether the final outcome meet the task requirement. Such long procedural setups will produce sparse signal in term of model evaluation.

Reward Metric. For reward modeling, most offline RL methods borrow the metric from task metric like IoU, while come to the online environment, due to the sparsity of task success rate, which present significant challenges for end-to-end multi-turn RL training (Lu et al., 2025a) *i.e.*, lack of training efficiency, lack of

Table 3: **Public benchmarks of MLLM most commonly used in visual RL.** Only benchmarks relevant to visual reinforcement learning are included (RL-focused training & evaluation); task-specific benchmarks, such as MME (Fu et al., 2023), are excluded from consideration. ‘Tr’ and ‘Te’ refer to the ‘Train’ and ‘Test’, respectively.

Benchmark	Date	Tr/Te	Description (benchmark info. and RL reward signal)
SEED-Bench-R1 (Chen et al., 2025c)	Mar 2025	Tr&Te	Video-QA pairs with human-preference reward model
Video-Holmes (Cheng et al., 2025)	May 2025	Te	Human-ranked T2I pairs from diverse generation models
VisuLogic (Xu et al., 2025a)	Apr 2025	Tr&Te	Visual-reasoning QA set; exact-match reward enables RL fine-tuning
R1-ShareVL (Yao et al., 2025)	May 2025	Tr	52 k MM-Eureka subset for Share-GRPO RL training
Ego-R1 (Tian et al., 2025)	Jun 2025	Tr&Te	25 k CoTT egocentric traces enabling RL training for ultra-long video reasoning
Long-RL (Chen et al., 2025f)	Jul 2025	Tr&Te	104 K long-video QA pairs (GRPO accuracy / format reward)
VisCOT (Shao et al., 2024a)	Mar 2024	Tr&Te	438 k visual chain-of-thought traces with step-wise rewards for RL
MMK12 (Meng et al., 2025)	Mar 2025	Tr&Te	15.6 K multimodal math problems (rule-based accuracy / format rewards)
Time-R1 (Wang et al., 2025h)	Mar 2025	Tr&Te	2.5 K TimeRFT grounding spans (IoU reward)
VSI-Bench (Yang et al., 2024)	Dec 2024	Te	Spatial QA benchmark offering RL exact-match reward
MME-Reasoning (Yuan et al., 2025a)	May 2025	Te	Logic QA benchmark
K12-2M (Wang et al., 2025d)	May 2025	Tr	2 M multimodal math pairs for RL training
MathVista (Lu et al., 2024)	Oct 2023	Te	Visual-math QA benchmark; test-only RL exact-match reward
MathVerse (Zhang et al., 2024c)	Mar 2024	Te	Diagram-math QA benchmark; test-only RL exact-match reward
EMMA (Hao et al., 2025)	Jan 2025	Te	Robust multimodal reasoning benchmark challenging current MLLMs
WeMath (Qiao et al., 2024)	Jul 2024	Te	Multimodal math reasoning benchmark with diagrams
DynaMATH (Zou et al., 2024)	Oct 2024	Te	Dynamic visual math reasoning robustness benchmark for VLMs
MM-IQ (Cai et al., 2025a)	Feb 2025	Te	Human-like multimodal abstraction and reasoning benchmark
OlympiadBench (He et al., 2024a)	Feb 2024	Te	Bilingual multimodal Olympiad-level scientific reasoning benchmark
ZeroBench (Roberts et al., 2025)	Feb 2025	Te	near-impossible visual reasoning stress test for LMMs
MMM-PRO (Yue et al., 2024)	Sep 2024	Te	robust multidisciplinary multimodal understanding benchmark
MME-CoT (Jiang et al., 2025a)	Feb 2025	Te	Multimodal chain-of-thought reasoning benchmark dataset
MMIR (Yan et al., 2025)	Feb 2025	Te	Multimodal inconsistency reasoning benchmark dataset
SpatialEval (Wang et al., 2024a)	Jun 2024	Te	Synthetic spatial reasoning benchmark for VLMs
MMReason (Wang et al., 2024a)	Jun 2025	Te	Synthetic spatial reasoning benchmark for VLMs
IntentBench (Yang et al., 2025d)	Jun 2025	Te	Omnimodal evaluation demands unified audio-visual comprehension

informativeness, step-level reward is proposed to address this issue, such as developing a reward or critic models (Bai et al., 2024; Chae et al., 2024).

Model-State Metric. To fully understand the model behavior beyond task success rate, trajectory length being an important metric as it can reflect how efficient model can address the task. A smart agent should be able to resolve the task with minimal steps. This pose challenges for agents with advanced planning ability.

4.6 Benchmarks

A variety of new benchmarks explicitly support RL-based training and evaluation in the visual domain (see Table 3). For **MLLM**, recent datasets target complex multi-hop reasoning and alignment with human preferences. For example, SEED-Bench-R1 (Chen et al., 2025c) introduces a hierarchical egocentric video question-answering benchmark with 50k training questions and a human-verified validation set. Long Video RL (Chen et al., 2025f) scales up multi-step reasoning on long videos: it provides 52k QA pairs with detailed reasoning annotations. Another recent benchmark, Ego-R1 Bench (Tian et al., 2025), focuses on ultra-long (week-long) egocentric videos; an RL-trained “chain-of-tool-thought” agent must invoke perception tools in 7 sequential steps on average to answer each query, illustrating the use of step-wise reasoning accuracy as a core challenge. In the image domain, VisuLogic (Xu et al., 2025a) contains 1,000 carefully crafted visual reasoning puzzles (*e.g.*, spatial and logic problems) to evaluate pure vision-centric reasoning, and most models perform only slightly above random on this benchmark.

Benchmarks for **visual generation** tasks predominantly supply human preference data that serve as reward models for policy optimization. Datasets like ImageReward (Xu et al., 2023) and HPS v1 & v2 (Wu et al., 2023b;b) collect human-ranked pairs of text-to-image outputs, allowing one to train a scalar reward function

Table 4: **Public benchmarks of Visual Generation (image/video/3D) most commonly used in visual RL.** Only benchmarks relevant to visual reinforcement learning are included (RL-focused training & evaluation). ‘Tr’ and ‘Te’ refer to the ‘Train’ and ‘Test’, respectively.

Benchmark	Date	Tr/Te	Description (benchmark info. and RL reward signal)
ImageReward (Xu et al., 2023)	Apr 2023	Tr&Te	Human-ranked pairs for T2I; reward model outputs scalar score (used in (Wu et al., 2025b; Xiao et al., 2024; Zhou et al., 2025b))
HPS (Wu et al., 2023b)	Mar 2023	Tr&Te	Human-ranked T2I pairs from diverse generation models (used in (Wu et al., 2023b))
HPS V2 (Wu et al., 2023a)	Jun 2023	Tr&Te	Human-ranked T2I pairs across diverse prompts, preference-based reward (used in (Duan et al., 2025; Gu et al., 2024))
Pick-a-Pic (Kirstain et al., 2023)	May 2023	Tr&Te	User preferences for pairwise rankings over T2I generations (used in (Wallace et al., 2024; Li et al., 2024b; Gu et al., 2024; Lee et al., 2024))
VideoReward (Liu et al., 2025b)	Jan 2025	Te	Human-ranked video pairs across quality, motion, and text alignment (used in (Liu et al., 2025b))
T2I-CompBench (Huang et al., 2023)	Jul 2023	Tr&Te	Compositional text-to-image dataset covering attributes and object relations. (used in (Gupta et al., 2025; Duan et al., 2025))
StarVector (Rodriguez et al., 2025a)	Dec 2023	Tr&Te	SVG Code Generation Data, Match Reward (used in (Rodriguez et al., 2025b))
AnimeReward (Zhu et al., 2025a)	Apr 2025	Tr	Multi-dimensional (<i>e.g.</i> , character consistency) human preference anime videos (used in (Zhu et al., 2025a))
VideoPrefer (Wu et al., 2024)	Dec 2024	Tr	MLLM-annotated 135K video preference pairs (used in (Wu et al., 2024))

Table 5: **Public benchmarks of VLAs most commonly used in visual RL.** Only benchmarks relevant to visual reinforcement learning are included (RL-focused training & evaluation). ‘Tr’ and ‘Te’ refer to the ‘Train’ and ‘Test’, respectively.

Benchmark	Date	Tr/Te	Description (benchmark info. and RL reward signal)
GUI-R1-3K (Luo et al., 2025)	Apr 2025	Tr&Te	GUI trajectories spanning Windows, Linux, macOS, Android, and Web platforms
SE-GUI-3k (Yuan et al., 2025b)	May 2025	Tr	3,018 examples (desktop / web / mobile) with instruction and bounding box
UI-R1 (Lu et al., 2025)	May 2025	Tr	136 mobile GUI tasks covering 5 action types (click, scroll, swipe, text-input)
CAGUI (Zhang et al., 2025j)	Jun 2025	Te	55 K trajectories from 30 Chinese Android apps, 8 domains
Mobile-R1 (Gu et al., 2025)	Jun 2025	Tr&Te	More than 500 online task trajectories from 28 Chinese apps
Mind2web (Deng et al., 2023)	Jun 2023	Tr&Te	2 k tasks on 137 real websites; success/fail reward for RL
AITZ (Zhang et al., 2024b)	Jun 2023	Tr&Te	18,643 Android screen-action pairs with CoAT reasoning
Omniac (Kapoor et al., 2024)	Feb 2024	Tr&Te	Desktop + web 9.8 k scripted tasks
GUICours (Chen et al., 2024b)	Jun 2024	Tr&Te	GUIEnv/Act/Chat datasets (10 M OCR + 67 k navigation)
Habitat (Puig et al., 2023)	Oct 2023	Tr&Te	Interactive embodied-AI scenes with humans and robots
VLN-CE (Krantz et al., 2020)	Apr 2020	Tr&Te	Continuous embodied navigation dataset with language instructions
RLBench (James et al., 2020)	Apr 2020	Tr&Te	Multi-task simulated robot manipulation benchmark dataset
RoboCasa (Nasiriany et al., 2024)	Jun 2024	Tr	Large-scale kitchen-task simulation for generalist robotics
LIBERO (Liu et al., 2023a)	Jun 2023	Tr	Lifelong robot learning benchmark with 100 manipulation tasks
VLABench (Zhang et al., 2024d)	Dec 2024	Tr&Te	Long-horizon language-conditioned manipulation benchmark for robots

that scores generations. Such reward models have been used to refine text-to-image diffusion models via RLHF, aligning outputs with human aesthetic preferences. Similarly, Pick-a-Pic (Kirstain et al., 2023) and VideoReward (Liu et al., 2025b) extend this to broader user preferences (motion smoothness, text alignment). Some benchmarks also facilitate robust evaluation of generative RL agents on generalization. T2I-CompBench (Huang et al., 2023) is a text-to-image compositionality test set that requires correctly binding novel combinations of attributes and object relations – a measure of compositional generalization often used to assess RL-trained generators. Likewise, domain-specific benchmarks define verifiable success criteria as rewards: StarVector (Rodriguez et al., 2025a) provides SVG code-generation tasks with a strict shape-matching reward, and AnimeReward (Zhu et al., 2025a) targets consistency in animated video generations with multi-dimensional human preference scores (image-video coherence, character consistency, etc.).

For **vision–language action** agents, numerous benchmarks provide expert trajectories and simulated environments with clear reward signals for policy training and robust evaluation. Many are centered on GUI and web interaction tasks, where success can be unambiguously measured. For instance, GUI-R1-3K (Luo et al., 2025) compiles 3,000+ GUI manipulation trajectories across Windows, Linux, macOS, Android, and web platforms. It introduces an “R1-style” dense reward scheme mapping each correct action (*e.g.*, clicking the right button, entering correct text, a valid scroll) to positive feedback, providing step-wise reinforcement that guides an agent through multi-step UI tasks. Building on this, SE-GUI (Yuan et al., 2025b) curates 3k high-quality GUI examples with grounded instructions and bounding-box annotations, which are used to train agents with a self-imitation RL strategy. Evaluation-focused suites like UI-R1 (Lu et al., 2025) define a fixed set of unseen tasks (*e.g.*, 136 mobile GUI tasks spanning click, scroll, swipe, text-input actions) to test generalization of learned policies. Meanwhile, web interaction benchmarks such as Mind2Web (Deng et al., 2023) offer 2,000 tasks on real websites with a binary success/failure reward for completing each task. Some datasets emphasize exact match and reproducibility: AITZ (Zhang et al., 2024b) (Android Interaction w/ CoAT reasoning) logs 18k screen-action pairs with corresponding tool-assisted rationales, and uses an exact action match reward to ensure precise adherence to instructions. On the other hand, broader benchmarks like OmniAct (Kapoor et al., 2024) and GUICoURS (Chen et al., 2024b) target generalist agent capabilities across diverse domains. OmniAct integrates nearly 10k scripted desktop and web tasks into a single environment, while GUICoURS combines multimodal resources (10M OCR observations, 67k navigation demonstrations) spanning GUI, web, and chat interfaces. The reward structures in these benchmarks are carefully crafted, from rule-based metrics to preference scores, to guide policy learning and reflect task goals. They enable visual RL agents to learn from meaningful feedback and be evaluated not just on task success, but also on alignment with human reasoning and performance on complex, long-horizon decisions.

5 Challenges and Future Works

5.1 Effective Reasoning: Balancing Depth and Efficiency

A recurrent challenge in visual RL is reasoning calibration: excessively long chains of visual or verbal thoughts incur latency and compounding errors, whereas overly aggressive pruning discards salient cues. We foresee two research thrusts. (i) *Adaptive horizon policies*: train a termination critic that jointly optimizes answer quality and computational cost; curriculum-based reward shaping can gradually penalize redundant steps while preserving informative ones. (ii) *Meta-reasoning and few-shot self-evaluation*: incorporate a lightweight evaluator that critiques partial chains (*e.g.*, via frozen vision–language models) and decides whether further thinking is worthwhile. Future benchmarks should therefore report both success rate and reasoning efficiency metrics (average steps, FLOPs, latency), encouraging algorithms that achieve high accuracy with just-enough deliberation rather than maximal cogitation.

5.2 Long-Horizon RL in VLA

Long-horizon vision–language agents (VLA) must execute dozens of atomic actions (*e.g.*, clicks, drags, text edits) before any end-task reward is observed. Existing works such as OS-World (Abhyankar et al., 2025) and ARPO (Lu et al., 2025a) therefore fall back on sparse reward for each click and a binary task success flag yet empirical results suggest that even GRPO yields limited gains under such supervision. Future research should (i) *discover intrinsic sub-goals*: segment trajectories via state-change detection or language-conditioned clustering, then assign dense rewards to sub-goal completions; (ii) *learn affordance critics*: train contrastive vision–language models to score how much an action reduces the distance to the verbal goal, providing shaped feedback without manual labels; (iii) *hierarchical or option-based RL*: couple a high-level language planner that proposes semantic sub-tasks with a low-level policy fine-tuned by off-policy RL or decision transformers;

5.3 RL for Thinking with Vision

Recent works for visual planning, such as Chain-of-Focus (Zhang et al., 2025g) and Openthinking (Su et al., 2025b) all treat the picture as an external workspace: the agent may crop, sketch, highlight or insert visual tokens before emitting the next language token. While early prototypes rely on supervised heuristics for these

spatial actions, moving to reinforcement learning exposes four open problems. **(i) Action-space design.** Cropping or doodling is naturally continuous (x, y, w, h, \dots) yet RL libraries and GPU memories favor small discrete sets. Hybrid schemes that learn a differentiable proposal policy and then refine coordinates via policy gradient fine-tuning, as hinted by BRPO (Chu et al., 2025) and VRAG-RL (Wang et al., 2025f), remain largely unexplored. **(ii) Credit assignment.** Most benchmarks only reward the final task success (*e.g.*, answer correctness in VILASR (Wu et al., 2025a)); the whole visual chain-of-thought shares a single sparse scalar. Future work should mine step-wise proxy rewards, *e.g.*, CLIP similarity increase after a crop, or entropy drop in a learned belief state—to enable bootstrapped or hierarchical RL. **(iii) Data efficiency.** Sketching or inserting patches triggers extra forward passes through the vision encoder, making naive on-policy RL prohibitively expensive. Relabeling (DeepEyes (Zheng et al., 2025)) and model-based imagination (Pixel Reasoner (Su et al., 2025a)) point to sample-efficient alternatives, but principled replay and uncertainty-aware planners for visual actions are still missing. Therefore, future directions include: learning structured visual skills (crop, zoom, draw) via skill-prior RL; devising cross-modal reward shaping that scores each edit by how much it simplifies the remaining reasoning; and curating benchmarks whose metrics expose not just final accuracy.

5.4 Reward Model Design for Visual Generation

A central obstacle for reinforcement-learning-based visual generation is the lack of a scalable and faithful reward function. Widely used handcrafted metrics such as FID (Heusel et al., 2017) offer a convenient numerical signal, yet correlate only weakly with human judgments of aesthetics, semantic fidelity, or temporal coherence, especially when the task extends beyond single-frame images. Recent learned critics, such as ImageReward (Xu et al., 2023) and HPS (Wu et al., 2023b) for images, and VideoReward (Liu et al., 2025b) for videos to bridge this gap by training on pairwise human-preference data, but each model targets a narrow modality and captures only a slice of perceptual quality (*e.g.*, prompt alignment or visual appeal). As a result, policies optimized with PPO or GRPO often exploit loopholes in a single scalar signal, producing high-contrast artifacts, repetitive textures, or physically implausible motion that “game” the critic without improving real user satisfaction. The challenge, therefore, is to design reward models that (i) integrate complementary low-level signals (consistency, physics, geometry) with high-level human preferences, (ii) generalize across images, video and 3-D scenes, and (iii) remain robust against reward hacking while being cheap enough to update continually as user tastes evolve.

6 Conclusion

Visual reinforcement learning has transitioned from isolated proof-of-concepts to a vibrant research frontier that bridges vision, language, and action. Our review shows that modern progress is driven by three converging forces: (i) scalable reward supervision, moving from labour-intensive RLHF to group-relative and verifiable-signal pipelines; (ii) unified architectures, where a single policy is jointly optimised for perception, reasoning, and generation; and (iii) ever-richer benchmarks, which measure not only task success but also alignment with human preference and policy stability.

Yet significant challenges remain. First, data and compute efficiency are pressing: current methods often require orders of magnitude more samples than supervised counterparts. Second, robust generalization across domains, viewpoints, and embodiment settings is still limited. Third, reward design for long-horizon, open-world tasks lacks principled guidance, risking reward hacking, and unsafe behaviors. Finally, evaluation standards must evolve to capture real-world utility, ethical alignment, and energy footprint. Addressing these issues will likely involve tighter integration of model-based planning, self-supervised visual pre-training, adaptive curricula, and safety-aware optimization.

In summary, visual RL stands poised to transform how intelligent systems perceive and interact with their surroundings. By unifying methodological insights and charting unresolved questions, this survey aims to serve as both a reference and a catalyst for the next wave of research toward sample-efficient, reliable, and socially aligned visual decision-making agents.

References

- Reyna Abhyankar, Qi Qi, and Yiyang Zhang. Osworld-human: Benchmarking the efficiency of computer-use agents. *arXiv preprint arXiv:2506.16042*, 2025.
- Rishabh Agarwal, Max Schwarzer, Pablo Samuel Castro, Aaron C Courville, and Marc Bellemare. Deep reinforcement learning at the edge of the statistical precipice. *Advances in neural information processing systems*, 34:29304–29320, 2021.
- Hao Bai, Yifei Zhou, Jiayi Pan, Mert Cemri, Alane Suhr, Sergey Levine, and Aviral Kumar. Digirl: Training in-the-wild device-control agents with autonomous reinforcement learning. *Advances in Neural Information Processing Systems*, 37:12461–12495, 2024.
- Sule Bai, Mingxing Li, Yong Liu, Jing Tang, Haoji Zhang, Lei Sun, Xiangxiang Chu, and Yansong Tang. Univg-r1: Reasoning guided universal visual grounding with reinforcement learning. *arXiv preprint arXiv:2505.14231*, 2025.
- Eyal Betzalel, Coby Penso, Aviv Navon, and Ethan Fetaya. A study on the evaluation of generative models. *arXiv preprint arXiv:2206.10935*, 2022.
- Kevin Black, Michael Janner, Yilun Du, Ilya Kostrikov, and Sergey Levine. Training diffusion models with reinforcement learning. 2023.
- Rogério Bonatti, Dan Zhao, Francesco Bonacci, Dillon Dupont, Sara Abdali, Yinheng Li, Yadong Lu, Justin Wagle, Kazuhito Koishida, Arthur Buckner, et al. Windows agent arena: Evaluating multi-modal os agents at scale. *arXiv preprint arXiv:2409.08264*, 2024.
- Huanqia Cai, Yijun Yang, and Winston Hu. Mm-iq: Benchmarking human-like abstraction and reasoning in multimodal models. *arXiv preprint arXiv:2502.00698*, 2025a.
- Miaomiao Cai, Simiao Li, Wei Li, Xudong Huang, Hanting Chen, Jie Hu, and Yunhe Wang. Dspo: Direct semantic preference optimization for real-world image super-resolution. *arXiv preprint arXiv:2504.15176*, 2025b.
- Zhuoxuan Cai, Jian Zhang, Xinbin Yuan, Pengtao Jiang, Wenxiang Chen, Bowen Tang, Lujian Yao, Qiyuan Wang, Jinwen Chen, and Bo Li. Q-ponder: A unified training pipeline for reasoning-based visual quality assessment. *arXiv preprint arXiv:2506.05384*, 2025c.
- Meng Cao, Haoze Zhao, Can Zhang, Xiaojun Chang, Ian Reid, and Xiaodan Liang. Ground-r1: Incentivizing grounded visual reasoning via reinforcement learning. *arXiv preprint arXiv:2505.20272*, 2025.
- Hyunjoo Chae, Namyoung Kim, Kai Tzu-iunn Ong, Minju Gwak, Gwanwoo Song, Jihoon Kim, Sunghwan Kim, Dongha Lee, and Jinyoung Yeo. Web agents with world models: Learning and leveraging environment dynamics in web navigation. *arXiv preprint arXiv:2410.13232*, 2024.
- Chaofeng Chen, Annan Wang, Haoning Wu, Liang Liao, Wenxiu Sun, Qiong Yan, and Weisi Lin. Enhancing diffusion models with text-encoder reinforcement learning. In *European Conference on Computer Vision*, pp. 182–198. Springer, 2024a.
- Liang Chen, Hongcheng Gao, Tianyu Liu, Zhiqi Huang, Flood Sung, Xinyu Zhou, Yuxin Wu, and Baobao Chang. G1: Bootstrapping perception and reasoning abilities of vision-language model via reinforcement learning. *arXiv preprint arXiv:2505.13426*, 2025a.
- Wentong Chen, Junbo Cui, Jinyi Hu, Yujia Qin, Junjie Fang, Yue Zhao, Chongyi Wang, Jun Liu, Guirong Chen, Yupeng Huo, et al. Guicourse: From general vision language models to versatile gui agents. *arXiv preprint arXiv:2406.11317*, 2024b.
- Yi Chen, Yuying Ge, Rui Wang, Yixiao Ge, Junhao Cheng, Ying Shan, and Xihui Liu. Grpo-care: Consistency-aware reinforcement learning for multimodal reasoning. *arXiv preprint arXiv:2506.16141*, 2025b.

-
- Yi Chen, Yuying Ge, Rui Wang, Yixiao Ge, Lu Qiu, Ying Shan, and Xihui Liu. Exploring the effect of reinforcement learning on video understanding: Insights from seed-bench-r1. *arXiv preprint arXiv:2503.24376*, 2025c.
- Yuhui Chen, Haoran Li, Zhennan Jiang, Haowei Wen, and Dongbin Zhao. Tevir: Text-to-video reward with diffusion models for efficient reinforcement learning. *arXiv preprint arXiv:2505.19769*, 2025d.
- Yuhui Chen, Shuai Tian, Shugao Liu, Yingting Zhou, Haoran Li, and Dongbin Zhao. Conrft: A reinforced fine-tuning method for vla models via consistency policy. *arXiv preprint arXiv:2502.05450*, 2025e.
- Yukang Chen, Wei Huang, Baifeng Shi, Qinghao Hu, Hanrong Ye, Ligeng Zhu, Zhijian Liu, Pavlo Molchanov, Jan Kautz, Xiaojuan Qi, et al. Scaling rl to long videos. *arXiv preprint arXiv:2507.07966*, 2025f.
- Zengjue Chen, Runliang Niu, He Kong, and Qi Wang. Tgrpo: Fine-tuning vision-language-action model via trajectory-wise group relative policy optimization. *arXiv preprint arXiv:2506.08440*, 2025g.
- Zhangquan Chen, Xufang Luo, and Dongsheng Li. Visrl: Intention-driven visual perception via reinforced reasoning. *arXiv preprint arXiv:2503.07523*, 2025h.
- Junhao Cheng, Yuying Ge, Teng Wang, Yixiao Ge, Jing Liao, and Ying Shan. Video-holmes: Can mllm think like holmes for complex video reasoning? *arXiv preprint arXiv:2505.21374*, 2025.
- Kanzhi Cheng, Qiushi Sun, Yougang Chu, Fangzhi Xu, Yantao Li, Jianbing Zhang, and Zhiyong Wu. Seeclik: Harnessing gui grounding for advanced visual gui agents. *arXiv preprint arXiv:2401.10935*, 2024.
- Ethan Chern, Zhulin Hu, Steffi Chern, Siqi Kou, Jiadi Su, Yan Ma, Zhijie Deng, and Pengfei Liu. Thinking with generated images. *arXiv preprint arXiv:2505.22525*, 2025.
- Paul F Christiano, Jan Leike, Tom Brown, Miljan Martic, Shane Legg, and Dario Amodei. Deep reinforcement learning from human preferences. *Advances in neural information processing systems*, 30, 2017.
- Xu Chu, Xinrong Chen, Guanyu Wang, Zhijie Tan, Kui Huang, Wenyu Lv, Tong Mo, and Weiping Li. Qwen look again: Guiding vision-language reasoning models to re-attention visual information. *arXiv preprint arXiv:2505.23558*, 2025.
- Fengyuan Dai, Zifeng Zhuang, Yufei Huang, Siteng Huang, Bangyan Liao, Donglin Wang, and Fajie Yuan. Vard: Efficient and dense fine-tuning for diffusion models with value-based rl. *arXiv preprint arXiv:2505.15791*, 2025.
- Jisheng Dang, Jingze Wu, Teng Wang, Xuanhui Lin, Nannan Zhu, Hongbo Chen, Wei-Shi Zheng, Meng Wang, and Tat-Seng Chua. Reinforcing video reasoning with focused thinking. *arXiv preprint arXiv:2505.24718*, 2025.
- Google DeepMind. Gemini 2.5. <https://deepmind.google/technologies/gemini/>, 2025. Accessed: 2025-08-09.
- Xiang Deng, Yu Gu, Boyuan Zheng, Shijie Chen, Sam Stevens, Boshi Wang, Huan Sun, and Yu Su. Mind2web: Towards a generalist agent for the web. *Advances in Neural Information Processing Systems*, 36:28091–28114, 2023.
- Chengqi Duan, Rongyao Fang, Yuqing Wang, Kun Wang, Linjiang Huang, Xingyu Zeng, Hongsheng Li, and Xihui Liu. Got-r1: Unleashing reasoning capability of mllm for visual generation with reinforcement learning. *arXiv preprint arXiv:2505.17022*, 2025.
- Ying Fan, Olivia Watkins, Yuqing Du, Hao Liu, Moonkyung Ryu, Craig Boutilier, Pieter Abbeel, Mohammad Ghavamzadeh, Kangwook Lee, and Kimin Lee. Dpok: Reinforcement learning for fine-tuning text-to-image diffusion models. *Advances in Neural Information Processing Systems*, 36:79858–79885, 2023a.

-
- Ying Fan, Olivia Watkins, Yuqing Du, Hao Liu, Moonkyung Ryu, Craig Boutilier, Pieter Abbeel, Mohammad Ghavamzadeh, Kangwook Lee, and Kimin Lee. Reinforcement learning for fine-tuning text-to-image diffusion models. In *Thirty-seventh Conference on Neural Information Processing Systems (NeurIPS) 2023*. Neural Information Processing Systems Foundation, 2023b.
- Yue Fan, Xuehai He, Diji Yang, Kaizhi Zheng, Ching-Chen Kuo, Yuting Zheng, Sravana Jyothi Narayanaraju, Xinze Guan, and Xin Eric Wang. Grit: Teaching mllms to think with images. *arXiv preprint arXiv:2505.15879*, 2025.
- Xueji Fang, Liyuan Ma, Zhiyang Chen, Mingyuan Zhou, and Guo-jun Qi. Inlvg: Reinforce inference-time consistent long video generation with grpo. *arXiv preprint arXiv:2505.17574*, 2025.
- Kaituo Feng, Kaixiong Gong, Bohao Li, Zonghao Guo, Yibing Wang, Tianshuo Peng, Benyou Wang, and Xiangyu Yue. Video-r1: Reinforcing video reasoning in mllms. *arXiv: 2503.21776*, 2025.
- Chaoyou Fu, Peixian Chen, Yunhang Shen, Yulei Qin, Mengdan Zhang, Xu Lin, Jinrui Yang, Xiewu Zheng, Ke Li, Xing Sun, et al. Mme: A comprehensive evaluation benchmark for multimodal large language models. *arXiv preprint arXiv:2306.13394*, 2023.
- Matteo Gallici and Haitz Sáez de Ocáriz Borde. Fine-tuning next-scale visual autoregressive models with group relative policy optimization. *arXiv preprint arXiv:2505.23331*, 2025.
- Chen Gao, Liankai Jin, Xingyu Peng, Jiazhao Zhang, Yue Deng, Annan Li, He Wang, and Si Liu. Octonav: Towards generalist embodied navigation. *arXiv preprint arXiv:2506.09839*, 2025a.
- Longxi Gao, Li Zhang, and Mengwei Xu. Uishift: Enhancing vlm-based gui agents through self-supervised reinforcement learning. *arXiv preprint arXiv:2505.12493*, 2025b.
- Zigang Geng, Yibing Wang, Yeyao Ma, Chen Li, Yongming Rao, Shuyang Gu, Zhao Zhong, Qinglin Lu, Han Hu, Xiaosong Zhang, et al. X-omni: Reinforcement learning makes discrete autoregressive image generative models great again. *arXiv preprint arXiv:2507.22058*, 2025.
- Dhruba Ghosh, Hannaneh Hajishirzi, and Ludwig Schmidt. Geneval: An object-focused framework for evaluating text-to-image alignment. *Advances in Neural Information Processing Systems*, 36:52132–52152, 2023.
- Yunhao Gou, Kai Chen, Zhili Liu, Lanqing Hong, Xin Jin, Zhenguo Li, James T Kwok, and Yu Zhang. Perceptual decoupling for scalable multi-modal reasoning via reward-optimized captioning. *arXiv preprint arXiv:2506.04559*, 2025.
- Yash Goyal, Tejas Khot, Douglas Summers-Stay, Dhruv Batra, and Devi Parikh. Making the v in vqa matter: Elevating the role of image understanding in visual question answering. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 6904–6913, 2017.
- Jihao Gu, Qihang Ai, Yingyao Wang, Pi Bu, Jingxuan Xing, Zekun Zhu, Wei Jiang, Ziming Wang, Yingxiu Zhao, Ming-Liang Zhang, et al. Mobile-r1: Towards interactive reinforcement learning for vlm-based mobile agent via task-level rewards. *arXiv preprint arXiv:2506.20332*, 2025.
- Yi Gu, Zhendong Wang, Yueqin Yin, Yujia Xie, and Mingyuan Zhou. Diffusion-rpo: Aligning diffusion models through relative preference optimization. *arXiv preprint arXiv:2406.06382*, 2024.
- Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, et al. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*, 2025a.
- Yanjiang Guo, Jianke Zhang, Xiaoyu Chen, Xiang Ji, Yen-Jen Wang, Yucheng Hu, and Jianyu Chen. Improving vision-language-action model with online reinforcement learning. *arXiv preprint arXiv:2501.16664*, 2025b.
- Zirun Guo, Minjie Hong, and Tao Jin. Observe-r1: Unlocking reasoning abilities of mllms with dynamic progressive reinforcement learning. *arXiv preprint arXiv:2505.12432*, 2025c.

-
- Ziyu Guo, Renrui Zhang, Chengzhuo Tong, Zhizheng Zhao, Peng Gao, Hongsheng Li, and Pheng-Ann Heng. Can we generate images with cot? let’s verify and reinforce image generation step by step. *arXiv preprint arXiv:2501.13926*, 2025d.
- Shashank Gupta, Chaitanya Ahuja, Tsung-Yu Lin, Sreya Dutta Roy, Harrie Oosterhuis, Maarten de Rijke, and Satya Narayan Shukla. A simple and effective reinforcement learning method for text-to-image diffusion fine-tuning. *arXiv preprint arXiv:2503.00897*, 2025.
- Yunzhuo Hao, Jiawei Gu, Huichen Will Wang, Linjie Li, Zhengyuan Yang, Lijuan Wang, and Yu Cheng. Can mllms reason in multimodality? emma: An enhanced multimodal reasoning benchmark. *arXiv preprint arXiv:2501.05444*, 2025.
- Chaoqun He, Renjie Luo, Yuzhuo Bai, Shengding Hu, Zhen Leng Thai, Junhao Shen, Jinyi Hu, Xu Han, Yujie Huang, Yuxiang Zhang, Jie Liu, Lei Qi, Zhiyuan Liu, and Maosong Sun. Olympiadbench: A challenging benchmark for promoting agi with olympiad-level bilingual multimodal scientific problems, 2024a.
- Xuan He, Dongfu Jiang, Ge Zhang, Max Ku, Achint Soni, Sherman Siu, Haonan Chen, Abhranil Chandra, Ziyang Jiang, Aaran Arulraj, et al. Videoscore: Building automatic metrics to simulate fine-grained human feedback for video generation. *arXiv preprint arXiv:2406.15252*, 2024b.
- Zheqi He, Xinya Wu, Pengfei Zhou, Richeng Xuan, Guang Liu, Xi Yang, Qiannan Zhu, and Hua Huang. Cmmu: A benchmark for chinese multi-modal multi-type question understanding and reasoning. *arXiv preprint arXiv:2401.14011*, 2024c.
- Jack Hessel, Ari Holtzman, Maxwell Forbes, Ronan Le Bras, and Yejin Choi. Clipscore: A reference-free evaluation metric for image captioning. *arXiv preprint arXiv:2104.08718*, 2021.
- Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. *Advances in neural information processing systems*, 30, 2017.
- Jiaheng Hu, Rose Hendrix, Ali Farhadi, Aniruddha Kembhavi, Roberto Martín-Martín, Peter Stone, Kuo-Hao Zeng, and Kiana Ehsani. Flare: Achieving masterful and adaptive robot policies with large-scale reinforcement learning fine-tuning. *arXiv preprint arXiv:2409.16578*, 2024a.
- Xiwei Hu, Rui Wang, Yixiao Fang, Bin Fu, Pei Cheng, and Gang Yu. Ella: Equip diffusion models with llm for enhanced semantic alignment. *arXiv preprint arXiv:2403.05135*, 2024b.
- Zijing Hu, Fengda Zhang, Long Chen, Kun Kuang, Jiahui Li, Kaifeng Gao, Jun Xiao, Xin Wang, and Wenwu Zhu. Towards better alignment: Training diffusion models with reinforcement learning against sparse rewards. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pp. 23604–23614, 2025a.
- Zijing Hu, Fengda Zhang, and Kun Kuang. D-fusion: Direct preference optimization for aligning diffusion models with visually consistent samples. *arXiv preprint arXiv:2505.22002*, 2025b.
- Kaiyi Huang, Kaiyue Sun, Enze Xie, Zhenguo Li, and Xihui Liu. T2i-compbench: A comprehensive benchmark for open-world compositional text-to-image generation. *Advances in Neural Information Processing Systems*, 36:78723–78747, 2023.
- Zeyi Huang, Yuyang Ji, Anirudh Sundara Rajan, Zefan Cai, Wen Xiao, Junjie Hu, and Yong Jae Lee. Visualtoolagent (vista): A reinforcement learning framework for visual tool selection. *arXiv preprint arXiv:2505.20289*, 2025.
- Aaron Jaech, Adam Kalai, Adam Lerer, Adam Richardson, Ahmed El-Kishky, Aiden Low, Alec Helyar, Aleksander Madry, Alex Beutel, Alex Carney, et al. Openai o1 system card. *arXiv preprint arXiv:2412.16720*, 2024.
- Stephen James, Zicong Ma, David Rovick Arrojo, and Andrew J Davison. Rlbench: The robot learning benchmark & learning environment. *IEEE Robotics and Automation Letters*, 5(2):3019–3026, 2020.

-
- Dongzhi Jiang, Renrui Zhang, Ziyu Guo, Yanwei Li, Yu Qi, Xinyan Chen, Liuhui Wang, Jianhan Jin, Claire Guo, Shen Yan, et al. Mme-cot: Benchmarking chain-of-thought in large multimodal models for reasoning quality, robustness, and efficiency. *arXiv preprint arXiv:2502.09621*, 2025a.
- Jingjing Jiang, Chongjie Si, Jun Luo, Hanwang Zhang, and Chao Ma. Co-reinforcement learning for unified multimodal understanding and generation. *arXiv preprint arXiv:2505.17534*, 2025b.
- Scott Jordan, Yash Chandak, Daniel Cohen, Mengxue Zhang, and Philip Thomas. Evaluating the performance of reinforcement learning algorithms. In *International Conference on Machine Learning*, pp. 4962–4973. PMLR, 2020.
- Zhehan Kan, Yanlin Liu, Kun Yin, Xinghua Jiang, Xin Li, Haoyu Cao, Yinsong Liu, Deqiang Jiang, Xing Sun, Qingmin Liao, et al. Taco: Think-answer consistency for optimized long-chain reasoning and efficient data learning via reinforcement learning in llms. *arXiv preprint arXiv:2505.20777*, 2025.
- Raghav Kapoor, Yash Parag Butala, Melisa Russak, Jing Yu Koh, Kiran Kamble, Waseem AlShikh, and Ruslan Salakhutdinov. Omniaact: A dataset and benchmark for enabling multimodal generalist autonomous agents for desktop and web. In *European Conference on Computer Vision*, pp. 161–178. Springer, 2024.
- Minwoo Kim, Geunsik Bae, Jinwoo Lee, Woojae Shin, Changseung Kim, Myong-Yol Choi, Heejung Shin, and Hyondong Oh. Rapid: Robust and agile planner using inverse reinforcement learning for vision-based drone navigation. *arXiv preprint arXiv:2502.02054*, 2025.
- Yuval Kirstain, Adam Polyak, Uriel Singer, Shahbuland Matiana, Joe Penna, and Omer Levy. Pick-a-pic: An open dataset of user preferences for text-to-image generation. *Advances in neural information processing systems*, 36:36652–36663, 2023.
- Jacob Krantz, Erik Wijmans, Arjun Majumdar, Dhruv Batra, and Stefan Lee. Beyond the nav-graph: Vision-and-language navigation in continuous environments. In *European Conference on Computer Vision*, pp. 104–120. Springer, 2020.
- Nathan Lambert, Jacob Morrison, Valentina Pyatkin, Shengyi Huang, Hamish Ivison, Faeze Brahman, Lester James V Miranda, Alisa Liu, Nouha Dziri, Shane Lyu, et al. T³: Pushing frontiers in open language model post-training. *arXiv preprint arXiv:2411.15124*, 2024.
- Hung Le, Yue Wang, Akhilesh Deepak Gotmare, Silvio Savarese, and Steven Chu Hong Hoi. Coderl: Mastering code generation through pretrained models and deep reinforcement learning. *Advances in Neural Information Processing Systems*, 35:21314–21328, 2022.
- Seung Hyun Lee, Yinxiao Li, Junjie Ke, Innfarn Yoo, Han Zhang, Jiahui Yu, Qifei Wang, Fei Deng, Glenn Entis, Junfeng He, et al. Parrot: Pareto-optimal multi-reward reinforcement learning framework for text-to-image generation. In *European Conference on Computer Vision*, pp. 462–478. Springer, 2024.
- Bohao Li, Yuying Ge, Yixiao Ge, Guangzhi Wang, Rui Wang, Ruimao Zhang, and Ying Shan. Seed-bench: Benchmarking multimodal large language models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 13299–13308, 2024a.
- Hongyu Li, Songhao Han, Yue Liao, Junfeng Luo, Jialin Gao, Shuicheng Yan, and Si Liu. Reinforcement learning tuning for videollms: Reward design and data efficiency. *arXiv preprint arXiv:2506.01908*, 2025a.
- Jinzheng Li, Siboj Ju, Yanzhou Su, Hongguang Li, and Yiqing Shen. Enhancing llms’ reasoning-intensive multimedia search capabilities through fine-tuning and reinforcement learning. *arXiv preprint arXiv:2505.18831*, 2025b.
- Kaixin Li, Ziyang Meng, Hongzhan Lin, Ziyang Luo, Yuchen Tian, Jing Ma, Zhiyong Huang, and Tat-Seng Chua. Screenspot-pro: Gui grounding for professional high-resolution computer use. *arXiv preprint arXiv:2504.07981*, 2025c.

-
- Shufan Li, Konstantinos Kallidromitis, Akash Gokul, Yusuke Kato, and Kazuki Kozuka. Aligning diffusion models by optimizing human utility. *Advances in Neural Information Processing Systems*, 37:24897–24925, 2024b.
- Tiancheng Li, Jinxiu Liu, Huajun Chen, and Qi Liu. Instructrl4pix: Training diffusion for image editing by reinforcement learning. *arXiv preprint arXiv:2406.09973*, 2024c.
- Xinhao Li, Ziang Yan, Desen Meng, Lu Dong, Xiangyu Zeng, Yinan He, Yali Wang, Yu Qiao, Yi Wang, and Limin Wang. Videochat-r1: Enhancing spatio-temporal perception via reinforcement fine-tuning. *arXiv preprint arXiv:2504.06958*, 2025d.
- Yifan Li, Yifan Du, Kun Zhou, Jinpeng Wang, Wayne Xin Zhao, and Ji-Rong Wen. Evaluating object hallucination in large vision-language models. *arXiv preprint arXiv:2305.10355*, 2023.
- Yue Li, Meng Tian, Dechang Zhu, Jiangtong Zhu, Zhenyu Lin, Zhiwei Xiong, and Xinhai Zhao. Drive-r1: Bridging reasoning and planning in vlms for autonomous driving with reinforcement learning. *arXiv preprint arXiv:2506.18234*, 2025e.
- Zejian Li, Yize Li, Chenye Meng, Zhongni Liu, Yang Ling, Shengyuan Zhang, Guang Yang, Changyuan Yang, Zhiyuan Yang, and Lingyun Sun. Inversion-dpo: Precise and efficient post-training for diffusion models. *arXiv preprint arXiv:2507.11554*, 2025f.
- Zongzhao Li, Zongyang Ma, Mingze Li, Songyou Li, Yu Rong, Tingyang Xu, Ziqi Zhang, Deli Zhao, and Wenbing Huang. Star-r1: Spacial transformation reasoning by reinforcing multimodal llms. *arXiv preprint arXiv:2505.15804*, 2025g.
- Yiqing Liang, Jieli Qiu, Wenhao Ding, Zuxin Liu, James Tompkin, Mengdi Xu, Mengzhou Xia, Zhengzhong Tu, Laixi Shi, and Jiacheng Zhu. Modomodo: Multi-domain data mixtures for multimodal llm reinforcement learning. *arXiv preprint arXiv:2505.24871*, 2025.
- Youwei Liang, Junfeng He, Gang Li, Peizhao Li, Arseniy Klimovskiy, Nicholas Carolan, Jiao Sun, Jordi Pont-Tuset, Sarah Young, Feng Yang, et al. Rich human feedback for text-to-image generation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 19401–19411, 2024.
- Wang Lin, Liyu Jia, Wentao Hu, Kaihang Pan, Zhongqi Yue, Wei Zhao, Jingyuan Chen, Fei Wu, and Hanwang Zhang. Reasoning physical video generation with diffusion timestep tokens via reinforcement learning. *arXiv preprint arXiv:2504.15932*, 2025.
- Bo Liu, Yifeng Zhu, Chongkai Gao, Yihao Feng, Qiang Liu, Yuke Zhu, and Peter Stone. Libero: Benchmarking knowledge transfer for lifelong robot learning. *Advances in Neural Information Processing Systems*, 36: 44776–44791, 2023a.
- Jie Liu, Gongye Liu, Jiajun Liang, Yangguang Li, Jiaheng Liu, Xintao Wang, Pengfei Wan, Di Zhang, and Wanli Ouyang. Flow-grpo: Training flow matching models via online rl. *arXiv preprint arXiv:2505.05470*, 2025a.
- Jie Liu, Gongye Liu, Jiajun Liang, Ziyang Yuan, Xiaokun Liu, Mingwu Zheng, Xiele Wu, Qiulin Wang, Wenyu Qin, Menghan Xia, et al. Improving video generation with human feedback. *arXiv preprint arXiv:2501.13918*, 2025b.
- Jijia Liu, Feng Gao, Bingwen Wei, Xinlei Chen, Qingmin Liao, Yi Wu, Chao Yu, and Yu Wang. What can rl bring to vla generalization? an empirical study. *arXiv preprint arXiv:2505.19789*, 2025c.
- Kendong Liu, Zhiyu Zhu, Chuanhao Li, Hui Liu, Huanqiang Zeng, and Junhui Hou. Prefpaint: Aligning image inpainting diffusion model with human preference. *Advances in Neural Information Processing Systems*, 37:30554–30589, 2024a.
- Qingming Liu, Zhen Liu, Dinghuai Zhang, and Kui Jia. Nabla-r2d3: Effective and efficient 3d diffusion alignment with 2d rewards. *arXiv preprint arXiv:2506.15684*, 2025d.

-
- Yuan Liu, Haodong Duan, Yuanhan Zhang, Bo Li, Songyang Zhang, Wangbo Zhao, Yike Yuan, Jiaqi Wang, Conghui He, Ziwei Liu, et al. Mmbench: Is your multi-modal model an all-around player? In *European conference on computer vision*, pp. 216–233. Springer, 2024b.
- Yuliang Liu, Zhang Li, Hongliang Li, Wenwen Yu, Mingxin Huang, Dezhi Peng, Mingyu Liu, Mingrui Chen, Chunyuan Li, Lianwen Jin, et al. On the hidden mystery of ocr in large multimodal models. *arXiv preprint arXiv:2305.07895*, 2(5):6, 2023b.
- Yuqi Liu, Tianyuan Qu, Zhisheng Zhong, Bohao Peng, Shu Liu, Bei Yu, and Jiaya Jia. Visionreasoner: Unified visual perception and reasoning via reinforcement learning. *arXiv preprint arXiv:2505.12081*, 2025e.
- Ziyu Liu, Zeyi Sun, Yuhang Zang, Xiaoyi Dong, Yuhang Cao, Haodong Duan, Dahua Lin, and Jiaqi Wang. Visual-rft: Visual reinforcement fine-tuning. *arXiv preprint arXiv:2503.01785*, 2025f.
- Fanbin Lu, Zhisheng Zhong, Shu Liu, Chi-Wing Fu, and Jiaya Jia. Arpo: End-to-end policy optimization for gui agents with experience replay. *arXiv preprint arXiv:2505.16282*, 2025a.
- Guanxing Lu, Wenkai Guo, Chubin Zhang, Yuheng Zhou, Haonan Jiang, Zifeng Gao, Yansong Tang, and Ziwei Wang. Vla-rl: Towards masterful and general robotic manipulation with scalable reinforcement learning. *arXiv preprint arXiv:2505.18719*, 2025b.
- Pan Lu, Hritik Bansal, Tony Xia, Jiacheng Liu, Chunyuan Li, Hannaneh Hajishirzi, Hao Cheng, Kai-Wei Chang, Michel Galley, and Jianfeng Gao. Mathvista: Evaluating mathematical reasoning of foundation models in visual contexts. *arXiv preprint arXiv:2310.02255*, 2023.
- Pan Lu, Hritik Bansal, Tony Xia, Jiacheng Liu, Chunyuan Li, Hannaneh Hajishirzi, Hao Cheng, Kai-Wei Chang, Michel Galley, and Jianfeng Gao. Mathvista: Evaluating mathematical reasoning of foundation models in visual contexts. In *International Conference on Learning Representations (ICLR)*, 2024.
- Xing Han Lù, Amirhossein Kazemnejad, Nicholas Meade, Arkil Patel, Dongchan Shin, Alejandra Zambrano, Karolina Stańczak, Peter Shaw, Christopher J Pal, and Siva Reddy. Agentrewardbench: Evaluating automatic evaluations of web agent trajectories. *arXiv preprint arXiv:2504.08942*, 2025.
- Zhengxi Lu, Yuxiang Chai, Yaxuan Guo, Xi Yin, Liang Liu, Hao Wang, Han Xiao, Shuai Ren, Guanqing Xiong, and Hongsheng Li. Ui-r1: Enhancing efficient action prediction of gui agents by reinforcement learning. *arXiv preprint arXiv:2503.21620*, 2025.
- Run Luo, Lu Wang, Wanwei He, and Xiaobo Xia. Gui-r1: A generalist r1-style vision-language action model for gui agents. *arXiv preprint arXiv:2504.10458*, 2025.
- Yan Ma, Linge Du, Xuyang Shen, Shaoxiang Chen, Pengfei Li, Qibing Ren, Lizhuang Ma, Yuchao Dai, Pengfei Liu, and Junjie Yan. One rl to see them all: Visual triple unified reinforcement learning. *arXiv preprint arXiv:2505.18129*, 2025.
- Weijia Mao, Zhenheng Yang, and Mike Zheng Shou. Unirl: Self-improving unified multimodal models via supervised and reinforcement learning. *arXiv preprint arXiv:2505.23380*, 2025.
- Minesh Mathew, Dimosthenis Karatzas, and CV Jawahar. Docvqa: A dataset for vqa on document images. In *Proceedings of the IEEE/CVF winter conference on applications of computer vision*, pp. 2200–2209, 2021.
- Minesh Mathew, Viraj Bagal, Rubèn Tito, Dimosthenis Karatzas, Ernest Valveny, and CV Jawahar. Info-graphicvqa. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pp. 1697–1706, 2022.
- Nat McAleese, Rai Michael Pokorny, Juan Felipe Ceron Uribe, Evgenia Nitishinskaya, Maja Trebacz, and Jan Leike. Llm critics help catch llm bugs. *arXiv preprint arXiv:2407.00215*, 2024.

-
- Fanqing Meng, Lingxiao Du, Zongkai Liu, Zhixiang Zhou, Quanfeng Lu, Daocheng Fu, Tiancheng Han, Botian Shi, Wenhai Wang, Junjun He, et al. Mm-eureka: Exploring the frontiers of multimodal reasoning with rule-based reinforcement learning. *arXiv preprint arXiv:2503.07365*, 2025.
- Yanting Miao, William Loh, Suraj Kothawade, Pascal Poupart, Abdullah Rashwan, and Yeqing Li. Subject-driven text-to-image generation via preference-based reinforcement learning. *Advances in Neural Information Processing Systems*, 37:123563–123591, 2024a.
- Zichen Miao, Jiang Wang, Ze Wang, Zhengyuan Yang, Lijuan Wang, Qiang Qiu, and Zicheng Liu. Training diffusion models towards diverse image generation with reinforcement learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10844–10853, 2024b.
- Anand Mishra, Shashank Shekhar, Ajeet Kumar Singh, and Anirban Chakraborty. Ocr-vqa: Visual question answering by reading text in images. In *2019 international conference on document analysis and recognition (ICDAR)*, pp. 947–952. IEEE, 2019.
- Zhun Mou, Bin Xia, Zhengchao Huang, Wenming Yang, and Jiaya Jia. Gradeo: Towards human-like evaluation for text-to-video generation via multi-step reasoning. *arXiv preprint arXiv:2503.02341*, 2025.
- Hyelin Nam, Jaemin Kim, Dohun Lee, and Jong Chul Ye. Optical-flow guided prompt optimization for coherent video generation. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pp. 7837–7846, 2025.
- Soroush Nasiriany, Abhiram Maddukuri, Lance Zhang, Adeet Parikh, Aaron Lo, Abhishek Joshi, Ajay Mandlekar, and Yuke Zhu. Robocasa: Large-scale simulation of everyday tasks for generalist robots. *arXiv preprint arXiv:2406.02523*, 2024.
- Shravan Nayak, Xiangru Jian, Kevin Qinghong Lin, Juan A Rodriguez, Montek Kalsi, Rabiul Awal, Nicolas Chapados, M Tamer Özsu, Aishwarya Agrawal, David Vazquez, et al. Ui-vision: A desktop-centric gui benchmark for visual perception and interaction. *arXiv preprint arXiv:2503.15661*, 2025.
- Owen Oertell, Jonathan Daniel Chang, Yiyi Zhang, Kianté Brantley, and Wen Sun. Rl for consistency models: Reward guided text-to-image generation with fast inference. In *Reinforcement Learning Conference*, 2024.
- Yeongtak Oh, Jisoo Mok, Dohyun Chung, Juhyeon Shin, Sangha Park, Johan Barthelemy, and Sungroh Yoon. Repic: Reinforced post-training for personalizing multi-modal language models. *arXiv preprint arXiv:2506.18369*, 2025.
- Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35:27730–27744, 2022.
- Kaihang Pan, Wendong Bu, Yuruo Wu, Yang Wu, Kai Shen, Yunfei Li, Hang Zhao, Juncheng Li, Siliang Tang, and Yueting Zhuang. Focusdiff: Advancing fine-grained text-image alignment for autoregressive visual generation through rl. *arXiv preprint arXiv:2506.05501*, 2025.
- Zhenyu Pan and Han Liu. Metaspatial: Reinforcing 3d spatial reasoning in vlms for the metaverse. *arXiv preprint arXiv:2503.18470*, 2025.
- Georgios Papoudakis, Thomas Coste, Zhihao Wu, Jianye Hao, Jun Wang, and Kun Shao. Appvlm: A lightweight vision language model for online app control. *arXiv preprint arXiv:2502.06395*, 2025.
- Jinyoung Park, Jeehye Na, Jinyoung Kim, and Hyunwoo J Kim. Deepvideo-r1: Video reinforcement fine-tuning via difficulty-aware regressive grpo. *arXiv preprint arXiv:2506.07464*, 2025a.
- Sungjune Park, Hyunjun Kim, Junho Kim, Seongho Kim, and Yong Man Ro. Dip-r1: Deep inspection and perception with rl looking through and understanding complex scenes. *arXiv preprint arXiv:2505.23179*, 2025b.

-
- Xavier Puig, Eric Undersander, Andrew Szot, Mikael Dallaire Cote, Tsung-Yen Yang, Ruslan Partsey, Ruta Desai, Alexander William Clegg, Michal Hlavac, So Yeon Min, et al. Habitat 3.0: A co-habitat for humans, avatars and robots. *arXiv preprint arXiv:2310.13724*, 2023.
- Zhangyang Qi, Zhixiong Zhang, Yizhou Yu, Jiaqi Wang, and Hengshuang Zhao. Vln-r1: Vision-language navigation via reinforcement fine-tuning. *arXiv preprint arXiv:2506.17221*, 2025.
- Runqi Qiao, Qiuna Tan, Guanting Dong, Minhui Wu, Chong Sun, Xiaoshuai Song, Zhuoma GongQue, Shanglin Lei, Zhe Wei, Miaoxuan Zhang, et al. We-math: Does your large multimodal model achieve human-like mathematical reasoning? *arXiv preprint arXiv:2407.01284*, 2024.
- Yujia Qin, Yining Ye, Junjie Fang, Haoming Wang, Shihao Liang, Shizuo Tian, Junda Zhang, Jiahao Li, Yunxin Li, Shijue Huang, et al. Ui-tars: Pioneering automated gui interaction with native agents. *arXiv preprint arXiv:2501.12326*, 2025.
- Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International conference on machine learning*, pp. 8748–8763. PmLR, 2021.
- Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. *Advances in Neural Information Processing Systems*, 36:53728–53741, 2023.
- Hamid Rezaatofghi, Nathan Tsoi, JunYoung Gwak, Amir Sadeghian, Ian Reid, and Silvio Savarese. Generalized intersection over union: A metric and a loss for bounding box regression. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 658–666, 2019.
- Jonathan Roberts, Mohammad Reza Taesiri, Ansh Sharma, Akash Gupta, Samuel Roberts, Ioana Croitoru, Simion-Vlad Bogolin, Jialu Tang, Florian Langer, Vyas Raina, et al. Zerobench: An impossible visual benchmark for contemporary large multimodal models. *arXiv preprint arXiv:2502.09696*, 2025.
- Juan A Rodriguez, Abhay Puri, Shubham Agarwal, Issam H Laradji, Pau Rodriguez, Sai Rajeswar, David Vazquez, Christopher Pal, and Marco Pedersoli. Starvector: Generating scalable vector graphics code from images and text. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pp. 16175–16186, 2025a.
- Juan A Rodriguez, Haotian Zhang, Abhay Puri, Aarash Feizi, Rishav Pramanik, Pascal Wichmann, Arnab Mondal, Mohammad Reza Samsami, Rabiul Awal, Perouz Taslakian, et al. Rendering-aware reinforcement learning for vector graphics generation. *arXiv preprint arXiv:2505.20793*, 2025b.
- Masaki Saito, Shunta Saito, Masanori Koyama, and Sosuke Kobayashi. Train sparsely, generate densely: Memory-efficient unsupervised training of high-resolution temporal gan. *International Journal of Computer Vision*, 128(10):2586–2606, 2020.
- Tim Salimans, Ian Goodfellow, Wojciech Zaremba, Vicki Cheung, Alec Radford, and Xi Chen. Improved techniques for training gans. *Advances in neural information processing systems*, 29, 2016.
- Gabriel Sarch, Snigdha Saha, Naitik Khandelwal, Ayush Jain, Michael J Tarr, Aviral Kumar, and Katerina Fragkiadaki. Grounded reinforcement learning for visual reasoning. *arXiv preprint arXiv:2505.23678*, 2025.
- John Schulman, Philipp Moritz, Sergey Levine, Michael Jordan, and Pieter Abbeel. High-dimensional continuous control using generalized advantage estimation. *arXiv preprint arXiv:1506.02438*, 2015.
- John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.
- Hao Shao, Shengju Qian, Han Xiao, Guanglu Song, Zhuofan Zong, Letian Wang, Yu Liu, and Hongsheng Li. Visual cot: Unleashing chain-of-thought reasoning in multi-modal language models. *arXiv preprint arXiv:2403.16999*, 2024a.

-
- Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, YK Li, Y Wu, et al. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024b.
- Chuming Shen, Wei Wei, Xiaoye Qu, and Yu Cheng. Satori-r1: Incentivizing multimodal reasoning with spatial grounding and verifiable rewards. *arXiv preprint arXiv:2505.19094*, 2025a.
- Haozhan Shen, Peng Liu, Jingcheng Li, Chunxin Fang, Yibo Ma, Jiajia Liao, Qiaoli Shen, Zilun Zhang, Kangjia Zhao, Qianqian Zhang, et al. Vlm-r1: A stable and generalizable r1-style large vision-language model. *arXiv preprint arXiv:2504.07615*, 2025b.
- Yucheng Shi, Wenhao Yu, Zaitang Li, Yonglin Wang, Hongming Zhang, Ninghao Liu, Haitao Mi, and Dong Yu. Mobilegui-r1: Advancing mobile gui agent through reinforcement learning in online environment. *arXiv preprint arXiv:2507.05720*, 2025.
- Junyang Shu, Zhiwei Lin, and Yongtao Wang. Rftf: Reinforcement fine-tuning for embodied agents with temporal feedback. *arXiv preprint arXiv:2505.19767*, 2025.
- Amanpreet Singh, Vivek Natarajan, Meet Shah, Yu Jiang, Xinlei Chen, Dhruv Batra, Devi Parikh, and Marcus Rohrbach. Towards vqa models that can read. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 8317–8326, 2019.
- Alex Su, Haozhe Wang, Weimin Ren, Fangzhen Lin, and Wenhui Chen. Pixel reasoner: Incentivizing pixel-space reasoning with curiosity-driven reinforcement learning. *arXiv preprint arXiv:2505.15966*, 2025a.
- Zhaochen Su, Linjie Li, Mingyang Song, Yunzhuo Hao, Zhengyuan Yang, Jun Zhang, Guanjie Chen, Jiawei Gu, Juntao Li, Xiaoye Qu, et al. Openthinking: Learning to think with images via visual tool reinforcement learning. *arXiv preprint arXiv:2505.08617*, 2025b.
- Zhiqing Sun, Sheng Shen, Shengcao Cao, Haotian Liu, Chunyuan Li, Yikang Shen, Chuang Gan, Liang-Yan Gui, Yu-Xiong Wang, Yiming Yang, et al. Aligning large multimodal models with factually augmented rlhf. *arXiv preprint arXiv:2309.14525*, 2023.
- Huajie Tan, Yuheng Ji, Xiaoshuai Hao, Minglan Lin, Pengwei Wang, Zhongyuan Wang, and Shanghang Zhang. Reason-rft: Reinforcement fine-tuning for visual reasoning. *arXiv preprint arXiv:2503.20752*, 2025a.
- Shuhan Tan, Kairan Dou, Yue Zhao, and Philipp Krähenbühl. Interactive post-training for vision-language-action models. *arXiv preprint arXiv:2505.17016*, 2025b.
- Jiaqi Tang, Yu Xia, Yi-Feng Wu, Yuwei Hu, Yuhui Chen, Qing-Guo Chen, Xiaogang Xu, Xiangyu Wu, Hao Lu, Yanqing Ma, et al. Lpo: Towards accurate gui agent interaction via location preference optimization. *arXiv preprint arXiv:2506.09373*, 2025.
- Shulin Tian, Ruiqi Wang, Hongming Guo, Penghao Wu, Yuhao Dong, Xiuying Wang, Jingkan Yang, Hao Zhang, Hongyuan Zhu, and Ziwei Liu. Ego-r1: Chain-of-tool-thought for ultra-long egocentric video reasoning, 2025.
- Mert Unsal and Aylin Akkus. Easyarc: Evaluating vision language models on true visual reasoning. *arXiv preprint arXiv:2506.11595*, 2025.
- Thomas Unterthiner, Sjoerd Van Steenkiste, Karol Kurach, Raphaël Marinier, Marcin Michalski, and Sylvain Gelly. Fvd: A new metric for video generation. 2019.
- Ashwin Vinod, Shrey Pandit, Aditya Vavre, and Linshen Liu. Egovlm: Policy optimization for egocentric video understanding. *arXiv preprint arXiv:2506.03097*, 2025.
- Bram Wallace, Meihua Dang, Rafael Rafailov, Linqi Zhou, Aaron Lou, Senthil Purushwalkam, Stefano Ermon, Caiming Xiong, Shafiq Joty, and Nikhil Naik. Diffusion model alignment using direct preference optimization. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8228–8238, 2024.

-
- Zhongwei Wan, Zhihao Dou, Che Liu, Yu Zhang, Dongfei Cui, Qinjian Zhao, Hui Shen, Jing Xiong, Yi Xin, Yifan Jiang, et al. Srpo: Enhancing multimodal llm reasoning via reflection-aware reinforcement learning. *arXiv preprint arXiv:2506.01713*, 2025.
- Bohan Wang, Zhongqi Yue, Fengda Zhang, Shuo Chen, Li'an Bi, Junzhe Zhang, Xue Song, Kennard Yanting Chan, Jiachun Pan, Weijia Wu, et al. Discrete visual tokens of autoregression, by diffusion, and for reasoning. *arXiv e-prints*, pp. arXiv-2505, 2025a.
- Jiaqi Wang, Kevin Qinghong Lin, James Cheng, and Mike Zheng Shou. Think or not? selective reasoning via reinforcement learning for vision-language models. *arXiv preprint arXiv:2505.16854*, 2025b.
- Jiayu Wang, Yifei Ming, Zhenmei Shi, Vibhav Vineet, Xin Wang, Yixuan Li, and Neel Joshi. Is a picture worth a thousand words? delving into spatial reasoning for vision language models. In *The Thirty-Eighth Annual Conference on Neural Information Processing Systems*, 2024a.
- Junke Wang, Zhi Tian, Xun Wang, Xinyu Zhang, Weilin Huang, Zuxuan Wu, and Yu-Gang Jiang. Simplear: Pushing the frontier of autoregressive visual generation through pretraining, sft, and rl. *arXiv preprint arXiv:2504.11455*, 2025c.
- Ke Wang, Juntong Pan, Linda Wei, Aojun Zhou, Weikang Shi, Zimu Lu, Han Xiao, Yunqiao Yang, Houxing Ren, Mingjie Zhan, and Hongsheng Li. Mathcoder-VL: Bridging vision and code for enhanced multimodal mathematical reasoning. In *The 63rd Annual Meeting of the Association for Computational Linguistics*, 2025d. URL <https://openreview.net/forum?id=nvvtX1imAb>.
- Peiyao Wang and Haibin Ling. Svqa-r1: Reinforcing spatial reasoning in mllms via view-consistent reward optimization. *arXiv preprint arXiv:2506.01371*, 2025.
- Peiyu Wang, Yichen Wei, Yi Peng, Xiaokun Wang, Weijie Qiu, Wei Shen, Tianyidan Xie, Jiangbo Pei, Jianhao Zhang, Yunzhuo Hao, et al. Skywork r1v2: Multimodal hybrid reinforcement learning for reasoning. *arXiv preprint arXiv:2504.16656*, 2025e.
- Qiuchen Wang, Ruixue Ding, Yu Zeng, Zehui Chen, Lin Chen, Shihang Wang, Pengjun Xie, Fei Huang, and Feng Zhao. Vrag-rl: Empower vision-perception-based rag for visually rich information understanding via iterative reasoning with reinforcement learning. *arXiv preprint arXiv:2505.22019*, 2025f.
- Xinlong Wang, Xiaosong Zhang, Zhengxiong Luo, Quan Sun, Yufeng Cui, Jinsheng Wang, Fan Zhang, Yueze Wang, Zhen Li, Qiyang Yu, et al. Emu3: Next-token prediction is all you need. *arXiv preprint arXiv:2409.18869*, 2024b.
- Xiyao Wang, Zhengyuan Yang, Chao Feng, Yongyuan Liang, Yuhang Zhou, Xiaoyu Liu, Ziyi Zang, Ming Li, Chung-Ching Lin, Kevin Lin, et al. Vicrit: A verifiable reinforcement learning proxy task for visual perception in vlms. *arXiv preprint arXiv:2506.10128*, 2025g.
- Ye Wang, Ziheng Wang, Boshen Xu, Yang Du, Kejun Lin, Zihan Xiao, Zihao Yue, Jianzhong Ju, Liang Zhang, Dingyi Yang, Xiangnan Fang, Zewen He, Zhenbo Luo, Wenxuan Wang, Junqi Lin, Jian Luan, and Qin Jin. Time-r1: Post-training large vision language model for temporal video grounding. *arXiv preprint arXiv:2503.13377*, 2025h.
- Yibin Wang, Zhimin Li, Yuhang Zang, Chunyu Wang, Qinglin Lu, Cheng Jin, and Jiaqi Wang. Unified multimodal chain-of-thought reward model through reinforcement fine-tuning. *arXiv preprint arXiv:2505.03318*, 2025i.
- Yibin Wang, Yuhang Zang, Hao Li, Cheng Jin, and Jiaqi Wang. Unified reward model for multimodal understanding and generation. *arXiv preprint arXiv:2503.05236*, 2025j.
- Zhou Wang, Alan C Bovik, Hamid R Sheikh, and Eero P Simoncelli. Image quality assessment: from error visibility to structural similarity. *IEEE transactions on image processing*, 13(4):600–612, 2004.

-
- Zifu Wang, Junyi Zhu, Bo Tang, Zhiyu Li, Feiyu Xiong, Jiaqian Yu, and Matthew B Blaschko. Jigsaw-r1: A study of rule-based visual reinforcement learning with jigsaw puzzles. *arXiv preprint arXiv:2505.23590*, 2025k.
- Fanyue Wei, Wei Zeng, Zhenyang Li, Dawei Yin, Lixin Duan, and Wen Li. Powerful and flexible: Personalized text-to-image generation via reinforcement learning. In *European Conference on Computer Vision*, pp. 394–410. Springer, 2024.
- Junfei Wu, Jian Guan, Kaituo Feng, Qiang Liu, Shu Wu, Liang Wang, Wei Wu, and Tieniu Tan. Reinforcing spatial reasoning in vision-language models with interwoven thinking and visual drawing. *arXiv preprint arXiv:2506.09965*, 2025a.
- Mingrui Wu, Lu Wang, Pu Zhao, Fangkai Yang, Jianjin Zhang, Jianfeng Liu, Yuefeng Zhan, Weihao Han, Hao Sun, Jiayi Ji, et al. Reprompt: Reasoning-augmented reprompting for text-to-image generation via reinforcement learning. *arXiv preprint arXiv:2505.17540*, 2025b.
- Tianhe Wu, Jian Zou, Jie Liang, Lei Zhang, and Kede Ma. Visualquality-r1: Reasoning-induced image quality assessment via reinforcement learning to rank. *arXiv preprint arXiv:2505.14460*, 2025c.
- Weijia Wu, Zhuang Li, Yefei He, Mike Zheng Shou, Chunhua Shen, Lele Cheng, Yan Li, Tingting Gao, and Di Zhang. Paragraph-to-image generation with information-enriched diffusion model. *International Journal of Computer Vision*, pp. 1–22, 2025d.
- Xiaoshi Wu, Yiming Hao, Keqiang Sun, Yixiong Chen, Feng Zhu, Rui Zhao, and Hongsheng Li. Human preference score v2: A solid benchmark for evaluating human preferences of text-to-image synthesis. *arXiv preprint arXiv:2306.09341*, 2023a.
- Xiaoshi Wu, Keqiang Sun, Feng Zhu, Rui Zhao, and Hongsheng Li. Human preference score: Better aligning text-to-image models with human preference. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 2096–2105, 2023b.
- Xun Wu, Shaohan Huang, Guolong Wang, Jing Xiong, and Furu Wei. Boosting text-to-video generative model with mllms feedback. *Advances in Neural Information Processing Systems*, 37:139444–139469, 2024.
- Jiaer Xia, Yuhang Zang, Peng Gao, Yixuan Li, and Kaiyang Zhou. Visionary-r1: Mitigating shortcuts in visual reasoning with reinforcement learning. *arXiv preprint arXiv:2505.14677*, 2025.
- Tong Xiao, Xin Xu, Zhenya Huang, Hongyu Gao, Quan Liu, Qi Liu, and Enhong Chen. Advancing multimodal reasoning capabilities of multimodal large language models via visual perception reward. *arXiv preprint arXiv:2506.07218*, 2025a.
- Zhuo Xiao, Ping Jiang, Mingjie Zhou, Junzi Zhang, Zijian Huang, and Jianfeng Yang. Diffppo: Reinforcement learning fine-tuning of diffusion models for text-to-image generation. In *2024 International Conference on Neuromorphic Computing (ICNC)*, pp. 1–5. IEEE, 2024.
- Zilin Xiao, Jaywon Koo, Siru Ouyang, Jefferson Hernandez, Yu Meng, and Vicente Ordonez. Proxythinker: Test-time guidance through small visual reasoners. *arXiv preprint arXiv:2505.24872*, 2025b.
- LLM-Core-Team Xiaomi. MIMO-VL technical report, 2025. URL <https://arxiv.org/abs/2506.03569>.
- Tianbao Xie, Danyang Zhang, Jixuan Chen, Xiaochuan Li, Siheng Zhao, Ruisheng Cao, Toh J Hua, Zhoujun Cheng, Dongchan Shin, Fangyu Lei, et al. OSWorld: Benchmarking multimodal agents for open-ended tasks in real computer environments. *Advances in Neural Information Processing Systems*, 37:52040–52094, 2024.
- Zhenghao Xing, Xiaowei Hu, Chi-Wing Fu, Wenhao Wang, Jifeng Dai, and Pheng-Ann Heng. Echoink-r1: Exploring audio-visual reasoning in multimodal llms via reinforcement learning. *arXiv preprint arXiv:2505.04623*, 2025.

-
- Jiazheng Xu, Xiao Liu, Yuchen Wu, Yuxuan Tong, Qinkai Li, Ming Ding, Jie Tang, and Yuxiao Dong. Imagereward: Learning and evaluating human preferences for text-to-image generation. *Advances in Neural Information Processing Systems*, 36:15903–15935, 2023.
- Weiye Xu, Jiahao Wang, Weiyun Wang, Zhe Chen, Wengang Zhou, Aijun Yang, Lewei Lu, Houqiang Li, Xiaohua Wang, Xizhou Zhu, Wenhai Wang, Jifeng Dai, and Jinguo Zhu. Visulogic: A benchmark for evaluating visual reasoning in multi-modal large language models. *arXiv preprint arXiv:2504.15279*, 2025a. URL <https://arxiv.org/abs/2504.15279>.
- Yi Xu, Chengzu Li, Han Zhou, Xingchen Wan, Caiqi Zhang, Anna Korhonen, and Ivan Vulić. Visual planning: Let’s think only with images. *arXiv preprint arXiv:2505.11409*, 2025b.
- Zeyue Xue, Jie Wu, Yu Gao, Fangyuan Kong, Lingting Zhu, Mengzhao Chen, Zhiheng Liu, Wei Liu, Qiushan Guo, Weilin Huang, et al. Dancegrp: Unleashing grp on visual generation. *arXiv preprint arXiv:2505.07818*, 2025.
- Qianqi Yan, Yue Fan, Hongquan Li, Shan Jiang, Yang Zhao, Xinze Guan, Ching-Chen Kuo, and Xin Eric Wang. Multimodal inconsistency reasoning (mmir): A new benchmark for multimodal reasoning models, 2025. URL <https://arxiv.org/abs/2502.16033>.
- Hongji Yang, Yucheng Zhou, Wencheng Han, and Jianbing Shen. Self-rewarding large vision-language models for optimizing prompts in text-to-image generation. *arXiv preprint arXiv:2505.16763*, 2025a.
- Jie Yang, Feipeng Ma, Zitian Wang, Dacheng Yin, Kang Rong, Fengyun Rao, and Ruimao Zhang. We-think: Toward general-purpose vision-language reasoning via reinforcement learning. *arXiv preprint arXiv:2506.07905*, 2025b.
- Jihan Yang, Shusheng Yang, Anjali Gupta, Rilyn Han, Li Fei-Fei, and Saining Xie. Thinking in Space: How Multimodal Large Language Models See, Remember and Recall Spaces. *arXiv preprint arXiv:2412.14171*, 2024.
- Ling Yang, Xincheng Zhang, Ye Tian, Chenming Shang, Minghao Xu, Wentao Zhang, and Bin Cui. Hermesflow: Seamlessly closing the gap in multimodal understanding and generation. *arXiv preprint arXiv:2502.12148*, 2025c.
- Qize Yang, Shimin Yao, Weixuan Chen, Shenghao Fu, Detao Bai, Jiaying Zhao, Boyuan Sun, Bowen Yin, Xihan Wei, and Jingren Zhou. Humanomniv2: From understanding to omni-modal reasoning with context. *arXiv preprint arXiv:2506.21277*, 2025d.
- Yan Yang, Dongxu Li, Yutong Dai, Yuhao Yang, Ziyang Luo, Zirui Zhao, Zhiyuan Hu, Junzhe Huang, Amrita Saha, Zeyuan Chen, et al. Gta1: Gui test-time scaling agent. *arXiv preprint arXiv:2507.05791*, 2025e.
- Yi Yang, Xiaoxuan He, Hongkun Pan, Xiyan Jiang, Yan Deng, Xingtao Yang, Haoyu Lu, Dacheng Yin, Fengyun Rao, Minfeng Zhu, et al. R1-onevision: Advancing generalized multimodal reasoning through cross-modal formalization. *arXiv preprint arXiv:2503.10615*, 2025f.
- Huanjin Yao, Qixiang Yin, Jingyi Zhang, Min Yang, Yibo Wang, Wenhao Wu, Fei Su, Li Shen, Minghui Qiu, Dacheng Tao, and Jiaying Huang. R1-sharevl: Incentivizing reasoning capability of multimodal large language models via share-grpo, 2025.
- Junliang Ye, Fangfu Liu, Qixiu Li, Zhengyi Wang, Yikai Wang, Xinzhou Wang, Yueqi Duan, and Jun Zhu. Dreamreward: Text-to-3d generation with human preference. In *European Conference on Computer Vision*, pp. 259–276. Springer, 2024.
- En Yu, Kangheng Lin, Liang Zhao, Jisheng Yin, Yana Wei, Yuang Peng, Haoran Wei, Jianjian Sun, Chunrui Han, Zheng Ge, et al. Perception-r1: Pioneering perception policy with reinforcement learning. *arXiv preprint arXiv:2504.07954*, 2025.

-
- Hangjie Yuan, Shiwei Zhang, Xiang Wang, Yujie Wei, Tao Feng, Yining Pan, Yingya Zhang, Ziwei Liu, Samuel Albanie, and Dong Ni. Instructvideo: Instructing video diffusion models with human feedback. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 6463–6474, 2024.
- Jiakang Yuan, Tianshuo Peng, Yilei Jiang, Yiting Lu, Renrui Zhang, Kaituo Feng, Chaoyou Fu, Tao Chen, Lei Bai, Bo Zhang, et al. Mme-reasoning: A comprehensive benchmark for logical reasoning in mllms. *arXiv preprint arXiv:2505.21327*, 2025a.
- Xinbin Yuan, Jian Zhang, Kaixin Li, Zhuoxuan Cai, Lujian Yao, Jie Chen, Enguang Wang, Qibin Hou, Jinwei Chen, Peng-Tao Jiang, et al. Enhancing visual grounding for gui agents via self-evolutionary reinforcement learning. *arXiv preprint arXiv:2505.12370*, 2025b.
- Zhihao Yuan, Shuyi Jiang, Chun-Mei Feng, Yaolun Zhang, Shuguang Cui, Zhen Li, and Na Zhao. Scene-r1: Video-grounded large language models for 3d scene reasoning without 3d annotations. *arXiv preprint arXiv:2506.17545*, 2025c.
- Xiang Yue, Tianyu Zheng, Yuansheng Ni, Yubo Wang, Kai Zhang, Shengbang Tong, Yuxuan Sun, Botao Yu, Ge Zhang, Huan Sun, Yu Su, Wenhui Chen, and Graham Neubig. Mmmu-pro: A more robust multi-discipline multimodal understanding benchmark. *arXiv preprint arXiv:2409.02813*, 2024.
- Alexey Zakharov and Shimon Whiteson. Goalladder: Incremental goal discovery with vision-language models. *arXiv preprint arXiv:2506.16396*, 2025.
- Yufei Zhan, Ziheng Wu, Yousong Zhu, Rongkun Xue, Ruipu Luo, Zhenghao Chen, Can Zhang, Yifan Li, Zhentao He, Zheming Yang, et al. Gthinker: Towards general multimodal reasoning via cue-guided rethinking. *arXiv preprint arXiv:2506.01078*, 2025a.
- Yufei Zhan, Yousong Zhu, Shurong Zheng, Hongyin Zhao, Fan Yang, Ming Tang, and Jinqiao Wang. Vision-r1: Evolving human-free alignment in large vision-language models via vision-guided reinforcement learning. *arXiv preprint arXiv:2503.18013*, 2025b.
- Bob Zhang, Haoran Li, Tao Zhang, Cilin Yan, Jiayin Cai, Xiaolong Jiang, and Yanbin Hao. Improving the reasoning of multi-image grounding in mllms via reinforcement learning. *arXiv preprint arXiv:2507.00748*, 2025a.
- Danyang Zhang, Situo Zhang, Ziyue Yang, Zichen Zhu, Zihan Zhao, Ruisheng Cao, Lu Chen, and Kai Yu. Progm: Build better gui agents with progress rewards. *arXiv preprint arXiv:2505.18121*, 2025b.
- Ge Zhang, Xinrun Du, Bei Chen, Yiming Liang, Tongxu Luo, Tianyu Zheng, Kang Zhu, Yuyang Cheng, Chunpu Xu, Shuyue Guo, et al. Cmmu: A chinese massive multi-discipline multimodal understanding benchmark. *arXiv preprint arXiv:2401.11944*, 2024a.
- Hongyin Zhang, Zifeng Zhuang, Han Zhao, Pengxiang Ding, Hongchao Lu, and Donglin Wang. Reinbot: Amplifying robot visual-language manipulation with reinforcement learning. *arXiv preprint arXiv:2505.07395*, 2025c.
- Jipeng Zhang, Kehao Miao, Renjie Pi, Zhaowei Wang, Runtao Liu, Rui Pan, and Tong Zhang. Vlgem: Enhancing vision-language verification via vision experts and iterative training. *arXiv preprint arXiv:2506.13888*, 2025d.
- Jiwen Zhang, Jihao Wu, Yihua Teng, Minghui Liao, Nuo Xu, Xiao Xiao, Zhongyu Wei, and Duyu Tang. Android in the zoo: Chain-of-action-thought for gui agents. *arXiv preprint arXiv:2403.02713*, 2024b.
- Junru Zhang, Lang Feng, Xu Guo, Yuhao Wu, Yabo Dong, and Duanqing Xu. Timemaster: Training time-series multimodal llms to reason via reinforcement learning. *arXiv preprint arXiv:2506.13705*, 2025e.
- Renrui Zhang, Dongzhi Jiang, Yichi Zhang, Haokun Lin, Ziyu Guo, Pengshuo Qiu, Aojun Zhou, Pan Lu, Kai-Wei Chang, Peng Gao, et al. Mathverse: Does your multi-modal llm truly see the diagrams in visual math problems? *arXiv preprint arXiv:2403.14624*, 2024c.

-
- Renrui Zhang, Chengzhuo Tong, Zhizheng Zhao, Ziyu Guo, Haoquan Zhang, Manyuan Zhang, Jiaming Liu, Peng Gao, and Hongsheng Li. Let’s verify and reinforce image generation step by step. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pp. 28662–28672, 2025f.
- Shiduo Zhang, Zhe Xu, Peiju Liu, Xiaopeng Yu, Yuan Li, Qinghui Gao, Zhaoye Fei, Zhangyue Yin, Zuxuan Wu, Yu-Gang Jiang, et al. Vlabench: A large-scale benchmark for language-conditioned robotics manipulation with long-horizon reasoning tasks. *arXiv preprint arXiv:2412.18194*, 2024d.
- Xintong Zhang, Zhi Gao, Bofei Zhang, Pengxiang Li, Xiaowen Zhang, Yang Liu, Tao Yuan, Yuwei Wu, Yunde Jia, Song-Chun Zhu, et al. Chain-of-focus: Adaptive visual search and zooming for multimodal reasoning via rl. *arXiv preprint arXiv:2505.15436*, 2025g.
- Xuanyu Zhang, Weiqi Li, Shijie Zhao, Junlin Li, Li Zhang, and Jian Zhang. Vq-insight: Teaching vlms for ai-generated video quality understanding via progressive visual reinforcement learning. *arXiv preprint arXiv:2506.18564*, 2025h.
- Yu Zhang, Yunqi Li, Yifan Yang, Rui Wang, Yuqing Yang, Dai Qi, Jianmin Bao, Dongdong Chen, Chong Luo, and Lili Qiu. Reasongen-rl: Cot for autoregressive image generation models through sft and rl. *arXiv preprint arXiv:2505.24875*, 2025i.
- Zhizheng Zhang, Wenxuan Xie, Xiaoyi Zhang, and Yan Lu. Reinforced ui instruction grounding: Towards a generic ui task automation api. *arXiv preprint arXiv:2310.04716*, 2023.
- Zhong Zhang, Yaxi Lu, Yikun Fu, Yupeng Huo, Shenzhi Yang, Yesai Wu, Han Si, Xin Cong, Haotian Chen, Yankai Lin, et al. Agentcpm-gui: Building mobile-use agents with reinforcement fine-tuning. *arXiv preprint arXiv:2506.01391*, 2025j.
- Han Zhao, Wenxuan Song, Donglin Wang, Xinyang Tong, Pengxiang Ding, Xuelian Cheng, and Zongyuan Ge. More: Unlocking scalability in reinforcement learning for quadruped vision-language-action models. *arXiv preprint arXiv:2503.08007*, 2025.
- Ziwei Zheng, Michael Yang, Jack Hong, Chenxiao Zhao, Guohai Xu, Le Yang, Chao Shen, and Xing Yu. Deepeyes: Incentivizing "thinking with images" via reinforcement learning. *arXiv preprint arXiv:2505.14362*, 2025.
- Artem Zholus, Maksim Kuznetsov, Roman Schutski, Rim Shayakhmetov, Daniil Polykovskiy, Sarath Chandar, and Alex Zhavoronkov. Bindgpt: A scalable framework for 3d molecular design via language modeling and reinforcement learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pp. 26083–26091, 2025.
- Hao Zhong, Muzhi Zhu, Zongze Du, Zheng Huang, Canyu Zhao, Mingyu Liu, Wen Wang, Hao Chen, and Chunhua Shen. Omni-rl: Reinforcement learning for omnimodal reasoning via two-system collaboration. *arXiv preprint arXiv:2505.20256*, 2025.
- Guanghao Zhou, Panjia Qiu, Cen Chen, Jie Wang, Zheming Yang, Jian Xu, and Minghui Qiu. Reinforced mllm: A survey on rl-based reasoning in multimodal large language models. *arXiv preprint arXiv:2504.21277*, 2025a.
- Shijie Zhou, Ruiyi Zhang, Huaisheng Zhu, Branislav Kveton, Yufan Zhou, Jiuxiang Gu, Jian Chen, and Changyou Chen. Multimodal llms as customized reward models for text-to-image generation, 2025b. URL <https://arxiv.org/abs/2507.21391>.
- Shuyan Zhou, Frank F Xu, Hao Zhu, Xuhui Zhou, Robert Lo, Abishek Sridhar, Xianyi Cheng, Tianyue Ou, Yonatan Bisk, Daniel Fried, et al. Webarena: A realistic web environment for building autonomous agents. *arXiv preprint arXiv:2307.13854*, 2023.
- Zhenglin Zhou, Xiaobo Xia, Fan Ma, Hehe Fan, Yi Yang, and Tat-Seng Chua. Dreamdpo: Aligning text-to-3d generation with human preferences via direct preference optimization. *arXiv preprint arXiv:2502.04370*, 2025c.

-
- Bingwen Zhu, Yudong Jiang, Baohan Xu, Siqian Yang, Mingyu Yin, Yidi Wu, Huyang Sun, and Zuxuan Wu. Aligning anime video generation with human feedback. *arXiv preprint arXiv:2504.10044*, 2025a.
- Liyun Zhu, Qixiang Chen, Xi Shen, and Xiaodong Cun. Vau-r1: Advancing video anomaly understanding via reinforcement fine-tuning. *arXiv preprint arXiv:2505.23504*, 2025b.
- Muzhi Zhu, Yuzhuo Tian, Hao Chen, Chunluan Zhou, Qingpei Guo, Yang Liu, Ming Yang, and Chunhua Shen. Segagent: Exploring pixel understanding capabilities in mllms by imitating human annotator trajectories. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pp. 3686–3696, 2025c.
- Muzhi Zhu, Hao Zhong, Canyu Zhao, Zongze Du, Zheng Huang, Mingyu Liu, Hao Chen, Cheng Zou, Jingdong Chen, Ming Yang, et al. Active-o3: Empowering multimodal large language models with active perception via grpo. *arXiv preprint arXiv:2505.21457*, 2025d.
- Xianwei Zhuang, Yuxin Xie, Yufan Deng, Dongchao Yang, Liming Liang, Jinghan Ru, Yuguo Yin, and Yuexian Zou. Vargpt-v1. 1: Improve visual autoregressive large unified model via iterative instruction tuning and reinforcement learning. *arXiv preprint arXiv:2504.02949*, 2025.
- Chengke Zou, Xingang Guo, Rui Yang, Junyu Zhang, Bin Hu, and Huan Zhang. Dynamath: A dynamic visual benchmark for evaluating mathematical reasoning robustness of vision language models, 2024.
- Xiandong Zou, Ruihao Xia, Hongsong Wang, and Pan Zhou. Dreamcs: Geometry-aware text-to-3d generation with unpaired 3d reward supervision. *arXiv preprint arXiv:2506.09814*, 2025.