

# Visualising GAP objects: current status and the future

Lukas Schnelle

GAPDays Summer 2026

Currently there are multiple packages, which provide functionality to visualise GAP objects.

Currently there are multiple packages, which provide functionality to visualise GAP objects.

# Background

Currently there are multiple packages, which provide functionality to visualise GAP objects.

# Motivation

Last GAPDays (Summer 2025) James Mitchell and I noticed that we both work on packages which can visualise graphs in tikz with some duplicate functionality.

Currently there are multiple packages, which provide functionality to visualise GAP objects.


Last GAPDays (Summer 2025) James Mitchell and I noticed that we both work on packages which can visualise graphs in tikz with some duplicate functionality.


First we will give a (likely incomplete) overview of them with some examples.


# XGAP (By Frank Celler and Max Neunhöffer)

Provides a GUI in which e.g. subgroup lattices can be investigated.  
Needs to be started separately.


```
schnellecom@CURIE:/opt/gap/pkg/sgap$ ./sgap.sh
```











## Advantages

- Direct GUI to use
- Freely movable visualisation

## Advantages

- Direct GUI to use
- Freely movable visualisation

## Challenges

- Needs to be started standalone
- Needs to be adjusted to every OS

# francy (by Manuel Martins)

## Idea

Allow the XGAP system to run in a Jupyter Notebook.

## Status

I was not able to get this running.

```

LoadPackage("digraphs"); LoadPackage("francy");

G := SymmetricGroup(3); as := AllSubgroups(G); nodes := [];
d := Digraph(as, {H, K} -> IsSubgroup(H, K));

vertices := DigraphVertices(d); edges := DigraphEdges(d);

canvas := Canvas(Concatenation("Subgroups Digraph of ",
    String(G)));
graph := Graph(GraphType.DIRECTED);
Add(canvas, graph);

customMessage := FrancyMessage(FrancyMessageType.INFO,
    "Simple Groups", "A group is simple if it is nontrivial
    and has no nontrivial normal subgroups.");

IsGroupSimple := function(i)
    Add(canvas, simpleGroupMessage);
    if IsSimpleGroup(as[i]) then
        Add(canvas, FrancyMessage("Simple",
            Concatenation("The vertex ", String(i),
                ", representing the subgroup ", String(as[i]),
                ", is simple.")));
    else
        Add(canvas, FrancyMessage("Not Simple",
            Concatenation("The vertex ", String(i),
                ", representing the subgroup ", String(as[i]),
                ", is not simple.")));
    fi;
    return Draw(canvas);
end;

```

```
for i in vertices do
  nodes[i] := Shape(ShapeType.CIRCLE, String(i));
  Add(nodes[i], Menu("Is this subgroup simple?",
    Callback(IsGroupSimple, [i])));
  Add(graph, nodes[i]);
od;

for i in edges do
  Add(graph, Link(nodes[i[1]], nodes[i[2]]));
od;

Draw(canvas);
```

(from [1])


Francy

Subgroups Digraph of  $\text{SymmetricGroup}([1..3])$ 

**Simple Groups** A group is simple if it is nontrivial and has no nontrivial normal subgroups.

**Simple** The vertex 2, representing the subgroup  $\text{Group}([2,3])$ , is simple.

**Not Simple** The vertex 6, representing the subgroup  $\text{SymmetricGroup}([1..3])$ , is not simple.



(from [1])

## Advantages

- Runs in browser
- Highly customisable

## Challenges

- Needs additional installation of Jupyter



## Advantages

- Runs in browser
- Highly customisable

## Challenges

- Needs additional installation of Jupyter

## Related packages


- jupyterviz
- semigroupviz

# SgpViz (by Manuel Delgado and José João Morais)

## Semigroup visualisation

- Can visualise e.g. Cayley graphs
- Using graphviz

```
gap> f := FreeMonoid("a","b");;
gap> a := GeneratorsOfMonoid( f )[ 1 ];;
gap> b := GeneratorsOfMonoid( f )[ 2 ];;
gap> r:=[[a^3,a^2], [a^2*b,a^2], [b*a^2,a^2], [b^2,a^2], [a*b*a,a], [b*a*b,b] ];;
gap> b21:= f/r;
<fp monoid on the generators [ a, b ]>
gap> DrawCayleyGraph(b21);
```



## Advantages

- Uses graphviz standard
- Outputs PDFs


## Challenges

- Needs additional installation of graphviz on system


# Automata (by Manuel Delgado, Steve Linton and José João Morais)

# Automata (by Manuel Delgado, Steve Linton and José João Morais)

```
gap> x:=Automaton("det",3,2,[ [ 2, 3, 0 ], [ 0, 1, 2 ] ],[ 1 ],[ 1, 2, 3 ]);;  
gap> DrawAutomaton(x);
```




```
gap> DrawAutomaton(x, ["st 1", "2", "C"]);
```





```
gap> DrawAutomaton(x,["st 1", "2", "c"],[[2],[1,3]]);
```



## Advantages

- Uses graphviz standard
- Outputs PDFs

## Advantages

- Uses graphviz standard
- Outputs PDFs

## Challenges

- Needs additional installation of graphviz on system

# graphviz (by James D. Mitchell and Matthew Pancer)

## Digraphs visualisation

- (some work on) having Digraphs package as extension
- Also uses graphviz standard


# graphviz (by James D. Mitchell and Matthew Pancer)

## Digraphs visualisation

- (some work on) having Digraphs package as extension
- Also uses graphviz standard

```
gap> D := Digraph([], [1], [2], [2]);  
<immutable digraph with 4 vertices, 3 edges>  
gap> SetDigraphVertexLabels(D,  
> ["Digraphs (GAP)",  
> "GAP kernel extension (C)",  
> "bliss (C++)",  
> "libplanarity (C)"]);  
gap> gv := GraphvizVertexLabelledDigraph(D);  
<graphviz digraph "hgn" with 4 nodes and 3 edges>  
gap> GraphvizSetAttr(gv, "node [shape=box]");  
<graphviz digraph "hgn" with 4 nodes and 3 edges>  
gap> GraphvizSetAttr(gv, "rankdir", "BT");  
<graphviz digraph "hgn" with 4 nodes and 3 edges>
```

```
gap> Print(AsString(gv), "\n");  
//dot  
digraph hgn {  
    node [shape=box] rankdir=BT  
    1 [label="Digraphs (GAP)"]  
    2 [label="GAP kernel extension (C)"]  
    3 [label="bliss (C++)"]  
    4 [label="libplanarity (C)"]  
    2 -> 1  
    3 -> 2  
    4 -> 2  
}
```



## Advantages

- Uses graphviz standard
- Structure so it can work with other packages
- Highly customisable
- Visualisations can be iterated

## Challenges

- Needs GAP function for everything in graphviz standard
- No immediate way to show results without additional installation on system

```
gap> Splash(gv);  
Error: /tmp/gaptempdirv6HuGo/hgn.dot: syntax error in line 4 near '('
```

# IntPic (by Manuel Delgado)

Visualises arrays of integers

Can be used to highlight different properties in large number of colours.



# IntPic (by Manuel Delgado)

Visualises arrays of integers

Can be used to highlight different properties in large number of colours.

```
gap> rg := [-5..23];;  
gap> len := 10;;  
gap> hg := rec();;  
gap> hg.highlights:=[[2,3,5,7],[11,13,17,19],[23]];;  
gap> tkz := IP_TikzArrayOfIntegers(rg,len,hg);;  
gap> Print(tkz);
```

```
gap> Print(tkz);
%tikz
\begin{tikzpicture}[every node/.style={draw,scale=1pt,
minimum width=20pt,inner sep=3pt,
line width=0pt,draw=black}]
\matrix[row sep=2pt,column sep=2pt]
{\node[]{}{15};&
\node[]{}{16};&
\node[fill=green]{}{17};&
\node[]{}{18};&
\node[fill=green]{}{19};&
\node[]{}{20};&
\node[]{}{21};&
\node[]{}{22};&
\node[fill=blue]{}{23};\\
\node[fill=red]{}{5};&
\node[]{}{6};&
\node[fill=red]{}{7};&
\node[]{}{8};&
\node[]{}{9};&
\node[]{}{10};&
\node[fill=green]{}{11};&
\node[]{}{12};&
\node[fill=green]{}{13};&
\node[]{}{14};\\
\node[]{}{-5};&
\node[]{}{-4};&
\node[]{}{-3};&
\node[]{}{-2};&
\node[]{}{-1};&
\node[]{}{0};&
\node[]{}{1};&
\node[fill=red]{}{2};&
\node[fill=red]{}{3};&
\node[]{}{4};\\
};
\end{tikzpicture}
```

|    |    |    |    |    |    |    |    |    |    |
|----|----|----|----|----|----|----|----|----|----|
| 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 |    |
| 5  | 6  | 7  | 8  | 9  | 10 | 11 | 12 | 13 | 14 |
| -5 | -4 | -3 | -2 | -1 | 0  | 1  | 2  | 3  | 4  |

## Advantages

- Uses tikz
- Highly customisable

## Advantages

- Uses tikz
- Highly customisable

## Challenges

- No immediate way to show results without compiling them

# GAPic (by Alice C. Niemeyer and many more)

## Visualising triangulated polyhedra

- Came from the `SimplicialSurfaces` package
- Expanded functionality like general polyhedra
- Has `SimplicialSurfaces` package as extension

```
gap> oct := Octahedron();;
gap> verticesPositions := [
> [ 0, 0, Sqrt(2.) ],
> [ 1, 1, 0 ],
> [ 1, -1, 0 ],
> [ -1, -1, 0 ],
> [ -1, 1, 0 ],
> [ 0, 0, -Sqrt(2.) ] ];;
gap> printRecord := SetVertexCoordinates3D(oct, verticesPositions, rec());;
gap> DrawComplexToJavaScript(oct, "octahedron.html", printRecord);;
```

Demonstration in browser

```
gap> oct := Octahedron();;
gap> verticesPositions := [
> [ 0, 0, Sqrt(2.) ],
> [ 1, 1, 0 ],
> [ 1, -1, 0 ],
> [ -1, -1, 0 ],
> [ -1, 1, 0 ],
> [ 0, 0, -Sqrt(2.) ] ];;
gap> printRecord := SetVertexCoordinates3D(oct, verticesPositions, rec());;
gap> DrawComplexToJavaScript(oct, "octahedron.html", printRecord);;
```

## Demonstration in browser

```
gap> printRecord := SetFaceColour(oct, 3, "0x00FF00", printRecord);
rec( edgeThickness := 0.03, faceColours := [ , "0x00FF00" ],
  vertexCoordinates3D := [ [ 0, 0, 1.41421 ], [ 1, 1, 0 ], [ 1, -1, 0 ], [ -1, -1, 0 ], [ -1, 1, 0 ],
    [ 0, 0, -1.41421 ] ] )
gap> DrawComplexToJavaScript(oct, "octahedron-coloured.html", printRecord);;
```

## Advantages

- Results can be opened with any browser
- High interactivity
- Results can be iterated
- Can use parameterised coordinates

## Challenges

- Every new feature needs own GAP function
- No immediate way to show results without generating them



There are certainly more packages that include some visualisation which I did not mention.

## (My) goals

Make visualisations in GAP

- more intuitive → accessible
- sustainable
- more visible

## (My) goals

Make visualisations in GAP

- more intuitive → accessible
- sustainable
- more visible

## Possible methods

- Use of package extensions?
- Use of existing standards

- What are your experiences with visualisations in GAP?
- What do you expect from a visualisation functionality?
- Is there anything you want to visualise but are not able to visualise yet?