



# **EK-TM4C1294XL-BOOST- DLPTRF7970ABP Firmware Development Package USER'S GUIDE**

---

# Copyright

Copyright © 2013-2015 Texas Instruments Incorporated. All rights reserved. Tiva and TivaWare are trademarks of Texas Instruments Instruments. ARM and Thumb are registered trademarks and Cortex is a trademark of ARM Limited. Other names and brands may be claimed as the property of others.

 Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this document.

Texas Instruments  
108 Wild Basin, Suite 350  
Austin, TX 78746  
[www.ti.com/tiva-c](http://www.ti.com/tiva-c)



## Revision Information

This is version 2.1.1.71 of this document, last updated on May 07, 2015.

# Table of Contents

<b>Copyright</b>	<b>2</b>
<b>Revision Information</b>	<b>2</b>
<b>1 Introduction</b>	<b>5</b>
<b>2 Example Applications</b>	<b>7</b>
2.1 NFC P2P Demo (nfc_p2p_demo)	7
<b>3 Buttons Driver</b>	<b>9</b>
3.1 Introduction	9
3.2 API Functions	9
3.3 Programming Example	10
<b>4 Pinout Module</b>	<b>13</b>
4.1 Introduction	13
4.2 API Functions	13
4.3 Programming Example	14
<b>IMPORTANT NOTICE</b>	<b>16</b>



# 1 Introduction

The Texas Instruments® Tiva™ EK-TM4C1294XL-BOOST-DLPTRF7970ABP evaluation board (Tiva C Series TM4C1294 Connected LaunchPad) is a low cost platform that can be used for software development and prototyping a hardware design. A variety of BoosterPacks are available to quickly extend the LaunchPad's features.

The EK-TM4C1294XL-BOOST-DLPTRF7970ABP includes a Tiva ARM® Cortex™-M4-based microcontroller and the following features:

- Tiva™ TM4C1294NCPDT microcontroller
- Ethernet connector
- USB OTG connector
- 2 user buttons
- 4 User LEDs
- 2 BoosterPack XL connectors
- On-board In-Circuit Debug Interface (ICDI)
- Power supply option from USB ICDI connection, USB OTG connection or external power connection
- Shunt jumper for microcontroller current consumption measurement

This document describes the board-specific drivers and example applications that are provided for this development board.



## 2 Example Applications

The example applications show how to utilize features of the EK-TM4C1294XL development board. Examples are included to show how to use many of the general features of the Tiva microcontroller, as well as the features that are unique to this development board.

A number of drivers are provided to make it easier to use the features of the EK-TM4C1294XL. These drivers also contain low-level code that make use of the TivaWare peripheral driver library and utilities.

There is an IAR workspace file (`ek-tm4c1294xl-boost-dlptrf7970abp.eww`) that contains the peripheral driver library project, along with all of the board example projects, in a single, easy-to-use workspace for use with Embedded Workbench.

There is a Keil multi-project workspace file (`ek-tm4c1294xl-boost-dlptrf7970abp.mpw`) that contains the peripheral driver library project, along with all of the board example projects, in a single, easy-to-use workspace for use with uVision.

All of these examples reside in the `examples/boards/ek-tm4c1294xl-boost-dlptrf7970abp` subdirectory of the firmware development package source distribution.

### 2.1 NFC P2P Demo (`nfc_p2p_demo`)

This example application demonstrates the operation of the Tiva C Series evaluation kit with the TRF7970ABP BoosterPack as a NFC P2P device.

The application supports reading and writing Text, URI, and SmartPoster Tags. The application gets a raw message buffer from the TRF79x0 stack, decodes the information to recognized tag types, then re-encodes the data to a buffer to be sent back out. Pressing switch SW1 sends a URI message with a link to the Tiva C series Launchpad website. Pressing switch SW2 echoes back the last tag received. If no tag has been received then this button does nothing. Full debug information is given across the UART0 channel to aid in NFC P2P development.

This application assumes the TRF7970ABP is connected to the boosterpack 2 headers on the development kit. To use the boosterpack 1 headers you will need to toggle the `TRF79X0_USE_BOOSTERPACK_2` define in `trf79x0_hw.h` and recompile the application.

For more information on NFC please see the full NFC specification list at [http://www.nfc-forum.org/specs/spec\\_list/](http://www.nfc-forum.org/specs/spec_list/).





## 3 Buttons Driver

Introduction .....	9
API Functions .....	9
Programming Example .....	10

### 3.1 Introduction

The buttons driver provides functions to make it easy to use the push buttons on the EK-TM4C1294XL evaluation board. The driver provides a function to initialize all the hardware required for the buttons, and features for debouncing and querying the button state.

This driver is located in `examples/boards/ek-tm4c1294xl-boost-dlpt7970abp/drivers`, with `buttons.c` containing the source code and `buttons.h` containing the API declarations for use by applications.

### 3.2 API Functions

#### Functions

- void `ButtonsInit` (void)
- uint8\_t `ButtonsPoll` (uint8\_t \*pui8Delta, uint8\_t \*pui8RawState)

#### 3.2.1 Function Documentation

##### 3.2.1.1 ButtonsInit

Initializes the GPIO pins used by the board pushbuttons.

**Prototype:**

```
void  
ButtonsInit(void)
```

**Description:**

This function must be called during application initialization to configure the GPIO pins to which the pushbuttons are attached. It enables the port used by the buttons and configures each button GPIO as an input with a weak pull-up.

**Returns:**

None.

##### 3.2.1.2 ButtonsPoll

Polls the current state of the buttons and determines which have changed.

**Prototype:**

```
uint8_t
ButtonsPoll(uint8_t *pui8Delta,
            uint8_t *pui8RawState)
```

**Parameters:**

***pui8Delta*** points to a character that will be written to indicate which button states changed since the last time this function was called. This value is derived from the debounced state of the buttons.

***pui8RawState*** points to a location where the raw button state will be stored.

**Description:**

This function should be called periodically by the application to poll the pushbuttons. It determines both the current debounced state of the buttons and also which buttons have changed state since the last time the function was called.

In order for button debouncing to work properly, this function should be called at a regular interval, even if the state of the buttons is not needed that often.

If button debouncing is not required, the caller can pass a pointer for the *pui8RawState* parameter in order to get the raw state of the buttons. The value returned in *pui8RawState* will be a bit mask where a 1 indicates the button is pressed.

**Returns:**

Returns the current debounced state of the buttons where a 1 in the button ID's position indicates that the button is pressed and a 0 indicates that it is released.

## 3.3 Programming Example

The following example shows how to use the buttons driver to initialize the buttons, debounce and read the buttons state.

```
//
// Map Left button to the GPIO Pin 0 of the button port.
//
#define LEFT_BUTTON          GPIO_PIN_0

//
// The button example
//
void
ButtonExample(void)
{
    unsigned char ucDelta, ucState;

    //
    // Initialize the buttons.
    //
    ButtonsInit();

    //
    // From timed processing loop (for example every 10 ms)
    //
    {
        //
        // Poll the buttons. When called periodically this function will
        // run the button debouncing algorithm.
    }
}
```

```
//
ucState = ButtonsPoll(&ucDelta, 0);

//
// Test to see if the SELECT button was pressed and do something
//
if(BUTTON_PRESSED(LEFT_BUTTON, ucState, ucDelta))
{
    //
    // TODO: SELECT button action code
    //
}
}
```



## 4 Pinout Module

Introduction .....	13
API Functions .....	13
Programming Example .....	14

### 4.1 Introduction

The pinout module is a common function for configuring the device pins for use by example applications. The pins are configured into the most common usage; it is possible that some of the pins might need to be reconfigured in order to support more specialized usage.

This driver is located in `examples/boards/ek-tm4c1294xl-boost-dlptrf7970abp/drivers`, with `pinout.c` containing the source code and `pinout.h` containing the API declarations for use by applications.

### 4.2 API Functions

#### Functions

- void [LEDRead](#) (uint32\_t \*pui32LEDValue)
- void [LEDWrite](#) (uint32\_t ui32LEDMask, uint32\_t ui32LEDValue)
- void [PinoutSet](#) (bool bEthernet, bool bUSB)

#### 4.2.1 Function Documentation

##### 4.2.1.1 LEDRead

This function reads the state to the LED bank.

**Prototype:**

```
void  
LEDRead(uint32_t *pui32LEDValue)
```

**Parameters:**

***pui32LEDValue*** is a pointer to where the LED value will be stored.

**Description:**

This function reads the state of the CLP LEDs and stores that state information into the variable pointed to by `pui32LEDValue`.

**Returns:**

None.

#### 4.2.1.2 LEDWrite

This function writes a state to the LED bank.

**Prototype:**

```
void  
LEDWrite(uint32_t ui32LEDMask,  
         uint32_t ui32LEDValue)
```

**Parameters:**

**ui32LEDMask** is a bit mask for which GPIO should be changed by this call.

**ui32LEDValue** is the new value to be applied to the LEDs after the ui32LEDMask is applied.

**Description:**

The first parameter acts as a mask. Only bits in the mask that are set will correspond to LEDs that may change. LEDs with a mask that is not set will not change. This works the same as GPIOPinWrite. After applying the mask the setting for each unmasked LED is written to the corresponding LED port pin via GPIOPinWrite.

**Returns:**

None.

#### 4.2.1.3 PinoutSet

Configures the device pins for the standard usages on the EK-TM4C1294XL.

**Prototype:**

```
void  
PinoutSet(bool bEthernet,  
          bool bUSB)
```

**Parameters:**

**bEthernet** is a boolean used to determine function of Ethernet pins. If true Ethernet pins are configured as Ethernet LEDs. If false GPIO are available for application use.

**bUSB** is a boolean used to determine function of USB pins. If true USB pins are configured for USB use. If false then USB pins are available for application use as GPIO.

**Description:**

This function enables the GPIO modules and configures the device pins for the default, standard usages on the EK-TM4C1294XL. Applications that require alternate configurations of the device pins can either not call this function and take full responsibility for configuring all the device pins, or can reconfigure the required device pins after calling this function.

**Returns:**

None.

## 4.3 Programming Example

The following example shows how to configure the device pins.

```
//  
// The pinout example.  
//  
void  
PinoutExample(void)  
{  
    //  
    // Configure the device pins.  
    // First argument determines whether the Ethernet pins will be configured  
    // in networking mode for this application.  
    // Second argument determines whether the USB pins will be configured for  
    // USB mode for this application.  
    //  
    PinoutSet(true, false);  
}
```

---

# IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as "components") are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have **not** been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.

"So long and thanks for all the fish." - Douglas Adams

## Products

Audio	<a href="http://www.ti.com/audio">www.ti.com/audio</a>
Amplifiers	<a href="http://amplifier.ti.com">amplifier.ti.com</a>
Data Converters	<a href="http://dataconverter.ti.com">dataconverter.ti.com</a>
DLP® Products	<a href="http://www.dlp.com">www.dlp.com</a>
DSP	<a href="http://dsp.ti.com">dsp.ti.com</a>
Clocks and Timers	<a href="http://www.ti.com/clocks">www.ti.com/clocks</a>
Interface	<a href="http://interface.ti.com">interface.ti.com</a>
Logic	<a href="http://logic.ti.com">logic.ti.com</a>
Power Mgmt	<a href="http://power.ti.com">power.ti.com</a>
Microcontrollers	<a href="http://microcontroller.ti.com">microcontroller.ti.com</a>
RFID	<a href="http://www.ti-rfid.com">www.ti-rfid.com</a>
OMAP Applications Processors	<a href="http://www.ti.com/omap">www.ti.com/omap</a>
Wireless Connectivity	<a href="http://www.ti.com/wirelessconnectivity">www.ti.com/wirelessconnectivity</a>

## Applications

Automotive and Transportation	<a href="http://www.ti.com/automotive">www.ti.com/automotive</a>
Communications and Telecom	<a href="http://www.ti.com/communications">www.ti.com/communications</a>
Computers and Peripherals	<a href="http://www.ti.com/computers">www.ti.com/computers</a>
Consumer Electronics	<a href="http://www.ti.com/consumer-apps">www.ti.com/consumer-apps</a>
Energy and Lighting	<a href="http://www.ti.com/energy">www.ti.com/energy</a>
Industrial	<a href="http://www.ti.com/industrial">www.ti.com/industrial</a>
Medical	<a href="http://www.ti.com/medical">www.ti.com/medical</a>
Security	<a href="http://www.ti.com/security">www.ti.com/security</a>
Space, Avionics and Defense	<a href="http://www.ti.com/space-avionics-defense">www.ti.com/space-avionics-defense</a>
Video and Imaging	<a href="http://www.ti.com/video">www.ti.com/video</a>

## TI E2E Community

[e2e.ti.com](http://e2e.ti.com)



---

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2013-2015, Texas Instruments Incorporated