

ADI for Reaction-Diffusion Systems

Generated by Doxygen 1.8.6

Thu Apr 23 2015 14:33:37

Contents

1	Module Index	1
1.1	Modules	1
2	Namespace Index	3
2.1	Namespace List	3
3	Class Index	5
3.1	Class List	5
4	Module Documentation	7
4.1	Diagonals of the matrix.	7
4.1.1	Detailed Description	7
5	Namespace Documentation	9
5.1	TriDiagMatrixSolver Namespace Reference	9
5.1.1	Detailed Description	9
5.1.2	Function Documentation	9
5.1.2.1	solve	9
6	Class Documentation	11
6.1	GrayScott Class Reference	11
6.1.1	Member Function Documentation	11
6.1.1.1	print_fields	11
6.1.1.2	run	11
6.2	TriDiagMatrix Class Reference	11
6.2.1	Constructor & Destructor Documentation	12
6.2.1.1	TriDiagMatrix	12
6.2.1.2	TriDiagMatrix	12
	Index	13

Chapter 1

Module Index

1.1 Modules

Here is a list of all modules:

Diagonals of the matrix.	7
----------------------------------	---

Chapter 2

Namespace Index

2.1 Namespace List

Here is a list of all documented namespaces with brief descriptions:

TriDiagMatrixSolver	9
---	---

Chapter 3

Class Index

3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

GrayScott	11
TriDiagMatrix	11

Chapter 4

Module Documentation

4.1 Diagonals of the matrix.

4.1.1 Detailed Description

They all have the same length ($n_{_}$), but have 0 values where they are out of the matrix. The indices determine the row.

| m0 u0 0 | | l1 m1 u1 | | 0 l2 m2 |

i.e.: $l_{_}[0]$ and $u_{_}[2]$ are 0.

Chapter 5

Namespace Documentation

5.1 TriDiagMatrixSolver Namespace Reference

Functions

- void [solve](#) (const [TriDiagMatrix](#) &mat, const std::vector< double > &rhs, double *result, unsigned int inc)

5.1.1 Detailed Description

Solver for a tridiagonal matrix system.

5.1.2 Function Documentation

5.1.2.1 void TriDiagMatrixSolver::solve (const TriDiagMatrix & *mat*, const std::vector< double > & *rhs*, double * *result*, unsigned int *inc*)

Solve a tridiagonal matrix system.

Parameters

<i>mat</i>	tridiagonal matrix
<i>rhs</i>	right-hand side of the system
<i>result</i>	vector for the result, pointer to the first element to store
<i>inc</i>	increment for the elements of the result

Chapter 6

Class Documentation

6.1 GrayScott Class Reference

Public Member Functions

- **GrayScott** (int N, double L, double dt, double Du, double Dv, double F, double k, int nSteps)
- void [run](#) ()
- void [print_fields](#) (std::string uName, std::string vName)

6.1.1 Member Function Documentation

6.1.1.1 void GrayScott::print_fields (std::string *uName*, std::string *vName*)

Print the fields to the specified file.

Parameters

<i>uName</i>	filename of the file to print u to
<i>vName</i>	filename of the file to print v to

6.1.1.2 void GrayScott::run ()

Run the simulation.

The documentation for this class was generated from the following files:

- grayscott.hpp
- grayscott.cpp

6.2 TriDiagMatrix Class Reference

Public Member Functions

- [TriDiagMatrix](#) ()
- [TriDiagMatrix](#) (int N, double l, double m, double u)
- int **size** () const
- std::vector< double > **getL** () const
- std::vector< double > **getM** () const
- std::vector< double > **getU** () const

Friends

- `std::ostream & operator<< (std::ostream &os, const TriDiagMatrix &matrix)`

6.2.1 Constructor & Destructor Documentation

6.2.1.1 `TriDiagMatrix::TriDiagMatrix ()`

Default constructor

6.2.1.2 `TriDiagMatrix::TriDiagMatrix (int N, double l, double m, double u)`

Construct an object of the type [TriDiagMatrix](#)

Parameters

<i>n</i>	size of the matrix
<i>l</i>	value on the lower diagonal
<i>m</i>	value on the middle diagonal
<i>u</i>	value on the upper diagonal

The documentation for this class was generated from the following files:

- `tridiagmatrix.hpp`
- `tridiagmatrix.cpp`

Index

Diagonals of the matrix., [7](#)

GrayScott, [11](#)

 print_fields, [11](#)

 run, [11](#)

print_fields

 GrayScott, [11](#)

run

 GrayScott, [11](#)

solve

 TriDiagMatrixSolver, [9](#)

TriDiagMatrix, [11](#)

 TriDiagMatrix, [12](#)

 TriDiagMatrix, [12](#)

TriDiagMatrixSolver, [9](#)

 solve, [9](#)