

6.S096 Lecture 5 – Object-Oriented C++

Abstraction, Inheritance, STL

Andre Kessler

January 17, 2014

Outline

- 1 Assignment 2
- 2 Crash course in the STL
- 3 Inheritance
- 4 Pitfalls

Assignment 2

Linked list library (list)

- Writing linked list code that other programs can use
- No memory leaks!

Minimum spanning tree (mst)

- Using the STL
- Implementing an algorithm
- Writing fast C++

Rational numbers library (rational)

- Overloading arithmetic functions
- Edge cases
- Exceptions

Extended: due 1/22 at midnight

Crash course in the STL

<vector>

Remember the Array class we were writing last time? A better version already exists in C++, so we don't need to write it ourselves!

```
#include <vector>
// In our code:
std::vector<int> intArray;
while( /* getting data */ ) {
    intArray.push_back( data );
}
int tenthItem = intArray[9]; // like an array
// Automatically destroys data when done
```

The angle brackets < and > let us specialize this type: we can replace T with any other type T, like `std::vector<T>`.

Crash course in the STL

STL? What's that?

STL stands for Standard Template Library. Containers and algorithms to use on those containers, all with a common interface. Another vector:

```
#include <vector>
#include <string>
// In our code:
std::vector<std::string> stringList;
stringList.push_back( "C99" );
stringList.push_back( "C++03" );
stringList.push_back( "C++11" );
for( auto str : stringList ) { // "range-for"
    std::cout << str << "\n";
}
```

Some (BAD!) code that needs to be refactored

We've got a struct to hold some shape data for different ShapeTypes.

```
// BAD CODE!  
  
enum ShapeType { CIRCLE = 0, SQUARE = 1,  
                 RECTANGLE = 2, TRIANGLE = 3 };  
  
// needs to be big enough to hold the shape  
struct Shape {  
    ShapeType type;  
    double a, b, c, d;  
};
```

And we want a function to compute the area, given a shape.

Some (BAD!) code that needs to be refactored

Without some good object-oriented practices, code like this can become a tangled mess of switch or if/else statements.

```
// BAD CODE!  
double area( const Shape &shape ) {  
    switch( shape.type ) {  
        case CIRCLE: return M_PI * shape.a * shape.a;  
        case SQUARE: return shape.a * shape.a;  
        case RECTANGLE: return shape.a * shape.b;  
        case TRIANGLE: return 0.5 * shape.a * shape.b;  
        default: std::cerr << "Error, invalid shape!\n";  
    }  
    return 0.0;  
}
```

What's so bad?

Any time we want to make a function that works differently on different types of shapes, we need this same switch statement.

Lots of code repetition.

The member variable names do not describe their purpose.

Not extensible: when we add a new shape, we have to modify every one of these functions.

Our refactoring: an abstract class

- Let's create an abstract class Shape. We do this by giving the class some virtual functions; these are functions which child classes can override.
- Could have member variables or not (in this case, we won't)
- Pure virtual functions (the = 0).
- Notice the destructor is virtual.

```
class Shape {  
public:  
    virtual double area() const = 0; //pure virtual  
    virtual ~Shape() {}  
};
```

Inheritance

```
class Shape {  
public:  
    virtual double area() const = 0; //pure virtual  
    virtual ~Shape() {}  
};  
class Circle : public Shape {  
    double _radius;  
public:  
    Circle( double theRadius ) : _radius{theRadius} {}  
    ~Circle() {}  
    inline double radius() const { return _radius; }  
    double area() const { return  
                                _radius * _radius * M_PI; }  
};
```

Closer look at the child class...

- Syntax is `class Derived : public Base`

```
class Circle : public Shape {  
    double _radius;  
public:  
    Circle( double theRadius ) : _radius{theRadius} {}  
    ~Circle() {}  
    inline double radius() const { return _radius; }  
    double area() const { return  
                        _radius * _radius * M_PI; }  
};
```

Know the functions C++ automatically creates!

Looks like a pretty empty class, right?

```
class Empty{};
```

Know the functions C++ automatically creates!

Looks like a pretty empty class, right? **Wrong!**

```
class Empty{  
public:  
    Empty() { /*...*/ } // constructor  
    // copy constructor  
    Empty( const Empty &rhs ) { /*...*/ }  
    // copy assignment  
    Empty& operator=( const Empty& rhs ) { /*...*/ }  
    ~Empty() { /*...*/ } // destructor  
};
```

If we don't want these functions, have to disallow by making them private and indicating = delete!

Examples

Some other tips from Scott Meyers:

- Item 7: Declare destructors virtual in polymorphic classes.
- Item 10: Have assignment operators return a reference to `*this`.
- Item 12: Copy all parts of an object.
- Item 22: Declare data members private
- Item 32: Make sure public inheritance models “is-a”.

Read his book, Effective C++!

Examples

Let's see some examples...

Wrap-up & Wednesday

Monday 1/20 is a holiday!

Second assignment due Weds. 1/22 at midnight

Class on Weds. 1/22 is back in 54-100 at 2pm.

- Design patterns and anti-patterns

Questions?

- I'm available after class or on Piazza.
- Office hours 5-7pm Mon, Tues in 26-142