

# Using SPECFEM3D\_GLOBE-7.0.0 for ASKI – Analysis of Sensitivity and Kernel Inversion, versions 1.0 to 1.2

Florian Schumacher<sup>1</sup>

<sup>1</sup>*Ruhr-Universität Bochum*

Aug 2016

Copyright ©2016 Florian Schumacher. Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled “GNU Free Documentation License”.

If you use SPECFEM3D\_GLOBE for ASKI for your own research, please cite our paper [SFL16]:

F. Schumacher, W. Friederich and S. Lamara,

”A flexible, extendable, modular and computationally efficient approach to scattering-integral-based seismic full waveform inversion”,

*Geophysical Journal International*, (February, 2016) 204 (2): 1100-1119

<http://dx.doi.org/10.1093/gji/ggv505>

This documentation was written in the hope that it will be useful to the user, but it *cannot be assured* that it is accurate in every respect or complete in any sense. In fact, at some places *this manual is work in progress*.

Please do not hesitate to report any inconsistencies by opening (or adding to) an ”issues” topic on [https://github.com/seismology-RUB/SPECFEM3D\\_GLOBE\\_for\\_ASKI](https://github.com/seismology-RUB/SPECFEM3D_GLOBE_for_ASKI) or to improve this documentation by incorporating your experiences with SPECFEM3D for ASKI and your personal experience of getting used to it (at best by modifying the source and issuing a pull request on gitHub, in any case let us know about it! Thanks).

Furthermore, I am aware of the poor  $\LaTeX$  coding of this document (at the moment, `\sloppy` is used at the beginning of the document to avoid overfull hboxes in many places). There is a lot of potential to improve the document style, hence the readability of the manual as a whole, as well as the coding style of the particular `.tex` files. *Please do not hesitate to improve!*

The  $\LaTeX$  source files and all related components of this document are available via [https://github.com/seismology-RUB/SPECFEM3D\\_GLOBE\\_for\\_ASKI](https://github.com/seismology-RUB/SPECFEM3D_GLOBE_for_ASKI), sub-directory `doc/` of the repository.

Florian Schumacher, Aug 2016

# Guide Through This Manual

We assume that you have sufficient knowledge of how to run the regular `SPECFEM3D_GLOBE` software. (i.e. without extension for use with `ASKI` ).

For details on how to get started by installing everything required for using `SPECFEM3D_GLOBE` with `ASKI` , refer to section 1 (page 4).

Before you start using the code to produce output for `ASKI` , please consider the general comments in section 2 (page 7).

If you are planning to compute a lot of kernels for source-receiver paths (e.g. doing full waveform inversion) it makes sense to use the automated python script

`run_specfem3dGlobeForASKI_simulations.py` which conducts a lot of simulations in an automated fashion. Please read section 4 (page 8).

If you want to conduct one single simulation (or just a few ones) producing output for `ASKI` , please read section 3 (page 7).

Section 8 (page 16) is intended to be used as a reference section only.

Bracketed comments starting with “**TODO IN THE FUTURE:**” are intended to mark ideas for future work. So please ignore if you are just applying the code.

# Contents

<b>1</b>	<b>Installation and Getting Started</b>	<b>4</b>
1.1	Requirements . . . . .	4
1.2	Installing this package . . . . .	4
1.3	Using Already Extended Copy of SPECSEM3D_GLOBE-7.0.0 Code . . . . .	5
1.4	Extend Your Own SPECSEM3D_GLOBE-7.0.0 code to produce output for ASKI . . . . .	5
<b>2</b>	<b>General Things to Consider</b>	<b>7</b>
<b>3</b>	<b>One Single Simulation</b>	<b>7</b>
<b>4</b>	<b>Using Automated Python Script for Doing Several Simulations</b>	<b>8</b>
4.1	Manually Setting Par_file_ASKI . . . . .	8
4.2	Manually Setting CMTSOLUTION . . . . .	9
4.3	Manually Setting STATIONS . . . . .	9
<b>5</b>	<b>Importing external models into SPECSEM3D , e.g. simple background model or currently inverted model for next iteration step</b>	<b>10</b>
5.1	Overwrite background model by simple 1D layered gradient model . . . . .	10
5.2	Impose exported .kim model onto background model . . . . .	11
5.3	Impose checkerboard/spike-test model onto the resulting model . . . . .	11
<b>6</b>	<b>Preparing Synthetic Data as Expected by ASKI</b>	<b>12</b>
<b>7</b>	<b>Preparing Synthetically Computed “Measured” Data as Expected by ASKI</b>	<b>13</b>
<b>8</b>	<b>File Par_file_ASKI</b>	<b>16</b>
8.1	ASKI external model . . . . .	16
8.2	ASKI output . . . . .	17
8.3	Definition of back propagation Green function . . . . .	18
8.4	Frequency discretization . . . . .	18
8.5	Inversion grid . . . . .	19
	<b>References</b>	<b>20</b>
	<b>History</b>	<b>21</b>
	<b>GNU Free Documentation License</b>	<b>22</b>

# 1 Installation and Getting Started

This section explains how to install the SPECSEM3D\_GLOBE software ([http://geodynamics.org/cig/software/specsem3d\\_globe](http://geodynamics.org/cig/software/specsem3d_globe)) in order to be used as a forward method for ASKI. In general, a regularly installed SPECSEM3D\_GLOBE version is extended by certain few modifications so it can produce output for ASKI. So, SPECSEM3D\_GLOBE for ASKI basically has the same requirements and dependencies as the SPECSEM3D\_GLOBE code, except that it needs a bit more memory and weigh more disc space for output. *Load balancing might not be perfect anymore!!* You should, therefore, have sufficient knowledge of how to run the regular SPECSEM3D\_GLOBE software.

## 1.1 Requirements

1. You require an installation of the ASKI main package, available via <https://github.com/seismology-RUB/ASKI>:  

```
git clone --depth 1 --branch master https://github.com/seismology-RUB/ASKI
```

  
The directory created by the `git clone` command will be referred to below as ASKI/
2. You need a functioning installation of the SPECSEM3D\_GLOBE code, including modifications for usage with ASKI :
  - You can either use the modified slim version of SPECSEM3D\_GLOBE\_V7.0.0 that comes with this package (see section 1.3 (page 5)),
  - or use your running installation of SPECSEM3D\_GLOBE and extend it for usage with ASKI, as described below in section 1.4 (page 5).

In *both* cases you must install this package (section 1.2 (page 4)).

3. You need basic experience in using the regular SPECSEM3D\_GLOBE software!

## 1.2 Installing this package

Clone the latest version of the master branch of the `github` repository to *the same* directory where you have cloned the ASKI main package to (in the ASKI documentation exemplarily called `/your/programs/`), i.e. execute

```
git clone --depth 1 --branch master https://github.com/seismology-RUB/SPECSEM3D_GLOBE_for_ASKI
```

(in one line, of course) from local path `/your/programs/`. This will create subdirectory `/your/programs/SPECSEM3D_GLOBE_for_ASKI` (also referred to below simply as `SPECSEM3D_GLOBE_for_ASKI/`) containing the code and documentation of the current release of the extension package SPECSEM3D\_GLOBE for ASKI.

Alternatively, go to [https://github.com/seismology-RUB/SPECSEM3D\\_GLOBE\\_for\\_ASKI](https://github.com/seismology-RUB/SPECSEM3D_GLOBE_for_ASKI) and download the content of the master branch as a `.zip` or try executing  

```
wget https://github.com/seismology-RUB/SPECSEM3D_GLOBE_for_ASKI/archive/master.zip
```

(in one line, of course) and extract it in such a way that the code files are contained in `/your/programs/SPECSEM3D_GLOBE_for_ASKI/`.

Furthermore you need to compile few more ASKI binaries following these step:

- In `SPECFEM3D_GLOBE_for_ASKI/Makefile` , set `COMPILER` appropriately, adjust `FFLAGS` if required and set the variables `BLAS`, `LAPACK`, just as you did in `ASKI/Makefile` when installing the `ASKI` main package.
- Execute the command `make all` from path `SPECFEM3D_GLOBE_for_ASKI/`

After that, `SPECFEM3D_GLOBE_for_ASKI/../../ASKI/bin/` should contain the new binaries.

The latest version of the master branch of gitHub repository [https://github.com/seismology-RUB/SPECFEM3D\\_GLOBE\\_for\\_ASKI](https://github.com/seismology-RUB/SPECFEM3D_GLOBE_for_ASKI) should be consistent with the latest version of the `ASKI` repository's master branch.

### 1.3 Using Already Extended Copy of `SPECFEM3D_GLOBE-7.0.0` Code

`SPECFEM3D_GLOBE_for_ASKI/specfem3d_globe` contains a copy of the release version `SPECFEM3D_GLOBE-V7.0.0` (released 10 July 2015) that was extended by the steps 2.-9. as in section 1.4 (page 5) in order to produce output for `ASKI` . Furthermore, `utils` and `documentation` (not required for use with `ASKI` ) were removed in order to keep the directory `SPECFEM3D_GLOBE_for_ASKI/specfem3d_globe` small.

Re-configure and compile the software on your system according to the compilers you are using etc., e.g. by executing the following commands from path `SPECFEM3D_GLOBE_for_ASKI/specfem3d_globe/`:

```
> ./configure FC=gfortran MPIFC=mpif90
> make xmeshfem3D xspecfem3D
```

In order to produce `ASKI` output in `SPECFEM3D` simulations, copy file `SPECFEM3D_GLOBE_for_ASKI/Par_file_ASKI` to your respective `DATA/` path (which is e.g. `specfem3d_globe/EXAMPLES/my_example/DATA/` , or `specfem3d_globe/DATA/` ). This file must be adjusted for any specific simulation (just as all other parameter files) and is described in detail in section 8 (page 16).

### 1.4 Extend Your Own `SPECFEM3D_GLOBE-7.0.0` code to produce output for `ASKI`

If you have a regular `SPECFEM3D_GLOBE` installation which has not significantly different functionality compared with `SPECFEM3D_GLOBE` release version 7.0.0 (2015-07-10), you can extend it for `ASKI` by the following steps:

1. Install `SPECFEM3D_GLOBE` on your system and make it run, gain experience in using it (below, the installation path is referred to as `specfem3d_globe/`).
2. Append content of file `SPECFEM3D_GLOBE_for_ASKI/specfem3D_par_ASKI.f90` to file `specfem3d_globe/src/specfem3D/specfem3D_par.F90`
3. In `specfem3d_globe/src/specfem3D/prepare_timerun.F90` in subroutine `prepare_timerun` :  
add the following line at the beginning of the subroutine, after the `use ...` statements:  
`use specfem_for_ASKI_par`  
add the following line close to the end of the subroutine, before `synchronize_all()`

is called:

```
call prepare_timerun_ASKI()
```

4. In `specfem3d_globe/src/specfem3D/iterate_time.F90` in subroutine `iterate_time`:  
add the following line at the beginning of the subroutine, after the `use ...` statements:  
`use specfem_for_ASKI_par`  
add the following line just before the `enddo` of the main time loop:  
`call write_ASKI_output()`
5. Append content of file `SPECFEM3D_GLOBE_for_ASKI/ASKI_external_model.f90` to file `specfem3d_globe/src/meshfem3D/meshfem3D_par.f90`
6. In `specfem3d_globe/src/meshfem3D/setup_model.f90` in subroutine `setup_model`:  
add the following line at the beginning of the subroutine, after the `use ...` statements:  
`use ASKI_external_model`  
add the following line just before info output is written to `IMAIN`, after the 3D models are broadcasted:  
`call broadcast_ASKI_external_model(myrank)`
7. In `specfem3d_globe/src/meshfem3D/get_model.F90` in subroutine `get_model`:  
add the following line at the beginning of the subroutine, after the `use ...` statements:  
`use ASKI_external_model`  
add the following lines just before define elastic parameters in the model (i.e. setting all arrays `rhostore`, `kappavstore`, `muvstore`, ...), just after all other `get_model` routines:  

```
call values_ASKI_external_model(iregion_code, xmesh, ymesh,
                                zmesh, r, &
                                vpv, vph, vsv, vsh, rho, Qmu, Qkappa, eta_aniso, dvp, &
                                c11, c12, c13, c14, c15, c16, c22, c23, c24, c25, &
                                c26, c33, c34, c35, c36, c44, c45, c46, c55, c56, c66)
```
8. Append content of file `SPECFEM3D_GLOBE_for_ASKI/parallel_ASKI.f90` to file `specfem3d_globe/src/shared/parallel.f90`
9. Recompile the relevant `SPECFEM3D` binaries by issuing  
`make xmeshfem3D xspecfem3D` in directory `specfem3d_globe/`
10. In order to produce `ASKI` output in `SPECFEM3D` simulations, copy file `SPECFEM3D_GLOBE_for_ASKI/Par_file_ASKI` to your respective `DATA/` path (which is e.g. `specfem3d_globe/EXAMPLES/my_example/DATA/`, or `specfem3d_globe/DATA/`). This file must be adjusted for any specific simulation (just as all other parameter files) and is described in detail in section 8 (page 16).

If you have a newer version of `SPECFEM3D_GLOBE` which does not work with `ASKI` as thus described, we are happy to hear about it. Please feel free to get in touch with the `ASKI` developers (via <https://github.com/seismology-RUB> or <http://www.rub.de/aski>).

## 2 General Things to Consider

- parameters `FILE_KERNEL_REFERENCE_MODEL` and `FILE_WAVEFIELD_POINTS` of the `ASKI` parameter file for a specific iteration step must be set to some main `ASKI` output file, which is the basefile name of `ASKI_outfile` extended by `.main`, see 8.2 (page 17). Use the main `ASKI` output file of some arbitrary `ASKI` output, e.g. the kernel displacement output of the first source or some kernel green tensor output.
- As there is a fixed order assumed of the `ASKI` wavefield points (by procs and local element numbering), the computation of many kernels (e.g. for many source-receiver paths in an inversion) can only be consistent, if the *same* mesh decomposition and the *same* number of procs is used at all times (for those kernels you want to use together in some analysis, e.g. all kernels in your specific iteration step of an inversion). It may, hence, be sensible to run the mesher *once* before all simulations are conducted (only re-setting the source mechanism and `Par_file_ASKI` before a specific simulation, adjust your script `run_mesher_solver.bash` appropriately). Such a mechanism is supported by the automated python script through flag `use_different_command_in_first_simulation`.
- You must use `PRINT_SOURCE_TIME_FUNCTION = .true.` in the `SPECFEM3D Par_file` in order to ensure correct functionality (relevant for cases `ASKI_DECONVOLVE_STF = .true.` in `Par_file_ASKI`).
- You must set `ROTATE_SEISMOGRAMS_RT = .false.` in the `SPECFEM3D Par_file` in order to ensure that synthetic data (or measured data for synthetic studies) can be transformed to the spectral `ASKI` format correctly (by programs as in sections 6 (page 12), 7 (page 13)).

## 3 One Single Simulation

As usual, you need to set the mesh according to the needs of your seismic problem, e.g. the resolved highest frequency etc. You need to choose a `SPECFEM3D` background model (defined in `Par_file` as usual). For details on how to import the current model of an inversion (the inverted model of the last iteration step) into `SPECFEM3D`, see section 5 (page 10). Refer to the same section on how to set a different 1D background model or superimpose a checkerboard / spike-test model.

Set the regular `SPECFEM3D` files `Par_file`, `CMTSOLUTION` and `STATIONS` (standard `SPECFEM3D` functionality).

Additionally, you need to set file `Par_file_ASKI` to desired values. The file is described in detail in section 8 (page 16).

After that, you are ready to run the code. Since all relevant information for producing `ASKI` output are read on runtime, you do not need to recompile the `SPECFEM3D` code every time you run a `SPECFEM3D` simulation for `ASKI`, you just need to set the above listed parameter files.

## 4 Using Automated Python Script for Doing Several Simulations

As usual, you need to set the mesh according to the needs of your seismic problem, e.g. the resolved highest frequency etc. You need to choose a SPEC-FEM3D background model (defined in `Par_file` as usual). For details on how to import the current model of an inversion (the inverted model of the last iteration step) into SPEC-FEM3D, see section 5 (page 10). Refer to the same section on how to set a different 1D background model or superimpose a checkerboard / spike-test model.

Python script `run_specfem3dGlobeForASKI_simulations.py` (provided in directory `SPEC-FEM3D_GLOBE_for_ASKI/`) conducts the specified kernel simulations (as described inside the script on the top) by running SPEC-FEM3D simulations one after another, setting all parameter files before each simulation appropriately. You need to edit the parameters in the first part of the script and set all variables defined there to appropriate values, as described in the comments in the script

(**TODO IN THE FUTURE:** maybe it is better to have an input (file?) mechanism to this script. But then: more overhead/extra requirements (packages, arguments handling) to cope with on cluster machines ...)

The python script may not be suitable for the HPC system you are using. If you are not able to adapt it in a way which makes it possible to be used, you might have to figure out an analogous way yourself how to perform the tasks done by this script.

In case of using the provided python script `run_specfem3dGlobeForASKI_simulations.py`, some parameters in SPEC-FEM3D files `CMTSOLUTION`, `Par_file` and in file `Par_file_ASKI` are automatically changed, while the script conducts the SPEC-FEM3D simulations one after another.

In the following, only those parameters/lines are listed, which, if necessary, need to be set *manually* before running this python script. All other parameters are set by the script.

### 4.1 Manually Setting `Par_file_ASKI`

The following `Par_file_ASKI` parameters need to be set manually before running the python script, since they are not changed/set by the script.

- `USE_ASKI_BACKGROUND_MODEL, FILE_ASKI_BACKGROUND_MODEL`
- `IMPOSE_ASKI_INVERTED_MODEL, FILE_ASKI_INVERTED_MODEL`
- `ASKI_INVERTED_MODEL_INTERPOLATION_TYPE, ASKI_INVERTED_MODEL_FACTOR_SHEPARD_RADIUS`
- `IMPOSE_ASKI_CHECKER_MODEL, FILE_ASKI_CHECKER_MODEL`
- `ASKI_MAIN_FILE_ONLY` (must be set to `.false.`, otherwise no ASKI wavefield output will be produced!)
- `OVERWRITE_ASKI_OUTPUT`
- `ASKI_DECONVOLVE_STF` (strongly recommended to set to `.true.` always)



- ASKI\_DFT\_double
- ASKI\_DFT\_apply\_taper, ASKI\_DFT\_taper\_percentage
- in case of `define_ASKI_output_volume_by_inversion_grid = False` in the python script, you need to manually set all parameters concerning the inversion grid, i.e. `ASKI_type_inversion_grid`, `ASKI_nchunk`, `ASKI_(c/w) (lat/lon)`, `ASKI_rot_gamma`, `ASKI_r (min/max)`

*It is important to notice, that the flag `ASKI_DECONVOLVE_STF` is not changed by the automated python script. Although it is required for Green functions (“gt” simulations) to use `ASKI_DECONVOLVE_STF = .true.` in order to get the displacement field w.r.t. a Dirac impulse source-time function, the situation might arise, that for the forward wavefields (“displ” simulations) emanated by the seismic events you want to use a pre-defined source wavelet (e.g. Ricker wavelet) that *should not* be deconvolved from the wavefields. For now, This can only be realized by doing two separate runs with the python script, one for all “gt” simulations (setting `ASKI_DECONVOLVE_STF = .true.`) and one for the “displ” simulations (setting `ASKI_DECONVOLVE_STF = .false.`).*

## 4.2 Manually Setting CMTSOLUTION

The python script *always* automatically sets “latitude:”, “longitude:”, “depth:”, “Mrr:”, “Mtt:”, “Mpp:”, “Mrt:”, “Mrp:”, “Mtp:”. In case of “gt” and “displ” simulations, “half duration:” is set to “0.” ASKI follows the idea to also compute “displ” wavefields with an impulsive source-time function (setting `ASKI_DECONVOLVE_STF = .true.`) and apply filters afterwards. For simulations of type “data”, however, “half duration:” is *not* modified by the python script! So, if you wish to do a “data” simulation using a “half duration:” value different from “0.”, you should conduct those in a separate run of the python script (not mixing with “displ” or “gt” simulations).

## 4.3 Manually Setting STATIONS

In the upper part of the python script, the flag `create_specfem_stations` can be set to `True`. In this case, the SPECFEM3D STATIONS file is automatically generated from the ASKI file `FILE_STATION_LIST`.

If you do not use this flag to automatically generate the SPECFEM3D STATIONS file, you must provide it manually. The standard SPECFEM3D STATIONS file should contain the definition of stations as in the ASKI file `FILE_STATION_LIST`, in consistend SPECFEM3D notation, i.e. coordinate columns being lat (third column of STATIONS and fourth column of `FILE_STATION_LIST`) and lon (fourth column of STATIONS and third column of `FILE_STATION_LIST`) and elev (sixth column of STATIONS and fifth column of `FILE_STATION_LIST`).

You must also assure to use the very same station names and network codes in file STATIONS as in ASKI file `FILE_STATION_LIST`!

## 5 Importing external models into SPECSEM3D , e.g. simple background model or currently inverted model for next iteration step

There are three types of external models that can be put (in combination) into SPECSEM3D, using the additional module `ASKI_external_model`:

Simple 1D layered spline-interpolation models can overwrite the SPECSEM3D model chosen in `Par_file`. Exported `.kim` files (as produced by `ASKI` program `exportKim` with option `-otxt`) may be superimposed onto the background model (default SPECSEM3D model or `ASKI` 1D background model) and used as a model for the new iteration of full waveform inversion of `ASKI`. After that, a checkerboard / spike-test model can be superimposed onto the resulting model, imposing relative model perturbations in a checkerboard or spike-like fashion that can be used for resolution analysis.

These three types of external models are explained in the following. The use of any of these is controlled by respective flags in `Par_file_ASKI`.

### 5.1 Overwrite background model by simple 1D layered gradient model

The logical flag `USE_ASKI_BACKGROUND_MODEL` in `Par_file_ASKI` indicates whether SPECSEM3D\_GLOBE should use the 1D reference model as defined in the text file with name given by `FILE_ASKI_BACKGROUND_MODEL`, relative to `DATA/`. This mode will overwrite model values on all GLL points, dependent on depth. *A model like this will not affect the meshing of spectral elements or any internal boundaries created by the meshing process!*

The 1D model is defined by a list of model values at given depth nodes between which a spline interpolation is done. A template of such a background model file, containing documenting commentary, is given by file `SPECSEM3D_GLOBE_for_ASKI/ASKI_background_model_template`. The specific format of this text file is described now in the following:

**the first line** is ignored, this line may contain a short description of the model or can be empty.

**the second and third line** simply define the characteristics of the depth nodes which are defined in the table (for convenience when reading the file by the program):

The second line must contain the number of layers, between which discontinuities are allowed in the 1D model. At the boundary of any two layers, there should be a “double node”, i.e. two lines with *same* depth. There is no spline interpolation done accross any layer boundaries, i.e. over any double node. Different model values on either side of a double node will be interpreted as a discontinuity in the model. You can also set the same model value on either side of a double node, e.g. if you want to have a half space of the same model values as a gradient coming from above, etc.

The third line contains as many integer values (separated by white space) as there are layers (as defined by line two) and gives for each layer the number of nodes.

**starting from line 4**, each line defines a depth node giving (isotropic) model values at this depth. The columns are separated by white space and assume the meaning:

depth [m]    density [ $\text{g/cm}^3$ ]    vp [km/s]    vs [km/s]    Qmu    Qkappa

The depth is assumed to be monotonically *increasing*, the first line should have depth 0.

**Everything below** the expected number of lines is ignored, so you can also add commentary below the model definition.

## 5.2 Impose exported .kim model onto background model

This functionality is controlled by logical flag `IMPOSE_ASKI_INVERTED_MODEL` along with the parameters `FILE_ASKI_INVERTED_MODEL`, `ASKI_INVERTED_MODEL_INTERPOLATION_TYPE`, `ASKI_INVERTED_MODEL_FACTOR_SHEPARD_RADIUS` in `Par_file_ASKI`.

`FILE_ASKI_INVERTED_MODEL` provides the filename (relative to directory `DATA/`) of the exported .kim file (text file as produced using option `-otxt` of `ASKI` executable `exportKim`).

`ASKI_INVERTED_MODEL_INTERPOLATION_TYPE` and `ASKI_INVERTED_MODEL_FACTOR_SHEPARD_RADIUS` control the method of interpolating the given inverted model (defined on an `ASKI` internal inversion grid) onto the GLL points used in your `SPECFEM3D` simulation. At the moment, an unstructured 3D interpolation after Shepard [She68] is supported which is founded on inverse-distance weighting and accounts for issues of nearby points, direction and slope. `ASKI_INVERTED_MODEL_INTERPOLATION_TYPE` can be either set to `shepard_standard` or to `shepard_factor_radius`.

In case of type `shepard_factor_radius`, the factor given by `ASKI_INVERTED_MODEL_FACTOR_SHEPARD_RADIUS` controls the influence of neighbouring control nodes on the interpolation (larger factor will include more control nodes (further away) for the interpolation). For a particular GLL point, first the closest control node of the inverted model (center of inversion grid cell) is found. Then this distance is multiplied by `ASKI_INVERTED_MODEL_FACTOR_SHEPARD_RADIUS` to yield a radius within which all contained control nodes of the inverted model will be taken into account to compute the interpolated value for that GLL point.

Method `shepard_standard` is the same as using `shepard_factor_radius` with `ASKI_INVERTED_MODEL_FACTOR_SHEPARD_RADIUS = 2.0`. This factor proved to be a good choice. When setting the method to `shepard_standard`, any value given for `ASKI_INVERTED_MODEL_FACTOR_SHEPARD_RADIUS` is ignored.

## 5.3 Impose checkerboard/spike-test model onto the resulting model

*A checkerboard/spike-test model as described in this section is only supported for 1-chunk simulations!*

Onto the “final” resulting model (i.e. the chosen `SPECFEM3D` model, after possibly overwriting by an `ASKI` 1D background model (or not), after possibly superimposing a .kim inverted model (or not)), relative checkerboard / spike-test anomalies can be superimposed in order to conduct resolution analysis tests.

These anomalies are defined by their width and gaps between them (in km on the surface), in both, lat and lon direction of the chunk (i.e. the XI and ETA directions), as well as the depth locations and thicknesses of checker layers. The anomalies are defined by positive percentages which alternate in sign throughout the checker grid. A template of such a model file, containing documenting commentary, is given by file `SPECFEM3D_GLOBE_for_ASKI/checker_model_template`. The specific format of this text file is described now in the following:

**the first line** is ignored, this line may contain a short description of the model or can be empty.

**the second and third line** define the lateral distribution of checkers and background gaps in

between in lat and long direction of the model chunk. The given sizes [km] at the surface of the Earth are projected into depth and distributed equi-angularly on the model chunk.

**the fourth line** gives the number of depth layers in which there should be checker patterns. Must be a positive integer.

**the fifth line** defines the depth values [km] of the upper boundaries of the checker layer.

**the sixth line** defines the thicknesses [km] of the checker layers.

**the seventh line** finally contains 5 percentage values separated by white space, defining the relative model anomaly values [positive percentage] of the 5 isotropic parameters density, vp, vs, Qmu, Qkappa. The anomalies will be alternating in sign, i.e. varying +anomaly -anomaly, etc.

Everything below the expected content is ignored. Also, from each of the above described lines, only the expected content is read (e.g. just two numbers are read from lines 2-3) and everything behind is ignored. This way, you may add arbitrary commentary to a file.

## 6 Preparing Synthetic Data as Expected by ASKI

Use executable `transformSpecfem3dGlobeSyntheticData`, as described below.

It is assumed that a copy of the content of the `OUTPUT_FILES` directory (without the `MPI_DATABASES` files etc...) of all involved `SPECFEM3D` simulations (which contain the standard seismograms files) can be found at the path as choosen by the automated python script (see 4 (page 8)), i.e. filename of the kernel displacement file for the respective event with the extension `_OUTPUT_FILES`. The synthetic data then is written in the required form to path `PATH_SYNTHETIC_DATA/`, where the filenames are by convention `synthetics_EVENTID_STATIONNAME_COMPONENT`. Make sure that the `ASKI` frequency discretization as defined by the `ASKI` main parfile and iter parfile is correctly set! Also, all other objects used for an `ASKI` iteration step (like wavefield points file, inversion grid etc.) must be in place, since for executing `transformSpecfem3dGlobeSyntheticData` the basic requirements for an iteration step are initiated (compare `ASKI` manual, section “Initiate Basic Requirements”).

### The executable `transformSpecfem3dGlobeSyntheticData`

Transforms standard `SPECFEM3D_GLOBE_7.0.0` output to `ASKI 1.0-1.2` spectral data in synthetic-data format.

It is assumed that seismograms were written as `NEZ`, and *not* as `ZRT`, i.e. `ROTATE_SEISMOGRAMS_RT = .false.`

It is assumed that text files were written, one file per seismogram, i.e. `OUTPUT_SEISMOS_ASCII_TEXT = .true.`, `SAVE_ALL_SEISMOS_IN_ONE_FILE = .false.`, `USE_BINARY_FOR_LARGE_FILE = .false.`

Executing `transformSpecfem3dGlobeSyntheticData` (without arguments) will print a help message how to use it and will list the required positional arguments and mandatory options and optional options (listed in the following with a short description).

**positional arguments of executable `transformSpecfem3dGlobeSyntheticData`**

**`main_parfile`** Main parameter file of inversion.

### **mandatory options**

**`-bicode band_instrument_code`** `band_instrument_code` must be two characters, band code and instrument code i.e. the first two characters before the component in seismogram filename. E.g. “LH” if your filenames look like “`network.staname.LH*.sem`”.

**`-dt time_step`** `time_step` is the real number defining the time step of the seismograms as given in files `output_mesher.txt`, `output_solver.txt`

**`-nstep number_of_time_samples`** `number_of_time_samples` is the number of samples NSTEP as given in file `output_solver.txt`

**`-ocomp output_components`** `output_components` is a vector of receiver components for which synthetic data output is produced. Valid components are CX , CY , CZ , N , S , E , W , UP , DOWN (also see ASKI user manual, section on “Data in ASKI”).

### **optional options**

**`-evid eventID`** If set, `eventID` indicates the single event for which synthetic data is produced. Otherwise, synthetic data is produced for all events (as defined in `FILE_EVENT_LIST` given in the ASKI main parfile).

**`-dconv`** If set, the normalized and differentiated source time function will be deconvolved from the differentiated synthetics. It is assumed that the source time function (error function) was written to file `plot_source_time_function.txt`, i.e. flag `PRINT_SOURCE_TIME_FUNCTION` was set to `.true.` in `SPECFEM3D Par_file`. `-dconv` is consistent with `ASKI_DECONVOLVE_STF = .true.` in `Par_file_ASKI`. In case `ASKI_DECONVOLVE_STF` was `.true.`, here flag `-dconv` should be set for consistency!

## **7 Preparing Synthetically Computed “Measured” Data as Expected by ASKI**

For synthetic tests, you might want to treat synthetic data computed by SPECFEM w.r.t. some perturbed earth model as (noise-free) measured data. SPECFEM3D for ASKI “data” simulations (e.g. produced by automated python script, 4 (page 8)) will produce these data in standard SPECFEM time-domain output formats. In order to transform these time series to frequency-domain measured data files in the form required by ASKI there are two possibilities:

First of all, the ASKI executable `transformMeasuredData` can be utilized for this purpose after appropriately renaming the text output trace files as required for input of `transformMeasuredData` option `-txt`).

As an alternative (providing more possibilities of data processing like scaling, filtering, differentiating), you can use executable `transformSpecfem3dGlobeMeasuredData`, as described below. It is assumed that a copy of the content of the `OUTPUT_FILES` folder (without the `MPI_DATABASES` files etc...) of the “data” simulations (which contain the standard seismograms files) can be found in respective directory `PATH_MEASURED_DATA/data_EVENTID_OUTPUT_FILES`. The measured data files then are written in the required form to path `PATH_MEASURED_DATA/`, where the filenames are by convention `data_EVENTID_STATIONNAME_COMP`. Make sure that the frequency discretization of ASKI measured data as defined by the ASKI main parfile is correctly set, as well as the measured data path!

### The executable `transformSpecfem3dGlobeMeasuredData`

Transforms standard `SPECFEM3D_GLOBE_7.0.0` output to ASKI 1.0-1.2 spectral data in measured-data format.

It is assumed that seismograms were written as NEZ, and *not* as ZRT, i.e. `ROTATE_SEISMOGRAMS_RT = .false.`).

It is assumed that text files were written, one file per seismogram, i.e. `OUTPUT_SEISMOS_ASCII_TEXT = .true.`, `SAVE_ALL_SEISMOS_IN_ONE_FILE = .false.`, `USE_BINARY_FOR_LARGE_FILE = .false.`.

Executing `transformSpecfem3dGlobeMeasuredData` (without arguments) will print a help message how to use it and will list the required positional arguments and mandatory options and optional options (listed in the following with a short description).

### positional arguments of executable `transformSpecfem3dGlobeMeasuredData`

**main\_parfile** Main parameter file of inversion.

### mandatory options

**-bicode band\_instrument\_code** `band_instrument_code` must be two characters, band code and instrument code i.e. the first two characters before the component in seismogram filename. E.g. “LH” if your filenames look like “`network.staname.LH*.sem`”.

**-dt time\_step** `time_step` is the real number defining the time step of the seismograms as given in files `output_mesher.txt`, `output_solver.txt`

**-nstep number\_of\_time\_samples** `number_of_time_samples` is the number of samples `NSTEP` as given in file `output_solver.txt`

**-ocomp output\_components** `output_components` is a vector of receiver components for which measured data output is produced. Valid components are CX , CY , CZ , N , S , E , W , UP , DOWN (also see ASKI user manual, section on “Data in ASKI ”).

## optional options

**-filter** If set, the respective event filters and station (component) filters as defined by the ASKI main parfile will be applied to the spectra before writing them to file. I.e. if in the ASKI main parfile any filtering is switched off (by respective flags), *no* filtering will be applied by executable `transformSpecfem3dGlobeMeasuredData` ! If in ASKI main parfile, only event filters are enabled, then this option `-filter` will cause the executable only to apply the event filters etc.

**-evid eventID** If set, `eventID` indicates the single event for which measured data is produced. Otherwise, measured data is produced for all events (as defined in `FILE_EVENT_LIST` given in the ASKI main parfile).

**-cfreq forward\_method** Instead of the ASKI standard definition of real-valued frequencies by  $f_k = k \cdot \Delta f$  (for frequency indices  $k$  and frequency step  $\Delta f$ ), the data is produced w.r.t. complex frequencies consistent with the given forward method `forward_method`. For instance, setting `-cfreq GEMINI` will produce Gemini-consistent spectral data at complex frequencies with additional constant imaginary part  $\sigma = -5\Delta f/2\pi$ , thus implicitly using the actual frequencies  $f_k = k \cdot \Delta f + i \cdot \sigma$  (with  $i$  being the imaginary unit, also see ASKI user manual, section on “Data in ASKI ”). Any filter values (in case of `-filter` is set) are assumed to be given at those complex frequencies, too!

**-dconv** If set, the normalized and differentiated source time function will be deconvolved from the differentiated seismograms. It is assumed that the source time function (error function) was written to file `plot_source_time_function.txt`, i.e. flag `PRINT_SOURCE_TIME_FUNCTION` was set to `.true.` in `SPECFEM3D Par_file`. `-dconv` is consistent with `ASKI_DECONVOLVE_STF = .true.` in `Par_file_ASKI`. When producing “measured data” that is to be modelled by (filtered) waveforms w.r.t. an impulsive source, it is recommended to set `-dconv` here and use `-filter`.

**-diffths** If set, the time series will *additionally* be differentiated (in the frequency domain after Fourier transform). This option is sensible to set when you require velocity seismograms (spectra).

**-scale ts\_scale\_factor** If set, the time series are scaled with factor `ts_scale_factor` (must be different from 0) after reading in, before transforming to frequency domain.

## 8 File `Par_file_ASKI`

File `Par_file_ASKI` is, just like the file `Par_file`, located in directory `DATA/` of your current `SPECFEM3D` example. It basically controls `ASKI` functionality if used along with an `ASKI` extended `SPECFEM3D` installation. If in such an extended `SPECFEM3D` version the file `Par_file_ASKI` is not present, no `ASKI` output is produced and `SPECFEM3D` runs with standard functionality.

In the following, we give a short description of the functionality of parameters defined in file `Par_file_ASKI`.

### 8.1 `ASKI` external model

First the `SPECFEM3D` model is set, as defined by standard `SPECFEM` mechanisms (i.e. by flag `MODEL` in file `Par_file`). Then, *only if indicated* by flag `USE_ASKI_BACKGROUND_MODEL`, this model is overwritten by the `ASKI` 1D background model at all depths where this background model is defined (see 5.1 (page 10)).

After that, *only if indicated*, by flag `IMPOSE_ASKI_INVERTED_MODEL` an `ASKI` inverted model is superimposed to the then existing model values (will set absolute model values, but at the boundaries of the inversion domain it will smooth out to the existing model, see 5.2 (page 11)).

Yet after that, `ONLY IF INDICATED BELOW`, one can superimpose a checkerboard by relative model anomalies. By setting the respective flags to `.false.`, this checkerboard can be superimposed to any standard `SPECFEM` model, as well as the `ASKI` background model or the `ASKI` inverted model.

#### **`USE_ASKI_BACKGROUND_MODEL`, `FILE_ASKI_BACKGROUND_MODEL`**

Logical flag `USE_ASKI_BACKGROUND_MODEL` indicates whether at all to use a 1D background model and

`FILE_ASKI_BACKGROUND_MODEL`, defines a filename relative to `DATA/` from which the 1D model is read. For the required format of this text file, see 5.1 (page 10).

#### **`IMPOSE_ASKI_INVERTED_MODEL`, `FILE_ASKI_INVERTED_MODEL`, `ASKI_INVERTED_MODEL_INTERPOLATION_TYPE`, `ASKI_INVERTED_MODEL_FACTOR_SHEPARD_RADIUS`**

Logical flag `IMPOSE_ASKI_INVERTED_MODEL` indicates whether at all to impose an `ASKI` inverted model onto the existing model (standard background or standard background plus `ASKI` 1D background).

`FILE_ASKI_INVERTED_MODEL` gives the filename relative to `DATA/` where to find the file containing the the exported `.kim` file (text file as produced using option `-otxt` of `ASKI` executable `exportKim`).

Parameters `ASKI_INVERTED_MODEL_INTERPOLATION_TYPE`, `ASKI_INVERTED_MODEL_FACTOR_SHEPARD_RADIUS` control the way of interpolating the model values given on control nodes of an `ASKI` inversion grid onto the `GLL` points of the current `SPECFEM3D` mesh. For their meaning see 5.2 (page 11).



## **IMPOSE\_ASKI\_CHECKER\_MODEL, FILE\_ASKI\_CHECKER\_MODEL**

Logical flag `IMPOSE_ASKI_CHECKER_MODEL` indicates whether to impose a relative checkerboard / spike-test model after defining the model by the chosen `SPECFEM3D` model, a possible `ASKI` background model and possible an `ASKI` inverted model.

`FILE_ASKI_CHECKER_MODEL` gives the filename relative to `DATA/` where to find the file containing the definition of the checkerboard / spike grid.

## **8.2 ASKI output**

### **COMPUTE\_ASKI\_OUTPUT, ASKI\_MAIN\_FILE\_ONLY, OVERWRITE\_ASKI\_OUTPUT**

Parameter `COMPUTE_ASKI_OUTPUT` controls whether at all `ASKI` output is produced by the `SPECFEM3D` solver (i.e. kernel green tensor kernel displacement main or frequency files).

If `COMPUTE_ASKI_OUTPUT = .true.`, then logical flag `ASKI_MAIN_FILE_ONLY` controls whether to produce only the `.main` output file at the beginning of a simulation and immediately terminate. No frequency output files and no `SPECFEM` seismograms will be produced in this case. This functionality is useful, if you want to check the resolution of wavefield points with regard of your chosen inversion grid or you want to look at the kernel reference model (background model used by `SPECFEM`) *before* running all your simulations for an iteration step of `ASKI` waveform inversion. With one single `.main` output file available, namely, you can execute the `ASKI` executable `initBasics` and check for everything related to your wavefield points and inversion grid.

Logical flag `OVERWRITE_ASKI_OUTPUT` controls if the `ASKI` output files shall be overwritten if existend or not. If set to `.false.` and any of those files exist, the `SPECFEM3D` solver will terminate raising an error message.

Setting `COMPUTE_ASKI_OUTPUT = .false.` will *not* prevent the `SPECFEM3D` mesher from setting an `ASKI` background/external/checker (if indicated by above logical flags) ! So you can use an `ASKI` external model along with a standard `SPECFEM3D` simulation.

### **ASKI\_outfile, ASKI\_output\_ID**

`ASKI_outfile` defines the absolute base file name of `ASKI` output files. The actual output files of this simulation will be this base name appended by file extensions `.main` (for main output file) and `.jf#####` for each frequency (e.g. `.jf000013` for frequency index 13).

`ASKI_output_ID` is a character string of maximum length as defined by parameter `length_ASKI_output_ID` in file

`SPECFEM3D_GLOBE_for_ASKI/specfem3D_par_ASKI.f90` with which all output files of the current simulation will be tagged, and it will be used to check consistency of the files (could be a timestamp, eventID, station name + component etc).

### **ASKI\_DECONVOLVE\_STF**

Logical flag `ASKI_DECONVOLVE_STF` indicates whether to deconvolve (the derivative of) the source time function from the wavefield spectra before writing them to files. Select `.true.`

for any Green function computations! Even if a Heaviside source time function is used, the velocity field is not exactly a Green function (i.e. displacement wavefield w.r.t. an impulse source time function), since a steep error function is used by SPECSEM to resemble a quasi-Heaviside function. This steep error function, furthermore, is dependent on timestep `DT`! Hence, only by deconvolution of (the derivative of) this quasi-Heaviside source time function, the real Green function (generated by an impulsive Dirac source time function), which is independent of the time step can be computed. *However, for now it is assumed that a quasi-Heaviside is used! Any other actually used source-time-function is not accounted for correctly, when* `ASKI_DECONVOLVE_STF = .true..`

### 8.3 Definition of back propagation Green function

Since `SPECSEM3D_GLOBE` does not properly support the use of single force sources, the computation of Green functions requires some additional definitions which are required by the `ASKI` extension code to `SPECSEM3D_GLOBE`.

#### **COMPUTE\_ASKI\_GREEN\_FUNCTION, ASKI\_GREEN\_FUNCTION\_COMPONENT**

Logical flag `COMPUTE_ASKI_GREEN_FUNCTION` indicates whether this type of `ASKI` output is a Green function wavefield (i.e. a generalized backpropagation from a receiver) or not. Set to `.false.` if this is a forward wavefield computation from some seismic source. The source position and source depth of this Green function (i.e. technically the respective `ASKI` receiver position) must be defined as usual in the `CMTSOLUTION` file.

By `ASKI_GREEN_FUNCTION_COMPONENT`, the direction of the single force source of this Green function is defined (in case of `COMPUTE_ASKI_GREEN_FUNCTION = .true.`). At the moment, the following directions are supported (following the `ASKI` nomenclature for receiver components):

`N`, `E`, `UP` : pointing to local 'N'orth, 'E'ast or 'UP' direction, dependent on source position  
`CX`, `CY`, `CZ` : global Cartesian X, Y, Z directions

### 8.4 Frequency discretization

The double precision `df` [Hz] and integer values `jf` have the following meaning: The spectra are saved for all frequencies  $f = jf * df$  [Hz].

#### **ASKI\_df, ASKI\_nf, ASKI\_jf**

`ASKI_df` is a predefined frequency step that is used to evaluate the spectrum. In case we want to do an inverse FT in case of time-domain sensitivity kernel computation, we need to choose `ASKI_df` with care as `ASKI_df = 1/length_of_time_series` and suitably high frequency indices (dependent on frequency content). Otherwise we could lose periodicity (if in  $\exp(-i2\pi(k)(n)/N)$   $N$  is no integer, these are no roots of 1 anymore). The spectra are saved for frequencies  $f = (ASKI_jf) * ASKI_df$  (`ASKI_nf` many).

## **ASKI\_DFT\_double**

Choose precision of Discrete Fourier Transform. If there is enough memory available, it is highly recommended to use `ASKI_DFT_double = .true.` in which case double complex spectra are hold in memory (single precision is written to file, though, but less roundoffs during transformation). Otherwise choose `ASKI_DFT_double = .false.` in which case single precision spectra will be used in memory. The transformation coefficients  $\exp(-i*2\pi*f*t)$  are always in double complex precision!

## **ASKI\_DFT\_apply\_taper, ASKI\_DFT\_taper\_percentage**

Decide whether the (oversampled, noisy, ...) time series should be tapered by a hanning taper (on tail) while applying the discrete fourier transform (on-the-fly). If `ASKI_DFT_apply_taper = .true.`, the value of `ASKI_DFT_taper_percentage` (between 0.0 and 1.0) defines the amount of total time for which the hanning taper will be applied at the tail of the time series.

## **8.5 Inversion grid**

### **ASKI\_type\_inversion\_grid**

ASKI supports several types of inversion grids for `FORWARD_METHOD = SPECFEM3D`.  
`ASKI_type_inversion_grid =`

1. (`TYPE_INVERSION_GRID = schunkInversionGrid`)  
ASKI internal, but SPECFEM independent simple spherical inverison grid
2. (`TYPE_INVERSION_GRID = scartInversionGrid`)  
NOT TO BE USED WITH SPECFEM3D\_GLOBE!  
ASKI internal, but SPECFEM independent Cartesian inversion grid:  
The values for ASKI output are stored at all inner GLL points of spectral elements which lie inside the block volume defined below by parameters `ASKI_(cw)(xyz)`. ASKI locates the coordinates of those points inside the inversion grid cells and computes integration weights for them.
3. (`TYPE_INVERSION_GRID = ecartInversionGrid`)  
External inversion grid provided e.g. by Trelis, which may contain tetrahedra, as well as hexahedra. As in case of `ASKI_type_inversion_grid = 2`, ASKI output is stored at all inner GLL points of elements which are inside the volume defined by `ASKI_(cw)(xyz)`. ASKI locates the wavefield points inside the inversion grid and computes weights.
4. (`TYPE_INVERSION_GRID = specfem3dInversionGrid`)  
Use SPECFEM elements as inversion grid:  
Wavefield points are *all* GLL points of an element for elements which are (at least partly) inside the volume defined by `ASKI_(cw)(xyz)`. Additionally store the jacobians for all wavefield points. Assume `ncell = ntot_wp/(NGLLX*NGLLY*NGLLY)` as the number of inversion grid cells, and the order of wavefield points accordingly (`do k=1, NGLLZ; do j=1, NGLLY; do i=1, NGLLX; ip=ip+1 ....`)

5. (TYPE\_INVERSION\_GRID = chunksInversionGrid)

ASKI internal, but SPECSEM independent more elaborate spherical inversion grid supporting several chunks

**ASKI\_nchunk, ASKI\_(c/w) (lat/lon), ASKI\_r (min/max), ASKI\_rot\_gamma**

Dependent on ASKI\_type\_inversion\_grid, (a selection of) the following parameters may be used to define a volume within which wavefield points are searched for:

ASKI\_nchunk defines the number of chunks of a chunk cubed sphere. SPECSEM3D\_GLOBE for ASKI supports 1,2,3 and 6 chunks (like the forward code itself). However, not all those values are supported by all types of inversion grids: the schunkInversionGrid only supports ASKI\_nchunk = 1, the ecartInversionGrid, specsem3dInversionGrid and chunksInversionGrid support all values 1,2,3,6.

ASKI\_clat, ASKI\_clon define the center of the first chunks (not used for full sphere with 6 chunks). ASKI\_wlat, ASKI\_wlon define the width of the chunk, in case of ASKI\_nchunk = 1. For ASKI\_nchunk = 2, 3, 6, always ASKI\_wlon = ASKI\_wlat = 90.0 is used. ASKI\_rot\_gamma defines the azimuthal rotation angle in degrees by which the 1,2 or 3 chunks are rotated (anti-clockwise) about the local vertical axis through the center of the first chunk (not used for ASKI\_nchunk = 6).

## References

- [SFL16] Florian Schumacher, Wolfgang Friederich, and Samir Lamara. A flexible, extendable, modular and computationally efficient approach to scattering-integral-based seismic full waveform inversion. *Geophysical Journal International*, 204(2):1100–1119, 2016.
- [She68] Donald Shepard. A two-dimensional interpolation function for irregularly-spaced data. In *Proceedings of the 1968 23rd ACM national conference*, ACM '68, pages 517–524, New York, NY, USA, 1968. ACM.

## History

This is a section on the history of this document, i.e. its previously published versions, as referred to by the GNU Free Documentation License (version 1.3).

### Using SPECSEM3D\_GLOBE-7.0.0 for ASKI versions 1.0 to 1.2, Aug 2016

Recognizable snippet from the title page (scaled):

Using SPECSEM3D\_GLOBE-7.0.0 for  
ASKI - Analysis of Sensitivity  
and Kernel Inversion, versions 1.0 to 1.2  
Aug 2016

**Title:** Using SPECSEM3D\_GLOBE-7.0.0 for ASKI versions 1.0 to 1.2, Aug 2016

**Year:** 2016

**Authors:** Florian Schumacher (Ruhr-Universität Bochum, Germany)

This version of this document is provided for download (as of August 2016) at  
[https://github.com/seismology-RUB/SPECSEM3D\\_GLOBE\\_for\\_ASKI/releases/tag/v1.2](https://github.com/seismology-RUB/SPECSEM3D_GLOBE_for_ASKI/releases/tag/v1.2)

**Direct link (as of August 2016):**

[https://github.com/seismology-RUB/SPECSEM3D\\_GLOBE\\_for\\_ASKI/releases/download/v1.2/SPECSEM3D\\_GLOBE\\_for\\_ASKI\\_manual\\_aug-2016.pdf](https://github.com/seismology-RUB/SPECSEM3D_GLOBE_for_ASKI/releases/download/v1.2/SPECSEM3D_GLOBE_for_ASKI_manual_aug-2016.pdf)

### Using SPECSEM3D\_GLOBE-7.0.0 for ASKI version 1.0, February 2016

Recognizable snippet from the title page (scaled):

Using SPECSEM3D\_GLOBE-7.0.0 for  
ASKI - Analysis of Sensitivity  
and Kernel Inversion, version 1.0  
February 2016

**Title:** Using SPECSEM3D\_GLOBE-7.0.0 for ASKI version 1.0, February 2016

**Year:** 2016

**Authors:** Florian Schumacher (Ruhr-Universität Bochum, Germany)

This version of this document is provided for download (as of August 2016) at  
[https://github.com/seismology-RUB/SPECSEM3D\\_GLOBE\\_for\\_ASKI/releases/tag/v1.0](https://github.com/seismology-RUB/SPECSEM3D_GLOBE_for_ASKI/releases/tag/v1.0)

**Direct link (as of August 2016):**

[https://github.com/seismology-RUB/SPECSEM3D\\_GLOBE\\_for\\_ASKI/releases/download/v1.0/SPECSEM3D\\_GLOBE\\_for\\_ASKI\\_1-0\\_manual\\_feb-2016.pdf](https://github.com/seismology-RUB/SPECSEM3D_GLOBE_for_ASKI/releases/download/v1.0/SPECSEM3D_GLOBE_for_ASKI_1-0_manual_feb-2016.pdf)

# GNU Free Documentation License

Version 1.3, 3 November 2008

Copyright © 2000, 2001, 2002, 2007, 2008 Free Software Foundation, Inc.

`<http://fsf.org/>`

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

## Preamble

The purpose of this License is to make a manual, textbook, or other functional and useful document “free” in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondly, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of “copyleft”, which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

## 1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The “**Document**”, below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as “**you**”. You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A “**Modified Version**” of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A “**Secondary Section**” is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document’s overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The “**Invariant Sections**” are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this

License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The “**Cover Texts**” are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A “**Transparent**” copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not “Transparent” is called “**Opaque**”.

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The “**Title Page**” means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, “Title Page” means the text near the most prominent appearance of the work’s title, preceding the beginning of the body of the text.

The “**publisher**” means any person or entity that distributes copies of the Document to the public.

A section “**Entitled XYZ**” means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as “**Acknowledgements**”, “**Dedications**”, “**Endorsements**”, or “**History**”.) To “**Preserve the Title**” of such a section when you modify the Document means that it remains a section “Entitled XYZ” according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

## 2. VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may

accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

### **3. COPYING IN QUANTITY**

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

### **4. MODIFICATIONS**

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.
- B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.



- C. State on the Title page the name of the publisher of the Modified Version, as the publisher.
- D. Preserve all the copyright notices of the Document.
- E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
- F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
- G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.
- H. Include an unaltered copy of this License.
- I. Preserve the section Entitled "History", Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.
- J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.
- K. For any section Entitled "Acknowledgements" or "Dedications", Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
- L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
- M. Delete any section Entitled "Endorsements". Such a section may not be included in the Modified Version.
- N. Do not retitle any existing section to be Entitled "Endorsements" or to conflict in title with any Invariant Section.
- O. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version's license notice. These titles must be distinct from any other section titles.

You may add a section Entitled "Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties—for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only

one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

## **5. COMBINING DOCUMENTS**

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled “History” in the various original documents, forming one section Entitled “History”; likewise combine any sections Entitled “Acknowledgements”, and any sections Entitled “Dedications”. You must delete all sections Entitled “Endorsements”.

## **6. COLLECTIONS OF DOCUMENTS**

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

## **7. AGGREGATION WITH INDEPENDENT WORKS**

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an “aggregate” if the copyright resulting from the compilation is not used to limit the legal rights of the compilation’s users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document’s Cover Texts may be

placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

## **8. TRANSLATION**

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled “Acknowledgements”, “Dedications”, or “History”, the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

## **9. TERMINATION**

You may not copy, modify, sublicense, or distribute the Document except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, or distribute it is void, and will automatically terminate your rights under this License.

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, receipt of a copy of some or all of the same material does not give you any rights to use it.

## **10. FUTURE REVISIONS OF THIS LICENSE**

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See <http://www.gnu.org/copyleft/>.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License “or any later version” applies to it, you

have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation. If the Document specifies that a proxy can decide which future versions of this License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Document.

## 11. RELICENSING

“Massive Multiauthor Collaboration Site” (or “MMC Site”) means any World Wide Web server that publishes copyrightable works and also provides prominent facilities for anybody to edit those works. A public wiki that anybody can edit is an example of such a server. A “Massive Multiauthor Collaboration” (or “MMC”) contained in the site means any set of copyrightable works thus published on the MMC site.

“CC-BY-SA” means the Creative Commons Attribution-Share Alike 3.0 license published by Creative Commons Corporation, a not-for-profit corporation with a principal place of business in San Francisco, California, as well as future copyleft versions of that license published by that same organization.

“Incorporate” means to publish or republish a Document, in whole or in part, as part of another Document.

An MMC is “eligible for relicensing” if it is licensed under this License, and if all works that were first published under this License somewhere other than this MMC, and subsequently incorporated in whole or in part into the MMC, (1) had no cover texts or invariant sections, and (2) were thus incorporated prior to November 1, 2008.

The operator of an MMC Site may republish an MMC contained in the site under CC-BY-SA on the same site at any time before August 1, 2009, provided the MMC is eligible for relicensing.

## **ADDENDUM: How to use this License for your documents**

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

Copyright © YEAR YOUR NAME. Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled “GNU Free Documentation License”.

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the “with ... Texts.” line with this:

with the Invariant Sections being LIST THEIR TITLES, with the Front-Cover Texts being LIST, and with the Back-Cover Texts being LIST.

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.