Internet Engineering Task Force (IETF)
Request for Comments: 6779
Category: Standards Track
ISSN: 2070-1721

U. Herberg
LIX, Ecole Polytechnique
R. Cole
US Army CERDEC
I. Chakeres
DRS CenGen

October 2012

Definition of Managed Objects for the Neighborhood Discovery Protocol

Abstract

This document defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes objects for configuring parameters of the Neighborhood Discovery Protocol (NHDP) process on a router. The MIB module defined in this document, denoted NHDP-MIB, also reports state, performance information, and notifications about NHDP. This additional state and performance information is useful to troubleshoot problems and performance issues during neighbor discovery.

Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in Section 2 of RFC 5741.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at http://www.rfc-editor.org/info/rfc6779.

Table of Contents

1. Introduction

This document defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes objects for configuring parameters of the Neighborhood Discovery Protocol (NHDP) [RFC6130] process on a router. The MIB module defined in this document, denoted NHDP-MIB, also reports state, performance information, and notifications about NHDP. This additional state and performance information is useful to troubleshoot problems and performance issues during neighbor discovery.

2. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to section 7 of RFC 3410 [RFC3410].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIv2, which is described in STD 58, RFC 2578 [RFC2578], STD 58, RFC 2579 [RFC2579] and STD 58, RFC 2580 [RFC2580].

3. Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and OPTIONAL" in this document are to be interpreted as described in [RFC2119].

4. Overview

[RFC6130] allows a router to discover and track topological information of routers up to two hops away by virtue of exchanging HELLO messages. This information is useful for routers running various routing and multicast flooding protocols developed within the IETF MANET Working Group.

4.1. Terms

The following definitions apply throughout this document:

- Notification Objects - triggers and associated notification messages allowing for asynchronous tracking of pre-defined events on the managed router.
- Configuration Objects - switches, tables, and objects that are initialized to default settings or set through the management interface defined by this MIB module.
- State Objects - automatically generated values that define the current operating state of the NHDP instance in the router.
- Performance Objects - automatically generated values that help an administrator or automated tool to assess the performance of the NHDP instance on the router and the overall discovery performance within the Mobile Ad Hoc Network (MANET).

4.2. Notation

The same notations as defined in [RFC6130] are used throughout this document.

5. Structure of the MIB Module

This section presents the structure of the NHDP-MIB module. The MIB module is arranged into the following structure:

- nhdpNotifications - objects defining NHDP-MIB notifications.
- nhdpObjects - defining objects within this MIB module. The objects are arranged into the following groups:
  - Configuration Group - defining objects related to the configuration of the NHDP instance on the router.
  - State Group - defining objects that reflect the current state of the NHDP instance running on the router.
  - Performance Group - defining objects that are useful to a management station when characterizing the performance of NHDP on the router and in the MANET.
- nhdpConformance - defining the minimal and maximal conformance requirements for implementations of this MIB module.

5.1. Notifications

This section describes the use of notifications and mechanisms to enhance the ability to manage NHDP routing domains.

5.1.1. Introduction

Notifications can be emitted by a router running an instance of this specification as a reaction to a specific event. This allows a network manager to efficiently determine the source of problems or significant changes of configuration or topology, instead of polling a possibly large number of routers.

5.1.2. Notification Generation

When an exception event occurs, the application notifies the local agent, which sends a notification to the appropriate SNMP management stations. The message includes the notification type and may include a list of notification-specific variables. Section 7 contains the notification definitions, which includes the variable lists. At least one IP address of the router that originates the notification is included in the variable list so that the network manager may determine the source of the notification.

5.1.3. Limiting Frequency of Notifications

To limit the frequency of notifications, the following additional mechanisms are suggested, similar to those in [RFC4750].

5.1.3.1. Ignoring Initial Activity

The majority of critical events occur when NHDP is first enabled on a router, at which time the symmetric neighbors and two-hop neighbors of the router are discovered. During this initial period, a potential flood of notifications is unnecessary since the events are expected. To avoid unnecessary notifications, a router SHOULD NOT originate expected notifications until a certain time interval has elapsed, which is to be predefined by the network manager. It is RECOMMENDED that this time interval is at least 3 x nhdpHelloInterval, so that symmetric neighbors are discovered. The suppression window for notifications is started when the nhdpIfStatus transitions from its default value of 'false(2)' to 'true(1)'.

5.1.3.2. Throttling Notifications

The mechanism for throttling the notifications is the same as in [RFC4750] (i.e., the number of transmitted notifications per time is bounded).

Appropriate values for the window time and upper bound are to be selected by the network manager and depend on the deployment of the MANET. If NHDP is deployed on a lossy, wireless medium, sending too many notifications in a short time interval may lead to collisions and dropped packets. In particular, in dense deployments of routers running NHDP (i.e., where each router has many neighbors), a change of the local topology may trigger many notifications at the same time. [RFC4750] recommends "7 traps with a window time of 10 seconds" as the upper bound. As NHDP is expected to be deployed in more lossy channels than OSPF, it is RECOMMENDED to choose a lower threshold for the number of notifications per time than that. Specifically, it is RECOMMENDED that the threshold value for the objects reflecting the change be set to a value of '10' and the DEFAULT values for these objects within the Notifications Group be set to this value. Further, a time window for the change objects is defined within this MIB module. It is RECOMMENDED that if the number of occurrences exceeds the change threshold within the previous change window, then the notification is to be sent. Furthermore, it is RECOMMENDED that the value for this window be set to at least 5 times the nhdpHelloInterval.

The following objects are used to define the thresholds and time windows for specific notifications defined in the NHDP-MIB module: nhdpNbrStateChangeThreshold, nhdpNbrStateChangeWindow, nhdp2HopNbrStateChangeThreshold, and nhdp2HopNbrStateChangeWindow.

5.1.3.3. One Notification per Event

Similar to the mechanism in [RFC4750], only one notification is sent per event.

5.2. The Configuration Group

The router running NHDP is configured with a set of controls. The authoritative list of configuration controls within the NHDP-MIB module are found within the MIB module itself. Generally, an attempt was made in developing the NHDP-MIB module to support all configuration objects defined in [RFC6130]. For all of the configuration parameters, the same constraints and default values of these parameters as defined in [RFC6130] are followed. Refer to [RFC5148] for guidance on setting jitter-related parameters, e.g., nhdpMaxJitter.

5.3. The State Group

The State Group reports current state information of a router running NHDP. The NHDP-MIB State Group tables were designed to contain the complete set of state information defined within the information bases specified in Sections 6, 7, and 8 of [RFC6130].

Two constructs, i.e., TEXTUAL-CONVENTIONs, are defined to support the tables in the State Group. NHDP stores and indexes information through sets of (dynamically defined) addresses, i.e., address sets. Within SMIv2, it is not possible to index tables with variably defined address sets. Hence, these TEXTUAL-CONVENTIONs are defined to provide a local mapping between NHDP-managed address sets and SMIv2 table indexing. These constructs are the NeighborIfIndex and NeighborRouterIndex. These are locally (to the router) defined, unique identifiers of virtual neighbors and neighbor interfaces. Due to the nature of NHDP, the local router may have identified distinct address sets but is not able to associate these as a single interface. Hence, two or more NeighborIfIndexes pointing to multiple distinct address sets may, in fact, be related to a common neighbor interface. This ambiguity may also hold with respect to the assignment of the NeighborRouterIndex. The local MIB agent is responsible for managing, aggregating, and retiring the defined indexes and for updating MIB tables using these indexes as the local router learns more about its neighbors' topologies. These constructs are used to define indexes to the appropriate State Group tables and to correlate table entries to address sets, virtual neighbor interfaces, and virtual neighbors within the MANET.

5.4. The Performance Group

The Performance Group reports values relevant to system performance. Unstable neighbors or 2-hop neighbors and frequent changes of sets can have a negative influence on the performance of NHDP. This MIB module defines several objects that can be polled in order to, e.g., calculate histories or monitor frequencies of changes. This may help the network administrator to determine unusual topology changes or other changes that affect stability and reliability of the MANET. One such framework is specified in [REPORT-MIB].

5.5. Tables and Indexing

The NHDP-MIB module contains a number of tables that record data related to:

- the local router,
- a local MANET interface on the router,

- other routers that are 1 hop removed from the local router,
- interfaces on other routers that are 1 hop removed from the local router, and
- other routers that are 2 hops removed from the local router.

The NHDP-MIB module's tables are indexed via the following constructs:

- nhdpIfIndex - the IfIndex of the local router on which NHDP is configured.
- nhdpDiscIfIndex - a locally managed index representing a known interface on a neighboring router.
- nhdpDiscRouterIndex - a locally managed index representing an ID of a known neighboring router.

These tables and their indexing are:

- nhdpInterfaceTable - describes the configuration of the interfaces of this router. This table has INDEX { nhdpIfIndex }.
- nhdpLibLocalIfSetTable - records all network addresses that are defined as local interface network addresses on this router. This table has INDEX { nhdpLibLocalIfSetIndex }.
- nhdpLibRemovedIfAddrSetTable - records network addresses that were recently used as local interface network addresses on this router but have been removed. This table has INDEX { nhdpLibRemovedIfAddrSetIndex }.
- nhdpInterfaceStateTable - records state information related to specific interfaces of this router. This table has INDEX { nhdpIfIndex }.
- nhdpDiscIfSetTable - includes the nhdpDiscRouterIndex of the discovered router, the nhdpDiscIfIndex of the discovered interface, and the current set of addresses associated with this neighbor interface. This table has INDEX { nhdpDiscIfSetIndex }.
- nhdpIibLinkSetTable - for each local interface, records all links belonging to other routers that are, or recently were, 1-hop neighbors to this router. This table has INDEX { nhdpIfIndex, nhdpDiscIfIndex }.

- nhdpIib2HopSetTable - for each local interface, records network addresses (one at a time) of symmetric 2-hop neighbors and the symmetric links to symmetric 1-hop neighbors of this router through which these symmetric 2-hop neighbors can be reached. This table has INDEX { nhdpIfIndex, nhdpDiscIfIndex, nhdpIib2HopSetIpAddressType, nhdpIib2HopSetIpAddress }.

- nhdpNibNeighborSetTable - records all network addresses of each 1-hop neighbor to this router. This table has INDEX { nhdpDiscRouterIndex }.

- nhdpNibLostNeighborSetTable - records network addresses of other routers that were recently symmetric 1-hop neighbors to this router but are now advertised as lost. This table has INDEX { nhdpDiscRouterIndex }.

- nhdpInterfacePerfTable - records performance objects that are measured for each local NHDP interface on this router. This table has INDEX { nhdpIfIndex }.

- nhdpDiscIfSetPerfTable - records performance objects that are measured for each discovered interface of a neighbor of this router. This table has INDEX { nhdpDiscIfIndex }.

- nhdpDiscNeighborSetPerfTable - records performance objects that are measured for discovered neighbors of this router. This table has INDEX { nhdpDiscRouterIndex }.

- nhdpIib2HopSetPerfTable - records performance objects that are measured for discovered 2-hop neighbors of this router. This table has INDEX { nhdpDiscRouterIndex }.

6. Relationship to Other MIB Modules

This section specifies the relationship of the MIB module contained in this document to other standards, particularly to standards containing other MIB modules. MIB modules and specific definitions imported from MIB modules that SHOULD be implemented in conjunction with the MIB module contained within this document are identified in this section.

6.1. Relationship to the SNMPv2-MIB

The System group in the SNMPv2-MIB module [RFC3418] is defined as being mandatory for all systems, and the objects apply to the entity as a whole. The System group provides identification of the management entity and certain other system-wide data. The NHDP-MIB module does not duplicate those objects.

6.2. Relationship to Routing Protocol MIB Modules Relying on the NHDP-MIB Module

[RFC6130] allows routing protocols to rely on the neighborhood information that is discovered by means of HELLO message exchange. In order to allow for troubleshooting, fault isolation, and management of such routing protocols through a routing protocol MIB module, it may be desired to align the State Group tables of the NHDP-MIB module and the routing protocol MIB module. This is accomplished through the definition of two TEXTUAL-CONVENTIONs in the NHDP-MIB module: the NeighborIfIndex and the NeighborRouterIndex. These object types are used to develop indexes into common NHDP-MIB module and routing protocol State Group tables. These objects are locally significant but should be locally common to the NHDP-MIB module and the routing protocol MIB module implemented on a common networked router. This will allow for improved cross-referencing of information across the two MIB modules.

6.3. MIB Modules Required for IMPORTS

The following NHDP-MIB module IMPORTS objects from SNMPv2-SMI [RFC2578], SNMPv2-TC [RFC2579], SNMPv2-CONF [RFC2580], IF-MIB [RFC2863], INET-ADDRESS-MIB [RFC4001], and FLOAT-TC-MIB [RFC6340].

7. Definitions

This section contains the MIB module defined by the specification.

```
NHDP-MIB DEFINITIONS ::= BEGIN

-- This MIB module defines objects for the management of
-- NHDP (RFC 6130) - The Neighborhood Discovery Protocol,
-- Clausen, T., Dearlove, C., and J. Dean, January 2011.

IMPORTS

    MODULE-IDENTITY, OBJECT-TYPE, NOTIFICATION-TYPE,
    Counter32, Counter64, Integer32, Unsigned32, mib-2,
                TimeTicks
                FROM SNMPv2-SMI  -- RFC 2578

    TEXTUAL-CONVENTION, TruthValue, TimeStamp,
                RowStatus
                FROM SNMPv2-TC  -- RFC 2579

    MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP
                FROM SNMPv2-CONF  -- STD 58
```

```
    SnmpAdminString
                FROM SNMP-FRAMEWORK-MIB  -- RFC 3411

    InetAddressType, InetAddress,
    InetAddressPrefixLength
                FROM INET-ADDRESS-MIB  -- RFC 4001
    InterfaceIndex
                FROM IF-MIB  -- RFC 2863

    Float32TC
                FROM FLOAT-TC-MIB  -- RFC 6340
    ;

nhdpMIB MODULE-IDENTITY
       LAST-UPDATED "201210221000Z" -- 22 October 2012
       ORGANIZATION "IETF MANET Working Group"
       CONTACT-INFO
       "WG E-Mail: manet@ietf.org

        WG Chairs: sratliff@cisco.com
                   jmacker@nrl.navy.mil


        Editors:   Ulrich Herberg
                   LIX, Ecole Polytechnique
                   91128 Palaiseau Cedex
                   France

                   ulrich@herberg.name
                   http://www.herberg.name/


                   Robert G. Cole
                   US Army CERDEC
                   Space and Terrestrial Communications
                   6010 Frankford Street
                   Bldg 6010, Room 453H
                   Aberdeen Proving Ground, Maryland 21005
                   USA
                   +1 443 395-8744

                   robert.g.cole@us.army.mil
                   http://www.cs.jhu.edu/~rgcole/
```

```
                    Ian D Chakeres
                    DRS CenGen
                    9250 Bendix Road North
                    Columbia, Maryland  21045
                    USA

                    ian.chakeres@gmail.com
                    http://www.ianchak.com/"

        DESCRIPTION
            "This NHDP-MIB module is applicable to routers
             implementing the Neighborhood Discovery Protocol
             defined in RFC 6130.

             Copyright (c) 2012 IETF Trust and the persons
             identified as authors of the code.  All rights reserved.

             Redistribution and use in source and binary forms, with
             or without modification, is permitted pursuant to, and
             subject to the license terms contained in, the Simplified
             BSD License set forth in Section 4.c of the IETF Trust's
             Legal Provisions Relating to IETF Documents
             (http://trustee.ietf.org/license-info).

             This version of this MIB module is part of RFC 6779; see
             the RFC itself for full legal notices."

        -- revision
        REVISION "201210221000Z" -- 22 October 2012
        DESCRIPTION
             "Initial version of this MIB module,
              published as RFC 6779."
        ::= { mib-2 213 }

--
-- Top-Level Components of this MIB Module
--
nhdpNotifications OBJECT IDENTIFIER ::= { nhdpMIB 0 }
nhdpObjects       OBJECT IDENTIFIER ::= { nhdpMIB 1 }
nhdpConformance   OBJECT IDENTIFIER ::= { nhdpMIB 2 }

--
-- TEXTUAL-CONVENTIONs
--
   -- Two new TEXTUAL-CONVENTIONs have been defined in
   -- this MIB module for indexing into the following
   -- tables and indexing into other tables in other MIB modules.
   -- This was necessary because NHDP manages and
```

```
   -- indexes based upon dynamic address tuples, i.e.,
   -- address sets, while SMI requires statically
   -- defined indexes for accessing its table rows.
   -- The NeighborIfIndex defines a unique (to the local router)
   -- index referencing a discovered virtual interface on another
   -- neighbor within the MANET.  The NeighborRouterIndex defines a
   -- unique (to the local router) index referencing a discovered
   -- virtual neighbor within the MANET.
   --
   -- Due to the nature of NHDP,
   -- different indexes may be related to common neighbor
   -- interfaces or common neighbor routers, but the information
   -- obtained through NHDP has not allowed the local router
   -- to relate these virtual objects (i.e., interfaces or routers)
   -- at this point in time.  As more topology information
   -- is gathered by the local router, it may associate
   -- virtual interfaces or routers and collapse these
   -- indexes appropriately.

   -- Multiple addresses can be associated with a
   -- given NeighborIfIndex.  Each NeighborIfIndex is
   -- associated with a NeighborRouterIndex.  Throughout
   -- the nhdpStateObjGroup, the
   -- NeighborIfIndex and the NeighborRouterIndex are used
   -- to define the set of IpAddrs related to a virtual
   -- neighbor interface or virtual neighbor under discussion.

NeighborIfIndex ::= TEXTUAL-CONVENTION
   DISPLAY-HINT "d"
   STATUS       current
   DESCRIPTION
      "An arbitrary, locally unique identifier associated with a
       virtual interface of a discovered NHDP neighbor.
       Due to the nature of NHDP, the local router
       may not know if two distinct addresses belong to the
       same interface of a neighbor or to two different
       interfaces.  As the local router gains more
       knowledge of its neighbors, its local view may change, and
       this table will be updated to reflect the local router's
       current understanding, associating address sets to neighbor
       interfaces.  The local router identifies a virtual neighbor
       interface through the receipt of address lists advertised
       through an NHDP HELLO message.

       All objects of type NeighborIfIndex are assigned by the agent
       out of a common number space.
```

```
        The value for each discovered virtual neighbor
        interface may not remain constant from
        one re-initialization of the entity's network management
        agent to the next re-initialization.  If the
        local router gains information associating two virtual
        interfaces on a neighbor as a common interface,
        then the agent MUST aggregate the two address sets to
        a single index chosen from the set of aggregated indexes,
        and it MUST update all tables in this
        MIB module that are indexed by indexes
        of type NeighborIfIndex.  It MAY then reuse freed
        index values following the next agent restart.

        The specific value is meaningful only within a given SNMP
        entity."
     SYNTAX       Unsigned32 (1..2147483647)

NeighborRouterIndex ::= TEXTUAL-CONVENTION
    DISPLAY-HINT "d"
    STATUS       current
    DESCRIPTION
       "An arbitrary, locally unique identifier associated with a
        virtual discovered neighbor (one or two hop).  Due to the
        nature of NHDP, the local router may identify
        multiple virtual neighbors that, in fact, are one and
        the same.  Neighbors that are two hops away with more than
        one advertised address will exhibit this behavior.  As the
        local router's knowledge of its neighbors' topology
        increases, the local router will be able to associate
        multiple virtual neighbor indexes into a single virtual
        neighbor index chosen from the set of aggregated indexes;
        it MUST update all tables in this MIB module indexed by these
        indexes, and it MAY reuse the freed indexes following the
        next agent re-initialization.

        All objects of type NeighborRouterIndex are assigned by
        the agent out of a common number space.

        The NeighborRouterIndex defines a discovered NHDP peer
        virtual neighbor of the local router.
        The value for each discovered virtual neighbor index MUST
        remain constant at least from one re-initialization of
        the entity's network management agent to the next
        re-initialization, except if an application is deleted
        and re-created.

        The specific value is meaningful only within a given SNMP
        entity.  A NeighborRouterIndex value MUST not be reused
```

```
       until the next agent restart."
    SYNTAX       Unsigned32 (1..2147483647)

--
-- nhdpObjects
--

--    1) Configuration Objects Group
--    2) State Objects Group
--    3) Performance Objects Group

--
-- nhdpConfigurationObjGrp
--

-- Contains the NHDP objects that configure specific options
-- that determine the overall performance and operation of
-- NHDP.

nhdpConfigurationObjGrp  OBJECT IDENTIFIER ::= { nhdpObjects 1 }

   nhdpInterfaceTable  OBJECT-TYPE
      SYNTAX      SEQUENCE OF NhdpInterfaceEntry
      MAX-ACCESS  not-accessible
      STATUS      current
      DESCRIPTION
         "The nhdpInterfaceTable describes the
          configuration of the interfaces of this router
          that are intended to use MANET control protocols.
          As such, this table 'sparse augments' the ifTable
          specifically when NHDP is to be configured to
          operate over this interface.  The interface is
          identified by the ifIndex from the interfaces
          group defined in the Interfaces Group MIB module.

          A conceptual row in this table exists if and only
          if either a manager has explicitly created the row
          or there is an interface on the managed device
          that supports and runs NHDP.

          The manager can create a row by setting
          rowStatus to 'createAndGo' or 'createAndWait'.
          Row objects having associated DEFVAL clauses are
          automatically defined by the agent with these
          values during row creation, unless the manager
          explicitly defines these object values during the
          row creation.
```

```
            If the corresponding entry with ifIndex value
            is deleted from the Interface Table, then the entry
            in this table is automatically deleted,
            NHDP is disabled on this interface,
            and all configuration and state information
            related to this interface is to be removed
            from memory."
         REFERENCE
            "RFC 2863 - The Interfaces Group MIB, McCloghrie,
            K., and F. Kastenholtz, June 2000"
      ::= { nhdpConfigurationObjGrp 1 }

      nhdpInterfaceEntry  OBJECT-TYPE
         SYNTAX      NhdpInterfaceEntry
         MAX-ACCESS  not-accessible
         STATUS      current
         DESCRIPTION
            "The nhdpInterfaceEntry describes one NHDP
            local interface configuration as indexed by
            its ifIndex as defined in the Standard MIB II
            Interface Table (RFC 2863).

            The objects in this table are persistent, and when
            written, the device SHOULD save the change to
            non-volatile storage.  For further information
            on the storage behavior for these objects, refer
            to the description for the nhdpIfRowStatus
            object."
         INDEX { nhdpIfIndex }
      ::= { nhdpInterfaceTable 1 }

      NhdpInterfaceEntry ::=
         SEQUENCE {
            nhdpIfIndex
               InterfaceIndex,
            nhdpIfName
               SnmpAdminString,
            nhdpIfStatus
               TruthValue,
            nhdpHelloInterval
               Unsigned32,
            nhdpHelloMinInterval
               Unsigned32,
            nhdpRefreshInterval
               Unsigned32,
            nhdpLHoldTime
               Unsigned32,
            nhdpHHoldTime
```

```
            Unsigned32,
         nhdpHystAcceptQuality
            Float32TC,
         nhdpHystRejectQuality
            Float32TC,
         nhdpInitialQuality
            Float32TC,
         nhdpInitialPending
            TruthValue,
         nhdpHpMaxJitter
            Unsigned32,
         nhdpHtMaxJitter
            Unsigned32,
         nhdpIfRowStatus
            RowStatus
      }

   nhdpIfIndex  OBJECT-TYPE
      SYNTAX      InterfaceIndex
      MAX-ACCESS  not-accessible
      STATUS      current
      DESCRIPTION
         "This value MUST correspond to an ifIndex referring
          to a valid entry in the Interfaces Table."
      REFERENCE
         "RFC 2863 - The Interfaces Group MIB, McCloghrie, K.,
          and F. Kastenholtz, June 2000"
   ::= { nhdpInterfaceEntry 1 }

   nhdpIfName  OBJECT-TYPE
      SYNTAX      SnmpAdminString
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "The textual name of the interface.  The value of this
          object SHOULD be the name of the interface as assigned by
          the local device.  This can be a text-name, such as 'le0'
          or a simple port number, such as '1',
          depending on the interface-naming syntax of the device.

          If there is no local name or this object is otherwise not
          applicable, then this object contains a zero-length string."
   ::= { nhdpInterfaceEntry 2 }

   nhdpIfStatus  OBJECT-TYPE
      SYNTAX      TruthValue
      MAX-ACCESS  read-create
      STATUS      current
```

```
      DESCRIPTION
         "nhdpIfStatus indicates whether this interface is
          currently running NHDP.  A value of 'true(1)' indicates
          that NHDP is running on this interface.
          A value of 'false(2)' indicates that NHDP is not
          currently running on this interface.  This corresponds
          to the I_manet parameter in the Local Interface Set
          of NHDP."
      DEFVAL { false }
   ::= { nhdpInterfaceEntry 3 }

   --
   -- Interface Parameters - Message Intervals
   --

   nhdpHelloInterval  OBJECT-TYPE
      SYNTAX      Unsigned32
      UNITS       "milliseconds"
      MAX-ACCESS  read-create
      STATUS      current
      DESCRIPTION
         "nhdpHelloInterval corresponds to
          HELLO_INTERVAL of NHDP and represents the
          maximum time between the transmission of two
          successive HELLO messages on this MANET interface.

          Guidance for setting this object may be found
          in Section 5 of the NHDP specification (RFC 6130),
          which indicates that:
             o nhdpHelloInterval > 0
             o nhdpHelloInterval >= nhdpHelloMinInterval"
      REFERENCE
         "Section 5 on Protocol Parameters and
          Constraints of RFC 6130 - Mobile Ad Hoc
          Network (MANET) Neighborhood Discovery
          Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
      DEFVAL { 2000 }
   ::= { nhdpInterfaceEntry 4 }

   nhdpHelloMinInterval  OBJECT-TYPE
      SYNTAX      Unsigned32
      UNITS       "milliseconds"
      MAX-ACCESS  read-create
      STATUS      current
      DESCRIPTION
         "nhdpHelloMinInterval corresponds to
          HELLO_MIN_INTERVAL of NHDP and represents
```

```
            the minimum interval between transmission
            of two successive HELLO messages on this
            MANET interface.

            Guidance for setting this object may be found
            in Section 5 of the NHDP specification (RFC 6130),
            which indicates that:
               o nhdpHelloMinInterval <= nhdpHelloInterval"
         REFERENCE
            "Section 5 on Protocol Parameters and
            Constraints of RFC 6130 - Mobile Ad Hoc Network
            (MANET) Neighborhood Discovery Protocol (NHDP),
            Clausen, T., Dearlove, C., and J. Dean, April 2011"
         DEFVAL { 500 }
      ::= { nhdpInterfaceEntry 5 }

      nhdpRefreshInterval  OBJECT-TYPE
         SYNTAX      Unsigned32
         UNITS       "milliseconds"
         MAX-ACCESS  read-create
         STATUS      current
         DESCRIPTION
            "nhdpRefreshInterval corresponds to
            REFRESH_INTERVAL of NHDP and represents the
            maximum interval between advertisements of
            each 1-hop neighbor network address and its
            status.  Each advertisement is in a HELLO
            message on this MANET interface.

            Guidance for setting this object may be found
            in Section 5 of the NHDP specification (RFC 6130),
            which indicates that:
               o nhdpRefreshInterval >= nhdpHelloInterval"
         REFERENCE
            "Section 5 on Protocol Parameters and
            Constraints of RFC 6130 - Mobile Ad Hoc Network
            (MANET) Neighborhood Discovery Protocol (NHDP),
            Clausen, T., Dearlove, C., and J. Dean, April 2011"
         DEFVAL { 2000 }
      ::= { nhdpInterfaceEntry 6 }

      --
      -- Interface Parameters - Information Validity times
      --

      nhdpLHoldTime  OBJECT-TYPE
         SYNTAX      Unsigned32
         UNITS       "milliseconds"
```

```
      MAX-ACCESS  read-create
      STATUS      current
      DESCRIPTION
         "nhdpLHoldTime corresponds to
          L_HOLD_TIME of NHDP and represents the period
          of advertisement, on this MANET interface, of
          former 1-hop neighbor network addresses as lost
          in HELLO messages, allowing recipients of these
          HELLO messages to accelerate removal of this
          information from their Link Sets.

          Guidance for setting this object may be found
          in Section 5 of the NHDP specification (RFC 6130),
          which indicates that it should be assigned a
          value significantly greater than the refresh
          interval held by nhdpRefreshInterval."
      REFERENCE
         "Section 5 on Protocol Parameters and
          Constraints of RFC 6130 - Mobile Ad Hoc Network
          (MANET) Neighborhood Discovery Protocol (NHDP),
          Clausen, T., Dearlove, C., and J. Dean, April 2011"
      DEFVAL { 6000 }
   ::= { nhdpInterfaceEntry 7 }

   nhdpHHoldTime  OBJECT-TYPE
      SYNTAX      Unsigned32
      UNITS       "milliseconds"
      MAX-ACCESS  read-create
      STATUS      current
      DESCRIPTION
         "nhdpHHoldTime corresponds to
          H_HOLD_TIME of NHDP and is used as the value
          in the VALIDITY_TIME Message TLV included in all
          HELLO messages on this MANET interface.  It is then
          used by each router receiving such a HELLO message
          to indicate the validity of the information taken
          from that HELLO message and recorded in the receiving
          router's Information Bases.

          Guidance for setting this object may be found
          in Section 5 of the NHDP specification (RFC 6130),
          which indicates that it should be assigned a
          value significantly greater than the refresh interval
          held by nhdpRefreshInterval and must be representable
          as described in RFC 5497."
      REFERENCE
         "Section 5 on Protocol Parameters and
          Constraints of RFC 6130 - Mobile Ad Hoc Network
```

```
            (MANET) Neighborhood Discovery Protocol (NHDP),
            Clausen, T., Dearlove, C., and J. Dean, April 2011"
         DEFVAL { 6000 }
      ::= { nhdpInterfaceEntry 8 }

      --
      -- Interface Parameters - Link Quality
      --

      nhdpHystAcceptQuality  OBJECT-TYPE
         SYNTAX      Float32TC
         MAX-ACCESS  read-create
         STATUS      current
         DESCRIPTION
            "nhdpHystAcceptQuality corresponds to
            HYST_ACCEPT of NHDP and represents the link
            quality threshold at or above which a link becomes
            usable, if it was not already so.

            Guidance for setting this object may be found
            in Section 5 of the NHDP specification (RFC 6130),
            which indicates that:
               o 0 <= nhdpHystRejectQuality
                   <= nhdpHystAcceptQuality <= 1.0

            The default value for this object is 1.0. According to
            RFC 6340:
               Since these textual conventions are defined in terms
               of the OCTET STRING type, the SMI's mechanisms for
               formally setting range constraints are not available.
               MIB designers using these textual conventions will need
               to use DESCRIPTION clauses to spell out any applicable
               range constraints beyond those implied by the underlying
               IEEE types.
            Therefore, this object does not have a DEFVAL clause."
         REFERENCE
            "Section 5 on Protocol Parameters and
            Constraints of RFC 6130 - Mobile Ad Hoc Network
            (MANET) Neighborhood Discovery Protocol (NHDP),
            Clausen, T., Dearlove, C., and J. Dean, April 2011"
      --    DEFVAL { 1.0 }   see DESCRIPTION
      ::= { nhdpInterfaceEntry 9 }

      nhdpHystRejectQuality  OBJECT-TYPE
         SYNTAX      Float32TC
         MAX-ACCESS  read-create
         STATUS      current
         DESCRIPTION
```

```
          "nhdpHystRejectQuality corresponds to
           HYST_REJECT of NHDP and represents the
           link quality threshold below which a
           link becomes unusable, if it was not
           already so.

           Guidance for setting this object may be found
           in Section 5 of the NHDP specification (RFC 6130),
           which indicates that:
              o 0 <= nhdpHystRejectQuality
                  <= nhdpHystAcceptQuality <= 1.0

           The default value for this object is 0.0. According to
           RFC 6340:
              Since these textual conventions are defined in terms
              of the OCTET STRING type, the SMI's mechanisms for
              formally setting range constraints are not available.
              MIB designers using these textual conventions will need
              to use DESCRIPTION clauses to spell out any applicable
              range constraints beyond those implied by the underlying
              IEEE types.
           Therefore, this object does not have a DEFVAL clause."
       REFERENCE
          "Section 5 on Protocol Parameters and
           Constraints of RFC 6130 - Mobile Ad Hoc Network
           (MANET) Neighborhood Discovery Protocol (NHDP),
           Clausen, T., Dearlove, C., and J. Dean, April 2011"
--     DEFVAL { 0.0 }   see DESCRIPTION
    ::= { nhdpInterfaceEntry 10 }

    nhdpInitialQuality  OBJECT-TYPE
       SYNTAX      Float32TC
       MAX-ACCESS  read-create
       STATUS      current
       DESCRIPTION
          "nhdpInitialQuality corresponds to
           INITIAL_QUALITY of NHDP and represents the
           initial quality of a newly identified link.

           Guidance for setting this object may be found
           in Section 5 of the NHDP specification (RFC 6130),
           which indicates that:
              o 0 <= nhdpInitialQuality <= 1.0

           The default value for this object is 1.0. According to
           RFC 6340:
              Since these textual conventions are defined in terms
              of the OCTET STRING type, the SMI's mechanisms for
```

```
                formally setting range constraints are not available.
                MIB designers using these textual conventions will need
                to use DESCRIPTION clauses to spell out any applicable
                range constraints beyond those implied by the underlying
                IEEE types.
             Therefore, this object does not have a DEFVAL clause."
      REFERENCE
         "Section 5 on Protocol Parameters and
          Constraints of RFC 6130 - Mobile Ad Hoc Network
          (MANET) Neighborhood Discovery Protocol (NHDP),
          Clausen, T., Dearlove, C., and J. Dean, April 2011"
--    DEFVAL { 1.0 }   see DESCRIPTION
   ::= { nhdpInterfaceEntry 11 }

   nhdpInitialPending  OBJECT-TYPE
      SYNTAX      TruthValue
      MAX-ACCESS  read-create
      STATUS      current
      DESCRIPTION
         "nhdpInitialPending corresponds to
          INITIAL_PENDING of NHDP.  If the value of this object
          is 'true(1)', then a newly identified link is considered
          pending and is not usable until the link quality
          has reached or exceeded the nhdpHystAcceptQuality
          threshold.

          Guidance for setting this object may be found
          in Section 5 of the NHDP specification (RFC 6130),
          which indicates that:
             o If nhdpInitialQuality >= nhdpHystAcceptQuality,
               then nhdpInitialPending := false(2).
             o If nhdpInitialQuality < nhdpHystRejectQuality,
               then nhdpInitialPending := true(1)."
      REFERENCE
         "Section 5 on Protocol Parameters and
          Constraints of RFC 6130 - Mobile Ad Hoc Network
          (MANET) Neighborhood Discovery Protocol (NHDP),
          Clausen, T., Dearlove, C., and J. Dean, April 2011"
      DEFVAL { false }
   ::= { nhdpInterfaceEntry 12 }

   --
   -- Interface Parameters - Jitter
   --
   nhdpHpMaxJitter  OBJECT-TYPE
      SYNTAX      Unsigned32
      UNITS       "milliseconds"
      MAX-ACCESS  read-create
```

```
      STATUS      current
      DESCRIPTION
         "nhdpHpMaxJitter corresponds to
          HP_MAXJITTER of NHDP and represents the
          value of MAXJITTER used in RFC 5148 for
          periodically generated HELLO messages on
          this MANET interface.

          Guidance for setting this object may be found
          in Section 5 of RFC 5148, which indicates that:
             o nhdpHpMaxJitter <= nhdpHelloInterval / 2
             o nhdpHpMaxJitter should not be greater
               than nhdpHelloInterval / 4
             o If nhdpMinHelloInterval > 0, then
               nhdpHpMaxJitter <= nhdpHelloMinInterval; and
               nhdpHpMaxJitter should not be greater than
               nhdpHelloMinInterval / 2"
      REFERENCE
         "Section 5 of RFC 5148 - Jitter Considerations in
          Mobile Ad Hoc Networks (MANETs),
          Clausen, T., Dearlove, C., and B. Adamson, February 2008"
      DEFVAL { 500 }
   ::= { nhdpInterfaceEntry 13 }

   nhdpHtMaxJitter  OBJECT-TYPE
      SYNTAX      Unsigned32
      UNITS       "milliseconds"
      MAX-ACCESS  read-create
      STATUS      current
      DESCRIPTION
         "nhdpHtMaxJitter corresponds to
          HT_MAXJITTER of NHDP and represents the
          value of MAXJITTER used in RFC 5148 for
          externally triggered HELLO messages on this
          MANET interface.

          Guidance for setting this object may be found
          in Section 5 of RFC 5148, which indicates that:
             o nhdpHtMaxJitter <= nhdpHelloInterval / 2
             o nhdpHtMaxJitter should not be greater
               than nhdpHelloInterval / 4
             o If nhdpMinHelloInterval > 0, then
               nhdpHtMaxJitter <= nhdpHelloMinInterval; and
               nhdpHtMaxJitter should not be greater than
               nhdpHelloMinInterval / 2"
      REFERENCE
         "Section 5 of RFC 5148 - Jitter Considerations in
          Mobile Ad Hoc Networks (MANETs),
```

```
            Clausen, T., Dearlove, C., and B. Adamson, February 2008"
         DEFVAL { 500 }
      ::= { nhdpInterfaceEntry 14 }

      nhdpIfRowStatus  OBJECT-TYPE
         SYNTAX      RowStatus
         MAX-ACCESS  read-create
         STATUS      current
         DESCRIPTION
            "This object permits management of the table
             by facilitating actions such as row creation,
             construction, and destruction.  The value of
             this object has no effect on whether other
             objects in this conceptual row can be
             modified.

             An entry may not exist in the 'active(1)' state unless all
             objects in the entry have a defined appropriate value.  For
             objects with DEFVAL clauses, the management station
             does not need to specify the value of this object in order
             for the row to transit to the 'active(1)' state; the default
             value for this object is used.  For objects that do not
             have DEFVAL clauses, then the network manager MUST
             specify the value of this object prior to this row
             transitioning to the 'active(1)' state.

             When this object transitions to 'active(1)', all objects
             in this row SHOULD be written to non-volatile (stable)
             storage.  Read-create objects in this row MAY be modified.
             When an object in a row with nhdpIfRowStatus of 'active(1)'
             is changed, then the updated value MUST be reflected in NHDP,
             and this new object value MUST be written to non-volatile
             storage.

             If the value of this object is not equal to 'active(1)',
             all associated entries in the nhdpLibLocalIfSetTable,
             nhdpInterfaceStateTable, nhdpIibLinkSetTable, and
             nhdpInterfacePerfTable MUST be deleted."
         REFERENCE
            "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
             Discovery Protocol (NHDP), Clausen, T., Dearlove,
             C., and J. Dean, April 2011"
         DEFVAL { active }
      ::= { nhdpInterfaceEntry 15 }

      --
      -- Router Parameters - Information Validity Time
      --
```

```
   nhdpNHoldTime  OBJECT-TYPE
      SYNTAX      Unsigned32
      UNITS       "milliseconds"
      MAX-ACCESS  read-write
      STATUS      current
      DESCRIPTION
         "nhdpNHoldTime corresponds to
          N_HOLD_TIME of NHDP and is used as the period
          during which former 1-hop neighbor network
          addresses are advertised as lost in HELLO
          messages, allowing recipients of these HELLO
          messages to accelerate removal of this information
          from their 2-Hop Sets.

          This object is persistent, and when written,
          the entity SHOULD save the change to
          non-volatile storage."
      REFERENCE
         "Section 5 on Protocol Parameters and
          Constraints of RFC 6130 - Mobile Ad Hoc Network
          (MANET) Neighborhood Discovery Protocol (NHDP),
          Clausen, T., Dearlove, C., and J. Dean, April 2011"
      DEFVAL { 6000 }
   ::= { nhdpConfigurationObjGrp 2 }

   nhdpIHoldTime  OBJECT-TYPE
      SYNTAX      Unsigned32
      UNITS       "milliseconds"
      MAX-ACCESS  read-write
      STATUS      current
      DESCRIPTION
         "nhdpIHoldTime corresponds to
          I_HOLD_TIME of NHDP and represents the period
          for which a recently used local interface network
          address is recorded.

          This object is persistent, and when written,
          the entity SHOULD save the change to
          non-volatile storage."
      REFERENCE
         "Section 5 on Protocol Parameters and
          Constraints of RFC 6130 - Mobile Ad Hoc Network
          (MANET) Neighborhood Discovery Protocol (NHDP),
          Clausen, T., Dearlove, C., and J. Dean, April 2011"
      DEFVAL { 6000 }

   ::= { nhdpConfigurationObjGrp 3 }
```

```
   -- A router's Local Information Base (LIB)

   --
   -- Local Interface Set Table
   --

   nhdpLibLocalIfSetTable OBJECT-TYPE
      SYNTAX      SEQUENCE OF NhdpLibLocalIfSetEntry
      MAX-ACCESS  not-accessible
      STATUS      current
      DESCRIPTION
         "A router's Local Interface Set records all
          network addresses that are defined as local
          MANET interface network addresses.
          As such, this table 'sparse augments' the
          nhdpInterfaceTable when network addresses are
          being defined for the interfaces existing within
          the nhdpInterfaceTable.  The local interface
          is defined by the nhdpIfIndex.

          The Local Interface Set consists of Local Interface
          Address Tuples per MANET interface and their prefix
          lengths (in order to determine the network addresses
          related to the interface).

          A conceptual row in this table exists if and only
          if a manager has explicitly created the row.  The
          manager can create a row by setting rowStatus
          to 'createAndGo' or 'createAndWait'.

          Further guidance on the addition or removal of
          local addresses and network addresses is found
          in Section 9 of RFC 6130."
      REFERENCE
          "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
           Discovery Protocol (NHDP), Clausen, T., Dearlove,
           C., and J. Dean, April 2011"
   ::= { nhdpConfigurationObjGrp 4 }

   nhdpLibLocalIfSetEntry  OBJECT-TYPE
      SYNTAX      NhdpLibLocalIfSetEntry
      MAX-ACCESS  not-accessible
      STATUS      current
      DESCRIPTION
         "A router's Local Interface Set consists
          of Configured Interface Address Tuples for each network
          interface.
```

```
            The objects in this table are persistent, and when
            written, the device SHOULD save the change to
            non-volatile storage.  For further information
            on the storage behavior for these objects, refer
            to the description for the nhdpLibLocalIfSetRowStatus
            object."
         REFERENCE
            "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
            Discovery Protocol (NHDP), Clausen, T., Dearlove,
            C., and J. Dean, April 2011"
         INDEX { nhdpLibLocalIfSetIndex }
      ::= { nhdpLibLocalIfSetTable 1 }

      NhdpLibLocalIfSetEntry ::=
         SEQUENCE {
            nhdpLibLocalIfSetIndex
               Integer32,
            nhdpLibLocalIfSetIfIndex
               InterfaceIndex,
            nhdpLibLocalIfSetIpAddrType
               InetAddressType,
            nhdpLibLocalIfSetIpAddr
               InetAddress,
            nhdpLibLocalIfSetIpAddrPrefixLen
               InetAddressPrefixLength,
            nhdpLibLocalIfSetRowStatus
               RowStatus
         }

      nhdpLibLocalIfSetIndex  OBJECT-TYPE
         SYNTAX      Integer32 (0..65535)
         MAX-ACCESS  not-accessible
         STATUS      current
         DESCRIPTION
            "The index for this table.  Necessary
            because multiple addresses may be associated
            with a given nhdpIfIndex."
         REFERENCE
            "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
            Discovery Protocol (NHDP), Clausen, T., Dearlove,
            C., and J. Dean, April 2011"
      ::= { nhdpLibLocalIfSetEntry 1 }

      nhdpLibLocalIfSetIfIndex  OBJECT-TYPE
         SYNTAX      InterfaceIndex
         MAX-ACCESS  read-only
         STATUS      current
         DESCRIPTION
```

```
         "Specifies the local nhdpIfIndex for which this
          IP address was added."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
   ::= { nhdpLibLocalIfSetEntry 2 }

   nhdpLibLocalIfSetIpAddrType  OBJECT-TYPE
      SYNTAX      InetAddressType
      MAX-ACCESS  read-create
      STATUS      current
      DESCRIPTION
         "The type of the nhdpLibLocalIfSetIpAddr
          in the InetAddress MIB (RFC 4001).

          Only the values 'ipv4(1)' and
          'ipv6(2)' are supported."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
   ::= { nhdpLibLocalIfSetEntry 3 }

   nhdpLibLocalIfSetIpAddr  OBJECT-TYPE
      SYNTAX      InetAddress (SIZE(4|16))
      MAX-ACCESS  read-create
      STATUS      current
      DESCRIPTION
         "nhdpLibLocalIfSetIpAddr is an
          address of an interface of
          this router.

          This object is interpreted according to
          the setting of nhdpLibLocalIfSetIpAddrType."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
         C., and J. Dean, April 2011"
   ::= { nhdpLibLocalIfSetEntry 4 }

   nhdpLibLocalIfSetIpAddrPrefixLen  OBJECT-TYPE
      SYNTAX      InetAddressPrefixLength
      MAX-ACCESS  read-create
      STATUS      current
      DESCRIPTION
         "Indicates the number of leading one bits that
          form the mask.  The mask is logically ANDed
```

```
            to the nhdpLibLocalIfSetIpAddr to determine
            the address prefix.  A row match is true
            if the address used as an index falls within
            the network address range defined by the
            address prefix."
         REFERENCE
            "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
            Discovery Protocol (NHDP), Clausen, T., Dearlove,
            C., and J. Dean, April 2011"
      ::= { nhdpLibLocalIfSetEntry 5 }

      nhdpLibLocalIfSetRowStatus  OBJECT-TYPE
         SYNTAX      RowStatus
         MAX-ACCESS  read-create
         STATUS      current
         DESCRIPTION
            "This object permits management of the table
            by facilitating actions such as row creation,
            construction, and destruction.  The value of
            this object has no effect on whether other
            objects in this conceptual row can be
            modified.

            An entry may not exist in the 'active(1)' state unless all
            read-create objects in the entry have a defined
            appropriate value.  As no objects in this table have
            DEFVAL clauses, the management station MUST specify
            the values of all read-create objects prior to this row
            transitioning to the 'active(1)' state.

            When this object transitions to 'active(1)', all objects
            in this row SHOULD be written to non-volatile (stable)
            storage.  Read-create objects in this row MAY be modified.
            When an object in a row with nhdpIfRowStatus of 'active(1)'
            is changed, then the updated value MUST be reflected in NHDP,
            and this new object value MUST be written to non-volatile
            storage."
         REFERENCE
            "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
            Discovery Protocol (NHDP), Clausen, T., Dearlove,
            C., and J. Dean, April 2011"
         DEFVAL { notReady }
       ::= { nhdpLibLocalIfSetEntry 6 }

      --
      -- Removed Interface Addr Set Table
      --
```

```
   nhdpLibRemovedIfAddrSetTable OBJECT-TYPE
      SYNTAX      SEQUENCE OF NhdpLibRemovedIfAddrSetEntry
      MAX-ACCESS  not-accessible
      STATUS      current
      DESCRIPTION
         "A router's Removed Interface Address Set records
          network addresses that were recently used as local
          interface network addresses.  If a router's interface
          network addresses are immutable, then the Removed
          Interface Address Set is always empty and may be omitted.
          It consists of Removed Interface Address Tuples, one
          per network address."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
   ::= { nhdpConfigurationObjGrp 5 }

   nhdpLibRemovedIfAddrSetEntry  OBJECT-TYPE
      SYNTAX      NhdpLibRemovedIfAddrSetEntry
      MAX-ACCESS  not-accessible
      STATUS      current
      DESCRIPTION
         "A router's Removed Interface Address Set consists
          of Removed Interface Address Tuples, one per network
          address:

          (IR_local_iface_addr, IR_time)

          The association between these addresses and the
          router's Interface is found in the Standard MIB II's
          IP address table (RFC 1213)."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
      INDEX { nhdpLibRemovedIfAddrSetIndex }
   ::= { nhdpLibRemovedIfAddrSetTable 1 }

   NhdpLibRemovedIfAddrSetEntry ::=
      SEQUENCE {
         nhdpLibRemovedIfAddrSetIndex
            Integer32,
         nhdpLibRemovedIfAddrSetIpAddrType
            InetAddressType,
         nhdpLibRemovedIfAddrSetIpAddr
            InetAddress,
         nhdpLibRemovedIfAddrSetIpAddrPrefixLen
```

```
            InetAddressPrefixLength,
         nhdpLibRemovedIfAddrSetIfIndex
            InterfaceIndex,
         nhdpLibRemovedIfAddrSetIRTime
            TimeStamp
      }

   nhdpLibRemovedIfAddrSetIndex  OBJECT-TYPE
      SYNTAX      Integer32 (0..65535)
      MAX-ACCESS  not-accessible
      STATUS      current
      DESCRIPTION
         "The index for this table.  Necessary
          because multiple addresses may be associated
          with a given nhdpIfIndex."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
   ::= { nhdpLibRemovedIfAddrSetEntry 1 }

   nhdpLibRemovedIfAddrSetIpAddrType  OBJECT-TYPE
      SYNTAX      InetAddressType
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "The type of the nhdpLibRemovedIfAddrSetIpAddr
          in the InetAddress MIB (RFC 4001).

          Only the values 'ipv4(1)' and
          'ipv6(2)' are supported."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
   ::= { nhdpLibRemovedIfAddrSetEntry 2 }

   nhdpLibRemovedIfAddrSetIpAddr  OBJECT-TYPE
      SYNTAX      InetAddress (SIZE(4|16))
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "nhdpLibRemovedIfAddrSetIpAddr is a
          recently used address of an interface of
          this router."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
```

```
          C., and J. Dean, April 2011"
   ::= { nhdpLibRemovedIfAddrSetEntry 3 }

   nhdpLibRemovedIfAddrSetIpAddrPrefixLen  OBJECT-TYPE
      SYNTAX      InetAddressPrefixLength
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "Indicates the number of leading one bits that
          form the mask.  The mask is logically ANDed
          to the nhdpLibRemovedIfAddrSetIpAddr to determine
          the address prefix.  A row match is true
          if the address used as an index falls within
          the network address range defined by the
          address prefix."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
   ::= { nhdpLibRemovedIfAddrSetEntry 4 }

   nhdpLibRemovedIfAddrSetIfIndex  OBJECT-TYPE
      SYNTAX      InterfaceIndex
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "Specifies the local IfIndex from which this
          IP address was recently removed."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
   ::= { nhdpLibRemovedIfAddrSetEntry 5 }

   nhdpLibRemovedIfAddrSetIRTime  OBJECT-TYPE
      SYNTAX      TimeStamp
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "nhdpLibRemovedIfAddrSetIRTime specifies the value
          of sysUptime when this entry should expire and be
          removed from the nhdpLibRemovedIfAddrSetTable."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
   ::= { nhdpLibRemovedIfAddrSetEntry 6 }
```

```
--
-- nhdpStateObjGrp
--

-- Contains information describing the current state of the NHDP
-- process on this router.

nhdpStateObjGrp  OBJECT IDENTIFIER ::= { nhdpObjects 2 }

   nhdpUpTime  OBJECT-TYPE
      SYNTAX      TimeStamp
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "The value of sysUpTime at the time the current NHDP
          process was initialized."
   ::= { nhdpStateObjGrp 1 }

   nhdpInterfaceStateTable  OBJECT-TYPE
      SYNTAX      SEQUENCE OF NhdpInterfaceStateEntry
      MAX-ACCESS  not-accessible
      STATUS      current
      DESCRIPTION
         "nhdpInterfaceStateTable lists state information
          related to specific interfaces of this router.
          The value of nhdpIfIndex is an ifIndex from the
          interfaces group defined in the Interfaces Group
          MIB.

          The objects in this table are persistent, and when
          written, the entity SHOULD save the change to
          non-volatile storage."
      REFERENCE
         "RFC 2863 - The Interfaces Group MIB, McCloghrie,
          K., and F. Kastenholtz, June 2000."
   ::= { nhdpStateObjGrp 2 }

   nhdpInterfaceStateEntry  OBJECT-TYPE
      SYNTAX      NhdpInterfaceStateEntry
      MAX-ACCESS  not-accessible
      STATUS      current
      DESCRIPTION
         "nhdpInterfaceStateEntry describes one NHDP
          local interface state as indexed by
          its nhdpIfIndex."
      INDEX { nhdpIfIndex }
   ::= { nhdpInterfaceStateTable 1 }
```

```
   NhdpInterfaceStateEntry ::=
      SEQUENCE {
         nhdpIfStateUpTime
            TimeStamp
         }

   nhdpIfStateUpTime  OBJECT-TYPE
      SYNTAX      TimeStamp
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "The value of the sysUpTime when
          NHDP was last initialized on this
          MANET interface."
   ::= { nhdpInterfaceStateEntry 1 }

   --
   -- This table allows for the mapping between discovered
   -- remote interfaces and routers and their addresses.
   --

   nhdpDiscIfSetTable OBJECT-TYPE
      SYNTAX       SEQUENCE OF NhdpDiscIfSetEntry
      MAX-ACCESS   not-accessible
      STATUS       current
      DESCRIPTION
         "A router's set of discovered interfaces on
          neighboring routers."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
   ::= { nhdpStateObjGrp 3 }

   nhdpDiscIfSetEntry  OBJECT-TYPE
      SYNTAX      NhdpDiscIfSetEntry
      MAX-ACCESS  not-accessible
      STATUS      current
      DESCRIPTION
         "The entries include the nhdpDiscRouterIndex of
          the discovered router, the nhdpDiscIfIndex
          of the discovered interface, and the
          current set of addresses associated
          with this neighbor interface.  The
          nhdpDiscIfIndex uniquely identifies
          the remote interface address sets
          through this table.  It does not need
          to be unique across the MANET but MUST
```

```
          be locally unique within this router."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
      INDEX { nhdpDiscIfSetIndex }
   ::= { nhdpDiscIfSetTable 1 }

   NhdpDiscIfSetEntry ::=
      SEQUENCE {
         nhdpDiscIfSetIndex
            Integer32,
         nhdpDiscIfIndex
            NeighborIfIndex,
         nhdpDiscRouterIndex
            NeighborRouterIndex,
         nhdpDiscIfSetIpAddrType
            InetAddressType,
         nhdpDiscIfSetIpAddr
            InetAddress,
         nhdpDiscIfSetIpAddrPrefixLen
            InetAddressPrefixLength
      }

   nhdpDiscIfSetIndex  OBJECT-TYPE
      SYNTAX      Integer32 (0..65535)
      MAX-ACCESS  not-accessible
      STATUS      current
      DESCRIPTION
         "The index for this table.  Necessary
          because multiple addresses may be associated
          with a given nhdpDiscIfIndex."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
   ::= { nhdpDiscIfSetEntry 1 }

   nhdpDiscIfIndex  OBJECT-TYPE
      SYNTAX      NeighborIfIndex
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "The NHDP interface index (locally created)
          of a neighbor's interface.  Used for cross-
          indexing into other NHDP tables and other
          MIB modules."
      REFERENCE
```

```
          "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
           Discovery Protocol (NHDP), Clausen, T., Dearlove,
           C., and J. Dean, April 2011"
      ::= { nhdpDiscIfSetEntry 2 }

      nhdpDiscRouterIndex  OBJECT-TYPE
         SYNTAX      NeighborRouterIndex
         MAX-ACCESS  read-only
         STATUS      current
         DESCRIPTION
            "The NHDP neighbor index (locally created)
             of a neighboring router.  Used for cross-
             indexing into other NHDP tables and other
             MIB modules."
         REFERENCE
            "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
             Discovery Protocol (NHDP), Clausen, T., Dearlove,
             C., and J. Dean, April 2011"
      ::= { nhdpDiscIfSetEntry 3 }

      nhdpDiscIfSetIpAddrType  OBJECT-TYPE
         SYNTAX      InetAddressType
         MAX-ACCESS  read-only
         STATUS      current
         DESCRIPTION
            "The type of the nhdpDiscIfSetIpAddr
             in the InetAddress MIB (RFC 4001).

             Only the values 'ipv4(1)' and
             'ipv6(2)' are supported."
         REFERENCE
            "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
             Discovery Protocol (NHDP), Clausen, T., Dearlove,
             C., and J. Dean, April 2011"
      ::= { nhdpDiscIfSetEntry 4 }

      nhdpDiscIfSetIpAddr  OBJECT-TYPE
         SYNTAX      InetAddress (SIZE(4|16))
         MAX-ACCESS  read-only
         STATUS      current
         DESCRIPTION
            "The nhdpDiscIfSetIpAddr is a
             recently used address of a neighbor
             of this router."
         REFERENCE
            "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
             Discovery Protocol (NHDP), Clausen, T., Dearlove,
             C., and J. Dean, April 2011"
```

```
   ::= { nhdpDiscIfSetEntry 5 }

   nhdpDiscIfSetIpAddrPrefixLen  OBJECT-TYPE
      SYNTAX      InetAddressPrefixLength
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "Indicates the number of leading one bits that
          form the mask.  The mask is logically ANDed
          to the nhdpDiscIfSetIpAddr to determine
          the address prefix.  A row match is true
          if the address used as an index falls within
          the network address range defined by the
          address prefix."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
   ::= { nhdpDiscIfSetEntry 6 }

   -- Interface Information Base (IIB)

   --
   -- Link Set
   --

   nhdpIibLinkSetTable  OBJECT-TYPE
      SYNTAX      SEQUENCE OF NhdpIibLinkSetEntry
      MAX-ACCESS  not-accessible
      STATUS      current
      DESCRIPTION
         "A Link Set of an interface records all links
          from other routers that are, or recently
          were, 1-hop neighbors."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
   ::= { nhdpStateObjGrp 4 }

   nhdpIibLinkSetEntry  OBJECT-TYPE
      SYNTAX      NhdpIibLinkSetEntry
      MAX-ACCESS  not-accessible
      STATUS      current
      DESCRIPTION
         "A Link Set consists of Link Tuples, each
          representing a single link indexed by the
          local and remote interface pair:
```

```
          (L_neighbor_iface_addr_list, L_HEARD_time,
           L_SYM_time, L_quality, L_pending,
           L_lost, L_time).

          The local interface is indexed via the
          nhdpIfIndex.  The 1-hop interface is
          indexed via the nhdpDiscIfIndex.  There
          SHOULD be an entry in this table for each
          local interface and associated 1-hop
          neighbor reachable on this local interface.

          Note that L_quality is not included in the
          entries below, because updates may be
          required too frequently."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
      INDEX { nhdpIfIndex,
              nhdpDiscIfIndex }
   ::= { nhdpIibLinkSetTable 1 }

   NhdpIibLinkSetEntry ::=
      SEQUENCE {
         nhdpIibLinkSetLHeardTime
            TimeStamp,
         nhdpIibLinkSetLSymTime
            TimeStamp,
         nhdpIibLinkSetLPending
            TruthValue,
         nhdpIibLinkSetLLost
            TruthValue,
         nhdpIibLinkSetLTime
            TimeStamp
      }

   nhdpIibLinkSetLHeardTime  OBJECT-TYPE
      SYNTAX      TimeStamp
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "nhdpIibLinkSetLHeardTime corresponds
          to L_HEARD_time of NHDP and represents the
          time up to which the MANET interface of the
          1-hop neighbor would be considered heard if
          not considering link quality."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
```

```
            Discovery Protocol (NHDP), Clausen, T., Dearlove,
            C., and J. Dean, April 2011"
    ::= { nhdpIibLinkSetEntry 1 }

    nhdpIibLinkSetLSymTime  OBJECT-TYPE
       SYNTAX      TimeStamp
       MAX-ACCESS  read-only
       STATUS      current
       DESCRIPTION
          "nhdpIibLinkSetLSymTime corresponds
           to L_SYM_time of NHDP and represents the time
           up to which the link to the 1-hop neighbor
           would be considered symmetric if not considering
           link quality."
       REFERENCE
          "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
           Discovery Protocol (NHDP), Clausen, T., Dearlove,
           C., and J. Dean, April 2011"
    ::= { nhdpIibLinkSetEntry 2 }

    nhdpIibLinkSetLPending  OBJECT-TYPE
       SYNTAX      TruthValue
       MAX-ACCESS  read-only
       STATUS      current
       DESCRIPTION
          "nhdpIibLinkSetLPending corresponds
           to L_pending of NHDP and is a boolean flag,
           describing if a link is considered pending
           (i.e., a candidate, but not yet established,
           link)."
       REFERENCE
          "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
           Discovery Protocol (NHDP), Clausen, T., Dearlove,
           C., and J. Dean, April 2011"
    ::= { nhdpIibLinkSetEntry 3 }

    nhdpIibLinkSetLLost  OBJECT-TYPE
       SYNTAX      TruthValue
       MAX-ACCESS  read-only
       STATUS      current
       DESCRIPTION
          "nhdpIibLinkSetLLost corresponds
           to L_lost of NHDP and is a boolean flag,
           describing if a link is considered lost due
           to low link quality."
       REFERENCE
          "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
           Discovery Protocol (NHDP), Clausen, T., Dearlove,
```

```
          C., and J. Dean, April 2011"
   ::= { nhdpIibLinkSetEntry 4 }

   nhdpIibLinkSetLTime  OBJECT-TYPE
      SYNTAX      TimeStamp
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "nhdpIibLinkSetLTime specifies the value
          of sysUptime when this entry should expire and be
          removed from the nhdpIibLinkSetTable."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
   ::= { nhdpIibLinkSetEntry 5 }

   --
   -- 2-Hop Set
   --
   nhdpIib2HopSetTable  OBJECT-TYPE
      SYNTAX      SEQUENCE OF NhdpIib2HopSetEntry
      MAX-ACCESS  not-accessible
      STATUS      current
      DESCRIPTION
         "A 2-Hop Set of an interface records network
          addresses of symmetric 2-hop neighbors and
          the symmetric links to symmetric 1-hop neighbors
          through which these symmetric 2-hop neighbors
          can be reached.  It consists of 2-Hop Tuples."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
   ::= { nhdpStateObjGrp 5 }

   nhdpIib2HopSetEntry  OBJECT-TYPE
      SYNTAX      NhdpIib2HopSetEntry
      MAX-ACCESS  not-accessible
      STATUS      current
      DESCRIPTION
         "nhdpIib2HopSetTable consists of 2-Hop Tuples,
          each representing a single network address of
          a symmetric 2-hop neighbor and a single MANET
          interface of a symmetric 1-hop neighbor.

          (N2_neighbor_iface_addr_list,
           N2_2hop_addr, N2_time).
```

```
          The entries include the 2-hop neighbor addresses,
          which act as the table index, and associated
          1-hop symmetric link address set, designated
          through nhdpDiscIfIndex, and an expiration time.
          The nhdpIfIndex in the INDEX is the
          interface index of the local interface
          through which these 2-hop addresses are
          accessible.  The nhdpDiscIfIndex in the
          INDEX represents the 1-hop neighbor interface
          through which these 2-hop addresses are
          reachable."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
      INDEX { nhdpIfIndex,
              nhdpDiscIfIndex,
              nhdpIib2HopSetIpAddressType,
              nhdpIib2HopSetIpAddress
      }
   ::= { nhdpIib2HopSetTable 1 }

   NhdpIib2HopSetEntry ::=
      SEQUENCE {
         nhdpIib2HopSetIpAddressType
            InetAddressType,
         nhdpIib2HopSetIpAddress
            InetAddress,
         nhdpIib2HopSetIpAddrPrefixLen
            InetAddressPrefixLength,
         nhdpIib2HopSet1HopIfIndex
            NeighborIfIndex,
         nhdpIib2HopSetN2Time
            TimeStamp
      }

   nhdpIib2HopSetIpAddressType  OBJECT-TYPE
      SYNTAX      InetAddressType
      MAX-ACCESS  not-accessible
      STATUS      current
      DESCRIPTION
         "The type of the nhdpIib2HopSetIpAddress
          in the InetAddress MIB module (RFC 4001).

          Only the values 'ipv4(1)' and
          'ipv6(2)' are supported."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
```

```
            Discovery Protocol (NHDP), Clausen, T., Dearlove,
            C., and J. Dean, April 2011"
    ::= { nhdpIib2HopSetEntry 1 }

    nhdpIib2HopSetIpAddress  OBJECT-TYPE
       SYNTAX      InetAddress (SIZE(4|16))
       MAX-ACCESS  not-accessible
       STATUS      current
       DESCRIPTION
          "nhdpIib2HopSetIpAddr corresponds
           to N2_2hop_addr of NHDP and is a network
           address of a symmetric 2-hop neighbor that
           has a symmetric link (using any MANET
           interface) to the indicated symmetric
           1-hop neighbor."
       REFERENCE
          "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
           Discovery Protocol (NHDP), Clausen, T., Dearlove,
           C., and J. Dean, April 2011"
    ::= { nhdpIib2HopSetEntry 2 }

    nhdpIib2HopSetIpAddrPrefixLen  OBJECT-TYPE
       SYNTAX      InetAddressPrefixLength
       MAX-ACCESS  read-only
       STATUS      current
       DESCRIPTION
          "Indicates the number of leading one bits that
           form the mask.  The mask is logically ANDed
           to the nhdpIib2HopSetIpAddress to determine
           the address prefix.  A row match is true
           if the address used as an index falls within
           the network address range defined by the
           address prefix."
       REFERENCE
          "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
           Discovery Protocol (NHDP), Clausen, T., Dearlove,
           C., and J. Dean, April 2011"
    ::= { nhdpIib2HopSetEntry 3 }

    nhdpIib2HopSet1HopIfIndex  OBJECT-TYPE
       SYNTAX      NeighborIfIndex
       MAX-ACCESS  read-only
       STATUS      current
       DESCRIPTION
          "nhdpIib2HopSet1HopIfIndex is
           nhdpDiscIfIndex of the 1-hop
           neighbor that communicated the ipAddress
           of the 2-hop neighbor in this row entry."
```

```
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
   ::= { nhdpIib2HopSetEntry 4 }

   nhdpIib2HopSetN2Time  OBJECT-TYPE
      SYNTAX      TimeStamp
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "nhdpIib2HopSetN2Time specifies the value
          of sysUptime when this entry should expire and be
          removed from the nhdpIib2HopSetTable."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
   ::= { nhdpIib2HopSetEntry 5 }

   --
   -- Neighbor Information Base (NIB)
   --
   -- Each router maintains a Neighbor Information Base
   -- that records information about addresses of
   -- current and recently symmetric 1-hop neighbors.

   --
   -- Neighbor Set
   --
   --     The Neighbor Set Table is small because
   --     most of the corresponding information is found
   --     in the nhdpDiscoveredIfTable above.
   --

   nhdpNibNeighborSetTable  OBJECT-TYPE
      SYNTAX       SEQUENCE OF NhdpNibNeighborSetEntry
      MAX-ACCESS   not-accessible
      STATUS       current
      DESCRIPTION
         "A router's Neighbor Set records all
          network addresses of each 1-hop
          neighbor."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
   ::= { nhdpStateObjGrp 6 }
```

```
   nhdpNibNeighborSetEntry  OBJECT-TYPE
      SYNTAX      NhdpNibNeighborSetEntry
      MAX-ACCESS  not-accessible
      STATUS      current
      DESCRIPTION
         "A router's Neighbor Set consists
          of Neighbor Tuples, each representing
          a single 1-hop neighbor:

          (N_neighbor_addr_list, N_symmetric)"
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
      INDEX { nhdpDiscRouterIndex }
   ::= { nhdpNibNeighborSetTable 1 }

   NhdpNibNeighborSetEntry ::=
      SEQUENCE {
         nhdpNibNeighborSetNSymmetric
            TruthValue
      }

   nhdpNibNeighborSetNSymmetric  OBJECT-TYPE
      SYNTAX      TruthValue
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "nhdpNibNeighborNSymmetric corresponds
          to N_symmetric of NHDP and is a boolean flag,
          describing if this is a symmetric 1-hop neighbor."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
   ::= { nhdpNibNeighborSetEntry 1 }

   --
   -- Lost Neighbor Set
   --
   nhdpNibLostNeighborSetTable  OBJECT-TYPE
      SYNTAX      SEQUENCE OF NhdpNibLostNeighborSetEntry
      MAX-ACCESS  not-accessible
      STATUS      current
      DESCRIPTION
         "A router's Lost Neighbor Set records network
          addresses of routers that were recently
          symmetric 1-hop neighbors but are now
```

```
            advertised as lost."
         REFERENCE
            "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
             Discovery Protocol (NHDP), Clausen, T., Dearlove,
             C., and J. Dean, April 2011"
      ::= { nhdpStateObjGrp 7 }

      nhdpNibLostNeighborSetEntry  OBJECT-TYPE
         SYNTAX      NhdpNibLostNeighborSetEntry
         MAX-ACCESS  not-accessible
         STATUS      current
         DESCRIPTION
            "A router's Lost Neighbor Set consists of
             Lost Neighbor Tuples, each representing a
             single such network address:

             (NL_neighbor_addr, NL_time)"
         REFERENCE
            "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
             Discovery Protocol (NHDP), Clausen, T., Dearlove,
             C., and J. Dean, April 2011"
         INDEX { nhdpDiscRouterIndex }
      ::= { nhdpNibLostNeighborSetTable 1 }

      NhdpNibLostNeighborSetEntry ::=
         SEQUENCE {
            nhdpNibLostNeighborSetNLTime
               TimeStamp
         }

      nhdpNibLostNeighborSetNLTime  OBJECT-TYPE
         SYNTAX      TimeStamp
         MAX-ACCESS  read-only
         STATUS      current
         DESCRIPTION
            "nhdpNibLostNeighborSetNLTime
             specifies the value of sysUptime when this entry
             should expire and be removed from the
             nhdpNibLostNeighborSetTable."
         REFERENCE
            "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
             Discovery Protocol (NHDP), Clausen, T., Dearlove,
             C., and J. Dean, April 2011"
      ::= { nhdpNibLostNeighborSetEntry 1 }

   --
   -- nhdpPerformanceObjGrp
   --
```

```
-- Contains objects that help to characterize the performance of
-- the NHDP process, typically counters.
--
nhdpPerformanceObjGrp  OBJECT IDENTIFIER ::= { nhdpObjects 3 }

  --
  -- Objects per local interface
  --

  nhdpInterfacePerfTable  OBJECT-TYPE
      SYNTAX      SEQUENCE OF NhdpInterfacePerfEntry
      MAX-ACCESS  not-accessible
      STATUS      current
      DESCRIPTION
         "This table summarizes performance objects that are
          measured per local NHDP interface."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
   ::= { nhdpPerformanceObjGrp 1 }

   nhdpInterfacePerfEntry  OBJECT-TYPE
      SYNTAX      NhdpInterfacePerfEntry
      MAX-ACCESS  not-accessible
      STATUS      current
      DESCRIPTION
         "A single entry contains performance counters for
          a local NHDP interface."
      INDEX { nhdpIfIndex }

   ::= { nhdpInterfacePerfTable 1 }

   NhdpInterfacePerfEntry ::=
      SEQUENCE {
         nhdpIfHelloMessageXmits
            Counter32,
         nhdpIfHelloMessageRecvd
            Counter32,
         nhdpIfHelloMessageXmitAccumulatedSize
            Counter64,
         nhdpIfHelloMessageRecvdAccumulatedSize
            Counter64,
         nhdpIfHelloMessageTriggeredXmits
            Counter32,
         nhdpIfHelloMessagePeriodicXmits
            Counter32,
         nhdpIfHelloMessageXmitAccumulatedSymmetricNeighborCount
```

```
            Counter32,
         nhdpIfHelloMessageXmitAccumulatedHeardNeighborCount
            Counter32,
         nhdpIfHelloMessageXmitAccumulatedLostNeighborCount
            Counter32
      }

   nhdpIfHelloMessageXmits  OBJECT-TYPE
      SYNTAX      Counter32
      UNITS       "messages"
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "A counter is incremented each time a HELLO
          message has been transmitted on that interface."
   ::= { nhdpInterfacePerfEntry 1 }

   nhdpIfHelloMessageRecvd  OBJECT-TYPE
      SYNTAX      Counter32
      UNITS       "messages"
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "A counter is incremented each time a
          HELLO message has been received on that interface."
   ::= { nhdpInterfacePerfEntry 2 }

   nhdpIfHelloMessageXmitAccumulatedSize  OBJECT-TYPE
      SYNTAX      Counter64
      UNITS       "octets"
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "A counter is incremented by the number of octets in
          a HELLO message each time a
          HELLO message has been sent."
   ::= { nhdpInterfacePerfEntry 3 }

   nhdpIfHelloMessageRecvdAccumulatedSize  OBJECT-TYPE
      SYNTAX      Counter64
      UNITS       "octets"
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "A counter is incremented by the number of octets in
          a HELLO message each time a
          HELLO message has been received."
   ::= { nhdpInterfacePerfEntry 4 }
```

```
   nhdpIfHelloMessageTriggeredXmits  OBJECT-TYPE
      SYNTAX      Counter32
      UNITS       "messages"
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "A counter is incremented each time a triggered
          HELLO message has been sent."
   ::= { nhdpInterfacePerfEntry 5 }

   nhdpIfHelloMessagePeriodicXmits  OBJECT-TYPE
      SYNTAX      Counter32
      UNITS       "messages"
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "A counter is incremented each time a periodic
          HELLO message has been sent."
   ::= { nhdpInterfacePerfEntry 6 }

   nhdpIfHelloMessageXmitAccumulatedSymmetricNeighborCount  OBJECT-TYPE
      SYNTAX      Counter32
      UNITS       "neighbors"
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "A counter is incremented by the number of advertised
          symmetric neighbors in a HELLO each time a HELLO
          message has been sent."
   ::= { nhdpInterfacePerfEntry 7 }

   nhdpIfHelloMessageXmitAccumulatedHeardNeighborCount  OBJECT-TYPE
      SYNTAX      Counter32
      UNITS       "neighbors"
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "A counter is incremented by the number of advertised
          heard neighbors in a HELLO each time a HELLO
          message has been sent."
   ::= { nhdpInterfacePerfEntry 8 }

   nhdpIfHelloMessageXmitAccumulatedLostNeighborCount  OBJECT-TYPE
      SYNTAX      Counter32
      UNITS       "neighbors"
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
```

```
         "A counter is incremented by the number of advertised
          lost neighbors in a HELLO each time a HELLO
          message has been sent."
   ::= { nhdpInterfacePerfEntry 9 }

   --
   -- Objects per discovered neighbor interface
   --
   nhdpDiscIfSetPerfTable OBJECT-TYPE
      SYNTAX       SEQUENCE OF NhdpDiscIfSetPerfEntry
      MAX-ACCESS   not-accessible
      STATUS       current
      DESCRIPTION
         "A router's set of performance properties for
          each discovered interface of a neighbor."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
   ::= { nhdpPerformanceObjGrp 2 }

   nhdpDiscIfSetPerfEntry  OBJECT-TYPE
      SYNTAX      NhdpDiscIfSetPerfEntry
      MAX-ACCESS  not-accessible
      STATUS      current
      DESCRIPTION
         "There is an entry for each discovered
          interface of a neighbor."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
      INDEX { nhdpDiscIfIndex }
   ::= { nhdpDiscIfSetPerfTable 1 }

   NhdpDiscIfSetPerfEntry ::=
      SEQUENCE {
         nhdpDiscIfRecvdPackets
            Counter32,
         nhdpDiscIfExpectedPackets
            Counter32
      }

   nhdpDiscIfRecvdPackets  OBJECT-TYPE
      SYNTAX      Counter32
      UNITS       "packets"
      MAX-ACCESS  read-only
      STATUS      current
```

```
      DESCRIPTION
         "This counter increments each
          time this router receives a packet from that interface
          of the neighbor."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
         C., and J. Dean, April 2011"
   ::= { nhdpDiscIfSetPerfEntry 1 }

   nhdpDiscIfExpectedPackets  OBJECT-TYPE
      SYNTAX      Counter32
      UNITS       "packets"
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "This counter increments by the number
          of missed packets from this neighbor based
          on the packet sequence number each time this
          router receives a packet from that interface
          of the neighbor."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
   ::= { nhdpDiscIfSetPerfEntry 2 }

   --
   -- Objects concerning the Neighbor Set
   --
   nhdpNibNeighborSetChanges  OBJECT-TYPE
      SYNTAX      Counter32
      UNITS       "changes"
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "This counter increments each time the Neighbor Set changes.
          A change occurs whenever a new Neighbor Tuple has been
          added, a Neighbor Tuple has been removed, or any entry of
          a Neighbor Tuple has been modified."
   ::= { nhdpPerformanceObjGrp 3 }

   --
   -- Objects per discovered neighbor
   --

   nhdpDiscNeighborSetPerfTable OBJECT-TYPE
      SYNTAX       SEQUENCE OF NhdpDiscNeighborSetPerfEntry
```

```
      MAX-ACCESS   not-accessible
      STATUS       current
      DESCRIPTION
         "A router's set of discovered neighbors and
          their properties."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
   ::= { nhdpPerformanceObjGrp 4 }

   nhdpDiscNeighborSetPerfEntry  OBJECT-TYPE
      SYNTAX      NhdpDiscNeighborSetPerfEntry
      MAX-ACCESS  not-accessible
      STATUS      current
      DESCRIPTION
         "The entries include the nhdpDiscRouterIndex of
          the discovered router as well as performance
          objects related to changes of the Neighbor
          Set."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
      INDEX { nhdpDiscRouterIndex }
   ::= { nhdpDiscNeighborSetPerfTable 1 }

   NhdpDiscNeighborSetPerfEntry ::=
      SEQUENCE {
         nhdpDiscNeighborNibNeighborSetChanges
            Counter32,
         nhdpDiscNeighborNibNeighborSetUpTime
            TimeStamp,
         nhdpDiscNeighborNibNeighborSetReachableLinkChanges
            Counter32
      }

   nhdpDiscNeighborNibNeighborSetChanges  OBJECT-TYPE
      SYNTAX      Counter32
      UNITS       "changes"
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "This object returns the number of changes
          to the given Neighbor Tuple."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
```

```
          C., and J. Dean, April 2011"
   ::= { nhdpDiscNeighborSetPerfEntry 1 }

   nhdpDiscNeighborNibNeighborSetUpTime  OBJECT-TYPE
      SYNTAX      TimeStamp
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "This object returns the sysUpTime when
          the neighbor becomes 'nbrup'.  A neighbor is
          said to become 'nbrup' if a new nhdpNibNeighborSetEntry
          is created for a particular nhdpNibNeighborSetRouterIndex.
          It becomes 'nbrdown' if the entry for that neighbor
          has been deleted."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
   ::= { nhdpDiscNeighborSetPerfEntry 2 }

   nhdpDiscNeighborNibNeighborSetReachableLinkChanges  OBJECT-TYPE
      SYNTAX      Counter32
      UNITS       "changes"
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "This object counts each time the neighbor changes
          the interface(s) over which it is reachable.
          A change in the set of Link Tuples corresponding
          to the appropriate Neighbor Tuple is registered,
          i.e., a corresponding Link Tuple is added or removed
          from the set of all corresponding Link Tuples."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
   ::= { nhdpDiscNeighborSetPerfEntry 3 }

   --
   -- Objects per discovered 2-hop neighbor
   --
   nhdpIib2HopSetPerfTable  OBJECT-TYPE
      SYNTAX      SEQUENCE OF NhdpIib2HopSetPerfEntry
      MAX-ACCESS  not-accessible
      STATUS      current
      DESCRIPTION
         "This table contains performance objects per
          discovered 2-hop neighbor."
```

```
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
   ::= { nhdpPerformanceObjGrp 5 }

   nhdpIib2HopSetPerfEntry  OBJECT-TYPE
      SYNTAX      NhdpIib2HopSetPerfEntry
      MAX-ACCESS  not-accessible
      STATUS      current
      DESCRIPTION
         "The entries contain performance objects per
          discovered 2-hop neighbor."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
      INDEX { nhdpDiscRouterIndex }
   ::= { nhdpIib2HopSetPerfTable 1 }

   NhdpIib2HopSetPerfEntry ::=
      SEQUENCE {
         nhdpIib2HopSetPerfChanges
            Counter32,
         nhdpIib2HopSetPerfUpTime
            TimeStamp
      }

   nhdpIib2HopSetPerfChanges  OBJECT-TYPE
      SYNTAX      Counter32
      UNITS       "changes"
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "This object counts the changes of the union of all
          N2_neighbor_iface_addr_list of 2-Hop Tuples with an
          N2_2hop_addr equal to one of the given 2-hop
          neighbor's addresses."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
   ::= { nhdpIib2HopSetPerfEntry 1 }

   nhdpIib2HopSetPerfUpTime  OBJECT-TYPE
      SYNTAX      TimeStamp
      MAX-ACCESS  read-only
      STATUS      current
```

```
      DESCRIPTION
         "This object returns the sysUpTime
          when the 2-Hop Tuple
          corresponding to the given 2-hop neighbor IP address
          was registered in the nhdpIib2HopSetTable."
      REFERENCE
         "RFC 6130 - Mobile Ad Hoc Network (MANET) Neighborhood
          Discovery Protocol (NHDP), Clausen, T., Dearlove,
          C., and J. Dean, April 2011"
   ::= { nhdpIib2HopSetPerfEntry 2 }

--
-- nhdpNotifications
--

nhdpNotificationsObjects OBJECT IDENTIFIER ::= { nhdpNotifications 0 }
nhdpNotificationsControl OBJECT IDENTIFIER ::= { nhdpNotifications 1 }
nhdpNotificationsStates  OBJECT IDENTIFIER ::= { nhdpNotifications 2 }

   -- nhdpNotificationsObjects

   nhdpNbrStateChange  NOTIFICATION-TYPE
      OBJECTS { nhdpIfName,  -- The originator of
                             --     the notification.
                nhdpNbrState  -- The new state
      }
      STATUS       current
      DESCRIPTION
         "nhdpNbrStateChange is a notification sent when
          more than nhdpNbrStateChangeThreshold neighbors change
          their status (i.e., 'down(0)', 'asymmetric(1)', or
          'symmetric(2)') within a time window of
          nhdpNbrStateChangeWindow."
   ::= { nhdpNotificationsObjects 1 }

   nhdp2HopNbrStateChange  NOTIFICATION-TYPE
      OBJECTS { nhdpIfName,      -- The originator
                                 -- of the notification
                nhdp2HopNbrState  -- The new state
      }
      STATUS      current
      DESCRIPTION
         "nhdp2HopNbrStateChange is a notification sent
          when more than nhdp2HopNbrStateChangeThreshold 2-hop
          neighbors change their status (i.e., 'down(0)' or
          'up(1)') within a time window of
          nhdp2HopNbrStateChangeWindow."
   ::= { nhdpNotificationsObjects 2 }
```

```
   nhdpIfStateChange  NOTIFICATION-TYPE
      OBJECTS { nhdpIfName,  -- The local interface
                nhdpIfStatus  -- The new status
      }
      STATUS       current
      DESCRIPTION
         "nhdpIfStateChange is a notification sent when
          nhdpIfStatus has changed on this interface."
   ::= { nhdpNotificationsObjects 3 }

   -- nhdpNotificationsControl

   nhdpNbrStateChangeThreshold  OBJECT-TYPE
      SYNTAX      Integer32 (0..255)
      UNITS       "changes"
      MAX-ACCESS  read-write
      STATUS      current
      DESCRIPTION
         "A threshold value for the
          nhdpNbrStateChange object.  If the
          number of occurrences exceeds this threshold
          within the previous nhdpNbrStateChangeWindow,
          then the nhdpNbrStateChange notification
          is to be sent.

          It is recommended that the value of this
          threshold be set to at least 10 and higher
          in dense topologies with frequent expected
          topology changes."
      DEFVAL { 10 }
   ::= { nhdpNotificationsControl 1 }

   nhdpNbrStateChangeWindow  OBJECT-TYPE
      SYNTAX      TimeTicks
      MAX-ACCESS  read-write
      STATUS      current
      DESCRIPTION
         "A time window for the
          nhdpNbrStateChange object.  If the
          number of occurrences exceeds the
          nhdpNbrStateChangeThreshold
          within the previous nhdpNbrStateChangeWindow,
          then the nhdpNbrStateChange notification
          is to be sent.

          It is recommended that the value for this
          window be set to at least 5 times the
          nhdpHelloInterval.
```

```
            This object represents the time in hundredths
            of a second."
      DEFVAL { 1000 }
   ::= { nhdpNotificationsControl 2 }

   nhdp2HopNbrStateChangeThreshold  OBJECT-TYPE
      SYNTAX      Integer32 (0..255)
      UNITS       "changes"
      MAX-ACCESS  read-write
      STATUS      current
      DESCRIPTION
         "A threshold value for the
          nhdp2HopNbrStateChange object.  If the
          number of occurrences exceeds this threshold
          within the previous nhdp2HopNbrStateChangeWindow,
          then the nhdp2HopNbrStateChange notification
          is to be sent.

          It is recommended that the value of this
          threshold be set to at least 10 and higher
          when topologies are expected to be highly dynamic."
      DEFVAL { 10 }
   ::= { nhdpNotificationsControl 3 }

   nhdp2HopNbrStateChangeWindow  OBJECT-TYPE
      SYNTAX      TimeTicks
      MAX-ACCESS  read-write
      STATUS      current
      DESCRIPTION
         "A time window for the
          nhdp2HopNbrStateChange object.  If the
          number of occurrences exceeds the
          nhdp2HopNbrStateChangeThreshold
          within the previous nhdp2HopNbrStateChangeWindow,
          then the nhdp2HopNbrStateChange notification
          is to be sent.

          It is recommended that the value for this
          window be set to at least 5 times
          nhdpHelloInterval.

          This object represents the time in hundredths
          of a second."
      DEFVAL { 1000 }
   ::= { nhdpNotificationsControl 4 }

    -- nhdpNotificationStates
```

```
   nhdpNbrState OBJECT-TYPE
      SYNTAX      INTEGER {
                     down(0),
                     asymmetric(1),
                     symmetric(2)
                  }
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "NHDP neighbor states.  In NHDP, it is not
          necessary to remove Protocol Tuples from Protocol Sets
          at the exact time indicated, only to behave as if the
          Protocol Tuples were removed at that time.  This case is
          indicated here as 'down(0)', all other cases being
          indicated as 'asymmetric(1)' or 'symmetric(2)'.  If 'down(0)',
          the direct neighbor is also added to the
          nhdpNibLostNeighborSetTable."
   ::= { nhdpNotificationsStates 1 }

   nhdp2HopNbrState  OBJECT-TYPE
      SYNTAX      INTEGER {
                     down(0),
                     up(1)
                  }
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "NHDP 2-hop neighbor states.  In NHDP, it is not
          necessary to remove Protocol Tuples from Protocol Sets
          at the exact time indicated, only to behave as if the
          Protocol Tuples were removed at that time.  This case is
          indicated here as 'down(0)'; otherwise, it is 'up(1)'."
   ::= { nhdpNotificationsStates 2 }

--
-- nhdpConformance information
--

nhdpCompliances       OBJECT IDENTIFIER ::= { nhdpConformance 1 }
nhdpMIBGroups         OBJECT IDENTIFIER ::= { nhdpConformance 2 }

   -- Compliance Statements
   nhdpBasicCompliance  MODULE-COMPLIANCE
      STATUS      current
      DESCRIPTION
         "The basic implementation requirements for
          managed network entities that implement
          NHDP."
```

```
      MODULE -- this module
      MANDATORY-GROUPS { nhdpConfigurationGroup }
   ::= { nhdpCompliances 1 }

   nhdpFullCompliance  MODULE-COMPLIANCE
      STATUS      current
      DESCRIPTION
         "The full implementation requirements for
          managed network entities that implement
          NHDP."
      MODULE -- this module
      MANDATORY-GROUPS { nhdpConfigurationGroup,
                         nhdpStateGroup,
                         nhdpNotificationObjectGroup,
                         nhdpNotificationGroup,
                         nhdpPerformanceGroup
      }
   ::= { nhdpCompliances 2 }

--
-- Units of Conformance
--

   nhdpConfigurationGroup  OBJECT-GROUP
      OBJECTS {
         nhdpIfName,
         nhdpIfStatus,
         nhdpHelloInterval,
         nhdpHelloMinInterval,
         nhdpRefreshInterval,
         nhdpLHoldTime,
         nhdpHHoldTime,
         nhdpHystAcceptQuality,
         nhdpHystRejectQuality,
         nhdpInitialQuality,
         nhdpInitialPending,
         nhdpHpMaxJitter,
         nhdpHtMaxJitter,
         nhdpNHoldTime,
         nhdpIHoldTime,
         nhdpIfRowStatus,
         nhdpLibLocalIfSetIfIndex,
         nhdpLibLocalIfSetIpAddrType,
         nhdpLibLocalIfSetIpAddr,
         nhdpLibLocalIfSetIpAddrPrefixLen,
         nhdpLibLocalIfSetRowStatus,
         nhdpLibRemovedIfAddrSetIpAddrType,
         nhdpLibRemovedIfAddrSetIpAddr,
```

```
         nhdpLibRemovedIfAddrSetIpAddrPrefixLen,
         nhdpLibRemovedIfAddrSetIfIndex,
         nhdpLibRemovedIfAddrSetIRTime
      }
      STATUS      current
      DESCRIPTION
         "Set of NHDP configuration objects implemented
          in this module."
   ::= { nhdpMIBGroups 2 }

   nhdpStateGroup  OBJECT-GROUP
      OBJECTS {
         nhdpUpTime,
         nhdpIfStateUpTime,
         nhdpDiscRouterIndex,
         nhdpDiscIfIndex,
         nhdpDiscIfSetIpAddrType,
         nhdpDiscIfSetIpAddr,
         nhdpDiscIfSetIpAddrPrefixLen,
         nhdpIibLinkSetLHeardTime,
         nhdpIibLinkSetLSymTime,
         nhdpIibLinkSetLPending,
         nhdpIibLinkSetLLost,
         nhdpIibLinkSetLTime,
         nhdpIib2HopSetIpAddrPrefixLen,
         nhdpIib2HopSet1HopIfIndex,
         nhdpIib2HopSetN2Time,
         nhdpNibNeighborSetNSymmetric,
         nhdpNibLostNeighborSetNLTime
      }
      STATUS      current
      DESCRIPTION
         "Set of NHDP state objects implemented
          in this module."
   ::= { nhdpMIBGroups 3 }

   nhdpPerformanceGroup  OBJECT-GROUP
      OBJECTS {
         nhdpIfHelloMessageXmits,
         nhdpIfHelloMessageRecvd,
         nhdpIfHelloMessageXmitAccumulatedSize,
         nhdpIfHelloMessageRecvdAccumulatedSize,
         nhdpIfHelloMessageTriggeredXmits,
         nhdpIfHelloMessagePeriodicXmits,
         nhdpIfHelloMessageXmitAccumulatedSymmetricNeighborCount,
         nhdpIfHelloMessageXmitAccumulatedHeardNeighborCount,
         nhdpIfHelloMessageXmitAccumulatedLostNeighborCount,
         nhdpDiscIfRecvdPackets,
```

```
         nhdpDiscIfExpectedPackets,
         nhdpNibNeighborSetChanges,
         nhdpDiscNeighborNibNeighborSetChanges,
         nhdpDiscNeighborNibNeighborSetUpTime,
         nhdpDiscNeighborNibNeighborSetReachableLinkChanges,
         nhdpIib2HopSetPerfChanges,
         nhdpIib2HopSetPerfUpTime
      }
      STATUS      current
      DESCRIPTION
         "Set of NHDP performance objects implemented
          in this module."
   ::= { nhdpMIBGroups 4 }

   nhdpNotificationObjectGroup  OBJECT-GROUP
      OBJECTS {
         nhdpNbrStateChangeThreshold,
         nhdpNbrStateChangeWindow,
         nhdp2HopNbrStateChangeThreshold,
         nhdp2HopNbrStateChangeWindow,
         nhdpNbrState,
         nhdp2HopNbrState
      }
      STATUS      current
      DESCRIPTION
         "Set of NHDP notification objects implemented
          in this module."
   ::= { nhdpMIBGroups 5 }

   nhdpNotificationGroup  NOTIFICATION-GROUP
      NOTIFICATIONS {
         nhdpNbrStateChange,
         nhdp2HopNbrStateChange,
         nhdpIfStateChange
      }
      STATUS      current
      DESCRIPTION
         "Set of NHDP notifications implemented
          in this module."
   ::= { nhdpMIBGroups 6 }


END
```

8. Security Considerations

This MIB module defines objects for the configuration, monitoring, and notification of the Neighborhood Discovery Protocol [RFC6130]. NHDP allows routers to acquire topological information up to two hops away by virtue of exchanging HELLO messages. The information acquired by NHDP may be used by routing protocols. The neighborhood information, exchanged between routers using NHDP, serves these routing protocols as a baseline for calculating paths to all destinations in the MANET, relay set selection for network-wide transmissions, etc.

There are a number of management objects defined in this MIB module with a MAX-ACCESS clause of read-write and/or read-create. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations. These are the tables and objects and their sensitivity/vulnerability:

- nhdpIfStatus - This writable object turns on or off the NHDP process for the specified interface. If disabled, higher-level protocol functions, e.g., routing, would fail, causing network-wide disruptions.

- nhdpHelloInterval, nhdpHelloMinInterval, and nhdpRefreshInterval - These writable objects control the rate at which HELLO messages are sent on an interface. If set at too high a rate, this could represent a form of denial-of-service (DoS) attack by overloading interface resources.

- nhdpHystAcceptQuality, nhdpHystRejectQuality, nhdpInitialQuality, and nhdpInitialPending - These writable objects affect the perceived quality of the NHDP links and hence the overall stability of the network. If improperly set, these settings could result in network-wide disruptions.

- nhdpInterfaceTable - This table contains writable objects that affect the overall performance and stability of the NHDP process. Failure of the NHDP process would result in network-wide failure. Particularly sensitive objects from this table are discussed in the previous list items. This is the only table in the NHDP-MIB module with writable objects.

Some of the readable objects in this MIB module (i.e., objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments. It is thus important to control even GET and/or NOTIFY access to these objects and possibly

to even encrypt the values of these objects when sending them over the network via SNMP. These are the tables and objects and their sensitivity/vulnerability:

- nhdpDiscIfSetTable - The object contains information on discovered neighbors, specifically their IP address in the nhdpDiscIfSetIpAddr object. This information provides an adversary broad information on the members of the MANET, located within this single table. This information can be used to expedite attacks on the other members of the MANET without having to go through a laborious discovery process on their own. This object is the index into the table and has a MAX-ACCESS of 'not-accessible'. However, this information can be exposed using SNMP operations.

MANET technology is often deployed to support communications of emergency services or military tactical applications. In these applications, it is imperative to maintain the proper operation of the communications network and to protect sensitive information related to its operation. Therefore, it is RECOMMENDED to provide support for the Transport Security Model (TSM) [RFC5591] in combination with TLS/DTLS [RFC6353].

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPsec), there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

Implementations MUST provide the security features described by the SNMPv3 framework (see [RFC3410]), including full support for authentication and privacy via the User-based Security Model (USM) [RFC3414] with the AES cipher algorithm [RFC3826]. Implementations MAY also provide support for the Transport Security Model (TSM) [RFC5591] in combination with a secure transport such as SSH [RFC5592] or TLS/DTLS [RFC6353].

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

9. Applicability Statement

This document describes objects for configuring parameters of the Neighborhood Discovery Protocol [RFC6130] process on a router. This MIB module, denoted NHDP-MIB, also reports state, performance information, and notifications. This section provides some examples of how this MIB module can be used in MANET network deployments. A fuller discussion of MANET network management use cases and challenges will be provided elsewhere.

NHDP is designed to allow routers to automatically discover and track routers one hop remote (denoted "neighbors") and routers two hops remote (denoted "two-hop neighbors"). This information is used by other MANET protocols in operation on the router to perform routing, multicast forwarding, and other functions with ad hoc and mobile networks. In the following, three example scenarios are listed where this MIB module is useful:

- For a Parking Lot Initial Configuration Situation - It is common for the vehicles comprising the MANET being forward deployed at a remote location, e.g., the site of a natural disaster, to be off-loaded in a parking lot where an initial configuration of the networking devices is performed. The configuration is loaded into the devices from a fixed location Network Operation Center (NOC) at the parking lot, and the vehicles are stationary at the parking lot while the configuration changes are made. Standards-based methods for configuration management from the co-located NOC are necessary for this deployment option.

- For Mobile Vehicles with Low-Bandwidth Satellite Link to a Fixed NOC - Here, the vehicles carrying the MANET routers carry multiple wireless interfaces, one of which is a relatively low-bandwidth, on-the-move satellite connection that interconnects a fix NOC to the nodes of the MANET. Standards-based methods for monitoring and fault management from the fixed NOC are necessary for this deployment option.

- For Fixed NOC and Mobile Local Manager in Larger Vehicles - for larger vehicles, a hierarchical network management arrangement is useful. Centralized network management is performed from a fixed NOC while local management is performed locally from within the vehicles. Standards-based methods for configuration, monitoring, and fault management are necessary for this deployment option.

10. IANA Considerations

The MIB module in this document uses the following IANA-assigned OBJECT IDENTIFIER value recorded in the SMI Numbers registry:

Descriptor	OBJECT IDENTIFIER value
NHDP-MIB	{ mib-2 213 }

11. Acknowledgements

The authors wish to thank Benoit Claise, Thomas Clausen, Justin Dean, Adrian Farrel, Joel Halpern, Al Morton, and Thomas Nadeau for their detailed reviews and insightful comments regarding this document.

This MIB document uses the template authored by D. Harrington, which is based on contributions from the MIB Doctors, especially Juergen Schoenwaelder, Dave Perkins, C.M. Heard, and Randy Presuhn.

12. References

12.1. Normative References

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.

[RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)", STD 58, RFC 2578, April 1999.

[RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2", STD 58, RFC 2579, April 1999.

[RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIv2", STD 58, RFC 2580, April 1999.

[RFC2863] McCloghrie, K. and F. Kastenholz, "The Interfaces Group MIB", RFC 2863, June 2000.

[RFC3418] Presuhn, R., "Management Information Base (MIB) for the Simple Network Management Protocol (SNMP)", STD 62, RFC 3418, December 2002.

[RFC4001] Daniele, M., Haberman, B., Routhier, S., and J. Schoenwaelder, "Textual Conventions for Internet Network Addresses", RFC 4001, February 2005.

[RFC6130] Clausen, T., Dearlove, C., and J. Dean, "Mobile Ad Hoc Network (MANET) Neighborhood Discovery Protocol (NHDP)", RFC 6130, April 2011.

[RFC6340] Presuhn, R., "Textual Conventions for the Representation of Floating-Point Numbers", RFC 6340, August 2011.

12.2. Informative References

[REPORT-MIB] Cole, R., Macker, J., and A. Bierman, "Definition of Managed Objects for Performance Reporting", Work in Progress, January 2012.

[RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", RFC 3410, December 2002.

[RFC3414] Blumenthal, U. and B. Wijnen, "User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)", STD 62, RFC 3414, December 2002.

[RFC3826] Blumenthal, U., Maino, F., and K. McCloghrie, "The Advanced Encryption Standard (AES) Cipher Algorithm in the SNMP User-based Security Model", RFC 3826, June 2004.

[RFC4750] Joyal, D., Galecki, P., Giacalone, S., Coltun, R., and F. Baker, "OSPF Version 2 Management Information Base", RFC 4750, December 2006.

[RFC5148] Clausen, T., Dearlove, C., and B. Adamson, "Jitter Considerations in Mobile Ad Hoc Networks (MANETs)", RFC 5148, February 2008.

[RFC5591] Harrington, D. and W. Hardaker, "Transport Security Model for the Simple Network Management Protocol (SNMP)", RFC 5591, June 2009.

[RFC5592] Harrington, D., Salowey, J., and W. Hardaker, "Secure Shell Transport Model for the Simple Network Management Protocol (SNMP)", RFC 5592, June 2009.

[RFC6353] Hardaker, W., "Transport Layer Security (TLS) Transport Model for the Simple Network Management Protocol (SNMP)", RFC 6353, July 2011.

Authors' Addresses

Ulrich Herberg
LIX, Ecole Polytechnique
91128 Palaiseau Cedex
France

EMail: ulrich@herberg.name
URI: http://www.herberg.name/

Robert G. Cole
US Army CERDEC
Space and Terrestrial Communications
6010 Frankford Road, Bldg 6010, Room 453H
Aberdeen Proving Ground, Maryland 21005
United States

Phone: +1 443 395-8744
EMail: robert.g.cole@us.army.mil
URI: http://www.cs.jhu.edu/~rgcole/

Ian D Chakeres
DRS CenGen
9250 Bendix Road North
Columbia, Maryland 21045
United States

EMail: ian.chakeres@gmail.com
URI: http://www.ianchak.com/