IPv4 Multicast Routing MIB

Status of this Memo

This document specifies an Internet standards track protocol for the
Internet community, and requests discussion and suggestions for
improvements. Please refer to the current edition of the "Internet
Official Protocol Standards" (STD 1) for the standardization state
and status of this protocol. Distribution of this memo is unlimited.

Copyright Notice

Abstract

This memo defines a portion of the Management Information Base (MIB)
for use with network management protocols in the Internet community.
In particular, it describes managed objects used for managing IP
Multicast Routing for IPv4, independent of the specific multicast
routing protocol in use.

Table of Contents

1. Introduction

   This MIB describes objects used for managing IP Multicast Routing
   [16], independent of the specific multicast routing protocol [17-21]
   in use. Managed objects specific to particular multicast routing
   protocols are specified elsewhere. Similarly, this MIB does not
   support management of multicast routing for other address families,
   including IPv6. Such management may be supported by other MIBs.

2. The SNMP Management Framework

   The SNMP Management Framework presently consists of five major
   components:

   o   An overall architecture, described in RFC 2571 [1].

   o   Mechanisms for describing and naming objects and events for the
         purpose of management. The first version of this Structure of
         Management Information (SMI) is called SMIv1 and described in
         STD 16, RFC 1155 [2], STD 16, RFC 1212 [3] and RFC 1215 [4].
         The second version, called SMIv2, is described in STD 58, RFC
         2578 [5], STD 58, RFC 2579 [6] and STD 58, RFC 2580 [7].

   o   Message protocols for transferring management information. The
         first version of the SNMP message protocol is called SNMPv1 and
         described in STD 15, RFC 1157 [8]. A second version of the SNMP
         message protocol, which is not an Internet standards track
         protocol, is called SNMPv2c and described in RFC 1901 [9] and
         RFC 1906 [10]. The third version of the message protocol is
         called SNMPv3 and described in RFC 1906 [10], RFC 2572 [11] and
         RFC 2574 [12].

   o   Protocol operations for accessing management information. The
         first set of protocol operations and associated PDU formats is
         described in STD 15, RFC 1157 [8]. A second set of protocol
         operations and associated PDU formats is described in RFC 1905
         [13].

   o   A set of fundamental applications described in RFC 2573 [14] and
         the view-based access control mechanism described in RFC 2575
         [15].

   Managed objects are accessed via a virtual information store, termed
   the Management Information Base or MIB. Objects in the MIB are
   defined using the mechanisms defined in the SMI.

This memo specifies a MIB module that is compliant to the SMIv2. A
MIB conforming to the SMIv1 can be produced through the appropriate
translations. The resulting translated MIB must be semantically
equivalent, except where objects or events are omitted because no
translation is possible (use of Counter64). Some machine readable
information in SMIv2 will be converted into textual descriptions in
SMIv1 during the translation process. However, this loss of machine
readable information is not considered to change the semantics of the
MIB.

3. Overview

   This MIB module contains one scalar and five tables. The tables are:

   (1)   the IP Multicast Route Table containing multicast routing
         information for IP datagrams sent by particular sources to the
         IP multicast groups known to a router.

   (2)   the IP Multicast Routing Next Hop Table containing information
         on the next-hops for the routing IP multicast datagrams. Each
         entry is one of a list of next-hops on outgoing interfaces for
         particular sources sending to a particular multicast group
         address.

   (3)   the IP Multicast Routing Interface Table containing multicast
         routing information specific to interfaces.

   (4)   the IP Multicast Scope Boundary Table containing the boundaries
         configured for multicast scopes [22].

   (5)   the IP Multicast Scope Name Table containing human-readable
         names of multicast scope.

4. Definitions

IPMROUTE-STD-MIB DEFINITIONS ::= BEGIN

IMPORTS
    MODULE-IDENTITY, OBJECT-TYPE, mib-2,
    Integer32, Counter32, Counter64, Gauge32,
    IpAddress, TimeTicks   FROM SNMPv2-SMI
    RowStatus, TEXTUAL-CONVENTION,
    TruthValue   FROM SNMPv2-TC
    MODULE-COMPLIANCE, OBJECT-GROUP   FROM SNMPv2-CONF
    SnmpAdminString   FROM SNMP-FRAMEWORK-MIB
    InterfaceIndexOrZero,
    InterfaceIndex   FROM IF-MIB
    IANAipRouteProtocol,
    IANAipMRouteProtocol   FROM IANA-RTPROTO-MIB;

ipMRouteStdMIB MODULE-IDENTITY
    LAST-UPDATED "200009220000Z" -- September 22, 2000
    ORGANIZATION "IETF IDMR Working Group"
    CONTACT-INFO
            " Dave Thaler
              Microsoft Corporation
              One Microsoft Way
              Redmond, WA 98052-6399
              US

              Phone: +1 425 703 8835
              EMail: dthaler@microsoft.com"
    DESCRIPTION
            "The MIB module for management of IP Multicast routing, but
            independent of the specific multicast routing protocol in
            use."
    REVISION   "200009220000Z" -- September 22, 2000
    DESCRIPTION
            "Initial version, published as RFC 2932."
    ::= { mib-2 83 }

-- Textual Conventions

LanguageTag ::= TEXTUAL-CONVENTION

    DISPLAY-HINT "100a"
    STATUS   current
    DESCRIPTION
            "An RFC 1766-style language tag, with all alphabetic
            characters converted to lowercase. This restriction is
            intended to make the lexical ordering imposed by SNMP useful

              when applied to language tags. Note that it is
              theoretically possible for a valid language tag to exceed
              the allowed length of this syntax, and thus be impossible to
              represent with this syntax. Sampling of language tags in
              current use on the Internet suggests that this limit does
              not pose a serious problem in practice."
    SYNTAX   OCTET STRING (SIZE (1..100))

-- Top-level structure of the MIB

ipMRouteMIBObjects OBJECT IDENTIFIER ::= { ipMRouteStdMIB 1 }

ipMRoute   OBJECT IDENTIFIER ::= { ipMRouteMIBObjects 1 }

-- the IP Multicast Routing MIB-Group
--
-- a collection of objects providing information about
-- IP Multicast Groups

ipMRouteEnable OBJECT-TYPE
    SYNTAX   INTEGER { enabled(1), disabled(2) }
    MAX-ACCESS read-write
    STATUS   current
    DESCRIPTION
            "The enabled status of IP Multicast routing on this router."
    ::= { ipMRoute 1 }

ipMRouteEntryCount OBJECT-TYPE
    SYNTAX   Gauge32
    MAX-ACCESS read-only
    STATUS   current
    DESCRIPTION
            "The number of rows in the ipMRouteTable. This can be used
            to monitor the multicast routing table size."
    ::= { ipMRoute 7 }

ipMRouteTable OBJECT-TYPE
    SYNTAX   SEQUENCE OF IpMRouteEntry
    MAX-ACCESS not-accessible
    STATUS   current
    DESCRIPTION
            "The (conceptual) table containing multicast routing
            information for IP datagrams sent by particular sources to
            the IP multicast groups known to this router."
    ::= { ipMRoute 2 }

```
ipMRouteEntry OBJECT-TYPE
    SYNTAX      IpMRouteEntry
    MAX-ACCESS not-accessible
    STATUS      current
    DESCRIPTION
            "An entry (conceptual row) containing the multicast routing
             information for IP datagrams from a particular source and
             addressed to a particular IP multicast group address.
             Discontinuities in counters in this entry can be detected by
             observing the value of ipMRouteUpTime."
    INDEX       { ipMRouteGroup,
                  ipMRouteSource,
                  ipMRouteSourceMask }
    ::= { ipMRouteTable 1 }

IpMRouteEntry ::= SEQUENCE {
    ipMRouteGroup               IpAddress,
    ipMRouteSource              IpAddress,
    ipMRouteSourceMask          IpAddress,
    ipMRouteUpstreamNeighbor    IpAddress,
    ipMRouteInIfIndex           InterfaceIndexOrZero,
    ipMRouteUpTime              TimeTicks,
    ipMRouteExpiryTime          TimeTicks,
    ipMRoutePkts                Counter32,
    ipMRouteDifferentInIfPackets Counter32,
    ipMRouteOctets              Counter32,
    ipMRouteProtocol            IANAipMRouteProtocol,
    ipMRouteRtProto             IANAipRouteProtocol,
    ipMRouteRtAddress           IpAddress,
    ipMRouteRtMask              IpAddress,
    ipMRouteRtType              INTEGER,
    ipMRouteHCOctets            Counter64
}

ipMRouteGroup OBJECT-TYPE
    SYNTAX      IpAddress
    MAX-ACCESS not-accessible
    STATUS      current
    DESCRIPTION
            "The IP multicast group address for which this entry
             contains multicast routing information."
    ::= { ipMRouteEntry 1 }

ipMRouteSource OBJECT-TYPE
    SYNTAX      IpAddress
    MAX-ACCESS not-accessible
    STATUS      current
    DESCRIPTION
```

            "The network address which when combined with the
            corresponding value of ipMRouteSourceMask identifies the
            sources for which this entry contains multicast routing
            information."
    ::= { ipMRouteEntry 2 }

ipMRouteSourceMask OBJECT-TYPE
    SYNTAX   IpAddress
    MAX-ACCESS not-accessible
    STATUS   current
    DESCRIPTION
            "The network mask which when combined with the corresponding
            value of ipMRouteSource identifies the sources for which
            this entry contains multicast routing information."
    ::= { ipMRouteEntry 3 }

ipMRouteUpstreamNeighbor OBJECT-TYPE
    SYNTAX   IpAddress
    MAX-ACCESS read-only
    STATUS   current
    DESCRIPTION
            "The address of the upstream neighbor (e.g., RPF neighbor)
            from which IP datagrams from these sources to this multicast
            address are received, or 0.0.0.0 if the upstream neighbor is
            unknown (e.g., in CBT)."
    ::= { ipMRouteEntry 4 }

ipMRouteInIfIndex OBJECT-TYPE
    SYNTAX   InterfaceIndexOrZero
    MAX-ACCESS read-only
    STATUS   current
    DESCRIPTION
            "The value of ifIndex for the interface on which IP
            datagrams sent by these sources to this multicast address
            are received. A value of 0 indicates that datagrams are not
            subject to an incoming interface check, but may be accepted
            on multiple interfaces (e.g., in CBT)."
    ::= { ipMRouteEntry 5 }

ipMRouteUpTime OBJECT-TYPE
    SYNTAX   TimeTicks
    MAX-ACCESS read-only
    STATUS   current
    DESCRIPTION
            "The time since the multicast routing information
            represented by this entry was learned by the router."
    ::= { ipMRouteEntry 6 }

```
ipMRouteExpiryTime OBJECT-TYPE
    SYNTAX      TimeTicks
    MAX-ACCESS read-only
    STATUS      current
    DESCRIPTION
            "The minimum amount of time remaining before this entry will
            be aged out.  The value 0 indicates that the entry is not
            subject to aging."
    ::= { ipMRouteEntry 7 }

ipMRoutePkts OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS read-only
    STATUS      current
    DESCRIPTION
            "The number of packets which this router has received from
            these sources and addressed to this multicast group
            address."
    ::= { ipMRouteEntry 8 }

ipMRouteDifferentInIfPackets OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS read-only
    STATUS      current
    DESCRIPTION
            "The number of packets which this router has received from
            these sources and addressed to this multicast group address,
            which were dropped because they were not received on the
            interface indicated by ipMRouteInIfIndex.  Packets which are
            not subject to an incoming interface check (e.g., using CBT)
            are not counted."
    ::= { ipMRouteEntry 9 }

ipMRouteOctets OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS read-only
    STATUS      current
    DESCRIPTION
            "The number of octets contained in IP datagrams which were
            received from these sources and addressed to this multicast
            group address, and which were forwarded by this router."
    ::= { ipMRouteEntry 10 }

ipMRouteProtocol OBJECT-TYPE
    SYNTAX      IANAipMRouteProtocol
    MAX-ACCESS read-only
    STATUS      current
    DESCRIPTION
```

                "The multicast routing protocol via which this multicast
                forwarding entry was learned."
        ::= { ipMRouteEntry 11 }

ipMRouteRtProto OBJECT-TYPE
    SYNTAX   IANAipRouteProtocol
    MAX-ACCESS read-only
    STATUS   current
    DESCRIPTION
                "The routing mechanism via which the route used to find the
                upstream or parent interface for this multicast forwarding
                entry was learned. Inclusion of values for routing
                protocols is not intended to imply that those protocols need
                be supported."
        ::= { ipMRouteEntry 12 }

ipMRouteRtAddress OBJECT-TYPE
    SYNTAX   IpAddress
    MAX-ACCESS read-only
    STATUS   current
    DESCRIPTION
                "The address portion of the route used to find the upstream
                or parent interface for this multicast forwarding entry."
        ::= { ipMRouteEntry 13 }

ipMRouteRtMask OBJECT-TYPE
    SYNTAX   IpAddress
    MAX-ACCESS read-only
    STATUS   current
    DESCRIPTION
                "The mask associated with the route used to find the upstream
                or parent interface for this multicast forwarding entry."
        ::= { ipMRouteEntry 14 }

ipMRouteRtType OBJECT-TYPE
    SYNTAX   INTEGER {
                  unicast (1), -- Unicast route used in multicast RIB
                  multicast (2) -- Multicast route
                }
    MAX-ACCESS read-only
    STATUS   current
    DESCRIPTION
                "The reason the given route was placed in the (logical)
                multicast Routing Information Base (RIB). A value of
                unicast means that the route would normally be placed only
                in the unicast RIB, but was placed in the multicast RIB
                (instead or in addition) due to local configuration, such as
                when running PIM over RIP. A value of multicast means that

```
                the route was explicitly added to the multicast RIB by the
                routing protocol, such as DVMRP or Multiprotocol BGP."
        ::= { ipMRouteEntry 15 }

ipMRouteHCOctets OBJECT-TYPE
    SYNTAX      Counter64
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "The number of octets contained in IP datagrams which were
            received from these sources and addressed to this multicast
            group address, and which were forwarded by this router.
            This object is a 64-bit version of ipMRouteOctets."
        ::= { ipMRouteEntry 16 }

--
--  The IP Multicast Routing Next Hop Table
--

ipMRouteNextHopTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF IpMRouteNextHopEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "The (conceptual) table containing information on the next-
            hops on outgoing interfaces for routing IP multicast
            datagrams.  Each entry is one of a list of next-hops on
            outgoing interfaces for particular sources sending to a
            particular multicast group address."
        ::= { ipMRoute 3 }

ipMRouteNextHopEntry OBJECT-TYPE
    SYNTAX      IpMRouteNextHopEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "An entry (conceptual row) in the list of next-hops on
            outgoing interfaces to which IP multicast datagrams from
            particular sources to a IP multicast group address are
            routed.  Discontinuities in counters in this entry can be
            detected by observing the value of ipMRouteUpTime."
    INDEX       { ipMRouteNextHopGroup, ipMRouteNextHopSource,
                    ipMRouteNextHopSourceMask, ipMRouteNextHopIfIndex,
                    ipMRouteNextHopAddress }
        ::= { ipMRouteNextHopTable 1 }

IpMRouteNextHopEntry ::= SEQUENCE {
    ipMRouteNextHopGroup                IpAddress,
```

```
    ipMRouteNextHopSource               IpAddress,
    ipMRouteNextHopSourceMask           IpAddress,
    ipMRouteNextHopIfIndex              InterfaceIndex,
    ipMRouteNextHopAddress              IpAddress,
    ipMRouteNextHopState                INTEGER,
    ipMRouteNextHopUpTime               TimeTicks,
    ipMRouteNextHopExpiryTime           TimeTicks,
    ipMRouteNextHopClosestMemberHops    Integer32,
    ipMRouteNextHopProtocol             IANAipMRouteProtocol,
    ipMRouteNextHopPkts                 Counter32
}

ipMRouteNextHopGroup OBJECT-TYPE
    SYNTAX      IpAddress
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "The IP multicast group for which this entry specifies a
            next-hop on an outgoing interface."
    ::= { ipMRouteNextHopEntry 1 }

ipMRouteNextHopSource OBJECT-TYPE
    SYNTAX      IpAddress
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "The network address which when combined with the
            corresponding value of ipMRouteNextHopSourceMask identifies
            the sources for which this entry specifies a next-hop on an
            outgoing interface."
    ::= { ipMRouteNextHopEntry 2 }

ipMRouteNextHopSourceMask OBJECT-TYPE
    SYNTAX      IpAddress
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "The network mask which when combined with the corresponding
            value of ipMRouteNextHopSource identifies the sources for
            which this entry specifies a next-hop on an outgoing
            interface."
    ::= { ipMRouteNextHopEntry 3 }

ipMRouteNextHopIfIndex OBJECT-TYPE
    SYNTAX      InterfaceIndex
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
```

                     "The ifIndex value of the interface for the outgoing
                     interface for this next-hop."
          ::= { ipMRouteNextHopEntry 4 }

ipMRouteNextHopAddress OBJECT-TYPE
     SYNTAX   IpAddress
     MAX-ACCESS not-accessible
     STATUS   current
     DESCRIPTION
                     "The address of the next-hop specific to this entry. For
                     most interfaces, this is identical to ipMRouteNextHopGroup.
                     NBMA interfaces, however, may have multiple next-hop
                     addresses out a single outgoing interface."
          ::= { ipMRouteNextHopEntry 5 }

ipMRouteNextHopState OBJECT-TYPE
     SYNTAX   INTEGER { pruned(1), forwarding(2) }
     MAX-ACCESS read-only
     STATUS   current
     DESCRIPTION
                     "An indication of whether the outgoing interface and next-
                     hop represented by this entry is currently being used to
                     forward IP datagrams. The value 'forwarding' indicates it
                     is currently being used; the value 'pruned' indicates it is
                     not."
          ::= { ipMRouteNextHopEntry 6 }

ipMRouteNextHopUpTime OBJECT-TYPE
     SYNTAX   TimeTicks
     MAX-ACCESS read-only
     STATUS   current
     DESCRIPTION
                     "The time since the multicast routing information
                     represented by this entry was learned by the router."
          ::= { ipMRouteNextHopEntry 7 }

ipMRouteNextHopExpiryTime OBJECT-TYPE
     SYNTAX   TimeTicks
     MAX-ACCESS read-only
     STATUS   current
     DESCRIPTION
                     "The minimum amount of time remaining before this entry will
                     be aged out. If ipMRouteNextHopState is pruned(1), the
                     remaining time until the prune expires and the state reverts
                     to forwarding(2). Otherwise, the remaining time until this
                     entry is removed from the table. The time remaining may be
                     copied from ipMRouteExpiryTime if the protocol in use for
                     this entry does not specify next-hop timers. The value 0

```
                    indicates that the entry is not subject to aging."
        ::= { ipMRouteNextHopEntry 8 }

ipMRouteNextHopClosestMemberHops OBJECT-TYPE
    SYNTAX      Integer32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "The minimum number of hops between this router and any
            member of this IP multicast group reached via this next-hop
            on this outgoing interface.  Any IP multicast datagrams for
            the group which have a TTL less than this number of hops
            will not be forwarded to this next-hop."
        ::= { ipMRouteNextHopEntry 9 }

ipMRouteNextHopProtocol OBJECT-TYPE
    SYNTAX      IANAipMRouteProtocol
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "The routing mechanism via which this next-hop was learned."
        ::= { ipMRouteNextHopEntry 10 }

ipMRouteNextHopPkts OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
            "The number of packets which have been forwarded using this
            route."
        ::= { ipMRouteNextHopEntry 11 }

--
--  The Multicast Routing Interface Table
--

ipMRouteInterfaceTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF IpMRouteInterfaceEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "The (conceptual) table containing multicast routing
            information specific to interfaces."
        ::= { ipMRoute 4 }

ipMRouteInterfaceEntry OBJECT-TYPE
    SYNTAX      IpMRouteInterfaceEntry
    MAX-ACCESS  not-accessible
```

```
        STATUS      current
        DESCRIPTION
                "An entry (conceptual row) containing the multicast routing
                information for a particular interface."
        INDEX       { ipMRouteInterfaceIfIndex }
        ::= { ipMRouteInterfaceTable 1 }

IpMRouteInterfaceEntry ::= SEQUENCE {
    ipMRouteInterfaceIfIndex          InterfaceIndex,
    ipMRouteInterfaceTtl              Integer32,
    ipMRouteInterfaceProtocol         IANAipMRouteProtocol,
    ipMRouteInterfaceRateLimit        Integer32,
    ipMRouteInterfaceInMcastOctets    Counter32,
    ipMRouteInterfaceOutMcastOctets   Counter32,
    ipMRouteInterfaceHCInMcastOctets  Counter64,
    ipMRouteInterfaceHCOutMcastOctets Counter64
}

ipMRouteInterfaceIfIndex OBJECT-TYPE
    SYNTAX      InterfaceIndex
    MAX-ACCESS not-accessible
    STATUS      current
    DESCRIPTION
            "The ifIndex value of the interface for which this entry
            contains information."
    ::= { ipMRouteInterfaceEntry 1 }

ipMRouteInterfaceTtl OBJECT-TYPE
    SYNTAX      Integer32 (0..255)
    MAX-ACCESS read-write
    STATUS      current
    DESCRIPTION
            "The datagram TTL threshold for the interface. Any IP
            multicast datagrams with a TTL less than this threshold will
            not be forwarded out the interface. The default value of 0
            means all multicast packets are forwarded out the
            interface."
    ::= { ipMRouteInterfaceEntry 2 }

ipMRouteInterfaceProtocol OBJECT-TYPE
    SYNTAX      IANAipMRouteProtocol
    MAX-ACCESS read-only
    STATUS      current
    DESCRIPTION
            "The routing protocol running on this interface."
    ::= { ipMRouteInterfaceEntry 3 }

ipMRouteInterfaceRateLimit OBJECT-TYPE
```

```
        SYNTAX      Integer32
        MAX-ACCESS read-write
        STATUS      current
        DESCRIPTION
                "The rate-limit, in kilobits per second, of forwarded
                multicast traffic on the interface.  A rate-limit of 0
                indicates that no rate limiting is done."
        DEFVAL      { 0 }
        ::= { ipMRouteInterfaceEntry 4 }

ipMRouteInterfaceInMcastOctets OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS read-only
        STATUS      current
        DESCRIPTION
                "The number of octets of multicast packets that have arrived
                on the interface, including framing characters.  This object
                is similar to ifInOctets in the Interfaces MIB, except that
                only multicast packets are counted."
        ::= { ipMRouteInterfaceEntry 5 }

ipMRouteInterfaceOutMcastOctets OBJECT-TYPE
        SYNTAX      Counter32
        MAX-ACCESS read-only
        STATUS      current
        DESCRIPTION
                "The number of octets of multicast packets that have been
                sent on the interface."
        ::= { ipMRouteInterfaceEntry 6 }

ipMRouteInterfaceHCInMcastOctets OBJECT-TYPE
        SYNTAX      Counter64
        MAX-ACCESS read-only
        STATUS      current
        DESCRIPTION
                "The number of octets of multicast packets that have arrived
                on the interface, including framing characters.  This object
                is a 64-bit version of ipMRouteInterfaceInMcastOctets.  It
                is similar to ifHCInOctets in the Interfaces MIB, except
                that only multicast packets are counted."
        ::= { ipMRouteInterfaceEntry 7 }

ipMRouteInterfaceHCOutMcastOctets OBJECT-TYPE
        SYNTAX      Counter64
        MAX-ACCESS read-only
        STATUS      current
        DESCRIPTION
                "The number of octets of multicast packets that have been
```

```
                sent on the interface.  This object is a 64-bit version of
                ipMRouteInterfaceOutMcastOctets."
        ::= { ipMRouteInterfaceEntry 8 }

--
--  The IP Multicast Scope Boundary Table
--

ipMRouteBoundaryTable OBJECT-TYPE
    SYNTAX       SEQUENCE OF IpMRouteBoundaryEntry
    MAX-ACCESS not-accessible
    STATUS       current
    DESCRIPTION
            "The (conceptual) table listing the router's scoped
            multicast address boundaries."
    ::= { ipMRoute 5 }

ipMRouteBoundaryEntry OBJECT-TYPE
    SYNTAX       IpMRouteBoundaryEntry
    MAX-ACCESS not-accessible
    STATUS       current
    DESCRIPTION
            "An entry (conceptual row) in the ipMRouteBoundaryTable
            representing a scoped boundary."
    INDEX       { ipMRouteBoundaryIfIndex, ipMRouteBoundaryAddress,
                  ipMRouteBoundaryAddressMask }
    ::= { ipMRouteBoundaryTable 1 }

IpMRouteBoundaryEntry ::= SEQUENCE {
    ipMRouteBoundaryIfIndex            InterfaceIndex,
    ipMRouteBoundaryAddress            IpAddress,
    ipMRouteBoundaryAddressMask        IpAddress,
    ipMRouteBoundaryStatus             RowStatus
}

ipMRouteBoundaryIfIndex OBJECT-TYPE
    SYNTAX       InterfaceIndex
    MAX-ACCESS not-accessible
    STATUS       current
    DESCRIPTION
            "The IfIndex value for the interface to which this boundary
            applies.  Packets with a destination address in the
            associated address/mask range will not be forwarded out this
            interface."
    ::= { ipMRouteBoundaryEntry 1 }

ipMRouteBoundaryAddress OBJECT-TYPE
    SYNTAX       IpAddress
```

```
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "The group address which when combined with the
            corresponding value of ipMRouteBoundaryAddressMask
            identifies the group range for which the scoped boundary
            exists.  Scoped addresses must come from the range 239.x.x.x
            as specified in RFC 2365."
    ::= { ipMRouteBoundaryEntry 2 }

ipMRouteBoundaryAddressMask OBJECT-TYPE
    SYNTAX      IpAddress
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "The group address mask which when combined with the
            corresponding value of ipMRouteBoundaryAddress identifies
            the group range for which the scoped boundary exists."
    ::= { ipMRouteBoundaryEntry 3 }

ipMRouteBoundaryStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
            "The status of this row, by which new entries may be
            created, or old entries deleted from this table."
    ::= { ipMRouteBoundaryEntry 4 }

--
--   The IP Multicast Scope Name Table
--

ipMRouteScopeNameTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF IpMRouteScopeNameEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "The (conceptual) table listing the multicast scope names."
    ::= { ipMRoute 6 }

ipMRouteScopeNameEntry OBJECT-TYPE
    SYNTAX      IpMRouteScopeNameEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "An entry (conceptual row) in the ipMRouteScopeNameTable
            representing a multicast scope name."
```

```
     INDEX        { ipMRouteScopeNameAddress,
                    ipMRouteScopeNameAddressMask,
                    IMPLIED ipMRouteScopeNameLanguage }
     ::= { ipMRouteScopeNameTable 1 }

IpMRouteScopeNameEntry ::= SEQUENCE {
    ipMRouteScopeNameAddress             IpAddress,
    ipMRouteScopeNameAddressMask         IpAddress,
    ipMRouteScopeNameLanguage            LanguageTag,
    ipMRouteScopeNameString              SnmpAdminString,
    ipMRouteScopeNameDefault             TruthValue,
    ipMRouteScopeNameStatus              RowStatus
}

ipMRouteScopeNameAddress OBJECT-TYPE
    SYNTAX       IpAddress
    MAX-ACCESS not-accessible
    STATUS       current
    DESCRIPTION
            "The group address which when combined with the
            corresponding value of ipMRouteScopeNameAddressMask
            identifies the group range associated with the multicast
            scope.  Scoped addresses must come from the range
            239.x.x.x."
    ::= { ipMRouteScopeNameEntry 1 }

ipMRouteScopeNameAddressMask OBJECT-TYPE
    SYNTAX       IpAddress
    MAX-ACCESS not-accessible
    STATUS       current
    DESCRIPTION
            "The group address mask which when combined with the
            corresponding value of ipMRouteScopeNameAddress identifies
            the group range associated with the multicast scope."
    ::= { ipMRouteScopeNameEntry 2 }

ipMRouteScopeNameLanguage OBJECT-TYPE
    SYNTAX       LanguageTag
    MAX-ACCESS not-accessible
    STATUS       current
    DESCRIPTION
            "The RFC 1766-style language tag associated with the scope
            name."
    ::= { ipMRouteScopeNameEntry 3 }

ipMRouteScopeNameString OBJECT-TYPE
    SYNTAX       SnmpAdminString
    MAX-ACCESS read-create
```

```
        STATUS       current
        DESCRIPTION
                "The textual name associated with the multicast scope.  The
                value of this object should be suitable for displaying to
                end-users, such as when allocating a multicast address in
                this scope.  When no name is specified, the default value of
                this object should be the string 239.x.x.x/y with x and y
                replaced appropriately to describe the address and mask
                length associated with the scope."
        ::= { ipMRouteScopeNameEntry 4 }

ipMRouteScopeNameDefault OBJECT-TYPE
        SYNTAX       TruthValue
        MAX-ACCESS read-create
        STATUS       current
        DESCRIPTION
                "If true, indicates a preference that the name in the
                following language should be used by applications if no name
                is available in a desired language."
        DEFVAL { false }
        ::= { ipMRouteScopeNameEntry 5 }

ipMRouteScopeNameStatus OBJECT-TYPE
        SYNTAX       RowStatus
        MAX-ACCESS read-create
        STATUS       current
        DESCRIPTION
                "The status of this row, by which new entries may be
                created, or old entries deleted from this table."
        ::= { ipMRouteScopeNameEntry 6 }


-- conformance information

ipMRouteMIBConformance
                    OBJECT IDENTIFIER ::= { ipMRouteStdMIB 2 }
ipMRouteMIBCompliances
                    OBJECT IDENTIFIER ::= { ipMRouteMIBConformance 1 }
ipMRouteMIBGroups  OBJECT IDENTIFIER ::= { ipMRouteMIBConformance 2 }

-- compliance statements

ipMRouteMIBCompliance MODULE-COMPLIANCE
        STATUS  current
        DESCRIPTION
                "The compliance statement for the IP Multicast MIB."
        MODULE  -- this module
        MANDATORY-GROUPS { ipMRouteMIBBasicGroup,
```

                         ipMRouteMIBRouteGroup}

        GROUP   ipMRouteMIBBoundaryGroup
        DESCRIPTION
            "This group is mandatory if the router supports
            administratively-scoped multicast address boundaries."

        OBJECT   ipMRouteBoundaryStatus
        MIN-ACCESS read-only
        DESCRIPTION
            "Write access is not required."

        OBJECT   ipMRouteScopeNameStatus
        MIN-ACCESS read-only
        DESCRIPTION
            "Write access is not required."

        GROUP   ipMRouteMIBHCInterfaceGroup
        DESCRIPTION
            "This group is mandatory only for those network interfaces
            for which the value of the corresponding instance of ifSpeed
            is greater than 20,000,000 bits/second."

    ::= { ipMRouteMIBCompliances 1 }

-- units of conformance

ipMRouteMIBBasicGroup OBJECT-GROUP
    OBJECTS { ipMRouteEnable, ipMRouteEntryCount,
            ipMRouteUpstreamNeighbor, ipMRouteInIfIndex,
            ipMRouteUpTime, ipMRouteExpiryTime,
            ipMRouteNextHopState,
            ipMRouteNextHopUpTime,
            ipMRouteNextHopExpiryTime,
            ipMRouteNextHopProtocol,
            ipMRouteNextHopPkts,
            ipMRouteInterfaceTtl,
            ipMRouteInterfaceProtocol, ipMRouteInterfaceRateLimit,
            ipMRouteInterfaceInMcastOctets,
            ipMRouteInterfaceOutMcastOctets,
            ipMRouteProtocol
        }
    STATUS current
    DESCRIPTION
            "A collection of objects to support basic management of IP
            Multicast routing."
    ::= { ipMRouteMIBGroups 1 }

```
ipMRouteMIBHopCountGroup OBJECT-GROUP
    OBJECTS { ipMRouteNextHopClosestMemberHops }
    STATUS   current
    DESCRIPTION
            "A collection of objects to support management of the use of
            hop counts in IP Multicast routing."
    ::= { ipMRouteMIBGroups 2 }

ipMRouteMIBBoundaryGroup OBJECT-GROUP
    OBJECTS { ipMRouteBoundaryStatus, ipMRouteScopeNameString,
                ipMRouteScopeNameDefault, ipMRouteScopeNameStatus }
    STATUS   current
    DESCRIPTION
            "A collection of objects to support management of scoped
            multicast address boundaries."
    ::= { ipMRouteMIBGroups 3 }

ipMRouteMIBPktsOutGroup OBJECT-GROUP
    OBJECTS { ipMRouteNextHopPkts }
    STATUS   current
    DESCRIPTION
            "A collection of objects to support management of packet
            counters for each outgoing interface entry of a route."
    ::= { ipMRouteMIBGroups 4 }

ipMRouteMIBHCInterfaceGroup OBJECT-GROUP
    OBJECTS { ipMRouteInterfaceHCInMcastOctets,
                ipMRouteInterfaceHCOutMcastOctets,
                ipMRouteHCOctets }
    STATUS   current
    DESCRIPTION
            "A collection of objects providing information specific to
            high speed (greater than 20,000,000 bits/second) network
            interfaces."
    ::= { ipMRouteMIBGroups 5 }

ipMRouteMIBRouteGroup OBJECT-GROUP
    OBJECTS { ipMRouteRtProto, ipMRouteRtAddress,
                ipMRouteRtMask, ipMRouteRtType }
    STATUS   current
    DESCRIPTION
            "A collection of objects providing information on the
            relationship between multicast routing information, and the
            IP Forwarding Table."
    ::= { ipMRouteMIBGroups 6 }

ipMRouteMIBPktsGroup OBJECT-GROUP
    OBJECTS { ipMRoutePkts, ipMRouteDifferentInIfPackets,
```

```
            ipMRouteOctets }
    STATUS  current
    DESCRIPTION
            "A collection of objects to support management of packet
            counters for each forwarding entry."
    ::= { ipMRouteMIBGroups 7 }
```

END

5. IANA Considerations

    The ipMRouteRtProto, ipMRouteNextHopProtocol,
    ipMRouteInterfaceProtocol, and ipMRouteProtocol use textual
    conventions imported from the IANA-RTPROTO-MIB. The purpose of
    defining these textual conventions in a separate MIB module is to
    allow additional values to be defined without having to issue a new
    version of this document. The Internet Assigned Numbers Authority
    (IANA) is responsible for the assignment of all Internet numbers,
    including various SNMP-related numbers; it will administer the values
    associated with these textual conventions.

    The rules for additions or changes to the IANA-RTPROTO-MIB are
    outlined in the DESCRIPTION clause associated with its MODULE-
    IDENTITY statement.

    The current versions of the IANA-RTPROTO-MIB can be accessed from the
    IANA home page at: "http://www.iana.org/".

6. Security Considerations

    This MIB contains readable objects whose values provide information
    related to multicast routing, including information on what machines
    are sending to which groups. There are also a number of objects that
    have a MAX-ACCESS clause of read-write and/or read-create, such as
    those which allow an administrator to configure multicast boundaries.

    While unauthorized access to the readable objects is relatively
    innocuous, unauthorized access to the write-able objects could cause
    a denial of service, or could cause wider distribution of packets
    intended only for local distribution. Hence, the support for SET
    operations in a non-secure environment without proper protection can
    have a negative effect on network operations.

    SNMPv1 by itself is such an insecure environment. Even if the
    network itself is secure (for example by using IPSec), even then,
    there is no control as to who on the secure network is allowed to
    access and SET (change/create/delete) the objects in this MIB.

It is recommended that the implementers consider the security
features as provided by the SNMPv3 framework. Specifically, the use
of the User-based Security Model RFC 2574 [12] and the View-based
Access Control Model RFC 2575 [15] is recommended.

It is then a customer/user responsibility to ensure that the SNMP
entity giving access to this MIB, is properly configured to give
access to those objects only to those principals (users) that have
legitimate rights to access them.

7. Intellectual Property Notice

The IETF takes no position regarding the validity or scope of any
intellectual property or other rights that might be claimed to
pertain to the implementation or use of the technology described in
this document or the extent to which any license under such rights
might or might not be available; neither does it represent that it
has made any effort to identify any such rights. Information on the
IETF's procedures with respect to rights in standards-track and
standards-related documentation can be found in BCP-11. Copies of
claims of rights made available for publication and any assurances of
licenses to be made available, or the result of an attempt made to
obtain a general license or permission for the use of such
proprietary rights by implementers or users of this specification can
be obtained from the IETF Secretariat.

The IETF invites any interested party to bring to its attention any
copyrights, patents or patent applications, or other proprietary
rights which may cover technology that may be required to practice
this standard. Please address the information to the IETF Executive
Director.

8. Acknowledgements

This MIB module was updated based on feedback from the IETF's Inter-
Domain Multicast Routing (IDMR) Working Group.

9. Authors' Addresses

Keith McCloghrie
cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706

Phone: +1 408 526 5260
EMail: kzm@cisco.com

Dino Farinacci
Procket Networks
3850 North First Street
San Jose, CA 95134

Phone: +1 408-954-7909
Email: dino@procket.com

Dave Thaler
Microsoft Corporation
One Microsoft Way
Redmond, WA 98052-6399

Phone: +1 425 703 8835
EMail: dthaler@microsoft.com

10. References

   [1] Wijnen, B., Harrington, D. and R. Presuhn, "An Architecture for
        Describing SNMP Management Frameworks", RFC 2571, April 1999.

   [2] Rose, M. and K. McCloghrie, "Structure and Identification of
        Management Information for TCP/IP-based Internets", STD 16, RFC
        1155, May 1990.

   [3] Rose, M. and K. McCloghrie, "Concise MIB Definitions", STD 16,
        RFC 1212, March 1991.

   [4] Rose, M., "A Convention for Defining Traps for use with the
        SNMP", RFC 1215, March 1991.

   [5] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose,
        M. and S. Waldbusser, "Structure of Management Information
        Version 2 (SMIv2)", STD 58, RFC 2578, STD 58, April 1999.

   [6] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose,
        M. and S. Waldbusser, "Textual Conventions for SMIv2", STD 58,
        RFC 2579, April 1999.

   [7] McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose,
        M. and S. Waldbusser, "Conformance Statements for SMIv2", STD
        58, RFC 2580, April 1999.

   [8] Case, J., Fedor, M., Schoffstall, M. and J. Davin, "Simple
        Network Management Protocol", STD 15, RFC 1157, May 1990.

   [9] Case, J., McCloghrie, K., Rose, M. and S. Waldbusser,
        "Introduction to Community-based SNMPv2", RFC 1901, January
        1996.

   [10] Case, J., McCloghrie, K., Rose, M. and S. Waldbusser, "Transport
        Mappings for Version 2 of the Simple Network Management Protocol
        (SNMPv2)", RFC 1906, January 1996.

   [11] Case, J., Harrington D., Presuhn R. and B. Wijnen, "Message
        Processing and Dispatching for the Simple Network Management
        Protocol (SNMP)", RFC 2572, April 1999.

   [12] Blumenthal, U. and B. Wijnen, "User-based Security Model (USM)
        for version 3 of the Simple Network Management Protocol
        (SNMPv3)", RFC 2574, April 1999.

[13] Case, J., McCloghrie, K., Rose, M. and S. Waldbusser, "Protocol
     Operations for Version 2 of the Simple Network Management
     Protocol (SNMPv2)", RFC 1905, January 1996.

[14] Levi, D., Meyer, P. and B. Stewart, "SNMPv3 Applications", RFC
     2573, April 1999.

[15] Wijnen, B., Presuhn, R. and K. McCloghrie, "View-based Access
     Control Model (VACM) for the Simple Network Management Protocol
     (SNMP)", RFC 2575, April 1999.

[16] Deering, S., "Multicast Routing in a Datagram Internetwork", PhD
     thesis, Electrical Engineering Dept., Stanford University,
     December 1991.

[17] Waitzman, D., Partridge, C. and S. Deering, "Distance Vector
     Multicast Routing Protocol", RFC 1075, November 1988.

[18] Estrin, D., Farinacci, D., Helmy, A., Thaler, D., Deering, S.,
     Handley, M., Jacobson, V., Liu, C., Sharma, P. and L. Wei,
     "Protocol Independent Multicast-Sparse Mode (PIM-SM): Protocol
     Specification", RFC 2362, June 1998.

[19] Deering, S., Estrin, D., Farinacci, D., Jacobson, V., Helmy, A.
     and L. Wei, "Protocol Independent Multicast Version 2, Dense
     Mode Specification", Work in Progress.

[20] Moy, J., "Multicast Extensions to OSPF", RFC 1584, March 1994.

[21] Ballardie, A., "Core Based Trees (CBT version 2) Multicast
     Routing", RFC 2189, September 1997.

[22] Meyer, D., "Administratively Scoped IP Multicast", BCP 23, RFC
     2365, July 1998.

11. Full Copyright Statement

Acknowledgement