Internet Engineering Task Force (IETF)

Request for Comments: 8080 Category: Standards Track

ISSN: 2070-1721

0. Sury CZ.NIC R. Edmonds Fastly February 2017

Edwards-Curve Digital Security Algorithm (EdDSA) for DNSSEC

## **Abstract**

This document describes how to specify Edwards-curve Digital Security Algorithm (EdDSA) keys and signatures in DNS Security (DNSSEC). It uses EdDSA with the choice of two curves: Ed25519 and Ed448.

### Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in Section 2 of RFC 7841.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at http://www.rfc-editor.org/info/rfc8080.

# Copyright Notice

Copyright (c) 2017 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (http://trustee.ietf.org/license-info) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

### **Table of Contents**

Introduc	tion .			•	•	•		•	•	•	•	•		•	•	•	•	•	•	•	•	•	•	7
Requirem	ents La	angu	age	•																			•	
DNSKEY R	esource	e Ke	cor	ds				•																
RRSIG Re	source	Rec	ord	S																				
Algorith	m Numbe	er f	or	DS.	Ĺ	DŃS	SKE	ĒΥ,	. 6	and	l F	RRS	SIG	F	es	οι	irc	e	Re	co	ro	ls	•	
Examples				•				•	•	•														
.1. Ed25	519 Exa	Jame	es	•																				
.2. Ed44	8 Exam	oles		•																				
IANA Con	sidera	tion	s.	•																				
Security	Consid	dera	tio	ns																				
.1. Norm	ative F	Refe	ren	ces	5	•				•					•					•				
0.2. Info	rmative	Re	fer	end	e	s .		•	•	•	•	•			•	•	•	•		•	•	•	•	
nowledger	ents			•			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
hors' Add	resses			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
	Requirem DNSKEY R RRSIG Re Algorith Examples 1. Ed25 2. Ed44 IANA Con Security Reference 1.1. Norm 1.2. Info	Requirements Land DNSKEY Resource RRSIG Resource Algorithm Number Examples	Requirements Langu DNSKEY Resource Re RRSIG Resource Rec Algorithm Number f Examples	Requirements Language DNSKEY Resource Record RRSIG Resource Record Algorithm Number for Examples	Requirements Language . DNSKEY Resource Records RRSIG Resource Records Algorithm Number for DS Examples	Requirements Language DNSKEY Resource Records . RRSIG Resource Records . Algorithm Number for DS, I Examples	Requirements Language DNSKEY Resource Records RRSIG Resource Records Algorithm Number for DS, DNS Examples	Requirements Language																

### 1. Introduction

DNSSEC, which is broadly defined in [RFC4033], [RFC4034], and [RFC4035], uses cryptographic keys and digital signatures to provide authentication of DNS data. Currently, the most popular signature algorithm in use is RSA. GOST [RFC5933] and NIST-specified elliptic curve cryptography [RFC6605] are also standardized.

[RFC8032] describes the elliptic curve signature system Edwards-curve Digital Signature Algorithm (EdDSA) and recommends two curves, Ed25519 and Ed448.

This document defines the use of DNSSEC's DS, DNSKEY, and RRSIG resource records (RRs) with a new signing algorithm, EdDSA, using a choice of two curves: Ed25519 and Ed448.

## 2. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119].

#### 3. DNSKEY Resource Records

An Ed25519 public key consists of a 32-octet value, which is encoded into the Public Key field of a DNSKEY resource record as a simple bit string. The generation of a public key is defined in Section 5.1.5 of [RFC8032].

An Ed448 public key consists of a 57-octet value, which is encoded into the Public Key field of a DNSKEY resource record as a simple bit string. The generation of a public key is defined in Section 5.2.5 of [RFC8032].

#### 4. RRSIG Resource Records

An Ed25519 signature consists of a 64-octet value, which is encoded into the Signature field of an RRSIG resource record as a simple bit string. The Ed25519 signature algorithm and verification of the Ed25519 signature are described in Sections 5.1.6 and 5.1.7 of [RFC8032], respectively.

An Ed448 signature consists of a 114-octet value, which is encoded into the Signature field of an RRSIG resource record as a simple bit string. The Ed448 signature algorithm and verification of the Ed448 signature are described in Sections 5.2.6 and 5.2.7 of [RFC8032], respectively.

5. Algorithm Number for DS, DNSKEY, and RRSIG Resource Records

The algorithm number associated with the use of Ed25519 in DS, DNSKEY, and RRSIG resource records is 15. The algorithm number associated with the use of Ed448 in DS, DNSKEY, and RRSIG resource records is 16. This registration is fully defined in the IANA Considerations section.

# 6. Examples

# **6.1.** Ed25519 Examples

Private-key-format: v1.2 Algorithm: 15 (ED25519)

PrivateKey: ODIyNjAzODQ2MjgwODAxMjI2NDUxOTAyMDQxNDIyNjI=

example.com. 3600 IN DNSKEY 257 3 15 (

102Woi0iS8Aa25FQkUd9RMzZHJpBoRQwAQEX1SxZJA4= )

example.com. 3600 IN DS 3613 15 2 (

3aa5ab37efce57f737fc1627013fee07bdf241bd10f3b1964ab55c78e79

a304b )

example.com. 3600 IN MX 10 mail.example.com.

example.com. 3600 IN RRSIG MX 3 3600 (

1440021600 1438207200 3613 example.com. (

Edk+IB9KNNWg0HAjm7FazXyrd5m3Rk8zNZbvNpAcM+eysqcU0MIjWoevFkj

H5GaMWeG96GŬVZu6ECKOQmemHDg== )

**Sury & Edmonds** 

Standards Track

[Page 3]

Private-key-format: v1.2 Algorithm: 15 (ED25519)

PrivateKey: DSSF3o0s0f+ElWzj9E/0sxw8hLpk55chkmx0LYN5WiY=

example.com. 3600 IN DNSKEY 257 3 15 (

zPnZ/QwEe7S8C5SPz2OfS5RR40ATk2/rYnE9xHIEijs= )

example.com. 3600 IN DS 35217 15 2 (

401781b934e392de492ec77ae2e15d70f6575a1c0bc59c5275c04ebe80c

6614c )

example.com. 3600 IN MX 10 mail.example.com.

example.com. 3600 IN RRSIG MX 3 3600 (

1440021600 1438207200 35217 example.com. (

5LL2obmzdqjWI+Xto5eP5adXt/T5tMhasWvwcyW4L3SzfcRaw0le9bodhC+

oip9ayUGjŸ9T/rL4rN3bOuESGDA== )

# 6.2. Ed448 Examples

Private-key-format: v1.2 Algorithm: 16 (ED448)

PrivateKey: xZ+5Cgm463xugtkY5B0Jx6erFTXp13rYegst0gRtNs0YnaVpMx0Z/c5EiA9x

8wWbDDct/U3FhYWA

example.com. 3600 IN DNSKEY 257 3 16 (

3kgROaDjrhOH2iuixWBrc8g2EpBBLCdGzHmn+G2MpTPhpj/OiBVHHSfPodx

1FŸYUcJKm1MDpJtIA )

example.com. 3600 IN DS 9713 16 2 (

6ccf18d5bc5d7fc2fceb1d59d17321402f2aa8d368048db93dd811f5cb2

b19c7 )

example.com. 3600 IN MX 10 mail.example.com.

example.com. 3600 IN RRSIG MX 3 3600 (

1440021600 1438207200 9713 example.com. (

NmcOrgGKpr3GKYXcB1JmqqS4NYwhmechvJTqVzt3jR+Qy/lSLFoIk1L+9e3 9GPL+5tVzDPN3f9kAwiu8KCuPPjtl227ayaCZtRKZuJax7n9NuYlZJIusX0

SOIOKBGzG+yWYtz1/jjbzl5GGkWvREUCUA )

Private-key-format: v1.2 Algorithm: 16 (ED448)

PrivateKey: WEykD3ht3MHkU8iH4uV0Lz8JLwtRBSqiBoM6fF72+Mrp/u5gjxuB1DV6NnP0

2BĺZdz4hdSTk0d0A

example.com. 3600 IN DNSKEY 257 3 16 (

kkreGWoccSDmUBGAe7+zsbG6ZAFQp+syPmYUurBRQc3tDjeMCJcVMRDmgcN

Lp5HlHAMy12VoISsA )

example.com. 3600 IN DS 38353 16 2 (

645ff078b3568f5852b70cb60e8e696cc77b75bfaaffc118cf79cbda1ba

28af4 )

example.com. 3600 IN MX 10 mail.example.com.

example.com. 3600 IN RRSIG MX 3 3600 (

1440021600 1438207200 38353 example.com. (

+JjANio/LIzp7osmMYE5XD3H/YES8kXs5Vb9H8MjPS80AGZMD37+LsCIcjg 5ivt0d40m/UaqETEAsJjaYe56CEQP5lhRWuD2ivBqE0zfwJTyp4WqvpULbp

vaukswvv/WNEFxzEYQEIm9+xDlXj4pMAMA )

### 7. IANA Considerations

This document updates the IANA registry "Domain Name System Security (DNSSEC) Algorithm Numbers". The following entries have been added to the registry:

Number Description Mnemonic Zone Signing Trans. Sec. Reference	+	+   16   Ed448   ED448   Y   *
+	Ki C 0000	IXI C 0000 

<sup>\*</sup> There has been no determination of standardization of the use of this algorithm with Transaction Security.

# 8. Security Considerations

The security considerations of [RFC8032] and [RFC7748] are inherited in the usage of Ed25519 and Ed448 in DNSSEC.

Ed25519 is intended to operate at around the 128-bit security level and Ed448 at around the 224-bit security level. A sufficiently large quantum computer would be able to break both. Reasonable projections of the abilities of classical computers conclude that Ed25519 is

perfectly safe. Ed448 is provided for those applications with relaxed performance requirements and where there is a desire to hedge against analytical attacks on elliptic curves.

These assessments could, of course, change in the future if new attacks that work better than the ones known today are found.

A private key used for a DNSSEC zone MUST NOT be used for any other purpose than for that zone. Otherwise, cross-protocol or cross-application attacks are possible.

#### 9. References

## 9.1. Normative References

- [RFC4033] Arends, R., Austein, R., Larson, M., Massey, D., and S.
  Rose, "DNS Security Introduction and Requirements",
  RFC 4033, DOI 10.17487/RFC4033, March 2005,
  <http://www.rfc-editor.org/info/rfc4033>.
- [RFC4034] Arends, R., Austein, R., Larson, M., Massey, D., and S.
  Rose, "Resource Records for the DNS Security Extensions",
  RFC 4034, DOI 10.17487/RFC4034, March 2005,
  <a href="http://www.rfc-editor.org/info/rfc4034">http://www.rfc-editor.org/info/rfc4034</a>>.
- [RFC4035] Arends, R., Austein, R., Larson, M., Massey, D., and S. Rose, "Protocol Modifications for the DNS Security Extensions", RFC 4035, DOI 10.17487/RFC4035, March 2005, <a href="http://www.rfc-editor.org/info/rfc4035">http://www.rfc-editor.org/info/rfc4035</a>.
- [RFC7748] Langley, A., Hamburg, M., and S. Turner, "Elliptic Curves for Security", RFC 7748, DOI 10.17487/RFC7748, January 2016, <a href="http://www.rfc-editor.org/info/rfc7748">http://www.rfc-editor.org/info/rfc7748</a>.

## 9.2. Informative References

[RFC5933] Dolmatov, V., Ed., Chuprina, A., and I. Ustinov, "Use of GOST Signature Algorithms in DNSKEY and RRSIG Resource Records for DNSSEC", RFC 5933, DOI 10.17487/RFC5933, July 2010, <a href="http://www.rfc-editor.org/info/rfc5933">http://www.rfc-editor.org/info/rfc5933</a>.

[RFC6605] Hoffman, P. and W. Wijngaards, "Elliptic Curve Digital Signature Algorithm (DSA) for DNSSEC", RFC 6605, DOI 10.17487/RFC6605, April 2012, <a href="http://www.rfc-editor.org/info/rfc6605">http://www.rfc-editor.org/info/rfc6605</a>.

# **Acknowledgements**

Some of the material in this document is copied liberally from [RFC6605].

The authors of this document wish to thank Jan Vcelak, Pieter Lexis, Kees Monshouwer, Simon Josefsson, Paul Hoffman, and others for a review of this document.

## **Authors' Addresses**

Ondrej Sury CZ.NIC Milesovska 1136/5 Praha 130 00 Czech Republic

Email: ondrej.sury@nic.cz

Robert Edmonds Fastly Atlanta, Georgia United States of America

Email: edmonds@mycre.ws