

Network Working Group  
Request For Comments: 1156  
Obsoletes: RFC 1066

K. McCloghrie  
Hughes LAN Systems  
M. Rose  
Performance Systems International  
May 1990

Management Information Base for Network Management  
of TCP/IP-based internets

Table of Contents

1. Status of this Memo .....	1
2. IAB Policy Statement .....	2
3. Introduction .....	2
4. Objects .....	6
4.1 Object Groups .....	6
4.2 Format of Definitions .....	7
5. Object Definitions .....	8
5.1 The System Group .....	9
5.2 The Interfaces Group .....	11
5.2.1 The Interfaces Table .....	11
5.3 The Address Translation Group .....	23
5.4 The IP Group .....	26
5.4.1 The IP Address Table .....	34
5.4.2 The IP Routing Table .....	36
5.5 The ICMP Group .....	43
5.6 The TCP Group .....	53
5.7 The UDP Group .....	62
5.8 The EGP Group .....	64
5.8.1 The EGP Neighbor Table .....	65
6. Definitions .....	68
7. Acknowledgements .....	89
8. References .....	90
9. Security Considerations.....	91
10. Authors' Addresses.....	91

1. Status of this Memo

This RFC is a re-release of RFC 1066, with a changed "Status of this Memo", "IAB Policy Statement", and "Introduction" sections plus a few minor typographical corrections. The technical content of the document is unchanged from RFC 1066.

This memo provides the initial version of the Management Information Base (MIB) for use with network management protocols in TCP/IP-based internets in the short-term. In particular, together with its companion memos which describe the structure of management

information along with the initial network management protocol, these documents provide a simple, workable architecture and system for managing TCP/IP-based internets and in particular the Internet.

This memo specifies a Standard Protocol for the Internet community. TCP/IP implementations in the Internet which are network manageable are expected to adopt and implement this specification.

The Internet Activities Board recommends that all IP and TCP implementations be network manageable. This implies implementation of the Internet MIB (RFC-1156) and at least one of the two recommended management protocols SNMP (RFC-1157) or CMOT (RFC-1095). It should be noted that, at this time, SNMP is a full Internet standard and CMOT is a draft standard. See also the Host and Gateway Requirements RFCs for more specific information on the applicability of this standard.

Please refer to the latest edition of the "IAB Official Protocol Standards" RFC for current information on the state and status of standard Internet protocols.

Distribution of this memo is unlimited.

## 2. IAB Policy Statement

This MIB specification is the first edition of an evolving document defining variables needed for monitoring and control of various components of the Internet. Not all groups of defined variables are mandatory for all Internet components.

For example, the EGP group is mandatory for gateways using EGP but not for hosts which should not be running EGP. Similarly, the TCP group is mandatory for hosts running TCP but not for gateways which aren't running it. What IS mandatory, however, is that all variables of a group be supported if any element of the group is supported.

It is expected that additional MIB groups and variables will be defined over time to accommodate the monitoring and control needs of new or changing components of the Internet. The responsible working group(s) will continue to refine this specification.

## 3. Introduction

As reported in RFC 1052, IAB Recommendations for the Development of Internet Network Management Standards [1], the Internet Activities Board has directed the Internet Engineering Task Force (IETF) to create two new working groups in the area of network management. One group was charged with the further specification and definition of

elements to be included in the Management Information Base. The other was charged with defining the modifications to the Simple Network Management Protocol (SNMP) to accommodate the short-term needs of the network vendor and operator communities. In the long-term, the use of the OSI network management framework was to be examined using the ISO CMIS/CMIP [2,3] framework as a basis. Two documents were produced to define the management information: RFC 1065, which defined the Structure of Management Information (SMI) [4], and RFC 1066, which defined the Management Information Base (MIB) [5]. Both of these documents were designed so as to be compatible with both the SNMP and the OSI network management framework.

This strategy was quite successful in the short-term: Internet-based network management technology was fielded, by both the research and commercial communities, within a few months. As a result of this, portions of the Internet community became network manageable in a timely fashion.

As reported in RFC 1109, Report of the Second Ad Hoc Network Management Review Group [6], the requirements of the SNMP and the OSI network management frameworks were more different than anticipated. As such, the requirement for compatibility between the SMI/MIB and both frameworks was suspended.

The IAB has designated the SNMP, SMI, and the initial Internet MIB to be full "Standard Protocols" with "Recommended" status. By this action, the IAB recommends that all IP and TCP implementations be network manageable and that the implementations that are network manageable are expected to adopt and implement the SMI, MIB, and SNMP.

As such, the current network management framework for TCP/IP-based internets consists of: Structure and Identification of Management Information for TCP/IP-based Internets, which describes how managed objects contained in the MIB are defined as set forth in RFC 1155 [7]; Management Information Base for Network Management of TCP/IP-based Internets, which describes the managed objects contained in the MIB as set forth in this memo; and, the Simple Network Management Protocol, which defines the protocol used to manage these objects, as set forth in RFC 1157 [8].

The IAB also urged the working groups to be "extremely sensitive to the need to keep SNMP simple," and recommends that the MIB working group take as its starting inputs the MIB definitions found in the High-Level Entity Management Systems (HEMS) RFC 1024 [9], the initial SNMP specification [10], and the CMIS/CMIP memos [11,12].

Thus, the list of managed objects defined here, has been derived by taking only those elements which are considered essential. Since such elements are essential, there is no need to allow the implementation of individual objects, to be optional. Rather, all compliant implementations will contain all applicable (see below) objects defined in this memo.

This approach of taking only the essential objects is NOT restrictive, since the SMI defined in the companion memo provides three extensibility mechanisms: one, the addition of new standard objects through the definitions of new versions of the MIB; two, the addition of widely-available but non-standard objects through the multilateral subtree; and three, the addition of private objects through the enterprises subtree. Such additional objects can not only be used for vendor-specific elements, but also for experimentation as required to further the knowledge of which other objects are essential.

The primary criterion for being considered essential was for an object to be contained in all of the above referenced MIB definitions. A few other objects have been included, but only if the MIB working group believed they are truly essential. The detailed list of criteria against which potential inclusions in this (initial) MIB were considered, was:

- 1) An object needed to be essential for either fault or configuration management.
- 2) Only weak control objects were permitted (by weak, it is meant that tampering with them can do only limited damage). This criterion reflects the fact that the current management protocols are not sufficiently secure to do more powerful control operations.
- 3) Evidence of current use and utility was required.
- 4) An attempt was made to limit the number of objects to about 100 to make it easier for vendors to fully instrument their software.
- 5) To avoid redundant variables, it was required that no object be included that can be derived from others in the MIB.
- 6) Implementation specific objects (e.g., for BSD UNIX) were excluded.
- 7) It was agreed to avoid heavily instrumenting critical

sections of code. The general guideline was one counter per critical section per layer.

## 4. Objects

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. Objects in the MIB are defined using Abstract Syntax Notation One (ASN.1) [13].

The mechanisms used for describing these objects are specified in the companion memo. In particular, each object has a name, a syntax, and an encoding. The name is an object identifier, an administratively assigned name, which specifies an object type. The object type together with an object instance serves to uniquely identify a specific instantiation of the object. For human convenience, we often use a textual string, termed the OBJECT DESCRIPTOR, to also refer to the object type.

The syntax of an object type defines the abstract data structure corresponding to that object type. The ASN.1 language is used for this purpose. However, the companion memo purposely restricts the ASN.1 constructs which may be used. These restrictions are explicitly made for simplicity.

The encoding of an object type is simply how that object type is represented using the object type's syntax. Implicitly tied to the notion of an object type's syntax and encoding is how the object type is represented when being transmitted on the network. This memo specifies the use of the basic encoding rules of ASN.1 [14].

### 4.1. Object Groups

Since this list of managed objects contains only the essential elements, there is no need to allow individual objects to be optional. Rather, the objects are arranged into the following groups:

- System
- Interfaces
- Address Translation
- IP
- ICMP
- TCP
- UDP
- EGP

There are two reasons for defining these groups: one, to provide a means of assigning object identifiers; two, to provide a method for implementations of managed agents to know which objects they must implement. This method is as follows: if the semantics of a group is applicable to an implementation, then it must implement all objects

in that group. For example, an implementation must implement the EGP group if and only if it implements the EGP protocol.

#### 4.2. Format of Definitions

The next section contains the specification of all object types contained in the MIB. Following the conventions of the companion memo, the object types are defined using the following fields:

**OBJECT:**

-----

A textual name, termed the OBJECT DESCRIPTOR, for the object type, along with its corresponding OBJECT IDENTIFIER.

**Syntax:**

The abstract syntax for the object type, presented using ASN.1. This must resolve to an instance of the ASN.1 type ObjectSyntax defined in the SMI.

**Definition:**

A textual description of the semantics of the object type. Implementations should ensure that their interpretation of the object type fulfills this definition since this MIB is intended for use in multi-vendor environments. As such it is vital that object types have consistent meaning across all machines.

**Access:**

One of read-only, read-write, write-only, or not-accessible.

**Status:**

One of mandatory, optional, or obsolete.

## 5. Object Definitions

RFC1156-MIB

DEFINITIONS ::= BEGIN

IMPORTS

mgmt, OBJECT-TYPE, NetworkAddress, IpAddress,  
Counter, Gauge, TimeTicks  
FROM RFC1155-SMI;

mib OBJECT IDENTIFIER ::= { mgmt 1 }

system OBJECT IDENTIFIER ::= { mib 1 }

interfaces OBJECT IDENTIFIER ::= { mib 2 }

at OBJECT IDENTIFIER ::= { mib 3 }

ip OBJECT IDENTIFIER ::= { mib 4 }

icmp OBJECT IDENTIFIER ::= { mib 5 }

tcp OBJECT IDENTIFIER ::= { mib 6 }

udp OBJECT IDENTIFIER ::= { mib 7 }

egp OBJECT IDENTIFIER ::= { mib 8 }

END



### 5.1. The System Group

Implementation of the System group is mandatory for all systems.

**OBJECT:**

-----

sysDescr { system 1 }

**Syntax:**

OCTET STRING

**Definition:**

A textual description of the entity. This value should include the full name and version identification of the system's hardware type, software operating-system, and networking software. It is mandatory that this only contain printable ASCII characters.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

sysObjectID { system 2 }

**Syntax:**

OBJECT IDENTIFIER

**Definition:**

The vendor's authoritative identification of the network management subsystem contained in the entity. This value is allocated within the SMI enterprises subtree (1.3.6.1.4.1) and provides an easy and unambiguous means for determining "what kind of box" is being managed. For example, if vendor "Flintstones, Inc." was assigned the subtree 1.3.6.1.4.1.42, it could assign the identifier 1.3.6.1.4.1.42.1.1 to its "Fred Router".

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

sysUpTime { system 3 }

**Syntax:**

TimeTicks

**Definition:**

The time (in hundredths of a second) since the network management portion of the system was last re-initialized.

**Access:**

read-only.

**Status:**

mandatory.

## 5.2. The Interfaces Group

Implementation of the Interfaces group is mandatory for all systems.

OBJECT:

-----

ifNumber { interfaces 1 }

Syntax:

INTEGER

Definition:

The number of network interfaces (regardless of their current state) on which this system can send/receive IP datagrams.

Access:

read-only.

Status:

mandatory.

### 5.2.1. The Interfaces Table

OBJECT:

-----

ifTable { interfaces 2 }

Syntax:

SEQUENCE OF IfEntry

Definition:

A list of interface entries. The number of entries is given by the value of ifNumber.

Access:

read-write.

Status:

mandatory.

OBJECT:

-----

ifEntry { ifTable 1 }

Syntax:

IfEntry ::= SEQUENCE {

```
    ifIndex
        INTEGER,
    ifDescr
        OCTET STRING,
    ifType
        INTEGER,
    ifMtu
        INTEGER,
    ifSpeed
        Gauge,
    ifPhysAddress
        OCTET STRING,
    ifAdminStatus
        INTEGER,
    ifOperStatus
        INTEGER,
    ifLastChange
        TimeTicks,
    ifInOctets
        Counter,
    ifInUcastPkts
        Counter,
    ifInNUcastPkts
        Counter,
    ifInDiscards
        Counter,
    ifInErrors
        Counter,
    ifInUnknownProtos
        Counter,
    ifOutOctets
        Counter,
    ifOutUcastPkts
        Counter,
    ifOutNUcastPkts
        Counter,
    ifOutDiscards
        Counter,
    ifOutErrors
        Counter,
    ifOutQLen
        Gauge
}
```

**Definition:**

An interface entry containing objects at the subnetwork layer and below for a particular interface.

Access:  
    read-write.

Status:  
    mandatory.

We now consider the individual components of each interface entry:

OBJECT:

-----

    ifIndex { ifEntry 1 }

Syntax:  
    INTEGER

Definition:

    A unique value for each interface. Its value ranges between 1 and the value of ifNumber. The value for each interface must remain constant at least from one re-initialization of the entity's network management system to the next re-initialization.

Access:  
    read-only.

Status:  
    mandatory.

OBJECT:

-----

    ifDescr { ifEntry 2 }

Syntax:  
    OCTET STRING

Definition:

    A text string containing information about the interface. This string should include the name of the manufacturer, the product name and the version of the hardware interface. The string is intended for presentation to a human; it must not contain anything but printable ASCII characters.

Access:  
    read-only.

Status:  
    mandatory.

OBJECT:

-----

    ifType { ifEntry 3 }

Syntax:

```
INTEGER {
    other(1),           -- none of the following
    regular1822(2),
    hdh1822(3),
    ddn-x25(4),
    rfc877-x25(5),
    ethernet-csmacd(6),
    iso88023-csmacd(7),
    iso88024-tokenBus(8),
    iso88025-tokenRing(9),
    iso88026-man(10),
    starLan(11),
    proteon-10MBit(12),
    proteon-80MBit(13),
    hyperchannel(14),
    fddi(15),
    lapb(16),
    sdlc(17),
    t1-carrier(18),
    cept(19),           -- european equivalent of T-1
    basicIsdn(20),
    primaryIsdn(21),
                        -- proprietary serial
    propPointToPointSerial(22)
}
```

Definition:

The type of interface, distinguished according to the physical/link/network protocol(s) immediately "below" IP in the protocol stack.

Access:  
    read-only.

Status:  
    mandatory.

**OBJECT:**

-----

ifMtu { ifEntry 4 }

**Syntax:**

INTEGER

**Definition:**

The size of the largest IP datagram which can be sent/received on the interface, specified in octets.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

ifSpeed { ifEntry 5 }

**Syntax:**

Gauge

**Definition:**

An estimate of the interface's current bandwidth in bits per second. For interfaces which do not vary in bandwidth or for those where no accurate estimation can be made, this object should contain the nominal bandwidth.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

ifPhysAddress { ifEntry 6 }

**Syntax:**

OCTET STRING

**Definition:**

The interface's address at the protocol layer immediately

"below" IP in the protocol stack. For interfaces which do not have such an address (e.g., a serial line), this object should contain an octet string of zero length.

Access:  
read-only.

Status:  
mandatory.

OBJECT:

-----

ifAdminStatus { ifEntry 7 }

Syntax:

```
INTEGER {
    up(1),          -- ready to pass packets
    down(2),
    testing(3)      -- in some test mode
}
```

Definition:

The desired state of the interface. The testing(3) state indicates that no operational packets can be passed.

Access:  
read-write.

Status:  
mandatory.

OBJECT:

-----

ifOperStatus { ifEntry 8 }

Syntax:

```
INTEGER {
    up(1),          -- ready to pass packets
    down(2),
    testing(3)      -- in some test mode
}
```

Definition:

The current operational state of the interface. The testing(3) state indicates that no operational packets can be passed.



Access:  
    read-only.

Status:  
    mandatory.

OBJECT:  
-----  
    ifLastChange { ifEntry 9 }

Syntax:  
    TimeTicks

Definition:  
    The value of sysUpTime at the time the interface entered its current operational state. If the current state was entered prior to the last re-initialization of the local network management subsystem, then this object contains a zero value.

Access:  
    read-only.

Status:  
    mandatory.

OBJECT:  
-----  
    ifInOctets { ifEntry 10 }

Syntax:  
    Counter

Definition:  
    The total number of octets received on the interface, including framing characters.

Access:  
    read-only.

Status:  
    mandatory.

**OBJECT:**

-----

ifInUcastPkts { ifEntry 11 }

**Syntax:**

Counter

**Definition:**

The number of (subnet) unicast packets delivered to a higher-layer protocol.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

ifInNUcastPkts { ifEntry 12 }

**Syntax:**

Counter

**Definition:**

The number of non-unicast (i.e., subnet broadcast or subnet multicast) packets delivered to a higher-layer protocol.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

ifInDiscards { ifEntry 13 }

**Syntax:**

Counter

**Definition:**

The number of inbound packets which were chosen to be discarded even though no errors had been detected to prevent their being deliverable to a higher-layer

protocol. One possible reason for discarding such a packet could be to free up buffer space.

Access:  
read-only.

Status:  
mandatory.

OBJECT:  
-----  
ifInErrors { ifEntry 14 }

Syntax:  
Counter

Definition:  
The number of inbound packets that contained errors preventing them from being deliverable to a higher-layer protocol.

Access:  
read-only.

Status:  
mandatory.

OBJECT:  
-----  
ifInUnknownProtos { ifEntry 15 }

Syntax:  
Counter

Definition:  
The number of packets received via the interface which were discarded because of an unknown or unsupported protocol.

Access:  
read-only.

Status:  
mandatory.

**OBJECT:**

-----

ifOutOctets { ifEntry 16 }

**Syntax:**

Counter

**Definition:**

The total number of octets transmitted out of the interface, including framing characters.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

ifOutUcastPkts { ifEntry 17 }

**Syntax:**

Counter

**Definition:**

The total number of packets that higher-level protocols requested be transmitted to a subnet-unicast address, including those that were discarded or not sent.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

ifOutNUcastPkts { ifEntry 18 }

**Syntax:**

Counter

**Definition:**

The total number of packets that higher-level protocols requested be transmitted to a non-unicast (i.e., a subnet broadcast or subnet multicast) address, including those

that were discarded or not sent.

Access:  
read-only.

Status:  
mandatory.

OBJECT:  
-----  
ifOutDiscards { ifEntry 19 }

Syntax:  
Counter

Definition:  
The number of outbound packets which were chosen to be discarded even though no errors had been detected to prevent their being transmitted. One possible reason for discarding such a packet could be to free up buffer space.

Access:  
read-only.

Status:  
mandatory.

OBJECT:  
-----  
ifOutErrors { ifEntry 20 }

Syntax:  
Counter

Definition:  
The number of outbound packets that could not be transmitted because of errors.

Access:  
read-only.

Status:  
mandatory.

**OBJECT:**

-----

**ifOutQLen { ifEntry 21 }****Syntax:****Gauge****Definition:****The length of the output packet queue (in packets).****Access:****read-only.****Status:****mandatory.**

### 5.3. The Address Translation Group

Implementation of the Address Translation group is mandatory for all systems.

The Address Translation group contains one table which is the union across all interfaces of the translation tables for converting a NetworkAddress (e.g., an IP address) into a subnetwork-specific address. For lack of a better term, this document refers to such a subnetwork-specific address as a "physical" address.

Examples of such translation tables are: for broadcast media where ARP is in use, the translation table is equivalent to the ARP cache; or, on an X.25 network where non-algorithmic translation to X.121 addresses is required, the translation table contains the NetworkAddress to X.121 address equivalences.

OBJECT:

-----

atTable { at 1 }

Syntax:

SEQUENCE OF AtEntry

Definition:

The Address Translation tables contain the NetworkAddress to "physical" address equivalences. Some interfaces do not use translation tables for determining address equivalences (e.g., DDN-X.25 has an algorithmic method); if all interfaces are of this type, then the Address Translation table is empty, i.e., has zero entries.

Access:

read-write.

Status:

mandatory.

OBJECT:

-----

atEntry { atTable 1 }

Syntax:

AtEntry ::= SEQUENCE {  
    atIfIndex

```
        INTEGER,  
        atPhysAddress  
        OCTET STRING,  
        atNetAddress  
        NetworkAddress  
    }
```

**Definition:**

Each entry contains one NetworkAddress to "physical" address equivalence.

**Access:**

read-write.

**Status:**

mandatory.

We now consider the individual components of each Address Translation table entry:

**OBJECT:**

-----

atIfIndex { atEntry 1 }

**Syntax:**

INTEGER

**Definition:**

The interface on which this entry's equivalence is effective. The interface identified by a particular value of this index is the same interface as identified by the same value of ifIndex.

**Access:**

read-write.

**Status:**

mandatory.

**OBJECT:**

-----

atPhysAddress { atEntry 2 }

**Syntax:**

OCTET STRING



**Definition:**

The media-dependent "physical" address.

**Access:**

read-write.

**Status:**

mandatory.

**OBJECT:**

-----

atNetAddress { atEntry 3 }

**Syntax:**

NetworkAddress

**Definition:**

The NetworkAddress (e.g., the IP address) corresponding to the media-dependent "physical" address.

**Access:**

read-write.

**Status:**

mandatory.

#### 5.4. The IP Group

Implementation of the IP group is mandatory for all systems.

**OBJECT:**

-----

ipForwarding { ip 1 }

**Syntax:**

```
INTEGER {  
    gateway(1),    -- entity forwards datagrams  
    host(2)        -- entity does NOT forward datagrams  
}
```

**Definition:**

The indication of whether this entity is acting as an IP gateway in respect to the forwarding of datagrams received by, but not addressed to, this entity. IP gateways forward datagrams; Hosts do not (except those Source-Routed via the host).

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

ipDefaultTTL { ip 2 }

**Syntax:**

INTEGER

**Definition:**

The default value inserted into the Time-To-Live field of the IP header of datagrams originated at this entity, whenever a TTL value is not supplied by the transport layer protocol.

**Access:**

read-write.

**Status:**

mandatory.

**OBJECT:**

-----

**ipInReceives { ip 3 }****Syntax:****Counter****Definition:****The total number of input datagrams received from interfaces, including those received in error.****Access:****read-only.****Status:****mandatory.****OBJECT:**

-----

**ipInHdrErrors { ip 4 }****Syntax:****Counter****Definition:****The number of input datagrams discarded due to errors in their IP headers, including bad checksums, version number mismatch, other format errors, time-to-live exceeded, errors discovered in processing their IP options, etc.****Access:****read-only.****Status:****mandatory.****OBJECT:**

-----

**ipInAddrErrors { ip 5 }****Syntax:****Counter****Definition:****The number of input datagrams discarded because the IP address in their IP header's destination field was not a**

valid address to be received at this entity. This count includes invalid addresses (e.g., 0.0.0.0) and addresses of unsupported Classes (e.g., Class E). For entities which are not IP Gateways and therefore do not forward datagrams, this counter includes datagrams discarded because the destination address was not a local address.

Access:  
read-only.

Status:  
mandatory.

OBJECT:

-----

ipForwDatagrams { ip 6 }

Syntax:  
Counter

Definition:

The number of input datagrams for which this entity was not their final IP destination, as a result of which an attempt was made to find a route to forward them to that final destination. In entities which do not act as IP Gateways, this counter will include only those packets which were Source-Routed via this entity, and the Source-Route option processing was successful.

Access:  
read-only.

Status:  
mandatory.

OBJECT:

-----

ipInUnknownProtos { ip 7 }

Syntax:  
Counter

Definition:

The number of locally-addressed datagrams received successfully but discarded because of an unknown or unsupported protocol.

Access:  
read-only.

Status:  
mandatory.

OBJECT:

-----

ipInDiscards { ip 8 }

Syntax:  
Counter

Definition:

The number of input IP datagrams for which no problems were encountered to prevent their continued processing, but which were discarded (e.g. for lack of buffer space). Note that this counter does not include any datagrams discarded while awaiting re-assembly.

Access:  
read-only.

Status:  
mandatory.

OBJECT:

-----

ipInDelivers { ip 9 }

Syntax:  
Counter

Definition:

The total number of input datagrams successfully delivered to IP user-protocols (including ICMP).

Access:  
read-only.

Status:  
mandatory.

OBJECT:

-----

ipOutRequests { ip 10 }

**Syntax:**

Counter

**Definition:**

The total number of IP datagrams which local IP user-protocols (including ICMP) supplied to IP in requests for transmission. Note that this counter does not include any datagrams counted in ipForwDatagrams.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

ipOutDiscards { ip 11 }

**Syntax:**

Counter

**Definition:**

The number of output IP datagrams for which no problem was encountered to prevent their transmission to their destination, but which were discarded (e.g., for lack of buffer space). Note that this counter would include datagrams counted in ipForwDatagrams if any such packets met this (discretionary) discard criterion.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

ipOutNoRoutes { ip 12 }

**Syntax:**

Counter

**Definition:**

The number of IP datagrams discarded because no route could be found to transmit them to their destination. Note that this counter includes any packets counted in ipForwDatagrams which meet this "no-route" criterion.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

ipReasmTimeout { ip 13 }

**Syntax:**

INTEGER

**Definition:**

The maximum number of seconds which received fragments are held while they are awaiting reassembly at this entity.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

ipReasmReqds { ip 14 }

**Syntax:**

Counter

**Definition:**

The number of IP fragments received which needed to be reassembled at this entity.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

**ipReasmOKs { ip 15 }****Syntax:****Counter****Definition:****The number of IP datagrams successfully re-assembled.****Access:****read-only.****Status:****mandatory.****OBJECT:**

-----

**ipReasmFails { ip 16 }****Syntax:****Counter****Definition:****The number of failures detected by the IP re-assembly algorithm (for whatever reason: timed out, errors, etc).****Note that this is not necessarily a count of discarded IP fragments since some algorithms (notably RFC 815's) can lose track of the number of fragments by combining them as they are received.****Access:****read-only.****Status:****mandatory.****OBJECT:**

-----

**ipFragOKs { ip 17 }****Syntax:****Counter**



**Definition:**

The number of IP datagrams that have been successfully fragmented at this entity.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

ipFragFails { ip 18 }

**Syntax:**

Counter

**Definition:**

The number of IP datagrams that have been discarded because they needed to be fragmented at this entity but could not be, e.g., because their "Don't Fragment" flag was set.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

ipFragCreates { ip 19 }

**Syntax:**

Counter

**Definition:**

The number of IP datagram fragments that have been generated as a result of fragmentation at this entity.

**Access:**

read-only.

**Status:**

mandatory.

#### 5.4.1. The IP Address Table

The Ip Address table contains this entity's IP addressing information.

OBJECT:

-----

ipAddrTable { ip 20 }

Syntax:

SEQUENCE OF IpAddrEntry

Definition:

The table of addressing information relevant to this entity's IP addresses.

Access:

read-only.

Status:

mandatory.

OBJECT:

-----

ipAddrEntry { ipAddrTable 1 }

Syntax:

```
IpAddrEntry ::= SEQUENCE {  
    ipAdEntAddr  
        IpAddress,  
    ipAdEntIfIndex  
        INTEGER,  
    ipAdEntNetMask  
        IpAddress,  
    ipAdEntBcastAddr  
        INTEGER  
}
```

Definition:

The addressing information for one of this entity's IP addresses.

Access:

read-only.

Status:  
mandatory.

OBJECT:

-----

ipAdEntAddr { ipAddrEntry 1 }

Syntax:  
IpAddress

Definition:  
The IP address to which this entry's addressing  
information pertains.

Access:  
read-only.

Status:  
mandatory.

OBJECT:

-----

ipAdEntIfIndex { ipAddrEntry 2 }

Syntax:  
INTEGER

Definition:  
The index value which uniquely identifies the interface  
to which this entry is applicable. The interface  
identified by a particular value of this index is the  
same interface as identified by the same value of  
ifIndex.

Access:  
read-only.

Status:  
mandatory.

OBJECT:

-----

ipAdEntNetMask { ipAddrEntry 3 }

Syntax:  
    IpAddress

Definition:  
    The subnet mask associated with the IP address of this entry. The value of the mask is an IP address with all the network bits set to 1 and all the hosts bits set to 0.

Access:  
    read-only.

Status:  
    mandatory.

OBJECT:  
-----  
    ipAdEntBcastAddr { ipAddrEntry 4 }

Syntax:  
    INTEGER

Definition:  
    The value of the least-significant bit in the IP broadcast address used for sending datagrams on the (logical) interface associated with the IP address of this entry. For example, when the Internet standard all-ones broadcast address is used, the value will be 1.

Access:  
    read-only.

Status:  
    mandatory.

#### 5.4.2. The IP Routing Table

The IP Routing Table contains an entry for each route presently known to this entity. Note that the action to be taken in response to a request to read a non-existent entry, is specific to the network management protocol being used.

OBJECT:  
-----  
    ipRoutingTable { ip 21 }

Syntax:  
SEQUENCE OF IpRouteEntry

Definition:  
This entity's IP Routing table.

Access:  
read-write.

Status:  
mandatory.

OBJECT:

-----

ipRouteEntry { ipRoutingTable 1 }

Syntax:  
IpRouteEntry ::= SEQUENCE {  
    ipRouteDest  
        IpAddress,  
    ipRouteIfIndex  
        INTEGER,  
    ipRouteMetric1  
        INTEGER,  
    ipRouteMetric2  
        INTEGER,  
    ipRouteMetric3  
        INTEGER,  
    ipRouteMetric4  
        INTEGER,  
    ipRouteNextHop  
        IpAddress,  
    ipRouteType  
        INTEGER,  
    ipRouteProto  
        INTEGER,  
    ipRouteAge  
        INTEGER  
}

Definition:  
A route to a particular destination.

Access:  
read-write.

Status:  
mandatory.

We now consider the individual components of each route in the IP Routing Table:

OBJECT:

-----

ipRouteDest { ipRouteEntry 1 }

Syntax:  
IpAddress

Definition:

The destination IP address of this route. An entry with a value of 0.0.0.0 is considered a default route. Multiple such default routes can appear in the table, but access to such multiple entries is dependent on the table-access mechanisms defined by the network management protocol in use.

Access:  
read-write.

Status:  
mandatory.

OBJECT:

-----

ipRouteIfIndex { ipRouteEntry 2 }

Syntax:  
INTEGER

Definition:

The index value which uniquely identifies the local interface through which the next hop of this route should be reached. The interface identified by a particular value of this index is the same interface as identified by the same value of ifIndex.

Access:  
read-write.

Status:  
mandatory.

**OBJECT:**

-----

**ipRouteMetric1 { ipRouteEntry 3 }****Syntax:****INTEGER****Definition:**

The primary routing metric for this route. The semantics of this metric are determined by the routing-protocol specified in the route's ipRouteProto value. If this metric is not used, its value should be set to -1.

**Access:****read-write.****Status:****mandatory.****OBJECT:**

-----

**ipRouteMetric2 { ipRouteEntry 4 }****Syntax:****INTEGER****Definition:**

An alternate routing metric for this route. The semantics of this metric are determined by the routing-protocol specified in the route's ipRouteProto value. If this metric is not used, its value should be set to -1.

**Access:****read-write.****Status:****mandatory.****OBJECT:**

-----

**ipRouteMetric3 { ipRouteEntry 5 }****Syntax:****INTEGER**

**Definition:**

An alternate routing metric for this route. The semantics of this metric are determined by the routing-protocol specified in the route's ipRouteProto value. If this metric is not used, its value should be set to -1.

**Access:**

read-write.

**Status:**

mandatory.

**OBJECT:**

-----

ipRouteMetric4 { ipRouteEntry 6 }

**Syntax:**

INTEGER

**Definition:**

An alternate routing metric for this route. The semantics of this metric are determined by the routing-protocol specified in the route's ipRouteProto value. If this metric is not used, its value should be set to -1.

**Access:**

read-write.

**Status:**

mandatory.

**OBJECT:**

-----

ipRouteNextHop { ipRouteEntry 7 }

**Syntax:**

IpAddress

**Definition:**

The IP address of the next hop of this route.

**Access:**

read-write.

**Status:**

mandatory.



**OBJECT:**

-----

**ipRouteType { ipRouteEntry 8 }****Syntax:**

```
INTEGER {
    other(1),          -- none of the following
    invalid(2),        -- an invalidated route
    direct(3),          -- route to directly
                        -- connected (sub-)network
    remote(4),          -- route to a non-local
                        -- host/network/sub-network
}
```

**Definition:**

The type of route.

**Access:**

read-write.

**Status:**

mandatory.

**OBJECT:**

-----

**ipRouteProto { ipRouteEntry 9 }****Syntax:**

```
INTEGER {
    other(1),          -- none of the following
                        -- non-protocol information,
                        -- e.g., manually configured
    local(2),          -- entries
    netmgmt(3),        -- set via a network management
                        -- protocol
    icmp(4),           -- obtained via ICMP,
                        -- e.g., Redirect
                        -- the remaining values are
    egp(5),            -- all gateway routing protocols
}
```

```
        ggp(6),  
        hello(7),  
        rip(8),  
        is-is(9),  
        es-is(10),  
        ciscoIgrp(11),  
        bbnSpfIgp(12),  
        oigp(13)  
    }
```

**Definition:**

The routing mechanism via which this route was learned. Inclusion of values for gateway routing protocols is not intended to imply that hosts should support those protocols.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

ipRouteAge { ipRouteEntry 10 }

**Syntax:**

INTEGER

**Definition:**

The number of seconds since this route was last updated or otherwise determined to be correct. Note that no semantics of "too old" can be implied except through knowledge of the routing protocol by which the route was learned.

**Access:**

read-write.

**Status:**

mandatory.

### 5.5. The ICMP Group

Implementation of the ICMP group is mandatory for all systems.

The ICMP group contains the ICMP input and output statistics.

Note that individual counters for ICMP message (sub-)codes have been omitted from this (version of the) MIB for simplicity.

**OBJECT:**

-----

icmpInMsgs { icmp 1 }

**Syntax:**

Counter

**Definition:**

The total number of ICMP messages which the entity received. Note that this counter includes all those counted by icmpInErrors.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

icmpInErrors { icmp 2 }

**Syntax:**

Counter

**Definition:**

The number of ICMP messages which the entity received but determined as having errors (bad ICMP checksums, bad length, etc.).

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

**icmpInDestUnreachs { icmp 3 }****Syntax:****Counter****Definition:****The number of ICMP Destination Unreachable messages received.****Access:****read-only.****Status:****mandatory.****OBJECT:**

-----

**icmpInTimeExcds { icmp 4 }****Syntax:****Counter****Definition:****The number of ICMP Time Exceeded messages received.****Access:****read-only.****Status:****mandatory.****OBJECT:**

-----

**icmpInParmProbs { icmp 5 }****Syntax:****Counter****Definition:****The number of ICMP Parameter Problem messages received.****Access:****read-only.**

Status:  
mandatory.

OBJECT:  
-----  
icmpInSrcQuenchs { icmp 6 }

Syntax:  
Counter

Definition:  
The number of ICMP Source Quench messages received.

Access:  
read-only.

Status:  
mandatory.

OBJECT:  
-----  
icmpInRedirects { icmp 7 }

Syntax:  
Counter

Definition:  
The number of ICMP Redirect messages received.

Access:  
read-only.

Status:  
mandatory.

OBJECT:  
-----  
icmpInEchos { icmp 8 }

Syntax:  
Counter

Definition:  
The number of ICMP Echo (request) messages received.

Access:  
    read-only.

Status:  
    mandatory.

OBJECT:  
-----  
    icmpInEchoReps { icmp 9 }

Syntax:  
    Counter

Definition:  
    The number of ICMP Echo Reply messages received.

Access:  
    read-only.

Status:  
    mandatory.

OBJECT:  
-----  
    icmpInTimestamps { icmp 10 }

Syntax:  
    Counter

Definition:  
    The number of ICMP Timestamp (request) messages received.

Access:  
    read-only.

Status:  
    mandatory.

OBJECT:  
-----  
    icmpInTimestampReps { icmp 11 }

Syntax:  
    Counter

**Definition:**

The number of ICMP Timestamp Reply messages received.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

icmpInAddrMasks { icmp 12 }

**Syntax:**

Counter

**Definition:**

The number of ICMP Address Mask Request messages received.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

icmpInAddrMaskReps { icmp 13 }

**Syntax:**

Counter

**Definition:**

The number of ICMP Address Mask Reply messages received.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

icmpOutMsgs { icmp 14 }

**Syntax:****Counter****Definition:**

The total number of ICMP messages which this entity attempted to send. Note that this counter includes all those counted by icmpOutErrors.

**Access:****read-only.****Status:****mandatory.****OBJECT:**

-----

**icmpOutErrors { icmp 15 }****Syntax:****Counter****Definition:**

The number of ICMP messages which this entity did not send due to problems discovered within ICMP such as a lack of buffers. This value should not include errors discovered outside the ICMP layer such as the inability of IP to route the resultant datagram. In some implementations there may be no types of error which contribute to this counter's value.

**Access:****read-only.****Status:****mandatory.****OBJECT:**

-----

**icmpOutDestUnreachs { icmp 16 }****Syntax:****Counter****Definition:**

The number of ICMP Destination Unreachable messages sent.



Access:  
    read-only.

Status:  
    mandatory.

OBJECT:  
-----  
    icmpOutTimeExcds { icmp 17 }

Syntax:  
    Counter

Definition:  
    The number of ICMP Time Exceeded messages sent.

Access:  
    read-only.

Status:  
    mandatory.

OBJECT:  
-----  
    icmpOutParmProbs { icmp 18 }

Syntax:  
    Counter

Definition:  
    The number of ICMP Parameter Problem messages sent.

Access:  
    read-only.

Status:  
    mandatory.

OBJECT:  
-----  
    icmpOutSrcQuenchs { icmp 19 }

Syntax:  
    Counter

**Definition:**

The number of ICMP Source Quench messages sent.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

icmpOutRedirects { icmp 20 }

**Syntax:**

Counter

**Definition:**

The number of ICMP Redirect messages sent.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

icmpOutEchos { icmp 21 }

**Syntax:**

Counter

**Definition:**

The number of ICMP Echo (request) messages sent.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

icmpOutEchoReps { icmp 22 }

**Syntax:****Counter****Definition:****The number of ICMP Echo Reply messages sent.****Access:****read-only.****Status:****mandatory.****OBJECT:**

-----

**icmpOutTimestamps { icmp 23 }****Syntax:****Counter****Definition:****The number of ICMP Timestamp (request) messages sent.****Access:****read-only.****Status:****mandatory.****OBJECT:**

-----

**icmpOutTimestampReps { icmp 24 }****Syntax:****Counter****Definition:****The number of ICMP Timestamp Reply messages sent.****Access:****read-only.****Status:****mandatory.**

**OBJECT:**

-----

**icmpOutAddrMasks { icmp 25 }****Syntax:****Counter****Definition:****The number of ICMP Address Mask Request messages sent.****Access:****read-only.****Status:****mandatory.****OBJECT:**

-----

**icmpOutAddrMaskReps { icmp 26 }****Syntax:****Counter****Definition:****The number of ICMP Address Mask Reply messages sent.****Access:****read-only.****Status:****mandatory.**

## 5.6. The TCP Group

Implementation of the TCP group is mandatory for all systems that implement the TCP protocol.

Note that instances of object types that represent information about a particular TCP connection are transient; they persist only as long as the connection in question.

### OBJECT:

-----

tcpRtoAlgorithm { tcp 1 }

### Syntax:

```
INTEGER {
    other(1),      -- none of the following
    constant(2),  -- a constant rto
    rsre(3),       -- MIL-STD-1778, Appendix B
    vanj(4)        -- Van Jacobson's algorithm [15]
}
```

### Definition:

The algorithm used to determine the timeout value used for retransmitting unacknowledged octets.

### Access:

read-only.

### Status:

mandatory.

### OBJECT:

-----

tcpRtoMin { tcp 2 }

### Syntax:

INTEGER

### Definition:

The minimum value permitted by a TCP implementation for the retransmission timeout, measured in milliseconds. More refined semantics for objects of this type depend upon the algorithm used to determine the retransmission timeout. In particular, when the timeout algorithm is rsre(3), an object of this type has the semantics of the LBOUND quantity described in RFC 793.

Access:  
    read-only.

Status:  
    mandatory.

OBJECT:  
-----  
    tcpRtoMax { tcp 3 }

Syntax:  
    INTEGER

Definition:  
    The maximum value permitted by a TCP implementation for the retransmission timeout, measured in milliseconds. More refined semantics for objects of this type depend upon the algorithm used to determine the retransmission timeout. In particular, when the timeout algorithm is rsre(3), an object of this type has the semantics of the UBOUND quantity described in RFC 793.

Access:  
    read-only.

Status:  
    mandatory.

OBJECT:  
-----  
    tcpMaxConn { tcp 4 }

Syntax:  
    INTEGER

Definition:  
    The limit on the total number of TCP connections the entity can support. In entities where the maximum number of connections is dynamic, this object should contain the value "-1".

Access:  
    read-only.

Status:  
mandatory.

OBJECT:  
-----  
tcpActiveOpens { tcp 5 }

Syntax:  
Counter

Definition:  
The number of times TCP connections have made a direct transition to the SYN-SENT state from the CLOSED state.

Access:  
read-only.

Status:  
mandatory.

OBJECT:  
-----  
tcpPassiveOpens { tcp 6 }

Syntax:  
Counter

Definition:  
The number of times TCP connections have made a direct transition to the SYN-RCVD state from the LISTEN state.

Access:  
read-only.

Status:  
mandatory.

OBJECT:  
-----  
tcpAttemptFails { tcp 7 }

Syntax:  
Counter

**Definition:**

The number of times TCP connections have made a direct transition to the CLOSED state from either the SYN-SENT state or the SYN-RCVD state, plus the number of times TCP connections have made a direct transition to the LISTEN state from the SYN-RCVD state.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

tcpEstabResets { tcp 8 }

**Syntax:**

Counter

**Definition:**

The number of times TCP connections have made a direct transition to the CLOSED state from either the ESTABLISHED state or the CLOSE-WAIT state.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

tcpCurrEstab { tcp 9 }

**Syntax:**

Gauge

**Definition:**

The number of TCP connections for which the current state is either ESTABLISHED or CLOSE-WAIT.

**Access:**

read-only.



Status:  
mandatory.

OBJECT:  
-----  
tcpInSegs { tcp 10 }

Syntax:  
Counter

Definition:  
The total number of segments received, including those received in error. This count includes segments received on currently established connections.

Access:  
read-only.

Status:  
mandatory.

OBJECT:  
-----  
tcpOutSegs { tcp 11 }

Syntax:  
Counter

Definition:  
The total number of segments sent, including those on current connections but excluding those containing only retransmitted octets.

Access:  
read-only.

Status:  
mandatory.

OBJECT:  
-----  
tcpRetransSegs { tcp 12 }

Syntax:  
Counter

**Definition:**

The total number of segments retransmitted - that is, the number of TCP segments transmitted containing one or more previously transmitted octets.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

tcpConnTable { tcp 13 }

**Syntax:**

SEQUENCE OF TcpConnEntry

**Definition:**

A table containing TCP connection-specific information.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

tcpConnEntry { tcpConnTable 1 }

**Syntax:**

```
TcpConnEntry ::= SEQUENCE {  
    tcpConnState  
        INTEGER,  
    tcpConnLocalAddress  
        IpAddress,  
    tcpConnLocalPort  
        INTEGER (0..65535),  
    tcpConnRemAddress  
        IpAddress,  
    tcpConnRemPort  
        INTEGER (0..65535)  
}
```

**Definition:**

Information about a particular current TCP connection.  
An object of this type is transient, in that it ceases to exist when (or soon after) the connection makes the transition to the CLOSED state.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

tcpConnState { tcpConnEntry 1 }

**Syntax:**

```
INTEGER {  
    closed(1),  
    listen(2),  
    synSent(3),  
    synReceived(4),  
    established(5),  
    finWait1(6),  
    finWait2(7),  
    closeWait(8),  
    lastAck(9),  
    closing(10),  
    timeWait(11)  
}
```

**Definition:**

The state of this TCP connection.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

tcpConnLocalAddress { tcpConnEntry 2 }

**Syntax:**

IpAddress

**Definition:**

The local IP address for this TCP connection.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

tcpConnLocalPort { tcpConnEntry 3 }

**Syntax:**

INTEGER (0..65535)

**Definition:**

The local port number for this TCP connection.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

tcpConnRemAddress { tcpConnEntry 4 }

**Syntax:**

IpAddress

**Definition:**

The remote IP address for this TCP connection.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

tcpConnRemPort { tcpConnEntry 5 }

**Syntax:**  
    INTEGER (0..65535)

**Definition:**  
    The remote port number for this TCP connection.

**Access:**  
    read-only.

**Status:**  
    mandatory.

### 5.7. The UDP Group

Implementation of the UDP group is mandatory for all systems which implement the UDP protocol.

**OBJECT:**

-----

**udpInDatagrams { udp 1 }****Syntax:****Counter****Definition:****The total number of UDP datagrams delivered to UDP users.****Access:****read-only.****Status:****mandatory.****OBJECT:**

-----

**udpNoPorts { udp 2 }****Syntax:****Counter****Definition:****The total number of received UDP datagrams for which there was no application at the destination port.****Access:****read-only.****Status:****mandatory.****OBJECT:**

-----

**udpInErrors { udp 3 }****Syntax:****Counter**

**Definition:**

The number of received UDP datagrams that could not be delivered for reasons other than the lack of an application at the destination port.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

udpOutDatagrams { udp 4 }

**Syntax:**

Counter

**Definition:**

The total number of UDP datagrams sent from this entity.

**Access:**

read-only.

**Status:**

mandatory.

### 5.8. The EGP Group

Implementation of the EGP group is mandatory for all systems which implement the EGP protocol.

**OBJECT:**

-----

egpInMsgs { egp 1 }

**Syntax:**

Counter

**Definition:**

The number of EGP messages received without error.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

egpInErrors { egp 2 }

**Syntax:**

Counter

**Definition:**

The number of EGP messages received that proved to be in error.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

egpOutMsgs { egp 3 }

**Syntax:**

Counter



**Definition:**

The total number of locally generated EGP messages.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

egpOutErrors { egp 4 }

**Syntax:**

Counter

**Definition:**

The number of locally generated EGP messages not sent due to resource limitations within an EGP entity.

**Access:**

read-only.

**Status:**

mandatory.

#### 5.8.1. The EGP Neighbor Table

The Egp Neighbor table contains information about this entity's EGP neighbors.

**OBJECT:**

-----

egpNeighTable { egp 5 }

**Syntax:**

SEQUENCE OF EgpNeighEntry

**Definition:**

The EGP neighbor table.

**Access:**

read-only.

**Status:**

mandatory.

**OBJECT:**

-----

**egpNeighEntry { egpNeighTable 1 }****Syntax:**

```
EgpNeighEntry ::= SEQUENCE {  
    egpNeighState  
        INTEGER,  
    egpNeighAddr  
        IpAddress  
}
```

**Definition:**

Information about this entity's relationship with a particular EGP neighbor.

**Access:**

read-only.

**Status:**

mandatory.

We now consider the individual components of each EGP neighbor entry:

**OBJECT:**

-----

**egpNeighState { egpNeighEntry 1 }****Syntax:**

```
INTEGER {  
    idle(1),  
    acquisition(2),  
    down(3),  
    up(4),  
    cease(5)  
}
```

**Definition:**

The EGP state of the local system with respect to this entry's EGP neighbor. Each EGP state is represented by a value that is one greater than the numerical value associated with said state in RFC 904.

**Access:**

read-only.

Status:  
mandatory.

OBJECT:

-----

egpNeighAddr { egpNeighEntry 2 }

Syntax:  
IpAddress

Definition:  
The IP address of this entry's EGP neighbor.

Access:  
read-only.

Status:  
mandatory.

## 6. Definitions

RFC1156-MIB

DEFINITIONS ::= BEGIN

IMPORTS

mgmt, OBJECT-TYPE, NetworkAddress, IpAddress,  
Counter, Gauge, TimeTicks  
FROM RFC1155-SMI;

mib OBJECT IDENTIFIER ::= { mgmt 1 }

system OBJECT IDENTIFIER ::= { mib 1 }

interfaces OBJECT IDENTIFIER ::= { mib 2 }

at OBJECT IDENTIFIER ::= { mib 3 }

ip OBJECT IDENTIFIER ::= { mib 4 }

icmp OBJECT IDENTIFIER ::= { mib 5 }

tcp OBJECT IDENTIFIER ::= { mib 6 }

udp OBJECT IDENTIFIER ::= { mib 7 }

egp OBJECT IDENTIFIER ::= { mib 8 }

-- object types

-- the System group

sysDescr OBJECT-TYPE  
SYNTAX OCTET STRING  
ACCESS read-only  
STATUS mandatory  
::= { system 1 }

sysObjectId OBJECT-TYPE  
SYNTAX OBJECT IDENTIFIER  
ACCESS read-only  
STATUS mandatory  
::= { system 2 }

sysUpTime OBJECT-TYPE  
SYNTAX TimeTicks  
ACCESS read-only  
STATUS mandatory  
::= { system 3 }

-- the Interfaces group

ifNumber OBJECT-TYPE  
SYNTAX INTEGER

```
        ACCESS  read-only
        STATUS  mandatory
        ::= { interfaces 1 }

-- the Interfaces table

ifTable OBJECT-TYPE
    SYNTAX  SEQUENCE OF IfEntry
    ACCESS  read-write
    STATUS  mandatory
    ::= { interfaces 2 }

ifEntry OBJECT-TYPE
    SYNTAX  IfEntry
    ACCESS  read-write
    STATUS  mandatory
    ::= { ifTable 1 }

IfEntry ::= SEQUENCE {
    ifIndex
        INTEGER,
    ifDescr
        OCTET STRING,
    ifType
        INTEGER,
    ifMtu
        INTEGER,
    ifSpeed
        Gauge,
    ifPhysAddress
        OCTET STRING,
    ifAdminStatus
        INTEGER,
    ifOperStatus
        INTEGER,
    ifLastChange
        TimeTicks,
    ifInOctets
        Counter,
    ifInUcastPkts
        Counter,
    ifInNUcastPkts
        Counter,
    ifInDiscards
        Counter,
    ifInErrors
        Counter,
    ifInUnknownProtos
```

```
        Counter,
    ifOutOctets
        Counter,
    ifOutUcastPkts
        Counter,
    ifOutNUcastPkts
        Counter,
    ifOutDiscards
        Counter,
    ifOutErrors
        Counter,
    ifOutQLen
        Gauge
}

ifIndex OBJECT-TYPE
    SYNTAX  INTEGER
    ACCESS  read-only
    STATUS  mandatory
    ::= { ifEntry 1 }

ifDescr OBJECT-TYPE
    SYNTAX  OCTET STRING
    ACCESS  read-only
    STATUS  mandatory
    ::= { ifEntry 2 }

ifType OBJECT-TYPE
    SYNTAX  INTEGER {
        other(1),          -- none of the following
        regular1822(2),
        hdh1822(3),
        ddn-x25(4),
        rfc877-x25(5),
        ethernet-csmacd(6),
        iso88023-csmacd(7),
        iso88024-tokenBus(8),
        iso88025-tokenRing(9),
        iso88026-man(10),
        starLan(11),
        proteon-10MBit(12),
        proteon-80MBit(13),
        hyperchannel(14),
        fddi(15),
        lapb(16),
        sdlc(17),
        t1-carrier(18),
        cept(19),
```

```

        basicIsdn(20),
        primaryIsdn(21),
        propPointToPointSerial(22)
    }
    ACCESS read-only
    STATUS mandatory
    ::= { ifEntry 3 }

ifMtu OBJECT-TYPE
    SYNTAX INTEGER
    ACCESS read-only
    STATUS mandatory
    ::= { ifEntry 4 }

ifSpeed OBJECT-TYPE
    SYNTAX Gauge
    ACCESS read-only
    STATUS mandatory
    ::= { ifEntry 5 }

ifPhysAddress OBJECT-TYPE
    SYNTAX OCTET STRING
    ACCESS read-only
    STATUS mandatory
    ::= { ifEntry 6 }

ifAdminStatus OBJECT-TYPE
    SYNTAX INTEGER {
        up(1),
        down(2),
        testing(3)
    }
    ACCESS read-write
    STATUS mandatory
    ::= { ifEntry 7 }

ifOperStatus OBJECT-TYPE
    SYNTAX INTEGER {
        up(1),
        down(2),
        testing(3)
    }
    ACCESS read-only
    STATUS mandatory
    ::= { ifEntry 8 }

ifLastChange OBJECT-TYPE

```

```

-- ready to pass packets

```

```

-- in some test mode

```

```

-- ready to pass packets

```

```

-- in some test mode

```

```
SYNTAX   TimeTicks
ACCESS   read-only
STATUS   mandatory
::= { ifEntry 9 }

ifInOctets OBJECT-TYPE
SYNTAX   Counter
ACCESS   read-only
STATUS   mandatory
::= { ifEntry 10 }

ifInUcastPkts OBJECT-TYPE
SYNTAX   Counter
ACCESS   read-only
STATUS   mandatory
::= { ifEntry 11 }

ifInNUcastPkts OBJECT-TYPE
SYNTAX   Counter
ACCESS   read-only
STATUS   mandatory
::= { ifEntry 12 }

ifInDiscards OBJECT-TYPE
SYNTAX   Counter
ACCESS   read-only
STATUS   mandatory
::= { ifEntry 13 }

ifInErrors OBJECT-TYPE
SYNTAX   Counter
ACCESS   read-only
STATUS   mandatory
::= { ifEntry 14 }

ifInUnknownProtos OBJECT-TYPE
SYNTAX   Counter
ACCESS   read-only
STATUS   mandatory
::= { ifEntry 15 }

ifOutOctets OBJECT-TYPE
SYNTAX   Counter
ACCESS   read-only
STATUS   mandatory
::= { ifEntry 16 }

ifOutUcastPkts OBJECT-TYPE
```



```
SYNTAX Counter
ACCESS read-only
STATUS mandatory
::= { ifEntry 17 }

ifOutNUcastPkts OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    ::= { ifEntry 18 }

ifOutDiscards OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    ::= { ifEntry 19 }

ifOutErrors OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    ::= { ifEntry 20 }

ifOutQLen OBJECT-TYPE
    SYNTAX Gauge
    ACCESS read-only
    STATUS mandatory
    ::= { ifEntry 21 }

-- the Address Translation group

atTable OBJECT-TYPE
    SYNTAX SEQUENCE OF AtEntry
    ACCESS read-write
    STATUS mandatory
    ::= { at 1 }

atEntry OBJECT-TYPE
    SYNTAX AtEntry
    ACCESS read-write
    STATUS mandatory
    ::= { atTable 1 }

AtEntry ::= SEQUENCE {
    atIfIndex
        INTEGER,
    atPhysAddress
        OCTET STRING,
```

```
        atNetAddress
            NetworkAddress
    }

    atIfIndex OBJECT-TYPE
        SYNTAX  INTEGER
        ACCESS  read-write
        STATUS  mandatory
        ::= { atEntry 1 }

    atPhysAddress OBJECT-TYPE
        SYNTAX  OCTET STRING
        ACCESS  read-write
        STATUS  mandatory
        ::= { atEntry 2 }

    atNetAddress OBJECT-TYPE
        SYNTAX  NetworkAddress
        ACCESS  read-write
        STATUS  mandatory
        ::= { atEntry 3 }

-- the IP group

    ipForwarding OBJECT-TYPE
        SYNTAX  INTEGER {
            gateway(1), -- entity forwards datagrams
            host(2)     -- entity does NOT forward datagrams
        }
        ACCESS  read-only
        STATUS  mandatory
        ::= { ip 1 }

    ipDefaultTTL OBJECT-TYPE
        SYNTAX  INTEGER
        ACCESS  read-write
        STATUS  mandatory
        ::= { ip 2 }

    ipInReceives OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { ip 3 }

    ipInHdrErrors OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
```

```
STATUS mandatory
 ::= { ip 4 }

ipInAddrErrors OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    ::= { ip 5 }

ipForwDatagrams OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    ::= { ip 6 }

ipInUnknownProtos OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    ::= { ip 7 }

ipInDiscards OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    ::= { ip 8 }

ipInDelivers OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    ::= { ip 9 }

ipOutRequests OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    ::= { ip 10 }

ipOutDiscards OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    ::= { ip 11 }

ipOutNoRoutes OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
```

```
        STATUS mandatory
        ::= { ip 12 }

ipReasmTimeout OBJECT-TYPE
    SYNTAX  INTEGER
    ACCESS  read-only
    STATUS  mandatory
    ::= { ip 13 }

ipReasmReqds OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { ip 14 }

ipReasmOKs OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { ip 15 }

ipReasmFails OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { ip 16 }

ipFragOKs OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { ip 17 }

ipFragFails OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { ip 18 }

ipFragCreates OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { ip 19 }

-- the IP Interface table

ipAddrTable OBJECT-TYPE
```

```
SYNTAX  SEQUENCE OF IpAddrEntry
ACCESS  read-only
STATUS  mandatory
::= { ip 20 }
```

```
ipAddrEntry OBJECT-TYPE
SYNTAX  IpAddrEntry
ACCESS  read-only
STATUS  mandatory
::= { ipAddrTable 1 }
```

```
IpAddrEntry ::= SEQUENCE {
    ipAdEntAddr
        IpAddress,
    ipAdEntIfIndex
        INTEGER,
    ipAdEntNetMask
        IpAddress,
    ipAdEntBcastAddr
        INTEGER
}
```

```
ipAdEntAddr OBJECT-TYPE
SYNTAX  IpAddress
ACCESS  read-only
STATUS  mandatory
::= { ipAddrEntry 1 }
```

```
ipAdEntIfIndex OBJECT-TYPE
SYNTAX  INTEGER
ACCESS  read-only
STATUS  mandatory
::= { ipAddrEntry 2 }
```

```
ipAdEntNetMask OBJECT-TYPE
SYNTAX  IpAddress
ACCESS  read-only
STATUS  mandatory
::= { ipAddrEntry 3 }
```

```
ipAdEntBcastAddr OBJECT-TYPE
SYNTAX  INTEGER
ACCESS  read-only
STATUS  mandatory
::= { ipAddrEntry 4 }
```

```
-- the IP Routing table

ipRoutingTable OBJECT-TYPE
    SYNTAX  SEQUENCE OF IpRouteEntry
    ACCESS  read-write
    STATUS  mandatory
    ::= { ip 21 }

ipRouteEntry OBJECT-TYPE
    SYNTAX  IpRouteEntry
    ACCESS  read-write
    STATUS  mandatory
    ::= { ipRoutingTable 1 }

IpRouteEntry ::= SEQUENCE {
    ipRouteDest
        IpAddress,
    ipRouteIfIndex
        INTEGER,
    ipRouteMetric1
        INTEGER,
    ipRouteMetric2
        INTEGER,
    ipRouteMetric3
        INTEGER,
    ipRouteMetric4
        INTEGER,
    ipRouteNextHop
        IpAddress,
    ipRouteType
        INTEGER,
    ipRouteProto
        INTEGER,
    ipRouteAge
        INTEGER
}

ipRouteDest OBJECT-TYPE
    SYNTAX  IpAddress
    ACCESS  read-write
    STATUS  mandatory
    ::= { ipRouteEntry 1 }

ipRouteIfIndex OBJECT-TYPE
    SYNTAX  INTEGER
    ACCESS  read-write
    STATUS  mandatory
    ::= { ipRouteEntry 2 }
```

```
ipRouteMetric1 OBJECT-TYPE
    SYNTAX  INTEGER
    ACCESS  read-write
    STATUS  mandatory
    ::= { ipRouteEntry 3 }

ipRouteMetric2 OBJECT-TYPE
    SYNTAX  INTEGER
    ACCESS  read-write
    STATUS  mandatory
    ::= { ipRouteEntry 4 }

ipRouteMetric3 OBJECT-TYPE
    SYNTAX  INTEGER
    ACCESS  read-write
    STATUS  mandatory
    ::= { ipRouteEntry 5 }

ipRouteMetric4 OBJECT-TYPE
    SYNTAX  INTEGER
    ACCESS  read-write
    STATUS  mandatory
    ::= { ipRouteEntry 6 }

ipRouteNextHop OBJECT-TYPE
    SYNTAX  IpAddress
    ACCESS  read-write
    STATUS  mandatory
    ::= { ipRouteEntry 7 }

ipRouteType OBJECT-TYPE
    SYNTAX  INTEGER {
        other(1),      -- none of the following
        invalid(2),    -- an invalidated route
        direct(3),      -- route to directly
                        -- connected (sub-)network
        remote(4),      -- route to a non-local
                        -- host/network/sub-network
    }
    ACCESS  read-write
    STATUS  mandatory
    ::= { ipRouteEntry 8 }

ipRouteProto OBJECT-TYPE
    SYNTAX  INTEGER {
```

```

other(1),      -- none of the following
                -- non-protocol information
                --   e.g., manually
local(2),      --   configured entries

netmgmt(3),    -- set via a network
                --   management protocol

icmp(4),       -- obtained via ICMP,
                --   e.g., Redirect

                -- the following are
                -- gateway routing protocols
egp(5),
ggp(6),
hello(7),
rip(8),
is-is(9),
es-is(10),
ciscoIgrp(11),
bbnSpfIgp(12),
oigp(13)
}
ACCESS read-only
STATUS mandatory
::= { ipRouteEntry 9 }

ipRouteAge OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-write
STATUS mandatory
::= { ipRouteEntry 10 }

-- the ICMP group

icmpInMsgs OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
::= { icmp 1 }

icmpInErrors OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
::= { icmp 2 }

```



**icmpInDestUnreachs OBJECT-TYPE**

**SYNTAX** Counter  
**ACCESS** read-only  
**STATUS** mandatory  
**::=** { icmp 3 }

**icmpInTimeExcds OBJECT-TYPE**

**SYNTAX** Counter  
**ACCESS** read-only  
**STATUS** mandatory  
**::=** { icmp 4 }

**icmpInParmProbs OBJECT-TYPE**

**SYNTAX** Counter  
**ACCESS** read-only  
**STATUS** mandatory  
**::=** { icmp 5 }

**icmpInSrcQuenchs OBJECT-TYPE**

**SYNTAX** Counter  
**ACCESS** read-only  
**STATUS** mandatory  
**::=** { icmp 6 }

**icmpInRedirects OBJECT-TYPE**

**SYNTAX** Counter  
**ACCESS** read-only  
**STATUS** mandatory  
**::=** { icmp 7 }

**icmpInEchos OBJECT-TYPE**

**SYNTAX** Counter  
**ACCESS** read-only  
**STATUS** mandatory  
**::=** { icmp 8 }

**icmpInEchoReps OBJECT-TYPE**

**SYNTAX** Counter  
**ACCESS** read-only  
**STATUS** mandatory  
**::=** { icmp 9 }

**icmpInTimestamps OBJECT-TYPE**

**SYNTAX** Counter  
**ACCESS** read-only  
**STATUS** mandatory  
**::=** { icmp 10 }

icmpInTimestampReps OBJECT-TYPE  
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
::= { icmp 11 }

icmpInAddrMasks OBJECT-TYPE  
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
::= { icmp 12 }

icmpInAddrMaskReps OBJECT-TYPE  
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
::= { icmp 13 }

icmpOutMsgs OBJECT-TYPE  
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
::= { icmp 14 }

icmpOutErrors OBJECT-TYPE  
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
::= { icmp 15 }

icmpOutDestUnreachs OBJECT-TYPE  
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
::= { icmp 16 }

icmpOutTimeExcds OBJECT-TYPE  
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
::= { icmp 17 }

icmpOutParmProbs OBJECT-TYPE  
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
::= { icmp 18 }

icmpOutSrcQuenchs OBJECT-TYPE  
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
::= { icmp 19 }

icmpOutRedirects OBJECT-TYPE  
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
::= { icmp 20 }

icmpOutEchos OBJECT-TYPE  
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
::= { icmp 21 }

icmpOutEchoReps OBJECT-TYPE  
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
::= { icmp 22 }

icmpOutTimestamps OBJECT-TYPE  
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
::= { icmp 23 }

icmpOutTimestampReps OBJECT-TYPE  
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
::= { icmp 24 }

icmpOutAddrMasks OBJECT-TYPE  
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
::= { icmp 25 }

icmpOutAddrMaskReps OBJECT-TYPE  
SYNTAX Counter  
ACCESS read-only  
STATUS mandatory  
::= { icmp 26 }

-- the TCP group

```
tcpRtoAlgorithm OBJECT-TYPE
    SYNTAX  INTEGER {
        other(1),      -- none of the following
        constant(2),   -- a constant rto
        rsre(3),       -- MIL-STD-1778, Appendix B
        vanj(4)        -- Van Jacobson's algorithm [15]
    }
    ACCESS   read-only
    STATUS   mandatory
    ::= { tcp 1 }
```

```
tcpRtoMin OBJECT-TYPE
    SYNTAX  INTEGER
    ACCESS   read-only
    STATUS   mandatory
    ::= { tcp 2 }
```

```
tcpRtoMax OBJECT-TYPE
    SYNTAX  INTEGER
    ACCESS   read-only
    STATUS   mandatory
    ::= { tcp 3 }
```

```
tcpMaxConn OBJECT-TYPE
    SYNTAX  INTEGER
    ACCESS   read-only
    STATUS   mandatory
    ::= { tcp 4 }
```

```
tcpActiveOpens OBJECT-TYPE
    SYNTAX  Counter
    ACCESS   read-only
    STATUS   mandatory
    ::= { tcp 5 }
```

```
tcpPassiveOpens OBJECT-TYPE
    SYNTAX  Counter
    ACCESS   read-only
    STATUS   mandatory
    ::= { tcp 6 }
```

```
tcpAttemptFails OBJECT-TYPE
    SYNTAX  Counter
    ACCESS   read-only
    STATUS   mandatory
    ::= { tcp 7 }
```

```
tcpEstabResets OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    ::= { tcp 8 }

tcpCurrEstab OBJECT-TYPE
    SYNTAX Gauge
    ACCESS read-only
    STATUS mandatory
    ::= { tcp 9 }

tcpInSegs OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    ::= { tcp 10 }

tcpOutSegs OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    ::= { tcp 11 }

tcpRetransSegs OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    ::= { tcp 12 }

-- the TCP connections table

tcpConnTable OBJECT-TYPE
    SYNTAX SEQUENCE OF TcpConnEntry
    ACCESS read-only
    STATUS mandatory
    ::= { tcp 13 }

tcpConnEntry OBJECT-TYPE
    SYNTAX TcpConnEntry
    ACCESS read-only
    STATUS mandatory
    ::= { tcpConnTable 1 }

TcpConnEntry ::= SEQUENCE {
    tcpConnState
        INTEGER,
    tcpConnLocalAddress
```

```
        IpAddress,
        tcpConnLocalPort
            INTEGER (0..65535),
        tcpConnRemAddress
            IpAddress,
        tcpConnRemPort
            INTEGER (0..65535)
    }

tcpConnState OBJECT-TYPE
    SYNTAX  INTEGER {
        closed(1),
        listen(2),
        synSent(3),
        synReceived(4),
        established(5),
        finWait1(6),
        finWait2(7),
        closeWait(8),
        lastAck(9),
        closing(10),
        timeWait(11)
    }
    ACCESS  read-only
    STATUS  mandatory
    ::= { tcpConnEntry 1 }

tcpConnLocalAddress OBJECT-TYPE
    SYNTAX  IpAddress
    ACCESS  read-only
    STATUS  mandatory
    ::= { tcpConnEntry 2 }

tcpConnLocalPort OBJECT-TYPE
    SYNTAX  INTEGER (0..65535)
    ACCESS  read-only
    STATUS  mandatory
    ::= { tcpConnEntry 3 }

tcpConnRemAddress OBJECT-TYPE
    SYNTAX  IpAddress
    ACCESS  read-only
    STATUS  mandatory
    ::= { tcpConnEntry 4 }

tcpConnRemPort OBJECT-TYPE
    SYNTAX  INTEGER (0..65535)
    ACCESS  read-only
```

```
        STATUS mandatory
        ::= { tcpConnEntry 5 }

-- the UDP group

udpInDatagrams OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    ::= { udp 1 }

udpNoPorts OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    ::= { udp 2 }

udpInErrors OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    ::= { udp 3 }

udpOutDatagrams OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    ::= { udp 4 }

-- the EGP group

egpInMsgs OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    ::= { egp 1 }

egpInErrors OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    ::= { egp 2 }

egpOutMsgs OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    ::= { egp 3 }
```

```
egpOutErrors OBJECT-TYPE
    SYNTAX Counter
    ACCESS read-only
    STATUS mandatory
    ::= { egp 4 }

-- the EGP Neighbor table

egpNeighTable OBJECT-TYPE
    SYNTAX SEQUENCE OF EgpNeighEntry
    ACCESS read-only
    STATUS mandatory
    ::= { egp 5 }

egpNeighEntry OBJECT-TYPE
    SYNTAX EgpNeighEntry
    ACCESS read-only
    STATUS mandatory
    ::= { egpNeighTable 1 }

EgpNeighEntry ::= SEQUENCE {
    egpNeighState
        INTEGER,
    egpNeighAddr
        IpAddress
}

egpNeighState OBJECT-TYPE
    SYNTAX INTEGER {
        idle(1),
        acquisition(2),
        down(3),
        up(4),
        cease(5)
    }
    ACCESS read-only
    STATUS mandatory
    ::= { egpNeighEntry 1 }

egpNeighAddr OBJECT-TYPE
    SYNTAX IpAddress
    ACCESS read-only
    STATUS mandatory
    ::= { egpNeighEntry 2 }

END
```



## 7. Acknowledgements

The initial draft of this memo was heavily influenced by the the HEMS [9] and SNMP [10] MIBs.

Its final form is the result of the suggestions, the dicussions, and the compromises reached by the members of the IETF MIB working group:

Karl Auerbach, Epilogue Technology  
K. Ramesh Babu, Excelan  
Lawrence Besaw, Hewlett-Packard  
Jeffrey D. Case, University of Tennessee at Knoxville  
James R. Davin, Proteon  
Mark S. Fedor, NYSERNet  
Robb Foster, BBN  
Phill Gross, The MITRE Corporation  
Bent Torp Jensen, Convergent Technology  
Lee Labarre, The MITRE Corporation  
Dan Lynch, Advanced Computing Environments  
Keith McCloghrie, The Wollongong Group  
Dave Mackie, 3Com/Bridge  
Craig Partridge, BBN (chair)  
Jim Robertson, 3Com/Bridge  
Marshall T. Rose, The Wollongong Group  
Greg Satz, cisco  
Martin Lee Schoffstall, Rensselaer Polytechnic Institute  
Lou Steinberg, IBM  
Dean Throop, Data General  
Unni Warriier, Unisys

## 8. References

- [1] Cerf, V., "IAB Recommendations for the Development of Internet Network Management Standards", RFC 1052, IAB, April 1988.
- [2] Information processing systems - Open Systems Interconnection, "Management Information Services Definition", International Organization for Standardization, Draft Proposal 9595/2, December 1987.
- [3] Information processing systems - Open Systems Interconnection, "Management Information Protocol Specification", International Organization for Standardization, Draft Proposal 9596/2, December 1987.
- [4] Rose M., and K. McCloghrie, "Structure and Identification of Management Information for TCP/IP-based internets", RFC 1065, TWG, August 1988.
- [5] Partridge C., and G. Trewitt, "The High-Level Entity Management System (HEMS)", RFCs 1021-1024, BBN and Stanford, October 1987.
- [6] Cerf, V., "Report of the Second Ad Hoc Network Management Review Group", RFC 1109, IAB, August 1989.
- [7] Rose, M., and K. McCloghrie, "Structure and Identification of Management Information for TCP/IP-based Internets", RFC 1155, Performance Systems International and Hughes LAN Systems, May 1990.
- [8] Case, J., M. Fedor, M. Schoffstall, and J. Davin, "The Simple Network Management Protocol", RFC 1157, University of Tennessee at Knoxville, Performance Systems International, Performance Systems International, and the MIT Laboratory for Computer Science, May 1990.
- [9] Partridge C., and G. Trewitt, "HEMS Variable Definitions", RFC 1024, BBN and Stanford, October 1987.
- [10] Case, J., M. Fedor, M. Schoffstall, and J. Davin, "A Simple Network Management Protocol", RFC 1067, University of Tennessee At Knoxville, NYSERNet, Rensselaer Polytechnic, Proteon, August 1988.
- [11] LaBarre, L., "Structure and Identification of Management Information for the Internet", Internet Engineering Task Force working note, Network Information Center, SRI International, Menlo Park, California, April 1988.

- [12] LaBarre, L., "Transport Layer Management Information: TCP", Internet Engineering Task Force working note in preparation. Network Information Center, SRI International, Menlo Park, California, (unpublished).
- [13] Information processing systems - Open Systems Interconnection, "Specification of Abstract Syntax Notation One (ASN.1)", International Organization for Standardization, International Standard 8824, December 1987.
- [14] Information processing systems - Open Systems Interconnection, "Specification of Basic Encoding Rules for Abstract Notation One (ASN.1)", International Organization for Standardization, International Standard 8825, December 1987.
- [15] Jacobson, V., "Congestion Avoidance and Control", SIGCOMM, 1988, Stanford, California.

### Security Considerations

Security issues are not discussed in this memo.

### Authors' Addresses

Keith McCloghrie  
The Wollongong Group  
1129 San Antonio Road  
Palo Alto, CA 04303

Phone: (415) 962-7160

EMail: sytek!kzm@HPLABS.HP.COM

Marshall T. Rose  
PSI, Inc.  
PSI California Office  
P.O. Box 391776  
Mountain View, CA 94039

Phone: (415) 961-3380

EMail: mrose@PSI.COM