Fibre Channel Routing Information MIB

Status of This Memo

   This document specifies an Internet standards track protocol for the
   Internet community, and requests discussion and suggestions for
   improvements. Please refer to the current edition of the "Internet
   Official Protocol Standards" (STD 1) for the standardization state
   and status of this protocol. Distribution of this memo is unlimited.

Copyright Notice

Abstract

   This memo defines a portion of the Management Information Base (MIB)
   for use with network management protocols in the Internet community.
   In particular, it describes managed objects for information related
   to routing within a Fibre Channel fabric, which is independent of the
   usage of a particular routing protocol.

Table of Contents

1. Introduction

   This memo defines a portion of the Management Information Base (MIB)
   for use with network management protocols in the Internet community.
   In particular, it describes managed objects for information related
   to the Fibre Channel network's Routing Table for routing within a
   Fabric. Managed objects specific to particular routing protocols,
   such as the Fabric Shortest Path First (FSPF) protocol [FC-SW-4], are
   not specified in this MIB module.

   The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT",
   "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this
   document are to be interpreted as described in RFC 2119 [RFC2119].

2. The Internet-Standard Management Framework

   For a detailed overview of the documents that describe the current
   Internet-Standard Management Framework, please refer to section 7 of
   RFC 3410 [RFC3410].

   Managed objects are accessed via a virtual information store, termed
   the Management Information Base or MIB. MIB objects are generally
   accessed through the Simple Network Management Protocol (SNMP).
   Objects in the MIB are defined using the mechanisms defined in the
   Structure of Management Information (SMI). This memo specifies a MIB
   module that is compliant to the SMIv2, which is described in STD 58,
   RFC 2578 [RFC2578], STD 58, RFC 2579 [RFC2579] and STD 58, RFC 2580
   [RFC2580].

3. Short Overview of Fibre Channel

3.1. Introduction

   The Fibre Channel (FC) is logically a bidirectional point-to-point
   serial data channel, structured for high performance. Fibre Channel
   provides a general transport vehicle for higher-level protocols, such
   as Small Computer System Interface (SCSI) command sets, the High-
   Performance Parallel Interface (HIPPI) data framing, IP (Internet
   Protocol), IEEE 802.2, and others.

   Physically, Fibre Channel is an interconnection of multiple
   communication points, called N_Ports, interconnected either by a
   switching network, called a Fabric, or by a point-to-point link. A
   Fibre Channel "node" consists of one or more N_Ports. A Fabric may
   consist of multiple Interconnect Elements, some of which are
   switches. An N_Port connects to the Fabric via a port on a switch
   called an F_Port. When multiple FC nodes are connected to a single
   port on a switch via an "Arbitrated Loop" topology, the switch port

is called an FL_Port, and the nodes' ports are called NL_Ports. The
term Nx_Port is used to refer to either an N_Port or an NL_Port. The
term Fx_Port is used to refer to either an F_Port or an FL_Port. A
switch port, which is interconnected to another switch port via an
Inter-Switch Link (ISL), is called an E_Port. A B_Port connects a
bridge device with an E_Port on a switch; a B_Port provides a subset
of E_Port functionality.

Many Fibre Channel components, including the fabric, each node, and
most ports, have globally-unique names. These globally-unique names
are typically formatted as World Wide Names (WWNs). More information
on WWNs can be found in [FC-FS]. WWNs are expected to be persistent
across agent and unit resets.

Fibre Channel frames contain 24-bit address identifiers that identify
the frame's source and destination ports. Each FC port has both an
address identifier and a WWN. When a fabric is in use, the FC
address identifiers are dynamic and are assigned by a switch. Each
octet of a 24-bit address represents a level in an address hierarchy,
a Domain_ID being the highest level of the hierarchy.

3.2. Routing Protocols

The routing of frames within the Fabric is normally based on the
standard routing protocol, called the Fabric Shortest Path First
(FSPF) protocol. The operation of FSPF (or of any other routing
protocol) allows a switch to generate and maintain its own routing
table of how to forward frames it receives; i.e., a table in which to
look up the destination address of a received frame in order to
determine the best link by which to forward that frame towards its
destination.

3.3. Virtual Fabrics

The latest standard for an interconnecting Fabric containing multiple
Fabric Switch elements is [FC-SW-4] (which replaces the previous
revision, [FC-SW-3]). [FC-SW-4] carries forward the existing
specification for the operation of a single Fabric in a physical
infrastructure, augmenting it with the definition of Virtual Fabrics
and with the specification of how multiple Virtual Fabrics can
operate within one (or more) physical infrastructures. The use of
Virtual Fabrics provides for each frame to be tagged in its header to
indicate which one of several Virtual Fabrics that frame is being
transmitted on. All frames entering a particular "Core Switch"
[FC-SW-4] (i.e., a physical switch) on the same Virtual Fabric are
processed by the same "Virtual Switch" within that Core switch.

4. Relationship to Other MIBs

   The first standardized MIB for Fibre Channel [RFC2837] was focussed
   on Fibre Channel switches. It is being replaced by the more generic
   Fibre Channel Management MIB [FC-MGMT], which defines basic
   information for Fibre Channel hosts and switches, including
   extensions to the standard IF-MIB [RFC2863] for Fibre Channel
   interfaces.

   This MIB extends beyond [FC-MGMT] to cover the routing of traffic
   within a Fabric of a Fibre Channel network. The standard routing
   protocol for Fibre Channel is FSPF [FC-SW-4]. Another MIB [RFC4626]
   specifies management information specific to FSPF. This MIB contains
   routing information that is independent of FSPF (i.e., it would still
   apply even if a routing protocol other than FSPF were in use in the
   network).

   This MIB imports some common Textual Conventions from T11-TC-MIB,
   defined in [RFC4439].

5. MIB Overview

   This MIB module provides the means for monitoring the operation of,
   and configuring some parameters of, one or more instances of the FSPF
   protocol. (Note that there are no definitions in this MIB module of
   "managed actions" that can be invoked via SNMP.)

5.1. Fibre Channel Management Instance

   A Fibre Channel management instance is defined in [FC-MGMT] as a
   separable managed instance of Fibre Channel functionality. Fibre
   Channel functionality may be grouped into Fibre Channel management
   instances in whatever way is most convenient for the
   implementation(s). For example, one such grouping accommodates a
   single SNMP agent with multiple AgentX [RFC2741] sub-agents, each
   sub-agent implementing a different Fibre Channel management instance.

   The object, fcmInstanceIndex, is IMPORTed from the FC-MGMT-MIB
   [FC-MGMT] as the index value that uniquely identifies each Fibre
   Channel management instance within the same SNMP context ([RFC3411],
   Section 3.3.1).

5.2. Switch Index

   The FC-MGMT-MIB [FC-MGMT] defines the fcmSwitchTable as a table of
   information about Fibre Channel switches that are managed by Fibre
   Channel management instances. Each Fibre Channel management instance
   can manage one or more Fibre Channel switches. The Switch Index,
   fcmSwitchIndex, is IMPORTed from the FC-MGMT-MIB as the index value
   that uniquely identifies a Fibre Channel switch among those (one or
   more) managed by the same Fibre Channel management instance.

5.3. Fabric Index

   Whether operating on a physical Fabric (i.e., without Virtual
   Fabrics) or within a Virtual Fabric, the operation of FSPF within a
   Fabric is identical. Therefore, this MIB defines all Fabric-related
   information in tables that are INDEX-ed by an arbitrary integer,
   named a "Fabric Index", the syntax of which is IMPORTed from the
   T11-TC-MIB. When a device is connected to a single physical Fabric,
   without use of any virtual Fabrics, the value of this Fabric Index
   will always be 1. In an environment of multiple virtual and/or
   physical Fabrics, this index provides a means to distinguish one
   Fabric from another.

   It is quite possible, and may even be likely, that a Fibre Channel
   switch will have ports connected to multiple virtual and/or physical
   Fabrics. Thus, in order to simplify a management protocol query
   concerning all the Fabrics to which a single switch is connected,
   fcmSwitchIndex will be listed before t11FcRouteFabricIndex when they
   both appear in the same INDEX clause.

5.4. The t11FcRouteGroup Group

   This MIB contains one object group, the t11FcRouteGroup, which
   contains objects to allow the displaying and the configuring of
   routes in the Fibre Channel Routing tables for the locally managed
   switches.

5.5. The t11FcRouteTable's INDEX

   It is normally valuable for a MIB table that contains routes to be
   ordered such that a management application is able to query the table
   based on some attribute, without having to read every row in the MIB
   table. This requires that the rows in the table be ordered according
   to such attributes, and thus that those attributes be represented by
   objects included in the table's INDEX clause. Examples of this can
   be seen in the ipCidrRouteTable [RFC2096] and, more recently, the
   inetCidrRouteTable in [RFC4292].

While this useful feature results in an unusually large number (ten)
of objects in the t11FcRouteTable's INDEX clause, all ten are either
integers or strings of 3 (or zero) octet length, so the resulting
OIDs are not unusually large. (Specifically, the aggregate number of
sub-identifiers to be appended to an OBJECT-TYPE's OID, when naming
an instance of an object in the t11FcRouteTable, is at most 22 sub-
identifiers; i.e., less than the *minimum* number to be appended for
the inetCidrRouteTable table.)

6. The T11-FC-ROUTE-MIB Module

```
T11-FC-ROUTE-MIB DEFINITIONS ::= BEGIN

IMPORTS
    MODULE-IDENTITY, OBJECT-TYPE,
    Unsigned32, mib-2                     FROM SNMPv2-SMI  -- [RFC2578]
    MODULE-COMPLIANCE, OBJECT-GROUP    FROM SNMPv2-CONF -- [RFC2580]
    RowStatus, TimeStamp,
    StorageType                           FROM SNMPv2-TC   -- [RFC2579]
    InterfaceIndex, InterfaceIndexOrZero  FROM IF-MIB     -- [RFC2863]
    fcmInstanceIndex, fcmSwitchIndex,
    FcAddressIdOrZero, FcDomainIdOrZero FROM FC-MGMT-MIB -- [FC-MGMT]
    T11FabricIndex                        FROM T11-TC-MIB; -- [RFC4439]

t11FcRouteMIB MODULE-IDENTITY
    LAST-UPDATED "200608140000Z"
    ORGANIZATION "T11"
    CONTACT-INFO
                "        Claudio DeSanti
                 Cisco Systems, Inc.
                 170 West Tasman Drive
                 San Jose, CA 95134 USA
                 EMail: cds@cisco.com


                 Keith McCloghrie
                 Cisco Systems, Inc.
                 170 West Tasman Drive
                 San Jose, CA USA 95134
                 Email: kzm@cisco.com"
    DESCRIPTION
            "The MIB module for configuring and displaying Fibre
            Channel Route Information.

            Copyright (C) The Internet Society (2006).  This version
            of this MIB module is part of RFC 4625;  see the RFC
            itself for full legal notices."
    REVISION      "200608140000Z"
```

```
      DESCRIPTION
              "Initial version of this MIB module, published as RFC4625."

      ::= {mib-2 144 }

t11FcRouteNotifications OBJECT IDENTIFIER ::= { t11FcRouteMIB 0 }
t11FcRouteObjects       OBJECT IDENTIFIER ::= { t11FcRouteMIB 1 }
t11FcRouteConformance   OBJECT IDENTIFIER ::= { t11FcRouteMIB 2 }

--
-- Per-Fabric routing information
--
t11FcRouteFabricTable OBJECT-TYPE
    SYNTAX       SEQUENCE OF T11FcRouteFabricEntry
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
            "The table containing Fibre Channel Routing information
             that is specific to a Fabric."
    ::= { t11FcRouteObjects 1 }

t11FcRouteFabricEntry OBJECT-TYPE
    SYNTAX       T11FcRouteFabricEntry
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
            "Each entry contains routing information specific to a
             particular Fabric on a particular switch (identified by
             values of fcmInstanceIndex and fcmSwitchIndex)."
    INDEX       { fcmInstanceIndex, fcmSwitchIndex,
                   t11FcRouteFabricIndex }
    ::= { t11FcRouteFabricTable 1 }

T11FcRouteFabricEntry ::=
    SEQUENCE {
        t11FcRouteFabricIndex       T11FabricIndex,
        t11FcRouteFabricLastChange  TimeStamp
    }

t11FcRouteFabricIndex OBJECT-TYPE
    SYNTAX       T11FabricIndex
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
            "A unique index value that uniquely identifies a
             particular Fabric.

             In a Fabric conformant to FC-SW-3, only a single Fabric
```

can operate within a physical infrastructure, and thus
the value of this Fabric Index will always be 1.

In a Fabric conformant to FC-SW-4, multiple Virtual Fabrics
can operate within one (or more) physical infrastructures.
In such a case, index value is used to uniquely identify a
particular Fabric within a physical infrastructure."
    ::= { t11FcRouteFabricEntry 1 }

t11FcRouteFabricLastChange OBJECT-TYPE
    SYNTAX   TimeStamp
    MAX-ACCESS read-only
    STATUS   current
    DESCRIPTION
            "The value of sysUpTime at the most recent time when any
            corresponding row in the t11FcRouteTable was created,
            modified, or deleted. A corresponding row in the
            t11FcRouteTable is for the same management instance,
            the same switch, and same Fabric as the row in this table.

            If no change has occurred since the last restart of the
            management system, then the value of this object is 0."
    ::= { t11FcRouteFabricEntry 2 }

--
-- Fibre Channel Routing table
--
t11FcRouteTable OBJECT-TYPE
    SYNTAX   SEQUENCE OF T11FcRouteEntry
    MAX-ACCESS not-accessible
    STATUS   current
    DESCRIPTION
            "The Fibre Channel Routing tables for the
            locally managed switches. This table lists all the
            routes that are configured in and/or computed by any
            local switch for any Fabric.

            Such routes are used by a switch to forward frames (of user
            data) on a Fabric. The conceptual process is based on
            extracting the Destination Fibre Channel Address Identifier
            (D_ID) out of a received frame (of user data) and comparing
            it to each entry of this table that is applicable to the
            given switch and Fabric. Such comparison consists of first
            performing a logical-AND of the extracted D_ID with a mask
            (the value of t11FcRouteDestMask) and second comparing the
            result of that 'AND' operation to the value of
            t11FcRouteDestAddrId. A similar comparison is made of the
            Source Fibre Channel Address Identifier (S_ID) of a frame

                 against the t11FcRouteSrcAddrId and t11FcRouteSrcMask values
                 of an entry. If an entry's value of t11FcRouteInInterface
                 is non-zero, then a further comparison determines if the
                 frame was received on the appropriate interface. If all of
                 these comparisons for a particular entry are successful,
                 then that entry represents a potential route for forwarding
                 the received frame.

                 For entries configured by a user, t11FcRouteProto has
                 the value 'netmgmt'; only entries of this type can be
                 deleted by the user."
        ::= { t11FcRouteObjects 2 }

t11FcRouteEntry OBJECT-TYPE
    SYNTAX   T11FcRouteEntry
    MAX-ACCESS   not-accessible
    STATUS   current
    DESCRIPTION
            "Each entry contains a route to a particular destination,
             possibly from a particular subset of source addresses,
             on a particular Fabric via a particular output interface
             and learned in a particular manner."
    INDEX   { fcmInstanceIndex, fcmSwitchIndex,
                   t11FcRouteFabricIndex,
                   t11FcRouteDestAddrId, t11FcRouteDestMask,
                   t11FcRouteSrcAddrId, t11FcRouteSrcMask,
                   t11FcRouteInInterface, t11FcRouteProto,
                   t11FcRouteOutInterface }
    ::= { t11FcRouteTable 1 }
T11FcRouteEntry ::=
    SEQUENCE {
        t11FcRouteDestAddrId   FcAddressIdOrZero,
        t11FcRouteDestMask   FcAddressIdOrZero,
        t11FcRouteSrcAddrId   FcAddressIdOrZero,
        t11FcRouteSrcMask   FcAddressIdOrZero,
        t11FcRouteInInterface InterfaceIndexOrZero,
        t11FcRouteProto   INTEGER,
        t11FcRouteOutInterface InterfaceIndex,
        t11FcRouteDomainId   FcDomainIdOrZero,
        t11FcRouteMetric   Unsigned32,
        t11FcRouteType   INTEGER,
        t11FcRouteIfDown   INTEGER,
        t11FcRouteStorageType StorageType,
        t11FcRouteRowStatus   RowStatus
    }

t11FcRouteDestAddrId OBJECT-TYPE
    SYNTAX   FcAddressIdOrZero (SIZE (3))

```
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "The destination Fibre Channel Address Identifier of
             this route.  A zero-length string for this field is
             not allowed."
    ::= { t11FcRouteEntry 1 }


t11FcRouteDestMask OBJECT-TYPE
    SYNTAX      FcAddressIdOrZero
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "The mask to be logical-ANDed with a destination
             Fibre Channel Address Identifier before it is compared
             to the value in the t11FcRouteDestAddrId field.
             Allowed values are 255.255.255, 255.255.0, or 255.0.0.
             FSPF's definition generates routes to a Domain_ID,
             so the mask for all FSPF-generated routes is 255.0.0.
             The zero-length value has the same meaning as 0.0.0."
    ::= { t11FcRouteEntry 2 }


t11FcRouteSrcAddrId OBJECT-TYPE
    SYNTAX      FcAddressIdOrZero
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "The source Fibre Channel Address Identifier of this
             route.  Note that if this object and the corresponding
             instance of t11FcRouteSrcMask both have a value of 0.0.0,
             then this route matches all source addresses.  The
             zero-length value has the same meaning as 0.0.0."
    ::= { t11FcRouteEntry 3 }


t11FcRouteSrcMask OBJECT-TYPE
    SYNTAX      FcAddressIdOrZero
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "The mask to be logical-ANDed with a source
             Fibre Channel Address Identifier before it is compared
             to the value in the t11FcRouteSrcAddrId field.  Allowed
             values are 255.255.255, 255.255.0, 255.0.0, or 0.0.0.
             The zero-length value has the same meaning as 0.0.0."
    ::= { t11FcRouteEntry 4 }


t11FcRouteInInterface OBJECT-TYPE
    SYNTAX      InterfaceIndexOrZero
```

```
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "If the value of this object is non-zero, it is the
            value of ifIndex that identifies the local
            Fibre Channel interface through which a frame
            must have been received in order to match with
            this entry.  If the value of this object is zero,
            the matching does not require that the frame be
            received on any specific interface."
    ::= { t11FcRouteEntry 5 }

t11FcRouteProto OBJECT-TYPE
    SYNTAX    INTEGER {
                other(1),
                local(2),
                netmgmt(3),
                fspf(4)
             }
    MAX-ACCESS not-accessible
    STATUS    current
    DESCRIPTION
            "The mechanism via which this route was learned:
                other(1)  - not specified
                local(2)  - local interface
                netmgmt(3)- static route
                fspf(4)   - Fibre Shortest Path First
             "
    ::= { t11FcRouteEntry 6 }

t11FcRouteOutInterface OBJECT-TYPE
    SYNTAX      InterfaceIndex
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
            "The value of ifIndex that identifies the local
            Fibre Channel interface through which the next hop
            of this route is to be reached."
    ::= { t11FcRouteEntry 7 }

t11FcRouteDomainId OBJECT-TYPE
    SYNTAX      FcDomainIdOrZero
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
            "The domain_ID of next hop switch.

            This object can have a value of zero if the value
```

```
                of t11FcRouteProto is 'local'."
        ::= { t11FcRouteEntry 8 }


t11FcRouteMetric OBJECT-TYPE
        SYNTAX      Unsigned32 (0..65536)
        MAX-ACCESS  read-create
        STATUS      current
        DESCRIPTION
                "The routing metric for this route.

                The use of this object is dependent on t11FcRouteProto."
        ::= { t11FcRouteEntry 9 }


t11FcRouteType OBJECT-TYPE
        SYNTAX      INTEGER {
                        local(1),
                        remote(2)
                    }
        MAX-ACCESS  read-create
        STATUS      current
        DESCRIPTION
                "The type of route.

                local(1)  - a route for which the next Fibre Channel
                             port is the final destination;
                remote(2) - a route for which the next Fibre Channel
                             port is not the final destination."
        DEFVAL {local}
        ::= { t11FcRouteEntry 10 }


t11FcRouteIfDown OBJECT-TYPE
        SYNTAX      INTEGER {
                        remove(1),
                        retain(2)
                    }
        MAX-ACCESS  read-create
        STATUS      current
        DESCRIPTION
                "The value of this object indicates what happens to
                this route when the output interface (given by the
                corresponding value of t11FcRouteOutInterface) is
                operationally 'down'.  If this object's value is 'retain',
                the route is to be retained in this table.  If this
                object's value is 'remove', the route is to be removed
                from this table."
        DEFVAL  { retain }
        ::= { t11FcRouteEntry 11 }
```

```
t11FcRouteStorageType OBJECT-TYPE
    SYNTAX        StorageType
    MAX-ACCESS  read-create
    STATUS        current
    DESCRIPTION
            "The storage type for this conceptual row.
             Conceptual rows having the value 'permanent' need not
             allow write-access to any columnar objects in the row."
      DEFVAL { nonVolatile }
    ::= { t11FcRouteEntry 12 }

t11FcRouteRowStatus OBJECT-TYPE
    SYNTAX        RowStatus
    MAX-ACCESS  read-create
    STATUS        current
    DESCRIPTION
            "The status of this conceptual row.
             The only rows that can be deleted by setting this object to
             'destroy' are those for which t11FcRouteProto has the value
             'netmgmt'."
    ::= { t11FcRouteEntry 13 }

--
-- Conformance
--
t11FcRouteCompliances OBJECT IDENTIFIER
                        ::= { t11FcRouteConformance 1 }
t11FcRouteGroups      OBJECT IDENTIFIER
                        ::= { t11FcRouteConformance 2 }


t11FcRouteCompliance  MODULE-COMPLIANCE
    STATUS     current
    DESCRIPTION
            "The compliance statement for entities that
             implement the T11-FC-ROUTE-MIB.
--
-- Note: The next four OBJECT clauses are for auxiliary objects, and the
-- SMIv2 does not permit inclusion of objects that are not accessible
-- in an OBJECT clause (see Sections 3.1 & 5.4.3 in STD 58, RFC 2580).
-- Thus, these four clauses cannot be included below in the normal
-- location for OBJECT clauses.
--
--      OBJECT      t11FcRouteSrcAddrId
--      SYNTAX      FcAddressIdOrZero (SIZE (0))
--      DESCRIPTION
--              'Support is not required for routes that
--               match only a subset of possible source
```

```
--              addresses.'
--
--      OBJECT      t11FcRouteSrcMask
--      SYNTAX      FcAddressIdOrZero (SIZE (0))
--      DESCRIPTION
--              'Support is not required for routes that
--              match only a subset of possible source
--              addresses.'
--
--      OBJECT      t11FcRouteDestMask
--      DESCRIPTION
--              'Support is mandatory only for FSPF-generated
--              routes.  Since FSPF's definition generates
--              routes to a Domain_ID, the mask for all
--              FSPF-generated routes is 255.0.0.  Thus,
--              support is only required for 255.0.0.'
--
--      OBJECT      t11FcRouteInInterface
--      SYNTAX      InterfaceIndexOrZero (0)
--      DESCRIPTION
--              'Support for routes specific to particular
--              source interfaces is not required.'
--          "

    MODULE  -- this module
        MANDATORY-GROUPS { t11FcRouteGroup }

        OBJECT      t11FcRouteIfDown
        MIN-ACCESS read-only
        DESCRIPTION
                "Write access is not required."

        OBJECT      t11FcRouteDomainId
        MIN-ACCESS read-only
        DESCRIPTION
                "Write access is not required."

        OBJECT      t11FcRouteMetric
        MIN-ACCESS read-only
        DESCRIPTION
                "Write access is not required."

        OBJECT      t11FcRouteType
        MIN-ACCESS read-only
        DESCRIPTION
                "Write access is not required."

        OBJECT      t11FcRouteStorageType
```

```
        MIN-ACCESS read-only
        DESCRIPTION
              "Write access is not required."

        OBJECT      t11FcRouteRowStatus
        SYNTAX      INTEGER { active(1) }
        MIN-ACCESS read-only
        DESCRIPTION
              "Write access is not required."

    ::= { t11FcRouteCompliances 1 }
t11FcRouteGroup  OBJECT-GROUP
    OBJECTS  { t11FcRouteFabricLastChange,
               t11FcRouteDomainId,
               t11FcRouteMetric,
               t11FcRouteType,
               t11FcRouteIfDown,
               t11FcRouteStorageType,
               t11FcRouteRowStatus
             }
    STATUS    current
    DESCRIPTION
            "A collection of objects for displaying and configuring
             routes."
    ::= { t11FcRouteGroups 1 }

END
```

7. Acknowledgements

    This document was originally developed and approved by the INCITS
    Task Group T11.5 (http://www.t11.org) as the SM-RTM project. We wish
    to acknowledge the contributions and comments from the INCITS
    Technical Committee T11, including the following:

        T11 Chair: Robert Snively, Brocade
        T11 Vice Chair: Claudio DeSanti, Cisco Systems
        T11.5 Chair: Roger Cummings, Symantec
        T11.5 members, especially:
            Ken Hirata, Emulex
            Scott Kipp, McData
            Elizabeth G. Rodriguez, Dot Hill

    The document was subsequently approved by the IETF's IMSS Working
    Group, chaired by David Black (EMC Corporation). We also wish to
    acknowledge Bert Wijnen (Lucent Technologies), the IETF Area
    Director, for his review of the document.

8. IANA Considerations

    The IANA has assigned a MIB OID for the T11-FC-ROUTE-MIB module under
    the appropriate subtree.

9. Security Considerations

    There are several management objects defined in this MIB module with
    a MAX-ACCESS clause of read-write and/or read-create. Such objects
    may be considered sensitive or vulnerable in some network
    environments. The support for SET operations in a non-secure
    environment without proper protection can have a negative effect on
    network operations. These objects and their
    sensitivity/vulnerability are:

        t11FcRouteDomainId, t11FcRouteMetric, t11FcRouteType,
        t11FcRouteIfDown, t11FcRouteRowStatus
            -- configure new routes and/or modify existing routes.

    Such objects may be considered sensitive or vulnerable in some
    network environments. For example, the ability to change network
    topology or network speed may afford an attacker the ability to
    obtain better performance at the expense of other network users. The
    support for SET operations in a non-secure environment without proper
    protection can have a negative effect on network operations.

Some of the readable objects in this MIB module (i.e., objects with a
MAX-ACCESS other than not-accessible) may be considered sensitive or
vulnerable in some network environments. It is thus important to
control even GET and/or NOTIFY access to these objects and possibly
to even encrypt the values of these objects when sending them over
the network via SNMP. The objects and their
sensitivity/vulnerability are: the write-able objects listed above
plus one other:

        t11FcRouteLastChangeTime
            -- the time of the last routing table change.

SNMP versions prior to SNMPv3 did not include adequate security.
Even if the network itself is secure (for example by using IPSec),
even then, there is no control as to who on the secure network is
allowed to access and GET/SET (read/change/create/delete) the objects
in this MIB module.

It is RECOMMENDED that implementors consider the security features as
provided by the SNMPv3 framework (see [RFC3410], section 8),
including full support for the SNMPv3 cryptographic mechanisms (for
authentication and privacy).

Further, deployment of SNMP versions prior to SNMPv3 is NOT
RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to
enable cryptographic security. It is then a customer/operator
responsibility to ensure that the SNMP entity giving access to an
instance of this MIB module is properly configured to give access to
the objects only to those principals (users) that have legitimate
rights to indeed GET or SET (change/create/delete) them.

10. Normative References

[RFC2119]   Bradner, S., "Key words for use in RFCs to Indicate
               Requirement Levels", BCP 14, RFC 2119, March 1997.

[RFC2578]   McCloghrie, K., Perkins, D., Schoenwaelder, J., Case,
               J., Rose, M., and S. Waldbusser, "Structure of
               Management Information Version 2 (SMIv2)", STD 58, RFC
               2578, April 1999.

[RFC2579]   McCloghrie, K., Perkins, D., Schoenwaelder, J., Case,
               J., Rose, M., and S. Waldbusser, "Textual Conventions
               for SMIv2", STD 58, RFC 2579, April 1999.

[RFC2580]   McCloghrie, K., Perkins, D., Schoenwaelder, J., Case,
               J., Rose, M., and S. Waldbusser, "Conformance
               Statements for SMIv2", STD 58, RFC 2580, April 1999.

[RFC2863]   McCloghrie, K. and F. Kastenholz, "The Interfaces Group
               MIB", RFC 2863, June 2000.

[RFC3411]   Harrington, D., Presuhn, R., and B. Wijnen, "An
               Architecture for Describing Simple Network Management
               Protocol (SNMP) Management Frameworks", STD 62, RFC
               3411, December 2002.

[RFC4439]   DeSanti, C., Gaonkar, V., McCloghrie, K., and S. Gai,
               "Fibre Channel Fabric Address Manager MIB", RFC 4439,
               March 2006.

[RFC4626]   DeSanti, C., Gaonkar, V., McCloghrie, K., and S. Gai,
               "MIB for Fibre Channel's Fabric Shortest Path First
               (FSPF) Protocol", RFC 4626, September 2006.

[FC-FS]   "Fibre Channel - Framing and Signaling (FC-FS)", ANSI
               INCITS 373-2003, April 2003.

[FC-SW-3]   "Fibre Channel - Switch Fabric - 3 (FC-SW-3)", ANSI
               INCITS 384-2004, 2004.

[FC-SW-4]   "Fibre Channel - Switch Fabric - 4 (FC-SW-4)", ANSI
               INCITS 418-2006, 2006.

[FC-MGMT]   McCloghrie, K., "Fibre Channel Management MIB", RFC
               4044, May 2005.

11. Informative References

[RFC2096]   Baker, F., "IP Forwarding Table MIB", RFC 2096, January
               1997.

[RFC2741]   Daniele, M., Wijnen, B., Ellison, M., and D. Francisco,
               "Agent Extensibility (AgentX) Protocol Version 1", RFC
               2741, January 2000.

[RFC2837]   Teow, K., "Definitions of Managed Objects for the
               Fabric Element in Fibre Channel Standard", RFC 2837,
               May 2000.

[RFC3410]   Case, J., Mundy, R., Partain, D., and B. Stewart,
               "Introduction and Applicability Statements for
               Internet-Standard Management Framework", RFC 3410,
               December 2002.

[RFC4292]   Haberman, B., "IP Forwarding Table MIB", RFC 4292,
               April 2006.

Authors' Addresses

   Claudio DeSanti
   Cisco Systems, Inc.
   170 West Tasman Drive
   San Jose, CA 95134 USA

   Phone: +1 408 853-9172
   EMail: cds@cisco.com

   Srini Kode
   Consultant

   Phone: 408-348-5343
   EMail: srinikode@yahoo.com

   Keith McCloghrie
   Cisco Systems, Inc.
   170 West Tasman Drive
   San Jose, CA USA 95134

   Phone: +1 408-526-5260
   EMail: kzm@cisco.com

   Silvano Gai
   Retired

Full Copyright Statement

Intellectual Property

Acknowledgement