Mean Round-Trip Times in the ARPANET

In one of our current measurement projects we are interested in the
average values of important network parameters. For this purpose we
collect data on the network activity over seven consecutive days. This
data collection is only interrupted by down-time or maintenance of
either the net or our collecting facility (the "late" Sigma-7 or, in
future, the 360/91 at CCN).

The insight gained from the analysis of this data has been reported in
Network Measurement Group Note 18 (NIC 20793):

    L. Kleinrock and W. Naylor
    "On Measured Behavior of the ARPA Network"

This paper will be presented at the NCC '74 in Chicago.

In this RFC we want to report the mean round-trip times (or delays) that
were observed during these week-long measurements since we think these
figures are of general interest to the ARPA community. Let us first
define the term "round trip time" as it is used by the statistics
gathering program in the IMPs. When a message is sent from a source
HOST to a destination HOST, the following events, among others, can be
distinguished ($T(i)$ is the time of event i):

  $T(1)$: The message is passed from the user program to the NCP in the
          source HOST

  $T(2)$: The proper entry is made in the pending packet table (PPT) for
          single packet messages or the pending leader table (PLT) for
          multiple packet messages after the first packet is received by
          the source IMP

  $T(3)$: The first packet of the message is put on the proper output
          queue in the source IMP (at this time the input of the second
          packet is initiated)

  $T(4)$: The message is put on the HOST-output queue in the destination
          IMP (at this time the reassembly of the message is complete)

  $T(5)$: The RFNM is sent from the destination IMP to the source IMP

   T(6): The RFNM arrives at the source IMP

   T(7): The RFNM is accepted by the source HOST

The time intervals T(i)-T(i-1) are mainly due to the following delays
and waiting times:

   T(2)-T(1): -HOST processing delay
              -HOST-IMP transmission delay for the 32-bit leader
              -Waiting time for a message number to become free (only
               four messages can simultaneously be transmitted between
               any pair of source IMP - destination IMP)
              -Waiting time for a buffer to become free (there must be
               more than three buffers on the "free buffer list")
              -HOST-IMP transmission delay for the first packet
              -Waiting time for an entry in the PPT or PLT to become
               available (there are eight entries in the PPT and twelve
               in the PLT table)

   T(3)-T(2): -Waiting time for a store-and-forward (S/F) buffer to
               become free (the maximum number of S/F-buffers is 20).
              -Waiting time for a logical ACK-channel to become free
               (there are 8 logical ACK-channels for each physical
               channel).
              -For multiple packet messages, waiting time until the
               ALLOCATE is received (unless an allocation from a previous
               multiple-packet message still exists; such an allocation
               is returned in the RFNM and expires after 125 msec)

   T(4)-T(3): -Queuing delay, transmission delay, and propagation delay
               in all the IMPs and lines in the path from source IMP to
               destination IMP
              -Possibly retransmission delay due to transmission errors
               or lack of buffer space (for multiple packet messages the
               delays for the individual packets overlap)

   T(5)-T(4): -Queuing delay in the destination IMP
              -IMP-HOST transmission delay for the first packet
              -For multiple-packet messages, waiting time for reassembly
               buffers to become free to piggy-back an ALLOCATE on the
               RFNM (if this waiting time exceeds one second then the
               RFNM is sent without the ALLOCATE)

   T(6)-T(5): -Queuing delay, transmission delay, and propagation delay
               for the RFNM in all the IMPs and lines in the path from
               destination IMP to source IMP

   T(7)-T(6): -Queuing delay for the RFNM in the source IMP
              -IMP-HOST transmission delay for the RFNM

IMP processing delays are not included in this table since they are
usually very small. Also, some of the abovementioned waiting times
reduce to zero in many cases, e.g. the waiting time for a message number
to become available and the waiting time for a buffer to become free.

If the source and destination HOSTs are attached to the same IMP, this
table can be simplified as follows:

   T(2)-T(1): as before
   T(3)-T(2): for multiple packet messages: waiting time until
               reassembly space becomes available (there are up to 66
               reassembly buffers)
   T(4)-T(3): for multiple packet messages: HOST-IMP transmission delay
               for packets 2,3,...
   T(5)-T(4): as before
   T(6)-T(5): 0
   T(7)-T(6): as before

Up to now we have neglected the possibility that a single packet message
is rejected at the destination IMP because of lack of reassembly space.
If this occurs, the single packet message is treated as a request for
buffer space allocation and the time interval T(3)-T(2) increased by the
waiting time until the corresponding "ALLOCATE" is received.

The round trip time (RTT) is now defined as the time interval T(6)-T(2).
Note that the RTT for multiple packet messages does include the waiting
time until the ALLOCATE is received. It does, however, not include the
source HOST processing delay (i.e. delays in the NCP), the HOST-IMP
transmission delay, and the waiting time until a message number becomes
available. Note also, that the RFNM is sent after the first packet of a
multiple packet message has been received by the destination HOST.

Let us now turn to the presentation of the average round trip times as
they were measured during continuous seven-day periods in August and
December '73. In August, an average number of 2935 messages/minute were
entering the ARPANET. The overall mean round trip delay for all these
messages was 93 milliseconds (msec). The corresponding numbers for
December were 2226 messages/minute and 200 msec. An obvious question
that immediately arises is: why did the average round trip delay more
than double while the rate of incoming messages decreased? The answer
to this question can be found in the large round trip delays for the
status reports that are sent from each IMP to the NCC. Each IMP sends,
on the average, 2.29 status reports per minute to the NCC. Since there

were 45 sites connected to the net in December, a total of 103.05 status
reports per minute were sent to the NCC. Thus 4.63 percent of all
messages that entered the net were status reports.

The average round trip delay for all these status reports in December
was 1.66 sec. This number is five to ten times larger than the average
round-trip delay for status reports we observed in August. It is not
yet clear what change in the collection of status reports caused this
increase. One reason appears to be that the number of these reports was
doubled between August and December. Since the large round-trip delays
of these status reports distort the overall picture somewhat, we are
going to present the December data - wherever appropriate - with and
without the effect of these delays. (We should point out here that the
traffic/delay picture is distorted by the accumulated statistics
messages which were collected to produce this data. We have, however,
ignored this effect since these measurement messages represent less than
0.3% of the total traffic.) The overall mean round trip delay without
the status reports in December is 132 msec. This value is still more
than 35 msec larger than the corresponding value for August. However,
before we shall attempt to explain this difference we will first present
the measured data.

Table 1 shows the mean round trip delay as a function of the number of
hops over the minimum-hop path. This minimum number of hops was
calculated from the (static) topology of the net as it existed in August
and December of last year. The actual number of hops over which any
given message travels may, of course, be larger due to network
congestion, line failures or IMP failures. In fact, for August we
observed a minimum mean path length of 3.24 while the actual measured
mean path length was 3.30; in December we observed 4.02 and 4.40,
respectively. (See Network Measurement Group Note #18 for an
explanation of the computation of actual mean path length.) As expected
we observe a sharp increase of the mean round trip delay as the minimum
number of hops is increased. Note, however, that the mean round trip
delay is not a strictly increasing function of the minimum number of
hops.

Table 2 gives the mean round trip delay for messages from a given site.
The December data is presented with and without the large delays
incurred by the sending of status reports to the NCC. Table 3 shows the
mean round trip delay for messages to a given site. The largest round
trip delays, in December, were incurred by messages sent to the NCC-TIP
since these messages include all the status reports.

Table 4, finally, gives for each site the mean round trip delays to
those three destination IMP/TIP's to which the most messages were sent
during the seven-day measurement period in December. Let us first say
few words about the traffic distribution which is dealt with in more

detail in Network Measurement Group Note #18. There are several sites
which like to use their IMP as a kind of local multiplexer (UTAH, MIT,
HARV, CMU, USCT, CCAT, XROX, HAWT, MIT2). For these sites the most
favorite destination site is the source IMP itself. For several other
sites the most favorite destination site is just one hop away (BBN,
AMES, AMST, NCCT, RUTT). Nobody will be surprised that for many sites
ISI (ILL, MTRT, ETAT, SDAT, ARPT, RMLT, LONT) or SRI (UCSB, RADT, NBST)
is the most favorite site. There are several other sites (SDC, LL,
CASE, DOCT, BELV, ABRD, FNWT, LBL, NSAT, TYMT, MOFF, WPAT) which were
rather inactive in terms of generating traffic during the seven-day
measurement period in December. Most of their messages were status
reports sent to the NCC. (Those IMPs, for which the frequency of
messages to the NCC-TIP is less than 2.2 messages per minute, were down
for some time during the measurement period).

Let us now attempt to give a few explanations for the overall increase
in the mean round trip delay between August and December. These
explanations may also help to understand the differences in the mean
round trip delays for any given source IMP-destination IMP pair as
observed in Table 4.

1. Frequency of routing messages. Routing messages are the major
    source of queuing delay in a very lightly loaded net. In August, a
    routing message was sent every 640 msec. Since a routing message is
    1160 bits long, 3.625 percent of the bandwidth of a 50 kbs circuit
    was used for the sending of routing messages. For randomly arriving
    packets this corresponds to a mean queuing delay of 0.42 msec per
    hop. Between August and December the frequency of sending routing
    messages was made dependent on line speed and line utilization. As
    a result, routing messages are now sent on a 50 kbs circuit with
    zero load every 128 msec. This corresponds to a line utilization of
    18.125 percent and a mean queuing delay of 2.10 msec. The queuing
    delay due to routing messages in a very lightly loaded net in
    December was therefore five times as large as it was in August.

2. Traffic matrix. The overall mean round trip delay depends on the
    traffic matrix. If most of the messages are sent over distances of
    0 or 1 hop the overall round trip delay will be small. The heavy
    traffic between AMES and AMST over a high-speed circuit in August
    contributed to the small overall mean round trip delay.

3. Network topology. The mean round trip delay depends on the number
    of hops between source-IMP and destination-IMP and therefore on the
    network topology. Disregarding line or IMP failures, the mean
    number of hops for a message in August and December was,
    respectively, 3.24 and 4.02.

4. Averaging. The network load, given in number or messages per
    minute, represents an average over a seven-day period. Even though
    this number may be small, considerable queuing delays could have
    been incurred during bursts of traffic.

5. Host delays. The round trip delay includes the transmission delay
    of the first packet from the destination-IMP to the destination-
    HOST; therefore, the mean round trip delay may be influenced by HOST
    delays that are independent of the network load.

Table 1 Mean Round Trip Delay as a Function of the Number of Hops

HOPS	#MESSAGES/MINUTE		#SITE PAIRS		MEAN ROUND TRIP DELAY		
	AUG	DEC	AUG	DEC	AUG	DEC WITH STAT RPTS	DEC W/OUT STAT RPTS
0	646.9	378.3	39	45	27	44	41
1	487.6	288.7	86	100	25	65	50
2	191.0	143.1	118	138	70	119	80
3	380.7	226.9	148	168	95	131	112
4	218.5	274.1	176	196	102	167	119
5	276.3	185.6	204	228	109	217	134
6	183.8	136.3	210	258	175	355	167
7	333.6	212.7	218	256	178	301	240
8	156.7	161.1	160	234	222	365	241
9	59.0	160.3	102	208	270	308	218
10	0.6	29.9	40	124	331	939	410
11	1.0	18.9	20	46	344	998	699
12	-	10.2	-	20	-	992	655
13	-	0.01	-	4	-	809	809

Table 2 Mean Round Trip Delays for Messages from a Given Site

	SITE	#MESSAGES/MINUTE		MEAN ROUND TRIP DELAY		
		AUGUST	DECEMBER	AUGUST	DECEMBER WITH STATUS REPORTS	DECEMBER WITHOUT STATUS REPORTS
1	UCLA	50.7	40.3	130	282	165
2	SRI	377.3	147.9	45	189	174
3	UCSB	80.2	70.3	120	221	161
4	UTAH	27.0	46.2	136	247	169
5	BBN	120.4	128.3	110	133	133
6	MIT	120.6	96.9	126	160	150
7	RAND	29.3	34.2	127	323	208
8	SDC	1.7	2.4	521	2068	131
9	HARV	50.3	96.0	105	88	72
10	LL	4.4	6.7	201	602	187
11	STAN	49.7	39.7	173	300	191
12	ILL	26.8	53.4	158	216	165
13	CASE	57.6	2.5	138	1592	335
14	CMU	61.1	59.5	153	220	170
15	AMES	242.4	114.1	43	120	81
16	AMST	304.0	163.0	39	94	67
17	MTRT	89.5	60.0	126	199	142
18	RADT	27.7	29.1	145	273	160
19	NBST	98.4	48.2	118	213	152
20	ETAT	24.1	20.6	119	280	119
21	LLL	–	6.8	–	721	169
22	ISI	372.0	304.4	110	147	142
23	USCT	298.1	210.3	60	92	70
24	GWCT	10.5	14.1	144	381	102
25	DOCT	5.5	7.0	236	791	171
26	SDAT	14.7	22.9	164	322	177
27	BELV	1.3	2.4	243	1469	466
28	ARPT	57.9	64.3	84	150	93
29	ABRD	1.3	2.4	183	1402	554
30	BBNT	40.8	10.0	75	372	124
31	CCAT	177.7	86.7	83	147	115
32	XROX	56.8	71.7	79	136	78
33	FNWT	2.3	3.5	347	1466	174
34	LBL	1.2	2.7	384	1653	621
35	UCSD	11.9	19.3	237	413	205
36	HAWT	27.5	5.2	654	569	476
37	RMLT	10.4	13.0	122	387	97
40	NCCT	–	59.3	–	110	97
41	NSAT	0.6	3.4	1022	1870	1056
42	LONT	–	20.8	–	998	848
43	TYMT	–	3.7	–	1352	157

```
44  MIT2       -        5.6        -        720    100
45  MOFF       -        2.4        -       1982    447
46  RUTT       -       22.4        -        271    153
47  WPAT       -        2.7        -       1399    380
```

Table 3 Mean Round Trip Delay for Messages to a Given Site

	SITE	#MESSAGES/MINUTE		MEAN ROUND TRIP DELAY	
		AUGUST	DECEMBER	AUGUST	DECEMBER
1	UCLA	57.1	43.5	134	209
2	SRI	382.3	149.4	45	158
3	UCSB	61.1	59.1	117	138
4	UTAH	28.1	50.4	128	159
5	BBN	160.8	149.2	185	110
6	MIT	150.4	107.1	116	130
7	RAND	22.6	25.0	95	161
8	SDC	1.7	0.8	149	174
9	HARV	59.3	98.3	101	70
10	LL	4.6	5.2	195	202
11	STAN	65.3	40.6	135	162
12	ILL	29.1	69.8	156	149
13	CASE	52.6	4.0	127	262
14	CMU	74.8	68.9	135	165
15	AMES	210.3	117.2	40	75
16	AMST	316.7	135.0	38	86
17	MTRT	77.7	51.7	130	151
18	RADT	23.4	23.9	142	202
19	NBST	92.2	39.5	125	169
20	ETAT	25.4	22.8	110	111
21	LLL	-	3.7	-	185
22	ISI	361.9	299.2	107	130
23	USCT	298.1	190.6	60	68
24	GWCT	10.5	7.3	144	122
25	DOCT	5.5	4.2	236	187
26	SDAT	13.3	19.7	149	177
27	BELV	0.9	0.9	196	285
28	ARPT	55.4	58.3	78	95
29	ABRD	1.3	0.7	183	271
30	BBNT	40.8	6.4	75	159
31	CCAT	177.7	76.3	83	119
32	XROX	56.8	75.3	79	69
33	FNWT	2.3	1.4	347	165
34	LBL	1.2	0.9	384	305
35	UCSD	11.9	24.0	237	157
36	HAWT	27.5	5.0	654	458
37	RMLT	10.4	11.0	122	97
40	NCCT	-	140.1	-	1263
41	NSAT	0.6	1.6	1022	918
42	LONT	-	17.3	-	855
43	TYMT	-	1.6	-	160
44	MIT2	-	3.9	-	83
45	MOFF	-	0.2	-	219
46	RUTT	-	14.7	-	153
47	WPAT	-	0.5	-	282

Table 4 Mean Round Trip Delay to the Three Most Favorite Sites

FROM SITE	TO SITE	#MESSAGES/MINUTE		MEAN ROUND TRIP DELAY	
		AUGUST	DECEMBER	AUGUST	DECEMBER
1 UCLA	1 RAND	10.8	9.4	57	92
	26 SDAT	5.6	5.9	157	191
	22 ISI	3.1	3.1	99	146
2 SRI	12 RADT	16.6	19.5	142	163
	17 MTRT	21.9	18.7	140	161
	2 SRI	266.1	17.5	14	69
3 UCSB	2 SRI	8.1	17.8	72	68
	22 ISI	18.1	17.0	75	86
	14 CMU	16.6	11.8	140	152
4 UTAH	4 UTAH	3.5	13.5	136	27
	22 ISI	3.7	4.8	131	165
	5 BBN	4.2	4.1	168	204
5 BBN	40 NCCT	-	81.4	-	105
	5 BBN	12.5	19.7	102	37
	9 HARV	0.5	9.2	22	37
6 MIT	6 MIT	40.6	24.0	81	85
	23 USCT	9.8	13.9	150	173
	9 HARV	1.7	12.0	63	88
7 RAND	1 UCLA	12.5	10.4	54	96
	16 AMST	0.8	2.6	99	190
	40 NCCT	-	2.5	-	1941
8 SDC	40 NCCT	-	2.2	-	2217
	1 UCLA	0.2	0.2	110	136
	8 SDC	0.01	0.01	93	13
9 HARV	9 HARV	7.6	50.5	49	21
	2 MIT	1.6	11.9	62	85
	5 BBN	1.6	9.5	56	37
10 LL	40 NCCT	-	2.2	-	1420
	10 LL	1.5	1.8	238	135
	24 GWCT	0.04	0.6	146	80
11 STAN	14 CMU	3.0	7.0	215	207
	4 UTAH	0.2	5.5	117	117
	6 MIT	6.5	5.0	186	225

```
12 ILL          22 ISI    13.3     20.3     146      142
                15 AMES    0.8     14.6     109      135
                35 UCSD    6.7      6.5     192      269

13 CASE         40 NCCT    -        2.2      -      1744
                 1 UCLA    0.2      0.2     296      400
                 2 SRI     7.1      0.01    163      316

14 CMU          14 CMU    13.8     23.4     129       94
                 3 UCSB   13.8      9.2     153      166
                11 STAN    3.2      5.1     193      209

15 AMES         16 AMST   205.0    65.8      15       34
                12 ILL     1.2     19.6     115      120
                31 CCAT    3.2      4.6     174      230

16 AMST         15 AMES   176.8    74.3      13       28
                22 ISI    63.6     33.2      50       69
                32 XROX   13.3     17.4      41       60

17 MTRT         22 ISI    26.3     27.5     115      118
                 2 SRI    23.8     20.3     137      155
                 5 BBN     3.5      4.2     179      133

18 RADT          2 SRI    17.7     21.7     139      156
                 1 UCLA    0.4      2.3     265      181
                40 NCCT    -        2.3      -      1618

19 NBST          2 SRI    14.1     12.1     132      163
                22 ISI    29.6     11.8     100      117
                 5 BBN    21.6      9.6      71       97

20 ETAT         22 ISI    11.9     11.3     106      107
                24 GWCT    5.0      5.9      99      107
                40 NCCT    -        2.2      -      1602

21 LLL           5 BBN     -        2.9      -       183
                40 NCCT    -        2.2      -      1847
                 4 UTAH    -        0.5      -        71

22 ISI          28 ARPT   26.0     38.3     106      104
                23 USCT   69.0     32.7      80       92
                16 AMST   62.0     28.5      53       87

23 USCT         23 USCT   160.9    119.2     19       23
                22 ISI    69.2     34.1      78       91
                 6 MIT    12.9     19.6     135      150
```

24 GWCT	20 ETAT	6.6	10.8	93	91
	40 NCCT	-	2.1	-	1978
	10 LL	0.03	0.5	359	115

25 DOCT	40 NCCT	-	2.3	-	2091
	22 ISI	1.0	1.6	220	118
	15 AMES	1.9	1.2	167	198

26 SDAT	22 ISI	2.9	8.7	154	138
	1 UCLA	5.9	6.0	169	209
	2 SRI	1.0	4.4	182	184

27 BELV	40 NCCT	-	2.2	-	1553
	1 UCLA	0.1	0.2	405	517
	22 ISI	-	0.01	-	325

28 ARPT	22 ISI	27.4	41.6	106	101
	28 ARPT	19.2	13.7	20	35
	2 SRI	3.3	3.3	139	157

29 ABRD	40 NCCT	-	2.2	-	1461
	1 UCLA	0.2	0.2	439	562
	9 HARV	-	0.01	-	112

30 BBNT	5 BBN	24.2	5.1	36	64
	40 NCCT	-	2.1	-	1327
	22 ISI	4.2	1.1	170	217

31 CCAT	31 CCAT	81.9	28.2	15	31
	22 ISI	31.3	23.3	156	171
	5 BBN	7.8	7.3	45	42

32 XROX	32 XROX	20.2	36.4	19	15
	16 AMST	10.5	13.3	69	93
	14 CMU	2.5	3.0	193	251

33 FNWT	40 NCCT	-	2.2	-	2210
	9 HARV	0.01	0.3	208	194
	7 RAND	0.3	0.3	96	171

34 LBL	40 NCCT	-	2.4	-	1814
	41 NSAT	-	0.2	-	1674
	1 UCLA	0.1	0.2	295	478

35 UCSD	12 ILL	6.0	7.5	220	260
	16 AMST	1.7	4.9	120	172
	40 NCCT	-	2.0	-	2183

```
36 HAWT      36 HAWT    0.04      1.6      17       26
             22 ISI     5.1       1.0     600      623
             15 AMES    2.5       0.8     551      590

37 RMLT      22 ISI     7.5       9.0      68       67
             40 NCCT    -         2.2       -     1918
             28 ARPT    -         1.0       -       63

40 NCCT       5 BBN     -        41.2       -       33
             40 NCCT    -         6.6       -      433
             22 ISI     -         3.2       -      151

41 NSAT      40 NCCT    -         2.2       -     2308
              2 SRI     0.01      0.4     1046     1002
              3 UCSB    0.01      0.2     1169     1018

42 LONT      22 ISI     -         6.1       -      837
              2 SRI     -         3.7       -      884
              4 UTAH    -         2.2       -      921

43 TYMT      40 NCCT    -         2.6       -     1859
              2 SRI     -         0.5       -       79
              3 UCSB    -         0.2       -       74

44 MIT2      44 MIT2    -         2.8       -       18
             40 NCCT    -         2.3       -     1664
              1 UCLA    -         0.2       -      589

46 MOFF      40 NCCT    -         2.2       -     2091
              1 UCLA    -         0.2       -      447

46 RUTT       9 HARV    -         4.3       -       38
              5 BBN     -         3.5       -       93
             22 ISI     -         2.9       -      172

47 WPAT      40 NCCT    -         2.2       -     1643
              3 UCSB    -         0.2       -      301
              1 UCLA    -         0.2       -      671
```