

Independent Submission
Request for Comments: 7801
Category: Informational
ISSN: 2070-1721

V. Dolmatov, Ed.
Research Computer Center MSU
March 2016

GOST R 34.12-2015: Block Cipher "Kuznyechik"

Abstract

This document is intended to be a source of information about the Russian Federal standard GOST R 34.12-2015 describing the block cipher with a block length of $n=128$ bits and a key length of $k=256$ bits, which is also referred to as "Kuznyechik". This algorithm is one of the set of Russian cryptographic standard algorithms (called GOST algorithms).

Status of This Memo

This document is not an Internet Standards Track specification; it is published for informational purposes.

This is a contribution to the RFC Series, independently of any other RFC stream. The RFC Editor has chosen to publish this document at its discretion and makes no statement about its value for implementation or deployment. Documents approved for publication by the RFC Editor are not a candidate for any level of Internet Standard; see Section 2 of RFC 5741.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <http://www.rfc-editor.org/info/rfc7801>.

Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document.

Table of Contents

1. Scope	2
2. General Information	3
3. Definitions and Notations	3
3.1. Definitions	3
3.2. Notations	4
4. Parameter Values	6
4.1. Nonlinear Bijection	6
4.2. Linear Transformation	7
4.3. Transformations	8
4.4. Key Schedule	9
4.5. Basic Encryption Algorithm	9
4.5.1. Encryption	9
4.5.2. Decryption	9
5. Examples (Informative)	10
5.1. Transformation S	10
5.2. Transformation R	10
5.3. Transformation L	10
5.4. Key Schedule	11
5.5. Test Encryption	12
5.6. Test Decryption	13
6. Security Considerations	13
7. References	14
7.1. Normative References	14
7.2. Informative References	14
Author's Address	14

1. Scope

The Russian Federal standard [GOST3412-2015] specifies basic block ciphers used as cryptographic techniques for information processing and information protection including the provision of confidentiality, authenticity, and integrity of information during information transmission, processing, and storage in computer-aided systems.

The cryptographic algorithms specified in this standard are designed both for hardware and software implementation. They comply with modern cryptographic requirements and put no restrictions on the confidentiality level of the protected information.

The standard applies to development, operation, and modernization of the information systems of various purposes.

2. General Information

The block cipher "Kuznyechik" [GOST3412-2015] was developed by the Center for Information Protection and Special Communications of the Federal Security Service of the Russian Federation with participation of the Open Joint-Stock company "Information Technologies and Communication Systems" (InfoTeCS JSC). GOST R 34.12-2015 was approved and introduced by Decree #749 of the Federal Agency on Technical Regulating and Metrology on June 19, 2015.

Terms and concepts in the standard comply with the following international standards:

- o ISO/IEC 10116 [ISO-IEC10116] and
- o series of standards ISO/IEC 18033 [ISO-IEC18033-1] [ISO-IEC18033-3].

3. Definitions and Notations

The following terms and their corresponding definitions are used in the standard.

3.1. Definitions

Definitions

encryption algorithm: process that transforms plaintext into ciphertext (Section 2.19 of [ISO-IEC18033-1]),

decryption algorithm: process that transforms ciphertext into plaintext (Section 2.14 of [ISO-IEC18033-1]),

basic block cipher: block cipher that for a given key provides a single invertible mapping of the set of fixed-length plaintext blocks into ciphertext blocks of the same length,

block: string of bits of a defined length (Section 2.6 of [ISO-IEC18033-1]),

block cipher: symmetric encipherment system with the property that the encryption algorithm operates on a block of plaintext, i.e., a string of bits of a defined length, to yield a block of ciphertext (Section 2.7 of [ISO-IEC18033-1]),

Note: In GOST R 34.12-2015, it is established that the terms "block cipher" and "block encryption algorithm" are synonyms.

encryption: reversible transformation of data by a cryptographic algorithm to produce ciphertext, i.e., to hide the information content of the data (Section 2.18 of [ISO-IEC18033-1]),

round key: sequence of symbols that is calculated from the key and controls a transformation for one round of a block cipher,

key: sequence of symbols that controls the operation of a cryptographic transformation (e.g., encipherment and decipherment) (Section 2.21 of [ISO-IEC18033-1]),

Note: In GOST R 34.12-2015, the key must be a binary sequence.

plaintext: unencrypted information (Section 3.11 of [ISO-IEC10116]),

key schedule: calculation of round keys from the key,

decryption: reversal of a corresponding encipherment (Section 2.13 of [ISO-IEC18033-1]),

symmetric cryptographic technique: cryptographic technique that uses the same secret key for both the originator's and the recipient's transformation (Section 2.32 of [ISO-IEC18033-1]),

cipher: alternative term for encipherment system (Section 2.20 of [ISO-IEC18033-1]), and

ciphertext: data that has been transformed to hide its information content (Section 3.3 of [ISO-IEC10116]).

3.2. Notations

The following notations are used in the standard:

- | | |
|---------------------------|---|
| V^* | the set of all binary vector strings of a finite length (hereinafter referred to as the strings) including the empty string, |
| V_s | the set of all binary strings of length s , where s is a non-negative integer; substrings and string components are enumerated from right to left starting from zero, |
| $U[*]W$ | direct (Cartesian) product of two sets, U and W , |
| A | the number of components (the length) of a string A belonging to V^* (if A is an empty string, then $ A = 0$), |

- $A||B$ concatenation of strings A and B both belonging to V^* , i.e., a string from $V_{(|A|+|B|)}$, where the left substring from $V_{|A|}$ is equal to A , and the right substring from $V_{|B|}$ is equal to B ,
- $Z_{(2^n)}$ ring of residues modulo 2^n ,
- Q finite field $GF(2)[x]/p(x)$, where $p(x)=x^8+x^7+x^6+x+1$ belongs to $GF(2)[x]$; elements of field Q are represented by integers in such way that element $z_0+z_1*\theta+\dots+z_7*\theta^7$ belonging to Q corresponds to integer $z_0+2*z_1+\dots+2^7*z_7$, where $z_i=0$ or $z_i=1$, $i=0,1,\dots,7$ and θ denotes a residue class modulo $p(x)$ containing x ,
- (xor) exclusive-or of the two binary strings of the same length,
- $Vec_s: Z_{(2^s)} \rightarrow V_s$ bijective mapping that maps an element from ring $Z_{(2^s)}$ into its binary representation, i.e., for an element z of the ring $Z_{(2^s)}$, represented by the residue $z_0 + (2*z_1) + \dots + (2^{(s-1)}*z_{(s-1)})$, where $z_i \in \{0, 1\}$, $i = 0, \dots, n-1$, the equality $Vec_s(z) = z_{(s-1)}||\dots||z_1||z_0$ holds,
- $Int_s: V_s \rightarrow Z_{(2^s)}$ the mapping inverse to the mapping Vec_s , i.e., $Int_s = Vec_s^{(-1)}$,
- $\delta: V_8 \rightarrow Q$ bijective mapping that maps a binary string from V_8 into an element from field Q as follows: string $z_7||\dots||z_1||z_0$, where $z_i \in \{0, 1\}$, $i = 0, \dots, 7$, corresponds to the element $z_0+(z_1*\theta)+\dots+(z_7*\theta^7)$ belonging to Z ,
- $\text{nabla}: Q \rightarrow V_8$ the mapping inverse to the mapping δ , i.e., $\delta = \text{nabla}^{(-1)}$,
- PS composition of mappings, where the mapping S applies first, and
- P^s composition of mappings $P^{(s-1)}$ and P , where $P^1=P$.

4. Parameter Values

4.1. Nonlinear Bijection

The bijective nonlinear mapping is a substitution: $\Pi = (\text{Vec}_8)\Pi'(\text{Int}_8): V_8 \rightarrow V_8$, where $\Pi': Z_2(2^8) \rightarrow Z_2(2^8)$. The values of the substitution Π' are specified below as an array $\Pi' = (\Pi'(0), \Pi'(1), \dots, \Pi'(255))$:

$\Pi' =$
 (252, 238, 221, 17, 207, 110, 49, 22, 251, 196, 250,
 218, 35, 197, 4, 77, 233, 119, 240, 219, 147, 46,
 153, 186, 23, 54, 241, 187, 20, 205, 95, 193, 249,
 24, 101, 90, 226, 92, 239, 33, 129, 28, 60, 66,
 139, 1, 142, 79, 5, 132, 2, 174, 227, 106, 143,
 160, 6, 11, 237, 152, 127, 212, 211, 31, 235, 52,
 44, 81, 234, 200, 72, 171, 242, 42, 104, 162, 253,
 58, 206, 204, 181, 112, 14, 86, 8, 12, 118, 18,
 191, 114, 19, 71, 156, 183, 93, 135, 21, 161, 150,
 41, 16, 123, 154, 199, 243, 145, 120, 111, 157, 158,
 178, 177, 50, 117, 25, 61, 255, 53, 138, 126, 109,
 84, 198, 128, 195, 189, 13, 87, 223, 245, 36, 169,
 62, 168, 67, 201, 215, 121, 214, 246, 124, 34, 185,
 3, 224, 15, 236, 222, 122, 148, 176, 188, 220, 232,
 40, 80, 78, 51, 10, 74, 167, 151, 96, 115, 30,
 0, 98, 68, 26, 184, 56, 130, 100, 159, 38, 65,
 173, 69, 70, 146, 39, 94, 85, 47, 140, 163, 165,
 125, 105, 213, 149, 59, 7, 88, 179, 64, 134, 172,
 29, 247, 48, 55, 107, 228, 136, 217, 231, 137, 225,
 27, 131, 73, 76, 63, 248, 254, 141, 83, 170, 144,
 202, 216, 133, 97, 32, 113, 103, 164, 45, 43, 9,
 91, 203, 155, 37, 208, 190, 229, 108, 82, 89, 166,
 116, 210, 230, 244, 180, 192, 209, 102, 175, 194, 57,
 75, 99, 182).

$\text{Pi}^{(-1)}$ is the inverse of Pi ; the values of the substitution $\text{Pi}^{(-1)}$ are specified below as an array $\text{Pi}^{(-1)'} = (\text{Pi}^{(-1)'(0)}, \text{Pi}^{(-1)'(1)}, \dots, \text{Pi}^{(-1)'(255)})$:

$\text{Pi}^{(-1)'} =$
 (165, 45, 50, 143, 14, 48, 56, 192, 84, 230, 158,
 57, 85, 126, 82, 145, 100, 3, 87, 90, 28, 96,
 7, 24, 33, 114, 168, 209, 41, 198, 164, 63, 224,
 39, 141, 12, 130, 234, 174, 180, 154, 99, 73, 229,
 66, 228, 21, 183, 200, 6, 112, 157, 65, 117, 25,
 201, 170, 252, 77, 191, 42, 115, 132, 213, 195, 175,
 43, 134, 167, 177, 178, 91, 70, 211, 159, 253, 212,
 15, 156, 47, 155, 67, 239, 217, 121, 182, 83, 127,
 193, 240, 35, 231, 37, 94, 181, 30, 162, 223, 166,
 254, 172, 34, 249, 226, 74, 188, 53, 202, 238, 120,
 5, 107, 81, 225, 89, 163, 242, 113, 86, 17, 106,
 137, 148, 101, 140, 187, 119, 60, 123, 40, 171, 210,
 49, 222, 196, 95, 204, 207, 118, 44, 184, 216, 46,
 54, 219, 105, 179, 20, 149, 190, 98, 161, 59, 22,
 102, 233, 92, 108, 109, 173, 55, 97, 75, 185, 227,
 186, 241, 160, 133, 131, 218, 71, 197, 176, 51, 250,
 150, 111, 110, 194, 246, 80, 255, 93, 169, 142, 23,
 27, 151, 125, 236, 88, 247, 31, 251, 124, 9, 13,
 122, 103, 69, 135, 220, 232, 79, 29, 78, 4, 235,
 248, 243, 62, 61, 189, 138, 136, 221, 205, 11, 19,
 152, 2, 147, 128, 144, 208, 36, 52, 203, 237, 244,
 206, 153, 16, 68, 64, 146, 58, 1, 38, 18, 26,
 72, 104, 245, 129, 139, 199, 214, 32, 10, 8, 0,
 76, 215, 116).

4.2. Linear Transformation

The linear transformation is denoted by $l: (V_8)^{16} \rightarrow V_8$, and defined as:

$l(a_{15}, \dots, a_0) = \text{nabla}(148 \cdot \text{delta}(a_{15}) + 32 \cdot \text{delta}(a_{15}) +$
 $133 \cdot \text{delta}(a_{13}) + 16 \cdot \text{delta}(a_{12}) + 194 \cdot \text{delta}(a_{11}) +$
 $192 \cdot \text{delta}(a_{10}) + 1 \cdot \text{delta}(a_9) + 251 \cdot \text{delta}(a_8) + 1 \cdot \text{delta}(a_7) +$
 $192 \cdot \text{delta}(a_6) + 194 \cdot \text{delta}(a_5) + 16 \cdot \text{delta}(a_4) + 133 \cdot \text{delta}(a_3) +$
 $32 \cdot \text{delta}(a_2) + 148 \cdot \text{delta}(a_1) + 1 \cdot \text{delta}(a_0)),$

for all a_i belonging to V_8 , $i = 0, 1, \dots, 15$, where the addition and multiplication operations are in the field Q , and constants are elements of the field as defined above.

4.3. Transformations

The following transformations are applicable for encryption and decryption algorithms:

$X[x]:V_{128} \rightarrow V_{128}$ $X[k](a)=k(xor)a$, where k, a belong to V_{128} ,

$S:V_{128} \rightarrow V_{128}$ $S(a)=(a_{15}||\dots||a_0)=\pi(a_{15})||\dots||\pi(a_0)$, where $a_{15}||\dots||a_0$ belongs to V_{128} , a_i belongs to V_8 , $i=0,1,\dots,15$,

$S^{(-1)}:V_{128} \rightarrow V_{128}$ the inverse transformation of S , which may be calculated, for example, as follows:

$S^{(-1)}(a_{15}||\dots||a_0)=\pi^{(-1)}(a_{15})||\dots||\pi^{(-1)}(a_0)$, where $a_{15}||\dots||a_0$ belongs to V_{128} , a_i belongs to V_8 , $i=0,1,\dots,15$,

$R:V_{128} \rightarrow V_{128}$ $R(a_{15}||\dots||a_0)=l(a_{15},\dots,a_0)||a_{15}||\dots||a_1$, where $a_{15}||\dots||a_0$ belongs to V_{128} , a_i belongs to V_8 , $i=0,1,\dots,15$,

$L:V_{128} \rightarrow V_{128}$ $L(a)=R^{(16)}(a)$, where a belongs to V_{128} ,

$R^{(-1)}:V_{128} \rightarrow V_{128}$ the inverse transformation of R , which may be calculated, for example, as follows: $R^{(-1)}(a_{15}||\dots||a_0)=a_{14}||a_{13}||\dots||a_0||l(a_{14},a_{13},\dots,a_0,a_{15})$, where $a_{15}||\dots||a_0$ belongs to V_{128} , a_i belongs to V_8 , $i=0,1,\dots,15$,

$L^{(-1)}:V_{128} \rightarrow V_{128}$ $L^{(-1)}(a)=(R^{(-1)})^{(16)}(a)$, where a belongs to V_{128} , and

$F[k]:V_{128}[*]V_{128} \rightarrow V_{128}[*]V_{128}$

$F[k](a_1,a_0)=(LSX[k](a_1)(xor)a_0,a_1)$, where k, a_0, a_1 belong to V_{128} .

4.4. Key Schedule

Key schedule uses round constants C_i belonging to V_{128} , $i=1, 2, \dots, 32$, defined as

$C_i = L(\text{Vec}_{128}(i))$, $i=1, 2, \dots, 32$.

Round keys K_i , $i=1, 2, \dots, 10$ are derived from key $K = k_{255} || \dots || k_0$ belonging to V_{256} , k_i belongs to V_1 , $i=0, 1, \dots, 255$, as follows:

$K_1 = k_{255} || \dots || k_{128};$
 $K_2 = k_{127} || \dots || k_0;$
 $(K_{(2i+1)}, K_{(2i+2)}) = F[C_{(8(i-1)+8)}] \dots$
 $F[C_{(8(i-1)+1)}](K_{(2i-1)}, K_{(2i)}), i=1, 2, 3, 4.$

4.5. Basic Encryption Algorithm

4.5.1. Encryption

Depending on the values of round keys K_1, \dots, K_{10} , the encryption algorithm is a substitution $E_{(K_1, \dots, K_{10})}$ defined as follows:

$E_{(K_1, \dots, K_{10})}(a) = X[K_{10}]LSX[K_9] \dots LSX[K_2]LSX[K_1](a),$

where a belongs to V_{128} .

4.5.2. Decryption

Depending on the values of round keys K_1, \dots, K_{10} , the decryption algorithm is a substitution $D_{(K_1, \dots, K_{10})}$ defined as follows:

$D_{(K_1, \dots, K_{10})}(a) = X[K_1]L^{(-1)}S^{(-1)}X[K_2] \dots$
 $L^{(-1)}S^{(-1)}X[K_9]L^{(-1)}S^{(-1)}X[K_{10}](a),$

where a belongs to V_{128} .

5.4. Key Schedule

In this test example, the key is equal to:

$K = 8899aabbccddeeff0011223344556677fedcba98765432100123456789abcdef.$

$K_1 = 8899aabbccddeeff0011223344556677,$
 $K_2 = fedcba98765432100123456789abcdef.$

$C_1 = 6ea276726c487ab85d27bd10dd849401,$
 $X[C_1](K_1) = e63bdcc9a09594475d369f2399d1f276,$
 $SX[C_1](K_1) = 0998ca37a7947aabb78f4a5ae81b748a,$
 $LSX[C_1](K_1) = 3d0940999db75d6a9257071d5e6144a6,$
 $F[C_1](K_1, K_2) = (c3d5fa01ebe36f7a9374427ad7ca8949,$
 $8899aabbccddeeff0011223344556677).$

$C_2 = dc87ece4d890f4b3ba4eb92079cbe02,$
 $F[C_2]F[C_1](K_1, K_2) = (37777748e56453377d5e262d90903f87,$
 $c3d5fa01ebe36f7a9374427ad7ca8949).$

$C_3 = b2259a96b4d88e0be7690430a44f7f03,$
 $F[C_3]...F[C_1](K_1, K_2) = (f9eae5f29b2815e31f11ac5d9c29fb01,$
 $37777748e56453377d5e262d90903f87).$

$C_4 = 7bcd1b0b73e32ba5b79cb140f2551504,$
 $F[C_4]...F[C_1](K_1, K_2) = (e980089683d00d4be37dd3434699b98f,$
 $f9eae5f29b2815e31f11ac5d9c29fb01).$

$C_5 = 156f6d791fab511deabb0c502fd18105,$
 $F[C_5]...F[C_1](K_1, K_2) = (b7bd70acea4460714f4ebe13835cf004,$
 $e980089683d00d4be37dd3434699b98f).$

$C_6 = a74af7efab73df160dd208608b9efe06,$
 $F[C_6]...F[C_1](K_1, K_2) = (1a46ea1cf6ccd236467287df93fdf974,$
 $b7bd70acea4460714f4ebe13835cf004).$

$C_7 = c9e8819dc73ba5ae50f5b570561a6a07,$
 $F[C_7]...F[C_1](K_1, K_2) = (3d4553d8e9cfec6815ebadc40a9ffd04,$
 $1a46ea1cf6ccd236467287df93fdf974).$

$C_8 = f6593616e6055689adfb18027aa2a08,$
 $(K_3, K_4) = F[C_8]...F[C_1](K_1, K_2) =$
 $(db31485315694343228d6aef8cc78c44,$
 $3d4553d8e9cfec6815ebadc40a9ffd04).$

The round keys K_i , $i = 1, 2, \dots, 10$, take the following values:

```

K_1 = 8899aabbccddeeff0011223344556677,
K_2 = fedcba98765432100123456789abcdef,
K_3 = db31485315694343228d6aef8cc78c44,
K_4 = 3d4553d8e9cfec6815ebadc40a9ffd04,
K_5 = 57646468c44a5e28d3e59246f429f1ac,
K_6 = bd079435165c6432b532e82834da581b,
K_7 = 51e640757e8745de705727265a0098b1,
K_8 = 5a7925017b9fdd3ed72a91a22286f984,
K_9 = bb44e25378c73123a5f32f73cdb6e517,
K_10 = 72e9dd7416bcf45b755dbaa88e4a4043.

```

5.5. Test Encryption

In this test example, encryption is performed on the round keys specified in Section 5.4. Let the plaintext be

$a = 1122334455667700ffeeddccbbaa9988$,

then

```

X[K_1](a) = 99bb99ff99bb99ffffffffffffffffffff,
SX[K_1](a) = e87de8b6e87de8b6b6b6b6b6b6b6b6,
LSX[K_1](a) = e297b686e355b0a1cf4a2f9249140830,
LSX[K_2]LSX[K_1](a) = 285e497a0862d596b36f4258a1c69072,
LSX[K_3]...LSX[K_1](a) = 0187a3a429b567841ad50d29207cc34e,
LSX[K_4]...LSX[K_1](a) = ec9bdba057d4f4d77c5d70619dcad206,
LSX[K_5]...LSX[K_1](a) = 1357fd11de9257290c2a1473eb6bcde1,
LSX[K_6]...LSX[K_1](a) = 28ae31e7d4c2354261027ef0b32897df,
LSX[K_7]...LSX[K_1](a) = 07e223d56002c013d3f5e6f714b86d2d,
LSX[K_8]...LSX[K_1](a) = cd8ef6cd97e0e092a8e4cca61b38bf65,
LSX[K_9]...LSX[K_1](a) = 0d8e40e4a800d06b2f1b37ea379ead8e.

```

Then the ciphertext is

$b = X[K_{10}]LSX[K_9]...LSX[K_1](a) = 7f679d90bebc24305a468d42b9d4edcd$.

5.6. Test Decryption

In this test example, decryption is performed on the round keys specified in Section 5.4. Let the ciphertext be

$b = 7f679d90bebc24305a468d42b9d4edcd,$

then

```
X[K_10](b) = 0d8e40e4a800d06b2f1b37ea379ead8e,
L(-1)X[K_10](b) = 8a6b930a52211b45c5baa43ff8b91319,
S(-1)L(-1)X[K_10](b) = 76ca149eef27d1b10d17e3d5d68e5a72,
S(-1)L(-1)X[K_9]S(-1)L(-1)X[K_10](b) =
5d9b06d41b9d1d2d04df7755363e94a9,
S(-1)L(-1)X[K_8]...S(-1)L(-1)X[K_10](b) =
79487192aa45709c115559d6e9280f6e,
S(-1)L(-1)X[K_7]...S(-1)L(-1)X[K_10](b) =
ae506924c8ce331bb918fc5bdfb195fa,
S(-1)L(-1)X[K_6]...S(-1)L(-1)X[K_10](b) =
bbffbfbc8939eaaffafb8e22769e323aa,
S(-1)L(-1)X[K_5]...S(-1)L(-1)X[K_10](b) =
3cc2f07cc07a8bec0f3ea0ed2ae33e4a,
S(-1)L(-1)X[K_4]...S(-1)L(-1)X[K_10](b) =
f36f01291d0b96d591e228b72d011c36,
S(-1)L(-1)X[K_3]...S(-1)L(-1)X[K_10](b) =
1c4b0c1e950182b1ce696af5c0bfc5df,
S(-1)L(-1)X[K_2]...S(-1)L(-1)X[K_10](b) =
99bb99ff99bb99ffffffffffffffffffff.
```

Then the plaintext is

$a = X[K_1]S^{(-1)}L^{(-1)}X[K_2]...S^{(-1)}L^{(-1)}X[K_{10}](b) =$
 $1122334455667700ffeeddccbbaa9988.$

6. Security Considerations

This entire document is about security considerations.

7. References

7.1. Normative References

[GOST3412-2015]

"Information technology. Cryptographic data security. Block ciphers", GOST R 34.12-2015, Federal Agency on Technical Regulating and Metrology, 2015.

7.2. Informative References

[ISO-IEC10116]

ISO/IEC, "Information technology -- Security techniques -- Modes of operation for an n-bit block cipher", ISO/IEC 10116, 2006.

[ISO-IEC18033-1]

ISO/IEC, "Information technology -- Security techniques -- Encryption algorithms -- Part 1: General", ISO/IEC 18033-1, 2015.

[ISO-IEC18033-3]

ISO/IEC, "Information technology -- Security techniques -- Encryption algorithms -- Part 3: Block ciphers", ISO/IEC 18033-3, 2010.

Author's Address

Vasily Dolmatov (editor)
Research Computer Center MSU
Leninskiye Gory, 1, Building 4, MGU NIVC
Moscow 119991
Russian Federation

Email: dol@srcc.msu.ru