Network Working Group Request for Comments: 3128

Updates: 1858

Category: Informational

I. Miller Singularis Ltd June 2001

Protection Against a Variant of the Tiny Fragment Attack

### Status of this Memo

This memo provides information for the Internet community. It does not specify an Internet standard of any kind. Distribution of this memo is unlimited.

## Copyright Notice

Copyright (C) The Internet Society (2001). All Rights Reserved.

#### Abstract

This document discusses how RFC 1858 compliant filters can be vulnerable to a variant of the "Tiny Fragment Attack" described in section 3.1 of the RFC. This document describes the attack and recommends corrective action.

#### 1. Introduction

RFC 1858 provides an excellent description of a class of attack on Internet firewalls and proposes countermeasures. However one of these countmeasures, the "Indirect Method" (section 3.2.2) is vulnerable to a combination of two of the attacks described.

The attack combines the features of the "Tiny Fragment Attack" (section 3) and the "Overlapping Fragment Attack" (section 4).

### 1.1 The scope of the attack

Where the filtering rules allow incoming connections to a machine AND there other ports which allow only outgoing connections on the same host, the attack allows incoming connections to the supposedly outgoing-only ports.

Note that only the initial connection message need be fragmented. Once the connection is established further traffic on it is legal. The significance of this weakness will depend on the security policy in force.

Miller Informational [Page 1]

## 2. The Tiny Overlapping Fragment Attack

The attack typically consists of sending three fragments.

Fragment 1: (Fragment offset = 0; length >= 16)
Includes whole header and is entirely legal. Typically it
describes a SYN packet initiating a new TCP connection to a port
on the target host that is allowed to receive incoming
connections.
e.g., Incoming connection to port 25 SMTP.

Fragment 2: (Fragment offset = 0; length = 8)
Is only the first 8 bytes and could be legal depending on the other 8-bytes of the header, but is NOT legal combined with the corresponding bytes from Fragment 1. Such a fragment includes only the port numbers and sequence number from the TCP header. Typically this packet replaces the destination port number with a port number on which the destination host that is not allowed to receive incoming connections.

Fragment 3: (Fragment offset >= 2; length = rest of message)
Contains no header and completes the message. (This third
fragment is not part of the attack. However Fragment 1 cannot be
the complete message or it would be passed up to the application
before Fragment 2 arrived so a third fragment is necessary.)

# 2.1 Example of the attack

Consider the following trivial set of rules for incoming packets:

No	Action	Source Port	Dest. Port	Flags	Purpose
1 1	Permit	>1023	SMTP	ANY	Incoming E-mail
2	Permit	<b>&gt;1023</b>	ANY	Ack=1	Existing FTP data channel connections.
3	Deny	ANY	ANY	ANY	Default deny

Fragment 1: attacker(1234) -> target(SMTP) Ack=0
This is a new SMTP connection and is permitted by rule 1.

Fragment 2: attacker(1234) -> target(Telnet=23) Ack=absent
 All fields present conform to rule 2, as it could be the start of
 an FTP packet.

Miller Informational [Page 2]

Depending on the precise implementation of the fragment reassembly in the target machine's IP stack, fragment B may overwrite fragment A to produce:-

### 2.2 The failure of "Indirect Method"

The Indirect Method attempts to solve both Tiny Fragment and Overlapping Fragment attacks, solely by rejecting packets with F0=1. However none of the above fragments have F0=1, so none are rejected.

The failure is clear on careful reading. In section 3.2.2 "Indirect Method", RFC 1858 states:-

The indirect method relies on the observation that when a TCP packet is fragmented so as to force "interesting" header fields out of the zero-offset fragment, there must exist a fragment with FO equal to 1.

This is normally true where the fragments are genuine fragments, generally by bona fide software, but it is simply not true that a hacker forging fragments is forced to produce an F0=1 fragment simply because (s)he has produced an 8-byte F0=0 fragment. The vulnerability flows from this false premise.

### 3. Countermeasures

Whereas apparently very elegant, RFC 1858's Indirect Method is not robust. In addition to blocking F0=1 packets, it is also necessary to block F0=0 that hold less than a complete header.

- 4. Security Considerations

This memo is concerned entirely with the security implications of filtering fragmented IP packets.

# 5. Author's Address

Ian Miller Singularis Ltd 32 Stockwell Street Cambridge CB1 3ND UK

Phone: +44 1223 511943 EMail: Ian\_Miller@singularis.ltd.uk

### 6. Full Copyright Statement

Copyright (C) The Internet Society (2001). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

### **Acknowledgement**

Funding for the RFC Editor function is currently provided by the Internet Society.