Internet Engineering Task Force (IETF)

Request for Comments: 7224 Category: Standards Track

ISSN: 2070-1721

M. Bjorklund Tail-f Systems May 2014

# IANA Interface Type YANG Module

#### Abstract

This document defines the initial version of the iana-if-type YANG module.

#### Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in Section 2 of RFC 5741.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at http://www.rfc-editor.org/info/rfc7224.

# Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (http://trustee.ietf.org/license-info) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Bjorklund Standards Track [Page 1]

#### Table of Contents

1.	Introduction	2
2.	IANA-Maintained Interface Type YANG Module	2
3.	IANA-Maintained Interface Type YANG Module	35
3	3.1. URI Registrations	36
3	3.2. YANG Module Registrations	36
	Security Considerations	
	Normative References	

### 1. Introduction

This document defines the initial version of the iana-if-type YANG module for interface type definitions.

The iana-if-type module reflects IANA's existing "ifType definitions" registry [IFTYPE-IANA-REGISTRY]. The latest revision of the module can be obtained from the IANA web site.

Whenever a new interface type is added to the "ifType definitions" registry, the IANAifType-MIB and the iana-if-type YANG module are updated by IANA.

## 2. IANA-Maintained Interface Type YANG Module

This YANG module imports the "interface-type" identity from [RFC7223].

description

```
'This YANG module defines YANG identities for IANA-registered
   interface types.
   This YANG module is maintained by IANA and reflects the
   'ifType definitions' registry.
   The latest revision of this YANG module can be obtained from
   the IANA web site.
   Requests for new values should be made to IANA via
   email (iana@iana.org).
   Copyright (c) 2014 IETF Trust and the persons identified as
   authors of the code. All rights reserved.
   Redistribution and use in source and binary forms, with or
   without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License
   set forth in Section 4.c of the IETF Trust's Legal Provisions
   Relating to IETF Documents
   (http://trustee.ietf.org/license-info).
   The initial version of this YANG module is part of RFC 7224;
   see the RFC itself for full legal notices.'
  reference
    "IANA 'ifType definitions' registry.
     <http://www.iana.org/assignments/smi-numbers>";
revision 2014-05-08 {
  description
    "Initial revision.";
  reference
    "RFC 7224: IANA Interface Type YANG Module";
identity iana-interface-type {
  base if:interface-type;
  description
    "This identity is used as a base for all interface types defined in the 'ifType definitions' registry.";
}
```

```
identity other {
 base lana-interface-type;
identity regular1822 {
 base lana-interface-type;
identity hdh1822 {
 base lana-interface-type;
identity ddnX25 {
 base lana-interface-type;
identity rfc877x25 {
 base iana-interface-type;
 reference
    "RFC 1382 - SNMP MIB Extension for the X.25 Packet Layer";
identity ethernetCsmacd {
 base lana-interface-type;
 description
    'For all Ethernet-like interfaces, regardless of speed,
     as per RFC 3635.";
 reference
    "RFC 3635 - Definitions of Managed Objects for the
                Ethernet-like Interface Types";
identity iso88023Csmacd {
 base lana-interface-type;
 status deprecated;
 description
    "Deprecated via RFC 3635.
     Use ethernetCsmacd(6) instead.";
 reference
    "RFC 3635 - Definitions of Managed Objects for the
                Ethernet-like Interface Types";
identity iso88024TokenBus {
 base lana-interface-type;
identity iso88025TokenRing {
 base iana-interface-type;
identity iso88026Man {
 base lana-interface-type:
identity starLan {
 base iana-interface-type;
 status deprecated;
```

```
description
    "Deprecated via RFC 3635.
     Use ethernetCsmacd(6) instead.";
  reference
    "RFC 3635 - Definitions of Managed Objects for the
                Ethernet-like Interface Types";
identity proteon10Mbit {
  base lana-interface-type;
identity proteon80Mbit {
 base iana-interface-type;
identity hyperchannel {
  base lana-interface-type;
identity fddi {
  base iana-interface-type;
  reference
    "RFC 1512 - FDDI Management Information Base";
identity lapb {
  base lana-interface-type;
    "RFC 1381 - SNMP MIB Extension for X.25 LAPB";
identity sdlc {
  base lana-interface-type;
identity ds1 {
  base iana-interface-type;
  description
    "DS1-MIB.";
  reference
    "RFC 4805 - Definitions of Managed Objects for the
                DS1, J1, E1, DS2, and E2 Interface Types";
identity e1 {
  base lana-interface-type;
  status obsolete;
  description
    "Obsolete; see DS1-MIB.";
  reference
    "RFC 4805 - Definitions of Managed Objects for the
                DS1, J1, E1, DS2, and E2 Interface Types";
}
```

```
identity basicISDN {
  base lana-interface-type;
  description
    "No longer used. See also RFC 2127.":
identity primaryISDN {
  base lana-interface-type;
  description
    "No longer used. See also RFC 2127.";
identity propPointToPointSerial {
  base iana-interface-type;
  description
    "Proprietary serial.";
identity ppp {
  base iana-interface-type;
identity softwareLoopback {
  base iana-interface-type;
identity eon {
  base lana-interface-type;
  description
    "CLNP over IP.";
identity ethernet3Mbit {
  base iana-interface-type;
identity nsip {
  base iana-interface-type;
  description
    "XNS over IP.";
identity slip {
  base iana-interface-type;
  description
    "Generic SLIP.";
identity ultra {
  base lana-interface-type;
  description
    "Ultra Technologies.";
identity ds3 {
  base iana-interface-type;
  description
    "DS3-MIB.";
```

**Standards Track** 

[Page 6]

```
reference
    "RFC 3896 - Definitions of Managed Objects for the
                DS3/E3 Interface Type";
identity sip {
  base iana-interface-type;
  description
    "SMDS, coffee.";
  reference
    "RFC 1694 - Definitions of Managed Objects for SMDS
                 Interfaces using SMIv2";
identity frameRelay {
  base iana-interface-type;
  description
    "DTE only.";
  reference
    "RFC 2115 - Management Information Base for Frame Relay
                 DTEs Using SMIv2";
identity rs232 {
  base iana-interface-type;
  reference
    "RFC 1659 - Definitions of Managed Objects for RS-232-like
                 Hardware Devices using SMIv2";
identity para {
  base iana-interface-type;
  description
    "Parallel-port.";
  reference
    "RFC 1660 - Definitions of Managed Objects for
                 Parallel-printer-like Hardware Devices using
                 SMIv2";
identity arcnet {
  base iana-interface-type;
  description
    "ARCnet.";
identity arcnetPlus {
  base iana-interface-type;
  description
    "ARCnet Plus.":
}
```

```
identity atm {
  base iana-interface-type;
  description
    "ATM cells.":
identity miox25 {
  base lana-interface-type;
  reference
    "RFC 1461 - SNMP MIB extension for Multiprotocol
                 Interconnect over X.25";
identity sonet {
  base iana-interface-type;
description
    "SONET or SDH.";
identity x25ple {
  base lana-interface-type;
  reference
    "RFC 2127 - ISDN Management Information Base using SMIv2";
identity iso88022llc {
  base lana-interface-type;
identity localTalk {
  base iana-interface-type;
identity smdsDxi {
  base lana-interface-type;
identity frameRelayService {
  base iana-interface-type;
  description
    "FRNETSERV-MIB.";
  reference
    "RFC 2954 - Definitions of Managed Objects for Frame
                 Relay Service";
identity v35 {
  base iana-interface-type;
identity hssi {
  base lana-interface-type;
identity hippi {
 base iana-interface-type;
```

```
identity modem {
  base iana-interface-type;
  description
    "Generic modem.";
identity aal5 {
  base lana-interface-type;
  description
    "AAL5 over ATM.";
identity sonetPath {
  base lana-interface-type;
identity sonetVT {
  base lana-interface-type;
identity smdsIcip {
  base iana-interface-type;
  description
    "SMDS InterCarrier Interface.";
identity propVirtual {
  base lana-interface-type;
  description
    "Proprietary virtual/internal.";
  reference
    "RFC 2863 - The Interfaces Group MIB";
identity propMultiplexor {
  base lana-interface-type;
  description
    "Proprietary multiplexing.";
  reference
    "RFC 2863 - The Interfaces Group MIB";
identity ieee80212 {
 base lana-interface-type;
  description
    "100BaseVG.";
identity fibreChannel {
  base iana-interface-type;
  description
    "Fibre Channel.";
}
```

```
identity hippiInterface {
  base iana-interface-type;
  description
    "HIPPI interfaces.";
identity frameRelayInterconnect {
  base iana-interface-type;
  status obsolete;
  description
    'Obsolete; use either
     frameRelay(32) or frameRelayService(44).":
identity aflane8023 {
  base lana-interface-type;
  description
    "ATM Emulated LAN for 802.3.";
identity aflane8025 {
  base lana-interface-type;
  description
    "ATM Emulated LAN for 802.5.";
identity cctEmul {
  base iana-interface-type;
  description
    "ATM Emulated circuit.";
identity fastEther {
  base lana-interface-type;
  status deprecated;
  description
    "Obsoleted via RFC 3635.
     ethernetCsmacd(6) should be used instead.";
  reference
    "RFC 3635 - Definitions of Managed Objects for the
                Ethernet-like Interface Types";
identity isdn {
  base lana-interface-type;
  description
    "ISDN and X.25.";
  reference
    "RFC 1356 - Multiprotocol Interconnect on X.25 and ISDN
                in the Packet Mode";
}
```

```
identity v11 {
  base iana-interface-type;
  description
    "CCITT V.11/X.21.";
identity v36 {
  base iana-interface-type;
  description
    "CCITT V.36.";
identity g703at64k {
  base iana-interface-type;
  description
    "CCITT G703 at 64Kbps.";
identity g703at2mb {
  base iana-interface-type;
  status obsolete;
  description
    "Obsolete; see DS1-MIB.";
identity qllç {
  base lana-interface-type;
  description
    "SNA QLLC.";
identity fastEtherFX {
  base lana-interface-type;
  status deprecated;
  description
    "Obsoleted via RFC 3635.
     ethernetCsmacd(6) should be used instead.";
  reference
    "RFC 3635 - Definitions of Managed Objects for the
                 Ethernet-like Interface Types";
identity channel {
  base lana-interface-type;
  description
    "Channel.";
identity ieee80211 {
  base iana-interface-type;
  description
    "Radio spread spectrum.";
identity ibm370parChan {
  base lana-interface-type;
```

**Standards Track** 

[Page 11]

```
description
    "IBM System 360/370 OEMI Channel.";
identity escon {
  base lana-interface-type;
  description
    "IBM Enterprise Systems Connection.";
identity dlsw {
  base iana-interface-type;
  description
    "Data Link Switching.";
identity isdns {
  base iana-interface-type;
  description
    "ISDN S/T interface.";
identity isdnu {
  base iana-interface-type;
  description
    "ISDN U interface.";
identity lapd {
  base iana-interface-type;
  description
    "Link Access Protocol D.";
identity ipSwitch {
  base iana-interface-type;
  description
    "IP Świtching Objects.";
identity rsrb {
  base lana-interface-type;
  description
    "Remote Source Route Bridging.";
identity atmLogical {
  base lana-interface-type;
  description
    "ATM Logical Port.";
  reference
    "RFC 3606 - Definitions of Supplemental Managed Objects
                for ATM Interface";
identity ds0 {
  base lana-interface-type;
```

```
description
    "Digital Signal Level 0.";
  reference
    "RFC 2494 - Definitions of Managed Objects for the DSO
                 and DSO Bundle Interface Type";
identity ds0Bundle {
  base iana-interface-type;
  description
    "Group of ds0s on the same ds1.";
    "RFC 2494 - Definitions of Managed Objects for the DSO
                 and DSO Bundle Interface Type";
identity bsc {
  base iana-interface-type;
  description
    "Bisynchronous Protocol.";
identity async {
  base iana-interface-type;
  description
    "Asynchronous Protocol.";
identity cnr {
  base iana-interface-type;
  description
    "Combat Net Radio.";
identity iso88025Dtr {
  base lana-interface-type;
  description
    "ISO 802.5r DTR.";
identity eplrs {
  base iana-interface-type;
  description
    "Ext Pos Loc Report Sys.";
identity arap {
  base iana-interface-type;
  description
    "Appletalk Remote Access Protocol.";
identity propCnls {
  base lana-interface-type;
  description
    "Proprietary Connectionless Protocol.";
```

```
identity hostPad {
  base lana-interface-type;
  description
    "CCITT-ITU X.29 PAD Protocol.";
identity termPad {
  base iana-interface-type;
  description
    "CCITT-ITU X.3 PAD Facility.";
identity frameRelayMPI {
  base iana-interface-type;
description
    "Multiproto Interconnect over FR.";
identity x213 {
  base lana-interface-type;
  description
    "CCITT-ITU X213.";
identity adsl {
  base lana-interface-type;
  description
    "Asymmetric Digital Subscriber Loop.";
identity radsl {
  base iana-interface-type;
  description
    "Rate-Adapt. Digital Subscriber Loop.";
identity sdsl {
  base lana-interface-type;
  description
    "Symmetric Digital Subscriber Loop.";
identity vdsl {
  base lana-interface-type;
  description
    "Very H-Speed Digital Subscrib. Loop.";
identity iso88025CRFPInt {
  base iana-interface-type;
  description
    "ISO 802.5 CRFP.";
identity myrinet {
  base iana-interface-type;
```

**Standards Track** 

[Page 14]

```
description
    "Myricom Myrinet.";
identity voiceEM {
  base lana-interface-type;
  description
    "Voice recEive and transMit.";
identity voiceFXO {
  base lana-interface-type;
  description
    "Voice Foreign Exchange Office.";
identity voiceFXS {
  base iana-interface-type;
  description
    "Voice Foreign Exchange Station.";
identity voiceEncap {
  base iana-interface-type;
  description
    "Voice encapsulation.";
identity voiceOverIp {
  base iana-interface-type;
  description
    "Voice over IP encapsulation.";
identity atmDxi {
  base lana-interface-type;
  description
    "ATM DXI.";
identity atmFuni {
  base lana-interface-type;
  description
    "ATM FUNI.";
identity atmIma {
  base iana-interface-type;
  description
    "ATM IMA.";
identity pppMultilinkBundle {
  base iana-interface-type;
  description
    "PPP Multilink Bundle.";
}
```

**Standards Track** 

[Page 15]

```
identity ipOverCdlc {
  base iana-interface-type;
  description
    "IBM ipOverCdlc.";
identity ipOverClaw {
  base iana-interface-type;
  description
    "IBM Common Link Access to Workstn.";
identity stackToStack {
  base lana-interface-type;
  description
    "IBM stackToStack.";
identity virtualIpAddress {
  base lana-interface-type;
  description
    "IBM VIPA.";
identity mpc {
  base iana-interface-type;
  description
    "IBM multi-protocol channel support.";
identity ipOverAtm {
  base iana-interface-type;
  description
    "IBM ipOverAtm.";
  reference
    "RFC 2320 - Definitions of Managed Objects for Classical IP
                and ARP Over ATM Using SMIv2 (IPOA-MIB)";
identity iso88025Fiber {
  base lana-interface-type;
  description
    "ISO 802.5j Fiber Token Ring.";
identity tdlc {
  base lana-interface-type;
  description
    "IBM twinaxial data link control.";
identity gigabitEthernet {
  base iana-interface-type;
  status deprecated;
```

```
description
     'Obsoleted via RFC 3635.
     ethernetCsmacd(6) should be used instead.";
  reference
    "RFC 3635 - Definitions of Managed Objects for the
                 Ethernet-like Interface Types";
identity hdlc {
  base lana-interface-type;
  description
    "HDLC.";
identity lapf {
  base iana-interface-type;
  description
    "LAP F.";
identity v37 {
  base iana-interface-type;
  description
    "V.37.";
identity x25mlp {
  base iana-interface-type;
  description
    "Multi-Link Protocol.";
identity x25huntGroup {
  base iana-interface-type;
  description
    "X25 Hunt Group.";
identity transpHdlc {
  base iana-interface-type;
  description
    "Transp HDLC.";
identity interleave {
  base lana-interface-type;
  description
    "Interleave channel.";
identity fast {
  base lana-interface-type;
  description
    "Fast channel.";
}
```

```
identity ip {
  base iana-interface-type;
  description
    "IP (for APPN HPR in IP networks).";
identity docsCableMaclayer {
 base iana-interface-type;
  description
    "CATV Mac Layer.";
identity docsCableDownstream {
  base iana-interface-type;
  description
    "CATV Downstream interface.";
identity docsCableUpstream {
  base iana-interface-type;
  description
    "CATV Upstream interface.";
identity a12MppSwitch {
  base iana-interface-type;
  description
    "Avalon Parallel Processor.";
identity tunnel {
 base iana-interface-type;
  description
    "Encapsulation interface.";
identity coffee {
  base iana-interface-type;
  description
    "Coffee pot.";
  reference
    "RFC 2325 - Coffee MIB";
identity ces {
  base iana-interface-type;
  description
    "Circuit Emulation Service.";
identity atmSubInterface {
 base lana-interface-type;
  description
    "ATM Sub Interface.";
}
```

```
identity l2vlan {
  base lana-interface-type;
  description
    "Layer 2 Virtual LAN using 802.10.";
identity l3ipvlan {
  base iana-interface-type;
  description
    "Layer 3 Virtual LAN using IP.";
identity l3ipxvlan {
  base lana-interface-type;
  description
    "Layer 3 Virtual LAN using IPX.";
identity digitalPowerline {
  base lana-interface-type;
  description
    "IP over Power Lines.";
identity mediaMailOverIp {
  base iana-interface-type;
  description
    "Multimedia Mail over IP.";
identity dtm {
  base iana-interface-type;
  description
    "Dynamic synchronous Transfer Mode.";
identity dcn {
  base lana-interface-type;
  description
    "Data Communications Network.";
identity ipForward {
  base lana-interface-type;
  description
    "IP Forwarding Interface.";
identity msdsl {
  base iana-interface-type;
  description
    "Multi-rate Symmetric DSL.";
identity ieee1394 {
  base lana-interface-type;
```

```
description
    "IEEE1394 High Performance Serial Bus.";
identity if-gsn {
  base lana-interface-type;
  description
    "HIPPI-6400.";
identity dvbRccMacLayer {
  base iana-interface-type;
  description
    "DVB-RCC MAC Layer.";
identity dvbRccDownstream {
  base lana-interface-type;
  description
    "DVB-RCC Downstream Channel.":
identity dvbRccUpstream {
  base iana-interface-type;
  description
    "DVB-RCC Upstream Channel.";
identity atmVirtual {
  base iana-interface-type;
  description
    "ATM Virtual Interface.";
identity mplsTunnel {
  base iana-interface-type;
  description
    "MPLS Tunnel Virtual Interface.";
identity srp {
  base iana-interface-type;
  description
    "Spatial Reuse Protocol.";
identity voiceOverAtm {
  base lana-interface-type;
  description
    "Voice over ATM.";
identity voiceOverFrameRelay {
  base iana-interface-type;
  description
    "Voice Over Frame Relay.";
}
```

**Standards Track** 

[Page 20]

```
identity idsl {
  base lana-interface-type;
  description
    "Digital Subscriber Loop over ISDN.";
identity compositeLink {
  base iana-interface-type;
  description
    "Avici Composite Link Interface.";
identity ss7SigLink {
  base lana-interface-type;
  description
    "SS7 Signaling Link.";
identity propWirelessP2P {
  base iana-interface-type;
  description
    "Prop. P2P wireless interface.";
identity frForward {
  base lana-interface-type;
  description
    "Frame Forward Interface.";
identity rfc1483 {
  base iana-interface-type;
  description
    "Multiprotocol over ATM AAL5.";
  reference
    "RFC 1483 - Multiprotocol Encapsulation over ATM
                Adaptation Layer 5";
identity usb {
  base iana-interface-type;
  description
    "USB Interface.";
identity ieee8023adLag {
  base iana-interface-type;
  description
    "IEEE 802.3ad Link Aggregate.";
identity bgppolicyaccounting {
  base iana-interface-type;
  description
    "BGP Policy Accounting.";
}
```

```
identity frf16MfrBundle {
  base lana-interface-type;
  description
    "FRF.16 Multilink Frame Relay.":
identity h323Gatekeeper {
  base iana-interface-type;
  description
    "H323 Gatekeeper.";
identity h323Proxy {
  base iana-interface-type;
  description
    "H323 Voice and Video Proxy.";
identity mpls {
  base iana-interface-type;
  description
    "MPLS.";
identity mfSigLink {
  base iana-interface-type;
  description
    "Multi-frequency signaling link.";
identity hdsl2 {
 base iana-interface-type;
  description
    "High Bit-Rate DSL - 2nd generation.";
identity shdsl {
  base iana-interface-type;
  description
    "Multirate HDSL2.";
identity ds1FDL {
  base iana-interface-type;
  description
    "Facility Data Link (4Kbps) on a DS1.";
identity pos {
  base iana-interface-type;
  description
    "Packet over SONET/SDH Interface.";
}
```

```
identity dvbAsiIn {
  base lana-interface-type;
  description
    "DVB-ASI Input.";
identity dvbAsiOut {
  base iana-interface-type;
  description
    "DVB-ASI Output.";
identity plc {
  base iana-interface-type;
  description
    "Power Line Communications.";
identity nfas {
  base lana-interface-type;
  description
    "Non-Facility Associated Signaling.";
identity tr008<sub>.</sub>{
  base lana-interface-type;
  description
    "TR008.";
identity gr303RDT {
  base iana-interface-type;
  description
    "Remote Digital Terminal.";
identity gr303IDT {
  base lana-interface-type;
  description
    "Integrated Digital Terminal.";
identity isup {
  base iana-interface-type;
  description
    "ISUP.";
identity propDocsWirelessMaclayer {
  base iana-interface-type;
  description
    "Cisco proprietary Maclayer.";
}
```

```
identity propDocsWirelessDownstream {
  base lana-interface-type;
  description
    "Cisco proprietary Downstream.";
identity propDocsWirelessUpstream {
  base iana-interface-type;
  description
    "Cisco proprietary Upstream.";
identity hiperlan2 {
  base iana-interface-type;
  description
    "HIPERLAN Type 2 Radio Interface.";
identity propBWAp2Mp {
  base iana-interface-type;
  description
    "PropBroadbandWirelessAccesspt2Multipt (use of this value
     for IEEE 802.16 WMAN interfaces as per IEEE Std 802.16f is deprecated, and ieee80216WMAN(237) should be used
     instead).";
identity sonetOverheadChannel {
  base lana-interface-type;
  description
    "SONET Overhead Channel.";
identity digitalWrapperOverheadChannel {
  base lana-interface-type;
  description
    "Digital Wrapper.";
identity aal2 {
  base iana-interface-type;
  description
    "ATM adaptation layer 2.";
identity radioMAC {
  base lana-interface-type;
  description
    "MAC layer over radio links.";
identity atmRadio {
  base lana-interface-type;
  description
    "ATM over radio links.";
}
```

```
identity imt {
  base iana-interface-type;
  description
    "Inter-Machine Trunks.";
identity mvl {
 base iana-interface-type;
  description
    "Multiple Virtual Lines DSL.";
identity reachDSL {
  base iana-interface-type;
  description
    "Long Reach DSL.";
identity frDlciEndPt {
  base iana-interface-type;
  description
    "Frame Relay DLCI End Point.";
identity atmVciEndPt {
  base iana-interface-type;
  description
    "ATM VCI End Point.";
identity opticalChannel {
 base iana-interface-type;
  description
    "Optical Channel.";
identity opticalTransport {
  base iana-interface-type;
  description
    "Optical Transport.";
identity propAtm {
  base iana-interface-type;
  description
    "Proprietary ATM.";
identity voiceOverCable {
  base iana-interface-type;
  description
    "Voice Over Cable Interface.";
}
```

```
identity infiniband {
  base iana-interface-type;
  description
    "Infiniband.";
identity teLink {
  base iana-interface-type;
  description
    "TE Link.";
identity q2931 {
  base iana-interface-type;
  description
    "Q.2931.";
identity virtualTg {
  base iana-interface-type;
  description
    "Virtual Trunk Group.";
identity sipTg {
  base iana-interface-type;
  description
    "SIP Trunk Group.";
identity sipSig {
  base iana-interface-type;
description
"SIP Signaling.";
identity docsCableUpstreamChannel {
  base iana-interface-type;
  description
    "CATV Upstream Channel.";
identity econet {
  base iana-interface-type;
  description
    "Acorn Econet.";
identity pon155 {
  base iana-interface-type;
  description
    "FSAN 155Mb Symetrical PON interface.";
}
```

```
identity pon622 {
 base lana-interface-type;
 description
    "FSAN 622Mb Symetrical PON interface.";
identity bridge {
 base iana-interface-type;
 description
    "Transparent bridge interface.";
identity linegroup {
 base iana-interface-type;
 description
    "Interface common to multiple lines.";
identity voiceEMFGD {
 base lana-interface-type;
 description
    "Voice E&M Feature Group D.";
identity voiceFGDEANA {
 base lana-interface-type;
 description
    "Voice FGD Exchange Access North American.";
identity voiceDID {
 base iana-interface-type;
 description
    "Voice Direct Inward Dialing.";
identity mpegTransport {
 base iana-interface-type;
 description
    "MPEG transport interface.";
identity sixToFour {
 base iana-interface-type;
 status deprecated;
 description
    "6to4 interface (DEPRECATED).";
 reference
    "RFC 4087 - IP Tunnel MIB";
identity gtp {
 base lana-interface-type;
 description
    "GTP (GPRS Tunneling Protocol).";
}
```

**Standards Track** 

[Page 27]

```
identity pdnEtherLoop1 {
  base lana-interface-type;
  description
    "Paradyne EtherLoop 1.";
identity pdnEtherLoop2 {
  base iana-interface-type;
  description
    "Paradyne EtherLoop 2.";
identity opticalChannelGroup {
  base iana-interface-type;
  description
    "Optical Channel Group.";
identity homepna {
  base lana-interface-type;
  description
    "HomePNA ITU-T G.989.";
identity gfp {
  base iana-interface-type;
  description
    "Generic Framing Procedure (GFP).";
identity ciscoISLvlan {
  base lana-interface-type;
  description
    "Layer 2 Virtual LAN using Cisco ISL.";
identity actelisMetaLOOP {
  base iana-interface-type;
  description
    "Acteleis proprietary MetaLOOP High Speed Link.";
identity fcipLink {
  base lana-interface-type;
  description
    "FCIP Link.";
identity rpr {
  base iana-interface-type;
  description
    "Resilient Packet Ring Interface Type.";
}
```

```
identity qam {
  base iana-interface-type;
  description
    "RF Qam Interface.";
identity lmp {
 base iana-interface-type;
  description
    "Link Management Protocol.";
  reference
    "RFC 4327 - Link Management Protocol (LMP) Management
                Information Base (MIB)";
identity cblVectaStar {
  base lana-interface-type;
  description
    "Cambridge Broadband Networks Limited VectaStar.";
identity docsCableMCmtsDownstream {
  base iana-interface-type;
  description
    "CATV Modular CMTS Downstream Interface.":
identity adsl2 {
  base lana-interface-type;
  status deprecated;
  description
     Asymmetric Digital Subscriber Loop Version 2
     (DEPRECATED/OBSOLETED - please use adsl2plus(238)
     instead).";
  reference
    "RFC 4706 - Definitions of Managed Objects for Asymmetric
                Digital Subscriber Line 2 (ADSL2)";
identity macSecControlledIF {
  base lana-interface-type;
  description
    "MACSecControlled.";
identity macSecUncontrolledIF {
  base lana-interface-type;
  description
    "MACSecUncontrolled.";
identity aviciOpticalEther {
  base lana-interface-type;
  description
    "Avici Optical Ethernet Aggregate.";
```

```
identity atmbond {
 base lana-interface-type;
 description
   "atmbond.";
identity voiceFGDOS {
 base lana-interface-type;
 description
    "Voice FGD Operator Services.";
identity mocaVersion1 {
 base lana-interface-type:
 description
    "MultiMedia over Coax Alliance (MoCA) Interface
     as documented in information provided privately to IANA.";
identity ieee80216WMAN {
 base lana-interface-type;
 description
    "IEEE 802.16 WMAN interface.";
identity adsl2plus {
 base iana-interface-type;
 description
    "Asymmetric Digital Subscriber Loop Version 2 -
    Version 2 Plus and all variants.";
identity dvbRcsMacLayer {
 base lana-interface-type;
 description
    "DVB-RCS MAC Layer.";
 reference
    "RFC 5728 - The SatLabs Group DVB-RCS MIB";
identity dvbTdm {
 base iana-interface-type;
 description
    "DVB Satellite TDM.";
 reference
   "RFC 5728 - The SatLabs Group DVB-RCS MIB";
identity dvbRcsTdma {
 base iana-interface-type:
 description
    "DVB-RCS TDMA.";
 reference
    "RFC 5728 - The SatLabs Group DVB-RCS MIB";
```

```
identity x86Laps {
  base lana-interface-type;
  description
    "LAPS based on ITU-T X.86/Y.1323.";
identity wwanPP {
  base iana-interface-type;
  description
    "3GPP WWAN.";
identity wwanPP2 {
 base iana-interface-type;
description
    "3GPP2 WWAN.";
identity voiceEBS {
  base lana-interface-type;
  description
    "Voice P-phone EBS physical interface.";
identity ifPwType [{
  base lana-interface-type;
  description
    "Pseudowire interface type.";
  reference
    "RFC 5601 - Pseudowire (PW) Management Information Base (MIB)";
identity ilan {
  base lana-interface-type;
  description
    "Internal LAN on a bridge per IEEE 802.1ap.";
identity pip {
  base iana-interface-type;
  description
    "Provider Instance Port on a bridge per IEEE 802.1ah PBB.";
identity aluELP {
  base iana-interface-type;
  description
    "Alcatel-Lucent Ethernet Link Protection.";
identity gpon {
  base iana-interface-type;
  description
    "Gigabit-capable passive optical networks (G-PON) as per
     ITŬ-T G.948.";
```

Standards Track

[Page 31]

```
identity vdsl2 {
  base lana-interface-type;
  description
    "Very high speed digital subscriber line Version 2
     (as per ITU-T Recommendation G.993.2).";
    "RFC 5650 - Definitions of Managed Objects for Very High
                Speed Digital Subscriber Line 2 (VDSL2)";
identity capwapDot11Profile {
  base iana-interface-type;
  description
    "WLAN Profile Interface.";
  reference
    "RFC 5834 - Control and Provisioning of Wireless Access
                Points (CAPWAP) Protocol Binding MIB for
                IEEE 802.11";
identity capwapDot11Bss {
  base iana-interface-type;
  description
    "WLAN BSS Interface.";
  reference
    "RFC 5834 - Control and Provisioning of Wireless Access
                Points (CAPWAP) Protocol Binding MIB for
                IEEE 802.11";
identity capwapWtpVirtualRadio {
  base lana-interface-type;
  description
    "WTP Virtual Radio Interface.";
  reference
    "RFC 5833 - Control and Provisioning of Wireless Access Points (CAPWAP) Protocol Base MIB";
base lana-interface-type;
  description
    "bitsport.";
identity docsCableUpstreamRfPort {
  base iana-interface-type;
  description
    "DOCSIS CATV Upstream RF Port.";
}
```

```
identity cableDownstreamRfPort {
  base lana-interface-type;
  description
    "CATV downstream RF Port.":
identity vmwareVirtualNic {
  base iana-interface-type;
  description
    "VMware Virtual Network Interface.";
identity ieee802154 {
  base lana-interface-type;
  description
    "IEEE 802.15.4 WPAN interface.";
  reference
    "IEEE 802.15.4-2006";
identity otnOdu {
  base lana-interface-type;
  description
    "OTN Optical Data Unit.";
identity otnOtu {
  base iana-interface-type;
  description
    "OTN Optical channel Transport Unit.";
identity ifVfiType {
  base iana-interface-type;
  description
    "VPLS Forwarding Instance Interface Type.";
identity g9981 {
  base lana-interface-type;
  description
    "G.998.1 bonded interface.";
identity g9982 {
  base iana-interface-type;
  description
    "G.998.2 bonded interface.";
identity g9983 {
  base lana-interface-type;
  description
    "G.998.3 bonded interface.";
}
```

```
identity aluEpon {
    base iana-interface-type;
    description
      "Ethernet Passive Optical Networks (E-PON).":
  identity aluEponOnu {
    base iana-interface-type;
    description
      "EPON Optical Network Unit.";
  identity aluEponPhysicalUni {
    base iana-interface-type;
    description
      "EPON physical User to Network interface.";
  identity aluEponLogicalLink {
    base iana-interface-type;
    description
      "The emulation of a point-to-point link over the EPON
       layer.";
  identity aluGponOnu {
    base lana-interface-type;
    description
      "GPON Optical Network Unit.";
    reference
      "ITU-T G.984.2";
  identity aluGponPhysicalUni {
    base iana-interface-type;
    description
      "GPON physical User to Network interface.";
    reference
      "ITU-T G.984.2";
  identity vmwareNicTeam {
    base iana-interface-type;
    description
      "VMware NIC Team.";
<CODE ENDS>
```

#### 3. IANA Considerations

This document defines the initial version of the IANA-maintained iana-if-type YANG module.

The iana-if-type YANG module is intended to reflect the "ifType definitions" registry [IFTYPE-IANA-REGISTRY], exactly like the IANAifType-MIB MIB module [IANAifType-MIB] reflects the "ifType definitions" registry.

IANA has added this new note to the "iana-if-type YANG Module" registry:

Interface types must not be directly added to the iana-if-type YANG module. They must instead be added to the "ifType definitions" registry.

When an interface type is added to the "ifType definitions" registry, a new "identity" statement must be added to the iana-if-type YANG module. The name of the "identity" is the same as the corresponding enumeration in the IANAifType-MIB. The following substatements to the "identity" statement should be defined:

"base": Contains the value "iana-interface-type".

"status": Include only if a registration has been deprecated (use the value "deprecated") or obsoleted (use the value "obsolete").

"description": Replicate the description from the registry, if any. Insert line breaks as needed so that the line does not exceed 72 characters.

"reference": Replicate the reference from the registry, if any, and add the title of the document.

Unassigned or reserved values are not present in the module.

When the iana-if-type YANG module is updated, a new "revision" statement must be added in front of the existing revision statements.

IANA has added this new note to the "ifType definitions" registry:

When this registry is modified, the YANG module iana-if-type must be updated as defined in RFC 7224.

The "Reference" text in the "ifType definitions" registry has been updated as:

OLD:

[RFC1213][RFC2863]

NEW:

[RFC1213][RFC2863][RFC7224]

## 3.1. URI Registrations

This document registers a URI in the "IETF XML" registry [RFC3688]. Following the format in RFC 3688, the following registration has been made.

URI: urn:ietf:params:xml:ns:yang:iana-if-type

Registrant Contact: IANA.

XML: N/A; the requested URI is an XML namespace.

## 3.2. YANG Module Registrations

This document registers a YANG module in the "YANG Module Names" registry [RFC6020].

name: iana-if-type

namespace: urn:ietf:params:xml:ns:yang:iana-if-type

prefix: ianaift reference: RFC 7224

### 4. Security Considerations

Since this document does not introduce any technology or protocol, there are no security issues to be considered for this document itself.

### 5. Normative References

## [IANAifType-MIB]

Internet Assigned Numbers Authority, "IANAifType Textual
Convention definitions",
<http://www.iana.org/assignments/ianaiftype-mib>.

## [IFTYPE-IANA-REGISTRY]

Internet Assigned Numbers Authority, "ifType Definitions",
<http://www.iana.org/assignments/smi-numbers>.

[RFC3688] Mealling, M., "The IETF XML Registry", BCP 81, RFC 3688, January 2004.

[RFC6020] Bjorklund, M., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", RFC 6020, October 2010.

[RFC7223] Bjorklund, M., "A YANG Data Model for Interface Management", RFC 7223, May 2014.

#### **Author's Address**

Martin Bjorklund Tail-f Systems

EMail: mbj@tail-f.com