NWG/RFC# 717 JBP 30-JUN-76 16:58 35873 Assigned Network Numbers

Network Working Group Jon Postel Request for Comments 717 SRI-ARC NIC 35873 1 July 1976

**Assigned Network Numbers** 

This note specifies the numbers assigned to identify networks for use in the inter-network protocol experiments. Additional Numbers are assigned by Jon Postel [POSTEL@ISIC or (415) 326-6200 x3718].

## **Assigned Network Numbers**

NameDecimal	0ctal	
BBNRCCnet 3 SanFranPRnet ARPANET 10 BostonPRnet	3 3 7 7 12 11 13	

## Internetwork Header Format

For convenience the current Internetwork protocol header and TCP headers are reproduced here:

Octet Bit Use (Width)

--- Beginning of protocol-independent information ---

```
ODestination net (8)
1-3Destination host (24)
4Source net (8)
5-7Source host (24)
8-9Data length in octets (16)
10Header length in octets (8)
11 0-3Format (4)
This field selects the appropriate gateway processing and is used to dispatch the packet to the appropriate protocol module in the destination. The following values are defined for this field:
0 -- Escape; protocol is specified by a subsequent field
1 -- TCP
2 -- Secure TCP
3-16 -- Not allocated
17 -- Cross internet debugging
--- End of protocol-independent information
```

```
--- Beginning of TCP specific information ---
     4-7Protocol version (4)
12-15Sequence number (32)
16-17Window (16)
18-20Control (as before) (24)
21-23Destination port (24)
24Packet label for debugging(8)
25-27Source port (24)
28-31Acknowledgement number (32)
32-33Checksum (16)
34-Data
--- End of TCP specific information ---
--- Beginning of short TCP specific information ---
     4-7Protocol Version (4)
12-25Sequence number (32)
16Destination KID (8)
17Source KID (8)
18-19Control (no special function field)(16)
20-Data
--- End of short TCP specific information ---
```