Internet Engineering Task Force (IETF)

Request for Comments: 7128

Category: Informational ISSN: 2070-1721

R. Bush
Internet Initiative Japan
R. Austein
Dragon Research Labs
K. Patel
Cisco Systems
H. Gredler
Juniper Networks, Inc.
M. Waehlisch
FU Berlin
February 2014

Resource Public Key Infrastructure (RPKI) Router Implementation Report
Abstract

This document is an implementation report for the Resource Public Key Infrastructure (RPKI) Router protocol as defined in RFC 6810. The authors did not verify the accuracy of the information provided by respondents. The respondents are experts with the implementations they reported on, and their responses are considered authoritative for the implementations for which their responses represent. The respondents were asked to only use the "YES" answer if the feature had at least been tested in the lab.

Status of This Memo

This document is not an Internet Standards Track specification; it is published for informational purposes.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Not all documents approved by the IESG are a candidate for any level of Internet Standard; see Section 2 of RFC 5741.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at http://www.rfc-editor.org/info/rfc7128.

Bush, et al. Informational [Page 1]

Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (http://trustee.ietf.org/license-info) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	•			•				•	•				•	•	•	•	2
2.	Implementation Forms				•				•	•				•	•		•	3
3.	Protocol Data Units																•	4
4.	Protocol Sequence																	6
5 .	Protocol Transport	•		•	•				•	•				•	•	•	•	7
6.	Error Codes	•			•				•						•	•	•	7
7.	Incremental Updates Suppo	rt			•	•			•	•	•	•	•	•	•	•	•	8
8.	Session ID Support	•		•	•	•			•	•	•	•	•	•	•	•	•	8
9.	Incremental Session Start																	8
	Interoperable Implementat																	9
	0.1. Cisco Implementation																	9
	0.2. Juniper Implementati			•	•	•	•		•	•	•	•	•	•	•	•	•	9
	0.3. rpki.net Implementat			•	•	•	•		•	•	•	•	•	•	•	•	•	9
	0.4. RIPE NCC Implementat			•														9
	0.5. RTRlib Implementation																	9
	0.6. BBN RPSTIR Implement																	9
	Security Considerations .																•	9
	Acknowledgements	•	•	•	•	•	•	• •	•	•	•	•	•	•	•	•	•	10
13.	Normative References																	10

1. Introduction

In order to formally validate the origin Autonomous Systems (ASes) of BGP announcements, routers need a simple but reliable mechanism to receive Resource Public Key Infrastructure (RPKI) [RFC6810] prefix origin data from a trusted cache. The RPKI Router protocol defined in [RFC6810] provides a mechanism to deliver validated prefix origin data to routers.

This document provides an implementation report for the RPKI Router protocol as defined in RFC 6810 [RFC6810].

The authors did not verify the accuracy of the information provided by respondents or by any alternative means. The respondents are experts with the implementations they reported on, and their responses are considered authoritative for the implementations for which their responses represent. Respondents were asked to only use the "YES" answer if the feature had at least been tested in the lab.

2. **Implementation Forms**

Contact and implementation information for person filling out this form:

IOS

Name: Keyur Patel

Email: keyupate@cisco.com Vendor: Cisco Systems, Inc. Release: IOS Protocol Role: Client

XR

Name: Forhad Ahmed

Email: foahmed@cisco.com Vendor: Cisco Systems, Inc.

Release: IOS-XR Protocol Role: Client

JUNOS

Name: Hannes Gredler

Email: hannes@juniper.net

Vendor: Juniper Networks, Inc.

Release: JUNOS

Protocol Role: Client

rpki.net

Name: Rob Austein Email: sra@hactrn.net Vendor: rpki.net project

Release: http://subvert-rpki.hactrn.net/trunk/>

Protocol Role: Client, Server

NCC

Name: Tim Bruijnzeels Email: tim@ripe.net Vendor: RIPE NCC

Release: RIPE NCC validator-app 2.0.0 https://github.com/RIPE-NCC

/rpki-validator>

Protocol Role: Server

RTRlib

Name: Fabian Holler, Matthias Waehlisch

Email: waehlisch@ieee.org

Vendor: HAW Hamburg, FU Berlin, RTRlib project
Release: RTRlib 0.2 http://rpki.realmv6.org/

Protocol Role: Client

BBN

Name: David Mandelberg, Andrew Chi

Email: dmandelb@bbn.com

Vendor: Raytheon/BBN Technologies

Release: RPSTIR 0.2 http://sourceforge.net/projects/rpstir/>

Protocol Role: Server

3. Protocol Data Units

Does the implementation support Protocol Data Units (PDUs) as described in Section 5 of [RFC6810]?

PO: Serial Notify

P1: Serial Query

P2: Reset Query

P3: Cache Response

P4: IPv4 Prefix

P6: IPv6 Prefix

P7: End of Data

P8: Cache Reset

P10: Error Report

	IOS	XR	JUN0S	rpki .net clnt	rpki .net srvr	NCC	RTR-	BBN
Rcv.P0 Snd.P0 Rcv.P1 Snd.P1 Rcv.P2 Snd.P2 Rcv.P3 Snd.P3 Rcv.P4 Snd.P4 Rcv.P6 Snd.P6 Rcv.P7 Snd.P7 Snd.P7 Rcv.P8 Snd.P8 Rcv.P10 Snd.P10	YES	YES	YES YES YES YES YES YES YES N0~1	YES	YES	YES	YES	YES

Note 1: No, Error PDU gets silently ignored.

4. Protocol Sequence

Does the RPKI Router protocol implementation follow the four protocol sequences as outlined in Section 6 of [RFC6810]?

Start or Restart **S1:**

S2: **Typical Exchange**

No Incremental Update Available S3:

Cache Has No Data Available S4:

+	IOS	XR	JUN0S	rpki .net clnt	rpki .net srvr	NCC	RTRlib	BBN
S1	YES	YES	YES	YES	YES	YES	YES	YES
S2	YES	YES	YES	YES	YES	NO~1	YES	YES
S3	YES	YES	YES	YES	YES	YES	YES	YES
S4	YES	YES	YES	YES	YES	YES	YES	YES~2

Note 1: Does not implement Serial Query, thus Incremental Update is never available, so responds to Serial Query with Cache Reset as described in Section 6.3 of [RFC6810]

Sends Cache Reset in response to Serial Query when no data; Note 2: sends Error Report PDU in response to Reset Query when no data.

5. Protocol Transport

Does the RPKI Router protocol implementation support the different protocol transport mechanisms outlined in Section 7 of [RFC6810]?

	L			L	L	L		L	L	L
		105	XR	JUNOS	rpki .net clnt	rpki .net srvr	NCC	RTRlib	BBN	
_	SSH TLS TCP TCP-MD5 TCP-A0 IPsec	NO NO YES NO NO	YES NO YES NO NO	NO NO YES NO NO	YES NO YES NO NO	YES NO YES NO NO	NO NO YES NO NO	YES NO YES NO NO	YES NO YES NO NO	

6. Error Codes

Does the RPKI Router protocol implementation support the different protocol error codes outlined in Section 10 of [RFC6810]?

	IOS	XR	JUNOS	rpki .net clnt	rpki .net srvr	NCC	RTRlib	BBN
Rcv.0 Snd.0 Rcv.1 Snd.1 Rcv.2 Snd.2 Rcv.3 Snd.3 Rcv.4 Snd.4 Rcv.5 Snd.5 Rcv.6 Snd.7	YES	YES	NO NO NO NO NO NO NO NO NO NO NO	YES	YES	YES	YES	YES

Note 1: YES, but... fatal, so connection is dropped, but cache does not conclude it's inconsistent.

Bush, et al.

Informational

[Page 7]

7. Incremental Updates Support

Does the RPKI Router implementation support Incremental Updates as defined in Section 4 of [RFC6810]?

-	•	XR	JUNOS	rpki.net clnt	rpki.net srvr	NCC	RTRlib	BBN	
	NO		YES	YES	YES	NO		YES	

8. Session ID Support

Session ID is used to indicate that the cache server may have restarted and that the incremental restart may not be possible.

Does the RPKI Router protocol implementation support the Session ID procedures outlined in Section 5.1 of [RFC6810]?

IOS	XR	•	rpki.net clnt	•	•	•	•	•
YES	YES	YES		YES	N0~1	YES	YES	i

Note 1: NO, using random, but will FIX

9. Incremental Session Startup Support

Does the RPKI Router protocol implementation support Incremental session startups with Serial Number and Session ID as defined in Section 5.3 of [RFC6810]?

IOS	XR	JUNOS	rpki.net clnt	rpki.net srvr	NCC	RTRlib	BBN
T	r	YES	YES	YES	r	YES	

10. Interoperable Implementations

List other implementations with which you have tested the interoperability of the RPKI Router implementation.

10.1. Cisco Implementation

Cisco: The Cisco IOS and IOS-XR implementation should be interoperable with other vendor RPKI Router Protocol implementations. In particular, we have tested our interoperability with rpki.net's RPKI Router implementation.

10.2. Juniper Implementation

Juniper: The Juniper Networks, Inc. JUNOS implementation should be interoperable with other vendor RPKI Router Protocol implementations. In particular, we have tested our interoperability with rpki.net's and NCC's RPKI Router Cache implementation.

10.3. rpki.net Implementation

rpki.net: The rpki.net implementation should operate with other rpkirtr implementations. In particular, we have tested our rpki-rtr server's interoperability with Cisco IOS, Cisco IOS-XR, and Juniper.

10.4. RIPE NCC Implementation

RIPE NCC: The RIPE NCC validator has been tested by us with other rpki-rtr implementations. In particular, we have tested with RTRlib and CISCO IOS. We received positive feedback from close contacts who tested our validator with JUNOS and Quagga.

10.5. RTRlib Implementation

RTRlib: The RTRlib has been tested by us with other rpki-rtr implementations. In particular, we have tested with rtr-origin from rpki.net and RIPE NCC Validator.

10.6. BBN RPSTIR Implementation

BBN RPSTIR: We have not yet tested with any other implementations.

11. Security Considerations

No new security issues are introduced to the RPKI Router protocol defined in [RFC6810].

Bush, et al. Informational [Page 9]

12. Acknowledgements

The authors would like to thank Andrew Chi, David Mandelberg, Fabian Holler, Forhad Ahmed, and Tim Bruijnzeels for their contributions to this document.

13. Normative References

Bush, R. and R. Austein, "The Resource Public Key Infrastructure (RPKI) to Router Protocol", RFC 6810, [RFC6810] January 2013.

Authors' Addresses

Randy Bush Internet Initiative Japan 5147 Crystal Springs Bainbridge Island, Washington 98110 US

EMail: randy@psg.com

Rob Austein Dragon Research Labs

EMail: sra@hactrn.net

Keyur Patel Cisco Systems 170 West Tasman Drive San Jose, California 95134

EMail: keyupate@cisco.com

Hannes Gredler Juniper Networks, Inc. 1194 N. Mathilda Ave. Sunnyvale, California 94089 US

EMail: hannes@juniper.net

Matthias Waehlisch FU Berlin Takustr. 9 Berlin 14195 Germany

EMail: waehlisch@ieee.org

URI: http://www.inf.fu-berlin.de/~waehl