Network Working Group Request for Comments: 2013

Updates: 1213

Category: Standards Track

K. McCloghrie, Editor Cisco Systems November 1996

SNMPv2 Management Information Base for the User Datagram Protocol using SMIv2

Status of this Memo

This document specifies an Internet standards track protocol for the Internet community, and requests discussion and suggestions for improvements. Please refer to the current edition of the "Internet Official Protocol Standards" (STD 1) for the standardization state and status of this protocol. Distribution of this memo is unlimited.

IESG Note:

The IP, UDP, and TCP MIB modules currently support only IPv4. These three modules use the IpAddress type defined as an OCTET STRING of length 4 to represent the IPv4 32-bit internet addresses. (See RFC 1902, SMI for SNMPv2.) They do not support the new 128-bit IPv6 internet addresses.

Table of Contents

1. Introduction														
2. Definitions														
2.1 The UDP Group	 									• (•		
2.2 Conformance Information										• (
2.2.1 Compliance Statements														
2.2.2 Units of Conformance	 													
3. Acknowledgements	 									• (•		
4. References	 									• (
5. Security Considerations	 													
6. Editor's Address	 	 	 				 						 	

1. Introduction

A management system contains: several (potentially many) nodes, each with a processing entity, termed an agent, which has access to management instrumentation; at least one management station; and, a management protocol, used to convey management information between the agents and management stations. Operations of the protocol are carried out under an administrative framework which defines authentication, authorization, access control, and privacy policies.

McCloghrie

Management stations execute management applications which monitor and control managed elements. Managed elements are devices such as hosts, routers, terminal servers, etc., which are monitored and controlled via access to their management information.

Management information is viewed as a collection of managed objects, residing in a virtual information store, termed the Management Information Base (MIB). Collections of related objects are defined in MIB modules. These modules are written using a subset of OSI's Abstract Syntax Notation One (ASN.1) [1], termed the Structure of Management Information (SMI) [2].

This document is the MIB module which defines managed objects for managing implementations of the User Datagram Protocol (UDP) [3].

The managed objects in this MIB module were originally defined using the SNMPv1 framework as a part of MIB-II [4]. This document defines the same objects for UDP using the SNMPv2 framework.

2. Definitions

UDP-MIB DEFINITIONS ::= BEGIN

IMPORTS

MODULE-IDENTITY, OBJECT-TYPE, Counter32,
IpAddress, mib-2 FROM SNMPv2-SMI
MODULE-COMPLIANCE, OBJECT-GROUP FROM SNMPv2-CONF;

udpMIB MODULE-IDENTITY

LAST-UPDATED "9411010000Z"

ORGANIZATION "IETF SNMPv2 Working Group"

CONTACT-INFO

Keith McCloghrie

Postal: Cisco Systems, Inc.

170 West Tasman Drive San Jose, CA 95134-1706

IIS

Phone: +1 408 526 5260 Email: kzm@cisco.com"

```
DESCRIPTION
            "The MIB module for managing UDP implementations."
    REVISION
                  "9103310000Z"
    DESCRIPTION
            "The initial revision of this MIB module was part of MIB-
            II."
    ::= { mib-2 50 }
-- the UDP group
         OBJECT IDENTIFIER ::= { mib-2 7 }
udpInDatagrams OBJECT-TYPE
    SYNTAX
                Counter32
    MAX-ACCESS
              read-only
    STATUS
                current
    DESCRIPTION
            "The total number of UDP datagrams delivered to UDP users."
    ::= { udp 1 }
udpNoPorts OBJECT-TYPE
    SYNTAX
                Counter32
    MAX-ACCESS
                read-only
    STATUS
                current
    DESCRIPTION
            "The total number of received UDP datagrams for which there
    was no application at the destination port."
::= { udp 2 }
udpInErrors OBJECT-TYPE
                Counter32
    SYNTAX
    MAX-ACCESS
                read-only
    STATUS
                current
    DESCRIPTION
            "The number of received UDP datagrams that could not be
            delivered for reasons other than the lack of an application
            at the destination port."
    ::= { udp 3 }
udpOutDatagrams OBJECT-TYPE
                Counter32
    SYNTAX
    MAX-ACCESS read-only
                current
    STATUS
    DESCRIPTION
            "The total number of UDP datagrams sent from this entity."
    ::= \{ udp 4 \}
```

```
-- the UDP Listener table
-- The UDP listener table contains information about this
-- entity's UDP end-points on which a local application is
-- currently accepting datagrams.
udpTable OBJECT-TYPE
                 SEQUENCE OF UdpEntry
    SYNTAX
    MAX-ACCESS
                not-accessible
    STATUS
                 current
    DESCRIPTION
             "A table containing UDP listener information."
    ::= { udp 5 }
udpEntry OBJECT-TYPE
    SYNTAX
                 UdpEntry
    MAX-ACCESS not-accessible
    STATUS
                 current
    DESCRIPTION
             "Information about a particular current UDP listener." { udpLocalAddress, udpLocalPort }
    ::= { udpTable 1 }
UdpEntrv ::= SEOUENCE {
         udpLocalAddress
                           IpAddress.
         udpLocalPort
                           INTEGER
    }
udpLocalAddress OBJECT-TYPE
                 IpAddress
    SYNTAX
    MAX-ACCESS read-only
                 current
    STATUS
    DESCRIPTION
             "The local IP address for this UDP listener. In the case of a UDP listener which is willing to accept datagrams for any
             IP interface associated with the node, the value 0.0.0.0 is
             used."
    ::= { udpEntry 1 }
udpLocalPort OBJECT-TYPE
                 INTEGER (0..65535)
    SYNTAX
    MAX-ACCESS read-only
                 current
    STATUS
    DESCRIPTION
             "The local port number for this UDP listener."
    ::= { udpEntry 2 }
```

```
-- conformance information
udpMIBConformance OBJECT IDENTIFIER ::= { udpMIB 2 }
udpMIBCompliances OBJECT IDENTIFIER ::= { udpMIBConformance 1 }
                  OBJECT IDENTIFIER ::= { udpMIBConformance 2 }
udpMIBGroups
-- compliance statements
udpMIBCompliance MODULE-COMPLIANCE
    STATUS
           current
    DESCRIPTION
            "The compliance statement for SNMPv2 entities which
            implement UDP.'
    MODULE
           -- this module
        MANDATORY-GROUPS { udpGroup
    ::= { udpMIBCompliances 1 }
-- units of conformance
udpGroup OBJECT-GROUP
    OBJECTS
             { udpInDatagrams, udpNoPorts,
                udpInErrors, udpOutDatagrams,
                udpLocalAddress, udpLocalPort }
    STATUS
              current
    DESCRIPTION
            "The udp group of objects providing for management of UDP
            entities.
    ::= { udpMIBGroups 1 }
END
```

3. Acknowledgements

This document contains a modified subset of RFC 1213.

4. References

- [1] Information processing systems Open Systems Interconnection Specification of Abstract Syntax Notation One (ASN.1), International Organization for Standardization. International Standard 8824, (December, 1987).
- [2] McCloghrie, K., Editor, "Structure of Management Information for version 2 of the Simple Network Management Protocol (SNMPv2)", RFC 1902, Cisco Systems, January 1996.
- [3] Postel, J., "User Datagram Protocol", STD 6, RFC 768, USC-ISI, August 1980.
- [4] McCloghrie, K., and Rose, M., "Management Information Base for Network Management of TCP/IP-based internets: MIB-II", STD 17, RFC 1213, March 1991.

5. Security Considerations

Security issues are not discussed in this memo.

6. Editor's Address

Keith McCloghrie Cisco Systems, Inc. 170 West Tasman Drive San Jose, CA 95134-1706 US

Phone: +1 408 526 5260 EMail: kzm@cisco.com