

## Remote Monitoring MIB Extensions for Differentiated Services

### Status of this Memo

This document specifies an Internet standards track protocol for the Internet community, and requests discussion and suggestions for improvements. Please refer to the current edition of the "Internet Official Protocol Standards" (STD 1) for the standardization state and status of this protocol. Distribution of this memo is unlimited.

### Copyright Notice

Copyright (C) The Internet Society (2002). All Rights Reserved.

### Abstract

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes managed objects used for monitoring Differentiated Services (DS) Codepoint usage in packets which contain a DS field, utilizing the monitoring framework defined in the RMON-2 (Remote Network Monitoring Management Version 2) MIB.

### Table of Contents

1 The SNMP Network Management Framework .....	2
2 Overview .....	3
2.1 Terms .....	4
2.2 Relationship to Differentiated Services .....	4
2.3 Relationship to the Remote Monitoring MIBs .....	5
3 MIB Structure .....	6
3.1 DSCP Counter Aggregation .....	7
3.1.1 Counter Aggregation Configuration .....	8
3.2 MIB Group Overview .....	8
3.2.1 DSCP Counter Aggregation Control Group .....	9
3.2.2 DS Statistics Group .....	10
3.2.3 DS Protocol Distribution Group .....	10
3.2.4 DS Host Distribution Group .....	11
3.2.5 DSMON Capabilities Group .....	12
3.2.6 DS Matrix Distribution Group .....	13
3.3 RMON vs. DSMON Indexing Structure .....	13
4 Definitions .....	16

5 Counter Aggregation Configuration Usage Examples .....	108
5.1 Step 1: Unlock the Counter Aggregation Configuration .....	109
5.2 Step 2: Check the Maximum number of Counter Aggregation Groups .....	109
5.3 Step 3: Check if the counter aggregation profiles already exist .....	109
5.4 Step 4: Create the Counter Aggregation Control Entries .....	109
5.5 Step 5: Create the Counter Aggregation Group Descriptions .....	110
5.6 Step 6: Create the Counter Aggregation Profile Mappings .....	112
5.7 Step 7: Lock the Counter Aggregation Configuration .....	115
6 Intellectual Property .....	115
7 Acknowledgements .....	116
8 References .....	116
9 Security Considerations .....	118
10 Author's Address .....	119
11 Full Copyright Statement .....	120

## 1. The SNMP Network Management Framework

The SNMP Management Framework presently consists of five major components:

- o An overall architecture, described in RFC 2571 [RFC2571].
- o Mechanisms for describing and naming objects and events for the purpose of management. The first version of this Structure of Management Information (SMI) is called SMIV1 and is described in STD 16, RFC 1155 [RFC1155], STD 16, RFC 1212 [RFC1212] and RFC 1215 [RFC1215]. The second version, called SMIV2, is described in STD 58, RFC 2578 [RFC2578], RFC 2579 [RFC2579] and RFC 2580 [RFC2580].
- o Message protocols for transferring management information. The first version of the SNMP message protocol is called SNMPv1 and is described in STD 15, RFC 1157 [RFC1157]. A second version of the SNMP message protocol, which is not an Internet standards track protocol, is called SNMPv2c and is described in RFC 1901 [RFC1901] and RFC 1906 [RFC1906]. The third version of the message protocol is called SNMPv3 and is described in RFC 1906 [RFC1906], RFC 2572 [RFC2572] and RFC 2574 [RFC2574].
- o Protocol operations for accessing management information. The first set of protocol operations and associated PDU formats is described in STD 15, RFC 1157 [RFC1157]. A second set of protocol operations and associated PDU formats is described in RFC 1905 [RFC1905].

- o A set of fundamental applications described in RFC 2573 [RFC2573] and the view-based access control mechanism described in RFC 2575 [RFC2575].

A more detailed introduction to the current SNMP Management Framework can be found in RFC 2570 [RFC2570].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. Objects in the MIB are defined using the mechanisms defined in the SMI.

This memo specifies a MIB module that is compliant to the SMIV2. A MIB conforming to the SMIV1 can be produced through the appropriate translations. The resulting translated MIB must be semantically equivalent, except where objects or events are omitted because no translation is possible (use of Counter64). Some machine readable information in SMIV2 will be converted into textual descriptions in SMIV1 during the translation process. However, this loss of machine readable information is not considered to change the semantics of the MIB.

## 2. Overview

There is a need for a standardized way of monitoring the network traffic usage of Differentiated Services (DS) [RFC2474] codepoint values. Each DS codepoint (DSCP) value may be given a different treatment by a forwarding device, and this affects which packets get dropped or delayed during periods of network congestion.

The IETF DIFFSERV working group has redefined the semantics of the Type of Service (TOS) octet in the IP header, which is now called the 'DS field'. The 6-bit Codepoint (DSCP) portion is contained in the DS field, which provides for 64 different packet treatments for the implementation of differentiated network services.

By polling DSCP usage counters, an NMS can determine the network throughput for traffic associated with different DSCPs. This data can then be analyzed in order to 'tune' DSCP 'allocations' within a network, based on the Quality of Service (QoS) policies for that network.

Remote monitoring agents are typically implemented as independent software (and sometimes hardware) components, called 'RMON probes'. Note that DSMON-capable RMON probes simply collect and aggregate statistics, based on criteria (which includes the DSCP value) that can be determined by inspecting the contents of monitored packets and do not in any way monitor any aspect of a DS forwarding device's internal statistics.

## 2.1. Terms

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14, RFC 2119. [RFC2119]

This document uses some terms that need introduction:

### DataSource

A source of data for monitoring purposes. This term is used exactly as defined in the RMON-2 MIB [RFC2021].

### protocol

A specific protocol encapsulation, as identified for monitoring purposes. This term is used exactly as defined in the RMON Protocol Identifiers document [RFC2074].

### Counter Aggregation Group

A group of statistical counters that are being combined in the agent to produce one aggregated counter. Refer to sections 3.1 and 3.2.1 for details on counter aggregation groups.

### Counter Aggregation Profile

Also called 'profile'; A complete set of counter aggregation group mappings for DSCP values (i.e., 64 mappings, for each DSCP values 0 to 63), which are applied to all monitored packets on a particular data source and/or DSMON collection. Refer to sections 3.1 and 3.2.1 for details on counter aggregation profiles.

### High Capacity Monitoring

The generic capability to collect and store statistics with an internal range of 64 bits (e.g., Counter64). This term does not refer to implementation of the High Capacity RMON MIB [RFC3273].

## 2.2. Relationship to Differentiated Services

The DSMON MIB is a product of the RMONMIB WG, not the DIFFSERV WG, and it focuses on extending several existing RMON mechanisms to support additional packet classification, based on DSCP values observed in monitored packets. This document assumes the reader is familiar with the DS Architecture [RFC2475].

It is expected that complex management applications will use the counters in this MIB to help analyze DS-related throughput. It is expected that other metrics, such as delay and jitter, will also be analyzed, but support for other metrics is outside the scope of this document.

### 2.3. Relationship to the Remote Monitoring MIBs

This MIB is intended to be implemented in Remote Monitoring (RMON) probes, which support the RMON-2 MIB [RFC2021]. Such probes may be stand-alone devices, or may be co-located with other networking devices (e.g., ethernet switches and repeaters).

The DSMON functions are intended to be implemented in conjunction with the associated RMON functions, but the MIB is independent of all other RMON data tables.

Several concepts and even MIB objects from the RMON MIBs are used in the DSMON MIB:

#### Protocol Directory

The RMON-2 MIB [RFC2021] defines the `protocolDirTable`, which is a directory of all the protocols that the RMON-2 agent is capable of decoding and counting. The DSMON MIB utilizes this directory to identify the protocols detected in monitored packets. The `protocolDirLocalIndex` MIB object is used to identify protocol encapsulations in all DSMON data tables which classify and aggregate by protocol type in some manner. Note that the `protocolDirTable` is used for protocol identification only, independent of DSCP classification.

#### TimeFilter

The RMON-2 TimeFilter textual convention provides a mechanism to retrieve only rows which have been created or modified since the last polling interval (for a particular NMS). The DSMON MIB uses this textual convention in the large data tables, in order to minimize polling impact.

#### Zero-Based Counters

Since counters are instantiated by management action, as in the RMON MIBs, the DSMON MIB uses zero-based counters in all data collection tables. Specifically, the `ZeroBasedCounter32` textual convention from the RMON-2 MIB [RFC2021] and the `ZeroBasedCounter64` textual convention (defined in the HCNM-TC MIB [RFC2856]) are used to define counter objects in this MIB.

#### High Capacity Counters

The DSMON MIB uses the 'SNMPv1 coexistence' strategy adopted by the RMONMIB WG. That is, where a 64-bit counter is provided, a 32-bit version of the counter, and a 32-bit overflow counter are also provided.


### TopN Reports

The DSMON MIB uses the same TopN reporting MIB structure as the RMON-2 MIB [RFC2021]. TopN reporting can greatly reduce the polling overhead required to analyze DSCP usage patterns.

Some DESCRIPTION clauses for DSMON objects are very similar to those for existing RMON-2 or HC-RMON objects. This is intentional, since the semantics of the DSMON features are designed to be as close to existing RMON feature as possible, to allow developers and users some level of 'MIB re-use'.

## 3. MIB Structure

Figure 1: DSMON MIB Functional Structure



The DSMON MIB can be divided into three functional components:

- **DSMON Capabilities**  
Describes which DSMON object groups are supported by the agent on at least one data source.
- **Counter Aggregation Control**  
Controls how individual DIFFSERV codepoint counters are aggregated in DSMON data collections.
- **Data Collection**  
Controls how individual statistical collections are maintained by the agent and reported to management applications. The individual boxes within the Data Collection box represent the DSMON data collections (described in section 3.2):
  - Data Source Statistics
  - Protocol Statistics
  - Protocol Statistics TopN Reporting
  - Network Protocol Host Statistics
  - Network Protocol Host Statistics TopN Reporting
  - Application Protocol Matrix Statistics
  - Application Protocol Matrix Statistics TopN Reporting

### 3.1. DSCP Counter Aggregation

A mechanism to configure the agent to internally aggregate counters is provided, based on DSCP values. This is desirable for several reasons:

- **agent data reduction**  
An agent implementation can potentially reduce the number of counters maintained for a given DSMON collection.
- **agent data collection limitations**  
Some implementation strategies might provide for a limited number of high-speed (e.g., hardware-based) counters for either single or aggregated codepoints.
- **application data retrieval reduction**  
Applications that would otherwise aggregate counters for individual codepoints can move that function to the agent in order to reduce the polling overhead on the application, the network, and the agent device.
- **some unused codepoints at this time**  
Various DSCP values may be expected to remain unused on a given network, and may be aggregated for counting purposes.

- some DSCP values are mapped to the same packet treatment  
A network administrator may align the counter aggregation configuration of the monitoring device with the DS configuration, and aggregate statistics for DSCP values which are expected to receive the same treatment by the forwarding devices.

### 3.1.1. Counter Aggregation Configuration

The configuration of DSCP counter to counter aggregation group mappings is managed in a global manner, so that these settings can be shared across several DSMON collections and/or data sources. One complete set of DSCP counter mappings is called a counter aggregation profile. The DSMON control tables are very similar to existing RMON-2 control tables, except they contain an extra parameter to identify the counter aggregation profile the agent should use for the collection.

The appropriate granularity for counter aggregation profile assignment may be the data source, but in order to reduce MIB complexity (by avoiding an extra layer of tables), an instance of the counter aggregation profile parameter exists for each collection. An agent MAY choose to restrict configurations such that all DSMON data collections for the same data source must use the same counter aggregation profile.

The DSMON MIB supports the configuration of an arbitrary number of counter aggregation profiles. There is a top-level counter aggregation control table, which contains one entry for each counter aggregation profile. A subordinate counter aggregation profile table provides information about each DSCP counter to counter aggregation group mapping in each profile. An auxiliary counter aggregation group table also provides descriptive information about each counter aggregation group in each profile. Refer to section 3.2.1 for details on these MIB objects.

### 3.2. MIB Group Overview

The DSMON MIB contains six groups of MIB objects:

- dsmonAggregateControl group  
Controls the configuration of counter aggregation groups for the purpose of reducing the total number of counters maintained by the agent.
- dsmonStatsObjects group  
Report per counter aggregation group distribution statistics for a particular RMON dataSource.



- **dsmonPdistObjects group**  
Report per counter aggregation group distribution statistics for each application protocol detected on a particular RMON dataSource.
- **dsmonHostObjects group**  
Report host address distribution statistics for each counter aggregation group, detected on a particular RMON dataSource.
- **dsmonCapsObjects group**  
Report the static DSMON MIB functional capabilities of the agent implementation.
- **dsmonMatrixObjects group**  
Report host address pair distribution statistics for each counter aggregation group, detected on a particular RMON dataSource.

### 3.2.1. DSCP Counter Aggregation Control Group

This group contains 4 scalar objects and three tables, and is used by a management station to configure counter aggregation profiles.

The **dsmonMaxAggGroups** scalar is a read-only integer which indicates the maximum number of counter aggregation groups that the agent will allow to be configured into a single aggregation profile. This value **SHOULD** be equal to 64 (the number of codepoints), but an agent **MAY** limit the number of counter aggregation groups because of resource limitations (e.g., small number of hardware-based counters). At least one counter aggregation profile containing at least two counter aggregation groups **SHOULD** be supported by the agent. (Note that classifying all DSCP counters into the same statistical 'bucket' may yield a redundant data collection, which can be achieved more easily with an HC-RMON or RMON-2 collection instead.)

The **dsmonAggControlLocked** scalar is used as a top level switch, controlling most write access to the **dsmonAggControlTable**, **dsmonAggProfileTable**, and **dsmonAggGroupTable**. (The **dsmonAggControlOwner** object is the only exception.) All active DSMON collection data is deleted, and collection suspended, while this object is equal to 'false', since the meaning of one or more counter aggregation control tables may change when it is set back to 'true'.

The **dsmonAggControlChanges** counter and **dsmonAggControlLastChangeTime** timestamp can be used by a management station to detect that the codepoint to counter aggregation group mappings may have changed between polls.

The `dsmonAggControlTable` is a read-create table which contains one entry for each counter aggregation profile configured on the agent. Each entry is identified by a `dsmonAggControlIndex` value, which is also used as the major index into the `dsmonAggProfileTable` and `dsmonAggGroupTable`. The DSMON control tables with `DataSource` objects select a counter aggregation profile by referencing this index value.

The `dsmonAggProfileTable` is a read-write table which contains 64 rows for each associated entry in the `dsmonAggControlTable`, which **MUST** be indexed from 0 to 63. The agent creates this set of 64 instances when the associated `dsmonAggControlEntry` is activated, and deletes them when that `dsmonAggControlEntry` is deactivated. Each of the 64 rows represents a conceptual DSCP counter, identified by the same `dsmonAggProfileDSCP` value, and contains the DSCP counter to counter aggregation group mapping for that DSCP counter, in the indicated profile. The agent **SHOULD** use the value zero as the initial counter aggregation group assignment for each entry in this table.

The `dsmonAggGroupTable` contains an administratively assigned descriptive label for each configured counter aggregation group. This table is not required to be fully configured in order for data collection to occur, since collections are identified by the agent with integer indices. It is provided to allow the agent to store a descriptive string for each configured counter aggregation group. There is no attempt made to convey any real semantics for each counter aggregation group. A management station **MAY** choose not to configure entries in this table.

### 3.2.2. DS Statistics Group

This group contains two tables, the `dsmonStatsControlTable` and the `dsmonStatsTable`, and supports counter aggregation group distribution statistics for half and full-duplex, low and high speed interfaces. Packet and octets distributions are maintained in the `dsmonStatsTable` for each active control row in the `dsmonStatsControlTable`.

This group provides the lowest statistics granularity in the DSMON MIB. It is expected that a management application will analyze certain DS deployment or performance problems by first examining the counter aggregation group distribution for an entire data source with this group.

### 3.2.3. DS Protocol Distribution Group

This group contains two tables for statistics collection, (`dsmonPdistCtlTable` and `dsmonPdistStatsTable`), and two tables for a 'Top N' reporting function for the collected statistics (`dsmonPdistTopNCtlTable` and `dsmonPdistTopNTable`).

The dsmonPdistCtlTable and dsmonPdistStatsTable tables provide counter aggregation group distribution statistics for each selected protocol encapsulation in packets monitored on a particular dataSource. Packet and octets distributions (per counter aggregation group per protocol) are maintained in the dsmonPdistStatsTable for each active control row in the dsmonPdistCtlTable.

Due to the potentially large number of entries, the DS Protocol Distribution is different from the RMON-2 protocol distribution group in several ways:

- maximum desired entries parameter added to the control table
- inserts and deletes counters added to the control table
- support for LRU garbage collection in the dsmonPdistStatsTable
- TimeFilter index added to the dsmonPdistStatsTable
- the selection of protocols is not configurable. Rather than select individual protocols to monitor, (e.g., via a 'supportedOn/Off' extension to the protocolDirTable [RFC 2021]), a simplified configuration mechanism is provided. Since DSCP usage statistics are most interesting at the application layer, the dsmonPdistStatsTable is 'hardwired' to select only application layer (i.e., 'terminal') protocols for statistical analysis.

The TopN feature requires two additional tables: the dsmonPdistTopNCtlTable and the dsmonPdistTopNTable, and supports periodic usage reporting for the statistics maintained in the dsmonPdistStatsTable. This feature allows for simple periodic retrieval of the most used application/counter aggregation group combinations.

#### 3.2.4. DS Host Distribution Group

This group contains two tables for statistics collection, (dsmonHostCtlTable and dsmonHostTable), and two tables for a 'Top N' reporting function for the collected statistics (dsmonHostTopNCtlTable and dsmonHostTopNTable).

The dsmonHostCtlTable and dsmonHostTables provide host distribution statistics for each counter aggregation group detected in packets monitored on a particular dataSource. The DSMON Host collection is similar to the RMON-2 network layer host collection (nlHostTable). There is no DSMON application host table defined at this time.

It is expected that a management application will analyze certain DS deployment or performance problems by first determining the high priority DSCP values to examine (beyond the scope of this document) and then examining the `dsmonHostTable` or `dsmonHostTopNTable` statistics to determine which hosts are using the selected counter aggregation groups.

Packet and octets distributions (in and out, per counter aggregation group per host) are maintained in the `dsmonHostTable` for each active control row in the `dsmonHostCtlTable`.

The DS Host Distribution is different from the RMON-2 network layer host group in two ways:

- the `protocolDirLocalIndex` in the INDEX clause MUST identify a network protocol encapsulation which contains a DS field (e.g., IPv4 or IPv6). If a protocol encapsulation with multiple network layers is specified, then associated entries in this table refer to the innermost network protocol layer.
- the `dsmonHostCtlTable` supports limited IPv4 and IPv6 prefix aggregation by allowing the number of 'monitored address bits' in each address to be configured for each collection. The agent will zero out the selected number of rightmost address bits for counting purposes. This configuration parameter can dramatically reduce the number of entries which must be maintained by the agent, which should reduce CPU and memory resource requirements on the agent, and reduce polling overhead on the network and the management station. However, only one mask can be configured for each address type, rather than multiple different length masks for each address type, based on prefix value.

The TopN feature requires two additional tables: the `dsmonHostTopNCtlTable` and the `dsmonHostTopNTable`, and supports periodic usage reporting for the statistics maintained in the `dsmonHostTable`. This feature allows for simple periodic retrieval of the most used IP-host/DSCP combinations.

### 3.2.5. DSMON Capabilities Group

This group contains a single read-only scalar object, `dsmonCapabilities`, which provides an indication of the MIB groups within this MIB that the agent supports.

### 3.2.6. DS Matrix Distribution Group

This group contains three tables for statistics collection, (dsmonMatrixCtlTable, dsmonMatrixSDTable, and dsmonMatrixDSTable), and two tables for a 'Top N' reporting function for the collected statistics (dsmonMatrixTopNCtlTable and dsmonMatrixTopNTable).

The dsmonMatrixCtlTable, dsmonMatrixSDTable, and dsmonMatrixDSTable provide host-pair distribution statistics for each counter aggregation group detected in packets monitored on a particular dataSource. The DSMON Matrix collection is similar to the RMON-2 application layer matrix collection (alMatrixSDTable and alMatrixDSTable). There is no DSMON network layer matrix table defined at this time.

It is expected that a management application will analyze certain DS deployment or performance problems by first determining the high priority DSCP values to examine (beyond the scope of this document) and then examining the dsmonMatrixSDTable, dsmonMatrixDSTable, and/or dsmonMatrixTopNTable statistics to determine which host-pairs are using the selected counter aggregation groups.

Packet and octets distributions (source to destination, per counter aggregation group per host-pair) are maintained in the dsmonMatrixSDTable and dsmonMatrixDSTable for each active control row in the dsmonMatrixCtlTable.

The TopN feature requires two additional tables: the dsmonMatrixTopNCtlTable and the dsmonMatrixTopNTable, and supports periodic usage reporting for the statistics maintained in the dsmonMatrixSDTable. This feature allows for simple periodic retrieval of the most used IP-host-pair/DSCP combinations.

### 3.3. RMON vs. DSMON Indexing Structure

The DSMON-MIB control and data tables are very similar in structure and look-and-feel to existing RMON-2 and HC-RMON control tables for the comparable feature, in order to maintain consistent agent behavior and functionality across RMON MIBs. The DSMON data tables are indexed as closely as possible to the comparable RMON-2 or HC-RMON tables, with the addition of an index component for DSCP-based classification (i.e. dsmonAggGroup). Refer to Table 1 for a comparison of DSMON indexing structure with similar existing RMON features.

Table 1: DSMON Indexing Comparison

Existing RMON	DSMON
-----	
Full Duplex Interface Statistics	
mediaIndependentEntry mediaIndependentIndex	dsmonStatsControlEntry dsmonStatsControlIndex dsmonStatsEntry dsmonStatsControlIndex, dsmonAggGroupIndex
-----+-----	
Protocol Statistics	
protocolDistControlEntry protocolDistControlIndex protocolDistStatsEntry protocolDistControlIndex, protocolDirLocalIndex	dsmonPdistCtlEntry dsmonPdistCtlIndex dsmonPdistStatsEntry dsmonPdistCtlIndex, dsmonPdistTimeMark, dsmonAggGroupIndex, protocolDirLocalIndex
-----+-----	
Protocol TopN Distribution	
none	dsmonPdistTopNCtlEntry dsmonPdistTopNCtlIndex dsmonPdistTopNEntry dsmonPdistTopNCtlIndex, dsmonPdistTopNIndex
-----+-----	
Network Host Statistics	
hlHostControlEntry hlHostControlIndex nlHostEntry hlHostControlIndex, nlHostTimeMark, protocolDirLocalIndex, nlHostAddress	dsmonHostCtlEntry dsmonHostCtlIndex dsmonHostEntry dsmonHostCtlIndex, dsmonHostTimeMark, dsmonAggGroupIndex, protocolDirLocalIndex, dsmonHostAddress
-----+-----	

Table 1 (Continued): DSMON Indexing Comparison

Existing RMON	DSMON
-----+-----	
Network Host TopN Distribution	
none	dsmonHostTopNCtlEntry dsmonHostTopNCtlIndex dsmonHostTopNEntry dsmonHostTopNCtlIndex, dsmonHostTopNIndex
-----+-----	
Application Matrix Statistics	
hlMatrixControlEntry hlMatrixControlIndex alMatrixSDEntry hlMatrixControlIndex, alMatrixSDTimeMark, protocolDirLocalIndex, nlMatrixSDSourceAddress, nlMatrixSDDestAddress protocolDirLocalIndex  alMatrixDSEntry hlMatrixControlIndex, alMatrixDSTimeMark, protocolDirLocalIndex, nlMatrixDSDestAddress, nlMatrixDSSourceAddress protocolDirLocalIndex	dsmonMatrixCtlEntry dsmonMatrixCtlIndex dsmonMatrixSDEntry dsmonMatrixCtlIndex, dsmonMatrixTimeMark, dsmonAggGroupIndex, dsmonMatrixNLIndex, dsmonMatrixSourceAddress dsmonMatrixDestAddress dsmonMatrixALIndex  dsmonMatrixDSEntry dsmonMatrixCtlIndex, dsmonMatrixTimeMark, dsmonAggGroupIndex, dsmonMatrixNLIndex, dsmonMatrixDestAddress dsmonMatrixSourceAddress dsmonMatrixALIndex
-----+-----	
Application Matrix TopN Distribution	
none  (similar to nlMatrixTopN)	dsmonMatrixTopNCtlEntry dsmonMatrixTopNCtlIndex dsmonMatrixTopNEntry dsmonMatrixTopNCtlIndex, dsmonMatrixTopNIndex
-----+-----	

#### 4. Definitions

DSMON-MIB DEFINITIONS ::= BEGIN

##### IMPORTS

```

MODULE-IDENTITY, OBJECT-TYPE, Integer32,
Counter32, Gauge32
    FROM SNMPv2-SMI
MODULE-COMPLIANCE, OBJECT-GROUP
    FROM SNMPv2-CONF
RowStatus, TimeStamp, TEXTUAL-CONVENTION, TruthValue
    FROM SNMPv2-TC
OwnerString, rmon
    FROM RMON-MIB
protocolDirLocalIndex, LastCreateTime,
DataSource, ZeroBasedCounter32, TimeFilter
    FROM RMON2-MIB
CounterBasedGauge64, ZeroBasedCounter64
    FROM HCNUM-TC
SnmAdminString
    FROM SNMP-FRAMEWORK-MIB
Dscp
    FROM DIFFSERV-DSCP-TC;
```

##### dsmonMIB MODULE-IDENTITY

```

LAST-UPDATED      "200205310000Z"
ORGANIZATION      "IETF RMONMIB Working Group"
CONTACT-INFO      "
    Andy Bierman
    Cisco Systems, Inc.
    RMONMIB WG Chair and DSMON MIB Editor
```

```

Postal: 170 West Tasman Drive
        San Jose, CA USA 95134
Tel: +1 408 527-3711
E-mail: abierman@cisco.com
```

```

Send comments to <rmonmib@ietf.org>
Mailing list subscription info:
    http://www.ietf.org/mailman/listinfo/rmonmib "
```

##### DESCRIPTION

"This module defines Remote Monitoring MIB extensions for Differentiated Services enabled networks.

```

RMON DIFFSERV DSCP statistics
* Per Counter Aggregation Group
* Per Protocol Per Counter Aggregation Group
* Per Counter Aggregation Group Per Host
```



\* Per Counter Aggregation Group Per Host-Pair

In order to maintain the RMON 'look-and-feel' and semantic consistency, some of the text from the RMON-2 and HC-RMON MIBs by Steve Waldbusser has been adapted for use in this MIB."

REVISION "200205310000Z"

DESCRIPTION

"Initial version of the DSMON MIB module. This version published as RFC 3287."

::= { rmon 26 }

dsmonObjects OBJECT IDENTIFIER ::= { dsmonMIB 1 }  
 dsmonNotifications OBJECT IDENTIFIER ::= { dsmonMIB 2 }  
 dsmonConformance OBJECT IDENTIFIER ::= { dsmonMIB 3 }

dsmonAggObjects OBJECT IDENTIFIER ::= { dsmonObjects 1 }  
 dsmonStatsObjects OBJECT IDENTIFIER ::= { dsmonObjects 2 }  
 dsmonPdistObjects OBJECT IDENTIFIER ::= { dsmonObjects 3 }  
 dsmonHostObjects OBJECT IDENTIFIER ::= { dsmonObjects 4 }  
 dsmonCapsObjects OBJECT IDENTIFIER ::= { dsmonObjects 5 }  
 dsmonMatrixObjects OBJECT IDENTIFIER ::= { dsmonObjects 6 }

--

-- Textual Convention to define a  
 -- DSMON Counter Aggregation Group Index  
 --

DsmonCounterAggGroupIndex ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"This TC describes a data type which identifies a DSMON counter aggregation group, which is an arbitrary grouping of conceptual counters, for monitoring purposes only. The range for this data type begins with zero (instead of one), to allow for a direct mapping between counter indexing schemes that start at zero (e.g. DSCP values in packets) and counter aggregation group values."

SYNTAX Integer32 (0..2147483647)

--

-- Textual Convention to define a  
 -- DSMON Counter Aggregation Profile Index  
 --

DsmonCounterAggProfileIndex ::= TEXTUAL-CONVENTION

STATUS current

**DESCRIPTION**

"This TC describes a data type which identifies a DSMON counter aggregation profile, which is a set of counter aggregation group assignments for each of the 64 DSCP values, for a particular statistical collection."

**SYNTAX** Integer32 (1..2147483647)

```
-- *****
-- *
-- *          D S M O N    C A P A B I L I T I E S
-- *
-- *****
```

**dsmonCapabilities OBJECT-TYPE**

```
SYNTAX          BITS {
                                dsmonCounterAggControl(0),
                                dsmonStats(1),
                                dsmonStatsOvfl(2),
                                dsmonStatsHC(3),
                                dsmonPdist(4),
                                dsmonPdistOvfl(5),
                                dsmonPdistHC(6),
                                dsmonHost(7),
                                dsmonHostOvfl(8),
                                dsmonHostHC(9),
                                dsmonCaps(10),
                                dsmonMatrix(11),
                                dsmonMatrixOvfl(12),
                                dsmonMatrixHC(13)
                                }
```

**MAX-ACCESS** read-only

**STATUS** current

**DESCRIPTION**

"This object provides an indication of the DSMON groups supported by the agent. If a bit is set, then the agent implements all of the objects in the DSMON object group, where bit 'n' represents the MIB group identified by the OBJECT IDENTIFIER value { dsmonGroups n+1 }."

::= { dsmonCapsObjects 1 }

```
-- *****
-- *
-- *    A G G R E G A T I O N    C O N T R O L    G R O U P S
-- *
-- *****
```

**dsmonMaxAggGroups OBJECT-TYPE****SYNTAX** Integer32 (2..64)**MAX-ACCESS** read-only**STATUS** current**DESCRIPTION**

"The maximum number of counter aggregation groups that this agent can support. The agent will allow this number of distinct groups to be configured in the dsmonAggProfileTable, numbered from '0' to 'dsmonMaxAggGroups - 1', for each counter aggregation profile entry supported by the agent.

The agent **MUST NOT** lower this value during system operation, and **SHOULD** set this object to an appropriate value during system initialization."

::= { dsmonAggObjects 1 }

**dsmonAggControlLocked OBJECT-TYPE****SYNTAX** TruthValue**MAX-ACCESS** read-write**STATUS** current**DESCRIPTION**

"Controls the setup of counter aggregation groups for this agent.

If this object contains the value 'true', then write access to the objects in the dsmonAggControlTable (except the dsmonAggControlOwner object), dsmonAggProfileTable, and dsmonAggGroupTable is not permitted, and data collection is possible. This object only controls write access to these MIB objects. The DSMON data collection control tables (e.g., dsmonHostCtlTable) can be configured at any time, regardless of the value of this object.

If this object contains the value 'false', write access to the objects in the dsmonAggControlTable, dsmonAggProfileTable, and dsmonAggGroupTable is permitted, and data collection is not possible. In addition, all objects in all DSMON data tables (e.g., dsmonStatsTable) shall be deleted.

An agent is not required to process SNMP Set Requests for this object in conjunction with other objects from this MIB. This is intended to simplify the processing of Set Requests for tables such as the dsmonAggProfileTable, by eliminating the possibility that a single Set PDU will contain multiple varbinds which are in conflict, such as a PDU which both modifies the dsmonAggProfileTable and locks the

dsmonAggProfileTable at the same time.

Note that the agent is not required to validate the entire counter aggregation configuration when an attempt is made to transition an instance of this object from 'true' to 'false'. That validation is done if and when a DSMON data collection is activated.

An agent is required to reactivate any suspended data collections when this object transitions to 'true'. Each active data control entry (e.g., dsmonStatsControlEntry), will be validated with respect to the new counter aggregation configuration. If the counter aggregation profile referenced in the data collection is valid, then that collection will be restarted. Otherwise, the RowStatus object (e.g., dsmonStatsControlStatus) will be set to 'notReady' for that collection control entry."

::= { dsmonAggObjects 2 }

#### dsmonAggControlChanges OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

##### DESCRIPTION

"This object counts the number of times the value of the dsmonAggControlLocked object has changed. A management station can use this object to detect if counters in the DSMON data tables (e.g., dsmonStatsEntry) have been deleted and recreated between polls.

This object shall be incremented by one each time the dsmonAggControlLocked object changes from 'false' to 'true', or from 'true' to 'false'."

::= { dsmonAggObjects 3 }

#### dsmonAggControlLastChangeTime OBJECT-TYPE

SYNTAX TimeStamp

MAX-ACCESS read-only

STATUS current

##### DESCRIPTION

"This object identifies the value of sysUpTime at the moment the dsmonAggControlLocked object was last modified. A management station can use this object to detect if counters in the DSMON data tables (e.g., dsmonStatsEntry) have been deleted and recreated between polls.

This object shall be updated with the current value of sysUpTime, if the dsmonAggControlLocked object changes from

'false' to 'true', or from 'true' to 'false'.

Upon system initialization, this object shall contain the value zero."

::= { dsmonAggObjects 4 }

--  
--  
--

Counter Aggregation Control Table

dsmonAggControlTable OBJECT-TYPE

SYNTAX SEQUENCE OF DsmonAggControlEntry  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION

"This table provides an overall description and control point for all dsmonAggProfileEntries with the same dsmonAggControlIndex value.

A management application SHOULD create a counter aggregation profile by first creating and activating an entry in this table. This will cause the agent to create a set of 64 dsmonAggProfileEntries on behalf of this control entry. An application can then set the individual counter aggregation group assignments for each of the 64 DSCP values,

This table MUST NOT be modified if the dsmonAggControlLocked object is equal to 'true'.

Note that an agent MAY choose to limit the actual number of entries which may be created in this table, and (independently) the number of counter aggregation profiles which may be applied to a particular data source. In this case, the agent SHOULD return an error-status of 'resourceUnavailable(13)', as per section 4.2.5 of the 'Protocol Operations for SNMPv2' specification [RFC1905].

The agent SHOULD support non-volatile configuration of this table, and upon system initialization, the table SHOULD be initialized with the saved values. Otherwise, each potential counter aggregation group description string SHOULD contain the empty string."

::= { dsmonAggObjects 5 }

dsmonAggControlEntry OBJECT-TYPE

SYNTAX DsmonAggControlEntry  
MAX-ACCESS not-accessible

```

STATUS      current
DESCRIPTION
    "A conceptual row in the dsmonAggControlTable."
INDEX { dsmonAggControlIndex }
 ::= { dsmonAggControlTable 1 }

```

```

DsmonAggControlEntry ::= SEQUENCE {
    dsmonAggControlIndex      DsmonCounterAggProfileIndex,
    dsmonAggControlDescr      SnmpAdminString,
    dsmonAggControlOwner      OwnerString,
    dsmonAggControlStatus     RowStatus
}

```

```

dsmonAggControlIndex OBJECT-TYPE
    SYNTAX      DsmonCounterAggProfileIndex
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "An arbitrary integer index value used to identify the
         counter aggregation profile specified by this control
         entry."
    ::= { dsmonAggControlEntry 1 }

```

```

dsmonAggControlDescr OBJECT-TYPE
    SYNTAX      SnmpAdminString (SIZE (0..64))
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "An administratively assigned description of the counter
         aggregation profile identified by this entry.

        Upon first creation of an instance of this object, the agent
        SHOULD set this object to the empty string.  If the agent
        supports non-volatile storage, then this object SHOULD be
        re-initialized with its stored value after a system reboot.

        This object MUST NOT be modified if the associated
        dsmonAggControlStatus object is equal to 'active', or the
        dsmonAggControlLocked object is equal to 'true'."
    ::= { dsmonAggControlEntry 2 }

```

```

dsmonAggControlOwner OBJECT-TYPE
    SYNTAX      OwnerString
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "The entity that configured this entry and is therefore
         using the resources assigned to it."

```

```
::= { dsmonAggControlEntry 3 }
```

dsmonAggControlStatus OBJECT-TYPE

```
SYNTAX      RowStatus
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
```

"The status of this row.

An entry MUST NOT exist in the active state unless all objects in the entry have an appropriate value.

Upon setting this object to active(1), the agent will create a complete set of 64 associated entries in the dsmonAggProfileTable.

If this object is not equal to active(1), all associated entries in the dsmonAggProfileTable shall be deleted.

This object MUST NOT be modified if the dsmonAggControlLocked object is equal to 'true'."

```
::= { dsmonAggControlEntry 4 }
```

```
--
```

```
-- Counter Aggregation Profile Table
```

```
--
```

dsmonAggProfileTable OBJECT-TYPE

```
SYNTAX      SEQUENCE OF DsmonAggProfileEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
```

"Controls the setup of counter aggregation profiles for this agent. For each such profile, every DSCP value MUST be configured into exactly one counter aggregation group.

This table MUST NOT be modified if the dsmonAggControlLocked object is equal to 'true'.

The agent will create a set of 64 entries in this table (with the same dsmonAggControlIndex value) when the associated dsmonAggControlEntry is activated.

If the agent supports non-volatile configuration of this table, then upon system initialization, this table SHOULD be initialized with the saved values."

```
::= { dsmonAggObjects 6 }
```

**dsmonAggProfileEntry OBJECT-TYPE****SYNTAX** DsmonAggProfileEntry**MAX-ACCESS** not-accessible**STATUS** current**DESCRIPTION**

"A conceptual row in the dsmonAggProfileTable. The dsmonAggControlIndex value in the index identifies the dsmonAggControlEntry associated with each entry in this table."

**INDEX** { dsmonAggControlIndex, dsmonAggProfileDSCP }

::= { dsmonAggProfileTable 1 }

**DsmonAggProfileEntry ::= SEQUENCE {**

dsmonAggProfileDSCP Dscp,

dsmonAggGroupIndex DsmonCounterAggGroupIndex

**}****dsmonAggProfileDSCP OBJECT-TYPE****SYNTAX** Dscp**MAX-ACCESS** not-accessible**STATUS** current**DESCRIPTION**

"The specific DSCP value for the DSCP counter which is configured in a counter aggregation group by this entry."

::= { dsmonAggProfileEntry 1 }

**dsmonAggGroupIndex OBJECT-TYPE****SYNTAX** DsmonCounterAggGroupIndex**MAX-ACCESS** read-write**STATUS** current**DESCRIPTION**

"The counter aggregation group which contains this DSCP value. Upon creation of a new sub-tree (set of 64 entries with the same dsmonAggControlIndex value) in this table, the agent SHOULD initialize all related instances of this object to the value zero.

This object MUST NOT be modified if the dsmonAggControlLocked object is equal to 'true'."

**DEFVAL** { 0 }

::= { dsmonAggProfileEntry 2 }

--

-- Counter Aggregation Group Table

--



**dsmonAggGroupTable OBJECT-TYPE****SYNTAX** SEQUENCE OF DsmonAggGroupEntry**MAX-ACCESS** not-accessible**STATUS** current**DESCRIPTION**

"This table provides a description of each counter aggregation group configured on this system. Note that the semantics of a particular counter aggregation group are only relevant within the scope of a particular counter aggregation profile.

This table **MUST NOT** be modified if the dsmonAggControlLocked object is equal to 'true'.

Note that an agent **MAY** choose to limit the actual number of entries which may be created in this table, and (independently) the number of counter aggregation profiles which may be applied to a particular data source. In this case, the agent **SHOULD** return an error-status of 'resourceUnavailable(13)', as per section 4.2.5 of the 'Protocol Operations for SNMPv2' specification [RFC1905].

If the agent supports non-volatile configuration of this table, then upon system initialization, this table **SHOULD** be initialized with the saved values. Otherwise, each potential counter aggregation group description string **SHOULD** contain the empty string.

An agent **SHOULD** allow entries to be created or modified in this table, even if the specified dsmonAggControlIndex value does not identify a valid dsmonAggControlEntry or a complete set of valid dsmonAggProfileEntries, to reduce row creation order dependencies."

::= { dsmonAggObjects 7 }

**dsmonAggGroupEntry OBJECT-TYPE****SYNTAX** DsmonAggGroupEntry**MAX-ACCESS** not-accessible**STATUS** current**DESCRIPTION**

"A conceptual row in the dsmonAggGroupTable. The dsmonAggGroupIndex value in the INDEX identifies the counter aggregation group associated with each entry.

The dsmonAggControlIndex in the index identifies the counter aggregation profile associated with each entry, identified by the dsmonAggControlEntry and dsmonAggProfileEntries with the same index value.

The agent **SHOULD** support non-volatile configuration of this table, and upon system initialization, the table **SHOULD** be initialized with the saved values.

The `dsmonAggGroupIndex` in the index identifies the counter aggregation group associated with each entry. This object **SHOULD** be indexed from zero to 'N', where 'N' is less than the value of the `dsmonMaxAggGroups` for this agent."

```

INDEX { dsmonAggControlIndex, dsmonAggGroupIndex }
 ::= { dsmonAggGroupTable 1 }
DsmonAggGroupEntry ::= SEQUENCE {
    dsmonAggGroupDescr          SnmpAdminString,
    dsmonAggGroupStatus        RowStatus
}

dsmonAggGroupDescr OBJECT-TYPE
    SYNTAX      SnmpAdminString (SIZE (0..64))
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "An administratively assigned description of the counter
        aggregation group identified by this entry.

        Upon first creation of an instance of this object, the agent
        SHOULD set this object to the empty string.

        This object MUST NOT be modified if the associated
        dsmonAggGroupStatus object is equal to 'active', or the
        dsmonAggControlLocked object is equal to 'true'."
    ::= { dsmonAggGroupEntry 1 }

dsmonAggGroupStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "The status of this row.

        An entry MUST NOT exist in the active state unless all
        objects in the entry have an appropriate value.

        This object MUST NOT be modified if the
        dsmonAggControlLocked object is equal to 'true'."
    ::= { dsmonAggGroupEntry 2 }

```

```
-- *****
-- *
-- *   P E R - D A T A S O U R C E   C O L L E C T I O N S   *
-- *
-- *****
```

```
--
-- Per-DataSource Statistics Control Table
--
```

dsmonStatsControlTable OBJECT-TYPE

SYNTAX SEQUENCE OF DsmonStatsControlEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Controls the setup of per data source per counter aggregation group distribution statistics.

Note that an agent MAY choose to limit the actual number of entries which may be created in this table. In this case, the agent SHOULD return an error-status of 'resourceUnavailable(13)', as per section 4.2.5 of the 'Protocol Operations for SNMPv2' specification [RFC1905]."

::= { dsmonStatsObjects 1 }

dsmonStatsControlEntry OBJECT-TYPE

SYNTAX DsmonStatsControlEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"A conceptual row in the dsmonStatsControlTable.

Entries are created and deleted from this table by management action only, using the dsmonStatsControlStatus RowStatus object.

The agent SHOULD support non-volatile configuration of this table, and upon system initialization, the table SHOULD be initialized with the saved values.

Activation of a control row in this table will cause an associated dsmonStatsTable to be created and maintained by the agent."

INDEX { dsmonStatsControlIndex }

::= { dsmonStatsControlTable 1 }

DsmonStatsControlEntry ::= SEQUENCE {

dsmonStatsControlIndex

Integer32,

```

    dsmonStatsControlDataSource      DataSource,
    dsmonStatsControlAggProfile      DsmonCounterAggProfileIndex,
    dsmonStatsControlDroppedFrames   Counter32,
    dsmonStatsControlCreateTime      LastCreateTime,
    dsmonStatsControlOwner            OwnerString,
    dsmonStatsControlStatus           RowStatus
}

dsmonStatsControlIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..65535)
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "An arbitrary and unique index for this
         dsmonStatsControlEntry."
    ::= { dsmonStatsControlEntry 1 }

dsmonStatsControlDataSource OBJECT-TYPE
    SYNTAX      DataSource
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "The data source of this per protocol per counter
         aggregation group distribution.

        Note that only packets that contain a network protocol
         encapsulation which contains a DS field [RFC2474] will be
         counted in this table.

        This object MUST NOT be modified if the associated
         dsmonStatsControlStatus object is equal to active(1)."
```

```

    ::= { dsmonStatsControlEntry 2 }

dsmonStatsControlAggProfile OBJECT-TYPE
    SYNTAX      DsmonCounterAggProfileIndex
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "The dsmonAggControlIndex value identifying the counter
         aggregation profile which should be used on behalf of this
         dsmonStatsControlEntry.

        The associated dsmonAggControlEntry and
         dsmonAggProfileEntries, identified by the same
         dsmonAggControlIndex index value, MUST be active in order
         for this entry to remain active. It is possible for the
         counter aggregation configuration to change from a valid to
         invalid state for this dsmonStats collection. In this case,
```

the associated dsmonStatsControlStatus object will be changed to the 'notReady' state, and data collection will not occur on behalf of this control entry.

Note that an agent MAY choose to limit the actual number of counter aggregation profiles which may be applied to a particular data source.

This object MUST NOT be modified if the associated dsmonStatsControlStatus object is equal to active(1)."

::= { dsmonStatsControlEntry 3 }

**dsmonStatsControlDroppedFrames OBJECT-TYPE**

SYNTAX Counter32

UNITS "frames"

MAX-ACCESS read-only

STATUS current

**DESCRIPTION**

"The total number of frames which were received by the probe and therefore not accounted for in the \*StatsDropEvents, but for which the probe chose not to count for this entry for whatever reason. Most often, this event occurs when the probe is out of some resources and decides to shed load from this collection.

This count does not include packets that were not counted because they had MAC-layer errors.

Note that, unlike the dropEvents counter, this number is the exact number of frames dropped."

::= { dsmonStatsControlEntry 4 }

**dsmonStatsControlCreateTime OBJECT-TYPE**

SYNTAX LastCreateTime

MAX-ACCESS read-only

STATUS current

**DESCRIPTION**

"The value of sysUpTime when this control entry was last activated. This can be used by the management station to detect if the table has been deleted and recreated between polls."

::= { dsmonStatsControlEntry 5 }

**dsmonStatsControlOwner OBJECT-TYPE**

SYNTAX OwnerString

MAX-ACCESS read-create

STATUS current

**DESCRIPTION**

"The entity that configured this entry and is therefore using the resources assigned to it."  
::= { dsmonStatsControlEntry 6 }

dsmonStatsControlStatus OBJECT-TYPE

SYNTAX RowStatus  
MAX-ACCESS read-create  
STATUS current  
DESCRIPTION

"The status of this row.

An entry MUST NOT exist in the active state unless all objects in the entry have an appropriate value.

If this object is not equal to active(1), all associated entries in the dsmonStatsTable shall be deleted."  
::= { dsmonStatsControlEntry 7 }

--

-- Per-DataSource Statistics Table

--

dsmonStatsTable OBJECT-TYPE

SYNTAX SEQUENCE OF DsmonStatsEntry  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION

"A list of information on counter aggregation group usage for each monitored data source.

The following table defines per counter aggregation group statistics for full and/or half-duplex links as well as high capacity links.

For half-duplex links, or full-duplex-capable links operating in half-duplex mode, the dsmonStatsIn\* objects shall be used and the dsmonStatsOut\* objects will not increment.

For full-duplex links, the dsmonStatsOut\* objects will be present. Whenever possible, the probe SHOULD count packets moving away from the closest terminating equipment as output packets. Failing that, the probe SHOULD count packets moving away from the DTE as output packets.

If the dsmonAggControlLocked object is equal to 'false', then all entries in this table will be deleted and the agent will not process packets on behalf of any

```

        dsmonStatsControlEntry."
 ::= { dsmonStatsObjects 2 }

```

```

dsmonStatsEntry OBJECT-TYPE
    SYNTAX      DsmonStatsEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION

```

"A list of information on Differentiated Services DSCP usage, containing inbound and outbound packet and octet counters for each counter aggregation group configured for collection.

The dsmonStatsControlIndex value in the index identifies the dsmonStatsControlEntry on whose behalf this entry was created.

The dsmonAggGroupIndex value in the index is determined by examining the DSCP value in each monitored packet, and the dsmonAggProfileTable entry for that DSCP value.

Note that only packets that contain a network protocol encapsulation which contains a DS field [RFC2474] will be counted in this table.

An example of the indexing of this entry is dsmonStatsOutPkts.1.16"

```

INDEX { dsmonStatsControlIndex, dsmonAggGroupIndex }
 ::= { dsmonStatsTable 1 }

```

```

DsmonStatsEntry ::= SEQUENCE {
    dsmonStatsInPkts      ZeroBasedCounter32,
    dsmonStatsInOctets    ZeroBasedCounter32,
    dsmonStatsInOvflPkts  ZeroBasedCounter32,
    dsmonStatsInOvflOctets ZeroBasedCounter32,
    dsmonStatsInHCPkts    ZeroBasedCounter64,
    dsmonStatsInHCOctets  ZeroBasedCounter64,
    dsmonStatsOutPkts     ZeroBasedCounter32,
    dsmonStatsOutOctets   ZeroBasedCounter32,
    dsmonStatsOutOvflPkts ZeroBasedCounter32,
    dsmonStatsOutOvflOctets ZeroBasedCounter32,
    dsmonStatsOutHCPkts   ZeroBasedCounter64,
    dsmonStatsOutHCOctets ZeroBasedCounter64
}

```

```

dsmonStatsInPkts OBJECT-TYPE
    SYNTAX      ZeroBasedCounter32
    UNITS       "packets"

```

MAX-ACCESS read-only  
STATUS current  
DESCRIPTION

"The number of packets using one of the DSCP values in the indicated counter aggregation group, received on a half-duplex link or on the inbound connection of a full-duplex link."

::= { dsmonStatsEntry 1 }

dsmonStatsInOctets OBJECT-TYPE

SYNTAX ZeroBasedCounter32  
UNITS "octets"  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION

"The number of octets in packets, using one of the DSCP values in the indicated counter aggregation group, received on a half-duplex link or on the inbound connection of a full-duplex link."

::= { dsmonStatsEntry 2 }

dsmonStatsInOvflPkts OBJECT-TYPE

SYNTAX ZeroBasedCounter32  
MAX-ACCESS read-only  
STATUS deprecated  
DESCRIPTION

"The number of times the associated dsmonStatsInPkts counter has overflowed. Note that this object will only be instantiated if the associated dsmonStatsInHCPkts object is also instantiated for a particular dataSource."

::= { dsmonStatsEntry 3 }

dsmonStatsInOvflOctets OBJECT-TYPE

SYNTAX ZeroBasedCounter32  
MAX-ACCESS read-only  
STATUS deprecated  
DESCRIPTION

"The number of times the associated dsmonStatsInOctets counter has overflowed. Note that this object will only be instantiated if the associated dsmonStatsInHCOctets object is also instantiated for a particular dataSource."

::= { dsmonStatsEntry 4 }

dsmonStatsInHCPkts OBJECT-TYPE

SYNTAX ZeroBasedCounter64  
UNITS "packets"  
MAX-ACCESS read-only  
STATUS current



**DESCRIPTION**

"The 64-bit version of the dsmonStatsInPkts object.

Note that this object will only be instantiated if the RMON agent supports High Capacity monitoring for a particular dataSource."

::= { dsmonStatsEntry 5 }

**dsmonStatsInHC0ctets OBJECT-TYPE**

**SYNTAX** ZeroBasedCounter64

**UNITS** "octets"

**MAX-ACCESS** read-only

**STATUS** current

**DESCRIPTION**

"The 64-bit version of the dsmonStatsIn0ctets object.

Note that this object will only be instantiated if the RMON agent supports High Capacity monitoring for a particular dataSource."

::= { dsmonStatsEntry 6 }

**dsmonStatsOutPkts OBJECT-TYPE**

**SYNTAX** ZeroBasedCounter32

**UNITS** "packets"

**MAX-ACCESS** read-only

**STATUS** current

**DESCRIPTION**

"The number of packets using one of the DSCP values in the indicated counter aggregation group, received on a full-duplex link in the direction of the network."

::= { dsmonStatsEntry 7 }

**dsmonStatsOut0ctets OBJECT-TYPE**

**SYNTAX** ZeroBasedCounter32

**UNITS** "octets"

**MAX-ACCESS** read-only

**STATUS** current

**DESCRIPTION**

"The number of octets in packets, using one of the DSCP values in the indicated counter aggregation group, received on a full-duplex link in the direction of the network."

::= { dsmonStatsEntry 8 }

**dsmonStatsOut0vflPkts OBJECT-TYPE**

**SYNTAX** ZeroBasedCounter32

**MAX-ACCESS** read-only

**STATUS** deprecated

**DESCRIPTION**

"The number of times the associated dsmonStatsOutPkts counter has overflowed. Note that this object will only be instantiated if the associated dsmonStatsOutHCPkts object is also instantiated for a particular dataSource."

::= { dsmonStatsEntry 9 }

dsmonStatsOut0vflOctets OBJECT-TYPE

SYNTAX ZeroBasedCounter32

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of times the associated dsmonStatsOut0ctets counter has overflowed. Note that this object will only be instantiated if the associated dsmonStatsOutHCOctets object is also instantiated for a particular dataSource."

::= { dsmonStatsEntry 10 }

dsmonStatsOutHCPkts OBJECT-TYPE

SYNTAX ZeroBasedCounter64

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The 64-bit version of the dsmonStatsOutPkts object.

Note that this object will only be instantiated if the RMON agent supports High Capacity monitoring for a particular dataSource."

::= { dsmonStatsEntry 11 }

dsmonStatsOutHCOctets OBJECT-TYPE

SYNTAX ZeroBasedCounter64

UNITS "octets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The 64-bit version of the dsmonStatsOut0ctets object.

Note that this object will only be instantiated if the RMON agent supports High Capacity monitoring for a particular dataSource."

::= { dsmonStatsEntry 12 }

```
-- *****
-- *
-- *   P E R - P R O T O C O L   C O L L E C T I O N S   *
-- *
-- *****
```

```
--
-- DSCP Per-Protocol Statistics Control Table
--
```

dsmonPdistCtlTable OBJECT-TYPE

```
SYNTAX      SEQUENCE OF DsmonPdistCtlEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
```

"Controls the setup of per application per counter aggregation group distribution statistics.

Note that an agent MAY choose to limit the actual number of entries which may be created in this table. In this case, the agent SHOULD return an error-status of 'resourceUnavailable(13)', as per section 4.2.5 of the 'Protocol Operations for SNMPv2' specification [RFC1905]."

```
::= { dsmonPdistObjects 1 }
```

dsmonPdistCtlEntry OBJECT-TYPE

```
SYNTAX      DsmonPdistCtlEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
```

"A conceptual row in the dsmonPdistCtlTable.

Entries are created and deleted from this table by management action only, using the dsmonPdistCtlStatus RowStatus object.

The agent SHOULD support non-volatile configuration of this table, and upon system initialization, the table SHOULD be initialized with the saved values.

Activation of a control row in this table will cause an associated dsmonPdistStatsTable to be created and maintained by the agent."

```
INDEX { dsmonPdistCtlIndex }
::= { dsmonPdistCtlTable 1 }
```

DsmonPdistCtlEntry ::= SEQUENCE {

dsmonPdistCtlIndex	Integer32,
dsmonPdistCtlDataSource	DataSource,
dsmonPdistCtlAggProfile	DsmonCounterAggProfileIndex,
dsmonPdistCtlMaxDesiredEntries	Integer32,
dsmonPdistCtlDroppedFrames	Counter32,
dsmonPdistCtlInserts	Counter32,
dsmonPdistCtlDeletes	Counter32,

```

    dsmonPdistCtlCreateTime      LastCreateTime,
    dsmonPdistCtlOwner           OwnerString,
    dsmonPdistCtlStatus          RowStatus
}

dsmonPdistCtlIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..65535)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An arbitrary and unique index for this dsmonPdistCtlEntry."
    ::= { dsmonPdistCtlEntry 1 }

dsmonPdistCtlDataSource OBJECT-TYPE
    SYNTAX      DataSource
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The source of data for the this per protocol counter
        aggregation group distribution.

        This object MUST NOT be modified if the associated
        dsmonPdistCtlStatus object is equal to active(1)."
    ::= { dsmonPdistCtlEntry 2 }

dsmonPdistCtlAggProfile OBJECT-TYPE
    SYNTAX      DsmonCounterAggProfileIndex
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The dsmonAggControlIndex value identifying the counter
        aggregation profile which should be used on behalf of this
        dsmonPdistCtlEntry.

        The associated dsmonAggControlEntry and
        dsmonAggProfileEntries, identified by the same
        dsmonAggControlIndex index value, MUST be active in order
        for this entry to remain active. It is possible for the
        counter aggregation configuration to change from a valid to
        invalid state for this dsmonPdist collection. In this case,
        the associated dsmonPdistCtlStatus object will be changed to
        the 'notReady' state, and data collection will not occur on
        behalf of this control entry.

        Note that an agent MAY choose to limit the actual number of
        counter aggregation profiles which may be applied to a
        particular data source."

```

This object MUST NOT be modified if the associated  
dsmonPdlistCtlStatus object is equal to active(1)."  
 ::= { dsmonPdlistCtlEntry 3 }

dsmonPdlistCtlMaxDesiredEntries OBJECT-TYPE

SYNTAX Integer32 (-1 | 1..2147483647)  
MAX-ACCESS read-create  
STATUS current  
DESCRIPTION

"The maximum number of entries that are desired in the  
dsmonPdlistStatsTable on behalf of this control entry. The  
probe will not create more than this number of associated  
entries in the table, but MAY choose to create fewer entries  
in this table for any reason including the lack of  
resources.

If this value is set to -1, the probe MAY create any number  
of entries in this table.

This object MUST NOT be modified if the associated  
dsmonPdlistCtlStatus object is equal to active(1)."  
 ::= { dsmonPdlistCtlEntry 4 }

dsmonPdlistCtlDroppedFrames OBJECT-TYPE

SYNTAX Counter32  
UNITS "frames"  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION

"The total number of frames which were received by the probe  
and therefore not accounted for in the \*StatsDropEvents, but  
for which the probe chose not to count for this entry for  
whatever reason. Most often, this event occurs when the  
probe is out of some resources and decides to shed load from  
this collection.

This count does not include packets that were not counted  
because they had MAC-layer errors.

Note that, unlike the dropEvents counter, this number is the  
exact number of frames dropped."  
 ::= { dsmonPdlistCtlEntry 5 }

dsmonPdlistCtlInserts OBJECT-TYPE

SYNTAX Counter32  
UNITS "table entries"  
MAX-ACCESS read-only  
STATUS current

**DESCRIPTION**

"The number of times a dsmonPdist entry has been inserted into the dsmonPdistTable. If an entry is inserted, then deleted, and then inserted, this counter will be incremented by 2.

To allow for efficient implementation strategies, agents MAY delay updating this object for short periods of time. For example, an implementation strategy may allow internal data structures to differ from those visible via SNMP for short periods of time. This counter may reflect the internal data structures for those short periods of time.

Note that the table size can be determined by subtracting dsmonPdistCtlDeletes from dsmonPdistCtlInserts."

::= { dsmonPdistCtlEntry 6 }

**dsmonPdistCtlDeletes OBJECT-TYPE**

SYNTAX Counter32  
UNITS "table entries"  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION

"The number of times a dsmonPdist entry has been deleted from the dsmonPdist table (for any reason). If an entry is deleted, then inserted, and then deleted, this counter will be incremented by 2.

To allow for efficient implementation strategies, agents MAY delay updating this object for short periods of time. For example, an implementation strategy may allow internal data structures to differ from those visible via SNMP for short periods of time. This counter may reflect the internal data structures for those short periods of time.

Note that the table size can be determined by subtracting dsmonPdistCtlDeletes from dsmonPdistCtlInserts."

::= { dsmonPdistCtlEntry 7 }

**dsmonPdistCtlCreateTime OBJECT-TYPE**

SYNTAX LastCreateTime  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION

"The value of sysUpTime when this control entry was last activated. This can be used by the management station to detect if the table has been deleted and recreated between polls."

```
::= { dsmonPdistCtlEntry 8 }
```

```
dsmonPdistCtlOwner OBJECT-TYPE
```

```
SYNTAX      OwnerString
```

```
MAX-ACCESS  read-create
```

```
STATUS      current
```

```
DESCRIPTION
```

```
    "The entity that configured this entry and is therefore  
    using the resources assigned to it."
```

```
::= { dsmonPdistCtlEntry 9 }
```

```
dsmonPdistCtlStatus OBJECT-TYPE
```

```
SYNTAX      RowStatus
```

```
MAX-ACCESS  read-create
```

```
STATUS      current
```

```
DESCRIPTION
```

```
    "The status of this row.
```

```
    An entry MUST NOT exist in the active state unless all  
    objects in the entry have an appropriate value.
```

```
    If this object is not equal to active(1), all associated  
    entries in the dsmonPdistStatsTable shall be deleted."
```

```
::= { dsmonPdistCtlEntry 10 }
```

```
--
```

```
-- Per-Protocol Statistics Table
```

```
--
```

```
dsmonPdistStatsTable OBJECT-TYPE
```

```
SYNTAX      SEQUENCE OF DsmonPdistStatsEntry
```

```
MAX-ACCESS  not-accessible
```

```
STATUS      current
```

```
DESCRIPTION
```

```
    "A list of information on a per protocol per counter  
    aggregation group usage.
```

```
    If the dsmonAggControlLocked object is equal to 'false',  
    then all entries in this table will be deleted and the agent  
    will not process packets on behalf of any  
    dsmonPdistCtlEntry."
```

```
::= { dsmonPdistObjects 2 }
```

```
dsmonPdistStatsEntry OBJECT-TYPE
```

```
SYNTAX      DsmonPdistStatsEntry
```

```
MAX-ACCESS  not-accessible
```

```
STATUS      current
```

```
DESCRIPTION
```

"A list of information on Differentiated Services DSCP usage, containing packet and octet counters for each counter aggregation group configured for collection, and each protocol (as identified by the protocolDirLocalIndex for the protocol) identified in each monitored packet.

The dsmonPdistCtlIndex value in the index identifies the dsmonPdistCtlEntry on whose behalf this entry was created.

Note that only packets that contain a network protocol encapsulation which contains a DS field [RFC2474] will be counted in this table.

The dsmonAggGroupIndex value in the index is determined by examining the DSCP value in each monitored packet, and the dsmonAggProfileTable entry for that value.

The protocolDirLocalIndex in the index identifies the protocolDirEntry for the protocol encapsulation of each monitored packet. The agent will include only application layer protocols in the associated dsmonPdistStatsTable. Any 'terminal' protocol is considered to be an application protocol.

An example of the indexing of this entry is dsmonPdistStatsPkts.9.29943.0.42."

```
INDEX { dsmonPdistCtlIndex,
        dsmonPdistTimeMark,
        dsmonAggGroupIndex,
        protocolDirLocalIndex }
 ::= { dsmonPdistStatsTable 1 }
```

```
DsmonPdistStatsEntry ::= SEQUENCE {
    dsmonPdistTimeMark          TimeFilter,
    dsmonPdistStatsPkts         ZeroBasedCounter32,
    dsmonPdistStatsOctets       ZeroBasedCounter32,
    dsmonPdistStatsOvflPkts     ZeroBasedCounter32,
    dsmonPdistStatsOvflOctets   ZeroBasedCounter32,
    dsmonPdistStatsHCPkts       ZeroBasedCounter64,
    dsmonPdistStatsHCOctets     ZeroBasedCounter64,
    dsmonPdistStatsCreateTime   LastCreateTime
}
```

```
dsmonPdistTimeMark OBJECT-TYPE
    SYNTAX          TimeFilter
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
```



"The Time Filter index for this table. This object may be used by a management station to retrieve only rows which have been created or modified since a particular time. Note that the current value for a row are always returned and the TimeFilter is not a historical data archiving mechanism. Refer to RFC 2021 [RFC2021] for a detailed description of TimeFilter operation."

::= { dsmonPdistStatsEntry 1 }

dsmonPdistStatsPkts OBJECT-TYPE

SYNTAX ZeroBasedCounter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of packets, using one of the DSCP values in the indicated counter aggregation group, for the protocol identified by the associated protocolDirLocalIndex value."

::= { dsmonPdistStatsEntry 2 }

dsmonPdistStatsOctets OBJECT-TYPE

SYNTAX ZeroBasedCounter32

UNITS "octets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of octets in packets, using one of the DSCP values in the indicated counter aggregation group, for the protocol identified by the associated protocolDirLocalIndex value."

Note that this object doesn't count just those octets in the particular protocol frames, but includes the entire packet that contained the protocol."

::= { dsmonPdistStatsEntry 3 }

dsmonPdistStatsOvflPkts OBJECT-TYPE

SYNTAX ZeroBasedCounter32

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of times the associated dsmonPdistStatsPkts counter has overflowed. Note that this object will only be instantiated if the associated dsmonPdistStatsHCPkts object is also instantiated for a particular dataSource."

::= { dsmonPdistStatsEntry 4 }

dsmonPdistStatsOvflOctets OBJECT-TYPE

SYNTAX ZeroBasedCounter32  
MAX-ACCESS read-only  
STATUS deprecated  
DESCRIPTION  
    "The number of times the associated dsmonPdistStatsOctets  
    counter has overflowed. Note that this object will only be  
    instantiated if the associated dsmonPdistStatsHCOctets  
    object is also instantiated for a particular dataSource."  
 ::= { dsmonPdistStatsEntry 5 }

dsmonPdistStatsHCPkts OBJECT-TYPE  
SYNTAX ZeroBasedCounter64  
UNITS "packets"  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
    "The 64-bit version of the dsmonPdistStatsPkts object.  
  
    Note that this object will only be instantiated if the RMON  
    agent supports High Capacity monitoring for a particular  
    dataSource."  
 ::= { dsmonPdistStatsEntry 6 }

dsmonPdistStatsHCOctets OBJECT-TYPE  
SYNTAX ZeroBasedCounter64  
UNITS "octets"  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
    "The 64-bit version of the dsmonPdistStatsOctets object.  
  
    Note that this object will only be instantiated if the RMON  
    agent supports High Capacity monitoring for a particular  
    dataSource."  
 ::= { dsmonPdistStatsEntry 7 }

dsmonPdistStatsCreateTime OBJECT-TYPE  
SYNTAX LastCreateTime  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
    "The value of sysUpTime when this dsmonPdistStats entry was  
    last instantiated by the agent. This can be used by the  
    management station to detect if the entry has been deleted  
    and recreated between polls."  
 ::= { dsmonPdistStatsEntry 8 }

```
--
-- Per-Protocol Statistics TopN Control Table
--
```

dsmonPdistTopNCtlTable OBJECT-TYPE

```
SYNTAX      SEQUENCE OF DsmonPdistTopNCtlEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
```

"A set of parameters that control the creation of a report of the top N dsmonPdist entries according to a particular metric.

Note that an agent MAY choose to limit the actual number of entries which may be created in this table. In this case, the agent SHOULD return an error-status of 'resourceUnavailable(13)', as per section 4.2.5 of the 'Protocol Operations for SNMPv2' specification [RFC1905]."

```
::= { dsmonPdistObjects 3 }
```

dsmonPdistTopNCtlEntry OBJECT-TYPE

```
SYNTAX      DsmonPdistTopNCtlEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
```

"A conceptual row in the dsmonPdistTopNCtlTable.

Entries are created and deleted from this table by management action only, using the dsmonPdistTopNCtlStatus RowStatus object.

The agent SHOULD support non-volatile configuration of this table, and upon system initialization, the table SHOULD be initialized with the saved values.

Activation of a control row in this table will cause an associated dsmonPdistTopNTable to be created and maintained by the agent."

```
INDEX { dsmonPdistTopNCtlIndex }
::= { dsmonPdistTopNCtlTable 1 }
```

DsmonPdistTopNCtlEntry ::= SEQUENCE {

```
  dsmonPdistTopNCtlIndex      Integer32,
  dsmonPdistTopNCtlPdistIndex Integer32,
  dsmonPdistTopNCtlRateBase   INTEGER,
  dsmonPdistTopNCtlTimeRemaining Integer32,
  dsmonPdistTopNCtlGeneratedReprts Counter32,
  dsmonPdistTopNCtlDuration   Integer32,
```

```

    dsmonPdistTopNCtlRequestedSize      Integer32,
    dsmonPdistTopNCtlGrantedSize        Integer32,
    dsmonPdistTopNCtlStartTime          TimeStamp,
    dsmonPdistTopNCtlOwner              OwnerString,
    dsmonPdistTopNCtlStatus              RowStatus
}

dsmonPdistTopNCtlIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..65535)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An index that uniquely identifies an entry in the
        dsmonPdistTopNCtlTable, with the same dsmonPdistTopNCtlIndex
        value as this object. Each entry in this table defines one
        Top N report prepared on behalf of the dsmonPdistStatsEntry
        collection with the same dsmonPdistCtlIndex as this object."
    ::= { dsmonPdistTopNCtlEntry 1 }

dsmonPdistTopNCtlPdistIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..65535)
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The dsmonPdistTable for which a top N report will be
        prepared on behalf of this entry. The dsmonPdistTable is
        identified by the value of the dsmonPdistCtlIndex for that
        table - that value is used here to identify the particular
        table.

        This object MUST NOT be modified if the associated
        dsmonPdistTopNCtlStatus object is equal to active(1)."
```

```

    ::= { dsmonPdistTopNCtlEntry 2 }

dsmonPdistTopNCtlRateBase OBJECT-TYPE
    SYNTAX      INTEGER {
        dsmonPdistTopNPkts(1),
        dsmonPdistTopNOctets(2),
        dsmonPdistTopNHCPkts(3),
        dsmonPdistTopNHCOctets(4)
    }
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The variable for each dsmonPdist that the
        dsmonPdistTopNRate and dsmonPdistTopNHCRate variables are
        based upon. Each dsmonPdistTopN report generated on behalf
        of this control entry will be ranked in descending order,
```

based on the associated dsmonPdistStatsTable counter, identified by this object.

The following table identifies the dsmonPdistTable counter associated with each enumeration:

Enumeration	RateBase MIB Object
-----	-----
dsmonPdistTopNPkts	dsmonPdistStatsPkts
dsmonPdistTopNOctets	dsmonPdistStatsOctets
dsmonPdistTopNHCPkts	dsmonPdistStatsHCPkts
dsmonPdistTopNHCOctets	dsmonPdistStatsHCOctets

Note that the dsmonPdistTopNHCPkts and dsmonPdistTopNHCOctets enumerations are only available if the agent supports High Capacity monitoring.

This object MUST NOT be modified if the associated dsmonPdistTopNCtlStatus object is equal to active(1)."

```
::= { dsmonPdistTopNCtlEntry 3 }
```

dsmonPdistTopNCtlTimeRemaining OBJECT-TYPE

SYNTAX Integer32 (0..2147483647)

UNITS "seconds"

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The number of seconds left in the report currently being collected. When this object is modified by the management station, a new collection is started, possibly aborting a currently running report. The new value is used as the requested duration of this report, and is immediately loaded into the associated dsmonPdistTopNCtlDuration object.

When the report finishes, the probe will automatically start another collection with the same initial value of dsmonPdistTopNCtlTimeRemaining. Thus the management station may simply read the resulting reports repeatedly, checking the startTime and duration each time to ensure that a report was not missed or that the report parameters were not changed.

While the value of this object is non-zero, it decrements by one per second until it reaches zero. At the time that this object decrements to zero, the report is made accessible in the dsmonPdistTopNTable, overwriting any report that may be there.

When this object is modified by the management station, any associated entries in the dsmonPdistTopNTable shall be deleted."

DEFVAL { 1800 }  
 ::= { dsmonPdistTopNCtlEntry 4 }

dsmonPdistTopNCtlGeneratedReprts OBJECT-TYPE

SYNTAX Counter32  
 UNITS "reports"  
 MAX-ACCESS read-only  
 STATUS current  
 DESCRIPTION

"The number of reports that have been generated by this entry."

::= { dsmonPdistTopNCtlEntry 5 }

dsmonPdistTopNCtlDuration OBJECT-TYPE

SYNTAX Integer32 (0..2147483647)  
 UNITS "seconds"  
 MAX-ACCESS read-only  
 STATUS current  
 DESCRIPTION

"The number of seconds that this report has collected during the last sampling interval.

When the associated dsmonPdistTopNCtlTimeRemaining object is set, this object shall be set by the probe to the same value and shall not be modified until the next time the dsmonPdistTopNCtlTimeRemaining is set.

This value shall be zero if no reports have been requested for this dsmonPdistTopNCtlEntry."

::= { dsmonPdistTopNCtlEntry 6 }

dsmonPdistTopNCtlRequestedSize OBJECT-TYPE

SYNTAX Integer32 (0..2147483647)  
 UNITS "table entries"  
 MAX-ACCESS read-create  
 STATUS current  
 DESCRIPTION

"The maximum number of dsmonPdist entries requested for this report.

When this object is created or modified, the probe SHOULD set dsmonPdistTopNCtlGrantedSize as closely to this object as is possible for the particular probe implementation and available resources."

DEFVAL { 150 }

::= { dsmonPdistTopNCtlEntry 7 }

dsmonPdistTopNCtlGrantedSize OBJECT-TYPE

SYNTAX Integer32 (0..2147483647)

UNITS "table entries"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The maximum number of dsmonPdist entries in this report.

When the associated dsmonPdistTopNCtlRequestedSize object is created or modified, the probe SHOULD set this object as closely to the requested value as is possible for the particular implementation and available resources. The probe MUST NOT lower this value except as a result of a set to the associated dsmonPdistTopNCtlRequestedSize object.

Protocol entries with the highest value of dsmonPdistTopNRate or dsmonPdistTopNHCRate (depending on the value of the associated dsmonPdistTopNCtlRateBase object) shall be placed in this table in decreasing order of this rate until there is no more room or until there are no more dsmonPdist entries."

::= { dsmonPdistTopNCtlEntry 8 }

dsmonPdistTopNCtlStartTime OBJECT-TYPE

SYNTAX TimeStamp

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The value of sysUpTime when this top N report was last started. In other words, this is the time that the associated dsmonPdistTopNCtlTimeRemaining object was modified to start the requested report or the time the report was last automatically (re)started.

This object may be used by the management station to determine if a report was missed or not."

::= { dsmonPdistTopNCtlEntry 9 }

dsmonPdistTopNCtlOwner OBJECT-TYPE

SYNTAX OwnerString

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The entity that configured this entry and is therefore using the resources assigned to it."

```
::= { dsmonPdistTopNCtlEntry 10 }
```

dsmonPdistTopNCtlStatus OBJECT-TYPE

```
SYNTAX      RowStatus
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
```

"The status of this dsmonPdistTopNCtlEntry.

An entry MUST NOT exist in the active state unless all objects in the entry have an appropriate value.

If this object is not equal to active(1), all associated entries in the dsmonPdistTopNTable shall be deleted by the agent."

```
::= { dsmonPdistTopNCtlEntry 11 }
```

```
--
```

```
-- dsmonPdist TopN Table
```

```
--
```

dsmonPdistTopNTable OBJECT-TYPE

```
SYNTAX      SEQUENCE OF DsmonPdistTopNEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
```

"A set of statistics for those protocol distribution entries that have counted the highest number of octets or packets.

If the dsmonAggControlLocked object is equal to 'false', then all entries in this table SHALL be deleted, and the agent will not process TopN reports on behalf of any dsmonPdistTopNCtlEntry.

When the dsmonAggControlLocked object is set to 'true', then particular reports SHOULD be restarted from the beginning, on behalf of all active rows in the dsmonPdistTopNTable.

Note that dsmonPdist entries which did not increment at all during the report interval SHOULD NOT be included in dsmonPdistTopN reports."

```
::= { dsmonPdistObjects 4 }
```

dsmonPdistTopNEntry OBJECT-TYPE

```
SYNTAX      DsmonPdistTopNEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
```



"A conceptual row in the dsmonPdistTopNTable.

The dsmonPdistTopNCtlIndex value in the index identifies the dsmonPdistTopNCtlEntry on whose behalf this entry was created. Entries in this table are ordered from 1 to 'N', where lower numbers represent higher values of the rate base object, over the report interval."

```
INDEX { dsmonPdistTopNCtlIndex, dsmonPdistTopNIndex }
 ::= { dsmonPdistTopNTable 1 }
```

```
DsmonPdistTopNEntry ::= SEQUENCE {
    dsmonPdistTopNIndex                Integer32,
    dsmonPdistTopNPDLIndex             Integer32,
    dsmonPdistTopNAggGroup             DsmonCounterAggGroupIndex,
    dsmonPdistTopNRate                 Gauge32,
    dsmonPdistTopNRateOvfl             Gauge32,
    dsmonPdistTopNHCRate               CounterBasedGauge64
}
```

```
dsmonPdistTopNIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An index that uniquely identifies an entry in the
        dsmonPdistTopNTable among those in the same report. This
        index is between 1 and N, where N is the number of entries
        in this report. Note that 'N' may change over time, and may
        also be less than the dsmonPdistTopNCtlGrantedSize value
        associated with this entry."
    ::= { dsmonPdistTopNEntry 1 }
```

```
dsmonPdistTopNPDLIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The protocolDirLocalIndex value which identifies the
        protocol associated with this entry.

        If the protocolDirEntry associated with the
        protocolDirLocalIndex with the same value as this object is
        de-activated or deleted, then the agent MUST delete this
        dsmonPdistTopN entry."
    ::= { dsmonPdistTopNEntry 2 }
```

```
dsmonPdistTopNAggGroup OBJECT-TYPE
    SYNTAX      DsmonCounterAggGroupIndex
```

MAX-ACCESS read-only  
STATUS current  
DESCRIPTION

"The DSCP counter aggregation group index value associated with protocol identified in this entry. This object identifies the dsmonAggGroupEntry with the same dsmonAggControlIndex value as the associated dsmonPdistCtlAggProfile object and the same dsmonAggGroupIndex value as this object."

::= { dsmonPdistTopNEntry 3 }

dsmonPdistTopNRate OBJECT-TYPE

SYNTAX Gauge32  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION

"The amount of change in the selected variable during this sampling interval. The selected variable is this protocol's instance of the object selected by dsmonPdistTopNCtlRateBase.

If the associated dsmonPdistTopNCtlRateBase is equal to 'dsmonPdistTopNHCPkts' or 'dsmonPdistTopNHCOctets', then this object will contain the the least significant 32 bits of the associated dsmonPdistTopNHCRate object."

::= { dsmonPdistTopNEntry 4 }

dsmonPdistTopNRate0vfl OBJECT-TYPE

SYNTAX Gauge32  
MAX-ACCESS read-only  
STATUS deprecated  
DESCRIPTION

"The most significant 32 bits of the associated dsmonPdistTopNHCRate object.

If the associated dsmonPdistTopNCtlRateBase is equal to 'dsmonPdistTopNHCPkts' or 'dsmonPdistTopNHCOctets', then this object will contain the upper 32 bits of the associated dsmonPdistTopNHCRate object.

If the associated dsmonPdistTopNCtlRateBase is equal to 'dsmonPdistTopNPkts' or 'dsmonPdistTopNOctets', then this object will contain the value zero.

The agent MAY choose not to instantiate this object if High Capacity monitoring is not supported."

::= { dsmonPdistTopNEntry 5 }

**dsmonPdistTopNHCRate OBJECT-TYPE**

SYNTAX CounterBasedGauge64

MAX-ACCESS read-only

STATUS current

**DESCRIPTION**

"The amount of change in the selected variable during this sampling interval. The selected variable is this protocol's instance of the object selected by dsmonPdistTopNCtlRateBase.

If the associated dsmonPdistTopNCtlRateBase is equal to 'dsmonPdistTopNPkts' or 'dsmonPdistTopNOctets', then this object will contain the value zero, and the associated dsmonPdistTopNRate object will contain the change in the selected variable during the sampling interval.

The agent MAY choose not to instantiate this object if High Capacity monitoring is not supported."

::= { dsmonPdistTopNEntry 6 }

```
-- *****
-- *
-- *      P E R   -   H O S T           C O L L E C T I O N S
-- *
-- *****
```

```
--
-- NL Host Statistics Control Table
--
```

**dsmonHostCtlTable OBJECT-TYPE**

SYNTAX SEQUENCE OF DsmonHostCtlEntry

MAX-ACCESS not-accessible

STATUS current

**DESCRIPTION**

"Controls setup of per counter aggregation group, per network layer host distribution statistics.

Note that an agent MAY choose to limit the actual number of entries which may be created in this table. In this case, the agent SHOULD return an error-status of 'resourceUnavailable(13)', as per section 4.2.5 of the 'Protocol Operations for SNMPv2' specification [RFC1905]."

::= { dsmonHostObjects 1 }

**dsmonHostCtlEntry OBJECT-TYPE**

SYNTAX       DsmonHostCtlEntry  
 MAX-ACCESS   not-accessible  
 STATUS       current  
 DESCRIPTION

"A conceptual row in the dsmonHostCtlTable.

Entries are created and deleted from this table by management action only, using the dsmonHostCtlStatus RowStatus object.

The agent SHOULD support non-volatile configuration of this table, and upon system initialization, the table SHOULD be initialized with the saved values.

Activation of a control row in this table will cause an associated dsmonHostTable to be created and maintained by the agent."

INDEX { dsmonHostCtlIndex }  
 ::= { dsmonHostCtlTable 1 }

```
DsmonHostCtlEntry ::= SEQUENCE {
    dsmonHostCtlIndex                Integer32,
    dsmonHostCtlDataSource            DataSource,
    dsmonHostCtlAggProfile            DsmonCounterAggProfileIndex,
    dsmonHostCtlMaxDesiredEntries    Integer32,
    dsmonHostCtlIPv4PrefixLen         Integer32,
    dsmonHostCtlIPv6PrefixLen         Integer32,
    dsmonHostCtlDroppedFrames         Counter32,
    dsmonHostCtlInserts               Counter32,
    dsmonHostCtlDeletes               Counter32,
    dsmonHostCtlCreateTime            LastCreateTime,
    dsmonHostCtlOwner                 OwnerString,
    dsmonHostCtlStatus                RowStatus
}
```

dsmonHostCtlIndex OBJECT-TYPE

SYNTAX       Integer32 (1..65535)  
 MAX-ACCESS   not-accessible  
 STATUS       current  
 DESCRIPTION

"An arbitrary and unique index for this dsmonHostCtlEntry."

::= { dsmonHostCtlEntry 1 }

dsmonHostCtlDataSource OBJECT-TYPE

SYNTAX       DataSource  
 MAX-ACCESS   read-create  
 STATUS       current  
 DESCRIPTION

"The source of data for the associated dsmonHostTable.

Note that only packets that contain a network protocol encapsulation which contains a DS field [RFC2474] will be counted in this table.

This object MUST NOT be modified if the associated dsmonHostCtlStatus object is equal to active(1)."

::= { dsmonHostCtlEntry 2 }

#### dsmonHostCtlAggProfile OBJECT-TYPE

SYNTAX           DsmonCounterAggProfileIndex

MAX-ACCESS   read-create

STATUS       current

#### DESCRIPTION

"The dsmonAggControlIndex value identifying the counter aggregation profile which should be used on behalf of this dsmonHostCtlEntry.

The associated dsmonAggControlEntry and dsmonAggProfileEntries, identified by the same dsmonAggControlIndex index value, MUST be active in order for this entry to remain active. It is possible for the counter aggregation configuration to change from a valid to invalid state for this dsmonHost collection. In this case, the associated dsmonHostCtlStatus object will be changed to the 'notReady' state, and data collection will not occur on behalf of this control entry.

Note that an agent MAY choose to limit the actual number of counter aggregation profiles which may be applied to a particular data source.

This object MUST NOT be modified if the associated dsmonHostCtlStatus object is equal to active(1)."

::= { dsmonHostCtlEntry 3 }

#### dsmonHostCtlMaxDesiredEntries OBJECT-TYPE

SYNTAX           Integer32 (-1 | 1..2147483647)

UNITS           "table entries"

MAX-ACCESS   read-create

STATUS       current

#### DESCRIPTION

"The maximum number of entries that are desired in the dsmonHostTable on behalf of this control entry. The probe will not create more than this number of associated entries in the table, but MAY choose to create fewer entries in this table for any reason including the lack of resources.

If this value is set to -1, the probe MAY create any number of entries in this table.

This object MUST NOT be modified if the associated dsmonHostCtlStatus object is equal to active(1)."

::= { dsmonHostCtlEntry 4 }

**dsmonHostCtlIPv4PrefixLen OBJECT-TYPE**

SYNTAX Integer32 (8..32)

UNITS "bits"

MAX-ACCESS read-create

STATUS current

**DESCRIPTION**

"The number of 'leftmost' contiguous bits in the host address field for encapsulations of IPv4, that should be maintained in this collection. This object controls how the dsmonHostAddress object is derived for packets which contain an encapsulation of IPv4.

If this object has a value less than 32, then 'm' rightmost bits, where 'm' is equal to '32 - dsmonHostCtlIPv4PrefixLen', will be cleared to zero for counting purposes only. The 'leftmost' bit is the most significant bit of the first network-byte-order octet of the address.

If this object is equal to 32, then no bits are cleared in each dsmonHostAddress field.

This object MUST NOT be modified if the associated dsmonHostCtlStatus object is equal to active(1)."

DEFVAL { 32 }

::= { dsmonHostCtlEntry 5 }

**dsmonHostCtlIPv6PrefixLen OBJECT-TYPE**

SYNTAX Integer32 (8..128)

UNITS "bits"

MAX-ACCESS read-create

STATUS current

**DESCRIPTION**

"The number of 'leftmost' contiguous bits in the host address field for encapsulations of IPv6, that should be maintained in this collection. This object controls how the dsmonHostAddress object is derived for packets which contain an encapsulation of IPv6.

If this object has a value less than 128, then 'm' rightmost bits, where 'm' is equal to '128 -

dsmonHostCtlIPv6PrefixLen', will be cleared to zero for counting purposes only. The 'leftmost' bit is the most significant bit of the first network-byte-order octet of the address.

If this object is equal to 128, then no bits are cleared in each dsmonHostAddress field.

This object MUST NOT be modified if the associated dsmonHostCtlStatus object is equal to active(1)."

DEFVAL { 128 }  
 ::= { dsmonHostCtlEntry 6 }

#### dsmonHostCtlDroppedFrames OBJECT-TYPE

SYNTAX Counter32  
UNITS "frames"  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION

"The total number of frames which were received by the probe and therefore not accounted for in the \*StatsDropEvents, but for which the probe chose not to count for the associated dsmonHost entries for whatever reason. Most often, this event occurs when the probe is out of some resources and decides to shed load from this collection.

This count does not include packets that were not counted because they had MAC-layer errors.

Note that if the dsmonHostTable is inactive because no appropriate protocols are enabled in the protocol directory, this value SHOULD be 0.

Note that, unlike the dropEvents counter, this number is the exact number of frames dropped."

::= { dsmonHostCtlEntry 7 }

#### dsmonHostCtlInserts OBJECT-TYPE

SYNTAX Counter32  
UNITS "table entries"  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION

"The number of times a dsmonHost entry has been inserted into the dsmonHost table. If an entry is inserted, then deleted, and then inserted, this counter will be incremented by 2.

To allow for efficient implementation strategies, agents MAY delay updating this object for short periods of time. For example, an implementation strategy may allow internal data structures to differ from those visible via SNMP for short periods of time. This counter may reflect the internal data structures for those short periods of time.

Note that the table size can be determined by subtracting dsmonHostCtlDeletes from dsmonHostCtlInserts."

::= { dsmonHostCtlEntry 8 }

**dsmonHostCtlDeletes OBJECT-TYPE**

SYNTAX Counter32

UNITS "table entries"

MAX-ACCESS read-only

STATUS current

**DESCRIPTION**

"The number of times a dsmonHost entry has been deleted from the dsmonHost table (for any reason). If an entry is deleted, then inserted, and then deleted, this counter will be incremented by 2.

To allow for efficient implementation strategies, agents MAY delay updating this object for short periods of time. For example, an implementation strategy may allow internal data structures to differ from those visible via SNMP for short periods of time. This counter may reflect the internal data structures for those short periods of time.

Note that the table size can be determined by subtracting dsmonHostCtlDeletes from dsmonHostCtlInserts."

::= { dsmonHostCtlEntry 9 }

**dsmonHostCtlCreateTime OBJECT-TYPE**

SYNTAX LastCreateTime

MAX-ACCESS read-only

STATUS current

**DESCRIPTION**

"The value of sysUpTime when this control entry was last activated. This can be used by the management station to detect if the table has been deleted and recreated between polls."

::= { dsmonHostCtlEntry 10 }

**dsmonHostCtlOwner OBJECT-TYPE**

SYNTAX OwnerString

MAX-ACCESS read-create

STATUS current



## DESCRIPTION

"The entity that configured this entry and is therefore using the resources assigned to it."

::= { dsmonHostCtlEntry 11 }

## dsmonHostCtlStatus OBJECT-TYPE

SYNTAX RowStatus

MAX-ACCESS read-create

STATUS current

## DESCRIPTION

"The status of this dsmonHostCtlEntry.

An entry MUST NOT exist in the active state unless all objects in the entry have an appropriate value.

If this object is not equal to active(1), all associated entries in the dsmonHostTable shall be deleted."

::= { dsmonHostCtlEntry 12 }

--

-- NL Host Statistics Table

--

## dsmonHostTable OBJECT-TYPE

SYNTAX SEQUENCE OF DsmonHostEntry

MAX-ACCESS not-accessible

STATUS current

## DESCRIPTION

"A collection of statistics for particular network protocols which contain a DS field, and that has been discovered on a particular dataSource.

The probe will add to this table all appropriate network protocols, for each network address seen as the source or destination address in all packets with no MAC errors, and will increment octet and packet counts in the table for all packets with no MAC errors.

If the dsmonAggControlLocked object is equal to 'false', then all entries in this table will be deleted, and the agent will not process packets on behalf of any dsmonHostCtlEntry."

::= { dsmonHostObjects 2 }

## dsmonHostEntry OBJECT-TYPE

SYNTAX DsmonHostEntry

MAX-ACCESS not-accessible

STATUS current

**DESCRIPTION**

"A list of information on Differentiated Services DSCP usage, containing packet and octet counters for each counter aggregation group index configured for collection per host address, as identified in the dsmonAggProfileTable.

The dsmonHostCtlIndex value in the index identifies the dsmonHostCtlEntry on whose behalf this entry was created.

The protocolDirLocalIndex value in the index identifies the specific network layer protocol encapsulation associated with each entry, and the network protocol type of the dsmonHostAddress object. It MUST identify a protocolDirEntry which contains a DS field (e.g., IPv4 or IPv6). Note that if a protocol encapsulation with multiple network layers is specified, then associated entries in this table refer to the innermost network protocol layer host address.

The dsmonAggGroupIndex value in the index is determined by examining the DSCP value in each monitored packet, and the dsmonAggProfileTable entry configured for that value.

An example of the indexing of this entry is  
dsmonHostOutPkts.1.27273.3.200.4.171.69.120.0"

```
INDEX { dsmonHostCtlIndex,
        dsmonHostTimeMark,
        dsmonAggGroupIndex,
        protocolDirLocalIndex,
        dsmonHostAddress }
 ::= { dsmonHostTable 1 }
```

```
DsmonHostEntry ::= SEQUENCE {
    dsmonHostTimeMark          TimeFilter,
    dsmonHostAddress            OCTET STRING,
    dsmonHostInPkts             ZeroBasedCounter32,
    dsmonHostInOctets           ZeroBasedCounter32,
    dsmonHostInOvflPkts         ZeroBasedCounter32,
    dsmonHostInOvflOctets       ZeroBasedCounter32,
    dsmonHostInHCPkts           ZeroBasedCounter64,
    dsmonHostInHCOctets         ZeroBasedCounter64,
    dsmonHostOutPkts            ZeroBasedCounter32,
    dsmonHostOutOctets          ZeroBasedCounter32,
    dsmonHostOutOvflPkts        ZeroBasedCounter32,
    dsmonHostOutOvflOctets      ZeroBasedCounter32,
    dsmonHostOutHCPkts          ZeroBasedCounter64,
    dsmonHostOutHCOctets        ZeroBasedCounter64,
    dsmonHostCreateTime         LastCreateTime
```

}

**dsmonHostTimeMark OBJECT-TYPE**

SYNTAX TimeFilter  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION

"The Time Filter index for this table. This object may be used by a management station to retrieve only rows which have been created or modified since a particular time. Note that the current value for a row are always returned and the TimeFilter is not a historical data archiving mechanism. Refer to RFC 2021 [RFC2021] for a detailed description of TimeFilter operation."

::= { dsmonHostEntry 1 }

**dsmonHostAddress OBJECT-TYPE**

SYNTAX OCTET STRING (SIZE (0..110))  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION

"The network address for this dsmonHostEntry.

This object is encoded according to the protocol type indicated by the protocolDirLocalIndex value in the index.

In addition, this object may have some 'rightmost' bits cleared to zero for counting purposes, as indicated by the associated dsmonHostCtlIPv4PrefixLen or dsmonHostCtlIPv6PrefixLen objects."

::= { dsmonHostEntry 2 }

**dsmonHostInPkts OBJECT-TYPE**

SYNTAX ZeroBasedCounter32  
UNITS "packets"  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION

"The number of packets without errors, using one of the DSCP values in the indicated counter aggregation group, and transmitted to this address, since this entry was added to the dsmonHostTable. Note that this is the number of link-layer packets, so if a single network-layer packet is fragmented into several link-layer frames, this counter is incremented several times."

::= { dsmonHostEntry 3 }

**dsmonHostInOctets OBJECT-TYPE**

SYNTAX ZeroBasedCounter32  
UNITS "octets"  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
"The number of octets in all packets, transmitted to this address and using one of the DSCP values in the indicated counter aggregation group, since this entry was added to the dsmonHostTable (excluding framing bits but including FCS octets), excluding those octets in packets that contained errors."

Note this doesn't count just those octets in the particular protocol frames, but includes the entire packet that contained the protocol."

::= { dsmonHostEntry 4 }

dsmonHostInOvflPkts OBJECT-TYPE

SYNTAX ZeroBasedCounter32  
MAX-ACCESS read-only  
STATUS deprecated  
DESCRIPTION

"The number of times the associated dsmonHostInPkts counter has overflowed. Note that this object will only be instantiated if the associated dsmonHostInHCPkts object is also instantiated for a particular dataSource."

::= { dsmonHostEntry 5 }

dsmonHostInOvflOctets OBJECT-TYPE

SYNTAX ZeroBasedCounter32  
MAX-ACCESS read-only  
STATUS deprecated  
DESCRIPTION

"The number of times the associated dsmonHostInOctets counter has overflowed. Note that this object will only be instantiated if the associated dsmonHostInHCOctets object is also instantiated for a particular dataSource."

::= { dsmonHostEntry 6 }

dsmonHostInHCPkts OBJECT-TYPE

SYNTAX ZeroBasedCounter64  
UNITS "packets"  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION

"The 64-bit version of the dsmonHostInPkts object."

Note that this object will only be instantiated if the RMON

agent supports High Capacity monitoring for a particular  
dataSource."

::= { dsmonHostEntry 7 }

dsmonHostInHC0ctets OBJECT-TYPE

SYNTAX ZeroBasedCounter64  
UNITS "octets"  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION

"The 64-bit version of the dsmonHostIn0ctets object.

Note that this object will only be instantiated if the RMON  
agent supports High Capacity monitoring for a particular  
dataSource."

::= { dsmonHostEntry 8 }

dsmonHost0utPkts OBJECT-TYPE

SYNTAX ZeroBasedCounter32  
UNITS "packets"  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION

"The number of packets without errors, using one of the DSCP  
values in the indicated counter aggregation group, and  
transmitted by this address, since this entry was added to  
the dsmonHostTable. Note that this is the number of link-  
layer packets, so if a single network-layer packet is  
fragmented into several link-layer frames, this counter is  
incremented several times."

::= { dsmonHostEntry 9 }

dsmonHost0ut0ctets OBJECT-TYPE

SYNTAX ZeroBasedCounter32  
UNITS "octets"  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION

"The number of octets, transmitted by this address and using  
one of the DSCP values in the identified counter aggregation  
group, since this entry was added to the dsmonHostTable  
(excluding framing bits but including FCS octets), excluding  
those octets in packets that contained errors.

Note this doesn't count just those octets in the particular  
protocol frames, but includes the entire packet that  
contained the protocol."

::= { dsmonHostEntry 10 }

**dsmonHostOut0vflPkts OBJECT-TYPE****SYNTAX** ZeroBasedCounter32**MAX-ACCESS** read-only**STATUS** deprecated**DESCRIPTION**

"The number of times the associated dsmonHostOutPkts counter has overflowed. Note that this object will only be instantiated if the associated dsmonHostOutHCPkts object is also instantiated for a particular dataSource."

**::= { dsmonHostEntry 11 }****dsmonHostOut0vflOctets OBJECT-TYPE****SYNTAX** ZeroBasedCounter32**MAX-ACCESS** read-only**STATUS** deprecated**DESCRIPTION**

"The number of times the associated dsmonHostOutOctets counter has overflowed. Note that this object will only be instantiated if the associated dsmonHostOutHCOctets object is also instantiated for a particular dataSource."

**::= { dsmonHostEntry 12 }****dsmonHostOutHCPkts OBJECT-TYPE****SYNTAX** ZeroBasedCounter64**UNITS** "packets"**MAX-ACCESS** read-only**STATUS** current**DESCRIPTION**

"The 64-bit version of the dsmonHostOutPkts object.

Note that this object will only be instantiated if the RMON agent supports High Capacity monitoring for a particular dataSource."

**::= { dsmonHostEntry 13 }****dsmonHostOutHCOctets OBJECT-TYPE****SYNTAX** ZeroBasedCounter64**UNITS** "octets"**MAX-ACCESS** read-only**STATUS** current**DESCRIPTION**

"The 64-bit version of the dsmonHostOutOctets object.

Note that this object will only be instantiated if the RMON agent supports High Capacity monitoring for a particular dataSource."

**::= { dsmonHostEntry 14 }**

**dsmonHostCreateTime OBJECT-TYPE**

SYNTAX LastCreateTime

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The value of sysUpTime when this dsmonHost entry was last instantiated by the agent. This can be used by the management station to ensure that the entry has not been deleted and recreated between polls."

::= { dsmonHostEntry 15 }

--

## -- Per-Protocol Per-Host NL Statistics TopN Control Table

--

**dsmonHostTopNCtlTable OBJECT-TYPE**

SYNTAX SEQUENCE OF DsmonHostTopNCtlEntry

MAX-ACCESS not-accessible

STATUS current

## DESCRIPTION

"A set of parameters that control the creation of a report of the top N dsmonHost entries according to a selected metric.

Note that an agent MAY choose to limit the actual number of entries which may be created in this table. In this case, the agent SHOULD return an error-status of 'resourceUnavailable(13)', as per section 4.2.5 of the 'Protocol Operations for SNMPv2' specification [RFC1905]."

::= { dsmonHostObjects 3 }

**dsmonHostTopNCtlEntry OBJECT-TYPE**

SYNTAX DsmonHostTopNCtlEntry

MAX-ACCESS not-accessible

STATUS current

## DESCRIPTION

"A conceptual row in the dsmonHostTopNCtlTable.

Entries are created and deleted from this table by management action only, using the dsmonHostTopNCtlStatus RowStatus object.

The agent SHOULD support non-volatile configuration of this table, and upon system initialization, the table SHOULD be initialized with the saved values.

Activation of a control row in this table will cause an

associated dsmonHostTopNTable to be created and maintained by the agent."

```
INDEX { dsmonHostTopNCtlIndex }
::= { dsmonHostTopNCtlTable 1 }
```

```
DsmonHostTopNCtlEntry ::= SEQUENCE {
    dsmonHostTopNCtlIndex          Integer32,
    dsmonHostTopNCtlHostIndex      Integer32,
    dsmonHostTopNCtlRateBase       INTEGER,
    dsmonHostTopNCtlTimeRemaining  Integer32,
    dsmonHostTopNCtlGeneratedReports Counter32,
    dsmonHostTopNCtlDuration       Integer32,
    dsmonHostTopNCtlRequestedSize  Integer32,
    dsmonHostTopNCtlGrantedSize    Integer32,
    dsmonHostTopNCtlStartTime      TimeStamp,
    dsmonHostTopNCtlOwner          OwnerString,
    dsmonHostTopNCtlStatus         RowStatus
}
```

```
dsmonHostTopNCtlIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..65535)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An index that uniquely identifies an entry in the
        dsmonHostTopNCtlTable. Each such entry defines one Top N
        report prepared for one RMON dataSource."
    ::= { dsmonHostTopNCtlEntry 1 }
```

```
dsmonHostTopNCtlHostIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..65535)
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The dsmonHostTable for which a top N report will be
        prepared on behalf of this entry. The dsmonHostTable is
        identified by the value of the dsmonHostCtlIndex for that
        table - that value is used here to identify the particular
        table.

        This object MUST NOT be modified if the associated
        dsmonHostTopNCtlStatus object is equal to active(1)."
```

```
    ::= { dsmonHostTopNCtlEntry 2 }
```

```
dsmonHostTopNCtlRateBase OBJECT-TYPE
    SYNTAX      INTEGER {
        dsmonHostTopNInPkts(1),
        dsmonHostTopNInOctets(2),
```



```

        dsmonHostTopNOutPkts(3),
        dsmonHostTopNOutOctets(4),
        dsmonHostTopNTotalPkts(5),
        dsmonHostTopNTotalOctets(6),
        dsmonHostTopNInHCPkts(7),
        dsmonHostTopNInHCOctets(8),
        dsmonHostTopNOutHCPkts(9),
        dsmonHostTopNOutHCOctets(10),
        dsmonHostTopNTotalHCPkts(11),
        dsmonHostTopNTotalHCOctets(12)
    }
MAX-ACCESS read-create
STATUS current
DESCRIPTION
    "The variable(s) for each dsmonHost that the
    dsmonHostTopNRate and dsmonHostTopNHCRate variables are
    based upon. Each dsmonHostTopN report generated on behalf
    of this control entry will be ranked in descending order,
    based on the associated dsmonHostTable counter(s),
    identified by this object.

```

The following table identifies the dsmonHostTable counters associated with each enumeration:

Enumeration	RateBase MIB Objects
-----	-----
dsmonHostTopNInPkts	dsmonHostInPkts
dsmonHostTopNInOctets	dsmonHostInOctets
dsmonHostTopNOutPkts	dsmonHostOutPkts
dsmonHostTopNOutOctets	dsmonHostOutOctets
dsmonHostTopNTotalPkts	dsmonHostInPkts + dsmonHostOutPkts
dsmonHostTopNTotalOctets	dsmonHostInOctets + dsmonHostOutOctets
dsmonHostTopNInHCPkts	dsmonHostInHCPkts
dsmonHostTopNInHCOctets	dsmonHostInHCOctets
dsmonHostTopNOutHCPkts	dsmonHostOutHCPkts
dsmonHostTopNOutHCOctets	dsmonHostOutHCPkts
dsmonHostTopNTotalHCPkts	dsmonHostInHCPkts + dsmonHostOutHCPkts
dsmonHostTopNTotalHCOctets	dsmonHostInHCOctets + dsmonHostOutHCOctets

The following enumerations are only available if the agent supports High Capacity monitoring:

```

dsmonHostTopNInHCPkts
dsmonHostTopNInHCOctets

```

dsmonHostTopNOutHCPkts  
 dsmonHostTopNOutHCOctets  
 dsmonHostTopNTotalHCPkts  
 dsmonHostTopNTotalHCOctets

It is an implementation-specific matter whether an agent can detect an overflow condition resulting from the addition of two counter delta values for the following enumerations:

dsmonHostTopNTotalPkts  
 dsmonHostTopNTotalOctets  
 dsmonHostTopNTotalHCPkts  
 dsmonHostTopNTotalHCOctets

In the event such an overflow condition can be detected by the agent, the associated dsmonHostTopNRate, dsmonHostTopNRateOvfl, and/or dsmonHostTopNHCRate objects should be set to their maximum value.

This object MUST NOT be modified if the associated dsmonHostTopNCtlStatus object is equal to active(1)."  
 ::= { dsmonHostTopNCtlEntry 3 }

dsmonHostTopNCtlTimeRemaining OBJECT-TYPE

SYNTAX Integer32 (0..2147483647)

UNITS "seconds"

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The number of seconds left in the report currently being collected. When this object is modified by the management station, a new collection is started, possibly aborting a currently running report. The new value is used as the requested duration of this report, and is immediately loaded into the associated dsmonHostTopNCtlDuration object.

When the report finishes, the probe will automatically start another collection with the same initial value of dsmonHostTopNCtlTimeRemaining. Thus the management station may simply read the resulting reports repeatedly, checking the startTime and duration each time to ensure that a report was not missed or that the report parameters were not changed.

While the value of this object is non-zero, it decrements by one per second until it reaches zero. At the time that this object decrements to zero, the report is made accessible in the dsmonHostTopNTable, overwriting any report that may be

there.

When this object is modified by the management station, any associated entries in the dsmonHostTopNTable shall be deleted."

```
DEFVAL { 1800 }
::= { dsmonHostTopNCtlEntry 4 }
```

dsmonHostTopNCtlGeneratedReports OBJECT-TYPE

```
SYNTAX      Counter32
UNITS       "reports"
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The number of reports that have been generated by this
    entry."
::= { dsmonHostTopNCtlEntry 5 }
```

dsmonHostTopNCtlDuration OBJECT-TYPE

```
SYNTAX      Integer32 (0..2147483647)
UNITS       "seconds"
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The number of seconds that this report has collected during
    the last sampling interval."
```

When the associated dsmonHostTopNCtlTimeRemaining object is set, this object shall be set by the probe to the same value and shall not be modified until the next time the dsmonHostTopNCtlTimeRemaining is set.

This value shall be zero if no reports have been requested for this dsmonHostTopNCtlEntry."

```
::= { dsmonHostTopNCtlEntry 6 }
```

dsmonHostTopNCtlRequestedSize OBJECT-TYPE

```
SYNTAX      Integer32 (0..2147483647)
UNITS       "table entries"
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "The maximum number of dsmonHost entries requested for this
    report."
```

When this object is created or modified, the probe SHOULD set dsmonHostTopNCtlGrantedSize as closely to this object as is possible for the particular probe implementation and

available resources."  
 DEFVAL { 150 }  
 ::= { dsmonHostTopNCtlEntry 7 }

dsmonHostTopNCtlGrantedSize OBJECT-TYPE  
 SYNTAX Integer32 (0..2147483647)  
 UNITS "table entries"  
 MAX-ACCESS read-only  
 STATUS current  
 DESCRIPTION

"The maximum number of dsmonHost entries in this report.

When the associated dsmonHostTopNCtlRequestedSize object is created or modified, the probe SHOULD set this object as closely to the requested value as is possible for the particular implementation and available resources. The probe MUST NOT lower this value except as a result of a set to the associated dsmonHostTopNCtlRequestedSize object.

Protocol entries with the highest value of dsmonHostTopNRate or dsmonHostTopNHCRate (depending on the value of the associated dsmonHostTopNCtlRateBase object) shall be placed in this table in decreasing order of this rate until there is no more room or until there are no more dsmonHost entries."

::= { dsmonHostTopNCtlEntry 8 }

dsmonHostTopNCtlStartTime OBJECT-TYPE  
 SYNTAX TimeStamp  
 MAX-ACCESS read-only  
 STATUS current  
 DESCRIPTION

"The value of sysUpTime when this top N report was last started. In other words, this is the time that the associated dsmonHostTopNCtlTimeRemaining object was modified to start the requested report or the time the report was last automatically (re)started.

This object may be used by the management station to determine if a report was missed or not."

::= { dsmonHostTopNCtlEntry 9 }

dsmonHostTopNCtlOwner OBJECT-TYPE  
 SYNTAX OwnerString  
 MAX-ACCESS read-create  
 STATUS current  
 DESCRIPTION

"The entity that configured this entry and is therefore using the resources assigned to it."  
 ::= { dsmonHostTopNCtlEntry 10 }

dsmonHostTopNCtlStatus OBJECT-TYPE

SYNTAX RowStatus  
MAX-ACCESS read-create  
STATUS current  
DESCRIPTION

"The status of this dsmonHostTopNCtlEntry.

An entry MUST NOT exist in the active state unless all objects in the entry have an appropriate value.

If this object is not equal to active(1), all associated entries in the dsmonHostTopNTable shall be deleted by the agent."

::= { dsmonHostTopNCtlEntry 11 }

--  
-- dsmonHost TopN Table  
--

dsmonHostTopNTable OBJECT-TYPE

SYNTAX SEQUENCE OF DsmonHostTopNEntry  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION

"A set of statistics for those dsmonHost entries that have counted the highest number of octets or packets.

If the dsmonAggControlLocked object is equal to 'false', then all entries in this table SHALL be deleted, and the agent will not process TopN reports on behalf of any dsmonHostTopNCtlEntry.

When the dsmonAggControlLocked object is set to 'true', then particular reports SHOULD be restarted from the beginning, on behalf of all active rows in the dsmonHostTopNCtlTable.

Note that dsmonHost entries which did not increment at all during the report interval SHOULD NOT be included in dsmonHostTopN reports."

::= { dsmonHostObjects 4 }

dsmonHostTopNEntry OBJECT-TYPE

SYNTAX DsmonHostTopNEntry  
MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"A conceptual row in the dsmonHostTopNTable.

The dsmonHostTopNctlIndex value in the index identifies the dsmonHostTopNctlEntry on whose behalf this entry was created.

Entries in this table are ordered from 1 to 'N', where lower numbers represent higher values of the rate base object, over the report interval."

INDEX { dsmonHostTopNctlIndex, dsmonHostTopNIndex }

::= { dsmonHostTopNTable 1 }

DsmonHostTopNEntry ::= SEQUENCE {

dsmonHostTopNIndex	Integer32,
dsmonHostTopNPdLocalIndex	Integer32,
dsmonHostTopNAddress	OCTET STRING,
dsmonHostTopNaggGroup	DsmonCounterAggGroupIndex,
dsmonHostTopNRate	Gauge32,
dsmonHostTopNRateOvfl	Gauge32,
dsmonHostTopNHCRate	CounterBasedGauge64

}

dsmonHostTopNIndex OBJECT-TYPE

SYNTAX Integer32 (1..2147483647)

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An index that uniquely identifies an entry in the dsmonHostTopNTable among those in the same report. This index is between 1 and N, where N is the number of entries in this report."

::= { dsmonHostTopNEntry 1 }

dsmonHostTopNPdLocalIndex OBJECT-TYPE

SYNTAX Integer32 (1..2147483647)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The protocolDirLocalIndex value which identifies the protocol associated with the dsmonHostTopNAddress object in this entry.

If the protocolDirEntry associated with the protocolDirLocalIndex with the same value as this object is de-activated or deleted, then the agent MUST delete this dsmonHostTopN entry."

::= { dsmonHostTopNEntry 2 }

dsmonHostTopNAddress OBJECT-TYPE

SYNTAX OCTET STRING

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The dsmonHostAddress value for the network host identified in this entry. The associated dsmonHostTopNPDLocalIndex object identifies the network protocol type and the encoding rules for this object."

::= { dsmonHostTopNEntry 3 }

dsmonHostTopNAggGroup OBJECT-TYPE

SYNTAX DsmonCounterAggGroupIndex

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The counter aggregation group index value associated with host identified in this entry. This object identifies the dsmonAggGroupEntry with the same dsmonAggControlIndex value as the associated dsmonHostCtlAggProfile object and the same dsmonAggGroupIndex value as this object."

::= { dsmonHostTopNEntry 4 }

dsmonHostTopNRate OBJECT-TYPE

SYNTAX Gauge32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The amount of change in the selected variable during this sampling interval. The selected variable is this host's instance of the object selected by dsmonHostTopNCtrlRateBase.

If the associated dsmonHostTopNCtrlRateBase indicates a High Capacity monitoring enumeration, (e.g. 'dsmonHostTopNInHCPkts'), then this object will contain the the least significant 32 bits of the associated dsmonHostTopNHCRate object."

::= { dsmonHostTopNEntry 5 }

dsmonHostTopNRateOvfl OBJECT-TYPE

SYNTAX Gauge32

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The most significant 32 bits of the associated dsmonHostTopNHCRate object."

If the associated dsmonHostTopNCtlRateBase is equal to any of the High Capacity monitoring enumerations (e.g. 'dsmonHostTopNInHCPkts'), then this object will contain the upper 32 bits of the associated dsmonHostTopNHCRate object.

If the associated dsmonHostTopNCtlRateBase is not equal to any of High Capacity monitoring enumerations, then this object will contain the value zero.

The agent MAY choose not to instantiate this object if High Capacity monitoring is not supported."

::= { dsmonHostTopNEntry 6 }

dsmonHostTopNHCRate OBJECT-TYPE

SYNTAX CounterBasedGauge64

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The amount of change in the selected variable during this sampling interval. The selected variable is this host's instance of the object selected by dsmonHostTopNCtlRateBase.

If the associated dsmonHostTopNCtlRateBase is not equal to any of the High Capacity monitoring enumerations (e.g., 'dsmonHostTopNInPkts'), then this object will contain the value zero, and the associated dsmonHostTopNRate object will contain the change in the selected variable during the sampling interval.

The agent MAY choose not to instantiate this object if High Capacity monitoring is not supported."

::= { dsmonHostTopNEntry 7 }

```
-- *****
-- *
-- *   P E R   -   C O N V E R S I O N   C O L L E C T I O N S   *
-- *
-- *****
```

```
--
-- AL Matrix Statistics Control Table
--
```

dsmonMatrixCtlTable OBJECT-TYPE

SYNTAX SEQUENCE OF DsmonMatrixCtlEntry

MAX-ACCESS not-accessible

STATUS current



**DESCRIPTION**

"Controls setup of per counter aggregation group, per host-pair, application protocol distribution statistics.

Note that an agent MAY choose to limit the actual number of entries which may be created in this table. In this case, the agent SHOULD return an error-status of 'resourceUnavailable(13)', as per section 4.2.5 of the 'Protocol Operations for SNMPv2' specification [RFC1905]."

::= { dsmonMatrixObjects 1 }

**dsmonMatrixCtlEntry OBJECT-TYPE**

SYNTAX           DsmonMatrixCtlEntry  
MAX-ACCESS      not-accessible  
STATUS           current  
DESCRIPTION

"A conceptual row in the dsmonMatrixCtlTable.

Entries are created and deleted from this table by management action only, using the dsmonMatrixCtlStatus RowStatus object.

The agent SHOULD support non-volatile configuration of this table, and upon system initialization, the table SHOULD be initialized with the saved values.

Activation of a control row in this table will cause an associated dsmonMatrixSDTable and dsmonMatrixDSTable to be created and maintained by the agent."

INDEX { dsmonMatrixCtlIndex }  
::= { dsmonMatrixCtlTable 1 }

**DsmonMatrixCtlEntry ::= SEQUENCE {**

dsmonMatrixCtlIndex	Integer32,
dsmonMatrixCtlDataSource	DataSource,
dsmonMatrixCtlAggProfile	DsmonCounterAggProfileIndex,
dsmonMatrixCtlMaxDesiredEntries	Integer32,
dsmonMatrixCtlDroppedFrames	Counter32,
dsmonMatrixCtlInserts	Counter32,
dsmonMatrixCtlDeletes	Counter32,
dsmonMatrixCtlCreateTime	LastCreateTime,
dsmonMatrixCtlOwner	OwnerString,
dsmonMatrixCtlStatus	RowStatus

}

**dsmonMatrixCtlIndex OBJECT-TYPE**

SYNTAX           Integer32 (1..65535)  
MAX-ACCESS      not-accessible

STATUS current  
DESCRIPTION  
"An arbitrary and unique index for this  
dsmonMatrixCtlEntry."  
 ::= { dsmonMatrixCtlEntry 1 }

**dsmonMatrixCtlDataSource OBJECT-TYPE**

SYNTAX DataSource  
MAX-ACCESS read-create  
STATUS current  
DESCRIPTION  
"The source of data for the associated dsmonMatrixSDTable  
and dsmonMatrixDSTable.

Note that only packets that contain a network protocol  
encapsulation which contains a DS field [RFC2474] will be  
counted in this table.

This object MUST NOT be modified if the associated  
dsmonMatrixCtlStatus object is equal to active(1)."  
 ::= { dsmonMatrixCtlEntry 2 }

**dsmonMatrixCtlAggProfile OBJECT-TYPE**

SYNTAX DsmonCounterAggProfileIndex  
MAX-ACCESS read-create  
STATUS current  
DESCRIPTION  
"The dsmonAggControlIndex value identifying the counter  
aggregation profile which should be used on behalf of this  
dsmonMatrixCtlEntry.

The associated dsmonAggControlEntry and  
dsmonAggProfileEntries, identified by the same  
dsmonAggControlIndex index value, MUST be active in order  
for this entry to remain active. It is possible for the  
counter aggregation configuration to change from a valid to  
invalid state for this dsmonMatrix collection. In this  
case, the associated dsmonMatrixCtlStatus object will be  
changed to the 'notReady' state, and data collection will  
not occur on behalf of this control entry.

Note that an agent MAY choose to limit the actual number of  
counter aggregation profiles which may be applied to a  
particular data source.

This object MUST NOT be modified if the associated  
dsmonMatrixCtlStatus object is equal to active(1)."  
 ::= { dsmonMatrixCtlEntry 3 }

**dsmonMatrixCtlMaxDesiredEntries OBJECT-TYPE**

SYNTAX Integer32 (-1 | 1..2147483647)

UNITS "table entries"

MAX-ACCESS read-create

STATUS current

**DESCRIPTION**

"The maximum number of entries that are desired in the dsmonMatrix tables on behalf of this control entry. The probe will not create more than this number of associated entries in these tables, but may choose to create fewer entries in this table for any reason including the lack of resources.

If this value is set to -1, the probe may create any number of entries in this table.

This object **MUST NOT** be modified if the associated dsmonMatrixCtlStatus object is equal to active(1)."

::= { dsmonMatrixCtlEntry 4 }

**dsmonMatrixCtlDroppedFrames OBJECT-TYPE**

SYNTAX Counter32

UNITS "frames"

MAX-ACCESS read-only

STATUS current

**DESCRIPTION**

"The total number of frames which were received by the probe and therefore not accounted for in the \*StatsDropEvents, but for which the probe chose not to count for the associated dsmonMatrixSD and dsmonMatrixDS entries for whatever reason. Most often, this event occurs when the probe is out of some resources and decides to shed load from this collection.

This count does not include packets that were not counted because they had MAC-layer errors.

Note that if the dsmonMatrix tables are inactive because no appropriate protocols are enabled in the protocol directory, this value **SHOULD** be 0.

Note that, unlike the dropEvents counter, this number is the exact number of frames dropped."

::= { dsmonMatrixCtlEntry 5 }

**dsmonMatrixCtlInserts OBJECT-TYPE**

SYNTAX Counter32

UNITS "table entries"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of times a dsmonMatrix entry has been inserted into the dsmonMatrix tables. If an entry is inserted, then deleted, and then inserted, this counter will be incremented by 2. The addition of a conversation into both the dsmonMatrixSDTable and dsmonMatrixDSTable shall be counted as two insertions (even though every addition into one table must be accompanied by an insertion into the other).

To allow for efficient implementation strategies, agents may delay updating this object for short periods of time. For example, an implementation strategy may allow internal data structures to differ from those visible via SNMP for short periods of time. This counter may reflect the internal data structures for those short periods of time. Note that the sum of the dsmonMatrixSDTable and dsmonMatrixDSTable sizes can be determined by subtracting dsmonMatrixCtlDeletes from dsmonMatrixCtlInserts."

::= { dsmonMatrixCtlEntry 6 }

dsmonMatrixCtlDeletes OBJECT-TYPE

SYNTAX Counter32

UNITS "table entries"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of times a dsmonMatrix entry has been deleted from the dsmonMatrix tables (for any reason). If an entry is deleted, then inserted, and then deleted, this counter will be incremented by 2. The deletion of a conversation from both the dsmonMatrixSDTable and dsmonMatrixDSTable shall be counted as two deletions (even though every deletion from one table must be accompanied by a deletion from the other).

To allow for efficient implementation strategies, agents MAY delay updating this object for short periods of time. For example, an implementation strategy may allow internal data structures to differ from those visible via SNMP for short periods of time. This counter may reflect the internal data structures for those short periods of time.

Note that the sum of the dsmonMatrixSDTable and dsmonMatrixDSTable sizes can be determined by subtracting dsmonMatrixCtlDeletes from dsmonMatrixCtlInserts."

::= { dsmonMatrixCtlEntry 7 }

**dsmonMatrixCtlCreateTime OBJECT-TYPE**

SYNTAX LastCreateTime

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The value of sysUpTime when this control entry was last activated. This can be used by the management station to detect if the table has been deleted and recreated between polls."

::= { dsmonMatrixCtlEntry 8 }

**dsmonMatrixCtlOwner OBJECT-TYPE**

SYNTAX OwnerString

MAX-ACCESS read-create

STATUS current

## DESCRIPTION

"The entity that configured this entry and is therefore using the resources assigned to it."

::= { dsmonMatrixCtlEntry 9 }

**dsmonMatrixCtlStatus OBJECT-TYPE**

SYNTAX RowStatus

MAX-ACCESS read-create

STATUS current

## DESCRIPTION

"The status of this dsmonMatrixCtlEntry.

An entry MUST NOT exist in the active state unless all objects in the entry have an appropriate value.

If this object is not equal to active(1), all associated entries in the dsmonMatrixSDTable and dsmonMatrixDSTable shall be deleted."

::= { dsmonMatrixCtlEntry 10 }

--

**-- AL Matrix SD Statistics Table**

--

**dsmonMatrixSDTable OBJECT-TYPE**

SYNTAX SEQUENCE OF DsmonMatrixSDEntry

MAX-ACCESS not-accessible

STATUS current

## DESCRIPTION

"A list of application traffic matrix entries which collect statistics for conversations of a particular application protocol between two network-level addresses. This table is indexed first by the source address and then by the

destination address to make it convenient to collect all statistics from a particular address.

The probe will add to this table all pairs of addresses for all protocols seen in all packets with no MAC errors, and will increment octet and packet counts in the table for all packets with no MAC errors."

::= { dsmonMatrixObjects 2 }

dsmonMatrixSDEntry OBJECT-TYPE  
 SYNTAX DsmonMatrixSDEntry  
 MAX-ACCESS not-accessible  
 STATUS current  
 DESCRIPTION

"A conceptual row in the dsmonMatrixSDTable.

The dsmonMatrixCtlIndex value in the index identifies the dsmonMatrixCtlEntry on whose behalf this entry was created.

The dsmonAggGroupIndex value in the index is determined by examining the DSCP value in each monitored packet, and the dsmonAggProfileTable entry configured for that value."

INDEX { dsmonMatrixCtlIndex,  
 dsmonMatrixTimeMark,  
 dsmonAggGroupIndex,  
 dsmonMatrixNLIndex,  
 dsmonMatrixSourceAddress,  
 dsmonMatrixDestAddress,  
 dsmonMatrixALIndex  
 }

::= { dsmonMatrixSDTable 1 }

DsmonMatrixSDEntry ::= SEQUENCE {  
 dsmonMatrixTimeMark TimeFilter,  
 dsmonMatrixNLIndex Integer32,  
 dsmonMatrixSourceAddress OCTET STRING,  
 dsmonMatrixDestAddress OCTET STRING,  
 dsmonMatrixALIndex Integer32,  
 dsmonMatrixSDPkts ZeroBasedCounter32,  
 dsmonMatrixSD0vflPkts ZeroBasedCounter32,  
 dsmonMatrixSDHCPkts ZeroBasedCounter64,  
 dsmonMatrixSDOctets ZeroBasedCounter32,  
 dsmonMatrixSD0vflOctets ZeroBasedCounter32,  
 dsmonMatrixSDHCOctets ZeroBasedCounter64,  
 dsmonMatrixSDCreateTime LastCreateTime  
 }

dsmonMatrixTimeMark OBJECT-TYPE

SYNTAX TimeFilter  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION  
"The Time Filter index for this table. This object may be used by a management station to retrieve only rows which have been created or modified since a particular time. Note that the current value for a row are always returned and the TimeFilter is not a historical data archiving mechanism. Refer to RFC 2021 [RFC2021] for a detailed description of TimeFilter operation."

::= { dsmonMatrixSDEntry 1 }

dsmonMatrixNLIndex OBJECT-TYPE

SYNTAX Integer32 (1..2147483647)  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION

"The protocolDirLocalIndex value of a protocolDirEntry representing the specific network layer protocol encapsulation associated with each entry, and the network protocol type of the dsmonMatrixSourceAddress and dsmonMatrixDestAddress objects."

::= { dsmonMatrixSDEntry 2 }

dsmonMatrixSourceAddress OBJECT-TYPE

SYNTAX OCTET STRING (SIZE (0..54))  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION

"The network source address for this dsmonMatrix entry.

This is represented as an octet string with specific semantics and length as identified by the dsmonMatrixNLIndex component of the index.

For example, if the dsmonMatrixNLIndex indicates an encapsulation of IPv4, this object is encoded as a length octet of 4, followed by the 4 octets of the IPv4 address, in network byte order."

::= { dsmonMatrixSDEntry 3 }

dsmonMatrixDestAddress OBJECT-TYPE

SYNTAX OCTET STRING (SIZE (0..54))  
MAX-ACCESS not-accessible  
STATUS current  
DESCRIPTION

"The network destination address for this dsmonMatrix entry.

This is represented as an octet string with specific semantics and length as identified by the dsmonMatrixNLIndex component of the index.

For example, if the dsmonMatrixNLIndex indicates an encapsulation of IPv4, this object is encoded as a length octet of 4, followed by the 4 octets of the IPv4 address, in network byte order."

::= { dsmonMatrixSDEntry 4 }

dsmonMatrixALIndex OBJECT-TYPE

SYNTAX Integer32 (1..2147483647)

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The protocolDirLocalIndex value of the protocolDirEntry representing the specific application layer protocol associated with each entry.

It MUST identify an protocolDirEntry which is a direct or indirect descendant of the protocolDirEntry identified by the associated dsmonMatrixNLIndex object."

::= { dsmonMatrixSDEntry 5 }

dsmonMatrixSDPkts OBJECT-TYPE

SYNTAX ZeroBasedCounter32

UNITS "packets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of packets of this protocol type (indicated by the associated dsmonMatrixALIndex object) without errors transmitted from the source address to the destination address since this entry was added to the dsmonMatrixSDTable. Note that this is the number of link-layer packets, so if a single network-layer packet is fragmented into several link-layer frames, this counter is incremented several times."

::= { dsmonMatrixSDEntry 6 }

dsmonMatrixSDovflPkts OBJECT-TYPE

SYNTAX ZeroBasedCounter32

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of times the associated dsmonMatrixSDPkts counter has overflowed, since this entry was added to the dsmonMatrixSDTable."



```
::= { dsmonMatrixSDEntry 7 }
```

```
dsmonMatrixSDHCPkts OBJECT-TYPE
    SYNTAX      ZeroBasedCounter64
    UNITS       "packets"
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
```

"The 64-bit version of the dsmonMatrixSDPkts object.

Note that this object will only be instantiated if the RMON agent supports High Capacity monitoring for a particular dataSource."

```
::= { dsmonMatrixSDEntry 8 }
```

```
dsmonMatrixSDOctets OBJECT-TYPE
    SYNTAX      ZeroBasedCounter32
    UNITS       "octets"
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
```

"The number of octets in packets of this protocol type transmitted from the source address to the destination address since this entry was added to the dsmonMatrixSDTable (excluding framing bits but including FCS octets), excluding those octets in packets that contained errors.

Note this doesn't count just those octets in the particular protocol frames, but includes the entire packet that contained the protocol."

```
::= { dsmonMatrixSDEntry 9 }
```

```
dsmonMatrixSDovfOctets OBJECT-TYPE
    SYNTAX      ZeroBasedCounter32
    MAX-ACCESS   read-only
    STATUS      deprecated
    DESCRIPTION
```

"The number of times the associated dsmonMatrixSDOctets counter has overflowed, since this entry was added to the dsmonMatrixSDTable."

```
::= { dsmonMatrixSDEntry 10 }
```

```
dsmonMatrixSDHCOctets OBJECT-TYPE
    SYNTAX      ZeroBasedCounter64
    UNITS       "octets"
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
```

"The 64-bit version of the dsmonMatrixSDPkts object.

Note that this object will only be instantiated if the RMON agent supports High Capacity monitoring for a particular dataSource."

::= { dsmonMatrixSDEntry 11 }

dsmonMatrixSDCreateTime OBJECT-TYPE

SYNTAX LastCreateTime

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The value of sysUpTime when this entry was last activated. This can be used by the management station to ensure that the entry has not been deleted and recreated between polls."

::= { dsmonMatrixSDEntry 12 }

--

-- AL Matrix DS Statistics Table

--

dsmonMatrixDSTable OBJECT-TYPE

SYNTAX SEQUENCE OF DsmonMatrixDSEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"A list of application traffic matrix entries which collect statistics for conversations of a particular application protocol between two network-level addresses. This table is indexed first by the destination address and then by the source address to make it convenient to collect all statistics from a particular address.

The probe will add to this table all pairs of addresses for all protocols seen in all packets with no MAC errors, and will increment octet and packet counts in the table for all packets with no MAC errors."

::= { dsmonMatrixObjects 3 }

dsmonMatrixDSEntry OBJECT-TYPE

SYNTAX DsmonMatrixDSEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"A conceptual row in the dsmonMatrixDSTable. Note that this table is conceptually a re-ordered version of the dsmonMatrixSDTable. Therefore, all of the index values from

that table are used by reference, and their semantics are exactly as described in the dsmonMatrixSDTable.

The dsmonMatrixCtlIndex value in the index identifies the dsmonMatrixCtlEntry on whose behalf this entry was created.

The dsmonMatrixTimeMark value in the index identifies the Time Filter index for this table.

The dsmonAggGroupIndex value in the index is determined by examining the DSCP value in each monitored packet, and the dsmonAggProfileTable entry configured for that value.

The dsmonMatrixNLIndex value in the index identifies the protocolDirLocalIndex value of a protocolDirEntry representing the specific network layer protocol encapsulation associated with each entry, and the network protocol type of the dsmonMatrixSourceAddress and dsmonMatrixDestAddress objects.

The dsmonMatrixDestAddress value in the index identifies the network destination address for this dsmonMatrix entry.

The dsmonMatrixSourceAddress value in the index identifies the network source address for this dsmonMatrix entry.

The dsmonMatrixALIndex value in the index identifies the protocolDirLocalIndex value of the protocolDirEntry representing the specific application layer protocol associated with each entry."

```
INDEX { dsmonMatrixCtlIndex,
        dsmonMatrixTimeMark,
        dsmonAggGroupIndex,
        dsmonMatrixNLIndex,
        dsmonMatrixDestAddress,
        dsmonMatrixSourceAddress,
        dsmonMatrixALIndex
      }
 ::= { dsmonMatrixDSTable 1 }
```

```
DsmonMatrixDSEntry ::= SEQUENCE {
    dsmonMatrixDSPkts           ZeroBasedCounter32,
    dsmonMatrixDSOvflPkts      ZeroBasedCounter32,
    dsmonMatrixDSHCPkts        ZeroBasedCounter64,
    dsmonMatrixDSOctets         ZeroBasedCounter32,
    dsmonMatrixDSOvflOctets     ZeroBasedCounter32,
    dsmonMatrixDSHCOctets       ZeroBasedCounter64,
    dsmonMatrixDSCreateTime     LastCreateTime
}
```

```
}

dsmonMatrixDSPkts OBJECT-TYPE
    SYNTAX      ZeroBasedCounter32
    UNITS        "packets"
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "The number of packets of this protocol type (indicated by
        the associated dsmonMatrixALIndex object) without errors
        transmitted from the source address to the destination
        address since this entry was added to the
        dsmonMatrixDSTable. Note that this is the number of link-
        layer packets, so if a single network-layer packet is
        fragmented into several link-layer frames, this counter is
        incremented several times."
    ::= { dsmonMatrixDSEntry 1 }

dsmonMatrixDSOvflPkts OBJECT-TYPE
    SYNTAX      ZeroBasedCounter32
    MAX-ACCESS   read-only
    STATUS       deprecated
    DESCRIPTION
        "The number of times the associated dsmonMatrixDSPkts
        counter has overflowed, since this entry was added to the
        dsmonMatrixDSTable."
    ::= { dsmonMatrixDSEntry 2 }

dsmonMatrixDSHCPkts OBJECT-TYPE
    SYNTAX      ZeroBasedCounter64
    UNITS        "packets"
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "The 64-bit version of the dsmonMatrixDSPkts object.

        Note that this object will only be instantiated if the RMON
        agent supports High Capacity monitoring for a particular
        dataSource."
    ::= { dsmonMatrixDSEntry 3 }

dsmonMatrixDSOctets OBJECT-TYPE
    SYNTAX      ZeroBasedCounter32
    UNITS        "octets"
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "The number of octets in packets of this protocol type
```

transmitted from the source address to the destination address since this entry was added to the dsmonMatrixDSTable (excluding framing bits but including FCS octets), excluding those octets in packets that contained errors.

Note this doesn't count just those octets in the particular protocol frames, but includes the entire packet that contained the protocol."

::= { dsmonMatrixDSEntry 4 }

dsmonMatrixDSOvflOctets OBJECT-TYPE

SYNTAX ZeroBasedCounter32

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of times the associated dsmonMatrixDSOctets counter has overflowed, since this entry was added to the dsmonMatrixDSTable."

::= { dsmonMatrixDSEntry 5 }

dsmonMatrixDSHCOctets OBJECT-TYPE

SYNTAX ZeroBasedCounter64

UNITS "octets"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The 64-bit version of the dsmonMatrixDSPkts object.

Note that this object will only be instantiated if the RMON agent supports High Capacity monitoring for a particular dataSource."

::= { dsmonMatrixDSEntry 6 }

dsmonMatrixDSCreateTime OBJECT-TYPE

SYNTAX LastCreateTime

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The value of sysUpTime when this entry was last activated. This can be used by the management station to ensure that the entry has not been deleted and recreated between polls."

::= { dsmonMatrixDSEntry 7 }

--

-- Per-Protocol Per-Matrix Statistics TopN Control Table

--

**dsmonMatrixTopNCtlTable OBJECT-TYPE**

SYNTAX SEQUENCE OF DsmonMatrixTopNCtlEntry  
 MAX-ACCESS not-accessible  
 STATUS current  
 DESCRIPTION

"A set of parameters that control the creation of a report of the top N dsmonMatrix entries according to a selected metric.

Note that an agent MAY choose to limit the actual number of entries which may be created in this table. In this case, the agent SHOULD return an error-status of 'resourceUnavailable(13)', as per section 4.2.5 of the 'Protocol Operations for SNMPv2' specification [RFC1905]."

::= { dsmonMatrixObjects 4 }

**dsmonMatrixTopNCtlEntry OBJECT-TYPE**

SYNTAX DsmonMatrixTopNCtlEntry  
 MAX-ACCESS not-accessible  
 STATUS current  
 DESCRIPTION

"A conceptual row in the dsmonMatrixTopNCtlTable.

Entries are created and deleted from this table by management action only, using the dsmonMatrixTopNCtlStatus RowStatus object.

The agent SHOULD support non-volatile configuration of this table, and upon system initialization, the table SHOULD be initialized with the saved values.

Activation of a control row in this table will cause an associated dsmonMatrixTopNTable to be created and maintained by the agent."

INDEX { dsmonMatrixTopNCtlIndex }  
 ::= { dsmonMatrixTopNCtlTable 1 }

**DsmonMatrixTopNCtlEntry ::= SEQUENCE {**

dsmonMatrixTopNCtlIndex	Integer32,
dsmonMatrixTopNCtlMatrixIndex	Integer32,
dsmonMatrixTopNCtlRateBase	INTEGER,
dsmonMatrixTopNCtlTimeRemaining	Integer32,
dsmonMatrixTopNCtlGeneratedRpts	Counter32,
dsmonMatrixTopNCtlDuration	Integer32,
dsmonMatrixTopNCtlRequestedSize	Integer32,
dsmonMatrixTopNCtlGrantedSize	Integer32,
dsmonMatrixTopNCtlStartTime	TimeStamp,
dsmonMatrixTopNCtlOwner	OwnerString,

```

    dsmonMatrixTopNCtlStatus          RowStatus
}

dsmonMatrixTopNCtlIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..65535)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An index that uniquely identifies an entry in the
        dsmonMatrixTopNCtlTable.  Each such entry defines one Top N
        report prepared for one RMON dataSource."
    ::= { dsmonMatrixTopNCtlEntry 1 }

dsmonMatrixTopNCtlMatrixIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..65535)
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The dsmonMatrixSDTable for which a top N report will be
        prepared on behalf of this entry.  The dsmonMatrixSDTable is
        identified by the same value of the dsmonMatrixCtlIndex
        object.

        This object MUST NOT be modified if the associated
        dsmonMatrixTopNCtlStatus object is equal to active(1)."
```

```

    ::= { dsmonMatrixTopNCtlEntry 2 }

dsmonMatrixTopNCtlRateBase OBJECT-TYPE
    SYNTAX      INTEGER {
        dsmonMatrixTopNPkts(1),
        dsmonMatrixTopNOctets(2),
        dsmonMatrixTopNHCPkts(3),
        dsmonMatrixTopNHCOctets(4)
    }
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The variable for each dsmonMatrixSD entry that the
        dsmonMatrixTopNRate and dsmonMatrixTopNHCRate variables are
        based upon.  Each dsmonMatrixTopN report generated on behalf
        of this control entry will be ranked in descending order,
        based on the associated dsmonMatrixSDTable counter,
        identified by this object.

        The following table identifies the dsmonMatrixSDTable
        counters associated with each enumeration:
```

Enumeration	RateBase MIB Objects
-------------	----------------------

-----	-----
dsmonMatrixTopNPkts	dsmonMatrixSDPkts
dsmonMatrixTopNOctets	dsmonMatrixSDOctets
dsmonMatrixTopNHCPkts	dsmonMatrixSDHCPkts
dsmonMatrixTopNHCOctets	dsmonMatrixSDHCOctets

The following enumerations are only available if the agent supports High Capacity monitoring:

dsmonMatrixTopNHCPkts  
dsmonMatrixTopNHCOctets

This object MUST NOT be modified if the associated dsmonMatrixTopNCtlStatus object is equal to active(1)."  
 ::= { dsmonMatrixTopNCtlEntry 3 }

dsmonMatrixTopNCtlTimeRemaining OBJECT-TYPE

SYNTAX Integer32 (0..2147483647)

UNITS "seconds"

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The number of seconds left in the report currently being collected. When this object is modified by the management station, a new collection is started, possibly aborting a currently running report. The new value is used as the requested duration of this report, and is immediately loaded into the associated dsmonMatrixTopNCtlDuration object.

When the report finishes, the probe will automatically start another collection with the same initial value of dsmonMatrixTopNCtlTimeRemaining. Thus the management station may simply read the resulting reports repeatedly, checking the startTime and duration each time to ensure that a report was not missed or that the report parameters were not changed.

While the value of this object is non-zero, it decrements by one per second until it reaches zero. At the time that this object decrements to zero, the report is made accessible in the dsmonMatrixTopNTable, overwriting any report that may be there.

When this object is modified by the management station, any associated entries in the dsmonMatrixTopNTable shall be deleted."

DEFVAL { 1800 }

::= { dsmonMatrixTopNCtlEntry 4 }



**dsmonMatrixTopNCtlGeneratedRpts OBJECT-TYPE**

SYNTAX Counter32

UNITS "reports"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of reports that have been generated by this entry."

::= { dsmonMatrixTopNCtlEntry 5 }

**dsmonMatrixTopNCtlDuration OBJECT-TYPE**

SYNTAX Integer32 (0..2147483647)

UNITS "seconds"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of seconds that this report has collected during the last sampling interval."

When the associated dsmonMatrixTopNCtlTimeRemaining object is set, this object shall be set by the probe to the same value and shall not be modified until the next time the dsmonMatrixTopNCtlTimeRemaining is set.

This value shall be zero if no reports have been requested for this dsmonMatrixTopNCtlEntry."

::= { dsmonMatrixTopNCtlEntry 6 }

**dsmonMatrixTopNCtlRequestedSize OBJECT-TYPE**

SYNTAX Integer32 (0..2147483647)

UNITS "table entries"

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The maximum number of dsmonMatrix entries requested for this report."

When this object is created or modified, the probe SHOULD set dsmonMatrixTopNCtlGrantedSize as closely to this object as is possible for the particular probe implementation and available resources."

DEFVAL { 150 }

::= { dsmonMatrixTopNCtlEntry 7 }

**dsmonMatrixTopNCtlGrantedSize OBJECT-TYPE**

SYNTAX Integer32 (0..2147483647)

UNITS "table entries"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The maximum number of dsmonMatrix entries in this report.

When the associated dsmonMatrixTopNCtlRequestedSize object is created or modified, the probe SHOULD set this object as closely to the requested value as is possible for the particular implementation and available resources. The probe MUST NOT lower this value except as a result of a set to the associated dsmonMatrixTopNCtlRequestedSize object.

Protocol entries with the highest value of dsmonMatrixTopNRate or dsmonMatrixTopNHCRate (depending on the value of the associated dsmonMatrixTopNCtlRateBase object) shall be placed in this table in decreasing order of this rate until there is no more room or until there are no more dsmonMatrix entries."

::= { dsmonMatrixTopNCtlEntry 8 }

dsmonMatrixTopNCtlStartTime OBJECT-TYPE

SYNTAX TimeStamp

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The value of sysUpTime when this top N report was last started. In other words, this is the time that the associated dsmonMatrixTopNCtlTimeRemaining object was modified to start the requested report or the time the report was last automatically (re)started.

This object may be used by the management station to determine if a report was missed or not."

::= { dsmonMatrixTopNCtlEntry 9 }

dsmonMatrixTopNCtlOwner OBJECT-TYPE

SYNTAX OwnerString

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The entity that configured this entry and is therefore using the resources assigned to it."

::= { dsmonMatrixTopNCtlEntry 10 }

dsmonMatrixTopNCtlStatus OBJECT-TYPE

SYNTAX RowStatus

MAX-ACCESS read-create

STATUS current

## DESCRIPTION

"The status of this dsmonMatrixTopNCtlEntry.

An entry MUST NOT exist in the active state unless all objects in the entry have an appropriate value.

If this object is not equal to active(1), all associated entries in the dsmonMatrixTopNTable shall be deleted by the agent."

::= { dsmonMatrixTopNCtlEntry 11 }

--

-- dsmonMatrix TopN Table

--

## dsmonMatrixTopNTable OBJECT-TYPE

SYNTAX SEQUENCE OF DsmonMatrixTopNEntry

MAX-ACCESS not-accessible

STATUS current

## DESCRIPTION

"A set of statistics for those dsmonMatrix entries that have counted the highest number of octets or packets.

If the dsmonAggControlLocked object is equal to 'false', then all entries in this table SHALL be deleted, and the agent will not process TopN reports on behalf of any dsmonMatrixTopNCtlEntry.

When the dsmonAggControlLocked object is set to 'true', then particular reports SHOULD be restarted from the beginning, on behalf of all active rows in the dsmonMatrixTopNCtlTable.

Note that dsmonMatrix entries which did not increment at all during the report interval SHOULD NOT be included in dsmonMatrixTopN reports."

::= { dsmonMatrixObjects 5 }

## dsmonMatrixTopNEntry OBJECT-TYPE

SYNTAX DsmonMatrixTopNEntry

MAX-ACCESS not-accessible

STATUS current

## DESCRIPTION

"A conceptual row in the dsmonMatrixTopNTable.

The dsmonMatrixTopNCtlIndex value in the index identifies the dsmonMatrixTopNCtlEntry on whose behalf this entry was created.

Entries in this table are ordered from 1 to 'N', where lower numbers represent higher values of the rate base object, over the report interval."

```
INDEX { dsmonMatrixTopNCtlIndex, dsmonMatrixTopNIndex }
 ::= { dsmonMatrixTopNTable 1 }
```

```
DsmonMatrixTopNEntry ::= SEQUENCE {
    dsmonMatrixTopNIndex          Integer32,
    dsmonMatrixTopNAggGroup       DsmonCounterAggGroupIndex,
    dsmonMatrixTopNNLIndex        Integer32,
    dsmonMatrixTopNSourceAddress  OCTET STRING,
    dsmonMatrixTopNDestAddress    OCTET STRING,
    dsmonMatrixTopNALIndex        Integer32,
    dsmonMatrixTopNPktRate        Gauge32,
    dsmonMatrixTopNPktRateOvfl    Gauge32,
    dsmonMatrixTopNHCPktRate      CounterBasedGauge64,
    dsmonMatrixTopNRevPktRate     Gauge32,
    dsmonMatrixTopNRevPktRateOvfl Gauge32,
    dsmonMatrixTopNHCRcvPktRate   CounterBasedGauge64,
    dsmonMatrixTopNOctetRate      Gauge32,
    dsmonMatrixTopNOctetRateOvfl  Gauge32,
    dsmonMatrixTopNHCOctetRate    CounterBasedGauge64,
    dsmonMatrixTopNRevOctetRate   Gauge32,
    dsmonMatrixTopNRevOctetRateOvfl Gauge32,
    dsmonMatrixTopNHCRcvOctetRate CounterBasedGauge64
}
```

```
dsmonMatrixTopNIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An index that uniquely identifies an entry in the
        dsmonMatrixTopNTable among those in the same report. This
        index is between 1 and N, where N is the number of entries
        in this report."
    ::= { dsmonMatrixTopNEntry 1 }
```

```
dsmonMatrixTopNAggGroup OBJECT-TYPE
    SYNTAX      DsmonCounterAggGroupIndex
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The counter aggregation group index value associated with
        host identified in this entry. This object identifies the
        dsmonAggGroupEntry with the same dsmonAggControlIndex value
        as the associated dsmonMatrixCtlAggProfile object and the
        same dsmonAggGroupIndex value as this object."
```

::= { dsmonMatrixTopNEntry 2 }

dsmonMatrixTopNNLIndex OBJECT-TYPE

SYNTAX Integer32 (1..2147483647)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The protocolDirLocalIndex value which identifies the protocol associated with the dsmonMatrixTopNSourceAddress and dsmonMatrixTopNDestAddress objects in this entry.

If the protocolDirEntry associated with the protocolDirLocalIndex with the same value as this object is de-activated or deleted, then the agent MUST delete this dsmonMatrixTopN entry."

::= { dsmonMatrixTopNEntry 3 }

dsmonMatrixTopNSourceAddress OBJECT-TYPE

SYNTAX OCTET STRING

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The dsmonMatrixSDSourceAddress value for the source network host identified in this entry. The associated dsmonMatrixTopNNLIndex object identifies the network protocol type and the encoding rules for this object."

::= { dsmonMatrixTopNEntry 4 }

dsmonMatrixTopNDestAddress OBJECT-TYPE

SYNTAX OCTET STRING

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The dsmonMatrixSDDestAddress value for the destination network host identified in this entry. The associated dsmonMatrixTopNNLIndex object identifies the network protocol type and the encoding rules for this object."

::= { dsmonMatrixTopNEntry 5 }

dsmonMatrixTopNALIndex OBJECT-TYPE

SYNTAX Integer32 (1..2147483647)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The protocolDirLocalIndex value which identifies the application protocol associated with this entry.

If the protocolDirEntry associated with the

protocolDirLocalIndex with the same value as this object is de-activated or deleted, then the agent MUST delete this dsmonMatrixTopN entry."

::= { dsmonMatrixTopNEntry 6 }

**dsmonMatrixTopNPktRate OBJECT-TYPE**

SYNTAX Gauge32  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION

"The number of packets seen of this protocol from the source host to the destination host during this sampling interval, counted using the rules for counting the dsmonMatrixSDPkts object.

If the value of dsmonMatrixTopNCtlRateBase is dsmonMatrixTopNPkts, this variable will be used to sort this report.

If the value of the dsmonMatrixTopNCtlRateBase is dsmonMatrixTopNHCPkts or dsmonMatrixTopNHCOctets, then this object will contain the the least significant 32 bits of the associated dsmonMatrixTopNHCPktRate object."

::= { dsmonMatrixTopNEntry 7 }

**dsmonMatrixTopNPktRate0vfl OBJECT-TYPE**

SYNTAX Gauge32  
MAX-ACCESS read-only  
STATUS deprecated  
DESCRIPTION

"The most significant 32 bits of the associated dsmonMatrixTopNHCPktRate object.

If the associated dsmonMatrixTopNCtlRateBase is equal to dsmonMatrixTopNHCPkts or dsmonMatrixTopNHCOctets, then this object will contain the most significant 32 bits of the associated dsmonMatrixTopNHCPktRate object, otherwise this object will contain the value zero.

The agent MAY choose not to instantiate this object if High Capacity monitoring is not supported."

::= { dsmonMatrixTopNEntry 8 }

**dsmonMatrixTopNHCPktRate OBJECT-TYPE**

SYNTAX CounterBasedGauge64  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION

"The number of packets seen of this protocol from the source host to the destination host during this sampling interval, counted using the rules for counting the dsmonMatrixSDHCPkts object.

If the value of dsmonMatrixTopNctlRateBase is dsmonMatrixTopNHCPkts, this variable will be used to sort this report.

The agent MAY choose not to instantiate this object if High Capacity monitoring is not supported."

::= { dsmonMatrixTopNEntry 9 }

dsmonMatrixTopNRevPktRate OBJECT-TYPE

SYNTAX Gauge32  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION

"The number of packets seen of this protocol from the destination host to the source host during this sampling interval, counted using the rules for counting the dsmonMatrixDSPkts object (note that the corresponding dsmonMatrixSDPkts object selected is the one whose source address is equal to dsmonMatrixTopNDestAddress and whose destination address is equal to dsmonMatrixTopNSourceAddress.)"

::= { dsmonMatrixTopNEntry 10 }

dsmonMatrixTopNRevPktRateOvfl OBJECT-TYPE

SYNTAX Gauge32  
MAX-ACCESS read-only  
STATUS deprecated  
DESCRIPTION

"The most significant 32 bits of the associated dsmonMatrixTopNHCPktRate object.

If the associated dsmonMatrixTopNctlRateBase is equal to dsmonMatrixTopNHCPkts or dsmonMatrixTopNHCOctets, then this object will contain the most significant 32 bits of the associated dsmonMatrixTopNHCPktRate object, otherwise this object will contain the value zero.

The agent MAY choose not to instantiate this object if High Capacity monitoring is not supported."

::= { dsmonMatrixTopNEntry 11 }

dsmonMatrixTopNHCPktRate OBJECT-TYPE

SYNTAX CounterBasedGauge64

MAX-ACCESS read-only  
STATUS current  
DESCRIPTION

"The number of packets seen of this protocol from the destination host to the source host during this sampling interval, counted using the rules for counting the dsmonMatrixDSHCPkts object (note that the corresponding dsmonMatrixSDHCPkts object selected is the one whose source address is equal to dsmonMatrixTopNDestAddress and whose destination address is equal to dsmonMatrixTopNSourceAddress.)"

The agent MAY choose not to instantiate this object if High Capacity monitoring is not supported."

::= { dsmonMatrixTopNEntry 12 }

dsmonMatrixTopNOctetRate OBJECT-TYPE

SYNTAX Gauge32  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION

"The number of octets seen of this protocol from the source host to the destination host during this sampling interval, counted using the rules for counting the dsmonMatrixSDOctets object."

If the value of dsmonMatrixTopNCtrlRateBase is dsmonMatrixTopNOctets, this variable will be used to sort this report.

If the value of the dsmonMatrixTopNCtrlRateBase is dsmonMatrixTopNHCPkts or dsmonMatrixTopNHCOctets, then this object will contain the the least significant 32 bits of the associated dsmonMatrixTopNHCPktRate object."

::= { dsmonMatrixTopNEntry 13 }

dsmonMatrixTopNOctetRateOvfl OBJECT-TYPE

SYNTAX Gauge32  
MAX-ACCESS read-only  
STATUS deprecated  
DESCRIPTION

"The most significant 32 bits of the associated dsmonMatrixTopNHCOctetRate object."

If the associated dsmonMatrixTopNCtrlRateBase is equal to dsmonMatrixTopNHCPkts or dsmonMatrixTopNHCOctets, then this object will contain the most significant 32 bits of the associated dsmonMatrixTopNHCOctetRate object, otherwise this



object will contain the value zero.

The agent MAY choose not to instantiate this object if High Capacity monitoring is not supported."

::= { dsmonMatrixTopNEntry 14 }

dsmonMatrixTopNHCOctetRate OBJECT-TYPE

SYNTAX CounterBasedGauge64

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of octets seen of this protocol from the source host to the destination host during this sampling interval, counted using the rules for counting the dsmonMatrixSDHCOctets object.

If the value of dsmonMatrixTopNCtrlRateBase is dsmonMatrixTopNHCOctets, this variable will be used to sort this report.

The agent MAY choose not to instantiate this object if High Capacity monitoring is not supported."

::= { dsmonMatrixTopNEntry 15 }

dsmonMatrixTopNRevOctetRate OBJECT-TYPE

SYNTAX Gauge32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of octets seen of this protocol from the destination host to the source host during this sampling interval, counted using the rules for counting the dsmonMatrixDSOctets object (note that the corresponding dsmonMatrixSDOctets object selected is the one whose source address is equal to dsmonMatrixTopNDestAddress and whose destination address is equal to dsmonMatrixTopNSourceAddress.)"

::= { dsmonMatrixTopNEntry 16 }

dsmonMatrixTopNRevOctetRate0vfl OBJECT-TYPE

SYNTAX Gauge32

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The most significant 32 bits of the associated dsmonMatrixTopNHCRRevOctetRate object.

If the associated dsmonMatrixTopNCtrlRateBase is equal to

dsmonMatrixTopNHCPkts or dsmonMatrixTopNHCOCtets, then this object will contain the most significant 32 bits of the associated dsmonMatrixTopNHCRcvPktRate object, otherwise this object will contain the value zero.

The agent MAY choose not to instantiate this object if High Capacity monitoring is not supported."

::= { dsmonMatrixTopNEntry 17 }

dsmonMatrixTopNHCRcvOctetRate OBJECT-TYPE

SYNTAX CounterBasedGauge64

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of octets seen of this protocol from the destination host to the source host during this sampling interval, counted using the rules for counting the dsmonMatrixDSHCOctets object (note that the corresponding dsmonMatrixSDHCOctets object selected is the one whose source address is equal to dsmonMatrixTopNDestAddress and whose destination address is equal to dsmonMatrixTopNSourceAddress.)

The agent MAY choose not to instantiate this object if High Capacity monitoring is not supported."

::= { dsmonMatrixTopNEntry 18 }

--

-- Conformance Section

--

dsmonCompliances OBJECT IDENTIFIER ::= { dsmonConformance 1 }

dsmonGroups OBJECT IDENTIFIER ::= { dsmonConformance 2 }

--

-- Compliance for agents that do not support HC or Counter64

--

dsmonCompliance MODULE-COMPLIANCE

STATUS current

DESCRIPTION

"Describes the requirements for conformance to the Differentiated Services Monitoring MIB."

MODULE -- this module

MANDATORY-GROUPS {

dsmonCounterAggControlGroup,  
dsmonStatsGroup,  
dsmonCapsGroup

}

GROUP dsmonStatsHCGroup

DESCRIPTION

"The dsmonStatsHCGroup is mandatory for systems which implement High Capacity monitoring."

GROUP dsmonPdistGroup

DESCRIPTION

"The dsmonPdistGroup is mandatory for systems which implement RMON-2 protocolDirTable based protocol distribution monitoring."

GROUP dsmonPdistHCGroup

DESCRIPTION

"The dsmonPdistHCGroup is mandatory for systems which implement RMON-2 protocolDirTable based protocol distribution monitoring on high capacity interfaces."

GROUP dsmonHostGroup

DESCRIPTION

"The dsmonHostGroup is mandatory for systems which implement RMON-2 nlHostTable based network protocol monitoring."

GROUP dsmonHostHCGroup

DESCRIPTION

"The dsmonHostHCGroup is mandatory for systems which implement RMON-2 nlHostTable based network protocol monitoring, on high capacity interfaces."

GROUP dsmonMatrixGroup

DESCRIPTION

"The dsmonMatrixGroup is mandatory for systems which implement RMON-2 alMatrix based application protocol monitoring."

GROUP dsmonMatrixHCGroup

DESCRIPTION

"The dsmonMatrixHCGroup is mandatory for systems which implement RMON-2 alMatrix based application protocol monitoring, on high capacity interfaces."

::= { dsmonCompliances 1 }

--

-- Compliance for agents that support HC and Counter64

--

**dsmonHCCompliance MODULE-COMPLIANCE****STATUS** current**DESCRIPTION**

"Describes the requirements for conformance to the Differentiated Services Monitoring MIB for agents which also support High Capacity monitoring and the Counter64 data type."

**MODULE** -- this module**MANDATORY-GROUPS** {

dsmonCounterAggControlGroup,  
dsmonStatsGroup,  
dsmonStatsHCGroup,  
dsmonCapsGroup  
}

**GROUP** dsmonPdistGroup**DESCRIPTION**

"The dsmonPdistGroup is mandatory for systems which implement RMON-2 protocolDirTable based protocol distribution monitoring."

**GROUP** dsmonPdistHCGroup**DESCRIPTION**

"The dsmonPdistHCGroup is mandatory for systems which implement RMON-2 protocolDirTable based protocol distribution monitoring."

**GROUP** dsmonHostGroup**DESCRIPTION**

"The dsmonHostGroup is mandatory for systems which implement RMON-2 nlHostTable based network protocol monitoring."

**GROUP** dsmonHostHCGroup**DESCRIPTION**

"The dsmonHostHCGroup is mandatory for systems which implement RMON-2 nlHostTable based network protocol monitoring."

**GROUP** dsmonMatrixGroup**DESCRIPTION**

"The dsmonMatrixGroup is mandatory for systems which implement RMON-2 alMatrix based application protocol monitoring."

**GROUP** dsmonMatrixHCGroup**DESCRIPTION**

"The dsmonMatrixHCGroup is mandatory for systems which implement RMON-2 alMatrix based application protocol monitoring."

```
        monitoring."

 ::= { dsmonCompliances 2 }

--
-- Compliance for agents that support HC, but not Counter64
--

dsmonHCNoC64Compliance MODULE-COMPLIANCE
    STATUS deprecated
    DESCRIPTION
        "Describes the requirements for conformance to the
        Differentiated Services Monitoring MIB for an agent which
        supports high capacity monitoring, but does not support the
        Counter64 data type (e.g., only supports the SNMPv1
        protocol)."
```

MODULE -- this module

```
    MANDATORY-GROUPS {
        dsmonCounterAggControlGroup,
        dsmonStatsGroup,
        dsmonStatsOvflGroup,
        dsmonCapsGroup
    }

    GROUP dsmonStatsHCGroup
    DESCRIPTION
        "Implementation of the dsmonStatsHCGroup is not required.
        High Capacity monitoring."

    GROUP dsmonPdistGroup
    DESCRIPTION
        "The dsmonPdistGroup is mandatory for systems which
        implement RMON-2 protocolDirTable based protocol
        distribution monitoring."

    GROUP dsmonPdistOvflGroup
    DESCRIPTION
        "The dsmonPdistGroup is mandatory for systems which
        implement RMON-2 protocolDirTable based protocol
        distribution monitoring."

    GROUP dsmonPdistHCGroup
    DESCRIPTION
        "Implementation of the dsmonPdistHCGroup is not required."

    GROUP dsmonHostGroup
    DESCRIPTION
        "The dsmonHostGroup is mandatory for systems which implement
```

RMON-2 nlHostTable based network protocol monitoring."

GROUP dsmonHostOvflGroup

DESCRIPTION

"The dsmonHostGroup is mandatory for systems which implement RMON-2 nlHostTable based network protocol monitoring."

GROUP dsmonHostHCGroup

DESCRIPTION

"Implementation of the dsmonHostHCGroup is not required."

GROUP dsmonMatrixGroup

DESCRIPTION

"The dsmonMatrixGroup is mandatory for systems which implement RMON-2 alMatrix based application protocol monitoring."

GROUP dsmonMatrixOvflGroup

DESCRIPTION

"The dsmonMatrixGroup is mandatory for systems which implement RMON-2 alMatrix based application protocol monitoring."

GROUP dsmonMatrixHCGroup

DESCRIPTION

"Implementation of the dsmonMatrixHCGroup is not required."

::= { dsmonCompliances 3 }

## -- Object Groups

dsmonCounterAggControlGroup OBJECT-GROUP

OBJECTS {

dsmonMaxAggGroups,  
dsmonAggControlLocked,  
dsmonAggControlChanges,  
dsmonAggControlLastChangeTime,  
dsmonAggControlDescr,  
dsmonAggControlOwner,  
dsmonAggControlStatus,  
dsmonAggGroupIndex,  
dsmonAggGroupDescr,  
dsmonAggGroupStatus

}

STATUS current

DESCRIPTION

"A collection of objects used to configure and manage counter aggregation groups for DSMON collection purposes."  
 ::= { dsmonGroups 1 }

**dsmonStatsGroup OBJECT-GROUP**

OBJECTS {  
    dsmonStatsControlDataSource,  
    dsmonStatsControlAggProfile,  
    dsmonStatsControlDroppedFrames,  
    dsmonStatsControlCreateTime,  
    dsmonStatsControlOwner,  
    dsmonStatsControlStatus,  
    dsmonStatsInPkts,  
    dsmonStatsInOctets,  
    dsmonStatsOutPkts,  
    dsmonStatsOutOctets  
}

STATUS current

DESCRIPTION

"A collection of objects providing per DSCP statistics."  
 ::= { dsmonGroups 2 }

**dsmonStatsOvflGroup OBJECT-GROUP**

OBJECTS {  
    dsmonStatsInOvflPkts,  
    dsmonStatsInOvflOctets,  
    dsmonStatsOutOvflPkts,  
    dsmonStatsOutOvflOctets  
}

STATUS deprecated

DESCRIPTION

"A collection of objects providing per-DSCP overflow counters for systems with high capacity data sources, but without support for the Counter64 data type."  
 ::= { dsmonGroups 3 }

**dsmonStatsHCGroup OBJECT-GROUP**

OBJECTS {  
    dsmonStatsInHCPkts,  
    dsmonStatsInHCOctets,  
    dsmonStatsOutHCPkts,  
    dsmonStatsOutHCOctets  
}

STATUS current

DESCRIPTION

"A collection of objects providing per DSCP statistics for high capacity data sources."  
 ::= { dsmonGroups 4 }

**dsmonPdistGroup OBJECT-GROUP**

```
OBJECTS {
    dsmonPdistCtlDataSource,
    dsmonPdistCtlAggProfile,
    dsmonPdistCtlMaxDesiredEntries,
    dsmonPdistCtlDroppedFrames,
    dsmonPdistCtlInserts,
    dsmonPdistCtlDeletes,
    dsmonPdistCtlCreateTime,
    dsmonPdistCtlOwner,
    dsmonPdistCtlStatus,
    dsmonPdistStatsPkts,
    dsmonPdistStatsOctets,
    dsmonPdistStatsCreateTime,
    dsmonPdistTopNCtlPdistIndex,
    dsmonPdistTopNCtlRateBase,
    dsmonPdistTopNCtlTimeRemaining,
    dsmonPdistTopNCtlGeneratedReprts,
    dsmonPdistTopNCtlDuration,
    dsmonPdistTopNCtlRequestedSize,
    dsmonPdistTopNCtlGrantedSize,
    dsmonPdistTopNCtlStartTime,
    dsmonPdistTopNCtlOwner,
    dsmonPdistTopNCtlStatus,
    dsmonPdistTopNPDLocalIndex,
    dsmonPdistTopNAggGroup,
    dsmonPdistTopNRate
}
```

**STATUS** current

**DESCRIPTION**

"A collection of objects providing per protocol DSCP monitoring extensions to the RMON-2 MIB."

::= { dsmonGroups 5 }

**dsmonPdistOvflGroup OBJECT-GROUP**

```
OBJECTS {
    dsmonPdistStatsOvflPkts,
    dsmonPdistStatsOvflOctets,
    dsmonPdistTopNRateOvfl
}
```

**STATUS** deprecated

**DESCRIPTION**

"A collection of objects providing per-protocol DSCP overflow counters for systems with high capacity data sources, but without support for the Counter64 data type."

::= { dsmonGroups 6 }

**dsmonPdistHCGroup OBJECT-GROUP**



```
OBJECTS {
    dsmonPdlistStatsHCPkts,
    dsmonPdlistStatsHCOctets,
    dsmonPdlistTopNHCRate
}
STATUS current
DESCRIPTION
    "A collection of objects providing per protocol DSCP
    monitoring extensions to the RMON-2 MIB for High Capacity
    networks."
 ::= { dsmonGroups 7 }
```

dsmonHostGroup OBJECT-GROUP

```
OBJECTS {
    dsmonHostCtlDataSource,
    dsmonHostCtlAggProfile,
    dsmonHostCtlMaxDesiredEntries,
    dsmonHostCtlIPv4PrefixLen,
    dsmonHostCtlIPv6PrefixLen,
    dsmonHostCtlDroppedFrames,
    dsmonHostCtlInserts,
    dsmonHostCtlDeletes,
    dsmonHostCtlCreateTime,
    dsmonHostCtlOwner,
    dsmonHostCtlStatus,
    dsmonHostInPkts,
    dsmonHostInOctets,
    dsmonHostOutPkts,
    dsmonHostOutOctets,
    dsmonHostCreateTime,
    dsmonHostTopNCtlHostIndex,
    dsmonHostTopNCtlRateBase,
    dsmonHostTopNCtlTimeRemaining,
    dsmonHostTopNCtlGeneratedReports,
    dsmonHostTopNCtlDuration,
    dsmonHostTopNCtlRequestedSize,
    dsmonHostTopNCtlGrantedSize,
    dsmonHostTopNCtlStartTime,
    dsmonHostTopNCtlOwner,
    dsmonHostTopNCtlStatus,
    dsmonHostTopNPDLocalIndex,
    dsmonHostTopNAddress,
    dsmonHostTopNAggGroup,
    dsmonHostTopNRate
}
STATUS current
DESCRIPTION
    "A collection of objects providing per Host monitoring
```

```
        functions."
 ::= { dsmonGroups 8 }

dsmonHost0vflGroup OBJECT-GROUP
  OBJECTS {
    dsmonHostIn0vflPkts,
    dsmonHostIn0vflOctets,
    dsmonHostOut0vflPkts,
    dsmonHostOut0vflOctets,
    dsmonHostTopNRate0vfl
  }
  STATUS deprecated
  DESCRIPTION
    "A collection of objects providing per host DSCP overflow
    counters for systems with high capacity data sources, but
    without support for the Counter64 data type."
 ::= { dsmonGroups 9 }

dsmonHostHCGroup OBJECT-GROUP
  OBJECTS {
    dsmonHostInHCPkts,
    dsmonHostInHCOctets,
    dsmonHostOutHCPkts,
    dsmonHostOutHCOctets,
    dsmonHostTopNHCRate
  }
  STATUS current
  DESCRIPTION
    "A collection of objects providing per Host monitoring
    functions for High Capacity networks."
 ::= { dsmonGroups 10 }

dsmonCapsGroup OBJECT-GROUP
  OBJECTS {
    dsmonCapabilities
  }
  STATUS current
  DESCRIPTION
    "A collection of objects providing an indication of the
    DSMON monitoring functions supported by the agent."
 ::= { dsmonGroups 11 }

dsmonMatrixGroup OBJECT-GROUP
  OBJECTS {
    dsmonMatrixCtlDataSource,
    dsmonMatrixCtlAggProfile,
    dsmonMatrixCtlMaxDesiredEntries,
    dsmonMatrixCtlDroppedFrames,
```

```

dsmonMatrixCtlInserts,
dsmonMatrixCtlDeletes,
dsmonMatrixCtlCreateTime,
dsmonMatrixCtlOwner,
dsmonMatrixCtlStatus,
dsmonMatrixSDPkts,
dsmonMatrixSDOctets,
dsmonMatrixSDCreateTime,
dsmonMatrixDSPkts,
dsmonMatrixDSOctets,
dsmonMatrixDSCreateTime,
dsmonMatrixTopNCtlMatrixIndex,
dsmonMatrixTopNCtlRateBase,
dsmonMatrixTopNCtlTimeRemaining,
dsmonMatrixTopNCtlGeneratedRpts,
dsmonMatrixTopNCtlDuration,
dsmonMatrixTopNCtlRequestedSize,
dsmonMatrixTopNCtlGrantedSize,
dsmonMatrixTopNCtlStartTime,
dsmonMatrixTopNCtlOwner,
dsmonMatrixTopNCtlStatus,
dsmonMatrixTopNAggGroup,
dsmonMatrixTopNNLIndex,
dsmonMatrixTopNSourceAddress,
dsmonMatrixTopNDestAddress,
dsmonMatrixTopNALIndex,
dsmonMatrixTopNPktRate,
dsmonMatrixTopNRevPktRate,
dsmonMatrixTopNOctetRate,
dsmonMatrixTopNRevOctetRate

```

```

}

```

```

STATUS current

```

```

DESCRIPTION

```

```

    "A collection of objects providing per conversation
    monitoring functions."

```

```

 ::= { dsmonGroups 12 }

```

```

dsmonMatrixOvflGroup OBJECT-GROUP

```

```

    OBJECTS {

```

```

        dsmonMatrixSDOvflPkts,
        dsmonMatrixSDOvflOctets,
        dsmonMatrixDSOvflPkts,
        dsmonMatrixDSOvflOctets,
        dsmonMatrixTopNPktRateOvfl,
        dsmonMatrixTopNRevPktRateOvfl,
        dsmonMatrixTopNOctetRateOvfl,
        dsmonMatrixTopNRevOctetRateOvfl

```

```

    }

```

STATUS deprecated

DESCRIPTION

"A collection of objects providing per conversation monitoring functions for systems with high capacity data sources, but without support for the Counter64 data type."

::= { dsmonGroups 13 }

dsmonMatrixHCGroup OBJECT-GROUP

OBJECTS {

dsmonMatrixSDHCPkts,  
dsmonMatrixSDHCOctets,  
dsmonMatrixDSHCPkts,  
dsmonMatrixDSHCOctets,  
dsmonMatrixTopNHCPktRate,  
dsmonMatrixTopNHCRcvPktRate,  
dsmonMatrixTopNHCOctetRate,  
dsmonMatrixTopNHCRcvOctetRate

}

STATUS current

DESCRIPTION

"A collection of objects providing per conversation monitoring functions for High Capacity networks."

::= { dsmonGroups 14 }

END

## 5. Counter Aggregation Configuration Usage Examples

This section contains an example of the steps that may be followed by a management station to configure the objects in the dsmonCounterAggControlGroup.

A note about these examples:

- they do not define a standard
- an agent is not obligated to support them
- a management application is not constrained by them
- the SET(object = value [, ...]) notation is only conceptual, and is not meant to represent an actual SNMP Set PDU.

### 5.1. Step 1: Unlock the Counter Aggregation Configuration

Before any write operations to the tabular objects in this group can be made, the counter aggregation configuration must be unlocked by setting the `dsmonAggControlLocked` scalar to false:

```
SET(dsmonAggControlLocked.0 = false(2));
```

### 5.2. Step 2: Check the Maximum number of Counter Aggregation Groups

Make sure the desired counter aggregation groups have a chance of being configured on the agent.

```
maxGroups = GET(dsmonAggMaxAggGroups.0);
```

For this example, `maxGroups` is greater or equal to 64.

### 5.3. Step 3: Check if the counter aggregation profiles already exist

Make sure the desired counter aggregation profiles have not already been configured, or perhaps recreated after an agent restart. The following example is oversimplified, in that the entire counter aggregation configuration should actually be verified.

```
profile1Descr = GET(dsmonAggControlDescr.1);  
profile1Owner = GET(dsmonAggControlOwner.1);  
profile1Status = GET(dsmonAggControlStatus.1);
```

For this example, none of the counter aggregation profiles already exist.

### 5.4. Step 4: Create the Counter Aggregation Control Entries

The management station should create one entry in the `dsmonAggControlTable` for each counter aggregation profile to be configured on the agent.

Steps 4, 5, and 6 are repeated for each counter aggregation profile to be configured on the agent. There are 3 example counter aggregation profiles shown in each of these steps.

Example 1: Each DSCP in its own counter aggregation group.

```
SET(dsmonAggControlStatus.1 = createAndGo(4),  
    dsmonAggControlOwner.1 = "Example App 1",  
    dsmonAggControlDescr.1 = "1 DSCP Per Group");
```

Example 2: a collection of DIFFSERV PHBs.

```
SET(dsmonAggControlStatus.2 = createAndGo(4),  
    dsmonAggControlOwner.2 = "Example App 2",  
    dsmonAggControlDescr.2 = "June 2000 DIFFSERV PHBs");
```

Example 3: an aggregated collection of DIFFSERV PHBs.

```
SET(dsmonAggControlStatus.3 = createAndGo(4),  
    dsmonAggControlOwner.3 = "Example App 3",  
    dsmonAggControlDescr.3 = "Limited June 2000 PHBs");
```

#### 5.5. Step 5: Create the Counter Aggregation Group Descriptions

Example 1: Each DSCP in its own counter aggregation group. One group is created for each codepoint, for a total of 64 rows.

```
SET(dsmonAggGroupStatus.1.0 = createAndGo(4),  
    dsmonAggGroupDescr.1.0 = "DSCP 0");  
SET(dsmonAggGroupStatus.1.1 = createAndGo(4),  
    dsmonAggGroupDescr.1.1 = "DSCP 1");  
SET(dsmonAggGroupStatus.1.2 = createAndGo(4),  
    dsmonAggGroupDescr.1.2 = "DSCP 2");  
SET(dsmonAggGroupStatus.1.3 = createAndGo(4),  
    dsmonAggGroupDescr.1.3 = "DSCP 3");  
  
...  
  
SET(dsmonAggGroupStatus.1.63 = createAndGo(4),  
    dsmonAggGroupDescr.1.63 = "DSCP 63");
```

Example 2: a collection of current DIFFSERV PHBs. One group is created for each PHB to be monitored.

```
SET(dsmonAggGroupStatus.2.0 = createAndGo(4),
    dsmonAggGroupDescr.2.0 = "CS0");
SET(dsmonAggGroupStatus.2.1 = createAndGo(4),
    dsmonAggGroupDescr.2.1 = "CS1");
SET(dsmonAggGroupStatus.2.2 = createAndGo(4),
    dsmonAggGroupDescr.2.2 = "CS2");
SET(dsmonAggGroupStatus.2.3 = createAndGo(4),
    dsmonAggGroupDescr.2.3 = "CS3");
SET(dsmonAggGroupStatus.2.4 = createAndGo(4),
    dsmonAggGroupDescr.2.4 = "CS4");
SET(dsmonAggGroupStatus.2.5 = createAndGo(4),
    dsmonAggGroupDescr.2.5 = "CS5");
SET(dsmonAggGroupStatus.2.6 = createAndGo(4),
    dsmonAggGroupDescr.2.6 = "CS6");
SET(dsmonAggGroupStatus.2.7 = createAndGo(4),
    dsmonAggGroupDescr.2.7 = "CS7");
SET(dsmonAggGroupStatus.2.8 = createAndGo(4),
    dsmonAggGroupDescr.2.8 = "EF");
SET(dsmonAggGroupStatus.2.9 = createAndGo(4),
    dsmonAggGroupDescr.2.9 = "AF11");
SET(dsmonAggGroupStatus.2.10 = createAndGo(4),
    dsmonAggGroupDescr.2.10 = "AF12");
SET(dsmonAggGroupStatus.2.11 = createAndGo(4),
    dsmonAggGroupDescr.2.11 = "AF13");
SET(dsmonAggGroupStatus.2.12 = createAndGo(4),
    dsmonAggGroupDescr.2.12 = "AF21");
SET(dsmonAggGroupStatus.2.13 = createAndGo(4),
    dsmonAggGroupDescr.2.13 = "AF22");
SET(dsmonAggGroupStatus.2.14 = createAndGo(4),
    dsmonAggGroupDescr.2.14 = "AF23");
SET(dsmonAggGroupStatus.2.15 = createAndGo(4),
    dsmonAggGroupDescr.2.15 = "AF31");
SET(dsmonAggGroupStatus.2.16 = createAndGo(4),
    dsmonAggGroupDescr.2.16 = "AF32");
SET(dsmonAggGroupStatus.2.17 = createAndGo(4),
    dsmonAggGroupDescr.2.17 = "AF33");
SET(dsmonAggGroupStatus.2.18 = createAndGo(4),
    dsmonAggGroupDescr.2.18 = "AF41");
SET(dsmonAggGroupStatus.2.19 = createAndGo(4),
    dsmonAggGroupDescr.2.19 = "AF42");
SET(dsmonAggGroupStatus.2.20 = createAndGo(4),
    dsmonAggGroupDescr.2.20 = "AF43");
SET(dsmonAggGroupStatus.2.21 = createAndGo(4),
    dsmonAggGroupDescr.2.21 = "Nonzero Default");
```

**Example 3:** an aggregated representation of current DIFFSERV PHBs. One group is created for each counter aggregation to be monitored (8 rows in this example).

```
SET(dsmonAggGroupStatus.3.0 = createAndGo(4),
    dsmonAggGroupDescr.3.0 = "Zero CS");
SET(dsmonAggGroupStatus.3.1 = createAndGo(4),
    dsmonAggGroupDescr.3.1 = "Nonzero CS");
SET(dsmonAggGroupStatus.3.2 = createAndGo(4),
    dsmonAggGroupDescr.3.2 = "EF");
SET(dsmonAggGroupStatus.3.3 = createAndGo(4),
    dsmonAggGroupDescr.3.3 = "AF1");
SET(dsmonAggGroupStatus.3.4 = createAndGo(4),
    dsmonAggGroupDescr.3.4 = "AF2");
SET(dsmonAggGroupStatus.3.5 = createAndGo(4),
    dsmonAggGroupDescr.3.5 = "AF3");
SET(dsmonAggGroupStatus.3.6 = createAndGo(4),
    dsmonAggGroupDescr.3.6 = "AF4");
SET(dsmonAggGroupStatus.3.7 = createAndGo(4),
    dsmonAggGroupDescr.3.7 = "Nonzero Default");
```

#### 5.6. Step 6: Create the Counter Aggregation Profile Mappings

After the dsmonAggControlEntries are activated, the associated read-write dsmonAggProfileEntries will be created. The management station must create 64 entries in the dsmonAggProfileTable for each counter aggregation profile configured in the dsmonAggControlTable.

**Example 1:** Each DSCP in its own counter aggregation group

```
SET(dsmonAggGroupIndex.1.0 = 0,
    dsmonAggGroupIndex.1.1 = 1,
    dsmonAggGroupIndex.1.2 = 2,
    dsmonAggGroupIndex.1.3 = 3,
    ...
    dsmonAggGroupIndex.1.63 = 63);
```

**Example 2:** a collection of current DIFFSERV PHBs.

```
SET(dsmonAggGroupIndex.2.0 = 0,           -- CS0
    dsmonAggGroupIndex.2.1 = 21,         -- Nonzero Default
    dsmonAggGroupIndex.2.2 = 21,
    dsmonAggGroupIndex.2.3 = 21,
    dsmonAggGroupIndex.2.4 = 21,
    dsmonAggGroupIndex.2.5 = 21,
    dsmonAggGroupIndex.2.6 = 21,
    dsmonAggGroupIndex.2.7 = 21,
    dsmonAggGroupIndex.2.8 = 1,         -- CS1
```



```
dsmonAggGroupIndex.2.9 = 21,
dsmonAggGroupIndex.2.10 = 9,           -- AF11
dsmonAggGroupIndex.2.11 = 21,
dsmonAggGroupIndex.2.12 = 10,          -- AF12
dsmonAggGroupIndex.2.13 = 21,
dsmonAggGroupIndex.2.14 = 11,          -- AF13
dsmonAggGroupIndex.2.15 = 21,
dsmonAggGroupIndex.2.16 = 2,           -- CS2
dsmonAggGroupIndex.2.17 = 21,
dsmonAggGroupIndex.2.18 = 12,          -- AF21
dsmonAggGroupIndex.2.19 = 21,
dsmonAggGroupIndex.2.20 = 13,          -- AF22
dsmonAggGroupIndex.2.21 = 21,
dsmonAggGroupIndex.2.22 = 14,          -- AF23
dsmonAggGroupIndex.2.23 = 21,
dsmonAggGroupIndex.2.24 = 3,           -- CS3
dsmonAggGroupIndex.2.25 = 21,
dsmonAggGroupIndex.2.26 = 15,          -- AF31
dsmonAggGroupIndex.2.27 = 21,
dsmonAggGroupIndex.2.28 = 16,          -- AF32
dsmonAggGroupIndex.2.29 = 8,           -- EF
dsmonAggGroupIndex.2.30 = 17,          -- AF33
dsmonAggGroupIndex.2.31 = 21,
dsmonAggGroupIndex.2.32 = 4,           -- CS4
dsmonAggGroupIndex.2.33 = 21,
dsmonAggGroupIndex.2.34 = 18,          -- AF41
dsmonAggGroupIndex.2.35 = 21,
dsmonAggGroupIndex.2.36 = 19,          -- AF42
dsmonAggGroupIndex.2.37 = 21,
dsmonAggGroupIndex.2.38 = 20,          -- AF43
dsmonAggGroupIndex.2.39 = 21,
dsmonAggGroupIndex.2.40 = 5,           -- CS5
dsmonAggGroupIndex.2.41 = 21,
dsmonAggGroupIndex.2.42 = 21,
dsmonAggGroupIndex.2.43 = 21,
dsmonAggGroupIndex.2.44 = 21,
dsmonAggGroupIndex.2.45 = 21,
dsmonAggGroupIndex.2.46 = 21,
dsmonAggGroupIndex.2.47 = 21,
dsmonAggGroupIndex.2.48 = 6,           -- CS6
dsmonAggGroupIndex.2.49 = 21,
dsmonAggGroupIndex.2.50 = 21,
dsmonAggGroupIndex.2.51 = 21,
dsmonAggGroupIndex.2.52 = 21,
dsmonAggGroupIndex.2.53 = 21,
dsmonAggGroupIndex.2.54 = 21,
dsmonAggGroupIndex.2.55 = 21,
dsmonAggGroupIndex.2.56 = 7,           -- CS7
```

```
dsmonAggGroupIndex.2.57 = 21,  
dsmonAggGroupIndex.2.58 = 21,  
dsmonAggGroupIndex.2.59 = 21,  
dsmonAggGroupIndex.2.60 = 21,  
dsmonAggGroupIndex.2.61 = 21,  
dsmonAggGroupIndex.2.62 = 21,  
dsmonAggGroupIndex.2.63 = 21);
```

Example 3: an aggregated collection of current DIFFSERV PHBs.

```
SET(dsmonAggGroupIndex.3.0 = 0,           -- Zero CS  
    dsmonAggGroupIndex.3.1 = 7,           -- Nonzero Default  
    dsmonAggGroupIndex.3.2 = 7,  
    dsmonAggGroupIndex.3.3 = 7,  
    dsmonAggGroupIndex.3.4 = 7,  
    dsmonAggGroupIndex.3.5 = 7,  
    dsmonAggGroupIndex.3.6 = 7,  
    dsmonAggGroupIndex.3.7 = 7,  
    dsmonAggGroupIndex.3.8 = 1,           -- Nonzero CS  
    dsmonAggGroupIndex.3.9 = 7,  
    dsmonAggGroupIndex.3.10 = 3,          -- AF1  
    dsmonAggGroupIndex.3.11 = 7,  
    dsmonAggGroupIndex.3.12 = 3,  
    dsmonAggGroupIndex.3.13 = 7,  
    dsmonAggGroupIndex.3.14 = 3,  
    dsmonAggGroupIndex.3.15 = 7,  
    dsmonAggGroupIndex.3.16 = 1,  
    dsmonAggGroupIndex.3.17 = 7,  
    dsmonAggGroupIndex.3.18 = 4,          -- AF2  
    dsmonAggGroupIndex.3.19 = 7,  
    dsmonAggGroupIndex.3.20 = 4,  
    dsmonAggGroupIndex.3.21 = 7,  
    dsmonAggGroupIndex.3.22 = 4,  
    dsmonAggGroupIndex.3.23 = 7,  
    dsmonAggGroupIndex.3.24 = 1,  
    dsmonAggGroupIndex.3.25 = 7,  
    dsmonAggGroupIndex.3.26 = 5,          -- AF3  
    dsmonAggGroupIndex.3.27 = 7,  
    dsmonAggGroupIndex.3.28 = 5,  
    dsmonAggGroupIndex.3.29 = 2,          -- EF  
    dsmonAggGroupIndex.3.30 = 5,  
    dsmonAggGroupIndex.3.31 = 7,  
    dsmonAggGroupIndex.3.32 = 1,  
    dsmonAggGroupIndex.3.33 = 7,  
    dsmonAggGroupIndex.3.34 = 6,          -- AF4  
    dsmonAggGroupIndex.3.35 = 7,  
    dsmonAggGroupIndex.3.36 = 6,  
    dsmonAggGroupIndex.3.37 = 7,
```

```
dsmonAggGroupIndex.3.38 = 6,  
dsmonAggGroupIndex.3.39 = 7,  
dsmonAggGroupIndex.3.40 = 1,  
dsmonAggGroupIndex.3.41 = 7,  
dsmonAggGroupIndex.3.42 = 7,  
dsmonAggGroupIndex.3.43 = 7,  
dsmonAggGroupIndex.3.44 = 7,  
dsmonAggGroupIndex.3.45 = 7,  
dsmonAggGroupIndex.3.46 = 7,  
dsmonAggGroupIndex.3.47 = 7,  
dsmonAggGroupIndex.3.48 = 1,  
dsmonAggGroupIndex.3.49 = 7,  
dsmonAggGroupIndex.3.50 = 7,  
dsmonAggGroupIndex.3.51 = 7,  
dsmonAggGroupIndex.3.52 = 7,  
dsmonAggGroupIndex.3.53 = 7,  
dsmonAggGroupIndex.3.54 = 7,  
dsmonAggGroupIndex.3.55 = 7,  
dsmonAggGroupIndex.3.56 = 1,  
dsmonAggGroupIndex.3.57 = 7,  
dsmonAggGroupIndex.3.58 = 7,  
dsmonAggGroupIndex.3.59 = 7,  
dsmonAggGroupIndex.3.60 = 7,  
dsmonAggGroupIndex.3.61 = 7,  
dsmonAggGroupIndex.3.62 = 7,  
dsmonAggGroupIndex.3.63 = 7);
```

#### 5.7. Step 7: Lock the Counter Aggregation Configuration

Before any existing collections can be activated by the agent, the counter aggregation configuration must be locked, by setting the `dsmonAggControlLocked` scalar to 'true'.

```
SET(dsmonAggControlLocked.0 = true(1));
```

#### 6. Intellectual Property

The IETF takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on the IETF's procedures with respect to rights in standards-track and standards-related documentation can be found in BCP 11, RFC 2028. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of

such proprietary rights by implementors or users of this specification can be obtained from the IETF Secretariat.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights which may cover technology that may be required to practice this standard. Please address the information to the IETF Executive Director.

## 7. Acknowledgements

This memo is a product of the RMONMIB WG. It is based on an Internet Draft that was produced with a great deal of assistance from Keith McCloghrie and Bijendra Jain.

## 8. References

- [RFC1155] Rose, M. and K. McCloghrie, "Structure and Identification of Management Information for TCP/IP-based Internets", STD 16, RFC 1155, May 1990.
- [RFC1157] Case, J., Fedor, M., Schoffstall, M. and C. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, May 1990.
- [RFC1212] Rose, M. and K. McCloghrie, "Concise MIB Definitions", STD 16, RFC 1212, March 1991.
- [RFC1215] Rose, M., "A Convention for Defining Traps for use with the SNMP", RFC 1215, March 1991.
- [RFC1901] Case, J., McCloghrie, K., Rose, M. and S. Waldbusser, "Introduction to Community-based SNMPv2", RFC 1901, January 1996.
- [RFC1905] Case, J., McCloghrie, K., Rose, M. and S. Waldbusser, "Protocol Operations for Version 2 of the Simple Network Management Protocol (SNMPv2)", RFC 1905, January 1996.
- [RFC1906] Case, J., McCloghrie, K., Rose, M. and S. Waldbusser, "Transport Mappings for Version 2 of the Simple Network Management Protocol (SNMPv2)", RFC 1906, January 1996.
- [RFC2021] Waldbusser, S., "Remote Network Monitoring Management Information Base Version 2 using SMIV2", RFC 2021, January 1997.
- [RFC2026] Bradner, S., "The Internet Standards Process -- Revision 3", BCP 9, RFC 2026, October 1996.

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [RFC2474] Nichols, K., Blake, S., Baker, F. and D. Black, "Definition of the Differentiated Services Field (DS Field) in the IPv4 and IPv6 Headers", RFC 2474, December 1998.
- [RFC2475] Blake, S., Black, D., Carlson, M., Davies, E., Wang, Z. and W. Weiss, "An Architecture for Differentiated Services", RFC 2475, December 1998.
- [RFC2570] Case, J., Mundy, R., Partain, D. and B. Stewart, "Introduction to Version 3 of the Internet-standard Network Management Framework", RFC 2570, April 1999.
- [RFC2571] Wijnen, B., Harrington, D. and R. Presuhn, "An Architecture for Describing SNMP Management Frameworks", RFC 2571, April 1999.
- [RFC2572] Case, J., Harrington D., Presuhn R. and B. Wijnen, "Message Processing and Dispatching for the Simple Network Management Protocol (SNMP)", RFC 2572, April 1999.
- [RFC2573] Levi, D., Meyer, P. and B. Stewart, "SNMPv3 Applications", RFC 2573, April 1999.
- [RFC2574] Blumenthal, U. and B. Wijnen, "User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)", RFC 2574, April 1999.
- [RFC2575] Wijnen, B., Presuhn, R. and K. McCloghrie, "View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP)", RFC 2575, April 1999.
- [RFC2578] McCloghrie, K., Perkins, D. and J. Schoenwaelder, "Structure of Management Information Version 2 (SMIv2)", STD 58, RFC 2578, April 1999.
- [RFC2579] McCloghrie, K., Perkins, D. and J. Schoenwaelder, "Textual Conventions for SMIv2", STD 58, RFC 2579, April 1999.
- [RFC2580] McCloghrie, K., Perkins, D. and J. Schoenwaelder, "Conformance Statements for SMIv2", STD 58, RFC 2580, April 1999.
- [RFC2856] Bierman, A., McCloghrie, K., and R. Presuhn, "Textual Conventions for Additional High Capacity Data Types", RFC 2856, June 2000.

[RFC2895] Bierman, A., Bucci, C. and R. Iddon, "Remote Network Monitoring MIB Protocol Identifier Reference", RFC 2895, August 2000.

[RFC3273] Waldbusser, S., "Remote Monitoring Management Information Base for High Capacity Networks", RFC 3273, May 2002.

## 9. Security Considerations

In order to implement this MIB, a probe must capture all packets on the locally-attached network, including packets between third parties. These packets are analyzed to collect network addresses, protocol usage information, and conversation statistics. Data of this nature may be considered sensitive in some environments. In such environments the administrator may wish to restrict SNMP access to the probe.

There are a number of management objects defined in this MIB that have a MAX-ACCESS clause of read-write and/or read-create. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations.

SNMPv1 by itself is not a secure environment. Even if the network itself is secure (for example by using IPSec), even then, there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB.

It is recommended that the implementors consider the security features as provided by the SNMPv3 framework. Specifically, the use of the User-based Security Model RFC 2574 [RFC2574] and the View-based Access Control Model RFC 2575 [RFC2575] is recommended.

It is then a customer/user responsibility to ensure that the SNMP entity giving access to an instance of this MIB, is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

**10. Author's Address**

**Andy Bierman  
Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA USA 95134**

**Phone: +1 408-527-3711  
EMail: [abierman@cisco.com](mailto:abierman@cisco.com)**

## 11. Full Copyright Statement

Copyright (C) The Internet Society (2002). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

## Acknowledgement

Funding for the RFC Editor function is currently provided by the Internet Society.