Network Working Group Request for Comments: 2933 Category: Standards Track K. McCloghrie cisco Systems D. Farinacci Procket Networks D. Thaler Microsoft October 2000

# **Internet Group Management Protocol MIB**

#### Status of this Memo

This document specifies an Internet standards track protocol for the Internet community, and requests discussion and suggestions for improvements. Please refer to the current edition of the "Internet Official Protocol Standards" (STD 1) for the standardization state and status of this protocol. Distribution of this memo is unlimited.

## Copyright Notice

Copyright (C) The Internet Society (2000). All Rights Reserved.

#### Abstract

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes objects used for managing the Internet Group Management Protocol (IGMP).

#### Table of Contents

1	Introduction 1
2	The SNMP Network Management Framework 2
3	Overview 3
4	Definitions 3
5	Security Considerations 14
6	Intellectual Property Notice 15
	Acknowledgements
8	Authors' Addresses 16
9	References
10	Full Copyright Statement 19

#### 1. Introduction

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes objects used for managing the Internet

McCloghrie, et al.

Standards Track

[Page 1]

Group Management Protocol (IGMP), version 1 [16] or version 2 [17]. A future version of this MIB will support IGMP version 3 (currently a work in progress). All of this MIB module is applicable to IPv4 multicast routers; a subset is applicable to hosts implementing IGMP. Since IGMP is specific to IPv4, this MIB does not support management of equivalent functionality for other address families, such as IPv6. Such management may be supported by other MIBs.

# 2. The SNMP Network Management Framework

The SNMP Management Framework presently consists of five major components:

- An overall architecture, described in RFC 2571 [1].
- Mechanisms for describing and naming objects and events for the 0 purpose of management. The first version of this Structure of Management Information (SMI) is called SMIv1 and described in STD 16, RFC 1155 [2], STD 16, RFC 1212 [3] and RFC 1215 [4]. The second version, called SMIv2, is described in STD 58, RFC 2578 [5], STD 58, RFC 2579 [6] and STD 58, RFC 2580 [7].
- Message protocols for transferring management information. 0 first version of the SNMP message protocol is called SNMPv1 and described in STD 15, RFC 1157 [8]. A second version of the SNMP message protocol, which is not an Internet standards track protocol, is called SNMPv2c and described in RFC 1901 [9] and RFC 1906 [10]. The third version of the message protocol is called SNMPv3 and described in RFC 1906 [10], RFC 2572 [11] and RFC 2574 [12].
- 0 Protocol operations for accessing management information. first set of protocol operations and associated PDU formats is described in STD 15, RFC 1157 [8]. A second set of protocol operations and associated PDU formats is described in RFC 1905 Γ131.
- A set of fundamental applications described in RFC 2573 [14] and 0 the view-based access control mechanism described in RFC 2575 [15].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. Objects in the MIB are defined using the mechanisms defined in the SMI.

This memo specifies a MIB module that is compliant to the SMIv2. MIB conforming to the SMIv1 can be produced through the appropriate translations. The resulting translated MIB must be semantically equivalent, except where objects or events are omitted because no translation is possible (use of Counter64). Some machine readable information in SMIv2 will be converted into textual descriptions in SMIv1 during the translation process. However, this loss of machine readable information is not considered to change the semantics of the MIB.

#### 3. Overview

This MIB module contains two tables:

- (1) the IGMP Interface Table which contains one row for each interface on which IGMP is enabled, and
- the IGMP Cache Table which contains one row for each IP (2) multicast group for which there are members on a particular interface.

Both tables are intended to be implemented by hosts and routers, but some columnar objects in each table apply only to routers.

#### 4. Definitions

```
IGMP-STD-MIB DEFINITIONS ::= BEGIN
```

#### **IMPORTS**

MODULE-IDENTITY, OBJECT-TYPE, mib-2, Counter32, Gauge32, Unsigned32, IpAddress, TimeTicks FROM SNMPv2-SMI RowStatus, TruthValue FROM SNMPv2-TC MODULE-COMPLIANCE, OBJECT-GROUP FROM SNMPv2-CONF InterfaceIndexOrZero, InterfaceIndex FROM IF-MIB;

#### iampStdMIB MODULE-IDENTITY

LAST-UPDATED "200009280000Z" -- September 28, 2000 ORGANIZATION "IETF IDMR Working Group." CONTACT-INFO

" Dave Thaler **Microsoft Corporation** One Microsoft Way Redmond, WA 98052-6399

Phone: +1 425 703 8835

EMail: dthaler@microsoft.com"

DESCRIPTION

"The MIB module for IGMP Management."

"200009280000Z" -- September 28, 2000 REVISION

```
DESCRIPTION
            "Initial version, published as RFC 2933."
    ::= { mib-2 85 }
igmpMIBObjects
                   OBJECT IDENTIFIER ::= { igmpStdMIB 1 }
    The IGMP Interface Table
igmpInterfaceTable OBJECT-TYPE
               SEQUENCE OF IgmpInterfaceEntry
    SYNTAX
    MAX-ACCESS not-accessible
    STATUS
               current
    DESCRIPTION
            "The (conceptual) table listing the interfaces on which IGMP
            is enabled.
    ::= { igmpMIBObjects 1 }
igmpInterfaceEntry OBJECT-TYPE
    SYNTAX
               IgmpInterfaceEntry
    MAX-ACCESS not-accessible
               current
    STATUS
    DESCRIPTION
            "An entry (conceptual row) representing an interface on
            which IGMP is enabled."
    INDEX
               { igmpInterfaceIfIndex }
    ::= { igmpInterfaceTable 1 }
IgmpInterfaceEntry ::= SEQUENCE {
    igmpInterfaceIfIndex
                                        InterfaceIndex,
    igmpInterfaceQueryInterval
                                        Unsigned32,
                                        RowStatus
    iampInterfaceStatus
                                        Unsigned32,
    igmpInterfaceVersion
    igmpInterfaceQuerier
                                        IpAddress,
    igmpInterfaceQueryMaxResponseTime
                                        Unsigned32,
                                        TimeTicks,
    igmpInterfaceQuerierUpTime
    igmpInterfaceQuerierExpiryTime
                                        TimeTicks,
                                        TimeTicks,
    igmpInterfaceVersion1QuerierTimer
    igmpInterfaceWrongVersionQueries
                                        Counter32,
    igmpInterfaceJoins
                                        Counter32,
    igmpInterfaceProxyIfIndex
                                        InterfaceIndexOrZero,
    igmpInterfaceGroups
                                        Gauge32,
                                        Unsigned32,
    igmpInterfaceRobustness
    igmpInterfaceLastMembQueryIntvl
                                        Unsigned32
}
```

```
igmpInterfaceIfIndex OBJECT-TYPE
                InterfaceIndex
    SYNTAX
    MAX-ACCESS not-accessible
    STATUS
                current
    DESCRIPTION
             "The ifIndex value of the interface for which IGMP is
             enabled."
    ::= { igmpInterfaceEntry 1 }
igmpInterfaceQueryInterval OBJECT-TYPE
                Unsianed32
    SYNTAX
    UNITS
                "seconds"
    MAX-ACCESS read-create
    STATUS
                current
    DESCRIPTION
             "The frequency at which IGMP Host-Query packets are
            transmitted on this interface."
                { 125 }
    ::= { igmpInterfaceEntry 2 }
igmpInterfaceStatus OBJECT-TYPE
    SYNTAX
                RowStatus
    MAX-ACCESS read-create
               current
    STATUS
    DESCRIPTION
             "The activation of a row enables IGMP on the interface.
                                                                          The
            destruction of a row disables IGMP on the interface.'
    ::= { igmpInterfaceEntry 3 }
igmpInterfaceVersion OBJECT-TYPE
    SYNTAX
                Unsigned32
    MAX-ACCESS read-create
    STATUS
                current
    DESCRIPTION
             "The version of IGMP which is running on this interface.
            This object can be used to configure a router capable of running either value. For IGMP to function correctly, all
            routers on a LAN must be configured to run the same version
            of IGMP on that LAN."
    DEFVAL
                { 2 }
    ::= { igmpInterfaceEntry 4 }
igmpInterfaceQuerier OBJECT-TYPE
                IpAddress
    SYNTAX
    MAX-ACCESS read-only
                current
    STATUS
    DESCRIPTION
             "The address of the IGMP Querier on the IP subnet to which
```

```
this interface is attached."
    ::= { igmpInterfaceEntry 5 }
igmpInterfaceQueryMaxResponseTime OBJECT-TYPE
    SYNTAX
               Unsigned32 (0..255)
               "tenths of seconds"
    UNITS
    MAX-ACCESS read-create
              current
    STATUS
    DESCRIPTION
            "The maximum guery response time advertised in IGMPv2
            queries on this interface."
    DEFVAL
              { 100 }
    ::= { igmpInterfaceEntry 6 }
igmpInterfaceQuerierUpTime OBJECT-TYPE
    SYNTAX
              TimeTicks
    MAX-ACCESS read-only
    STATUS
               current
    DESCRIPTION
            "The time since igmpInterfaceQuerier was last changed."
    ::= { igmpInterfaceEntry 7 }
igmpInterfaceQuerierExpiryTime OBJECT-TYPE
    SYNTAX
              TimeTicks
    MAX-ACCESS read-only
    STATUS
              current
    DESCRIPTION
            "The amount of time remaining before the Other Querier
            Present Timer expires. If the local system is the querier,
            the value of this object is zero.
    ::= { igmpInterfaceEntry 8 }
igmpInterfaceVersion1QuerierTimer OBJECT-TYPE
    SYNTAX
              TimeTicks
    MAX-ACCESS read-only
    STATUS
             current
    DESCRIPTION
            "The time remaining until the host assumes that there are no
            IGMPv1 routers present on the interface. While this is non-
            zero, the host will reply to all queries with version 1
            membership reports."
    ::= { igmpInterfaceEntry 9 }
igmpInterfaceWrongVersionQueries OBJECT-TYPE
    SYNTAX
               Counter32
    MAX-ACCESS read-only
    STATUS
               current
    DESCRIPTION
```

```
"The number of queries received whose IGMP version does not
            match igmpInterfaceVersion, over the lifetime of the row
                    IGMP requires that all routers on a LAN be
            configured to run the same version of IGMP. Thus, if any
            queries are received with the wrong version, this indicates
            a configuration error."
    ::= { igmpInterfaceEntry 10 }
igmpInterfaceJoins OBJECT-TYPE
    SYNTAX
              Counter32
    MAX-ACCESS read-only
    STATUS
               current
    DESCRIPTION
            "The number of times a group membership has been added on
this interface; that is, the number of times an entry for
            this interface has been added to the Cache Table. This
            object gives an indication of the amount of IGMP activity
            over the lifetime of the row entry."
    ::= { igmpInterfaceEntry 11 }
igmpInterfaceProxyIfIndex OBJECT-TYPE
    SYNTAX
               InterfaceIndexOrZero
    MAX-ACCESS read-create
               current
    STATUS
    DESCRIPTION
            "Some devices implement a form of IGMP proxying whereby
            memberships learned on the interface represented by this
            row, cause IGMP Host Membership Reports to be sent on the
            interface whose ifIndex value is given by this object. Such
            a device would implement the igmpV2RouterMIBGroup only on
            its router interfaces (those interfaces with non-zero
            igmpInterfaceProxyIfIndex). Typically, the value of this
            object is 0, indicating that no proxying is being done."
               \{0\}
    DEFVAL
    ::= { igmpInterfaceEntry 12 }
igmpInterfaceGroups OBJECT-TYPE
    SYNTAX
              Gauge32
    MAX-ACCESS read-only
    STATUS
               current
    DESCRIPTION
            "The current number of entries for this interface in the
            Cache Table.
    ::= { igmpInterfaceEntry 13 }
igmpInterfaceRobustness OBJECT-TYPE
              Unsigned32 (1..255)
    SYNTAX
    MAX-ACCESS read-create
```

```
STATUS
                 current
    DESCRIPTION
              "The Robustness Variable allows tuning for the expected
              packet loss on a subnet. If a subnet is expected to be
             lossy, the Robustness Variable may be increased. IGMP is robust to (Robustness Variable-1) packet losses."
    DEFVAL
    ::= { igmpInterfaceEntry 14 }
igmpInterfaceLastMembQueryIntvl OBJECT-TYPE
                 Unsigned32 (0..255) "tenths of seconds"
    UNITS
    MAX-ACCESS read-create
    STATUS
                 current
    DESCRIPTION
              "The Last Member Query Interval is the Max Response Time
              inserted into Group-Specific Queries sent in response to
              Leave Group messages, and is also the amount of time between
             Group-Specific Query messages. This value may be tuned to modify the leave latency of the network. A reduced value results in reduced time to detect the loss of the last
              member of a group. The value of this object is irrelevant
              if igmpInterfaceVersion is 1.
    DEFVAL
                 { 10 }
    ::= { igmpInterfaceEntry 15 }
    The IGMP Cache Table
igmpCacheTable OBJECT-TYPE
                 SEQUENCE OF IgmpCacheEntry
    MAX-ACCESS not-accessible
    STATUS
                 current
    DESCRIPTION
              "The (conceptual) table listing the IP multicast groups for
              which there are members on a particular interface.
    ::= { igmpMIBObjects 2 }
igmpCacheEntry OBJECT-TYPE
                 IgmpCacheEntry
    SYNTAX
    MAX-ACCESS not-accessible
                 current
    STATUS
    DESCRIPTION
              "An entry (conceptual row) in the igmpCacheTable."
                 { igmpCacheAddress, igmpCacheIfIndex }
    ::= { igmpCacheTable 1 }
```

```
IgmpCacheEntry ::= SEQUENCE {
    igmpCacheAddress
                                 IpAddress,
    igmpCacheIfIndex
                                 InterfaceIndex,
    igmpCacheSelf
                                 TruthValue,
    igmpCacheLastReporter
                                 IpAddress,
    igmpCacheUpTime
                                 TimeTicks.
    igmpCacheExpirvTime
                                 TimeTicks.
                                 RowStatus,
    igmpCacheStatus
    igmpCacheVersion1HostTimer
                                 TimeTicks
}
igmpCacheAddress OBJECT-TYPE
    SYNTAX
               IpAddress
    MAX-ACCESS not-accessible
    STATUS
               current
    DESCRIPTION
            "The IP multicast group address for which this entry
            contains information."
    ::= { igmpCacheEntry 1 }
igmpCacheIfIndex OBJECT-TYPE
    SYNTAX
               InterfaceIndex
    MAX-ACCESS not-accessible
    STATUS
               current
    DESCRIPTION
            "The interface for which this entry contains information for
    an IP multicast group address."
::= { igmpCacheEntry 2 }
igmpCacheSelf OBJECT-TYPE
    SYNTAX
               TruthValue
    MAX-ACCESS read-create
    STATUS
               current
    DESCRIPTION
            "An indication of whether the local system is a member of
            this group address on this interface.
    DEFVAL
               { true }
    ::= { igmpCacheEntry 3 }
igmpCacheLastReporter OBJECT-TYPE
    SYNTAX
               IpAddress
    MAX-ACCESS read-only
               current
    STATUS
    DESCRIPTION
            "The IP address of the source of the last membership report
            received for this IP Multicast group address on this
            interface. If no membership report has been received, this
            object has the value 0.0.0.0."
```

```
::= { igmpCacheEntry 4 }
igmpCacheUpTime OBJECT-TYPE
                   TimeTicks
     SYNTAX
     MAX-ACCESS read-only
     STATUS
                   current
     DESCRIPTION
                "The time elapsed since this entry was created."
     ::= { igmpCacheEntry 5 }
igmpCacheExpiryTime OBJECT-TYPE
                  TimeTicks
     SYNTAX
     MAX-ACCESS read-only
     STATUS
                   current
     DESCRIPTION
                "The minimum amount of time remaining before this entry will
               be aged out. A value of 0 indicates that the entry is only
               present because igmpCacheSelf is true and that if the router left the group, this entry would be aged out immediately. Note that some implementations may process membership reports from the local system in the same way as reports
               from other hosts, so a value of 0 is not required.'
     ::= { igmpCacheEntry 6 }
igmpCacheStatus OBJECT-TYPE
     SYNTAX
                 RowStatus
     MAX-ACCESS read-create
     STATUS
                   current
     DESCRIPTION
                "The status of this entry."
     ::= { igmpCacheEntry 7 }
igmpCacheVersion1HostTimer OBJECT-TYPE
     SYNTAX
                   TimeTicks
     MAX-ACCESS read-only
     STATUS
                 current
     DESCRIPTION
               "The time remaining until the local router will assume that
               there are no longer any IGMP version 1 members on the IP
               subnet attached to this interface. Upon hearing any IGMPv1
               Membership Report, this value is reset to the group membership timer. While this time remaining is non-zero, the local router ignores any IGMPv2 Leave messages for this group that it receives on this interface."
     ::= { igmpCacheEntry 8 }
-- conformance information
```

```
igmpMIBConformance
                OBJECT IDENTIFIER ::= { igmpStdMIB 2 }
igmpMIBCompliances
               OBJECT IDENTIFIER ::= { igmpMIBConformance 1 }
OBJECT IDENTIFIER ::= { igmpMIBConformance 2 }
iampMIBGroups
-- compliance statements
igmpV1HostMIBCompliance MODULE-COMPLIANCE
    STATUS
            current
    DESCRIPTION
            "The compliance statement for hosts running IGMPv1 and
            implementing the IGMP MIB."
    MODULE
            -- this module
    MANDATORY-GROUPS { igmpBaseMIBGroup }
                igmpInterfaceStatus
    MIN-ACCESS réad-only
    DESCRIPTION
              "Write access is not required."
    OBJECT
               igmpCacheStatus
    MIN-ACCESS read-only
    DESCRIPTION
              "Write access is not required."
    ::= { igmpMIBCompliances 1 }
igmpV1RouterMIBCompliance MODULE-COMPLIANCE
    STATUS
            current
    DESCRIPTION
             "The compliance statement for routers running IGMPv1 and
            implementing the IGMP MIB."
           -- this module
      MANDATORY-GROUPS { igmpBaseMIBGroup,
                        igmpRouterMIBGroup
    OBJECT
                igmpInterfaceStatus
    MIN-ACCESS read-only
    DESCRIPTION
              "Write access is not required."
    OBJECT
                igmpCacheStatus
    MIN-ACCESS read-only
    DESCRIPTION
              "Write access is not required."
```

```
::= { igmpMIBCompliances 2 }
igmpV2HostMIBCompliance MODULE-COMPLIANCE
    STATUS
            current
    DESCRIPTION
             "The compliance statement for hosts running IGMPv2 and implementing the IGMP MIB."
    MODULE -- this module
    MANDATORY-GROUPS { igmpBaseMIBGroup,
                         igmpV2HostMIBGroup
    OBJECT
                igmpInterfaceStatus
    MIN-ACCESS read-only
    DESCRIPTION
              "Write access is not required."
                igmpCacheStatus
    OBJECT
    MIN-ACCESS read-only
    DESCRIPTION
              "Write access is not required."
    ::= { igmpMIBCompliances 3 }
igmpV2RouterMIBCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION
            "The compliance statement for routers running IGMPv2 and implementing the IGMP MIB."
            -- this module
    MODULE
    MANDATORY-GROUPS { igmpBaseMIBGroup,
                         igmpRouterMIBGroup,
                         igmpV2RouterMIBGroup
    OBJECT
                igmpInterfaceStatus
    MIN-ACCESS read-only
    DESCRIPTION
              "Write access is not required."
    OBJECT
                igmpCacheStatus
    MIN-ACCESS read-only
    DESCRIPTION
              "Write access is not required."
    ::= { igmpMIBCompliances 4 }
-- units of conformance
```

```
igmpBaseMIBGroup OBJECT-GROUP
    OBJECTS { igmpCacheSelf,
              igmpCacheStatus, igmpInterfaceStatus
    STATUS
            current
    DESCRIPTION
            "The basic collection of objects providing management of
            IGMP version 1 or 2.
    ::= { igmpMIBGroups 1 }
igmpRouterMIBGroup OBJECT-GROUP
    OBJECTS { igmpCacheUpTime, igmpCacheExpiryTime.
              igmpInterfaceJoins, igmpInterfaceGroups,
              igmpCacheLastReporter, igmpInterfaceQuerierUpTime,
              igmpInterfaceQuerierExpiryTime,
              igmpInterfaceQueryInterval
            current
    STATUS
    DESCRIPTION
            "A collection of additional objects for management of IGMP
            version 1 or 2 in routers.'
    ::= { igmpMIBGroups 2 }
igmpV2HostMIBGroup OBJECT-GROUP
    OBJECTS { igmpInterfaceVersion1QuerierTimer }
           current
    STATUS
    DESCRIPTION
            "A collection of additional objects for management of IGMP
            version 2 in hosts."
    ::= { igmpMIBGroups 3 }
iampHostOptMIBGroup OBJECT-GROUP
    OBJECTS { igmpCacheLastReporter, igmpInterfaceQuerier }
    STATUS current
    DESCRIPTION
            "A collection of optional objects for IGMP hosts.
            Supporting this group can be especially useful in an
            environment with a router which does not support the IGMP
            MIB."
    ::= { igmpMIBGroups 4 }
igmpV2RouterMIBGroup OBJECT-GROUP
    OBJECTS { igmpInterfaceVersion, igmpInterfaceQuerier,
              igmpInterfaceQueryMaxResponseTime,
              igmpInterfaceRobustness,
              igmpInterfaceWrongVersionQueries,
```

```
igmpInterfaceLastMembQueryIntvl,
              igmpCacheVersion1HostTimer
   STATUS
           current
   DESCRIPTION
            "A collection of additional objects for management of IGMP
            version 2 in routers."
    ::= { igmpMIBGroups 5 }
igmpV2ProxyMIBGroup OBJECT-GROUP
   OBJECTS { igmpInterfaceProxyIfIndex }
   STATUS
            current
   DESCRIPTION
            "A collection of additional objects for management of IGMP
            proxy devices.
    ::= { igmpMIBGroups 6 }
```

#### **END**

# 5. Security Considerations

This MIB contains readable objects whose values provide information related to multicast sessions. Some of these objects could contain sensitive information. In particular, the igmpCacheSelf and igmpCacheLastReporter can be used to identify machines which are listening to a given group address. There are also a number of objects that have a MAX-ACCESS clause of read-write and/or read-create, which allow an administrator to configure IGMP in the router.

While unauthorized access to the readable objects is relatively innocuous, unauthorized access to the write-able objects could cause a denial of service. Hence, the support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations.

SNMPv1 by itself is such an insecure environment. Even if the network itself is secure (for example by using IPSec), even then, there is no control as to who on the secure network is allowed to access and SET (change/create/delete) the objects in this MIB.

It is recommended that the implementers consider the security features as provided by the SNMPv3 framework. Specifically, the use of the User-based Security Model RFC 2574 [12] and the View-based Access Control Model RFC 2575 [15] is recommended.

It is then a customer/user responsibility to ensure that the SNMP entity giving access to this MIB, is properly configured to give access to those objects only to those principals (users) that have legitimate rights to access them.

# 6. Intellectual Property Notice

The IETF takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on the IETF's procedures with respect to rights in standards-track and standards-related documentation can be found in BCP-11. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF Secretariat.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights which may cover technology that may be required to practice this standard. Please address the information to the IETF Executive Director.

# 7. Acknowledgements

This MIB module was updated based on feedback from the IETF's Inter-Domain Multicast Routing (IDMR) Working Group.

### RFC 2933

October 2000

# 8. Authors' Addresses

Keith McCloghrie cisco Systems, Inc. 170 West Tasman Drive San Jose, CA 95134-1706

Phone: +1 408 526 5260 EMail: kzm@cisco.com

Dino Farinacci Procket Networks 3850 North First Street San Jose, CA 95134

Phone: +1 408-954-7909 Email: dino@procket.com

Dave Thaler Microsoft Corporation One Microsoft Way Redmond, WA 48105-6399

Phone: +1 425 703 8835

EMail: dthaler@microsoft.com

### 9. References

- Wijnen, B., Harrington, D. and R. Presuhn, "An Architecture for Describing SNMP Management Frameworks", RFC 2571, April 1999.
- Rose, M. and K. McCloghrie, "Structure and Identification of Management Information for TCP/IP-based Internets", STD 16, RFC Γ21 1155, May 1990.
- Rose, M. and K. McCloghrie, "Concise MIB Definitions", STD 16, [3] RFC 1212, March 1991.
- Rose, M., "A Convention for Defining Traps for use with the SNMP", RFC 1215, March 1991. Γ47
- McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M. and S. Waldbusser, "Structure of Management Information Version 2 (SMIv2)", STD 58, RFC 2578, April 1999. Γ5]
- McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M. and S. Waldbusser, "Textual Conventions for SMIv2", STD 58, Γ61 RFC 2579, April 1999.
- McCloghrie, K., Perkins, D., Schoenwaelder, J., Case, J., Rose, M. and S. Waldbusser, "Conformance Statements for SMIv2", STD 58, RFC 2580, April 1999. Γ71
- Case, J., Fedor, M., Schoffstall, M. and J. Davin, "Simple Network Management Protocol", STD 15, RFC 1157, May 1990. Г87
- Case, J., McCloghrie, K., Rose, M. and S. Waldbusser, Г91 "Introduction to Community-based SNMPv2", RFC 1901, January 1996.
- [10] Case, J., McCloghrie, K., Rose, M. and S. Waldbusser, "Transport Mappings for Version 2 of the Simple Network Management Protocol (SNMPv2)", RFC 1906, January 1996.
- [11] Case, J., Harrington D., Presuhn R. and B. Wijnen, "Message Processing and Dispatching for the Simple Network Management Protocol (SNMP)", RFC 2572, April 1999.
- [12] Blumenthal, U. and B. Wijnen, "User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)", RFC 2574, April 1999.

- [13] Case, J., McCloghrie, K., Rose, M. and S. Waldbusser, "Protocol Operations for Version 2 of the Simple Network Management Protocol (SNMPv2)", RFC 1905, January 1996.
- [14] Levi, D., Meyer, P. and B. Stewart, "SNMPv3 Applications", RFC
  2573, April 1999.
- [15] Wijnen, B., Presuhn, R. and K. McCloghrie, "View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP)", RFC 2575, April 1999.
- [16] Deering, S., "Host Extensions for IP Multicasting", STD 5, RFC 1112, August 1989.
- [17] Fenner, W., "Internet Group Management Protocol, Version 2", RFC 2236, November 1997.

### 10. Full Copyright Statement

Copyright (C) The Internet Society (2000). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

#### **Acknowledgement**

Funding for the RFC Editor function is currently provided by the Internet Society.