            Definitions of Managed Objects for RS-232-like Hardware Devices
                              using SMIv2

Status of this Memo

   This document specifies an Internet standards track protocol for the
   Internet community, and requests discussion and suggestions for
   improvements. Please refer to the current edition of the "Internet
   Official Protocol Standards" (STD 1) for the standardization state
   and status of this protocol. Distribution of this memo is unlimited.

Table of Contents

1. Introduction

   This memo defines an extension to the Management Information Base
   (MIB) for use with network management protocols in the Internet
   community. In particular, it defines objects for the management of
   RS-232-like devices.

2. The SNMPv2 Network Management Framework

   The SNMPv2 Network Management Framework consists of four major
   components. They are:

      o   RFC 1442 [1] which defines the SMI, the mechanisms used for
           describing and naming objects for the purpose of management.

      o   STD 17, RFC 1213 [2] defines MIB-II, the core set of managed
           objects for the Internet suite of protocols.

Stewart   [Page 1]

        o   RFC 1445 [3] which defines the administrative and other
                architectural aspects of the framework.

        o   RFC 1448 [4] which defines the protocol used for network
                access to managed objects.

   The Framework permits new objects to be defined for the purpose of
   experimentation and evaluation.

2.1. Object Definitions

   Managed objects are accessed via a virtual information store, termed
   the Management Information Base or MIB. Objects in the MIB are
   defined using the subset of Abstract Syntax Notation One (ASN.1)
   defined in the SMI. In particular, each object object type is named
   by an OBJECT IDENTIFIER, an administratively assigned name. The
   object type together with an object instance serves to uniquely
   identify a specific instantiation of the object. For human
   convenience, we often use a textual string, termed the descriptor, to
   refer to the object type.

3. Overview

   The RS-232-like Hardware Device MIB applies to interface ports that
   might logically support the Interface MIB, a Transmission MIB, or the
   Character MIB. The most common example is an RS-232 port with modem
   signals.

   The RS-232-like Hardware Device MIB is mandatory for all systems that
   have such a hardware port supporting services managed through some
   other MIB.

   The MIB includes multiple similar types of hardware, and as a result
   contains objects not applicable to all of those types. The
   compliance definitions herein thus have a general group for all
   implementations, and separate groups for the different types of
   ports, such as asynchronous and synchronous.

   The RS-232-like Hardware Port MIB includes RS-232, RS-422, RS-423,
   V.35, and other asynchronous or synchronous, serial physical links
   with a similar set of control signals.

   The MIB contains objects that relate to physical layer connections.
   Such connections may provide interesting hardware signals (other than
   for basic data transfer), such as RNG and DCD. Hardware ports also
   have such attributes as speed and bits per character.

The MIB comprises one base object and four tables, detailed in the
following sections. The tables contain objects for all ports,
asynchronous ports, and input and output control signals.

3.1. Relationship to Interface MIB

The RS-232-like MIB is one of many MIBs designed for layered use as
described in the Interface MIB [5]. In most implementations where it
is present, it will be in the lowest interface sublayer, that is, the
RS-232-like MIB represents the physical layer, providing service to
higher layers such as the Character MIB [6] or PPP MIB [7].

The Interface MIB's ifTestTable and ifRcvAddressTable are not
relevant to the RS-232-like MIB.

The RS-232-like MIB is relevant for ifType values rs232(33), v35(45),
and perhaps others.

The RS-232-like MIB requires the conformance groups ifGeneralGroup,
and ifFixedLengthGroup.

The value of ifSpeed is the same as rs232PortOutSpeed.

Usefulness of error counters in this MIB depends on the octet
counters in ifFixedLengthGroup.

4. Definitions

```
RS-232-MIB DEFINITIONS ::= BEGIN

IMPORTS
    MODULE-IDENTITY, OBJECT-TYPE, NOTIFICATION-TYPE,
    Counter32, Integer32
        FROM SNMPv2-SMI
    InterfaceIndex
        FROM IF-MIB
    transmission
        FROM RFC1213-MIB
    MODULE-COMPLIANCE, OBJECT-GROUP
        FROM SNMPv2-CONF;


rs232 MODULE-IDENTITY
    LAST-UPDATED "9405261700Z"
    ORGANIZATION "IETF Character MIB Working Group"
    CONTACT-INFO
            "         Bob Stewart
           Postal: Xyplex, Inc.
```

                        295 Foster Street
                        Littleton, MA 01460

                    Tel: 508-952-4816
                    Fax: 508-952-4887
                E-mail: rlstewart@eng.xyplex.com"
        DESCRIPTION
            "The MIB module for RS-232-like hardware devices."
        ::= { transmission 33 }

    -- Generic RS-232-like information

    rs232Number OBJECT-TYPE
        SYNTAX Integer32
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The number of ports (regardless of their current
            state) in the RS-232-like general port table."
        ::= { rs232 1 }

    -- RS-232-like General Port Table

    rs232PortTable OBJECT-TYPE
        SYNTAX SEQUENCE OF Rs232PortEntry
        MAX-ACCESS not-accessible
        STATUS current
        DESCRIPTION
            "A list of port entries. The number of entries is
            given by the value of rs232Number."
        ::= { rs232 2 }

    rs232PortEntry OBJECT-TYPE
        SYNTAX Rs232PortEntry
        MAX-ACCESS not-accessible
        STATUS current
        DESCRIPTION
            "Status and parameter values for a port."
        INDEX { rs232PortIndex }
        ::= { rs232PortTable 1 }

    Rs232PortEntry ::=
        SEQUENCE {
            rs232PortIndex
                InterfaceIndex,
            rs232PortType

```
                    INTEGER,
                rs232PortInSigNumber
                    Integer32,
                rs232PortOutSigNumber
                    Integer32,
                rs232PortInSpeed
                    Integer32,
                rs232PortOutSpeed
                    Integer32,
                rs232PortInFlowType
                    INTEGER,
                rs232PortOutFlowType
                    INTEGER
            }

    rs232PortIndex OBJECT-TYPE
        SYNTAX InterfaceIndex
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The value of ifIndex for the port.  By convention
            and if possible, hardware port numbers map directly
            to external connectors.  The value for each port must
            remain constant at least from one re-initialization
            of the network management agent to the next."
        ::= { rs232PortEntry 1 }

    rs232PortType OBJECT-TYPE
        SYNTAX INTEGER { other(1), rs232(2), rs422(3),
                         rs423(4), v35(5), x21(6) }
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The port's hardware type."
        ::= { rs232PortEntry 2 }

    rs232PortInSigNumber OBJECT-TYPE
        SYNTAX Integer32
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The number of input signals for the port in the
            input signal table (rs232PortInSigTable).  The table
            contains entries only for those signals the software
            can detect and that are useful to observe."
        ::= { rs232PortEntry 3 }
```

```
rs232PortOutSigNumber OBJECT-TYPE
    SYNTAX Integer32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of output signals for the port in the
        output signal table (rs232PortOutSigTable).  The
        table contains entries only for those signals the
        software can assert and that are useful to observe."
    ::= { rs232PortEntry 4 }

rs232PortInSpeed OBJECT-TYPE
    SYNTAX Integer32
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "The port's input speed in bits per second.  Note that
        non-standard values, such as 9612, are probably not allowed
        on most implementations."
    ::= { rs232PortEntry 5 }

rs232PortOutSpeed OBJECT-TYPE
    SYNTAX Integer32
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "The port's output speed in bits per second.  Note that
        non-standard values, such as 9612, are probably not allowed
        on most implementations."
    ::= { rs232PortEntry 6 }

rs232PortInFlowType OBJECT-TYPE
    SYNTAX INTEGER { none(1), ctsRts(2), dsrDtr(3) }
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "The port's type of input flow control.  'none'
        indicates no flow control at this level.
        'ctsRts' and 'dsrDtr' indicate use of the indicated
        hardware signals."
    ::= { rs232PortEntry 7 }

rs232PortOutFlowType OBJECT-TYPE
    SYNTAX INTEGER { none(1), ctsRts(2), dsrDtr(3) }
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "The port's type of output flow control.  'none'
```

```
            indicates no flow control at this level.
            'ctsRts' and 'dsrDtr' indicate use of the indicated
            hardware signals."
        ::= { rs232PortEntry 8 }


    -- RS-232-like Asynchronous Port Table

    rs232AsyncPortTable OBJECT-TYPE
        SYNTAX SEQUENCE OF Rs232AsyncPortEntry
        MAX-ACCESS not-accessible
        STATUS current
        DESCRIPTION
            "A list of asynchronous port entries.  Entries need
            not exist for synchronous ports."
        ::= { rs232 3 }

    rs232AsyncPortEntry OBJECT-TYPE
        SYNTAX Rs232AsyncPortEntry
        MAX-ACCESS not-accessible
        STATUS current
        DESCRIPTION
            "Status and parameter values for an asynchronous
            port."
        INDEX { rs232AsyncPortIndex }
        ::= { rs232AsyncPortTable 1 }

    Rs232AsyncPortEntry ::=
        SEQUENCE {
            rs232AsyncPortIndex
                InterfaceIndex,
            rs232AsyncPortBits
                INTEGER,
            rs232AsyncPortStopBits
                INTEGER,
            rs232AsyncPortParity
                INTEGER,
            rs232AsyncPortAutobaud
                INTEGER,
            rs232AsyncPortParityErrs
                Counter32,
            rs232AsyncPortFramingErrs
                Counter32,
            rs232AsyncPortOverrunErrs
                Counter32

        }
```

```
rs232AsyncPortIndex OBJECT-TYPE
    SYNTAX InterfaceIndex
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "A unique value for each port.  Its value is the
        same as rs232PortIndex for the port."
    ::= { rs232AsyncPortEntry 1 }

rs232AsyncPortBits OBJECT-TYPE
    SYNTAX INTEGER (5..8)
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "The port's number of bits in a character."
    ::= { rs232AsyncPortEntry 2 }

rs232AsyncPortStopBits OBJECT-TYPE
    SYNTAX INTEGER { one(1), two(2),
                     oneAndHalf(3), dynamic(4) }
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "The port's number of stop bits."
    ::= { rs232AsyncPortEntry 3 }

rs232AsyncPortParity OBJECT-TYPE
    SYNTAX INTEGER { none(1), odd(2), even(3),
                     mark(4), space(5) }
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "The port's sense of a character parity bit."
    ::= { rs232AsyncPortEntry 4 }

rs232AsyncPortAutobaud OBJECT-TYPE
    SYNTAX INTEGER { enabled(1), disabled(2) }
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "A control for the port's ability to automatically
        sense input speed.

        When rs232PortAutoBaud is 'enabled', a port may
        autobaud to values different from the set values for
        speed, parity, and character size.  As a result a
        network management system may temporarily observe
        values different from what was previously set."
```

```
        ::= { rs232AsyncPortEntry 5 }

    rs232AsyncPortParityErrs OBJECT-TYPE
        SYNTAX Counter32
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Total number of characters with a parity error,
            input from the port since system re-initialization
            and while the port state was 'up' or 'test'."
        ::= { rs232AsyncPortEntry 6 }

    rs232AsyncPortFramingErrs OBJECT-TYPE
        SYNTAX Counter32
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Total number of characters with a framing error,
            input from the port since system re-initialization
            and while the port state was 'up' or 'test'."
        ::= { rs232AsyncPortEntry 7 }

    rs232AsyncPortOverrunErrs OBJECT-TYPE
        SYNTAX Counter32
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Total number of characters with an overrun error,
            input from the port since system re-initialization
            and while the port state was 'up' or 'test'."
        ::= { rs232AsyncPortEntry 8 }


    -- RS-232-like Synchronous Port Table

    rs232SyncPortTable OBJECT-TYPE
        SYNTAX SEQUENCE OF Rs232SyncPortEntry
        MAX-ACCESS not-accessible
        STATUS current
        DESCRIPTION
            "A list of asynchronous port entries.  Entries need
            not exist for synchronous ports."
        ::= { rs232 4 }

    rs232SyncPortEntry OBJECT-TYPE
        SYNTAX Rs232SyncPortEntry
        MAX-ACCESS not-accessible
        STATUS current
```

```
        DESCRIPTION
            "Status and parameter values for a synchronous
            port."
        INDEX { rs232SyncPortIndex }
        ::= { rs232SyncPortTable 1 }

   Rs232SyncPortEntry ::=
        SEQUENCE {
            rs232SyncPortIndex
                InterfaceIndex,
            rs232SyncPortClockSource
                INTEGER,
            rs232SyncPortFrameCheckErrs
                Counter32,
            rs232SyncPortTransmitUnderrunErrs
                Counter32,
            rs232SyncPortReceiveOverrunErrs
                Counter32,
            rs232SyncPortInterruptedFrames
                Counter32,
            rs232SyncPortAbortedFrames
                Counter32,
            rs232SyncPortRole
                INTEGER,
            rs232SyncPortEncoding
                INTEGER,
            rs232SyncPortRTSControl
                INTEGER,
            rs232SyncPortRTSCTSDelay
                Integer32,
            rs232SyncPortMode
                INTEGER,
            rs232SyncPortIdlePattern
                INTEGER,
            rs232SyncPortMinFlags
                Integer32
        }

   rs232SyncPortIndex OBJECT-TYPE
        SYNTAX InterfaceIndex
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "A unique value for each port.  Its value is the
            same as rs232PortIndex for the port."
        ::= { rs232SyncPortEntry 1 }
```

```
rs232SyncPortClockSource OBJECT-TYPE
    SYNTAX INTEGER { internal(1), external(2), split(3) }
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "Source of the port's bit rate clock. 'split' means
        the tranmit clock is internal and the receive clock
        is external."
    ::= { rs232SyncPortEntry 2 }

rs232SyncPortFrameCheckErrs OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Total number of frames with an invalid frame check
        sequence, input from the port since system
        re-initialization and while the port state was 'up'
        or 'test'."
    ::= { rs232SyncPortEntry 3 }

rs232SyncPortTransmitUnderrunErrs OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Total number of frames that failed to be
        transmitted on the port since system
        re-initialization and while the port state was 'up'
        or 'test' because data was not available to the
        transmitter in time."
    ::= { rs232SyncPortEntry 4 }

rs232SyncPortReceiveOverrunErrs OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Total number of frames that failed to be received
        on the port since system re-initialization and while
        the port state was 'up' or 'test' because the
        receiver did not accept the data in time."
    ::= { rs232SyncPortEntry 5 }

rs232SyncPortInterruptedFrames OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
```

         DESCRIPTION
             "Total number of frames that failed to be received
             or transmitted on the port due to loss of modem
             signals since system re-initialization and while the
             port state was 'up' or 'test'."
         ::= { rs232SyncPortEntry 6 }

     rs232SyncPortAbortedFrames OBJECT-TYPE
         SYNTAX Counter32
         MAX-ACCESS read-only
         STATUS current
         DESCRIPTION
             "Number of frames aborted on the port due to
             receiving an abort sequence since system
             re-initialization and while the port state was 'up'
             or 'test'."
         ::= { rs232SyncPortEntry 7 }

     rs232SyncPortRole OBJECT-TYPE
         SYNTAX INTEGER { dte(1), dce(2) }
         MAX-ACCESS read-write
         STATUS current
         DESCRIPTION
             "The role the device is playing that is using this port.
                 dte   means the device is performing the role of
                         data terminal equipment
                 dce   means the device is performing the role of
                         data circuit-terminating equipment."
         DEFVAL { dce }
         ::= { rs232SyncPortEntry 8 }

     rs232SyncPortEncoding OBJECT-TYPE
         SYNTAX INTEGER { nrz(1), nrzi(2) }
         MAX-ACCESS read-write
         STATUS current
         DESCRIPTION
             "The bit stream encoding technique that is in effect
              for this port.
                 nrz   for Non-Return to Zero encoding
                 nrzi   for Non-Return to Zero Inverted encoding."
         DEFVAL { nrz }
         ::= { rs232SyncPortEntry 9 }

     rs232SyncPortRTSControl OBJECT-TYPE
         SYNTAX INTEGER { controlled(1), constant(2) }
         MAX-ACCESS read-write
         STATUS current
         DESCRIPTION

             "The method used to control the Request To Send (RTS)
              signal.

                  controlled when the DTE is asserts RTS each time
                              data needs to be transmitted and drops
                              RTS at some point after data
                              transmission begins.

                              If rs232SyncPortRole is 'dte', the
                              RTS is an output signal. The device
                              will issue a RTS and wait for a CTS
                              from the DCE before starting to
                              transmit.

                              If rs232SyncPortRole is 'dce', the
                              RTS is an input signal. The device
                              will issue a CTS only after having
                              received RTS and waiting the
                              rs232SyncPortRTSCTSDelay interval.

                  constant   when the DTE constantly asserts RTS."
         DEFVAL { constant }
         ::= { rs232SyncPortEntry 10 }

     rs232SyncPortRTSCTSDelay OBJECT-TYPE
         SYNTAX Integer32
         MAX-ACCESS read-write
         STATUS current
         DESCRIPTION
             "The interval (in milliseconds) that the DCE must wait
              after it sees RTS asserted before asserting CTS. This
              object exists in support of older synchronous devices
              that cannot recognize CTS within a certain interval
              after it asserts RTS."
         DEFVAL { 0 }
         ::= { rs232SyncPortEntry 11 }

     rs232SyncPortMode OBJECT-TYPE
         SYNTAX INTEGER { fdx(1), hdx(2), simplex-receive(3),
                           simplex-send(4) }
         MAX-ACCESS read-write
         STATUS current
         DESCRIPTION
             "The mode of operation of the port with respect to the
              direction and simultaneity of data transfer.

```
            fdx                 when frames on the data link can be
                                transmitted and received at the same
                                time

            hdx                 when frames can either be received
                                from the data link or transmitted
                                onto the data link but not at the
                                same time.

            simplex-receive  when frames can only be received on
                                this data link.

            simplex-send     when frames can only be sent on this
                                data link."
    DEFVAL { fdx }
    ::= { rs232SyncPortEntry 12 }

rs232SyncPortIdlePattern OBJECT-TYPE
    SYNTAX INTEGER  { mark(1), space(2) }
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "The bit pattern used to indicate an idle line."
    DEFVAL { space }
    ::= { rs232SyncPortEntry 13 }

rs232SyncPortMinFlags OBJECT-TYPE
    SYNTAX Integer32
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "The minimum number of flag patterns this port needs in
         order to recognize the end of one frame and the start
         of the next.  Plausible values are 1 and 2."
    DEFVAL { 2 }
    ::= { rs232SyncPortEntry 14 }


-- Input Signal Table

rs232InSigTable OBJECT-TYPE
    SYNTAX SEQUENCE OF Rs232InSigEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "A list of port input control signal entries
        implemented and visible to the software on the port,
        and useful to monitor."
```

```
         ::= { rs232 5 }

   rs232InSigEntry OBJECT-TYPE
       SYNTAX Rs232InSigEntry
       MAX-ACCESS not-accessible
       STATUS current
       DESCRIPTION
           "Input control signal status for a hardware port."
       INDEX { rs232InSigPortIndex, rs232InSigName }
       ::= { rs232InSigTable 1 }

   Rs232InSigEntry ::=
       SEQUENCE {
           rs232InSigPortIndex
               InterfaceIndex,
           rs232InSigName
               INTEGER,
           rs232InSigState
               INTEGER,
           rs232InSigChanges
               Counter32
       }

   rs232InSigPortIndex OBJECT-TYPE
       SYNTAX InterfaceIndex
       MAX-ACCESS read-only
       STATUS current
       DESCRIPTION
           "The value of rs232PortIndex for the port to which
           this entry belongs."
       ::= { rs232InSigEntry 1 }

   rs232InSigName OBJECT-TYPE
       SYNTAX INTEGER { rts(1), cts(2), dsr(3), dtr(4), ri(5),
                   dcd(6), sq(7), srs(8), srts(9),
                   scts(10), sdcd(11) }
       MAX-ACCESS read-only
       STATUS current
       DESCRIPTION
           "Identification of a hardware signal, as follows:

               rts     Request to Send
               cts     Clear to Send
               dsr     Data Set Ready
               dtr     Data Terminal Ready
               ri      Ring Indicator
               dcd     Received Line Signal Detector
               sq      Signal Quality Detector
```

```
                  srs     Data Signaling Rate Selector
                  srts    Secondary Request to Send
                  scts    Secondary Clear to Send
                  sdcd    Secondary Received Line Signal Detector
              "
        REFERENCE
            "EIA Standard RS-232-C, August 1969."
        ::= { rs232InSigEntry 2 }

    rs232InSigState OBJECT-TYPE
        SYNTAX INTEGER { none(1), on(2), off(3) }
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The current signal state."
        ::= { rs232InSigEntry 3 }

    rs232InSigChanges OBJECT-TYPE
        SYNTAX Counter32
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The number of times the signal has changed from
            'on' to 'off' or from 'off' to 'on'."
        ::= { rs232InSigEntry 4 }


    -- Output Signal Table

    rs232OutSigTable OBJECT-TYPE
        SYNTAX SEQUENCE OF Rs232OutSigEntry
        MAX-ACCESS not-accessible
        STATUS current
        DESCRIPTION
            "A list of port output control signal entries
            implemented and visible to the software on the port,
            and useful to monitor."
        ::= { rs232 6 }

    rs232OutSigEntry OBJECT-TYPE
        SYNTAX Rs232OutSigEntry
        MAX-ACCESS not-accessible
        STATUS current
        DESCRIPTION
            "Output control signal status for a hardware port."
        INDEX { rs232OutSigPortIndex, rs232OutSigName }
        ::= { rs232OutSigTable 1 }
```

```
    Rs232OutSigEntry ::=
        SEQUENCE {
            rs232OutSigPortIndex
                InterfaceIndex,
            rs232OutSigName
                INTEGER,
            rs232OutSigState
                INTEGER,
            rs232OutSigChanges
                Counter32
        }

    rs232OutSigPortIndex OBJECT-TYPE
        SYNTAX InterfaceIndex
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The value of rs232PortIndex for the port to which
            this entry belongs."
        ::= { rs232OutSigEntry 1 }

    rs232OutSigName OBJECT-TYPE
        SYNTAX INTEGER { rts(1), cts(2), dsr(3), dtr(4), ri(5),
                         dcd(6), sq(7), srs(8), srts(9),
                         scts(10), sdcd(11) }
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "Identification of a hardware signal, as follows:

                rts     Request to Send
                cts     Clear to Send
                dsr     Data Set Ready
                dtr     Data Terminal Ready
                ri      Ring Indicator
                dcd     Received Line Signal Detector
                sq      Signal Quality Detector
                srs     Data Signaling Rate Selector
                srts    Secondary Request to Send
                scts    Secondary Clear to Send
                sdcd    Secondary Received Line Signal Detector
             "
        REFERENCE
            "EIA Standard RS-232-C, August 1969."
        ::= { rs232OutSigEntry 2 }

    rs232OutSigState OBJECT-TYPE
        SYNTAX INTEGER { none(1), on(2), off(3) }
```

```
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The current signal state."
        ::= { rs232OutSigEntry 3 }

    rs232OutSigChanges OBJECT-TYPE
        SYNTAX Counter32
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The number of times the signal has changed from
            'on' to 'off' or from 'off' to 'on'."
        ::= { rs232OutSigEntry 4 }


    -- conformance information

    rs232Conformance OBJECT IDENTIFIER ::= { rs232 7 }

    rs232Groups      OBJECT IDENTIFIER ::= { rs232Conformance 1 }
    rs232Compliances OBJECT IDENTIFIER ::= { rs232Conformance 2 }


    -- compliance statements

    rs232Compliance MODULE-COMPLIANCE
        STATUS   current
        DESCRIPTION
                "The compliance statement for SNMPv2 entities
                which have RS-232-like hardware interfaces."

        MODULE   -- this module
            MANDATORY-GROUPS { rs232Group }

            GROUP   rs232AsyncGroup
            DESCRIPTION
                "The Asynch group is mandatory only for those
                 SNMPv2 entities which have asynchronous
                 interfaces Rs-232-like."

            GROUP   rs232SyncGroup
            DESCRIPTION
                "The Synch group is mandatory only for those
                 SNMPv2 entities which have synchronous
                 interfaces Rs-232-like."
        ::= { rs232Compliances 1 }
```

```
    -- units of conformance

    rs232Group      OBJECT-GROUP
        OBJECTS { rs232Number, rs232PortIndex, rs232PortType,
                  rs232PortInSigNumber, rs232PortOutSigNumber,
                  rs232PortInSpeed, rs232PortOutSpeed,
                  rs232PortInFlowType, rs232PortOutFlowType,
                  rs232InSigPortIndex, rs232InSigName,
                  rs232InSigState, rs232InSigChanges,
                  rs232OutSigPortIndex, rs232OutSigName,
                  rs232OutSigState, rs232OutSigChanges }
        STATUS  current
        DESCRIPTION
                "A collection of objects providing information
                 applicable to all RS-232-like interfaces."
        ::= { rs232Groups 1 }

    rs232AsyncGroup OBJECT-GROUP
        OBJECTS { rs232AsyncPortIndex, rs232AsyncPortBits,
                  rs232AsyncPortStopBits, rs232AsyncPortParity,
                  rs232AsyncPortAutobaud, rs232AsyncPortParityErrs,
                  rs232AsyncPortFramingErrs, rs232AsyncPortOverrunErrs }
        STATUS  current
        DESCRIPTION
                "A collection of objects providing information
                 applicable to asynchronous RS-232-like interfaces."
        ::= { rs232Groups 2 }

    rs232SyncGroup OBJECT-GROUP
        OBJECTS { rs232SyncPortIndex, rs232SyncPortClockSource,
                  rs232SyncPortFrameCheckErrs,
                  rs232SyncPortTransmitUnderrunErrs,
                  rs232SyncPortReceiveOverrunErrs,
                  rs232SyncPortInterruptedFrames,
                  rs232SyncPortAbortedFrames }
        STATUS  current
        DESCRIPTION
                "A collection of objects providing information
                 applicable to synchronous RS-232-like interfaces."
        ::= { rs232Groups 3 }

    rs232SyncSDLCGroup OBJECT-GROUP
        OBJECTS { rs232SyncPortRole,
                  rs232SyncPortEncoding,
                  rs232SyncPortRTSControl,
                  rs232SyncPortRTSCTSDelay,
                  rs232SyncPortMode,
                  rs232SyncPortIdlePattern,
```

                    rs232SyncPortMinFlags }
        STATUS   current
        DESCRIPTION
                "A collection of objects providing information
                 applicable to synchronous RS-232-like interfaces
                 running SDLC."
        ::= { rs232Groups 4 }

    END

5. Acknowledgements

    This memo was produced by the IETF Character MIB Working Group.

6. References

    [1] Case, J., McCloghrie, K., Rose, M., and S. Waldbusser, "Structure
        of Management Information for version 2 of the Simple Network
        Management Protocol (SNMPv2)", RFC 1442, SNMP Research,Inc.,
        Hughes LAN Systems, Dover Beach Consulting, Inc., Carnegie Mellon
        University, April 1993.

    [2] McCloghrie, K., and M. Rose, Editors, "Management Information
        Base for Network Management of TCP/IP-based internets: MIB-II",
        STD 17, RFC 1213, Hughes LAN Systems, Performance Systems
        International, March 1991.

    [3] Galvin, J., and K. McCloghrie, "Administrative Model for version
        2 of the Simple Network Management Protocol (SNMPv2)", RFC 1445,
        Trusted Information Systems, Hughes LAN Systems, April 1993.

    [4] Case, J., McCloghrie, K., Rose, M., and S. Waldbusser, "Protocol
        Operations for version 2 of the Simple Network Management
        Protocol (SNMPv2)", RFC 1448, SNMP Research,Inc., Hughes LAN
        Systems, Dover Beach Consulting, Inc., Carnegie Mellon
        University, April 1993.

    [5] McCloghrie, K., and F. Kastenholz, "Evolution of the Interfaces
        Group of MIB-II", RFC 1573, Hughes LAN Systems, FTP Software,
        January 1994.

    [6] Stewart, B., "Definitions of Managed Objects for Character Stream
        Devices using SMIv2", RFC 1658, Xyplex, Inc., July 1994.

    [7] Kastenholz, F., "The Definitions of Managed Objects for the Link
        Control Protocol of the Point-to-Point Protocol", RFC 1471, FTP
        Software, Inc., June 1993.

7. Security Considerations

Security issues are not discussed in this memo.

8. Author's Address

Bob Stewart
Xyplex, Inc.
295 Foster Street
Littleton, MA 01460

Phone: 508-952-4816
Fax: 508-952-4887
EMail: rlstewart@eng.xyplex.com