                Routing and Wavelength Assignment Information Model
                      for Wavelength Switched Optical Networks

Abstract

   This document provides a model of information needed by the Routing
   and Wavelength Assignment (RWA) process in Wavelength Switched
   Optical Networks (WSONs). The purpose of the information described
   in this model is to facilitate constrained optical path computation
   in WSONs. This model takes into account compatibility constraints
   between WSON signal attributes and network elements but does not
   include constraints due to optical impairments. Aspects of this
   information that may be of use to other technologies utilizing a
   GMPLS control plane are discussed.

Copyright Notice

Table of Contents

1. Introduction

The purpose of the WSON information model described in this document is to facilitate constrained optical path computation, and as such it is not a general-purpose network management information model. This constraint is frequently referred to as the "wavelength continuity" constraint, and the corresponding constrained optical path computation is known as the Routing and Wavelength Assignment (RWA) problem. Hence, the information model must provide sufficient topology and wavelength restriction and availability information to support this computation. More details on the RWA process and WSON subsystems and their properties can be found in [RFC6163]. The model defined here includes constraints between WSON signal attributes and network elements but does not include optical impairments.

In addition to presenting an information model suitable for path computation in WSON, this document also highlights model aspects that may have general applicability to other technologies utilizing a GMPLS control plane. The portion of the information model applicable to technologies beyond WSON is referred to as "general" to distinguish it from the "WSON-specific" portion that is applicable only to WSON technology.

2. Terminology

Refer to [RFC6163] for definitions of Reconfigurable Optical Add/Drop Multiplexer (ROADM), RWA, Wavelength Conversion, Wavelength Division Multiplexing (WDM), WSON, and other related terminology used in this document.

3. Routing and Wavelength Assignment Information Model

The WSON RWA information model in this document comprises four categories of information. The categories are independent of whether the information comes from a switching subsystem or from a line subsystem -- a switching subsystem refers to WSON nodes such as a ROADM or an Optical Add/Drop Multiplexer (OADM), and a line subsystem refers to devices such as WDM or Optical Amplifier. The categories are these:

o Node Information

o Link Information

o Dynamic Node Information

o Dynamic Link Information

Note that this is roughly the categorization used in Section 7 of
[G.7715].

In the following, where applicable, the Reduced Backus-Naur Form
(RBNF) syntax of [RBNF] is used to aid in defining the RWA
information model.

3.1. Dynamic and Relatively Static Information

All the RWA information of concern in a WSON network is subject to
change over time. Equipment can be upgraded; links may be placed in
or out of service and the like. However, from the point of view of
RWA computations, there is a difference between information that can
change with each successive connection establishment in the network
and information that is relatively static and independent of
connection establishment. A key example of the former is link
wavelength usage since this can change with connection setup/teardown
and this information is a key input to the RWA process. Examples of
relatively static information are the potential port connectivity of
a WDM ROADM, and the channel spacing on a WDM link.

This document separates, where possible, dynamic and static
information so that these can be kept separate in possible encodings.
This allows for separate updates of these two types of information,
thereby reducing processing and traffic load caused by the timely
distribution of the more dynamic RWA WSON information.

4. Node Information (General)

The node information described here contains the relatively static
information related to a WSON node. This includes connectivity
constraints amongst ports and wavelengths since WSON switches can
exhibit asymmetric switching properties. Additional information
could include properties of wavelength converters in the node, if any
are present. In [Switch] it was shown that the wavelength
connectivity constraints for a large class of practical WSON devices
can be modeled via switched and fixed connectivity matrices along
with corresponding switched and fixed port constraints. These
connectivity matrices are included with the node information, while
the switched and fixed port wavelength constraints are included with
the link information.

Formally,

<Node_Information> ::= <Node_ID> [<ConnectivityMatrix>...]

Where the Node_ID would be an appropriate identifier for the node
within the WSON RWA context.

Note that multiple connectivity matrices are allowed and hence can
fully support the most-general cases enumerated in [Switch].

4.1. Connectivity Matrix

The connectivity matrix (ConnectivityMatrix) represents either the
potential connectivity matrix for asymmetric switches (e.g., ROADMs
and such) or fixed connectivity for an asymmetric device such as a
multiplexer. Note that this matrix does not represent any particular
internal blocking behavior but indicates which input ports and
wavelengths could possibly be connected to a particular output port.
For a switch or ROADM, representing blocking that is dependent on the
internal state is beyond the scope of this document. Due to its
highly implementation-dependent nature, it would most likely not be
subject to standardization in the future. The connectivity matrix is
a conceptual M by N matrix representing the potential switched or
fixed connectivity, where M represents the number of input ports and
N the number of output ports. This is a "conceptual" matrix since
the matrix tends to exhibit structure that allows for very compact
representations that are useful for both transmission and path
computation.

Note that the connectivity matrix information element can be useful
in any technology context where asymmetric switches are utilized.

<ConnectivityMatrix> ::= <MatrixID>

                         <ConnType>

                         <Matrix>

Where

<MatrixID> is a unique identifier for the matrix.

<ConnType> can be either 0 or 1 depending upon whether the
connectivity is either fixed or switched.

<Matrix> represents the fixed or switched connectivity in that
Matrix(i, j) = 0 or 1 depending on whether input port i can connect
to output port j for one or more wavelengths.

5. Node Information (WSON Specific)

As discussed in [RFC6163], a WSON node may contain electro-optical
subsystems such as regenerators, wavelength converters or entire
switching subsystems. The model present here can be used in
characterizing the accessibility and availability of limited

   resources such as regenerators or wavelength converters as well as
   WSON signal attribute constraints of electro-optical subsystems. As
   such, this information element is fairly specific to WSON
   technologies.

   In this document, the term "resource" is used to refer to a physical
   component of a WSON node such as a regenerator or a wavelength
   converter. Multiple instances of such components are often present
   within a single WSON node. This term is not to be confused with the
   concept of forwarding or switching resources such as bandwidth or
   lambdas.

   A WSON node may include regenerators or wavelength converters
   arranged in a shared pool. As discussed in [RFC6163], a WSON node
   can also include WDM switches that use optical-electronic-optical
   (OEO) processing. There are a number of different approaches used in
   the design of WDM switches containing regenerator or converter pools.
   However, from the point of view of path computation, the following
   need to be known:

   1. The nodes that support regeneration or wavelength conversion.

   2. The accessibility and availability of a wavelength converter to
       convert from a given input wavelength on a particular input port
       to a desired output wavelength on a particular output port.

   3. Limitations on the types of signals that can be converted and the
       conversions that can be performed.

   Since resources tend to be packaged together in blocks of similar
   devices, e.g., on line cards or other types of modules, the
   fundamental unit of identifiable resource in this document is the
   "resource block".

   A resource block is a collection of resources from the same WSON node
   that are grouped together for administrative reasons and for ease of
   encoding in the protocols. All resources in the same resource block
   behave in the same way and have similar characteristics relevant to
   the optical system, e.g., processing properties, accessibility, etc.

   A resource pool is a collection of resource blocks for the purpose of
   representing throughput or cross-connect capabilities in a WSON node.
   A resource pool associates input ports or links on the node with
   output ports or links and is used to indicate how signals may be
   passed from an input port or link to an output port or link by way of
   a resource block (in other words, by way of a resource). A resource
   pool may, therefore, be modeled as a matrix.

A resource block may be present in multiple resource pools.

This leads to the following formal high-level model:

<Node_Information> ::= <Node_ID>

                        [<ConnectivityMatrix>...]

                        [<ResourcePool>]

Where

<ResourcePool> ::= <ResourceBlockInfo>...

                    [<ResourceAccessibility>...]

                    [<ResourceWaveConstraints>...]

                    [<RBPoolState>]

First, the accessibility of resource blocks is addressed; then, their
properties are discussed.

5.1. Resource Accessibility/Availability

A similar technique as used to model ROADMs, and optical switches can
be used to model regenerator/converter accessibility. This technique
was generally discussed in [RFC6163] and consisted of a matrix to
indicate possible connectivity along with wavelength constraints for
links/ports. Since regenerators or wavelength converters may be
considered a scarce resource, it is desirable that the model include,
if desired, the usage state (availability) of individual regenerators
or converters in the pool. Models that incorporate more state to
further reveal blocking conditions on input or output to particular
converters are for further study and not included here.

The three-stage model is shown schematically in Figures 1 and 2. The
difference between the two figures is that in Figure 1 it's assumed
that each signal that can get to a resource block may do so, while in
Figure 2 the access to sets of resource blocks is via a shared fiber
that imposes its own wavelength collision constraint. Figure 1 shows
that there can be more than one input to each resource block since
each input represents a single wavelength signal, while Figure 2
shows a single WDM input or output, e.g., a fiber, to/from each set
of blocks.

This model assumes N input ports (fibers), P resource blocks
containing one or more identical resources (e.g., wavelength
converters), and M output ports (fibers). Since not all input ports
can necessarily reach each resource block, the model starts with a
resource pool input matrix RI(i,p) = {0,1} depending on whether input
port i can potentially reach resource block p.

Since not all wavelengths can necessarily reach all the resources or
the resources may have limited input wavelength range, the model has
a set of relatively static input port constraints for each resource.
In addition, if the access to a set of resource blocks is via a
shared fiber (Figure 2), this would impose a dynamic wavelength
availability constraint on that shared fiber. The resource block
input port constraint is modeled via a static wavelength set
mechanism, and the case of shared access to a set of blocks is
modeled via a dynamic wavelength set mechanism.

Next, a state vector RA(j) = {0,...,k} is used to track the number of
resources in resource block j in use. This is the only state kept in
the resource pool model. This state is not necessary for modeling
"fixed" transponder system or full OEO switches with WDM interfaces,
i.e., systems where there is no sharing.

After that, a set of static resource output wavelength constraints
and possibly dynamic shared output fiber constraints maybe used. The
static constraints indicate what wavelengths a particular resource
block can generate or is restricted to generating, e.g., a fixed
regenerator would be limited to a single lambda. The dynamic
constraints would be used in the case where a single shared fiber is
used to output the resource block (Figure 2).

Finally, to complete the model, a resource pool output matrix RE(p,k)
= {0,1} depending on whether the output from resource block p can
reach output port k, may be used.

```
 I1   +------------+              +------------+ O1
----->|            |    +--------+ |            | ----->
 I2   |            +------+ Rb #1 +--------+    | O2
----->|            |    +--------+ |            | ----->
      |            |                          |
      | Resource   |    +--------+ | Resource   |
      | Pool       +------+        +------+ Pool       |
      |            |    + Rb #2 +        |            |
      | Input      +------+        +------- Output      |
      | Connection |    +--------+ | Connection |
      | Matrix     |         .      | Matrix     |
      |            |         .      |            |
      |            |         .      |            |
 IN   |            |    +--------+ |            | OM
----->|            +------+ Rb #P +-------+    | ----->
      |            |    +--------+ |            |
      +------------+    ^          ^ +------------+
                        |          |
                        |          |
                        |          |
                 Input wavelength  Output wavelength
                 constraints for   constraints for
                 each resource     each resource
```

   Note: Rb is a resource block.

        Figure 1: Schematic Diagram of the Resource Pool Model

```
    I1   +-------------+                          +-------------+ O1
   ----->|             |        +---------+       |             | ----->
    I2   |             +=======+  Rb #1  +-+      |             | O2
   ----->|             |        +---------+ |     |             | ----->
         |             |                    | ===== |           |
         | Resource    |        +---------+ |     | Resource    |
         | Pool        |     +-+  Rb #2  +-+|      | Pool        |
         |             |     | |+---------+        |             |
         | Input       | ==== |                    | Output      |
         | Connection  |     | |+---------+        | Connection  |
         | Matrix      |     +-|  Rb #3  |=======+ | Matrix      |
         |             |        +---------+       |             |
         |             |             .            |             |
         |             |             .            |             |
         |             |             .            |             |
    IN   |             |        +---------+       |             | OM
   ----->|             +=======+  Rb #P  +=======+|             | ----->
         |             |        +---------+       |             |
         +-------------+         ^          ^     +-------------+
                                 |          |
                                 |          |
              Single (shared) fibers for block input and output

                  Input wavelength        Output wavelength
                  availability for        availability for
                  each block input fiber  each block output fiber
```

   Note: Rb is a resource block.

    Figure 2: Schematic Diagram of the Resource Pool Model with
                   Shared Block Accessibility

   Formally, the model can be specified as:

   <ResourceAccessibility> ::= <PoolInputMatrix>

                              <PoolOutputMatrix>

   <ResourceWaveConstraints> ::= <InputWaveConstraints>

                                <OutputWaveConstraints>

   <RBSharedAccessWaveAvailability> ::= [<InAvailableWavelengths>]

                                      [<OutAvailableWavelengths>]

```
<RBPoolState> ::=      <ResourceBlockID>

                       <NumResourcesInUse>

                       [<RBSharedAccessWaveAvailability>]

                       [<RBPoolState>]
```

   Note that, except for <RBPoolState>, all the components of
   <ResourcePool> are relatively static. Also, the
   <InAvailableWavelengths> and <OutAvailableWavelengths> are only used
   in the cases of shared input or output access to the particular
   block. See the resource block information in the next section for
   how this is specified.

5.2. Resource Signal Constraints and Processing Capabilities

   The wavelength conversion abilities of a resource (e.g., regenerator,
   wavelength converter) were modeled in the <OutputWaveConstraints>
   previously discussed. As discussed in [RFC6163], the constraints on
   an electro-optical resource can be modeled in terms of input
   constraints, processing capabilities, and output constraints:

```
<ResourceBlockInfo> ::= <ResourceBlockSet>

                        [<InputConstraints>]

                        [<ProcessingCapabilities>]

                        [<OutputConstraints>]
```

   Where <ResourceBlockSet> is a list of resource block identifiers
   with the same characteristics. If this set is missing, the
   constraints are applied to the entire network element.

   The <InputConstraints> are constraints are based on signal
   compatibility and/or shared access constraint indication. The
   details of these constraints are defined in Section 5.3.

```
<InputConstraints> ::= <SharedInput>

                       [<OpticalInterfaceClassList>]

                       [<ClientSignalList>]
```

   The <ProcessingCapabilities> are important operations that the
   resource (or network element) can perform on the signal. The details
   of these capabilities are defined in Section 5.3.

```
<ProcessingCapabilities> ::= [<NumResources>]

                             [<RegenerationCapabilities>]

                             [<FaultPerfMon>]

                             [<VendorSpecific>]
```

The <OutputConstraints> are either restrictions on the properties of
the signal leaving the block, options concerning the signal
properties when leaving the resource, or shared fiber output
constraint indication.

```
<OutputConstraints> := <SharedOutput>

                       [<OpticalInterfaceClassList>]

                       [<ClientSignalList>]
```

5.3. Compatibility and Capability Details

5.3.1. Shared Input or Output Indication

As discussed in Section 5.2 and shown in Figure 2, the input or
output access to a resource block may be via a shared fiber. The
<SharedInput> and <SharedOutput> elements are indicators for this
condition with respect to the block being described.

5.3.2. Optical Interface Class List

```
<OpticalInterfaceClassList> ::= <OpticalInterfaceClass> ...
```

The Optical Interface Class is a unique number that identifies all
information related to optical characteristics of a physical
interface. The class may include other optical parameters related to
other interface properties. A class always includes signal
compatibility information.

The content of each class is out of the scope of this document and
can be defined by other entities (e.g., the ITU, optical equipment
vendors, etc.).

Since even current implementation of physical interfaces may support
different optical characteristics, a single interface may support
multiple interface classes. Which optical interface class is used
among all the ones available for an interface is out of the scope of
this document but is an output of the RWA process.

5.3.3. Acceptable Client Signal List

The list is simply:

<ClientSignalList>::=[<G-PID>]...

Where the Generalized Protocol Identifiers (G-PID) object represents one of the IETF-standardized G-PID values as defined in [RFC3471] and [RFC4328].

5.3.4. Processing Capability List

The ProcessingCapabilities are defined in Section 5.2.

The processing capability list sub-TLV is a list of processing functions that the WSON network element (NE) can perform on the signal including:

1. number of resources within the block

2. regeneration capability

3. fault and performance monitoring

4. vendor-specific capability

Note that the code points for fault and performance monitoring and vendor-specific capability are subject to further study.

6. Link Information (General)

MPLS-TE routing protocol extensions for OSPF [RFC3630] and IS-IS [RFC5305], along with GMPLS routing protocol extensions for OSPF [RFC4203] and IS-IS [RFC5307] provide the bulk of the relatively static link information needed by the RWA process. However, WSONs bring in additional link-related constraints. These stem from characterizing WDM line systems, restricting laser transmitter tuning, and switching subsystem port wavelength constraints, e.g., "colored" ROADM drop ports.

The following syntax summarizes both information from existing GMPLS routing protocols and new information that may be needed by the RWA process.

```
<LinkInfo> ::=  <LinkID>

                [<AdministrativeGroup>]

                [<InterfaceCapDesc>]

                [<Protection>]

                [<SRLG>...]

                [<TrafficEngineeringMetric>]

                [<PortLabelRestriction>...]
```

Note that these additional link characteristics only apply to line-side ports of a WDM system or add/drop ports pertaining to the resource pool (e.g., regenerator or wavelength converter pool). The advertisement of input/output tributary ports is not intended here.

6.1. Administrative Group

Administrative Group: Defined in [RFC3630] and extended for MPLS-TE [RFC7308]. Each set bit corresponds to one administrative group assigned to the interface. A link may belong to multiple groups. This is a configured quantity and can be used to influence routing decisions.

6.2. Interface Switching Capability Descriptor

InterfaceSwCapDesc: Defined in [RFC4202]; lets us know the different switching capabilities on this GMPLS interface. In both [RFC4203] and [RFC5307], this information gets combined with the maximum Link State Protocol Data Unit (LSP) bandwidth that can be used on this link at eight different priority levels.

6.3. Link Protection Type (for This Link)

Protection: Defined in [RFC4202] and implemented in [RFC4203] and [RFC5307]. Used to indicate what protection, if any, is guarding this link.

6.4. Shared Risk Link Group Information

SRLG: Defined in [RFC4202] and implemented in [RFC4203] and [RFC5307]. This allows for the grouping of links into shared risk groups, i.e., those links that are likely, for some reason, to fail at the same time.

6.5. Traffic Engineering Metric

   TrafficEngineeringMetric: Defined in [RFC3630] and [RFC5305]. This
   allows for the identification of a data-channel link metric value for
   traffic engineering that is separate from the metric used for path
   cost computation of the control plane.

   Note that multiple "link metric values" could find use in optical
   networks; however, it would be more useful to the RWA process to
   assign these specific meanings such as "link mile" metric,
   "probability of failure" metric, etc.

6.6. Port Label Restrictions

   Port label restrictions could be applied generally to any label types
   in GMPLS by adding new kinds of restrictions. Wavelength is a type
   of label.

   Port label (wavelength) restrictions (PortLabelRestriction) model the
   label (wavelength) restrictions that the link and various optical
   devices, such as Optical Cross-Connects (OXCs), ROADMs, and waveband
   multiplexers, may impose on a port. These restrictions tell us what
   wavelength may or may not be used on a link and are relatively
   static. This plays an important role in fully characterizing a WSON
   switching device [Switch]. Port wavelength restrictions are
   specified relative to the port in general or to a specific
   connectivity matrix (Section 4.1). [Switch] gives an example where
   both switch and fixed connectivity matrices are used and both types
   of constraints occur on the same port.

   <PortLabelRestriction> ::= <MatrixID>

                         <RestrictionType>

                         <Restriction parameters list>

   <Restriction parameters list> ::=

                         <Simple label restriction parameters> |

                         <Channel count restriction parameters> |

                         <Label range restriction parameters> |

                         <Simple+channel restriction parameters> |

                         <Exclusive label restriction parameters>

   <Simple label restriction parameters> ::= <LabelSet> ...

   <Channel count restriction parameters> ::= <MaxNumChannels>

   <Label range restriction parameters> ::= <MaxLabelRange>

                                            (<LabelSet> ...)

   <Simple+channel restriction parameters> ::= <MaxNumChannels>

                                               (<LabelSet> ...)

   <Exclusive label restriction parameters> ::= <LabelSet> ...

   Where

   MatrixID is the ID of the corresponding connectivity matrix (Section
   4.1).

   The RestrictionType parameter is used to specify general port
   restrictions and matrix-specific restrictions. It can take the
   following values and meanings:

      SIMPLE_LABEL: Simple label (wavelength) set restriction; the
         LabelSet parameter is required.

      CHANNEL_COUNT: The number of channels is restricted to be less
         than or equal to the MaxNumChannels parameter (which is
         required).

      LABEL_RANGE: Used to indicate a restriction on a range of labels
         that can be switched. For example, a waveband device with a
         tunable center frequency and passband. This constraint is
         characterized by the MaxLabelRange parameter, which indicates
         the maximum range of the labels, e.g., which may represent a
         waveband in terms of channels. Note that an additional
         parameter can be used to indicate the overall tuning range.
         Specific center frequency tuning information can be obtained
         from information about the dynamic channel in use. It is
         assumed that both center frequency and bandwidth (Q) tuning can
         be done without causing faults in existing signals.

SIMPLE LABEL and CHANNEL COUNT: In this case, the accompanying
   label set and MaxNumChannels indicate labels permitted on the
   port and the maximum number of labels that can be
   simultaneously used on the port.

LINK LABEL_EXCLUSIVITY: A label (wavelength) can be used at most
   once among a given set of ports. The set of ports is specified
   as a parameter to this constraint.

Restriction-specific parameters are used with one or more of the
previously listed restriction types. The currently defined
parameters are:

LabelSet is a conceptual set of labels (wavelengths).

MaxNumChannels is the maximum number of channels that can be
   simultaneously used (relative to either a port or a matrix).

LinkSet is a conceptual set of ports.

MaxLabelRange indicates the maximum range of the labels. For
example, if the port is a "colored" drop port of a ROADM, then there
are two restrictions: (a) CHANNEL_COUNT, with MaxNumChannels = 1, and
(b) SIMPLE_WAVELENGTH, with the wavelength set consisting of a single
member corresponding to the frequency of the permitted wavelength.
See [Switch] for a complete waveband example.

This information model for port wavelength (label) restrictions is
fairly general in that it can be applied to ports that have label
restrictions only or to ports that are part of an asymmetric switch
and have label restrictions. In addition, the types of label
restrictions that can be supported are extensible.

6.6.1. Port-Wavelength Exclusivity Example

Although there can be many different ROADM or switch architectures
that can lead to the constraint where a lambda (label) maybe used at
most once on a set of ports, Figure 3 shows a ROADM architecture
based on components known as Wavelength Selective Switches (WSSes)
[OFC08]. This ROADM is composed of splitters, combiners, and WSSes.
This ROADM has 11 output ports, which are numbered in the diagram.
Output ports 1-8 are known as drop ports and are intended to support
a single wavelength. Drop ports 1-4 output from WSS 2, which is fed
from WSS 1 via a single fiber. Due to this internal structure, a
constraint is placed on the output ports 1-4 that a lambda can be
used only once over the group of ports (assuming unicast and not
multicast operation). The output ports 5-8 have a similar constraint
due to the internal structure.

```
                            |            A
                            v        10  |
                        +-------+       +-------+
                        | Split |       |WSS  6 |
                        +-------+       +-------+
        +-----+          |  |  |          |  | |
        |  W  |          |  |  |          | +--------+   +-----+
        |  S  |----------------+          |  +----+  |   |  S  |
      9 |  S  |------------------   ---    ------   ----  |---  |  p  |
     -- |     |------------------   ---    --------    ----  |---|  l  |
        |  5  |----------------+    +------   ----------  |--  |  i  | <
        +-----+          +---------+    +--- - ----    -- ----  |  t  |
        +-----+          +---------+-+  +---- - --- --------- ----+  +-----+
        |  S  |          |       | |+------ - --- ------ ----+  +-----+
      ->|  p  |-----   --------- ----------+          |  |          +-----+
        |  l  |-----    ---------   --- ---- ------ ---- -- --  |  W  |
        |  i  |-----    +------+    +-------------+          | +-- --  |  S  | 11
        |  t  |-----+                                          |  S  | ->
        +-----+   +-+                                 +---- --  |  7  |
            |    +-- --- --------- --------- - - ---+  +-----+
            |    |   +-- - --------+ |
         +-------+ +-------+     +-------+     +-------+
         | WSS 1|  | Split|     | WSS 3|     | Split|
         +--+---+  +--+---+     +--+---+     +--+---+
            |         A            |            A
            v         |            v            |
         +-------+  +--+----+     +-------+     +--+----+
         | WSS 2 |  | Comb. |     | WSS 4 |     | Comb. |
         +-------+  +-------+     +-------+     +-------+
         1|2|3|4|    A A A A      5|6|7|8|      A A A A
          v v v v    | | | |       v v v v      | | | |
```

Figure 3: A ROADM Composed from Splitter, Combiners, and WSSes

7. Dynamic Components of the Information Model

In the previously presented information model, there are a limited
number of information elements that are dynamic, i.e., subject to
change with subsequent establishment and teardown of connections.
Depending on the protocol used to convey this overall information
model, it may be possible to send this dynamic information separately
from the relatively larger amount of static information needed to
characterize WSONs and their network elements.

7.1. Dynamic Link Information (General)

   For WSON links, the wavelength availability and which wavelengths are
   in use for shared backup purposes can be considered dynamic
   information and hence are grouped with the dynamic information in the
   following set:

   <DynamicLinkInfo> ::= <LinkID>

                          <AvailableLabels>

                          [<SharedBackupLabels>]

   AvailableLabels is a set of labels (wavelengths) currently available
   on the link. Given this information and the port wavelength
   restrictions, one can also determine which wavelengths are currently
   in use. This parameter could potentially be used with other
   technologies that GMPLS currently covers or may cover in the future.

   SharedBackupLabels is a set of labels (wavelengths) currently used
   for shared backup protection on the link. An example usage of this
   information in a WSON setting is given in [Shared]. This parameter
   could potentially be used with other technologies that GMPLS
   currently covers or may cover in the future.

   Note that the above does not dictate a particular encoding or
   placement for available label information. In some routing
   protocols, it may be advantageous or required to place this
   information within another information element such as the Interface
   Switching Capability Descriptor (ISCD). Consult the extensions that
   are specific to each routing protocol for details of placement of
   information elements.

7.2. Dynamic Node Information (WSON Specific)

   Currently the only node information that can be considered dynamic is
   the resource pool state, and it can be isolated into a dynamic node
   information element as follows:

   <DynamicNodeInfo> ::= <NodeID> [<ResourcePool>]

8. Security Considerations

   This document discusses an information model for RWA computation in
   WSONs. From a security standpoint, such a model is very similar to
   the information that can be currently conveyed via GMPLS routing
   protocols. Such information includes network topology, link state
   and current utilization, as well as the capabilities of switches and

routers within the network. As such, this information should be
protected from disclosure to unintended recipients. In addition, the
intentional modification of this information can significantly affect
network operations, particularly due to the large capacity of the
optical infrastructure to be controlled. A general discussion on
security in GMPLS networks can be found in [RFC5920].

9. References

9.1. Normative References

   [G.7715]   ITU-T, "Architecture and requirements for routing in the
              automatically switched optical networks", ITU-T
              Recommendation G.7715, June 2002.

   [RBNF]   Farrel, A., "Routing Backus-Naur Form (RBNF): A Syntax Used
              to Form Encoding Rules in Various Routing Protocol
              Specifications", RFC 5511, April 2009,
              <http://www.rfc-editor.org/info/rfc5511>.

   [RFC3471] Berger, L., Ed., "Generalized Multi-Protocol Label
              Switching (GMPLS) Signaling Functional Description", RFC
              3471, January 2003,
              <http://www.rfc-editor.org/info/rfc3471>.

   [RFC3630] van der Meer, J., Mackie, D., Swaminathan, V., Singer, D.,
              and P. Gentric, "RTP Payload Format for Transport of MPEG-4
              Elementary Streams", RFC 3640, November 2003,
              <http://www.rfc-editor.org/info/rfc3640>.

   [RFC4202] Kompella, K., Ed., and Y. Rekhter, Ed., "Routing Extensions
              in Support of Generalized Multi-Protocol Label Switching
              (GMPLS)", RFC 4202, October 2005,
              <http://www.rfc-editor.org/info/rfc4202>.

   [RFC4203] Kompella, K., Ed., and Y. Rekhter, Ed., "OSPF Extensions in
              Support of Generalized Multi-Protocol Label Switching
              (GMPLS)", RFC 4203, October 2005,
              <http://www.rfc-editor.org/info/rfc4203>.

   [RFC4328] Papadimitriou, D., Ed., "Generalized Multi-Protocol Label
              Switching (GMPLS) Signaling Extensions for G.709 Optical
              Transport Networks Control", RFC 4328, January 2006,
              <http://www.rfc-editor.org/info/rfc4328>.

   [RFC5305] Li, T. and H. Smit, "IS-IS Extensions for Traffic
              Engineering", RFC 5305, October 2008,
              <http://www.rfc-editor.org/info/rfc5305>.

   [RFC5307] Kompella, K., Ed., and Y. Rekhter, Ed., "IS-IS Extensions
              in Support of Generalized Multi-Protocol Label Switching
              (GMPLS)", RFC 5307, October 2008,
              <http://www.rfc-editor.org/info/rfc5307>.

   [RFC6163] Lee, Y., Ed., Bernstein, G., Ed., and W. Imajuku,
              "Framework for GMPLS and Path Computation Element (PCE)
              Control of Wavelength Switched Optical Networks (WSONs)",
              RFC 6163, April 2011,
              <http://www.rfc-editor.org/info/rfc6163>.

   [RFC7308] Osborne, E., "Extended Administrative Groups in MPLS
              Traffic Engineering (MPLS-TE)", RFC 7308, July 2014,
              <http://www.rfc-editor.org/info/rfc7308>.

9.2. Informative References

   [OFC08]   Roorda, P., and B. Collings, "Evolution to Colorless and
              Directionless ROADM Architectures", Optical Fiber
              Communication / National Fiber Optic Engineers Conference
              (OFC/NFOEC), 2008, pp. 1-3.

   [RFC5920] Fang, L., Ed., "Security Framework for MPLS and GMPLS
              Networks", RFC 5920, July 2010,
              <http://www.rfc-editor.org/info/rfc5920>.

   [Shared]   Bernstein, G., and Y. Lee, "Shared Backup Mesh Protection
              in PCE-based WSON Networks", iPOP 2008.

   [Switch]   Bernstein, G., Lee, Y., Gavler, A., and J. Martensson,
              "Modeling WDM Wavelength Switching Systems for Use in GMPLS
              and Automated Path Computation", Journal of Optical
              Communications and Networking, vol. 1, June 2009, pp.
              187-195.

Contributors

   Diego Caviglia
   Ericsson
   Via A. Negrone 1/A 16153
   Genoa, Italy

   Phone: +39 010 600 3736
   EMail: diego.caviglia@(marconi.com, ericsson.com)

   Anders Gavler
   Acreo AB
   Electrum 236
   SE - 164 40 Kista
   Sweden

   EMail: Anders.Gavler@acreo.se

   Jonas Martensson
   Acreo AB
   Electrum 236
   SE - 164 40 Kista
   Sweden

   EMail: Jonas.Martensson@acreo.se

   Itaru Nishioka
   NEC Corp.
   1753 Simonumabe, Nakahara-ku, Kawasaki, Kanagawa 211-8666
   Japan

   Phone: +81 44 396 3287
   EMail: i-nishioka@cb.jp.nec.com

   Lyndon Ong
   Ciena
   EMail: lyong@ciena.com

   Cyril Margaria
   EMail: cyril.margaria@gmail.com

Authors' Addresses

    Young Lee (editor)
    Huawei Technologies
    5369 Legacy Drive, Building 3
    Plano, TX   75023
    United States

    Phone: (469) 277-5838
    EMail: leeyoung@huawei.com

    Greg M. Bernstein (editor)
    Grotto Networking
    Fremont, CA
    United States

    Phone: (510) 573-2237
    EMail: gregb@grotto-networking.com

    Dan Li
    Huawei Technologies Co., Ltd.
    F3-5-B R&D Center, Huawei Base,
    Bantian, Longgang District
    Shenzhen 518129
    China

    Phone: +86-755-28973237
    EMail: danli@huawei.com

    Wataru Imajuku
    NTT Network Innovation Labs
    1-1 Hikari-no-oka, Yokosuka, Kanagawa
    Japan

    Phone: +81-(46) 859-4315
    EMail: imajuku.wataru@lab.ntt.co.jp