Network Working Group Request for Comments: 5542 Category: Standards Track T. Nadeau, Ed. BT D. Zelig, Ed. Oversi O. Nicklass, Ed. RADVISION May 2009

Definitions of Textual Conventions for Pseudowire (PW) Management Status of This Memo

This document specifies an Internet standards track protocol for the Internet community, and requests discussion and suggestions for improvements. Please refer to the current edition of the "Internet Official Protocol Standards" (STD 1) for the standardization state and status of this protocol. Distribution of this memo is unlimited.

Copyright Notice

Copyright (c) 2009 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents in effect on the date of publication of this document (http://trustee.ietf.org/license-info). Please review these documents carefully, as they describe your rights and restrictions with respect to this document.

This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.

Abstract

This memo defines a Management Information Base (MIB) module that contains textual conventions (TCs) to represent commonly used pseudowire (PW) management information. The intent is that these TCs will be imported and used in PW-related MIB modules that would otherwise define their own representations.

Table of Contents

1.	Introduction	2
	The Internet-Standard Management Framework	
	Conventions Used in This Document	
4.	Object Definitions	3
5.	Security Considerations	9
	IANA Considerations	
	References	
	7.1. Normative References	.0
	7.2. Informative References	.0

1. Introduction

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it defines textual conventions used for pseudowire (PW) technology and for Pseudowire Edge-to-Edge Emulation (PWE3) MIB modules.

2. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to section 7 of RFC 3410 [RFC3410].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIv2, which is described in STD 58, RFC 2578 [RFC2578], STD 58, RFC 2579 [RFC2579] and STD 58, RFC 2580 [RFC2580].

3. Conventions Used in This Document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119].

Nadeau, et al.

Standards Track

[Page 2]

4. Object Definitions

PW-TC-STD-MIB DEFINITIONS ::= BEGIN

IMPORTS

MODULE-IDENTITY, Unsigned32, mib-2 FROM SNMPv2-SMI -- [RFC2578]

TEXTUAL-CONVENTION FROM SNMPv2-TC;

-- [RFC2579]

pwTcStdMIB MODULE-IDENTITY

LAST-UPDATED "200904210000Z" -- 21 April 2009 00:00:00 GMT ORGANIZATION "Pseudowire Edge-to-Edge Emulation (PWE3) Working Group"

CONTACT-INFO

' Thomas D. Nadeau

Email: tom.nadeau@bt.com

David Zelig

Email: davidz@oversi.com

Orly Nicklass

Email: orlyn@radvision.com

The PWE3 Working Group (email distribution pwe3@ietf.org, http://www.ietf.org/html.charters/pwe3-charter.html)

DESCRIPTION

"This MIB module defines TEXTUAL-CONVENTIONS for concepts used in pseudowire edge-to-edge networks.

Copyright (c) 2009 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

 Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- Neither the name of Internet Society, IETF or IETF Trust, nor the names of specific contributors, may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS 'AS IS' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

This version of this MIB module is part of RFC 5542; see the RFC itself for full legal notices."

-- Revision history.

PwGroupID ::= TEXTUAL-CONVENTION DISPLAY-HINT "d" STATUS current DESCRIPTION

"An administrative identification for grouping a set of service-specific pseudowire services." SYNTAX Unsigned32

PwIDType ::= TEXTUAL-CONVENTION DISPLAY-HINT "d" STATUS current

```
DESCRIPTION
           "Pseudowire Identifier. Used to identify the PW
            (together with some other fields) in the signaling
            session."
    SYNTAX Unsigned32
PwIndexType ::= TEXTUAL-CONVENTION DISPLAY-HINT "d"
    STATUS
                   current
    DESCRIPTION
           "Pseudowire Index. A unique value, greater than zero, for each locally defined PW. Used for indexing
          several MIB tables associated with the particular PW. It is recommended that values are assigned contiguously starting from 1. The value for each PW MUST remain constant at least from one re-initialization
           to the next re-initialization."
    SYNTAX Unsigned32 (1..4294967295)
PwIndexOrZeroType ::= TEXTUAL-CONVENTION
    DISPLAY-HINT "d"
    STATUS
                     current
    DESCRIPTION
           "This TEXTUAL-CONVENTION is an extension of the
            PwIndexType convention. The latter defines a greater-
            than-zero value used to identify a pseudowire in the managed system. This extension permits the additional value of zero. The zero value is object-specific and MUST therefore be defined as part of the description of
            any object that uses this syntax. Examples of the usage of
            zero might include situations where pseudowire was unknown,
            or where none or all pseudowires need to be referenced."
     SYNTAX Unsigned32 (0..4294967295)
PwOperStatusTC ::= TEXTUAL-CONVENTION
                     current
    STATUS
    DESCRIPTION
       "Indicates the operational status of the PW.
                                    Ready to pass packets.
PW signaling is not yet finished, or
indications available at the service
       - up(1):
       - down(2):
                                    level indicate that the PW is not
                                    passing packets.
                                    AdminStatus at the PW level is set to
       - testing(3):
```

test.

```
The PW is not in a condition to pass packets but is in a 'pending' state,
     - dormant(4):
                            waiting for some external event.
                            Some component is missing to accomplish
     - notPresent(5):
                            the setup of the PW. It can be
                            configuration error, incomplete
     configuration, or a missing H/W component. - lowerLayerDown(6): One or more of the lower-layer interfaces
                            responsible for running the underlying PSN
                            is not in OperStatus 'up' state.'
 SYNTAX
          INTEGER {
     up(1),
     down(2),
testing(3),
     dormant(4),
     notPresent(5),
     lowerLayerDown(6)
PwAttachmentIdentifierType ::= TEXTUAL-CONVENTION
   STATUS
                current
   DESCRIPTION
       'An octet string used in the generalized Forward Error
       Correction (FEC) element for identifying attachment forwarder
       and groups. A NULL identifier is of zero length.
             OCTET STRING (SIZE (0..255))
  SYNTAX
PwGenIdType ::= TEXTUAL-CONVENTION
   STATUS
                current
   DESCRIPTION
      "Represents the Attachment Group Identifier (AGI) Type and
       Attachment Individual Identifier (AII) Type in generalized FEC
      signaling and configuration.
  SYNTAX
             Unsigned32( 0..254 )
PwCwStatusTC ::= TEXTUAL-CONVENTION
   STATUS
               current
   DESCRIPTION
      "Indicates the status of the control word (CW) negotiation
       based on the local configuration and the indications received
       from the peer node.
       waitingForNextMsg(1) indicates that the node is waiting for
       another label mapping from the peer.
```

sentWrongBitErrorCode(2) indicates that the local node has notified the peer about a mismatch in the C-bit.

rxWithdrawWithWrongBitErrorCode(3) indicates that a withdraw message has been received with the wrong C-bit error code.

illegalReceivedBit(4) indicates a C-bit configuration with the peer that is not compatible with the PW type.

cwPresent(5) indicates that the CW is present for this PW. If signaling is used, the C-bit is set and agreed upon between the nodes. For manually configured PW, the local configuration requires the use of the CW.

cwNotPresent(6) indicates that the CW is not present for this PW. If signaling is used, the C-bit is reset and agreed upon between the nodes. For manually configured PW, the local configuration requires that the CW not be used.

notYetKnown(7) indicates that a label mapping has not yet been received from the peer.

REFERENCE

"Martini, et al., 'Pseudowire Setup and Maintenance Using the Label Distribution Protocol', [RFC4447]."

```
SYNTAX INTEGER {
    waitingForNextMsg(1),
    sentWrongBitErrorCode(2),
    rxWithdrawWithWrongBitErrorCode(3),
    illegalReceivedBit(4),
    cwPresent(5),
    cwNotPresent(6),
    notYetKnown(7)
}
```

PwStatus ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"Indicates the status of the PW and the interfaces affecting this PW. If none of the bits are set, it indicates no faults are reported.

PwFragStatus ::= TEXTUAL-CONVENTION STATUS current DESCRIPTION

"Indicates the status of the fragmentation/reassembly process based on local configuration and peer capability.

noFrag(0) bit indicates that local configuration is for no fragmentation.

cfgFragGreaterThanPsnMtu(1) bit indicates that the local node is set to fragment, but the fragmentation size is greater than the MTU available at the PSN between the nodes. Fragmentation is not done in this case.

cfgFragButRemoteIncapable(2) bit indicates that the local configuration conveys the desire for fragmentation but the peer is not capable of reassembly.

remoteFragCapable(3) bit indicates that the remote node
is capable to accept fragmented PDUs.

fragEnabled(4) bit indicates that fragmentation will be used on this PW. Fragmentation can be used if the local node was configured for fragmentation, the peer has the capability to accept fragmented packets, and the CW is in use for this PW."

REFERENCE

"Malis, A. and M. Townsley, 'Pseudowire Emulation Edge-to-Edge (PWE3) Fragmentation and Reassembly', [RFC4623]."

Nadeau, et al.

Standards Track

[Page 8]

```
SYNTAX BITS {
    noFrag(0),
    cfgFragGreaterThanPsnMtu(1),
    cfgFragButRemoteIncapable(2),
    remoteFragCapable(3),
    fragEnabled(4)
    }

PwCfgIndexOrzero ::= TEXTUAL-CONVENTION
    DISPLAY-HINT "d"
    STATUS current
    DESCRIPTION
        "Index in any of the relevant configuration tables for supplement information regarding configuration of the specific technology. Value zero implies no additional configuration information is applicable."
    SYNTAX Unsigned32 (0..4294967295)
END
```

5. Security Considerations

This module does not define any management objects. Instead, it defines a set of textual conventions that may be used by other PWE3 MIB modules to define management objects.

Meaningful security considerations can only be written in the MIB modules that define management objects. Therefore, this document has no impact on the security of the Internet.

6. IANA Considerations

The MIB module in this document uses the following IANA-assigned OBJECT IDENTIFIER value recorded in the SMI Numbers registry:

Descriptor	OBJECT IDENTIFIER value
pwTcStdMIB	{ mib-2 188 }

7. References

7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.

- [RFC4447] Martini, L., Ed., Rosen, E., El-Aawar, N., Smith, T., and
 G. Heron, "Pseudowire Setup and Maintenance Using the
 Label Distribution Protocol (LDP)", RFC 4447, April 2006.
- [RFC4623] Malis, A. and M. Townsley, "Pseudowire Emulation Edge-to-Edge (PWE3) Fragmentation and Reassembly", RFC 4623, August 2006.

7.2. Informative References

[RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart,
"Introduction and Applicability Statements for InternetStandard Management Framework", RFC 3410, December 2002.

Authors' Addresses

Thomas D. Nadeau (editor) BT BT Centre 81 Newgate Street London EC1A 7AJ United Kingdom

EMail: tom.nadeau@bt.com

David Zelig (editor) Oversi Networks 1 Rishon Letzion St. Petah Tikva Israel

Phone: +972 77 3337 750 EMail: davidz@oversi.com

Orly Nicklass (editor) RADVISION 24 Raul Wallenberg Tel Aviv

Phone: +972 3 776 9444 EMail: orlyn@radvision.com