6.001: Structure and Interpretation of Computer **Programs**

- Today
 - The structure of 6.001
 - The content of 6.001
 - Beginning to Scheme

6.001 SICP 2/5/2007

6.001

- Main sources of information on logistics:
 - General information handout
 - Course web page
 - http://sicp.csail.mit.edu/
 - http://sicp.csail.mit.edu/Spring-2007/

6.001 SICP 2/5/2007 2/56

Course structure

1/56

3/56

- · Lectures
 - Delivered live here, twice a week (Tuesday and Thursday)
 - Versions of lectures also available on the web site, as audio annotated Power Point. Treat this like a live textbook. Versions are not identical to live lecture, but cover roughly same material.
 - Because lecture material is evolving, we strongly suggest that you attend live lectures, and use the online lectures as reinforcement.
- Recitations
 - Twice a week (Wednesday and Friday)
 - For Wednesday, don't go to recitation assigned by registrar: check the web site for your assigned section. If you have conflict, contact course secretary by EMAIL only.
 - You are expected to have attended the lecture (or listened to the online version) before recitation
 - Opportunity to reinforce ideas, learn details, clarify uncertainties, apply techniques to problems
- - Once a week (typically Monday, some on Tuesday)
 - You should really be there we provide a "carrot" to encourage you Ask questions, participate in active learning setting
 6.001 SICP

2/5/2007

6.001 SICP

6.001

- Grades
 - 2 mid-term quizzes 25%
 - Final exam 25%
 - 1 introductory project and 5 extended programming projects - 40%
 - weekly problem sets 10 % BUT YOU MUST ATTEMPT ALL OR COULD **RESULT IN FAILING GRADE!!**
 - Participation in tutorials and recitations up to 5% bonus points!!

Contact information

- Web site: http://sicp.csail.mit.edu/
- · Course secretary
 - Donna Kaufman, dkauf@mit.edu, 38-409a,
- Instructor in charge, lecturer
 - Eric Grimson, welg@csail.mit.edu
- · Co-lecturer
 - Rob Miller, rcm@csail.mit.edu

6.001 SICP 2/5/2007



Section Instructors

Prof. Michael Collins

Gerald Dalley



Prof. Peter Szolovits

4/56




Prof. Berthold Horn




Dr. Kimberle Koile

6.001 SICP

6/56










Other Issues Collaboration – Read description on web site Use of bibles – See description on web site Time spent on course Survey shows 15-18 hours/week Seeking help Lab assistants Other sources – departmental tutoring services, institute tutoring services (ask for help if you think you need it) Combination Inner door: 04862* Outer door: 94210 (evenings, weekends)



Getting assigned to a recitation

- We are **NOT** going to use the registrar's recitation assignments
- Please take a few minutes to fill out the sign
 - Turn in at the end of lecture
- We will post assignments for tomorrow's section later this afternoon on the course web site

6.001 SICP 13/56

6.001

- Today
 - The structure of 6.001
 - The content of 6.001
 - Beginning to Scheme

6.001 SICP 2/5/2007 14/56

What is the main focus of 6.001?

- This course is about Computer Science
- · Geometry was once equally misunderstood.
 - •Term comes from ghia & metra or earth & measure - suggests geometry is about surveying

15/56

- •But in fact it's about...
- By analogy, computer science deals with computation; knowledge about how to compute things
- Imperative knowledge

2/5/2007

Declarative Knowledge

• "What is true" knowledge

 \sqrt{x} is the y such that $y^2 = x$ and $y \ge 0$

2/5/2007 6.001 SICP

Imperative Knowledge

- · "How to" knowledge
- To find an approximation of square root of x:
 - Make a guess G
 - Improve the guess by averaging G and x/G
 - Keep improving the guess until it is good enough

Example: \sqrt{x} for x = 2.

X = 2	G = 1

6.001 SICP 2/5/2007 17/56

Imperative Knowledge

- · "How to" knowledge
- To find an approximation of square root of x:
 - Make a guess G
 - Improve the guess by averaging G and x/G

- Keep improving the guess until it is good enough

E	xample: \sqrt{x} for $x = 2$.	
X = 2	G€Û	
X/G = 2	$G = \frac{1}{2}(1+2) = 1.5$	
2/5/2007	6.001 SICP	18/56



- · "How to" knowledge
- To find an approximation of square root of x:
 - Make a guess G
 - Improve the guess by averaging G and x/G
 - Keep improving the guess until it is good enough

Example: \sqrt{x} for x = 2.

X = 2	G = 1	
X/G = 2	$G = \frac{1}{2}(1 + 2) = (1.5)$	
X/G = 4/3	$G = \frac{1}{2}(3/2 + 4/3) = 17/12 = 1.4166$	66
2/5/2007	6.001 SICP	19/56

Imperative Knowledge

- · "How to" knowledge
- To find an approximation of square root of x:
 - Make a guess G
 - Improve the guess by averaging G and x/G
 - Keep improving the guess until it is good enough

Example: \sqrt{x} for x = 2.

	I
X = 2	G = 1
X/G = 2	$G = \frac{1}{2}(1+2) = 1.5$
X/G = 4/3	$G = \frac{1}{2}(3/2 + 4/3) = (17/12) = 1.416666$
X/G = 24/17	$G = \frac{1}{2}(17/12 + 24/17) = 1.4142156$
2/5/2007	6.001 SICP 20/56


"How to" knowledge

Why "how to" knowledge?

· Could just store tons of "what is" information

2/5/2007 6.001 SICP

21/56



"How to" knowledge

Why "how to" knowledge?

- Could just store tons of "what is" information
- Much more useful to capture "how to" knowledge a series of steps to be followed to deduce a particular value
 - a recipe
 - called a procedure
- Actual evolution of steps inside machine for a particular version of the problem called a process
- Want to distinguish between procedure (recipe for square root in general) and process (computation of specific result); former is often much more valuable

5/2007 6.001 SICP 23/56

Describing "How to" knowledge

If we want to describe processes, we will need a language:

- Vocabulary basic primitives
- Rules for writing compound expressions syntax
- Rules for assigning meaning to constructs semantics
- Rules for capturing process of evaluation procedures

15 minutes

2/5/2007 6.001 SICP 24/56

Using procedures to control complexity Goals: Given a specific problem domain, we need to Create a set of primitive elements— simple data and procedures Create a set of rules for combining elements of language Create a set of rules for abstracting elements — treat complex things as primitives Why abstraction? — Can create complex procedures while suppressing details Target: Create complex systems while maintaining: efficiency, robustness, extensibility and flexibility. 25/2007 Control Complexity This is what we are actually going to spend the term discussing Create a set of rules for combining elements — treat complex things as primitives

Key Ideas of 6.001 Linguistic perspective on engineering design But no HASS credit! Primitives Means of combination Means of abstraction Means for capturing common patterns Controlling complexity Procedural and data abstractions Recursive programming, higher order procedures Functional programming versus object oriented programming Metalinguistic abstraction

26/56

6.001

- Today
 - The structure of 6.001
 - The content of 6.001
 - Beginning Scheme

2/5/2007 6.001 SICP 27/56

Computation as a metaphor

6.001 SICP

Capture descriptions of computational processes

Creating new languagesCreating evaluators

- Use abstractly to design solutions to complex problems
- Use a language to describe processes

2/5/2007 6.001 SICP 28/56

Describing processes

- Computational process:
 - Precise sequence of steps used to infer new information from a set of data
- · Computational procedure:
 - The "recipe" that describes that sequence of steps in general, independent of specific instance
- What are basic units on which to describe procedures?
 - Need to represent information somehow

2/5/2007 6.001 SICP 29/56


Representing basic information

- · Numbers
 - Primitive element single binary variable
 - Takes on one of two values (0 or 1)
 - · Represents one bit (binary digit) of information
 - Grouping together
 - Sequence of bits
 - Byte 8 bits
 - Word 16, 32 or 48 bits
- Characters
 - Sequence of bits that encode a character
 - · EBCDIC, ASCII, other encodings
- Words
 - Collections of characters, separated by spaces, other delimiters $_{25/2007}^{+0.01}$ collections of characters, separated by spaces, other delimiters

Binary numbers and operations

• Unsigned integers

2/5/2007



Binary numbers and operations

• Addition

10101 111 11100

6.001 SICP 32/56


Binary numbers and operations


6.001 SICP

31/56

- Can extend to signed integers (reserve one bit to denote positive versus negative)
- Can extend to character encodings (use some high order bits to mark characters versus numbers, plus encoding)


2/5/2007 6.001 SICP 33/56







35/5



... we don't care at some level!

- Dealing with procedures at level of bits is way too low-level!
- From perspective of language designer, simply need to know the interface between
 - Internal machine representation of bits of information, and
 - Abstractions for representing higher-order pieces of information, plus
 - Primitive, or built-in, procedures for crossing this boundary
 - you give the procedure a higher-order element, it converts to internal representation, runs some machinery, and returns a higher-order element

5/2007 6

Assuming a basic level of abstraction

- We assume that our language provides us with a basic set of data elements ...
 - Numbers
 - Characters
 - Booleans
- ... and with a basic set of operations on these primitive elements, together with a "contract" that assures a particular kind of output, given legal input
- Can then focus on using these basic elements to construct more complex processes

07 6.001 SICP 38/56

Our language for 6.001

- Scheme
 - Invented in 1975
- Dialect of Lisp

- Invented in 1959





959

Guy Steele Gerry Sussman

39/56



John McCarthy

6.001 SICP

Rules for describing processes in Scheme

- 1. Legal expressions have rules for constructing from simpler pieces
- (Almost) every expression has a value, which is "returned" when an expression is "evaluated".

 Semantics
- 3. Every value has a **type**, hence every (almost) expression has a **type**.

2/5/2007 6.001 SICP 40/56

Kinds of Language Constructs

- Primitives
- · Means of combination
- · Means of abstraction

2/5/2007 6.001 SICP 41/56

Language elements – primitives

- Self-evaluating primitives value of expression is just object itself
 - Numbers: 29, -35, 1.34, 1.2e5
 - Strings: "this is a string" " this is another string with %&^ and 34"
 - Booleans: #t, #f

2/5/2007 6.001 SICP 42/56

George Boole



A Founder

An Investigation of the Laws of Thought, 1854
-- "a calculus of symbolic reasoning"

2/5/2007 6.001 SICP 43/

Language elements – primitives

- Built-in procedures to manipulate primitive objects
 - Numbers: +, -, *, /, >, <, >=, <=, =
 - Strings: string-length, string=?
 - Booleans: boolean/and, boolean/or, not

2/5/2007 6.001 SICP 44/56


Language elements – primitives

- Names for built-in procedures
 - -+,*,-,/,=,...
 - What is the value of such an expression?
 - $-+ \rightarrow$ [#procedure ...]
 - Evaluate by looking up value associated with name in a special table

2/5/2007 6.001 SICP 45/56

Language elements – combinations

• How do we create expressions using these procedures?



• Evaluate by getting values of sub-expressions, then applying operator to values of arguments

2/5/2007 6.001 SICP 46/56

Language elements - combinations

• Can use nested combinations – just apply rules recursively

(* (+ 3 4) (- 8 2))

→42

2/5/2007 6.001 SICP

47/56

Language elements -- abstractions

• In order to abstract an expression, need way to give it a name

(define score 23)

- This is a special form
 - Does not evaluate second expression
 - Rather, it pairs name with value of the third expression
- · Return value is unspecified

/5/2007 6.001 SICP 48/56

Language elements -- abstractions

To get the value of a name, just look up pairing in environment

score → 23


- Note that we already did this for +, *, ... (define total (+ 12 13))
 (* 100 (/ score total)) → 92
- This creates a loop in our system, can create a complex thing, name it, treat it as primitive


5/2007 6.001 SICP 49/56


Scheme Basics


- · Rules for evaluation
- 1. If **self-evaluating**, return value.
- 2. If a **name**, return value associated with name in environment.
- 3. If a **special form**, do something special.
- 4. If a **combination**, then
 - a. *Evaluate* all of the subexpressions of combination (in any order)
 - b. *apply* the operator to the values of the operands (arguments) and return result


2007 6.001 SICP 50/56














Summary

- Primitive data types
- Primitive procedures
- Means of combination
- Means of abstraction names

2/5/2007 6.001 SICP 57/56