

```

:- include(parser).
:- include(scanner).
run(In, String, Out) :-
    scan(String, Tokens),
    parse(Tokens, SyntaxTree),
    execute(In, SyntaxTree, Out).

% Define number and identifier literals
% num/1 - Defines numbers
num(N) :- number(N).
% id/1 - Defines identifiers
id(I) :- atomic(I).

boolean(_, true, true).
boolean(_, false, false).
boolean(S0, LE > RE, X) :-
    expression(S0, LE, LR),
    expression(S0, RE, RR),
    (LR > RR) -> (X = true) ;
    (X = false).

boolean(S0, LE >= RE, X) :-
    expression(S0, LE, LR),
    expression(S0, RE, RR),
    (LR >= RR) -> (X = true) ;
    (X = false).

boolean(S0, LE < RE, X) :-
    expression(S0, LE, LR),
    expression(S0, RE, RR),
    (LR < RR) -> (X = true) ;
    (X = false).

boolean(S0, LE <= RE, X) :-
    expression(S0, LE, LR),
    expression(S0, RE, RR),
    (LR <= RR) -> (X = true) ;
    (X = false).

boolean(S0, LE == RE, X) :-
    expression(S0, LE, LR),
    expression(S0, RE, RR),
    (LR == RR) -> (X = true) ;
    (X = false).

%Execute given a program P and Binding Environment S0
% Execute/3 - Defines how a program should be executed.
% S0 is the binding Environment before the program is executed.
% P is the program.
% Sn is the binding environment after execution of the program.
execute(S0,P,Sn) :-
    command(S0,P,Sn).

% set/2 - Defines a set relation between an identifier and a number.
set(id(I),num(E)) :- id(I), num(E).

% bind/4 - Defines the procedure of binding a set relation between an identifier and
a number and a binding environment.
bind([], I, E, [set(I,E)]).
% Special case of bind/4 that make sure an identifier with an already existing set r
ealton is set to the new value and not duplicated and appended.
bind([set(I,_)|S0], I,E, [set(I,E)|S0]).
bind([set(H,A)|S0], I, E, [set(H,A)|Sn]) :-
    H \= I,
    bind(S0,I,E,Sn).

% expression/3 - Defines the evaluation of arithmetic expressions.
expression(S0,id(E),R) :-
    member(set(E,R), S0). % Retrives the numeric value of an identifier already
in the biding environment.
expression(_, num(E), E).
% Defines the 'addition' operator for two expressions.
expression(S0, E1 + E2, R) :-
    expression(S0, E1, R1), % Evaluate expression E1.
    expression(S0, E2, R2), % Evaluate expression E2.
    R is (R1 + R2). % Assign the return value the value of E1 + E2.
% Defines the 'subtraction' operator for two expressions.

```

```

expression(S0, E1 - E2, R) :-
    expression(S0, E1, R1), % Evaluate expression E1.
    expression(S0, E2, R2), % Evaluate expression E2.
    R is (R1 - R2). % Assign the return value the value of E1 - E2.
% Defines the 'multiplication' operator for two expressions.
expression(S0, E1 * E2, R) :-
    expression(S0, E1, R1), % Evaluate expression E1.
    expression(S0, E2, R2), % Evaluate expression E2.
    R is (R1 * R2). % Assign the return value the value of E1 * E2.
% Defines the 'negation' operator for two expressions.
expression(S0, - E, R) :-
    expression(S0, E, R1), % Evaluate expression E.
    R is (R1 * -1). % Assign the return value the value of -E.

%Define commands
% Command/3 - Defines the evaluation of different comand structures in a program.
% Define command skip as a fact
command(S0, skip, S0).
% Defines the command set.
command(S0, set(id(I), E), Sn) :-
    expression(S0, E, R), % Evaluate expression E
    bind(S0, I, R, Sn). % Bind the evaluate expression E to the identifier I
    and adds the set to the binding environment.
% Defines the command if.
command(S0, if(B, C1, _), Sn) :-
    (boolean(S0, B, true), command(S0, C1, Sn)). % If the boolean expression B is true pe
rform command C1.
command(S0, if(B, _, C2), Sn) :-
    (boolean(S0, B, false), command(S0, C2, Sn)). % If the boolean expression B is false
perform command C2.
% Defines the command seq
command(S0, seq(C1, C2), Sn) :-
    command(S0, C1, Sr), % First perform action C1
    command(Sr, C2, Sn). % Then perform actino C2
% Defines the command while
command(S0, while(B, _), S0) :-
    (boolean(S0, B, false)). % If the boolean expression B is false, stop.
command(S0, while(B, C), Sn) :-
    boolean(S0, B, true),
    command(S0, C, Sr), % Perform action C.
    command(Sr, while(B, C), Sn). % Recursivley call the command while with the same b
oolean expression but with updated Binding environment.

% -----
% -----EXAMPLE QUERY-----
% -----
%
% ?- run([set(x,3)], "y:=1; z:=0; while x>z do z:=z+1; y:=y*z od", Res).
% Res = [set(x,3), set(y,6), set(z,3)] ? ;
% no
%

```