



Times New Roman Bold
14,5 pt/ 17,4 pt - C87 M50 Y0 K20

Times New Roman Regular
10 pt/ 12 pt - CO MO YO K100

Times New Roman Regular
8,5 pt/ 10,2 pt - CO MO YO K100

Times New Roman Regular
8,5 pt/ 10,2 pt - CO MO YO K100

5 mm

Times New Roman Bold
12,5 pt/ 15 pt - C0 M0 Y0 K100

Times New Roman Regular
9,5 pt/ 11,5 pt - CO MO YO K100

• 13 mm

Times New Roman Regular
7,5 pt/ 9 pt - CO MO YO K100



180 x 260 mm




Figure 5. Power spectrum comparison between rest and task states for volunteer S6 under condition MV.




Figure 6. Function $\hat{\phi}_{\bar{p}}$ with (a) detection and (b) no detection of movement intention. The figure shows the results using five realizations of the task for volunteer S1 under condition MV.

seconds before and five seconds after the task initiation, whereas Figure 6b shows the same function for a case when no detection occurs with the execution of the task.

In order to consider a particular detection as valid, we defined a time interval when the task condition must be detected. The detection range comprised

Table 1. Reactive frequency for each volunteer.

Volunteer	S1	S2	S3	S4	S5	S6
f_R [Hz]	10,6	8,2	9,8			

the half of second before task execution (movement preparation), the actual time of execution, and the half-second after performing the task (latency) as depicted in Figure 6a.

We computed $\hat{\phi}_{\bar{p}}$ for all the volunteers and conditions using 1 (single trial), 4, 8, and 12 trials for the detector. We determined the detection rate for every volunteer based on the time interval to consider a detection as valid (Figure 6a). The false positives were computed as the detections outside this interval.

We determined the detection rate for all the volunteers and conditions of the study as the rate between the amount of valid detections over the total number of expected detections. In general, the highest detection rate obtained was for condition MV (Figure 7b), followed by IM (Figure 7c) and finally ST (Figure 7a). We obtained detection rates ranging from 53 to 97%, when using four realizations of the task, in five of the volunteers for condition MV, in three of them for IM, and in two of them for ST.

For imagery (IM), which is the condition to be used to command the BMI, the detection rates for three volunteers (S1, S2 and S5) are much lower than for the others (S3, S4 and S6). Furthermore, the detection rate does not improve significantly with the number of trials used in the detector for the volunteers with low detection rate. False positives varied among subjects, but all rates remained below 5% when using more than one trial for the detector.



180 x 260 mm

Different from most classifiers (Bai et al., 2007; 2011; Bhagat, 2014; Jiang et al., 2015; Kamavuako et al., 2015; Lew et al., 2012; 2014; Nikulin et al., 2008), the detector does not need training data to determine its parameters. The only previous knowledge needed for the SFT detector is the electrophysiological response, i.e., the only characteristic needed is the desynchronization present as a persistent feature related to movement intention, which is used to detect whether the volunteer intended a movement or not. This characteristic may be considered invariant among subjects and experiment conditions.

The BMI paradigm we use has two focuses: the triggering of high-level tasks by the electrophysiological activity of the BMI user obtained through EEG signals, and the execution and solution of several kinds of task by using robotic systems. Both of these aspects are treated as separate parts of our current research. However, we always keep a path that will allow the appropriate integration of these aspects into a single BMI.

As future work, we intend to extend and improve the proposed algorithm in order to detect more types of movement intention. In addition, we will explore other biosignal sources to increase the amount and robustness of control commands, as done in hybrid interfaces research (Allison et al., 2012; Fazli et al., 2012; Pfurtscheller et al., 2010).

Acknowledgements

This work has been supported by the Brazilian agencies CAPES, CNPq and FAPEMIG.

References

- Allison BZ, Brunner C, Altstätter C, Wagner IC, Grissmann S, Neuper C. A hybrid ERD/SSVEP BCI for continuous simultaneous two dimensional cursor control. *Journal of Neuroscience Methods*. 2012; 209(2):299-307. <http://dx.doi.org/10.1016/j.jneumeth.2012.05.015>.
- Bai O, Lin P, Vorbach S, Li J, Furlani S, Hallett M. Exploration of computational methods for classification of movement intention during human voluntary movement from single trial EEG. *Clinical Neurophysiology*. 2007; 118(12):2637-55. <http://dx.doi.org/10.1016/j.clinph.2007.08.025>. PMID:17967559.
- Bai O, Rathi V, Lin P, Huang D, Battapady H, Fei D-Y, Schneider L, Houdayer E, Chen X, Hallett M. Prediction of human voluntary movement before it occurs. *Clinical Neurophysiology*. 2011; 122(2):364-72. <http://dx.doi.org/10.1016/j.clinph.2010.07.010>. PMID:20675187.
- Behrmann M, Geng JJ, Shomstein S. Parietal cortex and attention. *Current Opinion in Neurobiology*. 2004; 14(2):212-7. <http://dx.doi.org/10.1016/j.conb.2004.03.012>. PMID:15082327.

Bhagat NA. Detecting movement intent from scalp EEG in a novel upper limb robotic rehabilitation system for stroke. In: 36th Annual International Conference of the IEEE Engineering in Medicine and Biology Society; 2014 Aug 26-30; Chicago, USA. Chicago: IEEE; 2014. p. 4127-30. <http://dx.doi.org/10.1109/EMBC.2014.6944532>.

Cecotti H. Spelling with non-invasive brain-computer interfaces: current and future trends. *The Journal of Physiology*. 2011; 105(1-3):106-14. PMID:21911058.

Doud AJ, Lucas JP, Pisansky MT, He B. Continuous three dimensional control of a virtual helicopter using a motor imagery based brain-computer interface. *PLoS One*. 2011; 6(10):e26322. <http://dx.doi.org/10.1371/journal.pone.0026322>. PMID:22046274.

Fatourechi M, Bashashati A, Ward RK, Birch GE. EMG and EOG artifacts in brain computer interface systems: a survey. *Clinical Neurophysiology*. 2007; 118(3):480-94. <http://dx.doi.org/10.1016/j.clinph.2006.10.019>. PMID:17169606.

Fazli S, Mehnert J, Steinbrink J, Curio G, Villringer A, Müller KR, Blankertz B. Enhanced performance by a hybrid NIRS-EEG brain computer interface. *NeuroImage*. 2012; 59(1):519-29. <http://dx.doi.org/10.1016/j.neuroimage.2011.07.084>. PMID:21840399.

Giuliana G, Mario M, Yassin J. A quality parameter for the detection of the intentionality of movement in patients with neurological tremor performing a finger-to-nose test. In: 33rd Annual International Conference of the IEEE EMBS; 2011 Aug 30-Sept 03; Boston, USA. Boston: IEEE; 2011. p. 7707-10. <http://dx.doi.org/10.1109/IEMBS.2011.6091899>.

Hochberg LR, Bacher D, Jarosiewicz B, Masse NY, Simeral JD, Vogel J, Haddadin S, Liu J, Cash SS, van der Smagt P, Donoghue JP. Reach and grasp by people with tetraplegia using a neurally controlled robotic arm. *Nature*. 2012; 485(7398):372-5. <http://dx.doi.org/10.1038/nature11076>. PMID:22596161.

Infantosi AF, Sá AM. A statistical test for evaluating the event-related synchronization/desynchronization and its potential use in brain-computer-interfaces. *IFMBE Proceedings*. 2007; 18:1122-6. http://dx.doi.org/10.1007/978-3-540-74471-9_260.

Jeon Y, Nam CS, Kim YJ, Whang MC. Event-related (De) synchronization (ERD/ERS) during motor imagery tasks: implications for brain-computer interfaces. *International Journal of Industrial Ergonomics*. 2011; 41(5):428-36. <http://dx.doi.org/10.1016/j.ergon.2011.03.005>.

Jiang N, Gizzi L, Mrachacz-Kersting N, Dremstrup K, Farina D. A brain-computer interface for single-trial detection of gait initiation from movement related cortical potentials. *Clinical Neurophysiology*. 2015; 126(1):154-9. <http://dx.doi.org/10.1016/j.clinph.2014.05.003>. PMID:24910150.

Kalcher J, Pfurtscheller G. Discrimination between phaselocked and non-phase-locked event-related EEG activity. *Electroencephalography and Clinical Neurophysiology*. 1995; 94(5):381-4. [http://dx.doi.org/10.1016/0013-4694\(95\)00040-6](http://dx.doi.org/10.1016/0013-4694(95)00040-6). PMID:7774524.

Kamavuako EN, Jochumsen M, Niazi IK, Dremstrup K. Comparison of features for movement prediction

5,5 mm

4,5 mm

3 mm

Times New Roman Bold
12,5 pt/ 15 pt - C0 M0 Y0 K100Times New Roman Regular
8,5 pt/ 10,2 pt - C0 M0 Y0 K100