Topoloka — One Video In. Google Maps for Indoors Out — In a Link.

Technical abstract · Round 1 · Techfest 2026-27

Topoloka — Greek τόπος (*topos*, "place") + Sanskrit लोक (*loka*, "world"): the place-world. It turns one walk-through video of an indoor space into an interactive, metric 3D twin served as a static link: free first-person roaming, a navigable floor, and a quality report anyone can audit.

> Every number below comes from the shipped artifacts of the end-to-end run on the public Melbourne metro capture — `test/metro_v1/` and the Kaggle kernel outputs it was assembled from. Nothing is projected or invented; where the system is weak, Section 7 says so with the same specificity.

1. The problem we actually solve

Indoor navigation is still broken for everyone: visitors in campuses, patients in hospitals, shoppers in malls, staff in factories. Floor-plan kiosks are static and dishonest; Google Maps gives up at the door; LiDAR twins need hardware nobody has. The question is not "can we build a 3D scanner" — it is **"what is the shortest path from one walk-through of a space to a stranger navigating that space as if they were there?"**

Our answer: **one ordinary video, a free-tier GPU pipeline, and a link.** No LiDAR. No app install for the visitor — the twin, the map, and (R2) the search and directions all run in the browser.

2. What the pipeline produces

From a single handheld monocular video, the pipeline produces a **metric, navigable Gaussian-splat twin** served as static files:

1. **A splat twin** — free first-person roaming at walking speed, with real collision against the reconstructed geometry.
2. **A metric 2.5D navigation layer** — every fused point placed in metres, gravity-aligned, discretized into a 5 cm walkability costmap with a floor outline; the foundation for search and routing.
3. **A trust layer** — every stage reports its quality gates (registration fraction, reprojection error, sharpness percentiles, scale stability); failures name their compensation, never hide.

3. The input: a public walk-through, plus the phone SOP

The R1 artifact is deliberately reproducible from **public, licensed footage**: *Modern Melbourne Metro Walkway Urban Design* by Joolsmagool (Pexels License), trimmed to **86.07 s at 1920×1080 / 30 fps**. It is a single continuous walk down a real transit corridor — tiled floor, curved metal panels, ad screens, a concourse — with no cuts, no people in the foreground, and no privacy exposure. The sample ships 14 preview frames plus the SfM, depth, nav, and web artifacts, and credits the source in its README.

The product's **phone capture SOP** is a first-class deliverable: EIS off, AE/AF locked, 4K30, two-pass loop with a 5 s still tail, ~0.4 m/s pace, stride-synced frame picking, QR anchors per zone. The public artifact uses the stock clip, which has no IMU, so gravity is estimated from the SfM camera-y mean instead of the phone's accelerometer. Nothing in the reconstruction code is stock-specific.

4. System architecture




Figure 1 — the whole pipeline runs on the Kaggle free tier; the repo's tooling pushes kernels and fetches artifacts, and the deliverable is a folder of static files (no server, no database, no account).

Three decisions carried most of the weight:

- **Scale is solved, not assumed.** Monocular SfM has arbitrary scale and metric depth models have approximate scale; we align them directly. For every visible sparse 3D point, `depth_m / camera_z` is one scale sample; the median over **37,844** samples makes the whole twin metric — distances and ETAs are real metres. The source and residual are reported in `scale.json`, so judges and users can audit them.
- **One frame convention, documented once.** Raw SfM (arbitrary frame) → nav frame (gravity-aligned, z-up, metres, `nav.json.align`) → three.js. The splat is trained with trainer-side auto-orient, centering, and scaling **disabled**, so the exported splat lands exactly in the documented frame — the silent misalignment that breaks most demo pipelines. The web viewer applies the same `align` block to the cloud, the splat, and the trajectory.
- **Everything runs on Kaggle, including the CPU stages.** The dev machine only edits code and drives the Kaggle CLI; every run is reproducible from a captured kernel log and a code tarball (the repo's `kaggle/` tooling).

5. Novelty, stated precisely

1. **A capture/reconstruction QA contract with numbers, not vibes.** On the metro sample, **6/6** checks pass: p10 Laplacian sharpness **582** (gate ≥ 100), **216** frames at 2.5 Hz, **216/216** views registered, **0.403 px** median reprojection error (gate ≤ 1.0), a **193-point** floor outline enclosing **315.05 m²**, and no geometry warnings.
2. **Zero-touch semantic POIs (R2)** — open-vocabulary detection + CLIP embeddings projected into 3D, so "where is the nearest washroom" works on a space nobody annotated.
3. **Dual-representation navigation** — splat for the eyes, 2.5D costmap for the legs: A* on the grid, smoothed routes, metric ETAs, minimap, route ribbon in first person.
4. **QR-fiducial-anchored AR (R3)** — scan a physical QR in the space, get your pose inside the twin in the browser; no native app, no VPS infrastructure.
5. **Honest engineering as a feature** — every artifact ships its own quality report; this abstract states where the system is weak instead of cropping it out.

6. Results (public metro capture, Oct 2026)

Metric	Value
Input	86.07 s public clip, 1920×1080 / 30 fps (Pexels License)
Frames kept	216 at 1600×900 (sharpest-per-window @ 2.5 Hz)
SfM registered fraction	216/216 = 100% (gate ≥ 60%)
SfM points / error	51,677 points; 0.403 px median, 0.613 px mean (gate ≤ 1.0)
Metric scale	6.2505 m/unit from metric depth; MAD 7.54% over 37,844 samples
Depth fusion	216/216 frames; 31.2 M raw depth points → 10.28 M voxel points
Costmap	1188 × 1259 cells @ 5 cm; 929,436 floor inliers; camera height 1.588 m
Walkable area	315.05 m² free (126,020 cells), 97,063 obstacle, 1,272,609 unknown
Splat	25,000 iters, full-res 1600×900; 510,336 web gaussians / 16.33 MB export
Hosted sample	457,221 gaussians / 14.63 MB (3 m volume crop), 250,000-point cloud
Pipeline time	CPU 59.2 min (SfM) + 61 s (nav); GPU 79.0 min total (depth, JIT, train, export)
Sample QA	6/6 PASS (see Section 5)

The GPU stage is a nerfstudio 1.1.5 splatfacto run on one Kaggle T4. The exported PLY is converted to the 32-byte web `.splat` format with higher SH bands dropped (DC only) and low-alpha gaussians pruned. The hosted bundle is the same twin opacity-pruned and cropped to a 3 m volume around the cloud: **18.4 MB of web payload** (14.63 MB splat + 3.75 MB cloud + nav), with the full sample folder at 24.7 MB including preview frames and reports.

pycolmap also produced a 3-frame secondary reconstruction; the largest model (216/216 frames) was used, and the warning is preserved in `sfm/sfm_report.json`.




*Figure 2 — the measured metric costmap behind collision and (R2) routing (the viewer also blocks unobserved cells and carves the 1 m walked path free): white = observed free cells (**315.05 m²** walkable), lavender = obstacle band above the floor, gray = unobserved, blue = camera path; 1188 × 1259 cells at 5 cm.*



Figure 3 — the shipped twin in a browser (hosted sample, 457,221 gaussians): the splat, the metric minimap (red = obstacles, blue = capture path) and the QA verdict in the HUD. The viewpoint is trajectory index 160 (64 s). Walls are soft where the source panels are reflective; the floor and sightlines are metric.

Viewer: https://sciencebanda09.github.io/topoloka/?capture=metro_v1 · Code: https://github.com/sciencebanda09/topoloka · Demo video: **pending upload**

7. Where the system is weak (and what we do about it)

- **Reflective, low-texture panels.** The station's glass/metal walls are the hardest part of this capture: at 457 K gaussians over 315 m^2 (~1.5 K/m^2) the walls are visibly softer than the tiled floor, and the ceiling is under-observed (the dark band in Figure 3). A room-scale capture at the same gaussian budget is far crisper. Denser densification and a view-dependent SH export are the next quality levers; both cost web payload.
- **DC-only web splat.** The web format drops SH bands 1–3, so view-dependent highlights on metal are flattened into their average colour. The export is a deliberate size/quality tradeoff, not an accident.
- **No IMU in the public clip.** Gravity comes from the SfM camera-y mean, not the phone; the phone SOP (Sensor Logger) is implemented but not exercised by this redistributable artifact.
- **Metric depth degrades past ~8–12 m.** Fusion is clipped there; the residual is reported in `depth/depth_report.json` rather than hidden.
- **Web payload and cold load.** 18.4 MB of web payload (14.63 MB splat; the full sample folder is 24.7 MB) is fine on broadband and marginal on a poor venue network; `.ksplat` compression and a lower gaussian budget are the fallbacks.
- **No POIs or routing UI yet.** The A* costmap, route rendering, and `?route` dev flag are scaffolded; semantic POIs and the search bar are R2.
- **Software rendering distorts splats.** Headless SwiftShader screenshots stretch anisotropic gaussians; all figures here were captured on a hardware GPU (ANGLE/D3D11). A reviewer comparing a software-rendered still to these figures should use a GPU-backed browser.

8. Round 2/3 roadmap

- **R2 (Nov 30):** POIs + open-vocabulary search + routing end-to-end behind the existing A*, minimap, and route-rendering scaffolding.
- **R3 (Dec 16–17):** capture on the IIT Bombay campus with the phone SOP + QR anchors; on-site twin + AR relocalization demo; live QA report shown to judges.

9. Reproducibility and credit

The repo contains the pipeline (all stages as small, readable modules), the Kaggle kernel definitions, the capture SOP, and a `test/metro_v1` capture with documented local viewing and the exact QA report. The source clip is credited in `test/metro_v1/README.md` (*Modern Melbourne Metro Walkway Urban Design* by Joolsmagool, Pexels License, trimmed to 86 s); the sample data is redistributed under that licence, the code under MIT.