

Comparing methods for MHC peptide binding using PSSM, SMM, and ANN

Kamilla Kjærgaard Jensen, s112819



Marie Louise Jespersen, s152153

Patrick Zecchin, s150701

Introduction

Overview

MHC peptide complex



Position Specific Scoring Matrix (PSSM)

1. position

EDRYK
EHYLK
QGHLP
EHLR
EHQEA
EHLR

$$g_a = \sum_b f_b \cdot q(a|b)$$

$$p_a = \frac{\alpha \cdot f_a + \beta \cdot g_a}{\alpha + \beta}$$

$$W_{ia} = 2 \cdot \frac{\log(\frac{p_a}{q_a})}{\log(2)}$$

1. AA

	f_a	g_a	p_a	W_a
A				
R				
N				
D				
C				
Q				
E				
G				
H				
I				
L				
K				
M				
F				
P				
S				
T				
W				
Y				
V				

Optimisation of β :

- Small β for large datasets
- Large β for small datasets

	A	R	N	D	C	Q	E	G	H	I	L	K	M	F	P	S	T	W	Y	V
1 Y	-2	-2	-2	-3	-2	-1	-2	-3	2	-1	-1	-2	-1	3	-3	-2	-2	2	7	-1
2 L	-1	-2	-3	-4	-1	-2	-3	-4	-3	2	4	-2	2	0	-3	-2	-1	-2	-1	1
3 P	-1	-2	-2	-2	-3	-2	-1	-2	-2	-3	-3	-1	-3	-4	8	-1	-1	-4	-3	-3
4 S	1	-1	0	-1	-1	0	0	-1	-1	-3	-3	0	-2	-3	-1	5	1	-3	-2	-2
5 C	-1	-4	-3	-4	9	-3	-4	-3	-3	-2	-2	-3	-2	-3	-3	-1	-1	-3	-3	-1

Calculate scores using the PSSM
for peptides in the test set


Stabilization Matrix Method (SMM)

Input vector: Sparse encoding

Length = peptide length * 20



Step 1: Input vector



Step 2: Calculate O


$$O = \sum_i l_i \cdot w_i$$

SMM – gradient descent

Input vector: Sparse encoding
Length = peptide length * 20

1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0

Step 1: Input vector



Step 2: Calculate O

$$O = \sum_i I_i \cdot w_i$$

Step 3: Calculate E

Gradient descent


$$E_{\text{per target}} = \frac{1}{2} \cdot (O - t)^2 + \frac{\lambda}{N} \sum_i w_i^2$$

Step 4: Update weights

$$\frac{\partial E}{\partial w_i} = (O - t) \cdot I_i + \frac{2 \cdot \lambda}{N} \cdot w_i$$

$$\Delta w_i = -\varepsilon \cdot \frac{\partial E}{\partial w_i}$$

Gradient descent




SMM – Monte Carlo

Input vector: Sparse encoding
Length = peptide length * 20

1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0

Step 1: Input vector



Step 2: Calculate O

$$O = \sum_i I_i \cdot w_i$$

Step 3: Calculate E

$$E = \frac{1}{2} \cdot \sum_i (O_i - t_i)^2 + \lambda \cdot \sum_i w_i^2$$

Monte Carlo

Step 4: Update weights

Update weights if the
move is accepted

Monte Carlo

Calculates global error

Peptide 1 ... N - Step 1-4

$$P(\text{accept}) = \min \left(1, \left(e^{\frac{-\Delta E}{T}} \right) \right)$$

If $\Delta E \leq 0$

- Accept move

If $\Delta E > 0$

- Pick a random number i ($0 \leq i \leq 1$)


- Accept if $\Delta E \leq i$

SMM - output

Input vector: Sparse encoding
Length = peptide length * 20

1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0

Step 1: Input vector



Step 2: Calculate O

$$O = \sum_i I_i \cdot w_i$$

Step 3: Calculate E

Gradient descent

$$E_{\text{per target}} = \frac{1}{2} \cdot (O - t)^2 + \frac{\lambda}{N} \sum_i w_i^2$$

Monte Carlo

$$E = \frac{1}{2} \cdot \sum_i (O_i - t_i)^2 + \lambda \cdot \sum_i w_i^2$$

Step 4: Update weights

$$\frac{\partial E}{\partial w_i} = (O - t) \cdot I_i + \frac{2 \cdot \lambda}{N} \cdot w_i$$

$$\Delta w_i = -\varepsilon \cdot \frac{\partial E}{\partial w_i}$$

Update weights if mc move is accepted

Calculate affinities using the SMM for peptides in the test set

Output = weight matrix

	A	R	N	D	C	Q	E	G	H	I	L	K	M	F	P	S	T	W	Y	V
1 Y	-2	-2	-2	-3	-2	-1	-2	-3	2	-1	-1	-2	-1	3	-3	-2	-2	2	2	1
2 L	-1	-2	-3	-4	-1	-2	-3	-4	-3	4	4	2	4	0	-3	-2	-1	-2	-1	1
3 P	-1	-2	-2	-2	-3	-2	-1	-2	-2	-3	-3	-1	-3	-4	8	-1	-1	-4	-3	-3
4 S	1	-1	0	-1	-1	0	0	-1	-1	-3	0	-2	-3	-1	5	1	-3	-2	-2	5
5 C	-1	-4	-3	-4	9	-3	-4	-3	-3	-2	-2	-3	-3	-3	-1	-1	-3	-3	-1	1

Vector of final weights
Length = input vector

w1 w2 w3 w4 w5 w6 w7 w8 w9 w10 w11 w12 w13 w14 w15 w16 w17 w18 w19 w20

Artificial Neural Network (ANN)

Input vector: Sparse or BLOSUM encoding
Length = peptide length * 20

1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0

Step 1: Input vector

Input = 180

1 (Bias)

1. round:
random weights

Step 2: Calculate output
of next neuron (H or O)

$$o = \sum x_i \cdot w_i \quad O = g(o)$$

Step 3: Calculate E

$$E = \frac{1}{2} \cdot (O - t)^2$$

Step 4: Update weights

$$\Delta w_j = -\varepsilon \cdot \frac{\partial E}{\partial w_j}; \Delta v_{\beta} = -\varepsilon \cdot \frac{\partial E}{\partial v_{\beta}}$$

$$\frac{\partial E}{\partial w_j} = (O - t) \cdot g'(o) \cdot H_j$$

$$\frac{\partial E}{\partial v_{\beta}} = g'(h_j) \cdot I_k \cdot (O - t) \cdot g'(o) \cdot w_j$$

ANN – forward and back

Input vector: Sparse or BLOSUM encoding
Length = peptide length * 20

1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0

Step 1: Input vector

Input = 180


1 (Bias)

1. round:
random weights

Forward

Step 2: Calculate output
of next neuron (H or O)

$$o = \sum x_i \cdot w_i \quad O = g(o)$$



Back propagation

Step 3: Calculate E

$$E = \frac{1}{2} \cdot (O - t)^2$$


Step 4: Update weights

$$\Delta w_j = -\epsilon \cdot \frac{\partial E}{\partial w_j}; \Delta v_{\beta} = -\epsilon \cdot \frac{\partial E}{\partial v_{\beta}}$$


$$\frac{\partial E}{\partial w_j} = (O - t) \cdot g'(o) \cdot H_j$$

$$\frac{\partial E}{\partial v_{\beta}} = g'(h_j) \cdot I_k \cdot (O - t) \cdot g'(o) \cdot w_j$$

ANN – early stopping




Cross-validation




Program

ANN




PSSM and SMM




Optimal parameters

- Expected:
 - Small dataset: large β
 - Large dataset: small β
- Unexpected:
 - Small dataset: small β
 - Sequence variance in dataset
 - Restricted binding motif





$$p_{ia} = \frac{\alpha \cdot f_{ia} + \beta \cdot g_{ia}}{\alpha + \beta}$$



Optimal parameters

- Large λ
 - Small dataset
 - Gradient descent based SMM





$$E_{per\ target} = \frac{1}{2} \cdot (O - t)^2 + \frac{\lambda}{N} \cdot \sum_i w_i^2$$

$$E = \frac{1}{2} \cdot \sum_i (O_i - t_i)^2 + \lambda \cdot \sum_i w_i^2.$$



Optimal parameters

- Small dataset:
 - large amount of cycles
 - Low information content
- BLOSUM encoding:
 - small amount of cycles
 - High information content





Performance comparison

- Very low performance: small datasets
 - Not enough data to learn
- PSSM/SMM
 - Large increase in performance with the size of the datasets





Performance comparison

- ANN
 - Good performance on all datasets
 - BLOSUM encoding generally best
 - Sparse vs. BLOSUM: no pattern in dataset size



Performance comparison

- SMM underperformance
 - Sparse vs. BLOSUM
 - Number of iterations for Monte Carlo
 - Divide by variance in sequences - Hobohm



Conclusion

- $ANN > PSSM > SMM$
- Performance generally better on larger datasets

Thank you for your attention