

The **overpic** package

Rolf Niepraschk
(Rolf.Niepraschk@gmx.de)

Version 2.3 – 2026/07/28

1 Introduction

The **overpic** environment is a combination between the **L^AT_EX** `picture` environment and another **L^AT_EX** object like an image used with the command `\includegraphics` of **graphicx** or a **tabular**. The resulting picture environment has the same dimensions as the included object. **L^AT_EX** commands can be placed on the object at any position; setting a grid for the orientation is possible.

2 Usage

Put `\usepackage[options]{overpic}` in the preamble of the document. The following package options are available:

- **abs**: Absolute positioning in multiples of `\unitlength`.
- **percent**: Relative positioning; the longer dimension has value 100. The `\unitlength` will be calculated accordingly. This is the default mode.
- **permil**: Relative positioning; the longer dimension has value 1000. The `\unitlength` will be calculated accordingly.

Other options will be tranfered to package **graphicx**.

overpic (*env.*) `\begin{overpic}[options]{filename} picture code \end{overpic}`

Sets the graphic *filename* and puts the *picture code* on the top of the graphic. The picture code can be any **T_EX** code inclusive other graphics.

The following options are possible:

- **abs**, **percent**, **permil**: The same as the package options (true or false).
- **rel**: Other value as base for relative positioning (e.g. 10000)
- **grid**: Drawing a grid for better orientation (true or false, default: false).
- **tics**: The distance of the grid tics (default: 10).