

The arraycols package*

Antoine Missier
antoine.missier@ac-toulouse.fr

May 4, 2024

1 Introduction

Although the remarkable tabularray package by Jianrui Lyu [1], developed in $\text{\LaTeX}$ 3, offers many new possibilities and great flexibility in composing tables, many users are still familiar with Frank Mittelbach and David Carlisle’s array package [2]. In addition to array, this modest arraycols package introduces new predefined column types for tables and also includes a command for wide horizontal rule drawing. Below is a summary of the column types and macro defined by arraycols, which will be detailed in the following section.

Column definitions	
L	Left adjusted column (applicable in LR mode for array environments or math mode for tabular environment)
C	Centered-adjusted column (similar to L but centered)
R	Right-adjusted column (similar to L but right-adjusted)
$t\{width\}$	Text column of fixed $\langle width \rangle$ (LR mode), similar to p, but with horizontal and vertical centering
x	Centered column in math mode with adjusted height to avoid touching the horizontal rules
y	Left-aligned column in math mode with adjusted height
$z\{width\}$	Centered column in math mode, similar to x, with adjusted height, but with fixed $\langle width \rangle$
T	Centered text column with adjusted width for tabularx environments (calculated like X column)
Z	Centered column for tabularx, similar to T, but in math mode with adjusted height, like x and z
I	Thick vertical rule (1 pt)
$V\{thickness\}$	Vertical rule with variable $\langle thickness \rangle$
Horizontal rules	
$\backslash whline$	Wide horizontal rule (1 pt)

*This document corresponds to arraycols v1.5, dated 2024/05/04. Thanks to François Bastouil for initial assistance with the English translation.