

NAME

ctanify – Prepare a package for upload to CTAN

SYNOPSIS

```
ctanify [--pkgname=string] [--[no]auto] [--tdsonly=filespec ...] [--[no]unixify] [--[no]skip]
[--tdsdir=dirname ...] [--tex=macro_pkg] [--[no]miscify] [--[no]tds] filespec[=dirname] ...
```

```
ctanify [--help]
```

```
ctanify [--version]
```

DESCRIPTION

ctanify is intended for developers who have a $\LaTeX$ package that they want to distribute via the Comprehensive $\TeX$ Archive Network (CTAN). Given a list of filenames, **ctanify** creates a tarball (a *.tar.gz* file) with the files laid out in CTAN's preferred structure. The tarball additionally contains a ZIP (*.zip*) file with copies of all files laid out in the standard $\TeX$ Directory Structure (TDS), which facilitates inclusion of the package in the $\TeX$ Live distribution.

OPTIONS

ctanify accepts the following command-line options:

-h, --help

Output basic usage information and exit.

-V, --version

Output **ctanify**'s version number and exit.

-p *string*, --pkgname=*string*

Specify explicitly a package name. Normally, **ctanify** uses the base name of the first *.ins* or *.sty* file listed as the package name. The package name forms the base name of the tarball that **ctanify** produces.

--noauto

Do not automatically add files to the tarball. Normally, **ctanify** automatically includes all files mentioned in a *.ins* file.

-t *filespec*, --tdsonly=*filespec*

Specify a subset of the files named on the command line to include only in the TDS ZIP file, not in the CTAN package directory. Wildcards are allowed (quoted if necessary), and **--tdsonly** can be used multiple times on the same command line.

At least one filename must be specified on the command line. **ctanify** automatically places files in the TDS tree based on their extension, but this can be overridden by specifying explicitly a target TDS directory using the form *filespec=dirname*. Wildcards are allowed for the *filespec* (quoted if necessary).

ADDITIONAL OPTIONS

The following options are unlikely to be necessary in ordinary usage. They are provided for special circumstances that may arise.

-d *dirname*, --tdsdir=*dirname*

Instead of creating a tarball for CTAN, merely create the package TDS tree rooted in directory *dirname*.

-T *macro_pkg*, --tex=*macro_pkg*

Assert that the files being packaged for CTAN target a $\TeX$ macro package other than $\LaTeX$. Some common examples of *macro_pkg* are *generic*, *plain*, and *context*.

-nou, --no-unixify

Store text files unmodified instead of converting their end-of-line character to Unix format (a single linefeed character with no carriage-return character), even though CTAN prefers receiving all files with Unix-format end-of-line characters.