Dimensional Input Parameter Language

DIPL Language Specification

Ondrej Pego Jaura 

October 2026

Contents

1 DIPL Language Specification — Version 1.1.0 **2**
1.1 Abstract . . . 2
1.2 Introduction . . . 3
1.3 Language Overview . . . 3
1.3.1 Key Characteristics . . . 4
1.4 Language Syntax . . . 4
1.5 File Format . . . 4
1.6 Execution Model . . . 4
1.6.1 Normative Execution Model . . . 4
1.6.2 Implementation Notes (Non-Normative) . . . 5
1.7 Error Handling . . . 6
1.8 Versioning . . . 6
1.9 Reference Implementation . . . 6
1.10 License . . . 6
1.11 Glossary . . . 6

2 Nodes **7**
2.1 Definition . . . 7
2.2 Modification . . . 8
2.3 Declaration . . . 8
2.4 Hierarchy . . . 8
2.4.1 Value nodes . . . 8
2.4.2 Container nodes . . . 8

3 Data Types **11**
3.1 Standard data types . . . 11
3.2 Derived data types . . . 12
3.3 Link nodes . . . 12

4 Values **13**
4.1 Empty values . . . 13
4.2 Scalars . . . 13
4.3 Arrays . . . 13
4.4 Blocks . . . 14
4.5 Tables . . . 14

5 References **15**
5.1 Reference Notation . . . 15
5.1.1 Source and absolute references . . . 15
5.1.2 Relative references . . . 16
5.1.3 Self-reference . . . 16
5.2 Source Declarations . . . 16
5.3 Imports . . . 17
5.4 Injections . . . 18
5.4.1 Value Injection . . . 18

5.5 Identity-preserving links . . . 18
5.5.1 Array and String Slicing . . . 18
5.5.2 Raw Source Injection . . . 19
5.5.3 Source and Unit Declaration Injection . . . 19

6 Expressions **19**
6.1 Logical . . . 20
6.2 Numerical . . . 21
6.3 Templates . . . 22

7 Units **23**
7.1 Standard Units . . . 24
7.1.1 Integer values after unit conversion . . . 24
7.2 Custom Units . . . 24

8 Functions **24**
8.1 Function Calls . . . 25
8.2 Function Arguments . . . 25
8.3 Function Results . . . 25
8.4 Evaluation and Errors . . . 25

9 Properties **25**
9.1 Directives . . . 26
9.1.1 Options . . . 26
9.1.2 Condition . . . 26
9.1.3 Guided setup . . . 27
9.1.4 Format . . . 27
9.1.5 Constants . . . 27
9.1.6 Tags . . . 27
9.1.7 Delimiter . . . 28
9.2 Metadata . . . 28

10 Conditions **30**

11 Schemas **31**
11.1 Declaration and Instantiation . . . 31
11.2 Required metadata . . . 33
11.3 Collection schemas . . . 33
11.4 Nested Schemas . . . 34
11.5 Rules . . . 34

12 Overrides **34**
12.1 Declaration . . . 34
12.2 Nested Paths . . . 35
12.3 Collection and Evaluation . . . 35
12.4 Replacement Values and Units . . . 36
12.5 Conditional Definitions . . . 36
12.6 Host Inputs and Provenance . . . 36

A Formal Grammar **37**

B Syntax Highlighting Fixture **46**

1 DIPL Language Specification — Version 1.1.0

DOI: 10.5281/zenodo.23376301

1.1 Abstract

DIPL (Dimensional Input Parameter Language) is a declarative language for describing structured input parameters for scientific and numerical software. It brings parameter values, data types, physical units, constraints, metadata, and relationships into one human-readable format. This specification defines DIPL's syntax, type

system, expression and unit semantics, schemas, validation, and execution model. It is intended for language users and implementers, and serves as the reference for the SNT implementation. The document includes a formal grammar and examples of the language's main constructs. DIPL aims to make scientific input definitions easier to inspect, validate, reuse, and exchange while preserving the dimensional and structural information that applications need.

Keywords: domain-specific language; scientific computing; configuration language; input parameters; physical units

1.2 Introduction

DIPL (Dimensional Input Parameter Language) is a domain-specific language for describing input parameters used by scientific simulations and numerical software.

Conventional configuration formats such as JSON, YAML, and INI are well suited for representing general-purpose data, but provide little support for concepts that are common in scientific computing. In particular, physical units, dimensional consistency, numerical types, parameter dependencies, and validation rules typically have to be implemented separately by the consuming application.

DIPL addresses these requirements at the language level. It provides a compact notation in which parameter values, units, structure, relationships, and validation rules can be expressed together and subsequently evaluated by a DIPL implementation.

The remainder of this specification defines the syntax and semantics of the language and describes the constructs available for building DIPL documents.

1.3 Language Overview

DIPL (Dimensional Input Parameter Language) is a declarative, strongly typed domain-specific language for defining structured scientific parameters, constraints, and relationships in a human-readable format.

A DIPL document consists of parameter declarations organized into hierarchical blocks through indentation. Each parameter combines:

- a name
- an explicit type
- an optional shape or structure
- a value expression
- an optional unit annotation
- optional properties for metadata, validation, and constraints

```
velocity float32[1,2:] = [[23.45, 23e-34, 45.1]] SI_km/s
    !condition ({.} < {?cfl_limit})

burst_energy float64 = 2.34e5 US_btu
```

A DIPL document is more than a collection of static values. It represents a structured and semantically validated configuration graph in which parameters, expressions, references, units, and constraints work together.

At a conceptual level:

- **Nodes** define the values and hierarchical structure of the configuration.
- **References and expressions** establish dependencies between parameters and allow values to be derived from other values.
- **Links** expose a canonical node through another read-only path without copying its data.
- **Units** provide dimensional information and ensure physical consistency during evaluation.
- **Properties** attach metadata and declarative constraints to the configuration.
- **Schemas** define expected structures and provide a basis for validating complete configurations.
- **Overrides** replace values in an existing parameter model while preserving its declarations and constraints.

This design allows DIPL to represent not only data, but also the semantic relationships and domain-specific rules governing that data. The resulting document can be interpreted both as **data** and as an **executable configuration model**: values can be evaluated, dependencies resolved, and semantic constraints validated by the DIPL interpreter.

1.3.1 Key Characteristics

Strong typing All parameters declare explicit types (e.g., `bool`, `uint32`, `float64`, `str`), enabling predictable behavior, type checking, and validation.

Units-aware computation Values may include physical units, which are automatically normalized and validated during evaluation, allowing dimensional consistency to be maintained throughout computations.

Declarative constraints and metadata Properties such as `!condition` define constraints that must be satisfied for a valid document, while metadata such as `?authors` provides descriptive information about individual nodes.

Hierarchical organization An indentation-based structure allows related parameters to be organized into groups, maps, and lists without additional syntactic overhead.

Referential expressions Parameters can reference other values within the document, allowing expressions to be built from existing data and making dependencies between parameters explicit.

Derived parameters Parameters can be defined in terms of other parameters, allowing simple dependency graphs to be expressed directly within the language.

External references Values and nodes can reference data from external sources, allowing DIPL documents to incorporate information without duplicating it locally.

Composable schemas Schemas provide a mechanism for describing the expected structure and constraints of data, supporting consistent definitions and validation across documents.

Guided setup annotations The optional `!setup` directive marks typed values for interactive input by supporting tools. Input controls can be inferred from the declared type, `!options`, `!labels`, units, and existing validation properties.

1.4 Language Syntax

The following chapters describe the syntax of the Dimensional Input Parameter Language. They introduce the individual language constructs used to define, represent, reference, and process scientific input data.

The syntax is presented from the fundamental building blocks of the language towards more advanced constructs. The chapters cover nodes and data types, values and units, references and expressions, as well as functions, properties, conditions, and schemas.

The following topics are covered:

- Nodes — the fundamental building blocks of a DIPL document.
- Data Types — the types available for representing data.
- Values — how values are represented and assigned.
- References — how data can refer to other nodes and sources.
- Expressions — expressions for deriving and transforming values.
- Units — dimensional quantities and their units.
- Functions — functions available for processing and transforming data.
- Properties — metadata and properties associated with nodes.
- Conditions — conditional definitions and constraints.
- Schemas — schemas for defining and validating structured data, including required metadata constraints.
- Overrides — value replacements applied before normal evaluation.

1.5 File Format

The source file MUST have an extension of either `.dip` or `.dipl`. Nodes with the smallest indentations in the file should be considered as the root nodes with an indentation level of 0.

1.6 Execution Model

1.6.1 Normative Execution Model

Evaluation of a DIPL document MUST proceed in the following stages, in order:

1. **Parsing**
   The input MUST be parsed into a structured representation of nodes. This includes processing indentation,

node types, and structural relationships. All top-level override regions MUST be collected at this stage, before normal node evaluation. Duplicate override targets MUST result in an error.

2. **Dependency Resolution**
   Value references MUST be resolved into a directed acyclic graph (DAG) of node dependencies.
   - An unresolved source or ordinary value reference MUST result in an error. The `def` and `ndef` operators test whether a node has a non-`none` value in an already-resolved domain at the point of evaluation. A missing node, a declaration without an assigned value, or an explicit `none` value yields `false` for `def` and `true` for `ndef`. These operators do not suppress errors resolving the source domain.
   - Cyclic dependencies MUST result in an error.
3. **Reference Evaluation**
   All ordinary reference expressions (e.g. `{<source>?<path>}`, `{?<path>}`) MUST be resolved to their corresponding values or node sets. `def` and `ndef` evaluate the referenced path's definition state as described above. Remote sources MUST be processed independently before their results are used.
4. **Expression and Value Evaluation**
   All node values MUST be evaluated, including:
   - scalar values
   - arrays and structured values
   - expressions involving references

   For an overridden node, only its replacement value MUST be evaluated, at the target declaration. Its dependencies MUST already be available then. The original value MUST NOT be evaluated. Subsequent dependents and conditional definitions MUST use the replacement value. These rules are defined in the Overrides chapter. If evaluation fails (e.g. invalid operations or unresolved values), evaluation MUST fail.
5. **Unit Normalization**
   All evaluated values MUST be converted to the canonical unit representation defined in the Units specification. Unit incompatibility MUST result in an error.
6. **Condition Evaluation**
   All conditions MUST be evaluated using the normalized value of the node. The `{.}` self-reference refers to this value.
   - If a condition evaluates to false, the node MUST be considered invalid.
   - If condition evaluation fails, evaluation MUST fail.
7. **Validation**
   All validation rules MUST be applied, including:
   - option constraints
   - value format checks
   - structural constraints
   - schema metadata constraints against effective metadata after schema defaults, instance metadata, and supported overrides have been applied. `required` MUST accept an explicitly present empty value; `nonempty` MUST reject empty or whitespace-only strings and empty or blank list entries.

   Any violation MUST result in an error.

Except for host-defined functions, conforming implementations MUST produce identical results for identical inputs and sources. Functions in DIPL are exception from this rule, because they are user defined and depend on the particular implementation and use case. If any stage fails, evaluation MUST terminate with an error.

1.6.2 Implementation Notes (Non-Normative)

A DIPL processor may implement the above stages using steps such as:

- parsing code lines into nodes
- combining multiline string blocks into single strings (e.g. text wrapped in `"""`)
- replacing special symbols with temporary markers (e.g. `\n`, `\'`, `\"`) and restoring them later
- determining node types (e.g. group, value, case)
- constructing node hierarchy and full names (e.g. `foo.bar.baz`)
- assigning property nodes to preceding value nodes
- validating indentation and structural consistency
- resolving references and expanding nodes

- evaluating expressions and parsing values (e.g. scalars like `34e+3`, arrays like `[[1,3],[4,5]]`)
- parsing and applying unit expressions (e.g. `kg/s`)
- applying modifications to existing nodes
- evaluating conditional branches and case expressions
- validating nodes against constraints (options, conditions, formats)

These steps are provided for guidance only. Implementations MAY use different internal strategies, provided the observable behavior conforms to the normative execution model defined above.

1.7 Error Handling

The following conditions MUST result in evaluation failure:

- unresolved source or node reference
- cyclic dependencies
- invalid query path
- type mismatch
- unit incompatibility
- expression evaluation failure
- duplicate, invalid, or unresolved override target
- a violated schema metadata constraint

Errors MUST be deterministic and MUST NOT be ignored.

1.8 Versioning

Language versioning is independent of any particular implementation. Each implementation MUST explicitly declare the version of the DIPL language it supports.

Future versions of the language MAY introduce extensions or modifications. Backward compatibility SHOULD be preserved where feasible.

Version 1.1.0 adds the valueless `!setup` property. Documents that do not use this property retain their Version 1.0.0 behavior.

1.9 Reference Implementation

A reference implementation of the DIPL language is provided as part of the SciNumTools v3 project.

The reference implementation includes:

- A C++ implementation
- Python bindings for integration and scripting use cases

Project: SciNumTools v3
Repository: https://github.com/scinumtools/snt3
Documentation: https://scinumtools.github.io/snt3/
Issues: https://github.com/scinumtools/snt3/issues

Independent implementations of the DIPL language (e.g., in Rust or Julia) are encouraged and welcome, and can be added to this list on request.

1.10 License

This specification is distributed under the MIT License. The license text is available in the SciNumTools v3 repository.

1.11 Glossary

Term	Meaning
Node	Fundamental element of a DIPL document
Value node	Node containing a typed value
Container node	Node containing child nodes
Path	Fully-qualified node path in the hierarchy
Group	Named container whose children are addressed by name

Term	Meaning
Map	Container whose children are addressed by key
List	Container whose children are addressed by index
Schema	Reusable structural contract for nodes
Definition	Statement creating a node and assigning its value
Declaration	Statement creating a typed node without a value
Modification	Statement assigning a value to an existing node
Override	Collected value replacement evaluated at an existing node's declaration
Source	Named external DIPL/text domain
Reference	Expression identifying existing nodes or external content
Import	An operation that inserts referenced nodes into the current node hierarchy
Injection	An operation that injects value to a node from local, or remote sources
Unit	Named physical or dimensional quantity
Expression	Construct that evaluates to a value
Property	Information attached to a node
Condition	Boolean validation rule
Metadata	Non-semantic descriptive information attached to a node

2 Nodes

The DIPL language distinguishes three different ways to create a parameter, depending on which parts of the parameter node are specified. A parameter can be fully defined, meaning that all node components—name, type, value, and optionally shape and units—are provided. Alternatively, a parameter can be declared by specifying only its name, type, and optional shape/units. After a parameter has been either defined or declared, its value component can be modified. Additionally, nodes can be ordered into a hierarchical structure by using indents.

2.1 Definition

All members of definition are separated with at least one empty space, and their order is not interchangeable.

Indentation is at the beginning of a line and it determines node hierarchy. Every new indentation level should be separated by two empty spaces.

Node **names** are formed from letters, numbers, underscores and hyphens. Dots have a special function in names, because they separate atomic (parent and child) node names.

There are four main **data types** in DIPL that are based on data types used in Python language: boolean (`bool`), integer (`int`), float (`float`) and string (`str`).

Node **values** are separated from the left-hand members by an equal sign. Unquoted values consist only of non-whitespace characters. If a value contains spaces, it must be enclosed in double quotes. If a node value spans multiple lines, a block must be used. A node value may be continued on the following line by placing an equal sign at the beginning of a line indented exactly two spaces further than the node definition. DIPL parameter values are described in detail in a separate section.

```
street str = "Fifth Avenue"
number int = 350
sizes float
  = [3.14, 2.718, -1.25, 0.577, 42.0, -7.5, 1.618, 0.001, 12.345, -0.333]
```

The two data types that support **units** are integers and floats. Units are written directly after a node value and are separated with an empty space. More detailed description of units is given in a chapter about units. In this subsection, we only describe basic syntax with respect to the nodes.

```
weight int = 87 kg
height float = 185 cm
```

Comments are always at the end of lines and start with a hash sign. It is also possible to use comments on empty lines to describe the code.

```
resolution int = 32  # low resolution
```

2.2 Modification

The first occurrence of a node is called a definition. All subsequent occurrences of a node with the same name are called modifications. The last modification is the one used in the parameter output. The data type of node needs to be set in each definition; however, it can be omitted in subsequent modifications. If a node is a dimensional parameter, units have to be set in a definition. One can use different units of the same dimension in modifications; however, the final value of the node will always be converted into units set by the definition.

```
size float = 70 cm     # definition
size float = 80 cm     # modifying only value
size = 90 cm           # omitting datatype
size = 100             # omitting units
size = 1 pc            # using different units of length

# Final parameter value is:
# size = 3.086e18 cm
```

2.3 Declaration

Declaration in DIPL is a special case of definition where equal sign and value part is not specified. The value must be later set in subsequent DIPL code using modifications, otherwise code will not be valid. Similarly to definitions, modification units are automatically converted to their declared units.

```
weight float kg    # declaration
weight = 2.3 t     # modification

# Final parameter value is:
# weight = 2.3e3 kg
```

2.4 Hierarchy

DIPL nodes are organized in a hierarchical way using indentation, i.e. number of empty spaces before nodes. **Parent** nodes have lower indentation as their **children** nodes. **Siblings** are nodes which share a common parent and indentation level. Multiple levels of hierarchy are also allowed, and there can be empty lines between the nodes. The number of empty spaces for each indentation level is two and tabs are not permitted.

2.4.1 Value nodes

```
grandfather str = "John"    # parent of Peter and Cintia
  father str = "Peter"      # John's child, Cintia's sibling
                            # Ben's and Lucia's parent
    son str = "Benjamin"    # Peter's child
    daughter str = "Lucia"  # Peter's child
  aunt str = "Cintia"       # John's child, Peter's sibling
```

Both parent and children nodes can be either definitions, modifications or declarations. Value nodes may have child nodes, but they cannot apply schemas themselves. Schema application is reserved for groups and collection items; a schema may, in turn, define value nodes and child containers. Nodes in the above example are equivalent to the fully-qualified **path notation** given below.

```
grandfather str = "John"
grandfather.father str = "Peter"
grandfather.father.son str = "Benjamin"
grandfather.father.daughter str = "Lucia"
grandfather.aunt str = "Cintia"
```

2.4.2 Container nodes

Besides basic value nodes, DIPL supports three types of container nodes.

Structure	Example	Semantics	Similar in C++	Similar in Python
Group	`foo`	Named child nodes	`struct`	`@dataclass`
Map	`foo[key]`	Child nodes addressed by key	`std::map`	`dict`

Structure	Example	Semantics	Similar in C++	Similar in Python
List	`foo[]`	Child nodes addressed by index	`std::vector`	`list`

Unlike value nodes, container nodes do not directly hold values. Instead, they organize child nodes into hierarchical structures. Depending on the container type, child nodes are addressed by name, key, or index.

Groups

Nodes may be organized into logical hierarchies using a special container node called a **group**.

Unlike value nodes, group nodes do not directly store values. Their sole purpose is to organize child nodes into a logical structure. The group's name becomes part of the fully-qualified path of all descendant nodes.

During parsing, node names are expanded into fully-qualified paths by prepending the names of all parent groups, separated by dots (`.`).

Node names may themselves contain dot-separated path segments. Both hierarchical notation and explicit path notation are equivalent and may be freely combined.

```
family                          # group node
  father str = "Peter"
    son str = "Benjamin"        # hierarchical notation

  father.daughter str = "Lucia" # mixed notation

family.aunt.dog str = "Lassie"  # explicit path notation
```

The example above produces the following fully-qualified node paths:

```
family.father = "Peter"
family.father.son = "Benjamin"
family.father.daughter = "Lucia"
family.aunt.dog = "Lassie"
```

Collections

Collections extend group nodes to represent associative and sequential data structures.

Explicit declaration of a map or list collection is optional and is used only when defining collection schemas. A collection can be explicitly declared by adding the corresponding data type keyword immediately after the group node name:

```
cars map    # declaration of a map collection
ships list  # declaration of a list collection
```

In most cases, explicit declaration is unnecessary. A collection is implicitly established by its first item. A collection item is specified by appending square brackets to the node name:

- `name[key]` denotes an item in a keyed collection (**map**).
- `name[]` denotes an item in an indexed collection (**list**). Item indices are assigned implicitly, starting at `0`.

A collection path shall use a consistent collection type. Once a collection has been established as keyed or indexed, all subsequent items at the same path shall use the same collection type. Mixing keyed and indexed items within a single collection is not permitted.

Collections may be nested.

Collection selectors are interpreted according to the type of the referenced collection.

When resolving a fully-qualified path, all parent collections shall already exist. Since the container type of each parent node is therefore known, selectors of the form `[value]` can be unambiguously interpreted either as map keys or list indices.

Only the final path segment may create a new node or collection item. Collection items are container nodes: they cannot declare a DIPL value directly. Place typed value nodes beneath the item group instead.

```
basket                      # group

  food map                  # declaration (optional)
```

```
  food[vegetables]          # keyed collection
    carrots float = 0.5 kg
    potatoes float = 2 kg

  food[fruits]
    apples int = 3
    water_melons int = 1

    berries list            # declaration (optional)

    berries[]               # indexed collection
      name str = "strawberry"
      weight float = 300 g

    berries[]
      name str = "cherry"
      weight float = 500 g
```

Equivalent fully-qualified path notation:

```
basket.food[vegetables].carrots float = 0.5 kg
basket.food[vegetables].potatoes float = 2 kg

basket.food[fruits].apples int = 3
basket.food[fruits].water_melons int = 1

basket.food[fruits].berries[0].name str = "strawberry"
basket.food[fruits].berries[0].weight float = 300 g

basket.food[fruits].berries[1].name str = "cherry"
basket.food[fruits].berries[1].weight float = 500 g
```

Equivalent JSON representation:

```
{
  "basket": {
    "food": {
      "vegetables": {
        "carrots": 0.5,
        "potatoes": 2.0
      },
      "fruits": {
        "apples": 3,
        "water_melons": 1,
        "berries": [
          {
            "name": "strawberry",
            "weight": 300
          },
          {
            "name": "cherry",
            "weight": 500
          }
        ]
      }
    }
  }
}
```

Collection items are accessed and modified in the same manner as regular nodes. For indexed collections, the item index shall be specified explicitly.

```
basket.food[fruits].apples = 3
```

```
basket.food[fruits].berries[1].weight = 250 g
```

3 Data Types

In this section we describe standard and derived data types that can be used in DIPL code. Standard types are categorized based on their value types into **booleans**, **integer numbers**, **floating-point numbers** and **strings**.

Numerical types may have derived types that specify additional representation properties such as **width**, **precision**, or **signedness**.

For integer types, derived types include signed and unsigned variants with different widths, such as `int8`, `int16`, `int32`, `int64`, `uint8`, `uint16`, `uint32`, and `uint64`.

For floating-point types, derived types specify the floating-point precision, such as `float16`, `float32`, and `float64`. `float16` is optional: an implementation may provide the type when its compiler and runtime support a usable 16-bit floating-point representation. The special case `float128` is a separate standard type, because its support on different platforms varies.

3.1 Standard data types

DIPL provides a minimal set of four built-in scalar data types. These types are designed to cover the most common use cases while keeping the language simple and predictable. Each type represents a distinct category of values and enforces basic constraints on how data is stored and interpreted.

Below is an overview of the supported scalar types and their typical usage.

Boolean (`bool`)

The Boolean type represents logical truth values. It is primarily used for control flow, conditional evaluation, and state representation.

```
day bool = true
night bool = false
```

Integer (`int`, `int32`, or `uint`, `uint32`)

The Integer types represent whole numbers without fractional components. The signed Integer type (`int`, or equivalently `int32`) has a signed 32-bit semantic range, allowing both positive and negative values within a fixed range. The unsigned Integer type (`uint`, or equivalently `uint32`) has an unsigned 32-bit semantic range and therefore represents only non-negative values. Assignments with units must remain whole numbers within that range after conversion to the node's units.

In the reference implementation, Integer values are internally represented using signed or unsigned 64-bit integers (`int64_t` or `uint64_t`), respectively.

```
year int = 2023
count uint = 42
```

Float (`float`, or equivalently `float64`, internally represented as a 64-bit floating-point value)

The Float type represents real numbers with fractional components. It has a 64-bit floating-point semantic representation, providing a wide range of values, including very large and very small numbers. In the reference implementation, Float values are internally represented using `double`. Finite values assigned to a floating-point node are checked against the declared type's range, even if its internal storage has a wider range. Zero is allowed; a nonzero magnitude smaller than the type's smallest positive subnormal value or larger than its largest finite value is rejected. This check applies to literals, arrays, evaluated expressions, references, and overrides before narrowing to the declared type.

```
duration float = 10             # integer form
weight float = 23.3             # floating form
distance float = 2.3e20         # scientific form
```

String (`str`)

The String type represents sequences of characters. In DIPL, strings are enclosed in double quotes. Triple double quotes can contain literal line breaks. It is used for textual data, labels, and any form of human-readable content.

Adjacent quoted strings inside parentheses are concatenated without adding spaces or newlines. Use `\n` inside a segment when a newline is wanted. A segment prefixed with `f` interpolates references; ordinary segments remain literal even when they contain `{{...}}`.

```
name str = "Tina"
message str = (
  "Hello, "
  f"{{?name}}"
  "!\nWelcome."
)

country str = "United States"  # single line text
address str = """
350 Fifth Avenue
NY 10118
"""                            # text on multiple lines
```

3.2 Derived data types

When DIPL parses parameters for programming languages such as C/C++ and Fortran, it is sometimes necessary to explicitly specify the precision and representation of integer and floating-point values. This is achieved through the use of derived data types.

Derived data types are semantically related to their corresponding standard types but may use a different internal representation. They carry additional metadata describing properties such as signedness and precision. Multiple DIPL types may share the same internal representation while retaining distinct semantics.

In C/C++, a string is typically represented as a sequence of characters. In DIPL, `char` and `str` are distinct types. The `char` type represents a single unsigned 8-bit character value, while `str` represents a sequence of characters. This distinction facilitates interoperability with C/C++ without imposing C/C++'s implementation- defined `char` signedness on DIPL.

The `byte` and `char` types are optional 8-bit types representing a single byte. Both are internally represented by `uint8_t`. The `byte` type represents an unsigned 8-bit numeric value intended for raw binary data, while `char` represents an unsigned 8-bit character value. Neither type specifies an inherent text encoding.

List of standard and derived data types

Standard	Derived	Internal representation
`bool`		`uint8_t`
`int`	`int8`, `int16`, `int32`, `int64`	`int64_t`
`uint`	`uint8`, `uint16`, `uint32`, `uint64`	`uint64_t`
`float`	`float16` (optional), `float32`, `float64`	`double`
`float128`		implementation-defined
`char`		`uint8_t`
`byte`		`uint8_t`
`str`		`string`

> [!NOTE] The `float16` and `float128` types are optional. Many platforms and compilers do not provide native support for 16-bit and 128-bit floating-point arithmetic. An implementation that does not support `float16` MUST reject it as an unsupported datatype; an implementation that supports it MUST document its representation, conversion, and arithmetic behavior.
>
> The `byte` and `char` types are optional. Both types are unsigned 8-bit types and are internally represented by `uint8_t`. `byte` values may be assigned from integer literals, while `char` values may be assigned from character or string literals. Neither type specifies a text encoding.

3.3 Link nodes

The `link` type is an identity-preserving node relation, not a scalar value type. It stores a target path and provides read-only traversal through that path; see References.

4 Values

4.1 Empty values

Similarly, as in Python, DIPL parameters can also be set empty using a special keyword `none`. Operations with empty parameters conform to basic Python rules and may lead to corresponding warnings, or errors. DIPL parameters with `none` values are considered to be fully defined, rather than only declared.

```
john
  car str = none
```

4.2 Scalars

Nodes with a single boolean, number or string value are called scalar nodes. If a node is scalar at its definition, it can be modified only with one value, or as empty. Example of scalar node values were already shown in section about data types.

```
hair bool = false
name str = "John"
age int = 73
height float = 173 cm
```

4.3 Arrays

Nodes can also store multiple values in arrays. Dimensionality of such arrays have to be specified next to the type using bracket notation.

Dimensionality of arrays

Example,	Description
`[:]`	Array can have arbitrary number of values
`[3:]`	Array must have minimum of 3 values
`[:5]`	Array must have maximum of 5 values
`[1:4]`	Array must have between 1 and 4 values
`[6:,:8,2:7]`	Settings of individual dimensions are separated by comma

Parsing of array values is handled by a custom parser that extracts individual values and array shape. Final values of nodes are automatically validated according to defined conditions.

```
data1 bool[4]   = [true,false,false,true]  # exactly four values
data2 int[:]    = [0,1,2,3,4,5,6]          # any number of values
data3 float[3:] = [0,1.34,1.34e4]          # at least 3 values
data4 float[:4] = [0,1.34,1.34e4]          # maximum of 4 values
data4 str[3:4]  = ["John","Peter","Simon"] # between 3 and 4 values
```

Multiple values above are written in a tight notation without empty spaces in between the values. Loose notation, with empty spaces, is also permitted. Additionally, arrays can be parsed from string values, wrapped into double quotes.

```
data1 bool[4]   = [true, false, false, true]
data2 int[4]    = "[1, 2, 3, 4]"
data3 str[3:4]  = "[\"John\", \"Peter\", \"Simon\"]"
```

Multidimensional arrays are defined similarly using nested bracket notation. Irregular array shapes, in which items along the same dimension contain different numbers of elements, are not allowed. Array values may span multiple lines.

```
matrix int[2,3] = [
  [0,1,2],
  [3,4,5]
]
```

Node units apply to all values in an array.

```
mass float[2:,:2] = [[25,50],[34.2,95.1],[1e3,1e4]] kg
```

4.4 Blocks

If node values are large or span multiple lines, block notation can be used. Block notation encloses values in triple quotation marks, similarly to Python. For numerical data types, units can be specified after the closing quotation marks.

An important advantage of parsing arrays from strings is that large datasets can be imported from external files using raw imports. See the chapter on references for more information.

```
# velocity field
velocity int[4,4] = """
[[ 0, 1, 2, 4],
 [ 5, 6, 7, 8],
 [ 9,10,11,12],
 [13,14,15,16]]
""" km/s   # units are optional for numerical data types

# large text
text str = """
This simulation models the transport of a passive scalar
in a three-dimensional domain. The numerical solver uses
a finite-volume discretization with configurable spatial
and temporal resolution.

Input parameters define the computational domain,
boundary conditions, material properties, and solver
settings. Physical units and parameter constraints are
validated before the simulation begins.
"""
```

4.5 Tables

When working with large amounts of data, presenting the information in a table can be more concise and easier to read. For this purpose, a dedicated node type called `table` is provided. This data type parses DIPL nodes from tabulated datasets that are supplied as a block value. As a convention, imported tabulated data files should have an extension `.dipt`.

The table structure closely resembles the standard CSV format but uses a specialized header syntax. The table header contains node declarations corresponding to the columns of the table. Each declaration must begin on a new line and must not be indented.

The table data section is separated from the header by a line containing three minus signs (`---`). Within the table body, individual values are separated by a single space. Alternative delimiters can be specified using the `!delimiter` node option, as described in the chapter on node properties.

```
output table = """
snapshot int
time float s
intensity float W/m2
---
0 0.234 2.34
1 1.355 9.4
2 2.535 3.4
3 3.255 2.3
4 4.455 23.4
"""
```

Table notation above is equivalent to:

```
output
  snapshot int[5] = [0,1,2,3,4]
  time float[5] = [0.234,1.355,2.535,3.255,4.455]
  intensity float[5] = [2.34,9.4,3.4,2.3,23.4] W/m2
```

[!NOTE] Table nodes can be declared similarly to other value nodes and defined later. This is especially useful when using `schemas`.

5 References

References have two main applications. One can either import some already parsed DIPL nodes into a new location, or inject other node values or contents of text files into a new node. Besides the two cases, references are also used in conditions and condition properties that are explained in a separate chapter.

5.1 Reference Notation

A DIPL reference identifies either content from a source or a node within a domain. A reference consists of an optional source identifier and an optional path, separated by `?`. The `.` symbol has different meanings depending on its position within a reference: within a path, it separates hierarchical node names; at the beginning of a relative reference, it determines the reference level; at the end of a path, it selects the complete subtree rooted at the target node rather than the node itself; and alone, `{.}`, it denotes a self-reference to the current node.

5.1.1 Source and absolute references

The following forms are absolute references:

Reference	Meaning
`{source}`	Raw content of `source`
`{?path}`	Value of the node `path` in the local domain
`{?path.}`	All descendants of `path` in the local domain
`{?}` / `{?.}`	Complete source node tree in the local domain
`{source?path}`	Value of the node `path` in `source`
`{source?path.}`	All descendants of `path` in `source`
`{source?}` / `{source?.}`	Complete source node tree in `source`

The `?` separates the source identifier from the node path. If the source component is omitted, the reference targets the **local domain**, consisting of the nodes parsed from the current DIPL file.

A path without a trailing `.` MUST resolve to a single node. A path ending in `.` selects the complete subtree rooted at the target node, including all descendant nodes recursively, and therefore produces a node set. A path MUST resolve to an existing node; otherwise evaluation MUST fail. A node set used where a single value is required MUST also cause evaluation to fail. The trailing `.` MAY be omitted when the entire source node tree is imported (`{?}`, `{source?}`). In these cases, the omitted trailing `.` is semantically equivalent to the `?` symbol.

A reference of the form {source} has no path component and returns the raw content of the referenced source as a string. Node-based access is provided only when a path component is specified. A referenced DIPL source is processed as a separate remote domain.

Absolute references can therefore be used both to **import nodes** and to **inject values**:

```
driver
  {?child}                      # single local node
  {garage?worker}               # single remote node

passengers
  {?family.}                    # local subtree
  {tourists?family.}            # remote subtree

sites
  {?.}                          # all local nodes
  {london?.}                    # all remote nodes
  # can be used also without trailing dot: {?} and {london?}

corpus str = {book}             # raw source content
chapter str = {?introduction}   # local node value
citation str = {law?paragraph}  # remote node value
```

The expected result type MUST be compatible with the context in which the reference is used.

5.1.2 Relative references

A relative reference resolves its path against a node in the current node hierarchy:

```
{.<path>}
{..<path>}
{...<path>}
...
{.<path>.}
{..<path>.}
{...<path>.}
...
```

The number of leading dots determines the reference level:

- `{.<path>}` resolves `path` relative to the current node;
- `{..<path>}` resolves `path` relative to the parent;
- `{...<path>}` resolves `path` relative to the grandparent;
- in general, **N** leading dots resolve the path relative to the node **N − 1** levels above the current node.

As with absolute references, a trailing `.` selects the complete descendant subtree rather than a single node.

A relative reference MUST NOT traverse beyond the root node. Such a reference is invalid and MUST result in an error.

```
uncle str = "John"
aunt str = "Jessica"
father str = "William"
  daughter str = {..aunt}
  son str = "Eliah"
    grandson str = {...uncle}
brother-in-law str = {.father}
```

Here `{..aunt}` resolves `aunt` from the parent context of `daughter`, while `{...uncle}` resolves `uncle` from the corresponding ancestor context of `grandson`. `{.father}` resolves `father` relative to the hierarchy containing `brother-in-law`.

5.1.3 Self-reference

`{.}` is a special self-reference and is distinct from `{.<path>}`. It refers to the **fully evaluated value of the current node** and is valid only within condition properties.

Before `{.}` is evaluated, the current node MUST have undergone:

1. resolution of all references;
2. evaluation of all expressions; and
3. normalization to the canonical unit representation defined by PUEL.

The resulting value retains its complete type information, including dimensionality and unit.

If evaluation of the current node fails, including because of an unresolved reference, type error, or unit incompatibility, `{.}` is undefined and evaluation of the containing condition MUST result in an error.

```
speed int = 78 kph
  !condition ({.} < 80 kph)
```

`{.}` MUST NOT be used outside condition properties.

5.2 Source Declarations

Sources are named using the `$source` declarator:

```
$source name = "path/to/file.dip"
```

A source declaration associates a source identifier with a file path. The source may subsequently be referenced any number of times using the absolute reference forms described above.

Sources declared inside a DIPL file MUST resolve their paths relative to the location of that DIPL file.

Implementations SHOULD additionally support defining sources through the host environment (code interface). Source paths supplied through the code interface MUST be interpreted relative to the calling context.

For example:

```
$source garage = "vehicles/garage.dip"
$source tourists = "people/tourists.dip"
$source book = "texts/book.txt"

driver
  {garage?worker}

passengers
  {tourists?family.}

corpus str = {book}
```

Thus, `$source` declarations establish the mapping between source identifiers and external files, while reference notation determines whether the reference accesses raw source content, a node value, a node subtree, or the evaluated value of a node in the current hierarchy.

5.3 Imports

Imports can be used to insert referenced nodes directly into the current DIPL hierarchy. Name paths of imported nodes are embedded into the current node hierarchy as shown in the following examples.

```
icecream
  waffle str = "standard"
  scoops
    strawberry int = 1
    chocolate int = 2

bowl
  {?icecream.scoops.}       # select all children nodes
plate {?icecream.waffle}    # select a specific node
```

The node hierarchy above is equivalent to the one given below.

```
icecream.waffle = "standard"
icecream.scoops.strawberry = 1
icecream.scoops.chocolate = 2
bowl.strawberry = 1
bowl.chocolate = 2
plate.waffle = "standard"
```

The example above demonstrates importing local nodes; the same mechanism applies to external DIPL files. In this case, a source name must be specified before the question mark.

```
$source pantry = "pantry.dip"

bag {pantry?.}                # import all nodes
bowl
  {pantry?fruits}             # selecting a specific node
  {pantry?veggies.potato}     # selecting a specific subnode
plate {pantry?veggies.}       # selecting all subnodes
```

So far, we have shown how to import regular nodes from a local or remote source. It is, however, also possible to import sources and custom units in the similar way. The request can select either one `{<source>?<path>}` or all `{<source>?.}` sources/units.

> [!NOTE] Request path is in this case not a node path but name of a source/unit.

Importing sources/units enables users to dynamically modify numerical code units and setting scripts via their DIPL.

```
$source init = "initial/settings.dip"
$source {init?.}           # all sources of 'init' are imported
$unit {units?.}            # all units are imported from an imported source 'units'
weight float = 23 mass     # using imported unit
```

5.4 Injections

Injections provide values to node definitions and modifications. They do not insert complete nodes or node sets.

5.4.1 Value Injection

A valid value injection MUST resolve to either:

- a single node, referenced without a trailing `.`;
- raw source content, referenced without a path.

When a node is referenced, its value is injected into the receiving expression and is subject to the type, dimensionality, and unit rules of that expression.

```
pop float = 5 km
foo float = 34 cm
bar float = {?foo} m    # resulting value is 0.34 m
baz float = {?foo}      # dimension mismatch
foo = {?pop}            # modification results in 500000 cm
```

Values can also be injected from remote DIPL sources:

```
$source pressure = "pressures.dip"
pressure float = {pressure?magnetic}
```

For injections, a path always identifies the node whose **value** is to be injected. Unlike node imports, injection paths MUST NOT select a node set.

5.5 Identity-preserving links

A link stores a source name and target path. It does not copy the target node or its descendants. Reads and path traversal through the link reach the canonical node, while the link keeps its own requested path and declaration location.

```
ontology
  concepts map
  concepts[body]
    label str = "body"

featured map
featured[body] link = {?ontology.concepts[body]}
```

The link may target a local node with `{?path}` or a named source with `{source?path}`. Targets must identify one node, without a trailing dot. A missing target or a chain of links that forms a cycle is an error in a live DIPL evaluation. Remote links resolve when the named source is loaded; a missing source or target is an error.

Links are read-only aliases. A value reached through a link may be read, but a definition, modification, or override must use its canonical path. A link to a group, map, list, or collection item exposes its descendants and collection items through the alias path. A link itself has no scalar value.

DIPH5 v3 stores the link's source name and target path, as well as the exact source bytes. Loading an archive restores the evaluated nodes, but does not reparse its named sources into executable source environments. Following a remote link therefore reports it as unresolved; local links continue to resolve from the stored nodes.

5.5.1 Array and String Slicing

Array values can be injected directly or sliced to match the required dimensions of the receiving node. Strings and arrays use the same slicing notation as Python.

A single array element can be selected:

```
sizes float[3] = [34,23.34,1e34] cm
mysize float = {?sizes}[1]
```

A range of elements can be selected:

```
masses float[2,2] = [[34,23.34],[1,1e34]] cm
mymass float[2] = {?masses}[:,1]
```

Strings can be sliced in the same way:

```
person str = "Will Smith"
surname str = {?person}[5:]
```

The resulting values are:

```
sizes = [3.400e+01, 2.334e+01, 1.000e+34]
mysize = 2.334e+01
masses = [[34,23.34],[1,1e34]]
mymass = [23.34,1e34]
person = "Will Smith"
surname = "Smith"
```

5.5.2 Raw Source Injection

Raw source injection provides a convenient way to keep large text or data blocks in external files. This separates data from the DIPL structure and makes both the source and the data easier to maintain.

When a reference contains no `?` path component, the referenced source is injected as text rather than as a node list.

```
$source velocity = "velocity.txt"
$source outputs = "outputs.txt"
$source message = "message.txt"

velocity int[3,4] = {velocity} km/s    # import an array
outputs table = {outputs}              # import a table
message str = {message}                # import text
```

The receiving node is responsible for interpreting the injected text according to its declared type.

5.5.3 Source and Unit Declaration Injection

Values used by `$source` and `$unit` declarations can themselves be injected from nodes. In these declarations, the injected value supplies the declaration argument rather than the value of an ordinary node.

For `$source`, the referenced node MUST contain a string. For `$unit`, the referenced node MUST contain a floating-point or integer value.

```
refs str = "path/to/sources.dip"
$source refs = {?refs}

mass float = 1 kg
$unit mass = {?mass}
```

In both cases, the path in the injection refers to the **value of a node**. Injection paths therefore differ from node imports: injections always request a node value and cannot request a node set.

6 Expressions

Node values can also be defined indirectly using expressions. Expression values consist of multiple values combined with mathematical expressions wrapped in additional parentheses, while they can span on multiple lines. The code will be automatically wrapped into a single line based on the balance of the parentheses

The outer parentheses identify the value as an expression. Expressions assigned to `bool` nodes, used by `!condition`, or used by `@if` and `@elif` must be logical expressions. Expressions assigned to integer or floating-point nodes must be numerical expressions.

```
result float = (
  12 + 3.43 - ( 6 * 7.89 ) / 1.2e3
)
```

```
# result = 15.39055
```

There are 4 different types of expressions in DIPL. Three of them (logical, numerical and textual, i.e. templates) are described below. Dimensional expressions, i.e. units, are described in a separate chapter.

> [!NOTE] All but unary operators used in expressions must be separated from values with at least one empty space.

Possible input values used by expressions are summarized in the following table:

Input values

Schema	Name	Example
`<bool>`	boolean	`true/false`
`<num>`	numerical	`24 cm`
`<ref>`	reference	`{?energy}`
`<expr>`	expression	`(12 cm == {?width} && true)`

Operators summarized below are evaluated according to their priority from highest `1` to lowest `6`, and can be nested accordingly.

6.1 Logical

Logical expressions are used to generate values for boolean nodes. The expressions can be composed of multiple nested logical operators that always return a true or false value.

An example of a logical expression is given below.

```
a bool = true
b float = 23.43 cm
c bool = (false || ( {?b} == 23.43 cm || ~{?a} )
          && {?a} || ndef( {?c} ))
# Node 'c' will be evaluated as 'true'
```

Expression operators evaluate only boolean values, either given directly or as a result of a nested expression.

Parentheses

Syntax	Priority	Description
`(<expr>)`	2	Parentheses operator evaluates expression `A` in a separate thread and returns its value
`def( <ref> )`	1	Returns true if the referenced node currently has a non-`none` value
`ndef( <ref> )`	1	Returns true if the referenced node is missing or currently has no non-`none` value

Numerical predicates

These functions inspect the evaluated numerical value, including values with units. Each returns one boolean: `has_*` is true when any element matches, and `all_finite` is true when every element is finite. They accept integer and floating-point scalars or arrays, including the `{.}` self-reference inside `!condition`. They inspect the value, not its uncertainty.

Function	Meaning
`has_nan(x)`	At least one element is NaN.
`has_inf(x)`	At least one element is either infinity.
`has_pos_inf(x)` / `has_neg_inf(x)`	At least one element is the specified infinity.
`has_positive(x)` / `has_negative(x)`	At least one element is strictly above / below zero; infinities qualify.
`has_zero(x)`	At least one element is exactly zero, including negative zero.
`all_finite(x)`	No element is NaN or infinite.

Function	Meaning

For an empty array, `has_*` returns false and `all_finite` returns true. For example:

```
samples float[3] = [1, 2, 3]
  !condition (all_finite({.}) && ~has_negative({.}))
```

The test uses the current state of the resolved domain. An unresolved source remains an error; `def` and `ndef` test a target path only after its source domain has been resolved.

Logical operators

Syntax	Priority	Description
`A || B || C ...`	6	Logical OR operator returns true if at least one expression (`A`, `B`, `C`, …) is true
`A && B && C ...`	5	Logical AND operator returns true if all expressions (`A`, `B`, `C`, …) are true

Numerical values with dimensions compared using comparison operations are automatically converted into the same units. Comparisons return a boolean or boolean array, depending on the operand shapes.

Comparisons also support arrays and operate element-wise. Two array operands must have identical shapes; a scalar operand is applied to every element of the array. An array comparison produces a boolean array with the array shape, while a scalar comparison produces a scalar boolean. When units are present, the operands must have compatible dimensions and are converted to the same units before comparison.

Comparison operators

Syntax	Priority	Description
`A == B`	3	Equality operator returns true if `A` and `B` have same dimensions and numeraical value up to EQUAL_PRECISION
`A != B`	3	Inequality operator returns true if `A` and `B` do not have same dimension or numerical value up to EQUAL_PRECISION
`A >= B`	3	Greater or equal operator returns true if `A` is greater or equal (up to EQUAL_PRECISION) than `B`
`A <= B`	3	Smaller or equal operator returns true if `A` is smaller or equal (up to EQUAL_PRECISION) than `B`
`A > B`	3	Greater than operator returns true if `A` is greater than `B`
`A < B`	3	Smaller than operator returns true if `A` is smaller than `B`

Single value operators

Syntax	Priority	Description
`~<bool>`	4	Negation operator returns true if value `A` is false

6.2 Numerical

Numerical expressions are used to generate values for numerical node types. If given, the expression result is automatically converted into node units. The target units should be placed after the expression parentheses end.

```
const
   c float = 299792458 m/s
energy float = (2 kg * pow( {?const.c}, 2 )) eV

# Node 'energy' will be parsed as 1.79751 eV
```

> [!NOTE] DIPL does not aim to substitute advanced numerical programming languages. Numerical expressions in DIPL are supposed to give a quick tool for generation of input values that can be easily derived from other parameters. Therefore, it implements only the most basic mathematical operations on scalar values. More advanced operations can be added in the future versions of DIPL.

Operators used in numerical expressions are summarized below:

Arithmetics

Syntax	Priority	Description
`A + B`	6	Addition of two values of a same dimension
`A - B`	6	Subtraction of two values of a same dimension
`A * B`	5	Multiplication of two values
`A / B`	5	Division of two values
`A ** B`	4	First value on the power of the second value
`+B`	3	Unary plus
`-B`	3	Unary minus

Parentheses operators evaluate expressions in a separate thread and return its final value. Most of the following operators require, that the final value has no dimensions.

Parentheses operators

Syntax	Priority	Description
`( <expr> )`	2	Standard parenthesis operator
`exp( <expr> )`	1	Returns exponential value of a dimensionless expression.
`pow( <expr>, <expr> )`	1	Returns first expression risen on a power of second dimensionless expression.
`ln( <expr> )`	1	Returns natural logarithmic value of a dimensionless expression.
`log10( <expr> )`	1	Returns common logarithmic value of a dimensionless expression.
`sin( <expr> )`	1	Returns sine value of a dimensionless expression.
`cos( <expr> )`	1	Returns cosine value of a dimensionless expression.
`tan( <expr> )`	1	Returns tangent value of a dimensionless expression.
`min( <expr>, <expr> )`	1	Returns minimum of the two expressions.
`max( <expr>, <expr> )`	1	Returns maximum of the two expressions.
`floor( <expr> )`	1	Returns the greatest integer less than or equal to the expression
`ceil( <expr> )`	1	Returns the smallest integer greater than or equal to the expression
`round( <expr> )`	1	Returns the closest integer or equal to the expression

> [!NOTE] Unlike the outer parentheses that define an expression, the inner parentheses must contain at least one whitespace separating the enclosed content. For example, `exp(2 cm)` is invalid, whereas `exp( 2 cm )` is valid.

6.3 Templates

Templates, or formatted text values, are used to convert node values into a textual representation. They follow the same syntax as standard string values, but are prefixed with an `f` before the opening quotation mark. All value types can be embedded into the text using standard Python-style formatting notation.

For longer output, adjacent quoted segments inside parentheses are joined without a separator. Each segment may independently use the `f` prefix, so only formatted segments interpolate references:

```
name str = "Tina"
greeting str = (
  "Hello, "
  f"{{?name}}"
  "!"
)
```

```
id int = 345
name str = "Tina"
body
  weight float = 62.3 kg
  height float = 177 cm
```

```
married bool = true

person str = f"""
ID:      {{?id}:05d}
Name:    {{?name}}
Weight:  {{?body.weight}:.3e}
Height:  {{?body.height}:.2f}
Married: {{?married}}
\{not a  reference}
"""

# Node 'person' will be parsed as:
#
# ID:      00345
# Name:    Tina
# Weight:  6.230e+01
# Height:  177.00
# Married: True
```

String expressions interpret starting double curly brackets always as a reference. Single curly brackets are interpreted as a plain test.

Basic syntax of parsing operators is described below:

Syntax	Description
`{{<ref>}}`	Default reference of a node value.
`{{<ref>}[<slice>]}`	Default reference of a node value slice.
`{{<ref>}:<format>}`	Formatted reference of a node value.
`{{<ref>}[<slice>]:<format>}`	Formatted reference of a node value slice.

Arrays can also be parsed using templates, however, without specifying a format. The format depends on the default Python string casting functions:

```
name str = "Will Smith"
widths float[2,3] = [[23.4,235.4,34],[1e10,2e23,5e20]]

preview str = f"""
Surname:  {{?name}[5:]}
Scalar:   {{?widths}[1,1]:.2e}
Array:
{{?widths}[:,1:]}
"""

# Node 'preview' will be parsed as:
#
# Surname:  Smith
# Scalar:   2.00e+23
# Array:
# [[2.354e+02 3.400e+01]
#  [2.000e+23 5.000e+20]]
```

7 Units

Units in DIPL follow a dedicated domain specific language PUEL designed for this purpose and defined in a separate specification. Consequently, every DIPL implementation MUST either provide a fully compliant units parser or utilize the reference units parser available in the SciNumTools v3 repository.

All values MUST be converted to a canonical unit representation before comparison or condition evaluation.

7.1 Standard Units

Each numerical value node has default units assigned at definition, or declaration. Subsequent modification without given units assume to be in default units. Values of modifications with different units (but same dimension) are converted to default units.

```
# definitions
age int = 30 a
height float = 185 cm
weight float = 80 kg

# modifications
age = 35
height = 190 cm
weight = 90000 g

# Modified values:
#
# age = 35 a
# height = 190 cm
# weight = 90 kg
```

7.1.1 Integer values after unit conversion

For an integer node, DIPL converts an explicitly unit-bearing assignment to the node's declared units **before** converting it to the declared integer type. The converted value MUST be finite, a whole number, and within the declared integer type's signed or unsigned range. DIPL MUST reject a fractional result; it MUST NOT round or truncate it to an integer. This rule applies to definitions, modifications, and overrides, including values obtained from expressions, references, and functions. For arrays, it applies to every element.

```
distance int = 2 m
distance = 200 cm       # valid: 2 m
distance = 150 cm       # invalid: 1.5 m is not an integer
```

Use a `float` node when fractional values in the declared units are valid. An assignment without explicit units is already expressed in the node's declared units and must satisfy the same integer rule.

7.2 Custom Units

Similarly as in case of references, it is also possible to define new units directly in the DIPL code. This can be achieved by a special node directive `$unit`. Custom units are referenced by their bare identifier, just like standard PUEL units. Square brackets are not valid in unit expressions. If the name of a custom unit is already used, the code will raise an error.

```
$unit mass = 30*kg
$unit length = 10*m
$unit time = 1*s

velocity float = 2 length/time
density float = 34 mass/length3
```

Each DIPL implementation MUST support the definition and integration of custom units directly through the code interface.

8 Functions

DIPL allows functions provided by the host implementation to be invoked from within a DIPL document. Functions extend the built-in expression syntax with custom logic and allow parameter values or nodes to be generated dynamically.

Note: The input and output data of a user-defined function may differ depending on the host implementation and the particular use case. However, the function interface defined by DIPL remains consistent: the environment list is passed to the function in the defined form, and the function returns a value/node list in the defined form.

8.1 Function Calls

A function call consists of a function name followed by parentheses:

```
# standard node definition
side float = 5 cm

# value injection from functions
volume float = fn_volume() cm3
surface int = fn_surface() mm2
prime bool = is_prime()
value str = print_value()

# node import from functions
parameters fetch_params()
shape
  shape_settings()
```

The function name identifies a function provided by the interpreter implementation. Implementations may provide functions written in the host language, such as C++, Python, or another supported language.

8.2 Function Arguments

Every function invocation receives an implicit `data` argument containing a copy of the value nodes that have already been parsed at the point of invocation.

In the reference implementation, this argument is represented by a `dip::Environment` object.

Explicit arguments may additionally be supplied in the function call. These arguments are evaluated before the function is invoked and are passed to the function together with the implicit `data` argument.

```
scale float = 10 cm
result float = calculate({?scale}, 2)
```

The exact representation and calling convention of the implicit `data` argument are implementation-defined.

8.3 Function Results

A function can be used either as a **value injection** or as a **node import**.

When used as a value injection, the function MUST return a value compatible with the declared DIPL node type. In the reference implementation, this is represented by `dip::ValueNodeData`.

When used as a node import, the function MUST return a list of nodes. In the reference implementation, this is represented by `dip::ValueNode::ListType`.

The function result MUST therefore match the syntactic context in which the function is invoked. An incompatible result MUST cause evaluation to fail.

8.4 Evaluation and Errors

Function calls are evaluated during parsing, as specified by the implementation.

Evaluation MUST fail if:

- the function cannot be resolved;
- the function execution results in an error; or
- the returned value is incompatible with the expected DIPL type or result context.

Implementations SHOULD provide diagnostic information identifying the function and the cause of the failure.

Unless explicitly specified otherwise by the function or implementation, function evaluation SHOULD be deterministic.

9 Properties

Numerical codes usually require initial parameter values with a specific format. In this section, we summarize properties that can be used in DIPL to restrict node values and describe their format. Each node property

directive is given on a new line immediately after node definitions, declarations or modification. All properties must have consistent indent, two whitespaces higher than their parent node.

9.1 Directives

9.1.1 Options

Used by: `int`, `float`, `str`

Initial code parameters often accept only a few discrete input values, also called options. These can be explicitly described during node definition or declaration.

The expected value of this clause is a list of values. It can be given explicitly or as a reference.

Node options can be specified for all data types except boolean. In case of boolean, the two options (`true` or `false`) are implicitly set. If the node has an other value than one of the options, DIPL will throw an error message.

Node definition and individual options can have different units, but they must have the same dimensionality. The final value of such modified node will be, however, converted into units specified in the definition. Options with explicit units are converted to the node's declared units before the effective value is compared with them. For an integer node, the effective value must also satisfy the integer conversion rule.

```
animal str = "dog"
  !options ["cat","dog","horse"]

energy float = 23 erg   # definition
  !options [43, 89]               # option in same units
  !options [23, 34] erg           # option in same units
  !options [3e-7, 5e+3] J         # option in different unit of energy

energy = 3e-7 J          # modification
# energy = 3 erg         # final value
```

Multiple `!options` clauses are allowed for the same node (e.g. each with different units). They combine into a single array of options against which the node value is evaluated.

```
energy float = 23 J
  !options [23, 45, 10, 234, 490, 1939] J
  !options [34, 234] erg
# all options: [23, 45, 10, 234, 490, 1939, 3.4e-6, 2.34e-7] J
```

Optional display labels can be attached to options with one `!labels` list. Its strings correspond, in order, to the combined values from every `!options` directive on the node. The number of labels must equal the number of options. Labels are preserved in DIPH5 and exposed by inspection tools; they do not change which values are accepted. Nodes without `!labels` behave as before.

```
resolution int = 16
  !options [16, 32, 64]
  !labels ["Low", "Medium", "High"]
```

For options declared in several clauses, provide all labels in one list:

```
energy float = 23 J
  !options [23, 45] J
  !options [34] erg
  !labels ["Reference", "High", "Low"]
```

9.1.2 Condition

Used by: `int`, `float`, `str`, `bool`

Numerical values can usually have values ranging in some intervals. To restrict node values to some particular interval, it is possible to set a logical condition using `!condition` directive and a logical expression. A given expression has to be evaluated as `true` after each definition or modification of a node.

In the example below, node `energy` can have values in a range of 23 and 26 erg. The actual value of node `energy` is matched using a special self-reference sign `{.}`.

```
energy float = 25 erg
  !condition (23 < {.} && {.} < 26)
```

9.1.3 Guided setup

Used by: `int`, `float`, `str`, `bool`

The valueless `!setup` directive marks a value for guided input by `snt dip setup`. The command infers a yes/no prompt for booleans, a choice list from `!options` (displaying `!labels` when supplied), text input for strings, and a DIPL value expression for numeric and array values. Existing values are offered as defaults. Each answer is checked immediately for type, shape, units, options, condition, and format. Invalid input is reported at its prompt. The complete project is validated again before the override is written.

```
method str = "rk4"
  !options ["euler", "rk4", "adaptive"]
  !labels ["Euler", "Runge-Kutta 4", "Adaptive Runge-Kutta"]
  !setup

steps int = 500
  !condition ({.} > 0)
  !setup
```

`!setup` only marks values for the guided command. It does not change ordinary DIPL parsing or force a value to be prompted in other interfaces.

9.1.4 Format

Used by: `str`

In general, string values wrapped into quote marks can contain all characters and can be arbitrary long. This can be restricted by defining their `!format` using standard regular expressions.

In the following example, node 'name' can contain only small and capital letters:

```
name str = "Ferdinant"
  !format "[a-zA-Z]+"
```

9.1.5 Constants

Used by: `int`, `float`, `str`, `bool`

Sometimes nodes have to stay constant and exclude ordinary modifications. This can be achieved by a directive `!constant`. If the node is declared without a value, its first assignment supplies the initial value. Later ordinary modifications are rejected. This applies independently to each instance of a schema field. An explicit `$override` may still replace a constant value.

Node `name` in the following example cannot be further modified.

```
name str = "John"
  !constant
name = "Mary"   # this modification will raise an error exception
```

9.1.6 Tags

Used by: `int`, `float`, `str`, `bool`

Tags provide a simple and effective mechanism for organizing and categorizing large sets of parameters. Any data type that supports tagging may define the dedicated `!tags` property, which accepts a list of tag values. In practice, it is recommended to use string values for tags to ensure consistency and interoperability.

Once assigned, tags enable nodes to be queried and filtered after parsing through the use of tag selectors. Every DIPL implementation SHOULD provide support for selecting parsed nodes based on their associated tags.

Tags should classify nodes for discovery and selection, such as identifying settings used by an exporter, diagnostic tool, or user interface. Keep tags as simple labels; they should not encode instructions, expressions, dependencies, or formatting rules.

Structured behavior belongs in typed DIPL nodes and reusable schemas—for example, an optional child schema defining export units or applicability. Descriptive information belongs in metadata. Consuming applications select nodes by their tags, inspect their typed settings and metadata, and implement the relevant behavior.

This separation keeps configuration explicit, supports validation and reuse, and avoids creating an application-specific language inside tag strings.

```
resolution int = 32
  !tags ["box", "grid"]
```

9.1.7 Delimiter

Used by: `table`

When entering values using a `table` node, columns are separated by whitespace by default.

For some input formats, such as CSV or TSV, a different column delimiter is required. DIPL therefore allows additional options to be specified for `table` nodes to define the delimiter used when parsing the table.

This makes it possible, for example, to prepend a DIPL header to a standard CSV file and use it directly as a DIPL table.

```
output table = """
snapshot int
time float s
intensity float W/m2
---
0, 0.234, 2.34
1, 1.355, 9.4
2, 2.535, 3.4
"""
  !delimiter ","
```

9.2 Metadata

Used by: `int`, `float`, `str`, `bool`, and schema definitions

Metadata provide additional information about a parameter without affecting its value or interpretation. They are intended for documentation, provenance, licensing, and versioning purposes, and may be used by documentation generators, scientific workflows, and other tooling.

In particular, provenance metadata describe the origin of a parameter's value, such as the publication, dataset, or other source from which it was obtained. This allows scientific and engineering data to remain traceable and properly attributed.

Unlike comments, metadata are part of the parsed document and are preserved during processing. Metadata may be attached to any explicit node in a dot-separated hierarchy: groups, map/list collections, map/list items, and values. For example, a map item can carry citation metadata directly, while its typed fields continue to be validated by the map's schema. Metadata is available through node inspection and is retained in DIPH5 artifacts.

At indentation zero before the first node in a `.dip` source, `?` metadata describes the source file itself. It is available through source inspection (`snt dip sources`) and is not inherited by the nodes declared in that file.

On a `$schema` declaration, metadata before the first member describe the reusable definition. Metadata attached to an individual schema member provide defaults for instances of that member. Explicit metadata on an instance replaces the corresponding schema-member field, while fields not set on the instance retain their defaults. Metadata on a schema definition itself is not inherited by instances. Explicitly empty metadata values are preserved and can be distinguished from fields that are absent in inspection results.

Schemas can impose metadata requirements with `!metadata`:

```
$schema citation
  !metadata authors required
  locator str
    ?url "https://example.org/reference"
    !metadata url nonempty
```

At the schema level, the rule applies to metadata on each group or item that uses the schema. Beneath a schema member, it applies to that member's metadata. Write the metadata name without its `?` prefix. `required` checks presence, so an explicitly empty annotation satisfies it. `nonempty` rejects empty and whitespace-only scalar strings. For list-valued metadata, it requires at least one item and rejects empty or whitespace-only items.

Member metadata defaults count toward constraints. An explicit instance value replaces the matching default, including an explicitly empty value. Constraints are checked after declarations and supported overrides. Metadata remains optional for schemas that declare no such rule. Schema inspection exposes the rules.

Table headers use indentation to distinguish table metadata from column metadata. Properties at indentation zero before the first column describe the table node; properties indented by two spaces beneath a column describe that column. This header syntax is shared by inline block tables and external `.dipt` files:

```
measurements table = """?descr "Experiment measurements"
time float s
  ?descr "Elapsed time"
speed float m/s
  ?descr "Measured flow speed"
---
0 3
1 4
"""
```

The table and column properties use the same metadata fields and merge rules as other DIPL nodes. Table-level metadata can also be attached to the table declaration in the enclosing `.dip` file.

The following metadata properties are currently defined:

Property	Description
`?descr`	Human-readable description of the parameter.
`?authors`	Author(s) of the referenced publication or data source.
`?title`	Title of the referenced publication, report, or dataset.
`?journal`	Journal, book, conference proceedings, or other publication.
`?year`	Year of publication or release.
`?volume`	Publication volume.
`?issue`	Publication issue.
`?pages`	Page range within the publication.
`?doi`	Digital Object Identifier (DOI).
`?url`	URL of the referenced resource.
`?version`	Version of the referenced document or dataset.
`?created`	Creation date of the referenced resource or metadata.
`?modified`	Last modification date of the referenced resource or metadata.
`?license`	License governing the referenced resource or dataset.
`?rationale`	Why the selected or default value is appropriate.
`?native`	Native target name(s), such as an application configuration key.
`?requires`	FQP or capability required for this node to apply.
`?conflicts`	FQP or capability that cannot coexist with this node or value.
`?implies`	Setting or capability normally enabled or required by this choice.
`?see`	Related FQP cross-reference(s).
`?example`	Recommended, optionally unit-aware example value(s).
`?recommended_range`	Advisory range; unlike `!condition`, this does not enforce validity.
`?performance_impact`	Computational-cost or memory implication.
`?scientific_impact`	Modelling or physical consequence.
`?deprecated`	Deprecation notice or version.
`?replacement`	FQP that supersedes a deprecated node.
`?since`	Software or schema version that introduced the node.
`?category`	Documentation grouping independent of hierarchy.
`?visibility`	Documentation or UI level, such as `basic`, `advanced`, or `expert`.

`?native`, `?requires`, `?conflicts`, `?implies`, `?see`, and `?example` accept either one scalar value or an array of strings. All other metadata properties accept one scalar value.

Example

```
thermal_conductivity float = 401 W/(m*K)
  ?descr "Thermal conductivity of high-purity copper measured at 293.15 K"
  ?authors "John A. Smith, Emily R. Johnson, Michael T. Brown"
  ?title "Thermal Conductivity of High-Purity Copper from 100 K to 500 K"
  ?journal "Journal of Materials Science"
  ?year 2024
  ?volume 59
  ?issue 8
  ?pages "4123-4137"
  ?doi "10.1007/s10853-024-12345-6"
  ?url "https://doi.org/10.1007/s10853-024-12345-6"
  ?version "Published Version"
  ?created "2024-03-18"
  ?modified "2024-04-02"
  ?license "CC BY 4.0"
```

10 Conditions

Conditions in DIPL provide a mechanism for controlling node parsing flow based on the evaluation of logical expressions. They allow values and parameters to be assigned dynamically depending on runtime state, enabling branching behavior within scripts and configurations. Each condition is evaluated in sequence, and only the first matching branch is executed.

DIPL supports the following set of condition clauses that define this branching structure. These clauses can be combined to express simple decisions as well as more complex, multi-branch logic. The structure is indentation-sensitive, meaning that all statements belonging to a clause must be nested under it with a higher indentation level.

- `@if (<expression>)` is a starting clause of each condition and requires as an argument result of a logical expression. If the expression is evaluated as true, its child nodes will be taken for further parsing and the condition is terminated.
- `@elif (<expression>)` is a subsequent condition clause and requires as an argument result of a logical expression. If the expression is evaluated as true, its child nodes will be taken for further parsing and the condition is terminated. If the expression is false, its child nodes are skipped and subsequent clauses are evaluated. For testing purposes, one can also use direct `true` or `false` keywords instead of expressions.
- `@else` is a special, optional, clause that is at the very end of conditions and does not require any expression. Each condition can have only one `@else` clause. If all previous `@if`-s and `@elif`-s are evaluated as false, child nodes of `@else` are taken.
- `@end` is a terminating clause whose main purpose is to separate two consecutive conditions. If omitted, a single condition terminates after last `@if`, `@elif` or `@else`.

```
winner int = 1

@if ({?winner} == 1)          # first case
  name str = "John"
@elif ({?winner} == 2)        # second case
  name str = "Jenny"
@else                         # default case
  name str = "Jonas"
@end                          # end of first condition

@if ({?name} == "Jenny")
  toy str = "doll"
@else
  toy str = "robot"
```

Nested conditions are also possible, provided that each child condition has indent higher than the parent condition.

```
@if false
  flower str = "rose"
```

```
@else
  flower str = "dandelion"
  @if false
    color str = "red"
  @elif false
    color str = "blue"
  @else
    @if true
      leaves int = 234
    color str = "yellow"
  tree str = "maple"

# The nodes above will be parsed as:
#
# flower = "dandelion"
# leaves = 234
# color  = "yellow"
# tree   = "maple"
```

> [!NOTE] Although nodes within a clause are indented more deeply than their surrounding siblings, this indentation does not affect the naming hierarchy. Internally, nodes inside a branching clause are assigned a temporary "clause parent" (e.g. `foo.@if1.bar`). Once the condition is resolved and the branch is applied, this intermediate scope is removed, and the node assumes its final name (e.g. `foo.bar`).

11 Schemas

Schemas provide a mechanism for defining reusable node structures.

A schema describes a set of nodes that may later be instantiated within groups, maps, or lists. By allowing common structures to be declared once and reused multiple times, schemas reduce duplication and promote consistency across related data.

Conceptually, a schema is similar to a type definition in a programming language. It defines the structure and properties that its instances shall contain, but does not itself create any nodes within the document hierarchy.

11.1 Declaration and Instantiation

Schemas are declared using the `$schema` directive. The schema name defines a reusable type. Nodes declared within the schema become members of that type and are inherited by all schema instances.

Metadata properties may immediately follow the schema declaration, before its first member. They describe the reusable definition and stay in the schema registry: they are not copied to the group, collection, or item that applies the schema, nor to its value nodes. Metadata indented beneath a value member describes that member and is copied when the schema is applied:

```
$schema settings
  ?descr "Reusable physics settings"
  ?since "0.8.3"
  speed float = 2 m/s
    ?descr "Flow speed"
```

Schema-level descriptive metadata are available through the environment's schema registry. A schema may also declare `!metadata` constraints before its first member. These constraints apply to metadata on each group or item that uses the schema; they are not descriptive metadata and are not inherited by instances.

For example, the following schemas define common structures that can be combined to describe a car:

```
$schema car
  manufacturer str;
  weight float kg;
  max_speed float km/h;

$schema vehicle
```

```
  registration str;
  year int;
```

A schema is instantiated by appending one or more schema names after a colon (`:`) to a group, map item, or list item declaration. Schemas cannot be applied to a value node, including a value node that has child nodes. Multiple schema names are separated by commas. For example, the following creates two `car` instances, each of which also conforms to the `vehicle` schema:

```
car[civic] : car, vehicle
  manufacturer = "Honda"
  weight = 1350 kg
  max_speed = 200 km/h
  registration = "M-AB 1234"
  year = 2020

car[320i] : car, vehicle
  manufacturer = "BMW"
  weight = 1570 kg
  max_speed = 235 km/h
  registration = "M-CD 5678"
  year = 2022
```

Schemas are independent of container type and may therefore be instantiated within groups, maps, or lists.

For example:

```
$schema person
  name str;
  age int years;
```

As a group:

```
father : person
  name = "Peter"
  age = 45 years
```

As a map item:

```
people[john] : person
  name = "John"
  age = 32 years
```

As a list item:

```
people[] : person
  name = "Anna"
  age = 28 years
```

Schema fields can be declared constant without a value. Each instance then supplies its own initial value; later ordinary modifications to that field are rejected:

```
$schema edge
  subject str
    !constant
  relation str
    !constant
  object str
    !constant

edges[example] : edge
  subject = "person"
  relation = "has_substantial_form"
  object = "human"

edges[other] : edge
  subject = "animal"
  relation = "is_a"
```

```
  object = "organism"

edges[example].relation = "is_a"  # error: already assigned
```

All declared fields still need a value in each instance. A schema field defined with a value is constant immediately; its instance cannot assign a different initial value through an ordinary modification. Explicit `$override` regions retain their usual ability to replace constants.

11.2 Required metadata

Schemas can require metadata on the instance itself and on individual schema members. Use `required` to require that an annotation is present, or `nonempty` to require a value containing non-whitespace content:

```
$schema citation
  !metadata authors required
  locator str
    ?url "https://example.org/reference"
    !metadata url nonempty

records map : citation
records[example]
  ?authors "Example author"
  locator = "Section 1"
```

The schema-level rule applies to the metadata on each applying group or item. The member rule applies to `locator` metadata. The schema's URL annotation is a default, so it satisfies `nonempty` when an instance leaves that field unspecified. An explicit empty instance annotation replaces the default and fails `nonempty`. Under `required`, an explicitly empty annotation counts as present.

`nonempty` rejects empty and whitespace-only scalar strings. For list-valued metadata, the list must contain an item and every item must contain non-whitespace text. Thus an empty list or a list containing an empty item fails. Metadata property names use their regular spelling without the `?`, such as `authors`, `url`, or `requires`.

Constraints are evaluated after schema defaults and instance annotations have been combined, after declarations are complete, and after supported overrides have been applied. An explicit empty override does not fall back to a schema default. Requirements from multiple applied schemas are combined: `nonempty` also satisfies `required`, while both rules remain independently visible in inspection. Unknown metadata names and rules are rejected during parsing. Diagnostics identify the affected path, metadata property, rule, and schema source location.

The schema hierarchy inspection API exposes instance-level and member-level constraints. DIPH5 snapshots retain evaluated metadata and schema application provenance, but do not contain reusable schema definitions. A snapshot records the result of evaluation; loading it does not re-run the original schema constraints.

11.3 Collection schemas

Schemas can also be applied to entire `map` and `list` collections. In this case, the schema is specified once in the collection declaration and is automatically applied to all subsequent items.

```
$schema vehicle
  speed float = 212 kph
  weight float = 1320 kg

$schema road
  tires str = "Continental"

vehicles map : vehicle       # schema applies to all items
vehicles[car] : road         # schema applies to this specific item
vehicles[ship]
```

In this example, both `car` and `ship` inherit the nodes defined by the `vehicle` schema, because it is applied to the entire `vehicles` collection. The `car` item additionally inherits the nodes defined by the `road` schema, while `ship` does not.

11.4 Nested Schemas

Schemas may contain both value nodes and container nodes, including nested groups, maps, lists, and other schema instances.

```
$schema address
  street str;
  city str;
  country str;

$schema person
  name str;
  age int years;

  residence : address
```

Because schemas describe structure independently of container type, they provide a uniform mechanism for defining reusable data models throughout a DIPL document.

11.5 Rules

The following rules shall apply:

- Schema names shall be unique within a document.
- A schema shall be declared before it is instantiated.
- A schema declaration does not create any nodes in the document hierarchy.
- A schema may contain value nodes and container nodes.
- A schema may instantiate other schemas.
- Schemas may be instantiated within groups, map items, and list items.
- The structure defined by a schema is inherited by all of its instances.
- Metadata remains optional unless an instance or member constraint is declared.
- Schema metadata constraints are validated against effective metadata after defaults, instance annotations, and supported overrides have been applied.

12 Overrides

Overrides tune the values of a parameter model. They may also create items in schema-backed maps and lists using ordinary collection item groups. They do not alter schemas, value types, or properties. Dependencies and conditional definitions are evaluated using the replacement values, so the evaluated model may contain different active nodes.

12.1 Declaration

An override region begins with the `$override` directive at indentation zero. Its body shall contain one or more value modifications or collection item groups, indented two spaces:

```
$override
  simulation.resolution = 1024
  simulation.box_size = 200 Mpc

simulation
  resolution int = 512
  box_size float = 100 Mpc
```

Each expanded value target shall be a fully qualified path to a value node normally declared outside override regions, or instantiated by an item group in the override. Schema members and collection members may be targeted using their instantiated paths, such as `materials[copper].density` or `particles[0].mass`. A value modification shall not implicitly append collection items, select a subtree, or replace an individual array element or slice. An array replacement assigns the whole value and shall satisfy its declared dimensions.

Override regions shall not appear inside schemas, groups, collection items, conditional blocks, or other override regions. Their bodies shall not contain type declarations, properties, metadata, imports, or collection declarations. An untyped path ending in an item selector is the only structural entry allowed. Blank lines and comments are permitted. An empty region is invalid.

For example, `resolution = 1024` is a modification, whereas `resolution int = 1024` is a definition and is invalid inside an override region.

12.2 Nested Paths

A body may combine dotted paths and indentation, using the same path composition rules as ordinary DIPL nodes:

```
simulation
  steps int = 100
  box_size float = 1 Mpc

$override
  simulation
    steps = 1024
    box_size = 200 Mpc
```

Inside an override body, a bare path such as `simulation` is only a prefix for its children. It shall not create a group or instantiate a schema. The example registers the targets `simulation.steps` and `simulation.box_size`.

Children shall be indented two spaces beyond their parent. An ordinary prefix shall contain at least one modification or collection item, directly or through further prefixes. Explicit collection keys and indices are allowed as prefixes, for example `materials[copper]`. An empty terminal selector such as `materials[]` appends a list item. A value modification may also have nested modifications to existing children of that value-bearing node. Its own value and each child's value are separate override targets.

Duplicate detection shall use expanded paths. Thus `simulation.steps = 1024` and a nested `steps = 1024` under `simulation` conflict even if their values are identical. Source locations shall retain the original, unexpanded lines.

12.3 Collection and Evaluation

An item group can create an item in an existing collection that declares at least one item schema. It uses the collection's schemas to instantiate value children, then applies its indented value modifications to those children:

```
$schema material
  density float = 1 g/cm^3

materials map : material
particles list : material

$override
  materials[copper]
    density = 8.96 g/cm^3
  particles[]
    density = 2 g/cm^3
```

An item path ending in `[key]` creates a new map key when it does not already exist. If the key exists, the item path acts as a prefix for modifications to that item. A path ending in `[]` appends one list item; an explicit list index refers to an existing item. New items require a collection item schema. Nested item groups may create items in collections declared by a parent item's schema. A value path such as `materials[copper].density = 2` only targets an existing value node; it never creates an item implicitly.

An unknown collection, a missing explicit list index, or a selector that does not match the collection kind is an error.

Item additions are evaluated after ordinary model declarations, in the order the additions were registered. This preserves existing list indices. A value defined earlier in the model cannot depend on a newly added item's value; normal forward-reference rules apply. The item group line supplies the new item's declaration location, while each modified child retains its override location.

All override regions shall be collected before normal node evaluation. Multiple regions may appear among top-level inputs; their textual position shall not establish precedence or change which declarations they target.

A target may be overridden only once. Repeated target paths shall fail even when their replacement values are identical or originate from different input files, regions, or host registrations.

When the target declaration is processed, the replacement shall be evaluated instead of its original value. The original declaration shall remain syntactically valid, but its original value expression or function shall not be evaluated. Subsequent ordinary modifications shall not replace an overridden value. Their structural role and declaration compatibility checks remain in effect. An override may replace a value marked `!constant` without removing that property.

Every collected override shall match an instantiated value node. After normal node processing, any unmatched target shall cause an unresolved override error. Value modifications alone shall not create missing targets.

12.4 Replacement Values and Units

Replacement values may use the normal value forms supported by the target: literals, arrays, `none`, references, expressions, and registered value functions. For example:

```
base float = 10 cm
radius float = 1 cm
diameter float = ({?radius} * 2) cm

$override
  radius = ({?base} * 2) cm
```

This produces `radius = 20 cm` and `diameter = 40 cm`. Alternative replacements include `radius = {?base} cm` or `radius = compute_radius() cm`, where the host has registered the value function `compute_radius`.

Dependencies of a replacement shall be available when the target declaration is evaluated. Moving the override region shall not enable forward references or make the target's original value available to its own replacement.

The target's declared type, dimension constraints, units, and properties shall be preserved. Explicit compatible replacement units shall be converted into the target's units; omitted units use the target's declared units. Incompatible physical dimensions shall fail. Units shall not be added to a dimensionless target. The effective value shall satisfy the normal schema, options, condition, and format constraints of the target.

12.5 Conditional Definitions

Overrides participate in normal dependency and conditional evaluation:

```
enabled bool = false
@if ({?enabled})
  steps int = 100
@end

$override
  enabled = true
  steps = 200
```

The overridden `enabled` activates the existing definition of `steps`, whose value becomes `200`. If `enabled` were overridden to `false` instead, the override of `steps` would be unresolved and evaluation would fail.

Changing which existing conditional definitions are active does not change the declared model. A new item requires its collection to exist after conditional evaluation; it cannot create a collection whose condition was false.

12.6 Host Inputs and Provenance

The reference implementation exposes `add_override_string(body)` and `add_override_file(path)`. Both accept an unwrapped override body containing modifications, collection item groups, and optional nested path prefixes. The first body level starts at indentation zero. They use the same target, duplicate, and validation rules as `$override` regions. Registration is atomic: a rejected body registers no entries. Target existence is checked during model evaluation.

An overridden node exposes its override state. Provenance retains both its original declaration and the replacement source, including the file path when available. Constraint diagnostics identify the offending override and

include the declaration as context. DIPH5 snapshots preserve the evaluated value and override provenance; they do not re-evaluate override expressions on loading.

Override targets belong to the current evaluated model. This directive does not define remote or source-domain override semantics.

A Formal Grammar

The following EBNF summarizes DIPL syntax. Context-sensitive constraints and lexical details are stated in the relevant chapters and in the comments in the grammar. `PUEL-unit-expression` is defined by the separate PUEL specification.

```
(* ========================================================================== *)
(* DIPL grammar                                                               *)
(*                                                                            *)
(* This grammar follows docs/dipl/specification.md and docs/dipl/syntax/*.md. *)
(* PUEL-unit-expression is defined by the separate PUEL specification.        *)
(*                                                                            *)
(* INDENT and DEDENT are lexer tokens.  An INDENT represents an increase of   *)
(* two spaces on a non-blank, non-comment line; a DEDENT represents a        *)
(* decrease. Tabs are not valid indentation.                                  *)
(* ========================================================================== *)

document
  = { blank-line | comment-line | source-metadata }
    { blank-line | comment-line | statement | override-region } ;

(* Source metadata belongs to the source file and is allowed only before its  *)
(* first statement, at indentation level zero.                                *)
source-metadata
  = metadata-property [ comment ] newline ;

statement
  = source-declaration
  | unit-declaration
  | schema-declaration
  | conditional
  | node-statement ;

(* -------------------------------------------------------------------------- *)
(* Nodes and hierarchy                                                        *)
(* -------------------------------------------------------------------------- *)

node-statement
  = value-definition
  | value-declaration
  | value-modification
  | container-declaration
  | collection-item
  | node-import
  | function-import ;

value-definition
  = node-path whitespace type-spec [ shape-spec ] whitespace "=" whitespace
    value [ whitespace PUEL-unit-expression ] [ comment ] newline
    { property-line } ;

value-declaration
  = node-path whitespace type-spec [ shape-spec ]
    [ whitespace PUEL-unit-expression ] [ ";" ] [ comment ] newline
    { property-line } ;
```

```
value-modification
  = node-path whitespace "=" whitespace value
    [ whitespace PUEL-unit-expression ] [ comment ] newline
    { property-line } ;

(* A group has no explicit type. map/list declarations establish a collection *)
(* type before items are added.                                               *)
container-declaration
  = node-path [ whitespace collection-kind ] [ schema-use ] [ comment ] newline
    [ block ] ;

collection-kind
  = "map" | "list" ;

collection-item
  = node-path-with-selector [ schema-use ] [ comment ] newline [ block ] ;

(* Imports insert a node or selected subtree at the current path. *)
node-import
  = [ node-path whitespace ] node-reference [ comment ] newline ;

(* A host function may return a list of nodes and be used as an import. *)
function-import
  = [ node-path whitespace ] function-call [ comment ] newline ;

block
  = INDENT { blank-line | comment-line | statement } DEDENT ;

(* ------------------------------------------------------------------------ *)
(* Sources, custom units, and schemas                                       *)
(* ------------------------------------------------------------------------ *)

source-declaration
  = "$source" whitespace source-name whitespace "=" whitespace source-value
    [ comment ] newline ;

source-value
  = string | node-reference ;

unit-declaration
  = "$unit" whitespace unit-name whitespace "=" whitespace unit-value
    [ comment ] newline ;

unit-value
  = PUEL-unit-expression | node-reference ;

schema-declaration
  = "$schema" whitespace schema-name [ comment ] newline schema-block ;

schema-block
  = INDENT { blank-line | comment-line | schema-metadata }
    { blank-line | comment-line | schema-member } DEDENT ;

schema-metadata
  = ( metadata-property | metadata-constraint ) [ comment ] newline ;

schema-member
  = value-declaration
  | container-declaration
  | collection-item ;
```

```
schema-use
  = whitespace ":" whitespace schema-name
    { optional-whitespace "," optional-whitespace schema-name } ;

(* ------------------------------------------------------------------------- *)
(* Overrides: permitted only in document, never in a nested statement block.  *)
(* ------------------------------------------------------------------------- *)

override-region
  = "$override" [ comment ] newline override-block ;

override-block
  = INDENT { blank-line | comment-line } override-entry
    { blank-line | comment-line | override-entry } DEDENT ;

override-entry
  = override-modification | override-prefix | override-item ;

(* A terminal selector may create a schema-backed item. *)
override-item
  = node-path-with-selector [ comment ] newline [ override-block ] ;

(* Other prefixes compose paths without declaring groups or items. *)
override-prefix
  = override-group-path [ comment ] newline override-block ;

override-group-path
  = name { [ "[" collection-key "]" ] "." name } ;

(* A value-bearing parent may also have modifications to existing children. *)
override-modification
  = override-path whitespace "=" whitespace value
    [ whitespace PUEL-unit-expression ] [ comment ] newline [ override-block ] ;

override-path
  = override-path-segment { "." override-path-segment } ;

override-path-segment
  = name [ "[" collection-key "]" ] ;

(* ------------------------------------------------------------------------- *)
(* Properties and metadata                                                   *)
(* ------------------------------------------------------------------------- *)

(* Version 1.1.0 adds the opt-in !setup marker for guided input tools. *)

property-line
  = INDENT property [ comment ] newline ;

property
  = options-property
  | labels-property
  | setup-property
  | condition-property
  | format-property
  | constant-property
  | tags-property
  | delimiter-property
  | metadata-constraint
  | metadata-property ;
```

```
metadata-constraint
  = "!metadata" whitespace metadata-name whitespace ("required" | "nonempty") ;

metadata-name
  = "description" | "authors" | "title" | "journal" | "year" | "volume"
  | "issue" | "pages" | "doi" | "url" | "version" | "created" | "modified"
  | "license" | "rationale" | "native" | "requires" | "conflicts" | "implies"
  | "see" | "example" | "recommended_range" | "performance_impact"
  | "scientific_impact" | "deprecated" | "replacement" | "since" | "category"
  | "visibility" ;

options-property
  = "!options" whitespace array [ whitespace PUEL-unit-expression ] ;

labels-property
  = "!labels" whitespace array ;

setup-property
  = "!setup" ;

condition-property
  = "!condition" whitespace parenthesized-logical-expression ;

format-property
  = "!format" whitespace string ;

constant-property
  = "!constant" ;

tags-property
  = "!tags" whitespace array ;

delimiter-property
  = "!delimiter" whitespace string ;

metadata-property
  = metadata-key whitespace metadata-value ;

metadata-key
  = "?descr" | "?authors" | "?title" | "?journal" | "?year"
  | "?volume" | "?issue" | "?pages" | "?doi" | "?url" | "?version"
  | "?created" | "?modified" | "?license" | "?rationale" | "?native"
  | "?requires" | "?conflicts" | "?implies" | "?see" | "?example"
  | "?recommended_range" | "?performance_impact" | "?scientific_impact"
  | "?deprecated" | "?replacement" | "?since" | "?category" | "?visibility" ;

metadata-value
  = string | integer | float | boolean | "none" | array ;

(* ---------------------------------------------------------------------------- *)
(* Conditions                                                                   *)
(* ---------------------------------------------------------------------------- *)

conditional
  = if-clause { elif-clause } [ else-clause ] [ end-clause ] ;

if-clause
  = "@if" whitespace condition-value [ comment ] newline block ;

elif-clause
```

```
  = "@elif" whitespace condition-value [ comment ] newline block ;

else-clause
  = "@else" [ comment ] newline block ;

end-clause
  = "@end" [ comment ] newline ;

condition-value
  = boolean | node-reference | function-call | parenthesized-logical-expression ;

(* ------------------------------------------------------------------------ *)
(* References, paths, and slices                                            *)
(* ------------------------------------------------------------------------ *)

reference
  = raw-source-reference | node-reference | self-reference ;

(* Raw content of a named source. *)
raw-source-reference
  = "{" source-name "}" ;

(* An omitted source name selects the local domain. An omitted path selects   *)
(* the complete node tree. A trailing dot selects a subtree.                  *)
node-reference
  = absolute-node-reference | relative-node-reference ;

absolute-node-reference
  = "{" [ source-name ] "?" [ absolute-path ] [ subtree-selector ] "}" ;

relative-node-reference
  = "{" relative-prefix node-path [ subtree-selector ] "}" ;

absolute-path
  = node-path ;

relative-prefix
  = "." { "." } ;

subtree-selector
  = "." ;

(* Valid only inside a !condition expression. *)
self-reference
  = "{.}" ;

node-path
  = path-segment { "." path-segment } ;

node-path-with-selector
  = path-segment { "." path-segment } "." selected-path-segment
  | selected-path-segment ;

path-segment
  = name [ collection-selector ] ;

selected-path-segment
  = name collection-selector ;

collection-selector
  = "[" [ collection-key ] "]" ;
```

```
collection-key
  = name | integer ;

slice
  = "[" slice-item { "," slice-item } "]" ;

slice-item
  = integer | [ integer ] ":" [ integer ] ;

(* ------------------------------------------------------------------------ *)
(* Values, arrays, tables, and templates                                    *)
(* ------------------------------------------------------------------------ *)

value
  = "none"
  | boolean
  | integer
  | float
  | string
  | string-block
  | template
  | parenthesized-string-concatenation
  | array
  | table-block
  | reference [ slice ]
  | function-call
  | parenthesized-numerical-expression
  | parenthesized-logical-expression ;

array
  = "[" [ value { optional-whitespace "," optional-whitespace value } ] "]" ;

string-block
  = triple-quote { block-character | newline } triple-quote ;

(* Table metadata is unindented; per-column metadata is indented beneath the  *)
(* corresponding column declaration.                                          *)
table-block
  = triple-quote table-header "---" newline { table-row newline } triple-quote ;

table-header
  = { metadata-property newline }
    { table-column newline { table-column-metadata newline } } ;

table-column
  = name whitespace type-spec [ shape-spec ] [ whitespace PUEL-unit-expression ] ;

table-column-metadata
  = INDENT metadata-property ;

table-row
  = table-field { table-delimiter table-field } ;

template
  = "f" ( string | string-block ) ;

parenthesized-string-concatenation
  = "(" optional-whitespace ( string | template )
    { optional-whitespace ( string | template ) } optional-whitespace ")" ;
```

```
template-substitution
  = "{{" node-reference [ slice ] [ ":" format-spec ] "}}" ;

(* ---------------------------------------------------------------------- *)
(* Expressions                                                            *)
(* ---------------------------------------------------------------------- *)

logical-expression
  = logical-or ;

(* Numerical and logical expressions have distinct outer wrappers. A value
   node's declared type selects the permitted wrapper: bool uses the logical
   form; integer and floating-point types use the numerical form. *)
parenthesized-numerical-expression
  = "(" optional-whitespace numerical-expression optional-whitespace ")" ;

parenthesized-logical-expression
  = "(" optional-whitespace logical-expression optional-whitespace ")" ;

logical-or
  = logical-and { whitespace "||" whitespace logical-and } ;

logical-and
  = comparison { whitespace "&&" whitespace comparison } ;

comparison
  = numerical-expression
    [ whitespace comparison-operator whitespace numerical-expression ] ;

comparison-operator
  = "==" | "!=" | ">=" | "<=" | ">" | "<" ;

numerical-expression
  = additive-expression ;

additive-expression
  = multiplicative-expression
    { whitespace ( "+" | "-" ) whitespace multiplicative-expression } ;

multiplicative-expression
  = power-expression
    { whitespace ( "*" | "/" ) whitespace power-expression } ;

power-expression
  = unary-expression [ whitespace "**" whitespace power-expression ] ;

unary-expression
  = [ "+" | "-" | "~" ] primary-expression ;

primary-expression
  = quantity
  | scalar
  | node-reference [ slice ]
  | self-reference
  | function-call
  | built-in-call
  | parenthesized-numerical-expression
  | parenthesized-logical-expression ;

quantity
  = ( integer | float ) [ whitespace PUEL-unit-expression ] ;
```

```
built-in-call
  = definition-test | numerical-function | numerical-predicate ;

definition-test
  = ( "def" | "ndef" ) "(" whitespace node-reference whitespace ")" ;

numerical-predicate
  = ( "has_nan" | "has_inf" | "has_pos_inf" | "has_neg_inf"
    | "has_positive" | "has_negative" | "has_zero" | "all_finite" )
    "(" optional-whitespace primary-expression optional-whitespace ")" ;

numerical-function
  = ( "exp" | "ln" | "log10" | "sin" | "cos" | "tan" | "floor" | "ceil" | "round" )
    "(" whitespace numerical-expression whitespace ")"
  | ( "pow" | "min" | "max" )
    "(" whitespace numerical-expression whitespace "," whitespace numerical-expression whitespace ")" ;

function-call
  = function-name "(" [ function-arguments ] ")" ;

function-arguments
  = value { optional-whitespace "," optional-whitespace value } ;

(* ------------------------------------------------------------------------ *)
(* Types, shapes, and lexical syntax                                        *)
(* ------------------------------------------------------------------------ *)

type-spec
  = "bool" | "int" | "uint" | "float" | "float128" | "str" | "char"
  | "byte" | "table" | "link" | signed-integer-type | unsigned-integer-type
  | floating-type ;

signed-integer-type
  = "int8" | "int16" | "int32" | "int64" ;

unsigned-integer-type
  = "uint8" | "uint16" | "uint32" | "uint64" ;

floating-type
  = "float16" | "float32" | "float64" ;

shape-spec
  = "[" shape-dimension { "," shape-dimension } "]" ;

shape-dimension
  = non-negative-integer
  | [ non-negative-integer ] ":" [ non-negative-integer ] ;

scalar
  = boolean | integer | float | string | "none" ;

boolean
  = "true" | "false" ;

integer
  = [ "+" | "-" ] digit { digit } ;

float
  = [ "+" | "-" ]
    ( digit { digit } [ "." { digit } ] | "." digit { digit } )
```

```
    [ ( "e" | "E" ) [ "+" | "-" ] digit { digit } ] ;

string
  = '"' { string-character | escape-sequence } '"' ;

triple-quote
  = '"""' ;

escape-sequence
  = "\\\"" | "\\n" | "\\\\" ;

name
  = name-character { name-character } ;

name-character
  = letter | digit | "_" | "-" ;

source-name
  = name ;

unit-name
  = name ;

schema-name
  = name ;

function-name
  = name ;

comment
  = "#" { character } ;

blank-line
  = [ whitespace ] newline ;

comment-line
  = [ whitespace ] comment newline ;

whitespace
  = " " { " " } ;

optional-whitespace
  = { " " } ;

newline
  = "\n" | "\r\n" ;

letter
  = "A" … "Z" | "a" … "z" ;

digit
  = "0" … "9" ;

non-negative-integer
  = digit { digit } ;

(* character, string-character, block-character, format-spec, table-field,  *)
(* and table-delimiter are lexical productions. Their exact treatment is     *)
(* defined by the Values, Expressions, and Properties chapters.              *)

(* ------------------------------------------------------------------------- *)
```

```
(* Context-sensitive constraints                                              *)
(* -------------------------------------------------------------------------- *)

(* - A definition/declaration establishes a node's type, shape, and default  *)
(*   unit. A modification must be compatible with those properties.           *)
(* - A parenthesized logical expression is valid only for a bool value node;  *)
(*   a parenthesized numerical expression is valid only for an integer or     *)
(*   floating-point value node.                                               *)
(* - Units are valid only for numerical value nodes and numerical table       *)
(*   columns.                                                                 *)
(* - float16, float128, byte, and char are optional types; implementations     *)
(*   that do not support an optional type MUST reject its use.                *)
(* - Properties immediately follow their node and are one indentation level   *)
(*   deeper. Their applicability is defined in syntax/properties.md.          *)
(* - {.} is valid only in a !condition expression.                            *)
(* - A trailing dot in a reference selects a subtree and is invalid where a   *)
(*   single value is required.                                                *)
(* - Map and list selectors cannot be mixed at the same collection path.      *)
(* - A `link` value MUST be one absolute node reference with a nonempty path; *)
(*   it cannot select a subtree or use a relative/self reference.             *)
(* - Links store only target source/path identity. Traversal follows targets,  *)
(*   while local descendants and writes through a link are invalid.           *)
(* - Schemas must be declared before use; source and unit names are unique.   *)
(* - Expanded override paths are unique across all override inputs,  *)
(*   and must resolve to value nodes instantiated normally or by an override *)
(*   item group. Remote target domains and partial arrays are not permitted. *)
(* - Overrides are collected before evaluation and applied at the target's   *)
(*   declaration; replacement dependencies must already be available there.  *)
(* - Overrides preserve declaration constraints, may replace !constant       *)
(*   values, and take precedence over subsequent ordinary modifications.    *)
(* - Functions are host-defined extensions; their availability and semantics  *)
(*   are implementation-specific.                                             *)
```

B Syntax Highlighting Fixture

The following shared fixture is rendered with the DIPL Skylight definition when this specification is built with Pandoc. It provides a visual check of the syntax highlighting used in the PDF specification.

```
# DIPL highlighting fixture: covers the syntax categories used by the lexer.

# Numeric-looking commented configuration must remain entirely a comment.
#       size = 10000 custom_length
#     files = 4
#   courant_factor = 0.25
# foo "bar" stays entirely a comment.
# Parentheses (including nested ones (like this)) stay entirely a comment.
# Expression ({?length} * 2) and "bar" stay entirely a comment.

# Declarations: external sources, custom units, and schemas.
$source imported = "data/other.dip"
$unit local_length = 2.5 m
$schema vehicle

# Strings and scalar values.
name str = "escaped quote: \"DIPL\""
multiline str = """triple quoted
value without interpolation and # text"""
formatted str = f"Length: {{?length}}"
formatted_slice str = f"Surname: {{?name}[9:]}"
formatted_multiline str = f"""Length: {{?length}}
Width: {{?width}}"""
```

```
# The same reference must retain its reference colour in every context.
reference_direct float = {?length}
reference_expression float = ({?length} * 2)
reference_template str = f"Length: {{?length}}"

enabled bool = true
disabled bool = false
missing bool = none
count int = -42
unsigned uint64 = 18446744073709551615
ratio float = 3.14159e-4
relative_tolerance float = 1e-12
  ?descr "Relative tolerance for the value correctness checks."
length float = 2.5 m
duration float = 12.0 s

# Arrays and table-like values.
values float[3] = [1.0, 2.0, 3.0] m
labels str[3:4] = "[\"John\", \"Peter\", \"Simon\"]"
table table = [1, 2, 3]

# Local and remote references, including subtree imports.
copied float = {?length}
selected float = {?values}[1]
row float[2] = {?values}[:2]
surname str = {?name}[9:]
remote float = {imported?length}
children
  {?vehicle.}

# Expressions and node properties.
calculated float = ({?length} * 2) cm
  !condition ({.} > 0 cm)
  !constant
  !format "%.3f"
  !tags ["example", "highlight"]
  !options [1, 2, 3] cm
  !labels ["One", "Two", "Three"]
  !setup
  !delimiter ","
  ?descr "A highlighted test value"
  ?authors "Ada Lovelace, Emmy Noether"
  ?title "DIPL Highlighting Fixture"
  ?journal "Scientific Numerical Tools Examples"
  ?year "2026"
  ?volume "8"
  ?issue "1"
  ?pages "1-2"
  ?doi "10.0000/example.dipl"
  ?url "https://example.invalid/dipl-fixture"
  ?version "1.0"
  ?created "2026-09-21"
  ?modified "2026-09-21"
  ?license "CC BY 4.0"
  ?rationale "Balances accuracy and cost"
  ?native ["ErrTolTheta", "TreeOpeningAngle"]
  ?requires ["build.gravity.self_gravity", "build.gravity.tree"]
  ?conflicts "build.gravity.direct"
  ?implies "build.gravity.tree"
  ?see ["gravity.force_accuracy", "gravity.softening"]
```

```
  ?example ["0.5", "0.7"]
  ?recommended_range "0.3 to 1.0"
  ?performance_impact "Smaller values cost more"
  ?scientific_impact "Smaller values improve accuracy"
  ?deprecated "Never"
  ?replacement "gravity.opening_angle"
  ?since "3.0"
  ?category "Gravity"
  ?visibility "advanced"

# Conditional branches.
@if ({?enabled})
  selected str = "yes"
@elif ({?count} > 0)
  selected str = "positive"
@else
  selected str = "no"
@end

# Nested nodes and additional units.
vehicle
  wheels int = 4
  mass float = 1200 kg

# Override bodies contain value modifications without type declarations.
$override # Tune the existing vehicle settings.
  vehicle
    wheels = 6
    mass = 1.5e3 kg

# Collection declarations and items.
units list
units[]
  name str = "length"
  unit str = "23*au"
sources map
sources[constants]
  filepath str = "data/constants.dip"

# Import complete source and unit trees.
$source {imported?.}
$unit {imported?units?.}
```