

Translation Rules

High Level

| [*Expr*, *Param*, *Identifier*, *Field*]

$SCJBlock == \text{seq } Expr$
 $Params == \text{seq } Param$
 $SCJMethSig == Name \times Params$
 $SCJMethod == SCJMethSig \times SCJBlock$
 $Methods == \text{seq } SCJMethod$
 $Fields == \text{seq } Field$
 $SCJClass == Identifier \times Fields \times Methods$
 $SCJProg == \text{seq } SCJClass$

| [*Action*, *Circ Var*, *CircParam*, *CircName*, *CircType*,
CircExpression, *Paragraph*, *Framework*, *ChannelDefinition*,
ChanSetDefinition, *ProcDefinition*]

$CircActions == \text{seq } Action$
 $CircActions == \text{seq } CircAction$
 $CircState == \text{seq } CircVar$
 $CircParams == \text{seq } CircParam$
 $CircProcess == CircName \times CircParams \times CircState \times CircActions$
 $CircParagraph ::= Paragraph \mid ChannelDefinition \mid ChanSetDefinition \mid ProcDefinition$
 $CircusProg == \text{seq } CircParagraph$

$CircProcess == ProcDefinition$
 $OhCircusClass == ClassDefinition$
 $ChanTuple == (\text{seq } ChannelDefinition, \text{seq } ChanSetDefinition)$
 $Channels == ChanTuple$
 $MCBChans == ChanTuple$
 $MCBActions == \text{seq } Action$
 $ClassTuple == (CircProcess, OhCircusClass, Channels, MCBChans, MCBActions)$

| $TransSCJProg : SCJProg \mapsto (CircusProg, Framework)$
| $\forall scjProg : SCJProg \mid$
| $TransSCJProg(scjProg) = (TransClasses(\text{seq } C), Framework)$

$ProcChannels == (\text{seq } ChannelDefinition, \text{seq } ChanSetDefinition)$
 $Channels == ProcChannels$
 $MCBChans == ProcChannels$
 $MCBActions == \text{seq } Action$

$TransClasses : \text{seq } SCJClass \rightarrow \text{seq } ClassTuple$	
$\begin{aligned} &\forall \text{ classes} : \text{seq } SCJClass \bullet \\ &\quad \forall \text{ class} SCJClass \bullet \\ &\quad \quad TransClasses(\langle \text{class} \rangle) = TransClass(\text{class}) \wedge \\ &\quad \quad TransClasses(\langle \text{class} \rangle \frown \text{classes}) = \langle TransClass(c) \rangle \frown TransClasses(\text{classes}) \end{aligned}$	
$TransClass : SCJClass \rightarrow ClassTuple$	
$\begin{aligned} &\forall \text{ class} : SCJClass \mid \exists \text{ meths} : \text{seq } Methods \bullet \text{ meths} = MethodsOf(\text{class}) \bullet \\ &\quad TransClass(\text{class}) = \\ &\quad \quad (TransProc(\text{class}), TransOhClass(\text{class}), TransChans(\text{meths}), TransMCBChan(\text{meths})) \end{aligned}$	
$TransMeths : \text{seq } SCJMethod \rightarrow \text{seq } Action$	
$\begin{aligned} &\forall \text{ meths} : \text{seq } SCJMethod \bullet \\ &\quad \forall \text{ meth} : SCJMethod \bullet \\ &\quad \quad TransMeths(\langle \text{meth} \rangle) = TransMeth(\text{meth}) \wedge \\ &\quad \quad TransMeths(\langle \text{meth} \rangle \frown \text{meths}) = \langle TransMeth(\text{meth}) \frown TransMeths(\text{meths}) \rangle \end{aligned}$	
$TransMeth : SCJMethod \rightarrow Action$	
$\begin{aligned} &\forall m : SCJMethod \bullet \\ &\quad \exists ms : SCJMethSig; b : SCJBlock; p : Params \mid \\ &\quad \quad TransMeth(m) = (TransMethSig(ms), TransBlock(b), TransParams(p)) \end{aligned}$	
$TransParams : Params \rightarrow CircParams$	
$\begin{aligned} &\forall \text{ params} : Params \bullet \\ &\quad \forall \text{ param} : Param \bullet \\ &\quad \quad TransParams(\langle \text{param} \rangle) = TransParam(\text{param}) \\ &\quad \quad TransParams(\langle \text{param} \rangle \frown \text{params}) = \langle TransParam(\text{param}) \frown TransParams(\text{params}) \rangle \end{aligned}$	
$TransParam : Param \rightarrow CircParam$	
$TransBlock : SCJBlock \rightarrow CircBlock$	
$\begin{aligned} &\forall \text{ block} : SCJBlock \bullet \\ &\quad \forall e : Expr \bullet \\ &\quad \quad TransBlock(\langle e \rangle) = TransExpr(e) \wedge \\ &\quad \quad TransBlock(\langle e \rangle \frown \text{block}) = \langle TransExpr(e) \frown TransBlock(\text{block}) \rangle \end{aligned}$	

Low Level

- $Method : MethodDeclaration \mapsto (Name, Params, ReturnType, Body) :$ translates an active application method into a *Circus* action
- $DataMethod : MethodDeclaration \mapsto :$ translates data methods into an *OhCircus* method
- $MethodBody : Block \mapsto \text{seq } CircExpression :$ translates a Java block, for example a method body
- $Registers : Block \mapsto \text{seq } Name :$ extracts the Names of the schedulables registered in a Java block
- $Returns : Block \mapsto \text{seq } Name :$ extracts the Names of the variables returned in a Java block
- $Variable : (Name, Type, InitExpression) \mapsto (CircName, CircType, CircExpression) :$ translates a variable
- $Parameters : (Name, Params, ReturnType, Body) \mapsto \text{seq } CircParam :$ translates a list of method parameters
- $\llbracket Name \rrbracket_{name} :$ translates the *name* to a Z identifier
- $\llbracket varType \rrbracket_{type} :$ translates types
- $\llbracket expr \rrbracket_{expression} :$ translates expressions

Auxiliary Functions

- *IdOf(name)*: yields the identifier of a component called *name*
- *ObjectIdOf(name)*: yields the identifier of the *Object* process of a component called *name*
- *ThreadIdOf(name)*: yields the identifier of the *Thread* process of a component called *name*
- *MethodName(method)*: yields the method name of *method*

Pattern Matching Rules

Safelet

```
1 public class Identifier implements Safelet
2 {
3   FieldDeclaration_1
4   ...
5   FieldDeclaration_n
6
7   ConstructorDeclaration
8
9   initializeApplication
10
11  getSequencer
12
13  AppMeth_1
14  ...
15  AppMeth_n
16 }
```

process $\llbracket Identifier \rrbracket_{Name} App \hat{=} \llbracket \llbracket ConstructorDeclaration \rrbracket_{Method} \rrbracket_{Parameters} \mathbf{begin}$

State

this : ref $\llbracket Identifier \rrbracket_{name} Class$

state *State*

Init

State '
this := **new** $\llbracket Identifier \rrbracket_{name} Class()$

InitializeApplication $\hat{=}$

$$\left(\begin{array}{l} initializeApplicationCall \longrightarrow \\ \llbracket \llbracket InitializeApplication \rrbracket_{Method} \rrbracket_{MethBody} \\ initializeApplicationRet \longrightarrow \\ \mathbf{Skip} \end{array} \right)$$

GetSequencer $\hat{=}$

$$\left(\begin{array}{l} getSequencerCall \longrightarrow \\ getSequencerRet ! \llbracket GetSequencer \rrbracket_{Returns} \longrightarrow \\ \mathbf{Skip} \end{array} \right)$$

$\llbracket AppMeth_1 \rrbracket_{Method}$

...

$\llbracket AppMeth_n \rrbracket_{Method}$

$$Methods \hat{=} \left(\begin{array}{l} GetSequencer \\ \square \\ InitializeApplication \\ \square \\ MethName(AppMeth_1) \\ \square \\ \dots \\ MethName(AppMeth_n) \\ \dots \end{array} \right) ; Methods$$

$$\bullet (Init ; Methods) \triangle (end_safelet_app \longrightarrow \mathbf{Skip})$$

end

Mission Sequencer

```

1 public class Identifier extends MissionSequencer
2 {
3   FieldDeclaration_1
4   ...
5   FieldDeclaration_n
6
7   ConstructorDeclaration
8
9   getNextMission
10
11  AppMeth_1
12  ...
13  AppMeth_n
14 }

```

process $\llbracket Identifier \rrbracket_{Name} App \hat{=} \llbracket \llbracket ConstructorDeclaration \rrbracket_{Method} \rrbracket_{Parameters}$ **begin**

State

this : ref $\llbracket Identifier \rrbracket_{name} Class$

state *State*

Init

State'
this := **new** $\llbracket Identifier \rrbracket_{name} Class()$

GetNextMission $\hat{=} \mathbf{var} \text{ ret} : MissionID \bullet$

$$\left(\begin{array}{l} getNextMissionCall . IdOf(Identifier) \longrightarrow \\ ret := this . getNextMission(); \\ getNextMissionRet . IdOf(Identifier) ! ret \longrightarrow \\ \mathbf{Skip} \end{array} \right)$$

$\llbracket AppMeth_1 \rrbracket_{Method}$

...

$\llbracket AppMeth_n \rrbracket_{Method}$

Methods $\hat{=}$

$$\left(\begin{array}{l} GetNextMission \\ \square \\ MethName(AppMeth_1) \\ \square \\ MethName(AppMeth_n) \\ \dots \end{array} \right); Methods$$

$\bullet (Init ; Methods) \triangle (end_sequencer_app . IdOf(Identifier) \longrightarrow \mathbf{Skip})$

end

Mission

```

1 public class Identifier extends Mission
2 {
3   FieldDeclaration_1
4   ...
5   FieldDeclaration_n
6
7   ConstructorDeclaration
8
9   initialize
10
11  cleanUp
12
13  AppMeth_1
14  ...
15  AppMeth_n
16 }

```

process $\llbracket Identifier \rrbracket App \hat{=} \llbracket \llbracket ConstructorDeclaration \rrbracket_{Method} \rrbracket_{Parameters}$ **begin**

State
this : ref $\llbracket Identifier \rrbracket_{name} Class$

state *State*

Init
State '
this := **new** $\llbracket Identifier \rrbracket_{name} Class()$

InitializePhase $\hat{=}$

$$\left(\begin{array}{l} initializeCall . IdOf(Identifier) \longrightarrow \\ \llbracket initialize \rrbracket_{Registers} initializeRet . IdOf(Identifier) \longrightarrow \\ \mathbf{Skip} \end{array} \right)$$

CleanupPhase $\hat{=}$

$$\left(\begin{array}{l} cleanupMissionCall . IdOf(Identifier) \longrightarrow \\ cleanupMissionRet . IdOf(Identifier) ! \mathbf{True} \longrightarrow \\ \mathbf{Skip} \end{array} \right)$$

$\llbracket AppMeth_1 \rrbracket_{Method}$

...

$\llbracket AppMeth_n \rrbracket_{Method}$

Methods $\hat{=}$
$$\left(\begin{array}{l} InitializePhase \\ \square \\ CleanupPhase \\ \square \\ MethName(AppMeth_1) \\ \square \\ MethName(AppMeth_n) \\ \dots \end{array} \right) ; Methods$$

• $(Init ; Methods) \triangle (end_mission_app . IdOf(Identifier) \longrightarrow \mathbf{Skip}$

end

Handlers

```

1 class Identifier extends HandlerType
2 {
3   FieldDeclaration_1
4   ...
5   FieldDeclaration_n
6
7   ConstructorDeclaration
8
9   handleAsyncEvent
10
11   AppMeth_1
12   ...
13   AppMeth_n
14 }

```

process $\llbracket PName \rrbracket App \hat{=} \llbracket \llbracket ConstructorDeclaration \rrbracket_{Method} \rrbracket_{Parameters}$ **begin**

State
this : ref $\llbracket Identifier \rrbracket_{name} Class$

state *State*

Init
State '
this := **new** $\llbracket Identifier \rrbracket_{name} Class()$

handleAsyncEvent $\hat{=}$

$$\left(\begin{array}{l} handleAsyncEventCall . IdOf(PName) \longrightarrow \\ \llbracket \llbracket HandleAsyncBody \rrbracket_{Method} \rrbracket_{MethBody}; \\ handleAsyncEventRet . IdOf(PName) \longrightarrow \\ \mathbf{Skip} \end{array} \right)$$

$\llbracket AppMeth_1 \rrbracket_{Method}$

...

$\llbracket AppMeth_n \rrbracket_{Method}$

Methods $\hat{=}$

$$\left(\begin{array}{l} handleAsyncEvent \\ \square \\ MethName(AppMeth_1) \\ \square \\ MethName(AppMeth_n) \\ \dots \end{array} \right); Methods$$

• (*Init* ; *Methods*) $\triangle (end_ \llbracket HandlerTypeIdOf(PName) \rrbracket \longrightarrow \mathbf{Skip})$

end

Managed Thread

```

1 public class Identifier extends ManagedThread
2 {
3   FieldDeclaration_1
4   ...
5   FieldDeclaration_n
6
7   ConstructorDeclaration
8
9   run
10
11  AppMeth_1
12  ...
13  AppMeth_n
14 }

```

process $\llbracket PName \rrbracket App \hat{=} \llbracket \llbracket ConstructorDeclaration \rrbracket_{Method} \rrbracket_{Parameters}$ **begin**

State
 $this : \text{ref } \llbracket Identifier \rrbracket_{name} Class$

state *State*

Init
 $State'$
 $this := \text{new } \llbracket Identifier \rrbracket_{name} Class()$

$Run \hat{=}$

$$\left(\begin{array}{l} runCall . IdOf(PName) \longrightarrow \\ \llbracket \llbracket run \rrbracket_{Method} \rrbracket_{MethBody}; \\ runRet . IfOf(PName) \longrightarrow \\ \text{Skip} \end{array} \right)$$

$\llbracket AppMeth_1 \rrbracket_{Method}$

...

$\llbracket AppMeth_n \rrbracket_{Method}$

$Methods \hat{=}$

$$\left(\begin{array}{l} Run \\ \square \\ MethName(AppMeth_1) \\ \square \\ MethName(AppMeth_n) \\ \dots \end{array} \right); Methods$$

• $(Init ; Methods) \triangle (end_managedThread_app . IdOf(PName) \longrightarrow \text{Skip})$

end

Data Class

class $\llbracket PName \rrbracket_{name}$ *Class* $\hat{=}$ **begin**

state *State*

$\llbracket VarName \rrbracket_{name} : \llbracket VarType \rrbracket_{type}$

state *State*

initial *Init*

State '

$\llbracket VarName \rrbracket'_{name} = \llbracket VarInit \rrbracket_{expression}$

$\llbracket DataMeth1 \rrbracket_{dataMeth}$

$\llbracket DataMeth2 \rrbracket_{dataMeth}$

...

• **Skip**

end