mission1

Tight Rope v0.88

 $4 th \ March \ 2017$

1 ID Files

1.1 MissionIds

 ${\bf section}\ {\it Mission Ids}\ {\bf parents}\ {\it scj_prelude}, {\it Mission Id}$

MyMissionMID: MissionID

 $\overline{\ distinct \langle null Mission Id, My Mission MID \rangle}$

1.2 SchedulablesIds

 ${\bf section}\ Schedulable Ids\ {\bf parents}\ scj_prelude, Schedulable Id$

main Sequencer SID: Schedulable ID

 $\begin{array}{l} APEHSID: Schedulable ID \\ PEHSID: Schedulable ID \end{array}$

 $distinct \langle null Sequencer Id, null Schedulable Id, main Sequencer SID,$

APEHSID, PEHSID⟩

1.3	Non-Paradigm	Objects
-----	--------------	----------------

1.4 ThreadIds

 ${\bf section}\ ThreadIds\ {\bf parents}\ scj_prelude, GlobalTypes$

 $Safe let TId: Thread ID \\ null Thread Id: Thread ID$

 $\overline{distinct\langle SafeletTId, nullThreadId\rangle}$

1.5 ObjectIds

2 Network

2.1 Network Channel Sets

```
section NetworkChannels parents scj\_prelude, MissionId, MissionIds,
        Schedulable Id, Schedulable Ids, Mission Chan, Top Level Mission Sequencer FWChan,
        Framework Chan, Safelet Chan, Aperiodic Event Handler Chan, Managed Thread Chan,
        One Shot Event Handler Chan, Periodic Event Handler Chan, Mission Sequencer Meth Chan
channelset TerminateSync ==
        \{ schedulables\_terminated, schedulables\_stopped, get\_activeSchedulables \} 
{\bf channel set} \ {\it Control Tier Sync} = =
        \{ | start\_toplevel\_sequencer, done\_toplevel\_sequencer, done\_safeletFW | \}
channelset TierSync ==
        \{ | start\_mission . MyMission, done\_mission . MyMission, \} 
        done_safeletFW, done_toplevel_sequencer \}
{f channel set} \ {\it Mission Sync} ==
        \{|done\_safeletFW, done\_toplevel\_sequencer, register, \}
signal Termination Call, signal Termination Ret, activate\_schedulables, done\_schedulable,
cleanupSchedulableCall, cleanupSchedulableRet }
channelset SchedulablesSync ==
        \{|activate\_schedulables, done\_safeletFW, done\_toplevel\_sequencer|\}
channelset ClusterSync ==
        \{|\ done\_toplevel\_sequencer, done\_safeletFW\ |\}
channelset SafeltAppSync =
\{ getSequencerCall, getSequencerRet, initializeApplicationCall, initializeApplicationRet, end\_safelet\_app \} \}
{f channel set} \ {\it Mission Sequencer App Sync} ==
\{|getNextMissionCall, getNextMissionRet, end\_sequencer\_app|\}
{f channel set} \ {\it MissionAppSync} ==
\{|initializeCall, register, initializeRet, cleanupMissionCall, cleanupMissionRet|\}
channelset AppSync ==
        [] { SafeltAppSync, MissionSequencerAppSync, MissionAppSync, }
        MTAppSync, OSEHSync, APEHSync, PEHSync,
        \{|getSequencer, end\_mission\_app, end\_managedThread\_app, | end\_managed
        setCeilingPriority, requestTerminationCall, requestTerminationRet, terminationPendingCall,
        terminationPendingRet, handleAsyncEventCall, handleAsyncEventRet \}
channelset ThreadSync ==
        \{ raise\_thread\_priority, lower\_thread\_priority, isInterruptedCall, isInterruptedRet, get\_priorityLevel \} \}
channelset \ LockingSync ==
        \{ lockAcquired, startSyncMeth, endSyncMeth, waitCall, waitRet, notify, isInterruptedCall, isInterruptedRet, \} \}
        interruptedCall, interruptedRet, done\_toplevel\_sequencer, get\_priorityLevel
```

2.2 Locking

 $\begin{array}{l} \textbf{section} \ \ NetworkLocking \ \textbf{parents} \ \ scj_prelude, \ GlobalTypes, \ FrameworkChan, \ MissionId, \ MissionIds, \ ThreadIds, \ NetworkChannels, \ ObjectFW, \ ThreadFW, \ Priority \end{array}$

```
\begin{array}{l} \mathbf{process} \ Threads \ \widehat{=} \\ \mathbf{(Skip)} \\ \\ \mathbf{process} \ Objects \ \widehat{=} \\ \mathbf{(Skip)} \\ \\ \mathbf{process} \ Locking \ \widehat{=} \ (Threads \ \llbracket \ ThreadSync \ \rrbracket \ Objects) \ \triangle \ (done\_toplevel\_sequencer \longrightarrow \mathbf{Skip}) \end{array}
```

2.3 Program

```
section Program parents scj_prelude, MissionId, MissionIds,
    SchedulableId, SchedulableIds, MissionChan, SchedulableMethChan, MissionFW,
    Safe let FW, Top Level Mission Sequencer FW, Network Channels, Managed Thread FW,
    Schedulable Mission Sequencer FW, Periodic Event Handler FW, One Shot Event Handler FW,
    Aperiodic Event Handler FW, Object FW, Thread FW,\\
    MyAppApp, mainSequencerApp, MyMissionApp, APEHApp, PEHApp
process ControlTier =
 SafeletFW
      [ControlTierSync]
  TopLevel Mission Sequencer FW (main Sequencer)
process Tier0 =
  MissionFW(MyMissionID)
      [MissionSync]
    (AperiodicEventHandlerFW(APEHID, aperiodic, (time(5,0), nullSchedulableId)))
        [SchedulablesSync]
    PeriodicEventHandlerFW(PEHID, (time(60, 0), time(5, 0), NULL, nullSchedulableId))
\mathbf{process} \ \mathit{Framework} \ \widehat{=}
  ControlTier\\
      [TierSync]
  (Tier0)
\mathbf{process} Application =
 MyAppApp
  mainSequencerApp
  MyMissionApp
  APEHApp(MyMissionID)
  PEHApp(apehID)
process\ Program \ \widehat{=}\ (Framework\ \llbracket\ AppSync\ \rrbracket\ Application)\ \llbracket\ LockingSync\ \rrbracket\ Locking
```

3 Safelet

 ${\bf section}\ MyAppApp\ {\bf parents}\ scj_prelude, Schedulable Id, Schedulable Ids, Safelet Chan, Method Call Binding Channels$

 $\mathbf{process}\,\mathit{MyAppApp} \,\, \widehat{=}\, \mathbf{begin}$

```
 \begin{array}{l} InitializeApplication \; \widehat{=} \\ \left( \begin{array}{l} initializeApplicationCall \longrightarrow \\ initializeApplicationRet \longrightarrow \\ \mathbf{Skip} \end{array} \right) \end{array}
```

 $\bullet \; (Methods) \; \triangle \; (end_safelet_app \longrightarrow \mathbf{Skip})$

end

4 Top Level Mission Sequencer

section mainSequencerApp parents TopLevelMissionSequencerChan, Mission Id, Mission Ids, Schedulable Id, Schedulable Ids, main Sequencer Class, Method Call Binding Channels $process mainSequencerApp \stackrel{\frown}{=} begin$ $State_{-}$ $this: {\bf ref}\ main Sequencer Class$ ${f state}\, State$ InitState' $this' = \mathbf{new} \ mainSequencerClass()$ $GetNextMission \stackrel{\frown}{=} \mathbf{var} \ ret : MissionID \bullet$ $ret := this. getNextMission(); \\ getNextMissionRet. mainSequencerSID! ret \longrightarrow$ \ Skip $Methods \stackrel{\frown}{=}$ (GetNextMission); Methods ullet (Init; Methods) \triangle (end_sequencer_app.mainSequencerSID \longrightarrow **Skip**) end

 $\begin{array}{l} \textbf{section} \ main Sequencer Class \ \textbf{parents} \ scj_prelude, Schedulable Id, Schedulable Ids, Safelet Chan, Method Call Binding Channels, Mission Id, Mission Ids \end{array}$

 $\mathbf{class}\,\mathit{mainSequencerClass} \,\, \widehat{=} \,\, \mathbf{begin}$

```
state \, State \, \_
notReleased: \mathbb{B}
```

 $\mathbf{state}\,\mathit{State}$

```
__initial Init_____
State'

notReleased' = true
```

• Skip

 \mathbf{end}

5 Missions

5.1 MyMission

 ${\bf section}\ MyMission App\ {\bf parents}\ scj_prelude, Mission Id, Mission Ids, \\ Schedulable Id, Schedulable Ids, Mission Chan, Schedulable Meth Chan, MyMission Meth Chan, \\ Method Call Binding Channels$

 $process MyMissionApp \stackrel{\frown}{=} begin$

```
 \begin{array}{l} InitializePhase \; \widehat{=} \\ \left( \begin{array}{l} initializeCall \; . \; MyMissionMID \longrightarrow \\ register \; ! \; APEHSID \; ! \; MyMissionMID \longrightarrow \\ register \; ! \; PEHSID \; ! \; MyMissionMID \longrightarrow \\ initializeRet \; . \; MyMissionMID \longrightarrow \\ \mathbf{Skip} \end{array} \right)
```

$$Methods \cong \begin{pmatrix} InitializePhase \\ \Box \\ CleanupPhase \end{pmatrix}$$
; $Methods$

ullet (Methods) \triangle (end_mission_app . MyMissionMID \longrightarrow **Skip**)

end

5.2 Schedulables of MyMission

 ${\bf section}\ APEHApp\ {\bf parents}\ Aperiodic Event Handler Chan, Schedulable Id, Schedulable Ids, Method Call Binding Channels$

```
 \begin{aligned} & \operatorname{process} APEHApp \; \widehat{=} \\ & \operatorname{controllingMission} : \operatorname{MissionID} \bullet \mathbf{begin} \end{aligned}   \begin{aligned} & \operatorname{handleAsyncEvent} \; \widehat{=} \\ & \left( \begin{array}{c} \operatorname{handleAsyncEvent} Call \cdot \operatorname{APEHSID} \longrightarrow \\ \operatorname{crequestTerminationCall} \cdot \operatorname{controllingMission} \cdot \operatorname{APEHSID} \longrightarrow \\ \operatorname{requestTerminationRet} \cdot \operatorname{controllingMission} \cdot \operatorname{APEHSID} ? \operatorname{requestTermination} \longrightarrow \\ \operatorname{Skip} \\ & \operatorname{handleAsyncEventRet} \cdot \operatorname{APEHSID} \longrightarrow \\ \operatorname{Skip} \\ & \\ \end{aligned}   \begin{aligned} & \operatorname{Methods} \; \widehat{=} \\ & \left( \operatorname{handleAsyncEvent} \right) \; ; \; \operatorname{Methods} \end{aligned}   \end{aligned}   \end{aligned}   \end{aligned}   \end{aligned}   \end{aligned}   \end{aligned} (\operatorname{Methods}) \; \triangle \left( \operatorname{end\_aperiodic\_app} \cdot \operatorname{APEHSID} \longrightarrow \operatorname{Skip} \right)   \end{aligned}   \end{aligned}   \end{aligned}   \end{aligned}   \end{aligned}   \end{aligned}   \end{aligned}   \end{aligned}   \end{aligned} (\operatorname{Methods}) \; \triangle \left( \operatorname{end\_aperiodic\_app} \cdot \operatorname{APEHSID} \longrightarrow \operatorname{Skip} \right)   \end{aligned}   \end{aligned}   \end{aligned}   \end{aligned}   \end{aligned}   \end{aligned}
```

 ${\bf section}\ PEHApp\ {\bf parents}\ Periodic Event Handler Chan, Schedulable Id, Schedulable Ids, Method Call Binding Channels$

```
process PEHApp \cong
apeh : SchedulableID \bullet \mathbf{begin}

handle AsyncEvent \cong
\begin{pmatrix} handle AsyncEvent Call . PEHSID \longrightarrow \\ (release . apeh \longrightarrow ); \\ Skip \end{pmatrix};
handle AsyncEventRet . PEHSID \longrightarrow \\ Skip \end{pmatrix}

Methods \cong
\begin{pmatrix} handle AsyncEvent \end{pmatrix}; Methods

• (Methods) \triangle (end\_periodic\_app . PEHSID \longrightarrow \mathbf{Skip})

end
```