ALGO® 3

Newborn Hearing Screener

Patent Pending



Speed.
Simplicity.
Accuracy.

Every time.

The AABR® technology you can trust

- Lowest refer rates[1] – supported by numerous published studies within respected peer-reviewed journals
- A complete screen of the hearing pathway in one simple step

Fast & simple operation

- Fully automated, objective pass/refer results that require no interpretation
- Completely standardized, pre-set screening parameters that cannot be adjusted
- Screens both ears simultaneously
- Compatibility with bar code scanners — allowing fast data entry
- Colored graphical displays guide you easily through the screening process
- Audio-visual tutorial provides helpful tips on how to conduct a screen

Data transfer & data management

- Unique DataBook® Data Tracking System software provides large storage capacity for screening records
- Transfer of screening data to a PC via diskette, USB flash drive, or CD
- EchoLink™ II software facilitates the transfer, storage, & tracking of data
  - Data can be transferred to a PC & imported into an EchoLink file for viewing, sorting, editing & archiving
  - Data can be transferred to, or retrieved from OZ SIMS®, NCHAM Hi*Track and Microsoft® Excel databases
- Compatibility with a variety of data management systems

Flexible screening workstation

- Cart allows easy transport of the ALGO 3 system to different locations
- Spacious shelves and drawer are available for storing screening supplies

[1] *References on file at Natus*

ALGO® 3
Newborn Hearing Screener
Patent Pending



The ALGO 3 Newborn Hearing Screening System includes:

- ALGO 3 Screener – with integrated laptop computer
- Screening cart
- Sensor cable
- Earphone cable
- Label Printer
- Instructional materials
- ALGO Check Kit
- ALGO DataBook® NHS Data Tracking System Software
- EchoLink™ II Software (on CD)

Technical Specifications:

Sweep Rates
37 clicks/second, (nominal) or
34 clicks/second (nominal) alternating

Power Supply

Power Rating
100-120 V~, 200-240 V~
100 VA, 50/60 Hz

Physical Characteristics

Nominal Dimensions (Screening Module)
Open: 15 x 17.5 x 16 inches
38.1 x 44.45 x 40.64 cm (H x W x D)
Closed: 5.25 x 17.5 x 16 inches
13.34 x 44.45 x 40.64 cm (H x W x D)

Nominal Dimensions (Cart w/Screening Module)
45.5 x 20.5 x 24 inches
115.6 x 52.07 x 60.96 cm (H x W x D)

Nominal Weight (Screening Module)
20 lbs (9.1 kg)

Nominal Weight (Cart w/Screening Module)
72 lbs (32.7 kg)

Temperature Range
10°→40° C operating (50°→104° F)
-20°→40° C storage (-4°→104° F)

Humidity Range
10-90% non-condensing

Operating Altitude
Sea level - 6000 ft

Safety and EMC Standards
Complies with: UL2601-1
CSA-22.2 601-1
EN60601-1
EN60601-1-2

Classifications
Class I equipment, Type BF applied part

Ordinary equipment for protecting against ingress of water

Not suitable for use in the presence of flammable anaesthetic mixtures with air, oxygen, or nitrous oxide

natus®
Natus Medical Inc. • San Carlos, CA USA
www.natus.com
customer _ service@natus.com
+1 650-802-0400, 800-255-3901
Fax: +1 650-802-0401

CE 0197

P/N 050916F