



SHAPE OPTIMIZATION USING PHIFEM

Josué Daniel Díaz Avalos¹, **Raphaël Bulle**², Stéphane Cotin², Louis Ducongé³, Michel Duprez², Antoine Laurain¹

¹ Universität Duisburg-Essen

² Inria de l'Université de Lorraine

³ Université de Lorraine

Submission type: Poster

Presenter: Raphaël Bulle (Inria de l'Université de Lorraine)

The level-set method for evolving interfaces was first introduced in [1] and has been applied to a variety of shape optimization problems (see e.g. [3,4,5,6,7,8]). The core idea of this method is to use a level-set description of the domain to be optimized and modify this level-set e.g. by the derivation of optimality conditions via the shape derivative of the domain [3].

Like the level-set method, the φ -FEM takes advantage of a description of the domain via a level-set. The φ -FEM is an immersed boundary finite element method (FEM) with optimal convergence rate and conditioning which does not require any non-standard quadrature rule on cut cells nor non-standard finite element shape functions [9,10]. Thus, the φ -FEM is naturally well suited to be used with the level-set method to perform shape optimization as it provides a good description of the evolving boundary without any re-meshing of the domain.

In this talk, we describe a preliminary study on a shape optimization algorithm using φ -FEM to solve the state equations. This algorithm is implemented in FEniCSx via the recent FormOpt shape optimization toolbox [8] and the phiFEM python package [11]. We investigate the benefits of using φ -FEM instead of a standard non-conforming FEM by performing several numerical comparisons on different types of shape optimization problems.

References

- [1] Osher, Stanley, and James A. Sethian. 1988. "Fronts Propagating with Curvature-Dependent Speed: Algorithms Based on Hamilton-Jacobi Formulations." *Journal of Computational Physics* 79(1):12-49. DOI: 10.1016/0021-9991(88)90002-2.
- [2] Sethian, J. A. 1999. *Level Set Methods and Fast Marching Methods: Evolving Interfaces in Computational Geometry, Fluid Mechanics, Computer Vision, and Materials Science*. Cambridge University Press.
- [3] Allaire, Grégoire, François Jouve, and Anca-Maria Toader. 2002. "A Level-Set Method for Shape Optimization." *Comptes Rendus Mathématique* 334(12):1125-30. DOI: 10.1016/S1631-073X(02)02412-3.
- [4] Feppon, F., G. Allaire, F. Bordeu, J. Cortial, and C. Dapogny. 2019. "Shape Optimization of a Coupled Thermal Fluid-Structure Problem in a Level Set Mesh Evolution Framework." *SeMA Journal* 76(3):413-58. DOI: 10.1007/s40324-018-00185-4.
- [5] Maury, Aymeric, Grégoire Allaire, and François Jouve. 2018. "Elasto-Plastic Shape Optimization Using the Level Set Method." *SIAM Journal on Control and Optimization* 56(1):556-81. DOI: 10.1137/17M1128940.

[6] Maury, Aymeric, Grégoire Allaire, and François Jouve. 2017. "Shape Optimisation with the Level Set Method for Contact Problems in Linearised Elasticity." *The SMAI Journal of Computational Mathematics* 3:249-92. DOI: 10.5802/smai-jcm.27.

[7] Laurain, Antoine. 2018. "A Level Set-Based Structural Optimization Code Using FEniCS." *Structural and Multidisciplinary Optimization* 58(3):1311-34. DOI: 10.1007/s00158-018-1950-2.

[8] Díaz-Avalos, Josué D., and Antoine Laurain. 2026. "FormOpt: A FEniCSx Toolbox for Level Set-Based Shape Optimization Supporting Parallel Computing." DOI: 10.48550/arXiv.2601.05709.

[9] Duprez, Michel, and Alexei Lozinski. 2020. " φ -FEM: A Finite Element Method on Domains Defined by Level-Sets." *SIAM Journal on Numerical Analysis* 58(2):1008-28. DOI: 10.1137/19M1248947.

[10] Duprez, Michel, Vanessa Lleras, and Alexei Lozinski. 2023. "A New φ -FEM Approach for Problems with Natural Boundary Conditions." *Numerical Methods for Partial Differential Equations* 39(1):281-303. DOI: 10.1002/num.22878.

[11] Bulle, Raphael, Michel Duprez, and Killian Vuillemot. 2025. "phiFEM: A Convenience Package for Using phiFEM with FEniCSx." DOI: 10.6084/M9.FIGSHARE.30373546.