



INTEGRATION OF EXTERNALLY DEFINED CONSTITUTIVE MODELS INTO FEniCSx USING DOLFINX-EXTERNAL-OPERATOR

Andrey Latyshev^{1,2}, Jørgen S. Dokken³, Jérémy Bleyer⁴, Corrado Maurini², Jack S. Hale¹

¹ University of Luxembourg

² Institut Jean Le Rond d'Alembert, Sorbonne Université

³ Simula Research Laboratory

⁴ Laboratoire Navier, École des Ponts ParisTech, Université Gustave Eiffel

Submission type: Software Demonstration

Presenter: Andrey Latyshev (University of Luxembourg, Institut Jean Le Rond d'Alembert, Sorbonne Université)

The Unified Form Language (UFL) (Alnaes et al., 2013) is essential for writing variational forms of partial differential equations (PDEs) in automated finite element solvers like FEniCS. However, UFL has a critical limitation: non-trivial solid mechanics problems, such as complex plasticity or neural network constitutive models, cannot be naturally formulated within it. This restriction has slowed FEniCS adoption in the broader solid mechanics community.

To overcome this bottleneck, we introduce DOLFINx-External-Operator (Latyshev et al., 2025), a novel software framework for FEniCSx. Based on DOLFINx's new data-centric design (Baratta et al., 2023), automatic UFL Expression code generation, and the UFL ExternalOperator extension (Bouziani & Ham, 2021), this tool enables the seamless integration of arbitrary constitutive models via third-party packages that support ndarray-like data structures, such as JAX (Bradbury et al., 2018) and Numba (Lam et al., 2015).

As a particular outcome, we leverage JAX for forward-mode algorithmic automatic differentiation (AD), eliminating the need for error-prone manual derivatives. We demonstrate the use of AD on a complex non-associative Mohr-Coulomb elastoplastic model with apex smoothing (Helfer et al., 2024). The framework and examples are open-source under the LGPLv3 license.

References

- Alnaes, M. S., Logg, A., Ølgaard, K. B., Rognes, M. E., & Wells, G. N. (2014). Unified form language: A domain-specific language for weak formulations of partial differential equations. *ACM Transactions on Mathematical Software*, 40(2), 9:1-9:37. DOI: 10.1145/2566630
- Baratta, I. A., Dean, J. P., Dokken, J. S., Habera, M., Hale, J. S., Richardson, C. N., Rognes, M. E., Scroggs, M. W., Sime, N., & Wells, G. N. (2023). DOLFINx: The next generation FEniCS problem solving environment. Zenodo. DOI: 10.5281/zenodo.10447666
- Bouziani, N., & Ham, D. A. (2021). Escaping the abstraction: A foreign function interface for the Unified Form Language [UFL] (arXiv:2111.00945). arXiv. DOI: 10.48550/arXiv.2111.00945

Bradbury, J., Frostig, R., Hawkins, P., Johnson, M. J., Katariya, Y., Leary, C., Maclaurin, D., Necula, G., Paszke, A., Vander-Plas, J., Wanderman-Milne, S., & Zhang, Q. (2018). JAX: Composable transformations of Python+NumPy programs (Version 0.3.13) [Computer software]. <http://github.com/jax-ml/jax>

Helfer, T., Michel, B., Proix, J.-M., Sercombe, J., Casella, M., & Salvo, M. (2024). Invariant-based implementation of the Mohr-Coulomb elasto-plastic model in OpenGeoSys using MFront (Version 4.2.1) [Computer software]. <https://thelfer.github.io/tfel/web/MohrCoulomb.html>

Latyshev, A., Bleyer, J., Maurini, C., & Hale, J. (2025). Expressing general constitutive models in FEniCSx using external operators and algorithmic automatic differentiation. *Journal of Theoretical, Computational and Applied Mechanics*. DOI: 10.46298/jtcam.14449