

03 21 Reinforcement Bars

03 21 05 – Reinforcing Steel Accessories

03 21 05.10 Rebar Accessories			Daily	Labor-	Unit	Material	2022 Bare Costs		Total	Total
			Crew	Output	Hours		Labor	Equipment		Incl O&P
1900	For continuous bottom wire runners, add	G			C.L.F.	49.50			49.50	54.50
1940	For continuous bottom plate, add	G			↓	264			264	290
2200	Screed chair base, 1/2" coil thread diam., 2-1/2" high, plain steel	G			C	410			410	455
2210	Galvanized	G				495			495	540
2220	5-1/2" high, plain	G				495			495	545
2250	Galvanized	G				585			585	645
2300	3/4" coil thread diam., 2-1/2" high, plain steel	G				535			535	590
2310	Galvanized	G				615			615	675
2320	5-1/2" high, plain steel	G				675			675	740
2350	Galvanized	G				835			835	915
2400	Screed holder, 1/2" coil thread diam. for pipe screed, plain steel, 6" long	G			↓	500			500	550
2420	12" long	G			C	760			760	840
2500	3/4" coil thread diam. for pipe screed, plain steel, 6" long	G				665			665	735
2520	12" long	G				1,075			1,075	1,175
2700	Screw anchor for bolts, plain steel, 3/4" diameter x 4" long	G				610			610	670
2720	1" diameter x 6" long	G				1,125			1,125	1,250
2740	1-1/2" diameter x 8" long	G				1,550			1,550	1,700
2800	Screw anchor eye bolts, 3/4" x 3" long	G				3,600			3,600	3,950
2820	1" x 3-1/2" long	G				4,650			4,650	5,100
2840	1-1/2" x 6" long	G				14,200			14,200	15,600
2900	Screw anchor bolts, 3/4" x 9" long	G				2,275			2,275	2,500
2920	1" x 12" long	G				4,375			4,375	4,825
3001	Slab lifting inserts, single pickup, galv, 3/4" diam., 5" high	G				2,400			2,400	2,650
3010	6" high	G				2,375			2,375	2,600
3030	7" high	G				2,425			2,425	2,650
3100	1" diameter, 5-1/2" high	G				2,450			2,450	2,700
3120	7" high	G				2,425			2,425	2,675
3200	Double pickup lifting inserts, 1" diameter, 5-1/2" high	G				4,750			4,750	5,225
3220	7" high	G				5,275			5,275	5,800
3330	1-1/2" diameter, 8" high	G				6,550			6,550	7,200
3800	Subgrade chairs, #4 bar head, 3-1/2" high	G				46			46	50.50
3850	12" high	G				54			54	59.50
3900	#6 bar head, 3-1/2" high	G				46			46	50.50
3950	12" high	G				54			54	59.50
4200	Subgrade stakes, no nail holes, 3/4" diameter, 12" long	G				298			298	330
4250	24" long	G				445			445	485
4300	7/8" diameter, 12" long	G				475			475	525
4350	24" long	G				505			505	555
4500	Tie wire, 16 ga. annealed steel	G			Cwt.	167			167	183

03 21 05.75 Splicing Reinforcing Bars

0010	SPlicing REINFORCING BARS	R032110-70								
0020	Including holding bars in place while splicing									
0100	Standard, self-aligning type, taper threaded, #4 bars	G	C-25	190	.168	Ea.	12.80	8.25	21.05	27
0105	#5 bars	G	↓	170	.188		15	9.20	24.20	30.50
0110	#6 bars	G	↓	150	.213		17.70	10.45	28.15	35.50
0120	#7 bars	G	↓	130	.246		21	12.05	33.05	41.50
0300	#8 bars	G	↓	115	.278		24.50	13.65	38.15	48
0305	#9 bars	G	C-5	105	.533		27.50	32	19.95	100
0310	#10 bars	G	"	95	.589	↓	34.50	35.50	22	92
0320	#11 bars	G	C-5	85	.659	Ea.	32.50	40	24.50	97
0330	#14 bars	G	↓	65	.862		51.50	52	32	135.50
0340	#18 bars	G	↓	45	1.244	↓	78.50	75	46.50	200