

09 62 Specialty Flooring

09 62 19 – Laminate Flooring

09 62 19.10 Floating Floor

		Crew	Daily Output	Labor-Hours	Unit	Material	2022 Bare Costs Labor	Equipment	Total	Total Incl 08
0010	FLOATING FLOOR									
8300	Floating floor, laminate, wood pattern strip, complete	1 Clab	133	.060	S.F.	5.45	2.74		8.19	10
8310	Components, T&G wood composite strips					4.20			4.20	4
8320	Film					.74			.74	
8330	Foam					.29			.29	
8340	Adhesive					.89			.89	
8350	Installation kit					.25			.25	
8360	Trim, 2" wide x 3' long				L.F.	8			8	8
8370	Reducer moulding				"	7.40			7.40	8

09 62 29 – Cork Flooring

09 62 29.10 Cork Tile Flooring

0010	CORK TILE FLOORING									
2200	Cork tile, standard finish, 1/8" thick	G	1 Tlf	315	.025	S.F.	3.51	1.35	4.86	5
2250	3/16" thick	G		315	.025		5.10	1.35	6.45	7
2300	5/16" thick	G		315	.025		4.49	1.35	5.84	6
2350	1/2" thick	G		315	.025		4.12	1.35	5.47	6
2500	Urethane finish, 1/8" thick	G		315	.025		5.70	1.35	7.05	8
2550	3/16" thick	G		315	.025		8.35	1.35	9.70	11
2600	5/16" thick	G		315	.025		6.90	1.35	8.25	9
2650	1/2" thick	G		315	.025		6.25	1.35	7.60	8

09 63 Masonry Flooring

09 63 13 – Brick Flooring

09 63 13.10 Miscellaneous Brick Flooring

0010	MISCELLANEOUS BRICK FLOORING									
0020	Acid-proof shales, red, 8" x 3-3/4" x 1-1/4" thick		D-7	.43	37.209	M	625	1,775	2,400	3,300
0050	2-1/4" thick		D-1	.40	40		1,025	2,000	3,025	4,125
0200	Acid-proof clay brick, 8" x 3-3/4" x 2-1/4" thick	G		.40	40		1,050	2,000	3,050	4,150
0250	9" x 4-1/2" x 3"	G		.95	.168	S.F.	4.20	8.45	12.65	17
0260	Cast ceramic, pressed, 4" x 8" x 1/2", unglazed		D-7	100	.160		7.50	7.70	15.20	19
0270	Glazed			100	.160		10	7.70	17.70	22
0280	Hand molded flooring, 4" x 8" x 3/4", unglazed			95	.168		9.90	8.10	18	22
0290	Glazed			95	.168		10.90	8.10	19	24
0300	8" hexagonal, 3/4" thick, unglazed			85	.188		9.50	9.05	18.55	23
0310	Glazed			85	.188		17.15	9.05	26.20	32
0400	Heavy duty industrial, cement mortar bed, 2" thick, not incl. brick		D-1	80	.200		.91	10.05	10.96	16
0450	Acid-proof joints, 1/4" wide		"	65	.246		1.72	12.35	14.07	20
0500	Pavers, 8" x 4", 1" to 1-1/4" thick, red		D-7	95	.168		2.16	8.10	10.26	14
0510	Ironspot		"	95	.168		5.40	8.10	13.50	17
0540	1-3/8" to 1-3/4" thick, red		D-1	95	.168		2.07	8.45	10.52	15
0560	Ironspot			95	.168		5.35	8.45	13.80	18
0580	2-1/4" thick, red			90	.178		12.25	8.90	21.15	27
0590	Ironspot			90	.178		22.50	8.90	31.40	38
0700	Paver, adobe brick, 6" x 12", 1/2" joint	G		42	.381		1.30	19.10	20.40	30
0710	Mexican red, 12" x 12"	G	1 Tlf	48	.167		1.80	8.85	10.65	14
0720	Saltillo, 12" x 12"	G	"	48	.167		1.38	8.85	10.23	14
0800	For sidewalks and patios with pavers, see Section 32 14 16.10									
0870	For epoxy joints, add		D-1	600	.027	S.F.	3.27	1.34	4.61	5
0880	For Furan underlayment, add		"	600	.027		2.70	1.34	4.04	4
0890	For waxed surface, steam cleaned, add		A-1H	1000	.008		.21	.36	.57	