## 07 13 Sheet Waterproofing

07 13 53 - Elastomeric Sheet Waterproofing

37 41	E2 40 Floatemaria Chaot Waterray Sing and Access		Daily		11.5		2022 Ba		7.1	Total
ALC: UNKNOWN	3 53.10 Elastomeric Sheet Waterproofing and Access.	Crew	Output	Hours	Unit	Material	Labor	Equipment	Total	Incl O&P
0010	ELASTOMERIC SHEET WATERPROOFING AND ACCESS.									
090	EPDM, plain, 45 mils thick	2 Rofc	580	.028	S.F.	.79	1.37		2.16	3.08
0100	60 mils thick		570	.028		.91	1.39		2.30	3.26
0300	Nylon reinforced sheets, 45 mils thick		580	.028		.97	1.37		2.34	3.29
0400	60 mils thick	1	570	.028	+	1.13	1.39		2.52	3.50
3600	Vulcanizing splicing tape for above, 2" wide	1			C.L.F.	63		i	63	69.50
0700	4" wide	1			"	355			355	390
0900	Adhesive, bonding, 60 S.F./gal.				Gal.	42			42	46
1000	Splicing, 75 S.F./gal.				Gal.	37			37	40.50
1200	Neoprene sheets, plain, 45 mils thick	2 Rofc	580	.028	S.F.	1.31	1.37		2.68	3.66
1300	60 mils thick	1	570	.028	i i	2.03	1.39		3.42	4.49
1500	Nylon reinforced, 45 mils thick	1	580	.028		2.63	1.37		4	5.10
1600	60 mils thick	1 1	570	.028		4.81	1.39		6.20	7.55
1800	120 mils thick	1 🔱	500	.032	+	8.10	1.59	William I	9.69	11.45
1900	Adhesive, splicing, 150 S.F./gal. per coat				Gal.	37			37	40.50
2100	Fiberglass reinforced, fluid applied, 1/8" thick	2 Rofc	500	.032	S.F.	1.58	1.59		3.17	4.31
2200	Polyethylene and rubberized asphalt sheets, 60 mils thick		550	.029		.70	1.44		2.14	3.11
2400	Polyvinyl chloride sheets, plain, 10 mils thick		580	.028		.17	1.37		1.54	2.41
2500	20 mils thick		570	.028		.23	1.39		1.62	2.51
2700	30 mils thick		560	.029	1	.23	1.42		1.65	2.55
3000	Adhesives, trowel grade, 40-100 S.F./gal.				Gal.	28.50			28.50	31.50
3100	Brush grade, 100-250 S.F./gal.	-			"	25.50			25.50	28.50
3300	Bitumen modified polyurethane, fluid applied, 55 mils thick	2 Rofc	665	.024	S.F.	1.17	1.19	T Committee	2.36	3.22
	the state of the s									

## 07 16 Cementitious and Reactive Waterproofing

07 16 16 - Crystalline Waterproofing

07 16 16.20 Cementitious Waterproofing

10	CEMENTITIOUS WATERPROOFING	
20	1/8" application, sprayed on	
50	A cont compatitious motallic clurry	

1/8" application, sprayed on			G-2A	1000	.024	S.F.	.67	1.06	.66	2.39	3.14
4 coat cementitious metallic slurry	. 7		1 Cefi	1.20	6.667	C.S.F.	81.50	355		436.50	610

## 07 17 Bentonite Waterproofing

07 17 13 - Bentonite Panel Waterproofing

n	7	1	7	K	3	14	n	E	0	n	٠	n	n	i	ŧ۷	>
ŭ	u						v		A.C	ш	U	v	ш	u		-

0010	BENTONITE								
0020	Panels, 4' x 4', 3/16" thick	1 Rofc 625	.013	S.F.	2.33	.63		2.96	3.59
0100	Rolls, 3/8" thick, with geotextile fabric both sides	″ 550	.015	#	1.97	.72		2.69	3.34
0300	Granular bentonite, 50 lb. bags (.625 C.F.)			Bag	25.50			25.50	28
0400	3/8" thick, troweled on	1 Rofc   475	.017	S.F.	1.28	.84		2.12	2.76
0500	Drain board, expanded polystyrene, 1-1/2" thick	1 Rohe 1600	.005	Total State of the	.42	.19		.61	.76
0510	2" thick	1   1600	.005	- 1 1	.56	.19	1	.75	.92
0520	3" thick	1   1600	.005		.84	.19		1.03	1.22
0530	4" thick	1600	.005		1.12	.19		1.31	1.53
0600	With filter fabric, 1-1/2" thick	1600	.005		.52	.19		.71	.87
0625	2" thick	1600	.005		.66	.19		.85	1.02
0650	3" thick	1600	.005		.94	.19		1.13	1.33
0675	4" thick	1 🗼   1600	.005	+1	1.22	.19	1	1.41 [	1.64