

# 09 32 Mortar-Bed Tiling

## 09 32 23 – Mortar-Bed Glass Mosaic Tiling

09 32 23.10 Glass Mosaics		Crew	Daily Output	Labor-Hours	Unit	Material	2022 Bare Costs Labor	Equipment	Total	Total Incl O&P
0010	<b>GLASS MOSAICS</b> 3/4" tile on 12" sheets, standard grout									
0300	Color group 1 & 2	D-7	73	.219	S.F.	7.80	10.50		18.30	24
0350	Color group 3		73	.219		7	10.50		17.50	23
0400	Color group 4		73	.219		19.65	10.50		30.15	37
0450	Color group 5		73	.219		19.05	10.50		29.55	36.50
0500	Color group 6		73	.219		22.50	10.50		33	40
0600	Color group 7		73	.219		22	10.50		32.50	39.50
0700	Color group 8, golds, silvers & specialties		64	.250		16.95	12		28.95	36
1020	1" tile on 12" sheets, opalescent finish		73	.219		15.45	10.50		25.95	32.50
1040	1" x 2" tile on 12" sheet, blend		73	.219		20.50	10.50		31	38
1060	2" tile on 12" sheet, blend		73	.219		21.50	10.50		32	39
1080	5/8" x random tile, linear, on 12" sheet, blend		73	.219		20.50	10.50		31	38
1600	Dots on 12" sheet		73	.219		20.50	10.50		31	38
1700	For glass mosaic tiles set in dry mortar, add		290	.055		.40	2.65		3.05	4.31
1720	For glass mosaic tiles set in Portland cement mortar, add		290	.055	↓	.01	2.65		2.66	3.88
1730	For polyblend sanded tile grout	↓	96.15	.166	Lb.	1.97	8		9.97	13.80

# 09 34 Waterproofing-Membrane Tiling

## 09 34 13 – Waterproofing-Membrane Ceramic Tiling

### 09 34 13.10 Ceramic Tile Waterproofing Membrane

0010	<b>CERAMIC TILE WATERPROOFING MEMBRANE</b>									
0020	On floors, including thinset									
0030	Fleece laminated polyethylene grid, 1/8" thick	D-7	250	.064	S.F.	2.28	3.07		5.35	7
0040	5/16" thick	"	250	.064	"	2.60	3.07		5.67	7.35
0050	On walls, including thinset									
0060	Fleece laminated polyethylene sheet, 8 mil thick	D-7	480	.033	S.F.	2.55	1.60		4.15	5.15
0070	Accessories, including thinset									
0080	Joint and corner sheet, 4 mils thick, 5" wide	1 Tlf	240	.033	L.F.	1.26	1.77		3.03	3.97
0090	7-1/4" wide		180	.044		1.71	2.36		4.07	5.35
0100	10" wide		120	.067	↓	2.09	3.54		5.63	7.50
0110	Pre-formed corners, inside		32	.250	Ea.	7.65	13.30		20.95	28
0120	Outside		32	.250		7.65	13.30		20.95	28
0130	2" flanged floor drain with 6" stainless steel grate		16	.500	↓	360	26.50		386.50	435
0140	EPS, sloped shower floor		480	.017	S.F.	15.55	.89		16.44	18.40
0150	Curb	↓	32	.250	L.F.	15.40	13.30		28.70	36.50

# 09 35 Chemical-Resistant Tiling

## 09 35 13 – Chemical-Resistant Ceramic Tiling

### 09 35 13.10 Chemical-Resistant Ceramic Tiling

0010	<b>CHEMICAL-RESISTANT CERAMIC TILING</b>									
0100	4-1/4" x 4-1/4" x 1/4", 1/8" joint	D-7	130	.123	S.F.	8.95	5.90		14.85	18.50
0200	6" x 6" x 1/2" thick		120	.133		10.55	6.40		16.95	21
0300	8" x 8" x 1/2" thick		110	.145		13.40	7		20.40	25
0400	4-1/4" x 4-1/4" x 1/4", 1/4" joint		130	.123		9.95	5.90		15.85	19.60
0500	6" x 6" x 1/2" thick		120	.133		12	6.40		18.40	22.50
0600	8" x 8" x 1/2" thick		110	.145		14.25	7		21.25	26
0700	4-1/4" x 4-1/4" x 1/4", 3/8" joint		130	.123		10.90	5.90		16.80	20.50
0800	6" x 6" x 1/2" thick		120	.133		13.25	6.40		19.65	24
0900	8" x 8" x 1/2" thick	↓	110	.145	↓	15.75	7		22.75	27.50