04.2	22 Concrete Unit Masor 22 10 - Concrete Masonry Units	ıry	در د	and to			ann de side et despe Bergijanske te Nederland	in martina no		last en la acquest a th	A Section of
04.00	240.44 Compared Black Board Brown			Daily Labor-			1	2022 Bare Costs			Total
0550	2 10.16 Concrete Block, Bond Beam	Crev			Hours	Unit	, Material	Labor	Equipment	Total ,	Incl O&P
2000		D-9	5	520	.092	L.F.	5.10	4.63		9.73	12.55
2100	Including grout and 2 #5 bars Regular block, 8" high, 8" thick	. D .O	2	200	100	1.5	7.50	/ 00		14.00	10.50
2150	12" thick	D-8		300	.133	L.F.	7.50	6.80		14.30	18.50
2500	Lightweight, 8" high, 8" thick	D-9 D-8		250	.192		9.55	9.60		19.15	25
2550	12" thick	D-9		305	.131	;	6.60	6.70		13.30	17.30
		J-7		255	.188	*	8.55	9.45		18	23.50
-	2 10.18 Concrete Block, Column					-					
0010	CONCRETE BLOCK, COLUMN or pilaster										
0050	Including vertical reinforcing (4-#4 bars) and grout										
0160	1 piece unit, 16" x 16"	D-1		26	.615	V.L.F.	13.70	31		44.70	61.50
0170	2 piece units, 16" x 20"			24	.667		21.50	33.50		55	73.50
0180	20" x 20"			22	.727		33	36.50		69.50	91.50
0190	22" x 24"			18	.889		48.50	44.50		93	121
0200	20" x 32"	• • •		14	1.143	+	57.50	57.50		115	149
04 22	2 10.19 Concrete Block, Insulation Inserts									AV AU	
0010	CONCRETE BLOCK, INSULATION INSERTS										
0100	Styrofoam, plant installed, add to block prices										
0200	8" x 16" units, 6" thick					S.F.	1.63			1.63	1.79
0250	8" thick						2.10			2.10	2.31
0300	10" thick	I	1	-			1.71	1		1.71	1.88
0350	12" thick	1	-	***************************************			2.18			2.18	2.40
0500	8" x 8" units, 8" thick	1	1				2.08	-		2.08	2.29
0550	12" thick	1		- 1		1	2.06	1		2.06	2.27
04 22	2 10.23 Concrete Block, Decorative										
0010	CONCRETE BLOCK, DECORATIVE, C90, 2000 psi										
0020	Embossed, simulated brick face										
0100	8" x 16" units, 4" thick	D-8	4	00 -	.100	S.F.	3.23	5.10		8.33	11.25
0200	8" thick		3	40	.118		3.39	6		9.39	12.75
0250	12" thick	1 +	3	00	.133	+	4.92	6.80		11.72	15.65
0400	Embossed both sides										
0500 1	8" thick	1 D-8	1 3	00	.133 .	S.F.	5.75	6.80		12.55	16.55
0550	12" thick	["	1 2	75	.145	"	6.95	7.45	-	14.40	18.80
1000	Fluted high strength										
1100	8" x 16" x 4" thick, flutes 1 side,	, D-8	3	45	.116	S.F.	4.28	5.95		10.23	13.60
1150 ;	Flutes 2 sides	- Land	3	35	.119		4.85	6.10		10.95	14.50
1200	8" thick	: 1	3	00	.133	1 1	5.45	6.80		12.25	16.25
1250	For special colors, add	1	1		4	+ 1	.69		1	.69	.76
1400	Deep grooved, smooth face										
1450	8" x 16" x 4" thick	D-8	1 3	45 :	.116	S.F.	2.68	5.95	1	8.63	11.85
1500	8" thick	["	3	00	.133	"	4.68	6.80		11.48	15.40
2000	Formblock, incl. inserts & reinforcing										
. 2100	8" x 16" x 8" thick	D-8	3	45	.116	S.E.	4.64	5.95		10.59	14
2150	12" thick	"	3	10	.129	er .	6	6.60		12.60	16.50
2500	Ground face										
2600	8" x 16" x 4" thick	. D-8			.116	S.F.	2.84	5.95		8.79	12.05
2650	6" thick	1			.123	1 1	5.10	6.30		11.40	15.05
2700	8" thick	1 +			.133 🖟		4.11	6.80		10.91	14.75
2750	12" thick	D-9	1 2	65	.181	+ 1	4.82	9.10	1	13.92	18.95
2900	For special colors, add, minimum						15%				
2950	For special colors, add, maximum						45%				
4000	Slump block										
4100	4" face height x 16" x 4" thick	D-1	. 1	65	.097	S.F.	5.50	4.86		10.36	13.35
_	the state of the s		-								